ODPOWIEDŹ NA KOMENDĘ 0xCE																
RAW												DECODED				
Α	9		1	0	1	0	1	0	0	1		Α	typ urządzenia	stała część każdej odpowiedzi		
6	5		0	1	1	0	0	1	0	1		7	typ urząużenia			
В	4		1	0	1	1	0	1	0	0		7				
D	2		1	1	0	1	0	0	1	0		4				
3	5		0	0	1	1	0	1	0	1		4	nr pompy			
5	6		0	1	0	1	0	1	1	0		3				
В	0		1	0	1	1	0	0	0	0		0				
Е	5		1	1	1	0	0	1	0	1		7				
6	3		0	1	1	0	0	0	1	1		C	zwrot komendy			
5	6		0	1	0	1	0	1	1	0		ш				
3	5		0	0	1	1	0	1	0	1		0	ilość użytecznych kolejnych bajtów w			
5	5		0	1	0	1	0	1	0	1		3	odpowiedzi			
	nast					ączni			jtów			0	03 = normalne działanie pompy			
	odpowiedzi, na końcu CRC16												05 – normaine uziaianie pompy			
													gdy 01 = pompa w trakcie bolusa			
								gdy of – politipa w trakole bolusa								
	0												gdy 01 = pompa zatrzymana			
	0															