

Table Name	Table Description
AMT_IDENTIFIER	Table used the most recent version of each Notable Concept, Substance, Basis of Strength Substance and Form (both active and inactive).
AMT_MAP	Table used the mapped products corresponding to each CTPP.
AMT_PROD_UOU	Table used the MPUUs which are mapped to a CTPP, plus TPUU, MP and attribute information
AMT_PROD_UCT	Table used the most recent version of each CTPP (both active and inactive), plus TPP, TP, MPP and attribute information.
AMT_SUBCOMP_PACK	Table used the subpack or component pack details which relate to a parent CTPP.
AMT_SUBSTANCE	Table used the Substances which relate to each MPUU, plus Basis of Strength Substance and attribute information.
AMT_UPLOAD_HISTORY	AMT data files upload history
AMT_VERSION	version information for AMT Data files
BIN	Inventory values associated with bins including AWP, resupply method, min and max.
BIN_BATCH	Batch information for bin entries.
BIN_TRAN	Inventory movement transactions for bins. Including cost, price, transaction type, pack and inventory units of measure at the time of the transaction.
BIN_TRANSACTION	Which records have already been part of an extract for Bin Transactions

COST_CENTRE	Cost centres - wards, clinics and / or distribution points
CREDIT_NOTE	Supplier Credit note header
CREDIT_NOTE_EXTR	Which records have already been part of an extract for Supplier Credit Note transactions.
CREDIT_NOTE_ITEM	Supplier Credit note items.
CRYSTAL_REPORTS	Crystal reports available for ad-hoc reporting.
DEBTOR	Debtors associated with patients.
DEBTOR_GROUP	Debtor group details for use in Private Hospital Billing.
DISP_ITEM	Disposal Register items.
DISPENSE	Dispensing details (header)
DISPENSE_CHARGE	Dispense charges for patients - Non PBS.
DISPENSE_CLASS	Dispensing / script classifications.
DISPENSE_DOSE	Dispense dose
DISPENSE_GROUP	Groups of dispense / script classifications.
DISPENSE_PACK_DETAILS	The phase specific pack details for a Goal Sheet dispensing. For example, the Route and Expiry Date for the Aqueous phase, and the Route and Expiry Date for the Lipid phase.
DISPENSE_PBS	PBS dispensing reference details derived from MCA
DISPENSE_PBS_ERROR_CODES	PBS Error codes in corresponding dispensed item.
DISPENSE_PBS_MANUF	PBS Cytotoxic dispensing information
DISPENSE_PROD	Dispensed products (Items)
DISPENSE_PROPERTY	The amount of each Property (e.g. sodium, chloride...) contained in each ingredient (dspn_prod_id) in a dispensing.

DISPENSE_S CAN	Dispensed items scanned
DISPOSAL	Disposal Register header
DISPOSAL_E XTR	Records have already been part of an extract for Disposal transactions
DIST_CR_ITE M	Distribution credit item.
DIST_CREDI T	Distribution credit header.
DIST_CREDI T_EXTR	Which records have already been part of an extract for Distribution Credit transactions
DIST_ITEM	Distribution items.
DISTRIBUTI ON	Distribution header.
DOCTOR	Doctors, prescribers and consultants
DRUG_COD E	Structured codes used for interaction, allergy and grouping purposes
DRUG_COD E_SITE	Drug Code information which are specific to a site (e.g. restricted notes)
DSPN_ALER T	Interaction, allergy, restriction and other warning identified during the dispensing process.
DSPN_EXTR	Which records have already been part of an extract for Dispensing transactions
DSPN_LIST	Dispensing lists.
DSPN_ORD ER	Dispensing orders (Doctor's orders from external clinical system).
DSPN_VERI FIED	Who verified the dispensing in Medication scanning check
EDI_INV_DE SP	Despatch and Invoice messages imported via the 'EDI from Supplier' window.
EDI_ORD	Electronic Data Interchange items (Purchase orders)
EDI_SUPPLI ER	Record of licensed EDI suppliers
EPRESCRIPT ION	The Patient and Clinician data elements will all be imported into the table from the 004

EPRESCRIPTION_ANNOTATION	Annotation records Created
EPRESCRIPTION_BASKET	Basket records created
EPRESCRIPTION_ITEM	The PrescribedItem data elements (and DispensedItem data elements for a repeat) will all be imported into the table from the 004.
ERROR_LOG	Warnings and errors associated with SMA transactions
EXTERNAL_LINK	External links (executable or web based) to allow context switching, and their allocated Function Key and invocation parameters.
EXTERNAL_MESSAGE	Data to be used by other applications. Allows i.Pharmacy to interact with external applications such as PBS Online.
EXTERNAL_MESSAGE_APPDC	Links to data generated OMS and MFN Messages
EXTERNAL_MESSAGE_BILL	Links to dispensing records for a billing interface to process.
EXTERNAL_MESSAGE_PES	Links to data generated by various transactions, for processing with e-Rx PES.
EXTERNAL_MESSAGE_ROBOT	Links to data generated by various transactions, for processing by the robot interface. Allows i.Pharmacy to interact bi-directionally with supported robots.
EXTERNAL_ORG	External organisations for borrows and loans.
EXTERNAL_PAYMENT	no data - Not used in this version
EXTERNAL_PRF	PRF (Prescription Record Form) records for patients for amounts related to dispensings from pharmacies external to the pharmacy doing the dispensing.

FAMILY	Family grouping for PRF purposes
FIN_HIERARCHY	Financial hierarchy (UK only)
FIN_STRUCTURE	Financial structures set up (UK only)
FIN_STRUCTURE_TYPE	Financial structure types (UK only)
FIN_TRAN	Financial transactions. These are non-inventory based transactions such as supplier credits
FIN_TRANSACTION	Which records have already been part of an extract for financial transactions
FIN_TRANSACTION_TYPE	Financial transaction types
FINANCE_CLASS	Financial classes for patient billing
FINANCE_SUBCLASS	Financial sub classes for patient billing
FRAME_PREFERENCES	Window frame preferences, as entered in Tools / Customise Tool bars
FREE_RETURN_ITEM	Free return items.
FREE_RETURN	Free return header (samples, patient returns etc.).
FREE_RETURN_EXTRACT	Which records have already been part of an extract for Free Return transactions.
FUNCTION_KEY	Function keys and their description, plus sort order.
GOAL_SHEET	Goal sheet header information
GOODS_RECEIPT	Goods Receipt header
GOODS_RECEIPT_EXTRACT	Which records have already been part of an extract for Goods Receipt transactions.
GR_ITEM	Goods Receipts items
GR_WORK	Goods receipt worksheet header
GR_WORK_ITEM	Goods receipt worksheet items

GS_CONSTRUCTION	General construction properties that apply to a goal sheet (may be phase specific) such as directions, shelf life and label format.
GS_CONSTRUCTION_ITEM	Specific Construction properties which apply to a Goal Sheet, e.g. "separate phases" or "consider containers" which are system controlled.
GS_FORMULATION	Goal Sheet Formulation details including status, patient details and QC, Overage and Wastage amounts per phase.
GS_FORMULATION_ALERT	Alerts triggered for Properties in the Goal Sheet Formulation window e.g. "out of range".
GS_FORMULATION_PRODUCT	The products allocated against a Goal Sheet Formulation, including Quantities (ordered, scaled, prepared, wastage, etc), phase and units.
GS_FORMULATION_PROPERTY	The Property amounts (e.g. sodium, potassium...) contained in a Goal Sheet Formulation, phase specific.
GS_FORMULATION_RESOURCE	Resources used for a Goal Sheet Formulation.
GS_LABEL_PRINTING	Details (format, number of copies etc.) regarding the printing of Goal Sheet labels for auditing purposes. A new row per Goal Sheet label is created each time labels are printed.
GS_NOTE	Method Notes added in {Goal Sheet Maintenance} which can be accessed/modified in the {Goal Sheet Order}.
GS_ORDER	Goal Sheet Order details including status, style, patient details, day and pack numbers.

GS_ORDER_NOTE	Method Notes against a Goal Sheet Order/Formulation. These default from the Goal Sheet Method Notes, but can be modified or added on the fly.
GS_ORDER_PROP	Property amounts and units contained in the Goal Sheet Order, along with dose range details.
GS_PATATTRIBUTE	Particular Patient Attribute range of values that apply when selecting a Goal Sheet.
GS_PROPERTY	Properties assigned to a Goal Sheet, with required quantity, unit and qualifier. Also dose range details, sequence order for various purposes and phase are included.
GS_RESOURCE	Resources used against the Goal Sheet, phase specific.
GS_ROUTE	Allowed Routes for the Goal Sheet, phase specific.
GTIN	GTIN values associated with a product and UOM combination
GTIN_DESC	Description of GTIN text label, based on locale e.g. GTIN or EAN
HARD_COPY_AUDIT	Hard copy auditing (UK only)
HARD_COPY_AUDIT_PARAMETERS	Hard copy audit parameters (UK only)
IMP_LIST_LOCATION	Imprest List Locations associated with Imprest lists
IPHARMERX	Certificate information for eRx
IPHARMNHC	Certificate information for NIHC
IPHARMMSLIC	Certificate information for My Script List Interface connector
IMPREST_ITEM	Imprest list items.
IMPREST_LIST	Imprest list header

IMPREST_LOCATION	Imprest List Locations
INSURER	Insurer identifiers - Not used in this version
INSURER_TABLE	Insurer information - Not used in this version
INTERACT	Interactions/Incompatibilities between drug codes (Stockley and STOCCA)
INTERFACE_MASTER	Supported dialogs or HL7 messages for different robot types and process flows. Used to control interaction with robot interfaces.
INTERVENTION	Interventions recorded
INTERVENTION_EXTR	Which records have already been part of an extract for Intervention transactions.
INTV_GROUP	Intervention Group details
INTV_TYPE	Intervention types.
INVOC_PARAMETER_LIST	System-controlled list of context-specific invocation parameters that may be used when an external link to another system is invoked (via pre-programmed function key).
INVOICE_SERVICE	User defined Invoice service codes
KIT	Kit Details
KIT_DIST	Kit issues
KIT_DIST_EXTR	Which records have already been part of an extract for Kit Distribution transactions
KIT_DIST_ITEM	Kit Distribution Item (Product) details
KIT_DISTRIBUTION	Kit Distribution details
KIT_ITEM	Kit Item (Product) details
KIT_ITEM_DETAIL	Kit issue details
KIT_ITEM_TRANSACTION	Kit Item (Product) Transaction details -links kit distribution item to transaction.
KIT_MAINT	Kit maintenance records

KIT_MAINT_ITEM	Kit maintenance items
KIT_TEMPLATE	Kit template header
KIT_TEMPLATE_ITEM	Kit template item.
LABEL_FORMAT	System and Crystal report names and descriptions for labels that can be allocated to site specific processes.
LBL_FMT_PROC	Label format associated with site specific processes such inpatient dispensing or bag labels
LIST_OF_VALUES	List of values that are populated in drop down lists, and other reference areas.
LM_CONTROL_PANEL	Control panel details (Manufacture control)
LM_CONTROL_PANEL_INGR_SUM	Control panel ingredient summary
LM_CONTROL_PANEL_INGREDIENT	Control panel ingredient details
LM_CONTROL_PANEL_RESOURCE	Control panel resource list
LM_ITEM	Local manufacture item details (Manufacturing module)
LOAN	Loan header
LOAN_EXTR	Which records have already been part of an extract for Loan Extract transactions
LOAN_ITEM	Loan item details
LOCAL_MANUF	Local manufacture header (Manufacturing module)
LOCAL_MANUF_EXTR	Which records have already been part of an extract for local manufacture transactions
LOCATION	Locations in stores for allocating to bins
MANUFACTURER	Manufacturers (non PBS)

MEASURABILITY	User defined volume and weight ranges, with the smallest quantity it is possible to measure accurately for each range.
MED_CHARACTER	Medication chart for a patient - header.
MED_CHT_DOSE	Dosage details pertaining to medication chart
MED_CHT_INGR	Ingredients for a medical chart item.
MED_CHT_ITEM	Ingredients in a medication chart item (Product) level
MESSAGES	List of messages prompted to users at application level
MIMS_AUGMDAT	MIMS Linking table - used to find GenericCode from ProductCode and FormCode
MIMS_AULINK_FORMULATION_ROUTE	MIMS Linking table - find Route of Admin at MIMS product formulation level. Can stop inappropriate warnings when a product is used topically.
MIMS_DRUG_CLASS_INTERACTION_PRECAUTION	Link table to find MIMS interaction precaution ID given two drug interaction class IDs
MIMS_DRUG_CLASS_INTERACTION	Core MIMS table - links to interaction alert elements for each pair of drug interaction classes.
MIMS_DRUG_GENERIC_ROUTE_INTERACTION	Find MIMS drug interaction class with GenericCode and RouteID
MIMS_DRUG_INTERACTION_CLASS	Text descriptions for each MIMS drug interaction class.
MIMS_DRUG_INTERACTION_REFERENCE	Lists literature references for each MIMS drug interaction class given two drug interaction class IDs
MIMS_DSM_ROUTE	Text description for each MIMS route of admin

MIMS_GENERIC	Lists each MIMS generic description, abbreviated description and links to approved generic name from generic synonyms in the same table (e.g. acetaminophen is linked to paracetamol)
MIMS_LIKELIHOOD	Text description of MIMS interaction likelihood
MIMS_LINK_AMT	Links AMT code to MIMS ProductCode and FormCode
MIMS_OBSERVATION	Text description of MIMS interaction observations
MIMS_PRECAUTION	Text description of MIMS interaction precautions
MIMS_SEVERITY	Text description of MIMS interaction severity
MIMS_UPLOAD_HISTORY	Holds MIMS update activity
MYSCRIPTLIST_ACCESS	Records each time active prescriptions are retrieved from MySQL for a patient
NBR_DESC	Number description for use in medication charts
ORD_WORK	Created lists such as 'Suggested by Inventory', 'Suggested by Use', 'User Defined' and 'Order templates'. - Order Worksheet Header
ORD_WORK_ITEM	Order Worksheet items
ORDER_ITEM	Purchase Order items
ORDERS	Purchase Order header.
ORDERS_EXTRACT	Which records have already been part of an extract for Purchase Order transactions
PAM_CALC	Patient Aminoglycoside Calculations
PAT_ATTRIBUTE	Patient specific attribute values
PAT_EPISODE	Patient Episodes plus episode specific information
PAT_INVOICE	Patient Invoice header

PAT_INVOIC E_EXTR	Which records have already been part of an extract for Patient Invoice transactions
PAT_INVOIC E_ITEM	Patient Invoice items
PAT_INVOIC E_PAY	Patient Invoice payment records
PAT_HI	Patient Individual Health Identifier Records
PAT_NOTE	Patient Note information
PAT_NOTE_ DTL	Patient Note Detail
PAT_NOTE_ TEMP	Patient Note Template
PAT_PROD_ PERM_EXTR	Which records have already been part of an extract for Special Product Register transactions.
PAT_PROD_ PERMIT	Product Permit information for patients (Special Products Register)
PATCH	Patches applied, including upgrade and data modifications applied during implementation activities.
PATIENT	Patient details
PATIENT_US ER_WORKST ATION	Patient locking information if activated
PBCATCOL	These 5 'PowerBuilder System Repository' tables were found in v12 schema and Alter12_0_0.sql. Should these be in the schema??
PBCATEDT	Not referred anywhere in the i.Pharmacy application
PBCATFMT	Not referred anywhere in the i.Pharmacy application
PBCATTBL	Not referred anywhere in the i.Pharmacy application
PBCATVLD	Not referred anywhere in the i.Pharmacy application
PBS_CLAIM	PBS Claims - header
PBS_CODE	Codes for PBS drugs
PBS_CUSTO M_ERROR_C ODES	Custom PBS Error codes from PBS Online
PBS_ERROR _CODES	MCA Defined PBS error codes

PBS_ITEM	PBS item data such as max, price, number of repeats. Updated each month.
PBS_ITEM_TEMP	Pbs_item data that is no longer being used.
PBS_LINK	Links between PBS items and i.Pharmacy products
PBS_PAYMENT_STATEMENT	PBS Online Payment statement information
PBS_RECONCILIATION	Reconciliation details for PBS Online. Updated each time statement data is requested and received from Medicare. One row per claim.
PBS_RESTRICTION	PBS Restriction details
PBS_RESTRICTION_LINK	PBS Restriction Link details
PBS_RESTRICTION_NOTE	PBS Restriction Note details
PBS_WASTAGE_FACTOR	PBS wastage factor
PERSON	Patient links across sites. This allows the dispensing history for a person to be seen if they are in multiple sites.
PHARMACY	Pharmacy information
PRESCRIPTION	Prescriptions for tracking - header
PRESCRIPTION_ITEM_TRACK	Prescription tracking items
PRESCRIPTION_NOTES_DESC	Prescription notes (Description)
PRESCRIPTION_TRACK	Prescription tracking header
PROD_FORM	Product forms and verbs

PROD_MIMS_GENERIC	Used in manual mapping of products to MIMS Generics, linking i.Pharmacy products to one or more MIMS Generics, from which MIMS interaction classes may be found.
PROD_PROPERTY	Property information for products.
PROD_RESOURCE	Resources assigned against a product and associated details.
PROD_ROUTE	Route of administration applicable for the product.
PROD_SCHEDULE	The national Schedules (categories) that apply to all products. State level exceptions may apply.
PROD_SITE	Site specific product details such as product type, controlled drug indicator, short code.
PROD_SUBSTITUTE	Product substitution details
PROD_SUPP_PREF	Preferred supplier information for products
PROD_UOM	UOM (Units Of Measure) for each product, including both the Pack UOM and Inventory UOM, and the multiplier between each UOM.
PROD_WARNING_CODE	Warning Codes linked to products
PRODUCT	Product information that is globally accessed by all sites
PROFILE	Definition of a user profile. It provides a way of grouping Users into different security levels.
PROFILE_ACCESS	What functions will be available to users in that profile, across the application.
PROFILE_REPORT_ACCESS	Reports that can be accessed per profile, and hence each user.
PROP_ATTR	The Patient Attributes that apply per Dose Range for a Property.

PROP_DOSE	The Dose Ranges that apply for a Property.
PROP_UNIT	The Units that apply for a Property, along with default and current flags.
PROPERTY	Property details, which can be assigned against products, and used to construct Goal Sheets.
PROT_SCHE D_CHART	Protocols that have been assigned against a patient Medication Chart, showing header level information
PROT_SCHE D_ITEM	Details of products per Protocol that are assigned against a patient Medication Chart
PROT_SCHE D_PERIOD	Details for each Protocol product on a Medication Chart, showing all possible day / sequence combinations of the Protocol schedule with a Y/N flag regarding which apply to the product
PROTOCOL	Protocols which are available globally showing header level information
PROTOCOL_ BOM	Details of ingredients, for those products assigned per Protocol that have a Bill of Materials
PROTOCOL_ ITEM	Details of products assigned per Protocol
PROTOCOL_ SITE	Protocols available at a site
PVV_ADJ_IT EM	Master table the PVV adjustment when the pvv value is modified in the bin
PVV_ADJUS T	Item table the PVV adjustment, when there is a change to the PVV value in bin
RECON_ING RED	Reconstitution ingredients for each product Reconstitution Method.
RECON_LOT	Reconstituted stock amounts and details, such as created quantity, current quantity and discard status.

RECON_PROD	Reconstitution methods that have been configured per product, e.g. description, total quantity, unit, shelf life.
REPAY_ITEM	Repayment items (for borrow & lend)
REPAYMENT	Type of repayment (Lend/Borrow) made by Store to the External Organization. Header information
REPAYMENT_EXTR	Which records have already been part of an extract for Repayment transactions
REPRINT	Reprint details of the non-normal (Aseptic, Cytotoxic etc) batch sheets.
REPT_FMT_PROC	Names for application Crystal Reports available to each site.
REPT_FORMAT	Areas where a Crystal report can replace the in-built Power builder / System report.
REQN	Distribution Requests header
REQN_EXTR	Which records have already been part of an extract for distribution request transactions
REQN_ITEM	Distribution Requests items
RESOURCE	Resources available to be used in the Manufacturing. Resources can be recorded against: Container, Device, Facility, Handling/Packaging, Consumable, Personnel, QC Container
ROBOT	Robot name, type and associated store
ROBOT_AUDIT_MESSAGE	Will contain an ongoing audit of each message that is sent and received between iPharmacy and the robot.
ROBOT_CHUTE	Chutes available per robot, plus an indicator for bulk stock chutes.

ROBOT_CONSIS_EXTERNAL_IDS	External ids from Outbound Stock Take messages will be saved in this table for each robot, the corresponding Inbound message will pick up the oldest external id for the robot and populate the message with this. The row will be deleted.
ROBOT_ERROR_MESSAGE	Record of any errors that occurred during Viaduct processing of messages.
ROBOT_INTERFACE	The processes supported for the sending/receiving of robot messages/dialogs. Also, site specific priority for outbound messages/dialogs and number of items per message/dialog supported by the robot.
ROUTE	Routes of administration
RTPM_AMT_IDENTIFIER	Table used the CTPP's and indicators to identify in which state RTPM is monitored
SALES_TAX	Sales tax values
SCID_CACHE	Table scid's generated per site and other data
SITE	Sites, including name, code and address.
SITE_ACCOUNT_COMPONENT	Account component details associated with specific sites
SITE_SETTINGS	Module licencing
SPEC_PRODUCT_INDICATION	Special product indication types
SS_ACT_SCHEDULE4	Table used CTPP's and other informations related to Australian Capital Territory
SS_ARTGID_REFERENCESET	AMT ARTG snapshot data which gets refreshed every time data is uploaded
SS_ASSOCIATIONREFERENCESET	AMT Historical Associations snapshot data which gets refreshed every time data is uploaded

SS_CONCEPTS	AMT Concepts snapshot data which gets refreshed every time data is uploaded
SS_CTPP_CONCEPTS	AMT snapshot data which gets refreshed every time data is uploaded
SS_DESCRIPTIONS	AMT Concept Descriptions snapshot data which gets refreshed every time data is uploaded
SS_LANGUAGE	AMT Language snapshot to allow Preferred synonym to be identified where more than one synonym exists for an AMT Concept.
SS_MP_CONCEPTS	AMT Medicinal Product snapshot data which gets refreshed every time data is uploaded
SS_MPP_CONCEPTS	AMT Medicinal Product pack snapshot data which gets refreshed every time data is uploaded
SS_MPUU_CONCEPTS	AMT Medicinal Product Unit of Use snapshot data which gets refreshed every time data is uploaded
SS_NSW_SCHEDULE4	Table used CTPP's and other informations related to New South Wales
SS_NT_SCHEDULE4	Table used CTPP's and other informations related to Northern Territory
SS_QLD_SCHEDULE4	Table used CTPP's and other informations related to Queensland
SS_RELATIONSHIPS	AMT Relationships snapshot data which gets refreshed every time data is uploaded
SS_SA_SCHEDULE4	Table used CTPP's and other informations related to South Australia
SS_SCHEDULE8	Table used CTPP's and other informations related to Schedule 8
SS_STRENGTH_REFSET	AMT Strength snapshot data which gets refreshed every time data is uploaded

SS_SUBPAC K_QTY_REFS ET	AMT Subpack Quantity snapshot data which gets refreshed every time data is uploaded
SS_TAS_SCH EDULE4	Table used CTPP's and other informations related to Tasmania
SS_TP_CON CEPTS	AMT Trade Product snapshot data which gets refreshed every time data is uploaded
SS_TPP_CO NCEPTS	AMT Trade Product Pack snapshot data which gets refreshed every time data is uploaded
SS_TPUU_C ONCEPTS	AMT Trade Product Unit of Use snapshot data which gets refreshed every time data is uploaded
SS_UOU_QT Y_REFSET	AMT Unit of Use Quantity snapshot data which gets refreshed every time data is uploaded
SS_UOU_SIZ E_REFSET	AMT Unit of Use Size snapshot data which gets refreshed every time data is uploaded
SS_VIC_SCH EDULE4	Table used CTPP's and other informations related to Victoria
SS_WA_SCH EDULE4	Table used CTPP's and other informations related to Western Australia
STATIONERY	Stationery to allow specific report and label printers to be allocated to print jobs
STATIONERY _SETTINGS	Stationery and allocated printers for each user and workstation combination
STD_MANUF _NOTE	Product Method Note (Standard manufacture note) details
STK_ADJ_IT EM	Stock adjustment items. (Not related to stock takes)
STK_TAKE_G RP	Stock take groups
STK_TAKE_IT EM	Stock take items
STOCCA_AD C_PARM	ADC parameter settings

STOCCA_ALERT_PARM	Alert override settings at each site
STOCCA_DISP_PARM	Dispensing parameter settings
STOCCA_GLOBAL_PARAMETER	Global Parameter Settings. Currently holds Product Object Identifier (OID) and Description for MyHealth Record purposes.
STOCCA_INVENTORY_PARM	Inventory parameter settings
STOCCA_PARAMETER	General parameter settings
STOCCA_PBS_DISPENSING_PARAMETER	PBS dispensing parameter settings specific to each site
STOCCA_PBS_GLOBAL_PARAMETER	PBS global parameter settings
STOCCA_PROCESS	i.Pharmacy processes
STOCCA_PRODUCT_PARAMETER	Product parameter settings
STOCCA_REFERENCE_SITE_PARAMETER	Reference site information (Dispensing Parameters Area)
STOCCA_SPECIAL_PRODUCT_PARAMETER	Special Product Types which have Mandatory Or Optional set in regard to whether an Indication needs to be entered in the {Add Special Product Authority} window.
STOCCAMS_MESSAGE_PARAMETER	SMA (STOCCA Message) parameter settings
STOCK_ADJUST	Stock adjustment header
STOCK_ADJUST_EXTRACT	Which records have already been part of an extract for stock adjustment transactions
STOCK_TAKE	Stock take header
STOCK_TAKE_EXTRACT	Which records have already been part of an extract for stock take transactions
STOCK_VALUATION	Inventory movements for the Stock Valuation report.

STOCK_VAL UATION_BA CKUP	Stock valuation Archive
STORE	Store details
STORE_ACC _COMP	Account components associated with stores
SUPP_CATL	Supplier catalog information
SUPP_COST _CNTR	Cost Centres associated with Suppliers
SUPP_MAST	Master Suppliers that are used for allocation to a Supplier
SUPPLIER	Suppliers
TEAM	Teams to be assocaited with Doctors and / or Patients
TFR_ITEM	Store Transfer items
TFR_REQUE ST	Store Transfer Request header
TFR_REQUE ST_EXTR	Which records have already been part of an extract for Store Transfer Request transactions
TFR_RQST_I TEM	Store Transfer Request items
TPN_COMP_ RULES	TPN Component Rules
TRAN_ADD_ VAL	Added Value amounts that may be included into the price of a transaction
TRAN_TYPE	Transaction type details
TRANSFER	Store transfer header
TRANSFER_ EXTR	Which records have already been part of an extract for Store Transfer transactions
UNIT	System-controlled units that are used for Properties (e.g. mmol, mg) and for Patient Attributes (e.g. square metre, kilogram).
UOM	Unit of measure information
UPPN_MAP	Original prescription numebr for a dispensed item
USER_LIST_ OF_VAL	User Defined Codes – available for patient and product

USER_LOV_PAT	User Defined Codes - patient
USER_LOV_PROD	User Defined Codes - product
USER_PWD	Previous passwords for users
USER_SETTINGS	Most recent extract file path and the user who authorised some actions, per workstation per user.
USER_SITE_SETTINGS	Dispensing preferences for each user at a workstation
USER_WORKSTATION_AUDIT	Records when a user logs in and out of a site
USERS	User details
VAL_ADJ_ITEM	Adjustments to bin_cost (AWP) in bins details - items
VALUE_ADJUST	Adjustments to bin_cost (AWP) in bins details - header
VAR_DOSE_CHART	Variable dosage chart - header
VAR_DOSE_ITEM	Variable dosage chart items
VAR_DOSE_PERIOD	Period of variable dosage chart of patient
WARNING_CODES	Warning Codes for association with products
WORK_FLOW	Work flow details
WORKSTATION	Workstations
WORKSTATION_SETTINGS	Patient site, pharmacy and store used on a workstation per user

Table	Column	Data Type	Null	Description
DISPENSE	ALERT_ID	INT	NULL	Alert ID to link to dspn_alert record
DISPENSE	AUTHORISED_BY	VARCHAR (30)	NULL	Code of the user who authorised the dispense
DISPENSE	AUTHORISED_DT	DATETIME	NULL	Date and time that the user authorised the dispense
DISPENSE	BATSHT_PRINT_IND	CHAR(1)	NOT NULL	Indicator for Batch Sheet Print in Prescription details
DISPENSE	CEASE_DT	DATETIME	NULL	Cease date
DISPENSE	CHARGE_TYPE_CD	VARCHAR(5)	NULL	Code to indicate the charge type.

DISPENSE	CHART_DUR	VARCHAR(5)	NULL	Chart duration for PBS Hospital Medication Chart dispensing (01, 04 or 12 months)
DISPENSE	CHART_EXPIRY_IND	CHAR(1)	NOT NULL	Indicator for an expired PBS Hospital Medication Chart dispensing
DISPENSE	CHART_IND	CHAR(1)	NOT NULL	Indicator for PBS Hospital Medication Chart dispensing
DISPENSE	CHUTE_XID	VARCHAR(20)	NULL	Chute code for robot delivery of the item - link to robot_chute table.
DISPENSE	CMI_LOCAL_IND	CHAR (1)	NOT NULL	Indicator for Local CMI
DISPENSE	CMI_STAT_CD	VARCHAR (5)	NULL	Code to link to the CMI Status.
DISPENSE	COLLECTED_BY	VARCHAR (30)	NULL	Code of the user who processed the collection of the dispense
DISPENSE	COLLECTED_DT	DATETIME	NULL	Date and time that the user processed the collection of the dispense
DISPENSE	COST_CNTR_XID	VARCHAR (20)	NOT NULL	Cost Centre Code - Link to the Cost centre table
DISPENSE	CREATED_BY	VARCHAR (30)	NOT NULL	Code of the user was logged into the application at the time of record creation. OR the user who authorised the EDIT of the dispense.
DISPENSE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created
DISPENSE	DEFER_SCID_XID	VARCHAR (20)	NULL	A new SCID stored when a dispensing becomes Deferred and deferred item with that SCID sent to eRx
DISPENSE	DEL_TO_ID	INT	NULL	Identifier of the 'Delivered to' location
DISPENSE	DELETE_USER_CD	VARCHAR (15)	NULL	Code of user who has authorised the deletion of the record - same as the user who authorised the EDIT of the record
DISPENSE	DISPENSE_RECORD_GUID	VARCHAR(255)	NULL	Store Guid of the dispense
DISPENSE	DOCT_XID	VARCHAR (20)	NOT NULL	Code for Doctor - Link to the doctor table
DISPENSE	DSPN_ADDEDVALUE_AMT	NUMERIC(18,8)	NULL	added value amount.
DISPENSE	DSPN_AFT_THRESHOLD_IND	CHAR(1)	NOT NULL	dispensing after threshold indicator

DISPENSE	DSPN_ANCIL_DIR	VARCHAR (255)	NULL	Dispensed Product Ancillary directions, as obtained from linked warning table records, and edited by the user.
DISPENSE	DSPN_ANCIL_TEXT	VARCHAR (255)	NULL	Dispensed Product Ancillary Description, as obtained from linked warning table records, and edited by the user.
DISPENSE	DSPN_BILL_TYPE_CD	VARCHAR(5)	NULL	dispensing billing type code
DISPENSE	DSPN_CLAIM_HCD_CD	VARCHAR(5)	NULL	Dispensing HCD/non-HCD code.
DISPENSE	DSPN_CLAIMABLE_AMT	NUMERIC(18,8)	NULL	dispensing claimable amount
DISPENSE	DSPN_CLAIMABLE_IND	CHAR(1)	NOT NULL	dispensing claimable indicator
DISPENSE	DSPN_CLASS_ID	INT	NOT NULL	ID for dispense class - Link to dispense_class table
DISPENSE	DSPN_COSTCNTR_FEE_AMT	NUMERIC(18,8)	NULL	This field is used to update the Cost Centre Fee.
DISPENSE	DSPN_COSTCNTR_MARKUP_PCT	DECIMAL(8,6)	NULL	This field is used to update the Cost Centre Markup.
DISPENSE	DSPN_COSTCNTR_PRICE_IND	CHAR (1)	NOT NULL	This field is used to update Cost Centre Price Indicator.
DISPENSE	DSPN_CRE_TYPE_CD	VARCHAR (5)	NOT NULL	Dispense creation type code
DISPENSE	DSPN_DEBTOR_XID	VARCHAR(20)	NULL	dispensing debtor code
DISPENSE	DSPN_DIFF_PRICE_IND	CHAR(1)	NOT NULL	Differential price indicator.
DISPENSE	DSPN_DIR	VARCHAR (255)	NULL	Dispense Directions
DISPENSE	DSPN_DIRCODE_TYPE_CD	VARCHAR (5)	NOT NULL	Direction code type code - indicates either Ad hoc (FULL) or structured (SHORT)
DISPENSE	DSPN_DT	DATETIME	NOT NULL	Date the dispense transaction occurred
DISPENSE	DSPN_EDIT_TYPE_CD	VARCHAR (5)	NOT NULL	Dispense edit type code
DISPENSE	DSPN_FEE_AMT	NUMERIC(18,8)	NULL	Dispense fee amount.
DISPENSE	DSPN_FIN_SUB_XID	VARCHAR(20)	NULL	Link to financial sub class table
DISPENSE	DSPN_FLAT_AMT	NUMERIC(18,8)	NULL	Flat amount.
DISPENSE	DSPN_FORMULA_CD	VARCHAR(5)	NULL	Type of dispensing formula. Whether STD, Build or Goal Sheet
DISPENSE	DSPN_FULL_PRICE	NUMERIC(18,8)	NULL	Full Price of Dispensed Item

DISPENSE	DSPN_HCDCLM_ORD_ID	INT	NULL	Sequence order for the dispensing edits - used for determining High Cost Drug claim threshold recalculations.
DISPENSE	DSPN_ID	INT	NOT NULL	Unique ID used to identify the dispense record
DISPENSE	DSPN_LIST_ID	INT	NULL	Identifier to link to the Dispense list record
DISPENSE	DSPN_MARKUP_PCT	DECIMAL(8,6)	NULL	Markup percentage.
DISPENSE	DSPN_MAX_CHRG_AMT	NUMERIC(18,8)	NULL	maximum charge amount.
DISPENSE	DSPN_MIN_CHRG_AMT	NUMERIC(18,8)	NULL	minimum charge amount.
DISPENSE	DSPN_NOTE	VARCHAR (255)	NULL	Dispense Notes
DISPENSE	DSPN_ORDER_ID	INT	NULL	Dispensing Order ID to link to the dspn_order record
DISPENSE	DSPN_OVERRIDE_REASON_NOTE	VARCHAR(255)	NULL	override reason note.
DISPENSE	DSPN_PACK_QTY	NUMERIC(18,8)	NOT NULL	Number of packs in prescription details
DISPENSE	DSPN_PAYMENT_CATEGORY_CD	CHAR(1)	NULL	Patient payment category at the time of dispensing.
DISPENSE	DSPN_PBS_ID	INT	NULL	Unique ID used to identify dispensed PBS item
DISPENSE	DSPN_PBS_ONLINE_CYTOSTAT_CD	VARCHAR (5)	NULL	PBS online status for PBS Cyto dispensing.
DISPENSE	DSPN_PRIV_DA_FEE	NUMERIC(18,8)	NULL	private DA fees.
DISPENSE	DSPN_PRIV_S3RECORD_FEE	NUMERIC(18,8)	NULL	record fees.
DISPENSE	DSPN_PROD_TEXT	VARCHAR (255)	NOT NULL	The text as recorded in the 'Script Details' section of the prescription details window
DISPENSE	DSPN_REV_TYPE_CD	VARCHAR (5)	NULL	Reverse Dispense Type code
DISPENSE	DSPN_ROBOT_BATCH_ID	INT	NOT NULL	Dispense Robot batch identifier - links items which were Picked at the same time
DISPENSE	DSPN_ROBOT_ID	INT	NULL	Links to the external_message_robot.trans_id
DISPENSE	DSPN_STAT_CD	VARCHAR (5)	NOT NULL	Code to link to the Dispense Status.
DISPENSE	DSPN_STYLE_CD	VARCHAR (5)	NOT NULL	Code for dispensing style
DISPENSE	DSPN_SUPP_DT	DATETIME	NULL	The original dispense script date which is saved before Owing Mark Off
DISPENSE	DSPN_TOT_COST	NUMERIC(18,8)	NULL	Total cost of ingredients in the dispensing
DISPENSE	DSPN_TOT_PRICE	NUMERIC(18,8)	NULL	Total price of the dispensing including markups and fees

DISPENSE	DSPN_TPN_DURATION	DECIMAL(4,1)	NULL	dispensing tpn duration
DISPENSE	DSPN_TYPE_CD	VARCHAR (5)	NOT NULL	Code for dispensing type
DISPENSE	DSPN_UNIT_QTY	NUMERIC(18,8)	NULL	Number of inventory units
DISPENSE	DSPN_WARN	VARCHAR(8000)	NULL	the Warning Notes
DISPENSE	EDIT_USER_CD	VARCHAR (15)	NULL	Code of user who has authorised the edit of the record
DISPENSE	ERX_RPT_IND	CHAR(1)	NULL	To Update the Repeat order Status of IQEMO
DISPENSE	ESCRIPT_CHECK_IND	CHAR(1)	NULL	Indicates result when comparison done between ePrescription and Owing Script dispensing during Mark-off
DISPENSE	ESCRIPT_ITEM_ID	INT	NULL	ePrescription work flow to link a dispensing to the SCID/sequence combination in eprescription item
DISPENSE	ESCRIPT_MSG_STAT_CD	VARCHAR (5)	NULL	Store the eRx message status for the last received response (COMP or ERR)
DISPENSE	EXPIRY_DT	DATETIME	NULL	expiry date
DISPENSE	FRED_BILL_TYPE_CD	VARCHAR (5)	NULL	FRED Bill Type Code
DISPENSE	FRED_CODE	VARCHAR (15)	NULL	FRED Code
DISPENSE	FRED_DSPN_ID	INT	NULL	FRED Dispense Id
DISPENSE	GS_PRINT_IND	CHAR(1)	NULL	Goalsheet print indicator
DISPENSE	GSF_ID	INT	NULL	Link to the gs_formulation table
DISPENSE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record
DISPENSE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified
DISPENSE	LBL_FMT_ID	INT	NOT NULL	Label format ID - Link to label_format table
DISPENSE	MED_CHT_ITEM_ID	INT	NULL	Identifier link to Medication Chart Item record
DISPENSE	MIMS_ROUTE_ID	BIGINT	NULL	Column to save mims route id value
DISPENSE	NPBS_DEF_SUPP_IND	CHAR(1)	NOT NULL	Indicator for Defer supply in a Non-PBS Dispensing
DISPENSE	ORIG_DSPN_ID	INT	NULL	Original dispense ID. This is retained after the record is Edited or deleted

DISPENSE	ORIG_PAT_PRICE	NUMERIC(18,8)	NULL	Original patient price value. Used to refresh Patient Price, where it has been removed when Charge Type is changed to 'Hospital' but then changed back to 'Patient'.
DISPENSE	ORIG_PHARM_APPROVAL_NBR	VARCHAR (15)	NULL	OriginalPharmacyApprovalNumber for a non-PBS item from the ERX004 message.
DISPENSE	ORIG_SCRIPT_NBR	VARCHAR (15)	NULL	OriginalScriptNumber for a non-PBS item from the ERX004 message.
DISPENSE	OUTAGE_IND	CHAR(1)	NOT NULL	Indicates that an ePrescription dispensing could not be authorised due to an outage.
DISPENSE	OVERALLSCAN_STAT_CD	VARCHAR(5)	NULL	Code to link to the Overall scan status.
DISPENSE	OWING_MARKOFF_BY	VARCHAR(30)	NULL	Code of the user who marked off the Owing flag.
DISPENSE	OWING_MARKOFF_DT	DATETIME	NULL	Date and time that the Owing Mark Off was done.
DISPENSE	OWING_SCID_XID	VARCHAR (20)	NULL	SCID id which is entered in Enter SCID window when the 'Owing Script' check box is ticked
DISPENSE	PAT_EPS_ID	INT	NULL	Patient episode identifier - link to pat_episode table
DISPENSE	PAT_EPS_XID	VARCHAR (20)	NULL	Patient Episode Number
DISPENSE	PAT_FULL_NAME	VARCHAR (255)	NULL	Patient Full Name at the time of the transaction
DISPENSE	PAT_ID	INT	NOT NULL	Patient identifier - Link to patient table
DISPENSE	PAT_ORIG_PRF_PRICE	NUMERIC(18,8)	NULL	Original PRF price for PBS dispense.
DISPENSE	PAT_PRF_PRICE	NUMERIC(18,8)	NULL	Prescription Record Form Price
DISPENSE	PAT_PRICE	NUMERIC(18,8)	NULL	Price the patient needs to pay
DISPENSE	PAT_PRICING_TYPE_CD	VARCHAR(5)	NULL	Link to display the patient pricing type for Private Hospital Billing.
DISPENSE	PAT_SITE_SID	SMALLINT	NOT NULL	Site associated with patient record - Link to site table
DISPENSE	PES_DEL_DTZ	DATETIMEOFFSET	NULL	Date and time of Dispense reversal
DISPENSE	PES_DEL_RESPONSE_DTZ	DATETIMEOFFSET	NULL	Date and time of acknowledgement from the Delivery Service
DISPENSE	PES_DEL_RESULT	VARCHAR(20)	NULL	The response for the reversal

DISPENSE	PES_DSPN_DTZ	DATETIMEOFFSET	NULL	Date and time of dispense record creation
DISPENSE	PES_DSPN_RESPONSE_DTZ	DATETIMEOFFSET	NULL	Date and time receipt acknowledged by the Delivery Service
DISPENSE	PHARM_XID	VARCHAR (20)	NOT NULL	Code for Pharmacy - Link to pharmacy table
DISPENSE	PICK_IND	CHAR(1)	NOT NULL	Pick indicator
DISPENSE	PICK_MSG_COUNT	INT	NULL	Count of successful OutputMessages received from PillPick robot.
DISPENSE	PPN_ID	INT	NULL	Prescription identifier
DISPENSE	PREP_DT	DATETIME	NULL	Prepared date
DISPENSE	PREPARED_BY	VARCHAR (30)	NULL	Code of the user who prepared the dispense - this will be the same as the user who authorised the dispense, if it was not first 'prepared'.
DISPENSE	PREPARED_DT	DATETIME	NULL	Date and time that the user prepared the dispense
DISPENSE	PRES_DAY_SEQ	INT	NULL	Number indicating where the dispense sits in the sequence of items for the day
DISPENSE	PRES_DT	DATETIME	NULL	Prescription date as entered in the application.
DISPENSE	PROD_ID	INT	NULL	Product Identifier - Link to product table
DISPENSE	PROT_SCHED_PERIOD_ID	INT	NULL	Protocol schedule period identifier - Lnk to prot_sched_period table.
DISPENSE	PROTOCOL_ID	INT	NULL	Protocol number
DISPENSE	PROTOCOL_SHORT_CODE	VARCHAR (15)	NULL	Protocol Short code
DISPENSE	RECV_PRINT_IND	CHAR(1)	NOT NULL	Print indicator
DISPENSE	REF_SITE_SID	SMALLINT	NOT NULL	ID for site used for Reference information - Link to site table
DISPENSE	REPEAT_DSPN_ID	INT	NULL	Repeat Dispensing Identifier
DISPENSE	REPEAT_NBR	SMALLINT (2)	NULL	Repeat number
DISPENSE	REPEAT_REM_NBR	SMALLINT (2)	NULL	Number of repeats remaining
DISPENSE	REPEAT_SCID_XID	VARCHAR (20)	NULL	SCID ID where dispensing with Remaining Repeats >= 1, and repeat item sent to eRx using that SCID
DISPENSE	REPEAT_SITE_SID	SMALLINT	NULL	Repeat Dispensing Site Identifier

DISPENSE	REV_DSPN_ID	INT	NULL	Reverse dispensing identifier
DISPENSE	ROUTE_ID	INT	NULL	Code to link to the Route of administration
DISPENSE	RPT_INT	SMALLINT	NULL	Repeat Interval Days
DISPENSE	RTPM_CHECK_BY	VARCHAR (30)	NULL	Code of the user who authorised RTPM check
DISPENSE	RTPM_CHECK_DT	DATETIME	NULL	Date and time that the user authorised the RTPM Check
DISPENSE	RTPM_CODE	INT	NULL	The numeric code returned from the RTPM Monitor System.
DISPENSE	RTPM_STAT_DESC	VARCHAR(40)	NULL	RTPM Monitor System Response status – 'Red', 'Amber', 'Green', 'Error'.
DISPENSE	RTPM_URL_DESC	VARCHAR(1024)	NULL	The RTPM Monitor System URL details specific to the patient.
DISPENSE	SAME_DSPN_ID	INT	NULL	Dspn_id of the record used as the source, to create the 'same' dispensing
DISPENSE	SCID_XID	VARCHAR (20)	NULL	Unique Script Identifier (SCID) value relevant to the dispensing, from external_message_pes table
DISPENSE	SCRIPT_OWING_IND	CHAR (1)	NOT NULL	Indicator for script owing
DISPENSE	SHELF_LIFE_QTY	NUMERIC(18,8)	NULL	self life qty.
DISPENSE	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
DISPENSE	SLIFE_UNIT_PID	INT	NULL	self life unit
DISPENSE	SUBST_OVERRIDE_DESC	VARCHAR(255)	NULL	BrandSubstitution override reason captured and stored.
DISPENSE	TEAM_XID	VARCHAR (20)	NOT NULL	Code for Team - Link to the team table.
DISPENSE	USER_CD	VARCHAR (15)	NULL	ID of the user who authorised the dispense
DISPENSE	VERSION_ID	INT	NULL	Protocol Version identifier
DISPENSE_P BS	ANS_HIC_REF_DESC	VARCHAR (255)	NULL	ANS HIC Reference Description
DISPENSE_P BS	ANS_IND	CHAR (1)	NOT NULL	ANS Indicator
DISPENSE_P BS	ANS_STATUS_CD	VARCHAR (5)	NOT NULL	ANS Status Indicator
DISPENSE_P BS	AUTH_APP_NBR	VARCHAR (15)	NULL	Authority Approval Number for PBS Authority items.
DISPENSE_P BS	AUTH_NBR	VARCHAR (15)	NULL	Authority Number

DISPENSE_P BS	CARD_VERIFIED_IND	CHAR (1)	NOT NULL	Indicates that the concession card has been verified if the value is set to 'Y'
DISPENSE_P BS	CHART_PAT_CATG	VARCHAR(5)	NULL	PBS Hospital Medication Chart patient category
DISPENSE_P BS	CLAIM_AMT_APPROVED	NUMERIC(18,8)	NULL	Claim amount approved by MCA for PBS Online functionality
DISPENSE_P BS	CLAIM_REF_NO	INT	NULL	PBS claim Reference number
DISPENSE_P BS	CLAIM_REMOVAL_CNT	SMALLINT	NOT NULL	Indicates the number of times a particular claim has been removed.
DISPENSE_P BS	COMPOUNDER_XID	VARCHAR (20)	NULL	Compounder Identifier - Link to compounders table
DISPENSE_P BS	CONTAINER_CD	VARCHAR (5)	NULL	Container Code
DISPENSE_P BS	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
DISPENSE_P BS	CTG_CODE	VARCHAR (15)	NULL	Closing The Gap (CTG) code
DISPENSE_P BS	CTG_HANDWR_IND	CHAR(1)	NOT NULL	CTG Handwritten Indicator
DISPENSE_P BS	DEF_SUPP_IND	CHAR (1)	NOT NULL	Default supply indicator
DISPENSE_P BS	DSPN_DVA_CARD_TYPE_CD	VARHCAR(5)	NULL	DVA Card type - Link to list_of_val
DISPENSE_P BS	DSPN_DVA_NBR	VARCHAR(15)	NULL	DVA number
DISPENSE_P BS	DSPN_PBS_ID	INT	NOT NULL	Unique ID used to identify dispensed PBS item
DISPENSE_P BS	DSPN_PBS_ONLINE_STAT_CD	VARCHAR (5)	NULL	Status of the online PBS Claim
DISPENSE_P BS	DSPN_PRESC_QTY	NUMERIC (18,8)	NULL	Prescribed Qty for PBS Chemo dispensing.
DISPENSE_P BS	GLASS_BOTTLE_IND	CHAR (1)	NOT NULL	Glass Bottle Indicator
DISPENSE_P BS	HIC_REF_NO	VARCHAR (20)	NULL	MCA Price reference number
DISPENSE_P BS	HOSP_PROVIDER_NBR	VARCHAR (15)	NULL	Hospital Provider Number
DISPENSE_P BS	HSD_CONDITION_CD	VARCHAR (5)	NULL	HSD Condition Code in PBS
DISPENSE_P BS	IMM_SUPP_IND	CHAR (1)	NOT NULL	Immediate Supply Indicator
DISPENSE_P BS	INFUSION_XID	VARCHAR (20)	NULL	Infusion ID for PBS Normal
DISPENSE_P BS	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
DISPENSE_P BS	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.

DISPENSE_P BS	LM_PRICE_IND	CHAR (1)	NOT NULL	Local Manufacture Price Indicator
DISPENSE_P BS	MANUF_CD	VARCHAR (5)	NULL	Code to link to list_of_val for PBS Manufacturer
DISPENSE_P BS	MEDICARE_NBR	VARCHAR (15)	NULL	Medicare Number
DISPENSE_P BS	MEDICARE_SUBNBR	CHAR (1)	NULL	Medicare Sub-Number
DISPENSE_P BS	ORIG_PBS_PAYMENT_CATG_CD	VARCHAR (5)	NULL	Original PBS Payment Category Code
DISPENSE_P BS	ORIG_PHARM_APPROVAL_NBR	VARCHAR (15)	NULL	Original Pharmacy Approval Number
DISPENSE_P BS	ORIG_SCRIPT_NBR	VARCHAR (15)	NULL	Original Script Number
DISPENSE_P BS	ORIG_SCRIPT_TYPE_CD	VARCHAR (5)	NOT NULL	Link to Original Dispensing Script Type
DISPENSE_P BS	PACK_SIZE_QTY	NUMERIC(18,8)	NULL	Column to save pack size quantity against the corresponding prescription date
DISPENSE_P BS	PAPERLESS_IND	CHAR (1)	NOT NULL	Paperless Indicator
DISPENSE_P BS	PBS_CANCELLATION_NBR	VARCHAR (15)	NULL	PBS Cancellation number
DISPENSE_P BS	PBS_CATG_CD	VARCHAR (5)	NOT NULL	PBS Category Code
DISPENSE_P BS	PBS_CLAIM_ID	INT	NULL	Link to the pbs_claim table to indicate which claim the record is part of
DISPENSE_P BS	PBS_CLAIM_ITEM_ID	INT	NULL	PBS Claim Item Identifier
DISPENSE_P BS	PBS_CLAIM_PRICE	NUMERIC(18,8)	NOT NULL	PBS price to be claimed by the Pharmacy
DISPENSE_P BS	PBS_CLM_MOVE_BY	VARCHAR(30)	NULL	Code of the user who authorised a move from one PBS Claim to another.
DISPENSE_P BS	PBS_CLM_MOVE_DT	DATETIME	NULL	Date and time that a move from one PBS Claim to another was authorised.
DISPENSE_P BS	PBS_CODE	VARCHAR (15)	NOT NULL	PBS Code of the Item
DISPENSE_P BS	PBS_CONC_NBR	VARCHAR (15)	NULL	PBS Concession Number
DISPENSE_P BS	PBS_ITEM_PID	INT	NULL	Identifier to link records to pbs_item table.
DISPENSE_P BS	PBS_MAX_QTY	NUMERIC(18,8)	NULL	Column to save pbs maximum quantity against the corresponding prescription date
DISPENSE_P BS	PBS_PAYMENT_CATG_CD	VARCHAR (5)	NOT NULL	Code to link to list_of_val for PBS payment Category

DISPENSE_P BS	PBS_REPEAT_NBR	SMALLINT(2)	NULL	Column to save the pbs repeat number against the corresponding prescription date
DISPENSE_P BS	PBS_REST_CODE	VARCHAR (15)	NULL	PBS Restriction Code
DISPENSE_P BS	PBS_REST_NOTE	VARCHAR (255)	NULL	PBS Restriction Notes
DISPENSE_P BS	PREV_DEFERRED_IND	CHAR (1)	NOT NULL	Indicator for Previously deferred
DISPENSE_P BS	PREV_DSPN_DT	DATETIME	NULL	Previous Dispensing Date
DISPENSE_P BS	REG_24_IND	CHAR (1)	NOT NULL	Regulation 24 Indicator
DISPENSE_P BS	RESUB_FLAG_IND	CHAR (1)	NOT NULL	PBS Claim Resubmission Flag
DISPENSE_P BS	RTAC_NBR	VARCHAR(15)	NULL	RTAC Number for IF drug type
DISPENSE_P BS	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
DISPENSE_P BS	STREAMLINE_IND	CHAR(1)	NOT NULL	Streamline indicator
DISPENSE_P BS	UCP_IND	CHAR(1)	NOT NULL	Under CoPayment indicator
DISPENSE_P BS	VIAL_COMBO_DESC	VARCHAR (255)	NULL	Vial Combo Description for identified chemo items.
DISPENSE_P ROD	BIN_BATCH_ID	INT	NULL	Link to Bin batch table
DISPENSE_P ROD	BIN_TRAN_ID	INT	NULL	Unique ID used to link the bin transaction record, for the site
DISPENSE_P ROD	BOM_COMP_QTY	NUMERIC(18,8)	NULL	Quantity of the ingredient if for a non normal dispensing
DISPENSE_P ROD	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
DISPENSE_P ROD	DOSE_CALC_CD	VARCHAR (5)	NULL	Code for the dose calculation
DISPENSE_P ROD	DPP_INGR_DIFF_PRICE	NUMERIC(18,8)	NULL	Dispense ingredient difference price.
DISPENSE_P ROD	DSPN_BATCH_EXP_DT	DATETIME	NULL	Dispense Batch Expiry Date
DISPENSE_P ROD	DSPN_DIFF_PRICE_IND	CHAR(1)	NOT NULL	Differential price indicator.
DISPENSE_P ROD	DSPN_DSCD_CHRG_IND	CHAR (1)	NOT NULL	Dispense Discard Charge Indicator
DISPENSE_P ROD	DSPN_DSCD_IND	CHAR (1)	NULL	When the Discard Indicator column is set to 'YES', then the Discard Quantity is calculated automatically in dispensing
DISPENSE_P ROD	DSPN_DSCD_QTY	NUMERIC(18,8)	NULL	Dispense Discard Quantity

DISPENSE_P ROD	DSPN_FEE_AMT	NUMERIC(18,8)	NULL	Dispensing fee as recorded in dispense price tab
DISPENSE_P ROD	DSPN_FIN_SUB_XID	VARCHAR (20)	NULL	Financial sub class identifier
DISPENSE_P ROD	DSPN_FLAT_AMT	NUMERIC(18,8)	NULL	Base amount from dispensine price tab
DISPENSE_P ROD	DSPN_ID	INT	NOT NULL	ID to link to the dispense table
DISPENSE_P ROD	DSPN_INGR_ADDEDVALUE_ AMT	NUMERIC(18,8)	NULL	Ingredient added value amount
DISPENSE_P ROD	DSPN_INGR_FULL_PRICE	NUMERIC(18,8)	NULL	Ingredient Total Price of Dispensed Item
DISPENSE_P ROD	DSPN_INGR_ORIGPAT_PRICE	NUMERIC(18,8)	NULL	Original Ingredient price for the patient, for use when refreshing the Patient Price after Charge Type is changed to 'Hospital' then back to 'Patient'.
DISPENSE_P ROD	DSPN_INGR_PAT_PRICE	NUMERIC(18,8)	NULL	Ingredient patient price
DISPENSE_P ROD	DSPN_INGR_PRF_PRICE	NUMERIC(18,8)	NULL	Ingredient PRF price
DISPENSE_P ROD	DSPN_INGR_TOT_COST	NUMERIC(18,8)	NULL	Total cost of the ingredient
DISPENSE_P ROD	DSPN_INGR_TOT_PRICE	NUMERIC(18,8)	NULL	Total charge price of the ingredient
DISPENSE_P ROD	DSPN_LAST_BATCH	VARCHAR (10)	NULL	Batch no from dispensing of the dispensed product
DISPENSE_P ROD	DSPN_MARKUP_PCT	NUMERIC(8,6)	NULL	Markup percentage as entered in dispense price tab
DISPENSE_P ROD	DSPN_MAX_CHRG_AMT	NUMERIC(18,8)	NULL	Maximum charge amount as recorded in dispense price tab
DISPENSE_P ROD	DSPN_MIN_CHRG_AMT	NUMERIC(18,8)	NULL	Minimum charge amount as recorded in dispense price tab
DISPENSE_P ROD	DSPN_OVERRIDE_REASON_ NOTE	VARCHAR (255)	NULL	This is text entered by the user to indicate why they have overridden default values
DISPENSE_P ROD	DSPN_PBS_MANUF_ID	INT	NULL	Link to dispense_pbs_manuf table
DISPENSE_P ROD	DSPN_PRIV_DA_FEE	NUMERIC(18,8)	NULL	Drug of Addiction dispensing fee. Defaulted based on the Private DA Fee parameter.
DISPENSE_P ROD	DSPN_PRIV_S3RECORD_FEE	NUMERIC(18,8)	NULL	Recordable Drug dispensing fee. Defaulted based on the Private Recordable Fee parameter.
DISPENSE_P ROD	DSPN_PROD_ID	INT	NOT NULL	Unique ID used to identify dispensed product.

DISPENSE_P ROD	DSPN_QTY	NUMERIC(18,8)	NOT NULL	Dispensed Quantity
DISPENSE_P ROD	DSPN_VOL_ML	NUMERIC(18,8)	NULL	Dispense Volume in Millilitres
DISPENSE_P ROD	INVEN_DELIVERED_QTY	NUMERIC(18,8)	NULL	Column to save inventory delivered quantity value
DISPENSE_P ROD	INVEN_IND	CHAR (1)	NOT NULL	Inventory indicator
DISPENSE_P ROD	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
DISPENSE_P ROD	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
DISPENSE_P ROD	LOC_ID	INT	NULL	Store Location ID - Link to location table
DISPENSE_P ROD	NR_LOC_ID	INT	NULL	Non-robot Store Location ID - Link to location table; to accept remainder stock for a part pack robot dispensing.
DISPENSE_P ROD	OWN_SUPP_IND	CHAR (1)	NULL	Own Supply Indicator
DISPENSE_P ROD	PACK_DELIVERED_QTY	NUMERIC(18,8)	NULL	Pack Delivered Quantity
DISPENSE_P ROD	PAT_PRICING_TYPE_CD	VARCHAR(5)	NULL	Link patient's pricing type.
DISPENSE_P ROD	PERMIT_ID	INT	NULL	Permit Id for Special Product
DISPENSE_P ROD	PERMIT_OLD_ID	INT	NULL	Permit ID for Historic records.
DISPENSE_P ROD	PERMIT_OLD_SITE_SID	SMALLINT	NULL	Permit Site ID for Historic records.
DISPENSE_P ROD	PERMIT_SITE_SID	SMALLINT	NULL	Link to the site holding the pat_prod_permit (in special product register)
DISPENSE_P ROD	PHASE_TYPE_CD	VARCHAR (5)	NULL	TPN Phase: Lipid or Aqueous - used in Goal Sheet Manufacture
DISPENSE_P ROD	PROD_ID	INT	NULL	Product Identifier - Link to product table
DISPENSE_P ROD	PROD_USE_CD	VARCHAR (5)	NULL	Product usage code - Link to list_of_val table.
DISPENSE_P ROD	RANEG_BIN_TRAN_ID	INT	NULL	Robot adjustment (negative) - link to bin_tran table; to record the movement of part pack remainder amount out of robot bin.
DISPENSE_P ROD	RAPOS_BIN_TRAN_ID	INT	NULL	Robot adjustment (positive) - link to bin_tran table; to record the movement of part pack remainder amount into a non-robot bin.

DISPENSE_P ROD	RECON_ID	INT	NULL	Link to recon_prod table - Reconstitution identifier
DISPENSE_P ROD	RECON_LOT_ID	INT	NULL	Reconstitution lot id
DISPENSE_P ROD	RECON_LOT_QTY	NUMERIC(18,8)	NULL	Reconstitution Lot Quantity
DISPENSE_P ROD	RECON_REQ_QTY	NUMERIC(18,8)	NULL	Reconstitution Required Quantity
DISPENSE_P ROD	RECON_TOT_QTY	NUMERIC(18,8)	NULL	Reconstitution Total Quantity
DISPENSE_P ROD	RECON_TYPE_CD	VARCHAR (5)	NULL	Reconstitution Type
DISPENSE_P ROD	REV_DSPN_PROD_ID	INT	NULL	Reverse dispensing product id
DISPENSE_P ROD	ROB_REQ_QTY	NUMERIC(18,8)	NULL	Quantity requested from robot.
DISPENSE_P ROD	ROB_RETURN_QTY	NUMERIC(18,8)	NULL	Part pack amount to be returned to robot
DISPENSE_P ROD	ROB_ROUNDED_QTY	NUMERIC(18,8)	NULL	Rounded up pack quantity for dispensing using a robot bin.
DISPENSE_P ROD	ROBOT_STAT_CD	VARCHAR (5)	NULL	Code used to identify whether the item uses a robot bin or not (R/NR) for a robotic Store, then the pick status (EQ-Equal, NE-Not Equal, IERR-Error, REJ-Rejected, NP-Not Processed).
DISPENSE_P ROD	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
DISPENSE_P ROD	TAX_IND	CHAR (1)	NOT NULL	Indicates that GST applies to calculated patient price - Link to prod_schedule table
DISPENSE_P ROD	TOTAL_INVEN_DELIVERED_QTY	NUMERIC(18,8)	NULL	Total inventory quantity delivered from robot
DISPENSE_P ROD	TOTAL_PACK_DELIVERED_QTY	NUMERIC(18,8)	NULL	Total full pack quantity delivered from robot
DISPENSE_P ROD	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
DISPENSE_P ROD	VEHICLE_IND	CHAR (1)	NULL	Vehicle indicator - indicates that the product is the vehicle into which the other ingredients have been added and can be used for labelling purposes.
DIST_CR_ITEM	BIN_BATCH_ID	INT	NULL	Bin batch identifier
DIST_CR_ITEM	BIN_TRAN_ID	INT	NULL	Unique ID used to link the bin transaction record
DIST_CR_ITEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.

DIST_CR_ITEM	DCI_BATCH_EXP_DT	DATETIME	NULL	Distribution Credit Item Batch Expiry Date
DIST_CR_ITEM	DCI_STAT_CD	VARCHAR (5)	NOT NULL	Distribution Credit Item Status Code
DIST_CR_ITEM	DCI_TOT_COST	NUMERIC(18,8)	NULL	Distribution Credit Item Total Cost
DIST_CR_ITEM	DCI_TOT_EXT_COST	NUMERIC(18,8)	NULL	Distribution Credit Item Total Cost with Tax
DIST_CR_ITEM	DCI_TOT_EXT_PRICE	NUMERIC(18,8)	NULL	Distribution Credit Item Total Price with Tax
DIST_CR_ITEM	DCI_TOT_PRICE	NUMERIC(18,8)	NULL	Distribution Credit Item Total Price
DIST_CR_ITEM	DIST_CR_ID	INT	NOT NULL	Distribution Credit ID - Link to dist_credit table
DIST_CR_ITEM	DIST_CR_ITEM_BATCH	VARCHAR (10)	NULL	Distribution Credit Item Batch Number
DIST_CR_ITEM	DIST_CR_ITEM_COST	NUMERIC(18,8)	NOT NULL	Distribution Credit Item Cost
DIST_CR_ITEM	DIST_CR_ITEM_EXT_COST	NUMERIC(18,8)	NOT NULL	Distribution Credit Item Cost with Tax
DIST_CR_ITEM	DIST_CR_ITEM_EXT_PRICE	NUMERIC(18,8)	NOT NULL	Distribution Credit Item Price with Tax
DIST_CR_ITEM	DIST_CR_ITEM_ID	INT	NOT NULL	Unique ID for Distribution Credit Item, for the site
DIST_CR_ITEM	DIST_CR_ITEM_PRICE	NUMERIC(18,8)	NOT NULL	Distribution Credit Item Price
DIST_CR_ITEM	DIST_CR_QTY	NUMERIC(18,8)	NOT NULL	Distribution Credit Quantity
DIST_CR_ITEM	ISSUE_DT	DATETIME	NULL	Issue Date
DIST_CR_ITEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
DIST_CR_ITEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
DIST_CR_ITEM	LOC_ID	INT	NOT NULL	Store Location ID - Link to location table
DIST_CR_ITEM	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
DIST_CR_ITEM	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
DIST_CR_ITEM	TAX_IND	CHAR (1)	NOT NULL	Tax Indicator
DIST_CR_ITEM	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
DIST_CREDIT	COST_CNTR_XID	VARCHAR (20)	NOT NULL	Cost Centre Code - Link to the Cost centre table
DIST_CREDIT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
DIST_CREDIT	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
DIST_CREDIT	CUST_REF	VARCHAR (20)	NULL	Customer Reference

DIST_CREDIT	DIST_CR_DT	DATETIME	NOT NULL	Distribution Credit Date
DIST_CREDIT	DIST_CR_ID	INT	NOT NULL	Unique ID for Distribution Credit, for the site
DIST_CREDIT	DIST_CR_NOTE	VARCHAR (255)	NULL	Distribution Credit Notes
DIST_CREDIT	DIST_CR_PDE_IND	CHAR (1)	NOT NULL	Distribution Credit PDE Indicator
DIST_CREDIT	DIST_CR_STAT_CD	VARCHAR (5)	NOT NULL	Distribution Credit Status - Link to list_of_val table
DIST_CREDIT	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
DIST_CREDIT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
DIST_CREDIT	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
DIST_CREDIT	STORE_XID	VARCHAR (20)	NOT NULL	Code to link to the Store table
DIST_CREDIT	ROBOT_IND	CHAR(1)	NOT NULL	Robot indicator - Dist Credit created for PillPick by robot data service
DIST_CREDIT	VERIFIED_BY	VARCHAR (30)	NULL	Code of the User who verifies
DIST_ITEM	ADC_IND	CHAR(1)	NOT NULL	Indicates request is created from ADC
DIST_ITEM	ADC_IDENT_XID	VARCHAR(20)	NULL	To Update ADC Ident xid
DIST_ITEM	ADC_PROD_NAME_DESC	VARCHAR(1024)	NULL	indicates product description from OMS
DIST_ITEM	ADC_QTY	NUMERIC(18,8)	NULL	To Update ADC Quantity
DIST_ITEM	ADC_UOM_DESC	VARCHAR(40)	NULL	To update Uom Description comes from OMS
DIST_ITEM	BIN_BATCH_ID	INT	NULL	Bin batch identifier
DIST_ITEM	BIN_TRAN_ID	INT	NULL	Unique ID used to link the bin transaction record
DIST_ITEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
DIST_ITEM	DI_BATCH_EXP_DT	DATETIME	NULL	Distribution item Batch Expiry Date
DIST_ITEM	DIST_ID	INT	NOT NULL	Identification Key for Distribution
DIST_ITEM	DIST_ITEM_BATCH	VARCHAR (10)	NULL	Distribution Item Batch Number
DIST_ITEM	DIST_ITEM_ID	INT	NOT NULL	Unique Distribution Item ID, for the site
DIST_ITEM	DIST_ITEM_STAT_CD	VARCHAR (5)	NOT NULL	Distribution Item Status
DIST_ITEM	DIST_QTY	NUMERIC(18,8)	NULL	Distribution Quantity
DIST_ITEM	IMP_ITEM_ID	INT	NULL	Imprest Item ID - Link to imprest_item table
DIST_ITEM	INVEN_DELIVERED_QTY	NUMERIC(18,8)	NULL	Column to save inventory delivered quantity in the distribution

DIST_ITEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
DIST_ITEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
DIST_ITEM	LOC_ID	INT	NULL	Store Location ID - Link to location table
DIST_ITEM	NR_LOC_ID	INT	NULL	Non-robot Store Location ID - Link to location table; to accept remainder stock for a part pack robot distribution.
DIST_ITEM	PACK_DELIVERED_QTY	NUMERIC(18,8)	NULL	Pack delivered Quantity
DIST_ITEM	PICK_MSG_COUNT	INT	NULL	Count of successful OutputMessages received from PillPick robot.
DIST_ITEM	PROD_ID	INT	NULL	Product Identifier - Link to product table
DIST_ITEM	RANEG_BIN_TRAN_ID	INT	NULL	Robot adjustment (negative) - link to bin_tran table; to record the movement of part pack remainder amount out of robot bin.
DIST_ITEM	RAPOS_BIN_TRAN_ID	INT	NULL	Robot adjustment (positive) - link to bin_tran table; to record the movement of part pack remainder amount into a non-robot bin.
DIST_ITEM	REPLACE_FLAG	CHAR(1)	NULL	Replacement flag
DIST_ITEM	REQN_ITEM_ID	INT	NULL	Requisition Item Identifier - Link to reqn_item table
DIST_ITEM	ROB_RETURN_QTY	NUMERIC(18,8)	NULL	Part pack amount to be returned to robot
DIST_ITEM	ROB_ROUNDED_QTY	NUMERIC(18,8)	NULL	Rounded up pack quantity for distribution using a robot bin.
DIST_ITEM	ROBOT_STAT_CD	VARCHAR(5)	NOT NULL	Code used to identify whether the item uses a robot bin or not (R/NR).
DIST_ITEM	ROBOT_TRAN_ID	INT	NULL	Robot transaction Identifier - Link to external_message_robot table for the particular Request message.
DIST_ITEM	RQI_SITE_SID	SMALLINT	NULL	Requesting site identifier - Link to the site table
DIST_ITEM	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
DIST_ITEM	SUBST_IND	CHAR(1)	NULL	Substitution flag
DIST_ITEM	TAX_IND	CHAR (1)	NOT NULL	Tax Indicator

DIST_ITEM	UOM_ID	INT	NULL	Unit of Measurement Identifier - Link to UOM table
DIST_ITEM	URGENT_IND	CHAR (1)	NOT NULL	Urgency Indicator
DIST_ITEM	WARD_BOX_NBR	VARCHAR(255)	NULL	The box numbers for the boxes that the ward stock is delivered in, as received from the robot Output message.
DISTRIBUTION	ADC_IND	CHAR(1)	NOT NULL	Indicates ad ADC Distribution
DISTRIBUTION	ADC_NAME_ID	INT	NULL	ADC Name id
DISTRIBUTION	BULK_STOCK_IND	CHAR(1)	NOT NULL	Indicates that a bulk stock (ward box) chute was used.
DISTRIBUTION	CHUTE_XID	VARCHAR(20)	NULL	Chute code for robot delivery of the item - link to robot_chute table.
DISTRIBUTION	COST_CNTR_XID	VARCHAR(20)	NOT NULL	Short Code used to identify Charge center
DISTRIBUTION	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
DISTRIBUTION	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current.
DISTRIBUTION	CUST_ORD_REF	VARCHAR(20)	NULL	Customer Order Reference
DISTRIBUTION	DELIVERY_ADDR_NOTE	VARCHAR(255)	NULL	Delivery address
DISTRIBUTION	DIST_DT	DATETIME	NOT NULL	Distribution Date
DISTRIBUTION	DIST_GL_EXTRACT	INT	NULL	Not used in this version of i.Pharmacy
DISTRIBUTION	DIST_ID	INT	NOT NULL	Unique ID for Distribution, for the site
DISTRIBUTION	DIST_NOTE	VARCHAR(255)	NULL	Distribution Note
DISTRIBUTION	DIST_STAT_CD	VARCHAR(5)	NOT NULL	Distribution Status Code - Link to list_of_val table
DISTRIBUTION	FOLLOWUP_PRINT_IND	CHAR(1)	NOT NULL	Indicates whether the distribution followup report is printed at least once when this column has value 'Y'
DISTRIBUTION	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
DISTRIBUTION	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
DISTRIBUTION	PDE_IND	CHAR (1)	NOT NULL	PDE indicator

DISTRIBUTION	PICK_NTRQ_IND	CHAR(1)	NOT NULL	Pick Not Required Indicator - indicators whether the robot picking step was bypassed or not.
DISTRIBUTION	PRINT_IND	CHAR(1)	NOT NULL	Print indicator
DISTRIBUTION	ROBOT_STAT_CD	VARCHAR(5)	NOT NULL	Code used to identify whether the item uses a robot bin or not (R/NR).
DISTRIBUTION	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
DISTRIBUTION	STORE_XID	VARCHAR(20)	NOT NULL	Code to link to the Store table
DISTRIBUTION	URGENT_IND	CHAR(1)	NOT NULL	Urgency Indicator
DISTRIBUTION	VERIFIED_BY	VARCHAR(30)	NULL	Urgency Indicator
DISTRIBUTION	WARD_BOX_NBR	VARCHAR(255)	NULL	The box numbers for the boxes that the ward stock is delivered in, as received from the robot Output message.
DOCTOR	ADT_DOCT_XID	VARCHAR (20)	NULL	ADT Doctor code, used to match doctors in HL7 messaging
DOCTOR	CLIN_SYS_XID	VARCHAR (20)	NULL	Clinical System code
DOCTOR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
DOCTOR	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
DOCTOR	DOCT_ADDR_1	VARCHAR (40)	NULL	Doctor Address1
DOCTOR	DOCT_ADDR_2	VARCHAR (40)	NULL	Doctor Address2
DOCTOR	DOCT_ADDR_3	VARCHAR (40)	NULL	Doctor Address3
DOCTOR	DOCT_ADDR_4	VARCHAR (40)	NULL	Doctor Address4
DOCTOR	DOCT_CNTRY	VARCHAR (30)	NULL	Doctor Country
DOCTOR	DOCT_FIRST_NAME	VARCHAR (255)	NULL	Doctor First Name
DOCTOR	DOCT_NOTE	VARCHAR (255)	NULL	Doctor Notes
DOCTOR	DOCT_PHONE_1	VARCHAR (15)	NULL	Doctor Phone Number1
DOCTOR	DOCT_PHONE_2	VARCHAR (15)	NULL	Doctor Phone Number2
DOCTOR	DOCT_PHONE_3	VARCHAR (15)	NULL	Doctor Phone Number3
DOCTOR	DOCT_POSTCODE	VARCHAR (10)	NULL	Doctor Postal Code
DOCTOR	DOCT_SALUTATION	CHAR (10)	NULL	Doctor salutation
DOCTOR	DOCT_SURNAME	VARCHAR (255)	NULL	Doctor Surname
DOCTOR	DOCT_SURNAME_UC	VARCHAR (255)	NULL	Doctor Surname in upper case
DOCTOR	DOCT_XID	VARCHAR (20)	NOT NULL	Unique code for Doctor, for the site
DOCTOR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
DOCTOR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.

DOCTOR	PRAC_NAME	VARCHAR (255)	NULL	To Store the Practioner Name
DOCTOR	PRAC_EMAIL	VARCHAR(60)	NULL	To Store the Practioner Email
DOCTOR	PBS_PRES_NBR	VARCHAR (15)	NULL	PBS Prescriber Number
DOCTOR	PRES_TYPE_CD	VARCHAR (5)	NOT NULL	Prescriber Type code
DOCTOR	PRES_EMAIL	VARCHAR(60)	NULL	To store the prescriber Email
DOCTOR	PRES_HI_XID	VARCHAR(20)	NULL	To Store the Prescriber HPII id
DOCTOR	PROV_XID	VARCHAR (20)	NULL	Provider Directory ID
DOCTOR	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
DOCTOR	TEAM_POSN_DESC	VARCHAR (40)	NULL	Doctor Team Position Description
DOCTOR	TEAM_XID	VARCHAR (20)	NOT NULL	Code for Team - Link to the team table.
DSPN_ORDER	ADMIN_DT	DATETIME	NULL	Administration date-A value may be present for single dose orders
DSPN_ORDER	AMT_TYPE_CD	VARCHAR (5)	NULL	AMT Type Code
DSPN_ORDER	AUTH_NBR	VARCHAR(15)	NULL	Authority number for a PBS script.
DSPN_ORDER	CONC_CARD_TYPE_CD	VARCHAR(5)	NULL	Concession card type - Link to list_of_val
DSPN_ORDER	COST_CNTR_XID	VARCHAR (20)	NULL	Cost Centre Code - Link to the Cost centre table
DSPN_ORDER	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
DSPN_ORDER	DOCT_XID	VARCHAR (20)	NULL	Code for Doctor from the Order message - Link to the doctor table
DSPN_ORDER	DPO_DIRCODE_TYPE_CD	VARCHAR(5)	NOT NULL	Direction Code Type - link to user_site_settings table
DSPN_ORDER	DPO_SOURCE_CD	VARCHAR (5)	NOT NULL	DPO Source Code - Link to dpo_source_control table
DSPN_ORDER	DSPN_CLASS_ID	INT	NULL	ID for dispense class - Link to dispense_class table
DSPN_ORDER	DSPN_DIR	VARCHAR (255)	NULL	Dispense Directions (administration instructions)
DSPN_ORDER	DSPN_DOCT_XID	VARCHAR(20)	NULL	Code for Doctor to be used for the dispensing - Link to the doctor table
DSPN_ORDER	DSPN_ORDER_ID	INT	NOT NULL	Unique Dispensing Order ID, for the site
DSPN_ORDER	DSPN_REPEAT_NBR	SMALLINT	NULL	Repeat number to be used for the dispensing
DSPN_ORDER	DVA_CARD_TYPE_CD	VARCHAR(5)	NULL	DVA Card type - Link to list_of_val

DSPN_ORDER	DVA_NBR	VARCHAR(15)	NULL	DVA number
DSPN_ORDER	ENTITLEMENT_EXP_DT	DATETIME	NULL	Entitlement Expiry date.
DSPN_ORDER	ENTITLEMENT_NBR	VARCHAR(15)	NULL	Entitlement number.
DSPN_ORDER	ERX_ORDER_NOTE	VARCHAR(255)	NULL	erx order notes
DSPN_ORDER	GO_AHEAD_IND	CHAR(1)	NOT NULL	Go/No Go Ahead indicator (iQemo© interface)
DSPN_ORDER	HIGH_COST_HOLD_IND	CHAR(1)	NULL	On High Cost Hold/Release indicator (iQemo© interface)
DSPN_ORDER	INDICATION	VARCHAR (200)	NULL	Indication details supplied by Clinical System
DSPN_ORDER	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
DSPN_ORDER	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
DSPN_ORDER	MEDICARE_EXP_DT	DATETIME	NULL	Medicare Expiry date.
DSPN_ORDER	MEDICARE_NBR	VARCHAR(15)	NULL	Medicare number.
DSPN_ORDER	MEDICARE_SUBNBR	CHAR(1)	NULL	Medicare sub number.
DSPN_ORDER	MSG_ACTION_CD	VARCHAR (5)	NULL	Message Action Code - Link to dpo_source_control table
DSPN_ORDER	NO_ACTION_AUTH_BY	VARCHAR(30)	NULL	To update no action authorised user
DSPN_ORDER	NO_ACTION_AUTH_DT	DATETIME	NULL	To update no action authorised date
DSPN_ORDER	ORDER_VERIFIED_IND	CHAR(1)	NOT NULL	On Hold indicator (iQemo© interface)
DSPN_ORDER	ORIG_PLACER_ORDER_DESC	VARCHAR(40)	NULL	Value should be present where an existing order has been repeated in the prescribing system.
DSPN_ORDER	OWN_SUPP_IND	CHAR(1)	NULL	Indicator for Own supply dispensing
DSPN_ORDER	PAT_CLASS_DESC	VARCHAR (40)	NULL	Patient Dispensing Class Description supplied by Clinical System
DSPN_ORDER	PAT_ID	INT	NULL	Patient identifier - Link to patient table
DSPN_ORDER	PAT_SITE_SID	SMALLINT	NOT NULL	Site associated with patient record - Link to site table
DSPN_ORDER	PAT_XID	VARCHAR (20)	NOT NULL	Patient identifier - Link to patient table
DSPN_ORDER	PATIENT_NAME	VARCHAR (255)	NULL	Patient Name
DSPN_ORDER	PBS_CODE	VARCHAR(15)	NULL	Pbs code - Link to pbs_code table.

DSPN_ORDER	PBS_INGR_DATA_DESC	VARCHAR(1024)	NULL	Data will be concatenated from RXC segments(s) and stored, for display in Prescription Details (iQemo® interface)
DSPN_ORDER	PBS_PAYMENT_CATG_CD	VARCHAR (5)	NOT NULL	PBS payment category
DSPN_ORDER	PBS_PRES_NBR	VARCHAR(15)	NULL	PBS prescriber number.
DSPN_ORDER	PBS_REST_CODE	VARCHAR(15)	NULL	Restriction code.
DSPN_ORDER	PCIST_VERIFIED_BY	VARCHAR(30)	NULL	Pharmacist / User who verified this order, supplied by Clinical System
DSPN_ORDER	PHARM_APPROVAL_NBR	VARCHAR(15)	NULL	Pharmacy approval Number.
DSPN_ORDER	PHARM_DESC	VARCHAR(40)	NULL	pharmacy description
DSPN_ORDER	PLACER_ORDER_DESC	VARCHAR (40)	NOT NULL	Order Description supplied by Clinical System
DSPN_ORDER	PPN_ID	INT	NULL	Prescription Identifier, updated if the Prescription type is Electronic - Link to prescription table
DSPN_ORDER	PRES_DT	DATETIME	NOT NULL	Prescription Date
DSPN_ORDER	PRIORITY_DESC	VARCHAR (40)	NULL	Priority Description supplied by Clinical System
DSPN_ORDER	PROD_ID	INT	NULL	Product Identifier - Link to product table
DSPN_ORDER	REG_24_IND	CHAR(1)	NULL	Reg24 indicator.
DSPN_ORDER	REPEAT_NBR	SMALLINT	NULL	Repeat number from the Order message
DSPN_ORDER	ROUTE_ID	INT	NULL	Route identifier - Link to route table
DSPN_ORDER	RQST_AUTH_NBR	VARCHAR(15)	NULL	Authority Number supplied by Clinical System
DSPN_ORDER	RQST_COST_CNTR_XID	VARCHAR (20)	NULL	Cost Centre Code supplied by Clinical System
DSPN_ORDER	RQST_DOSAGE_FORM	VARCHAR (60)	NULL	Request Product Dosage Form supplied by Clinical System
DSPN_ORDER	RQST_DSPN_AMT	NUMERIC(18,8)	NULL	Requested Dispensed Amount supplied by Clinical System
DSPN_ORDER	RQST_DSPN_CLASS_ID	INT	NULL	Patient Dispense Class ID supplied by Clinical System
DSPN_ORDER	RQST_DURATION	VARCHAR (40)	NULL	Request Duration supplied by Clinical System
DSPN_ORDER	RQST_GENERIC_DESC	VARCHAR(255)	NULL	Generic description supplied by Clinical System

DSPN_ORDER	RQST_GIVE_STRENGTH	NUMERIC (9)	NULL	Dose Strength supplied by Clinical System
DSPN_ORDER	RQST_GIVE_STRENGTH_UNIT	VARCHAR (60)	NULL	Unit of the Product Dose supplied by Clinical System
DSPN_ORDER	RQST_GIVE_TIME_PER_UNIT	VARCHAR (20)	NULL	No of Days the Dose should be given supplied by Clinical System
DSPN_ORDER	RQST_PBS_CODE	VARCHAR(15)	NULL	PBS code supplied by Clinical System
DSPN_ORDER	RQST_PBS_REST_CODE	VARCHAR(15)	NULL	PBS restriction code supplied by Clinical System
DSPN_ORDER	RQST_PHARM_APPROVAL_NBR	VARCHAR(15)	NULL	Pharmacy approval number supplied by Clinical System
DSPN_ORDER	RQST_PROD_ID	BIGINT	NULL	Requested product ID / Concept ID
DSPN_ORDER	RQST_PRODUCT	VARCHAR (8000)	NOT NULL	Requested Product for Dispensing supplied by Clinical System
DSPN_ORDER	RQST_REG_24_IND	CHAR(1)	NULL	Regulation 24 indicator supplied by Clinical System
DSPN_ORDER	RQST_ROUTE_DESC	VARCHAR (40)	NULL	Route description supplied by Clinical System
DSPN_ORDER	RQST_ROUTE_ID	INT	NULL	Route identifiersupplied by Clinical System
DSPN_ORDER	RQST_TEAM_XID	VARCHAR(20)	NULL	Team identifier supplied by Clinical System
DSPN_ORDER	SAFETY_NET_NBR	VARCHAR(15)	NULL	Safety Net Number.
DSPN_ORDER	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
DSPN_ORDER	SITE_XID	VARCHAR (20)	NOT NULL	Site identifier - Link to site table
DSPN_ORDER	START_DT	DATETIME	NULL	start date
DSPN_ORDER	STOP_DT	DATETIME	NULL	Stop date
DSPN_ORDER	STOP_REASON_CD	VARCHAR (5)	NULL	The Code of Reason for Stopping the Prescription
DSPN_ORDER	STOP_REASON_NOTE	VARCHAR (255)	NULL	Stop Reason Notes supplied by Clinical System
DSPN_ORDER	TEAM_XID	VARCHAR(20)	NULL	Team updated for the order
DSPN_ORDER	TREATMENT_NOTE	VARCHAR (255)	NULL	Notes for the treatment supplied by Clinical System
DSPN_ORDER	USER_CD	VARCHAR (15)	NULL	Code of the user
DSPN_ORDER	VERIFIED_BY	VARCHAR(30)	NULL	Code for user who verified the order.
ORD_WORK	CONTRACT_NBR_REF	VARCHAR(20)	NULL	Contract Number Reference
ORD_WORK	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.

ORD_WORK	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
ORD_WORK	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
ORD_WORK	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
ORD_WORK	LOC_ID	INT	NULL	Store Location ID - Link to location table
ORD_WORK	LOC_TYPE_CD	VARCHAR(5)	NOT NULL	Location type (robot, non robot or both) - link to list_of_val table
ORD_WORK	ORD_NOTE	VARCHAR (255)	NULL	Order Notes
ORD_WORK	ORD_WORK_DESC	VARCHAR (40)	NULL	Suggested order description
ORD_WORK	ORD_WORK_DT	DATETIME	NOT NULL	Suggested order date
ORD_WORK	ORD_WORK_ID	INT	NOT NULL	Order Worksheet Number
ORD_WORK	ORD_WORK_STAT_CD	VARCHAR (5)	NOT NULL	Suggested order status code - Link to list_of_val table
ORD_WORK	ORD_WORK_TYPE_CD	VARCHAR (5)	NOT NULL	Suggested order type code - Link to list_of_val table
ORD_WORK	ROUNDING_CD	VARCHAR (5)	NOT NULL	Rounding code - Link to list_of_val table
ORD_WORK	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
ORD_WORK	STORE_XID	VARCHAR (20)	NULL	Code to link to the Store table
ORD_WORK	VERIFIED_BY	VARCHAR (30)	NULL	Code of the User who verifies
ORD_WORK_ITEM	COST_CNTR_XID	VARCHAR (20)	NULL	Cost Centre Code - Link to the Cost centre table
ORD_WORK_ITEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
ORD_WORK_ITEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
ORD_WORK_ITEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
ORD_WORK_ITEM	LOC_ID	INT	NULL	Store Location ID - Link to location table
ORD_WORK_ITEM	ORD_COST	NUMERIC(18,8)	NOT NULL	Order Cost
ORD_WORK_ITEM	ORD_EXT_COST	NUMERIC(18,8)	NOT NULL	Order Cost with Tax
ORD_WORK_ITEM	ORD_REF	VARCHAR (20)	NULL	Order Reference
ORD_WORK_ITEM	ORD_WORK_ID	INT	NOT NULL	Order Worksheet Number
ORD_WORK_ITEM	ORD_WORK_ITEM_ID	INT	NOT NULL	Order Worksheet Item Number

ORD_WORK_ITEM	ORD_WORK_QTY	NUMERIC(18,8)	NULL	Suggested Order qty
ORD_WORK_ITEM	OWI_STAT_CD	VARCHAR (5)	NOT NULL	Owing Status code - Link to list_of_val table
ORD_WORK_ITEM	PREF_LOGIC_IND	CHAR(1)	NULL	Indicates if preferred brand logic applies, based on AMT links between products
ORD_WORK_ITEM	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
ORD_WORK_ITEM	REQN_ITEM_ID	INT	NULL	Requisition Item Identifier
ORD_WORK_ITEM	RQL_SITE_SID	SMALLINT	NULL	Requesting site identifier - Link to site table
ORD_WORK_ITEM	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
ORD_WORK_ITEM	SUPP_XID	VARCHAR (20)	NULL	Code used to link to the Supplier record
ORD_WORK_ITEM	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
ORDER_ITEM	CONTRACT_REF_XID	VARCHAR(20)	NULL	Contract Number Reference
ORDER_ITEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
ORDER_ITEM	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
ORDER_ITEM	EXPECTED_DELIV_DT	DATETIME	NULL	Expected Delivery Date
ORDER_ITEM	LAST_MODIFIED_BY	VARCHAR (30)	NULL	Code for the user who last modified the record
ORDER_ITEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
ORDER_ITEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
ORDER_ITEM	LOC_ID	INT	NULL	Store Location ID - Link to location table
ORDER_ITEM	ORD_COST	NUMERIC(18,8)	NOT NULL	Order Cost
ORDER_ITEM	ORD_EXT_COST	NUMERIC(18,8)	NOT NULL	Order Cost with Tax
ORDER_ITEM	ORD_ID	INT	NOT NULL	Order number
ORDER_ITEM	ORD_ITEM_ID	INT	NOT NULL	Order Item Number
ORDER_ITEM	ORD_ITEM_SEQ	INT	NULL	Order item sequence
ORDER_ITEM	ORD_ITEM_STAT_CD	VARCHAR (5)	NOT NULL	Status of the order item - Link to list_of_val table
ORDER_ITEM	ORD_QTY	NUMERIC(18,8)	NOT NULL	Order Quantity
ORDER_ITEM	ORIG_ORD_QTY	NUMERIC(18,8)	NOT NULL	Original order quantity

ORDER_ITEM	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
ORDER_ITEM	REPLACE_FLAG	CHAR(1)	NULL	Indicates a product substitution has been done for a Direct Purchase item
ORDER_ITEM	REQN_ITEM_ID	INT	NULL	Requisition Item Identifier
ORDER_ITEM	RQI_SITE_SID	SMALLINT	NULL	Requesting site identifier - Link to site table
ORDER_ITEM	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
ORDER_ITEM	SUBST_IND	CHAR(1)	NULL	Indicates there was a substitution message for the item (but no replacement product suggested).
ORDER_ITEM	SUPP_CATL_ID	INT	NULL	Supplier Catalog ID - Link to supp_catl table
ORDER_ITEM	SUPP_CATL_XID	VARCHAR (20)	NULL	Supplier Catalogue Identifier
ORDER_ITEM	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
ORDERS	AMEND_USER_CD	VARCHAR (15)	NULL	Code of the User who modified the record
ORDERS	COST_CNTR_XID	VARCHAR (20)	NULL	Cost Centre Code - Link to the Cost centre table
ORDERS	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
ORDERS	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
ORDERS	DELIV_INST	VARCHAR (255)	NULL	Delivery instructions
ORDERS	EDI_BUILD_ID	INT	NULL	EDI Build ID for importing
ORDERS	EDI_REF	VARCHAR (255)	NULL	EDI reference
ORDERS	EDI_STAT_CD	VARCHAR (5)	NULL	EDI Status Code - Link to list_of_val table
ORDERS	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
ORDERS	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
ORDERS	ORD_DT	DATETIME	NOT NULL	Date the Order was placed
ORDERS	ORD_ID	INT	NOT NULL	Order number
ORDERS	ORD_NOTE	VARCHAR (255)	NULL	Order Notes
ORDERS	ORD_PRINT_IND	CHAR (1)	NOT NULL	Indicator for order printing
ORDERS	ORD_STAT_CD	VARCHAR (5)	NOT NULL	Order Status code - Link to list_of_val table
ORDERS	ORD_TYPE_CD	VARCHAR (5)	NOT NULL	Order Type code - Link to list_of_val table
ORDERS	PRINT_IND	CHAR (1)	NOT NULL	Print indicator

ORDERS	PRINTED_BY	VARCHAR (30)	NULL	Printed by
ORDERS	PRINTED_DT	DATETIME	NULL	Printed date
ORDERS	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
ORDERS	STORE_XID	VARCHAR (20)	NULL	Code to link to the Store table
ORDERS	SUPP_XID	VARCHAR (20)	NOT NULL	Code used to link to the Supplier table
ORDERS	USER_CD	VARCHAR (15)	NULL	Code to identify the user
ORDERS	VERIFIED_BY	VARCHAR (30)	NULL	Code of the User who verifies
ORDERS_EX TR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
ORDERS_EX TR	EXTR_ID	INT	NOT NULL	Unique ID used to identify the extraction
ORDERS_EX TR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
ORDERS_EX TR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
ORDERS_EX TR	ORD_ID	INT	NOT NULL	Order number
ORDERS_EX TR	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
PATIENT	ALIAS_PAT_ID	INT	NULL	Alias Patient Identifier - Link to patient table
PATIENT	ALIAS_PAT_SITE_SID	SMALLINT	NULL	ID for site used for Alias information- Link to site table
PATIENT	CONC_CARD_TYPE_CD	VARCHAR (5)	NULL	Patient Concession Card Type Code - Link to list_of_val table
PATIENT	COST_CNTR_XID	VARCHAR (20)	NULL	Cost Centre Code - Link to the Cost centre table
PATIENT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PATIENT	DEBTOR_XID	VARCHAR (20)	NULL	Code used to identify the debtor - Link to debtor table
PATIENT	DOCT_XID	VARCHAR (20)	NULL	Code for Doctor - Link to the doctor table
PATIENT	DVA_CARD_TYPE_CD	VARCHAR (5)	NULL	Patient DVA Card Type Code - Link to list_of_val table
PATIENT	DVA_NBR	VARCHAR (15)	NULL	Patient DVA Number
PATIENT	EMAIL	VARCHAR (60)	NULL	Patient Email
PATIENT	ENTITLEMENT_EXP_DT	DATETIME	NULL	Patient Entitlement Expiry Date
PATIENT	ENTITLEMENT_NBR	VARCHAR (15)	NULL	Patient Entitlement Number
PATIENT	EOP_EMAIL	VARCHAR (60)	NULL	Evidence of Prescription email address

PATIENT	EOP_METH_CD	VARCHAR (5)	NULL	Evidence of Prescription Method
PATIENT	EOP_MOB_PHONE	VARCHAR (15)	NULL	Evidence of Prescription mobile phone number
PATIENT	FAMILY_ID	INT	NULL	Family Identifier - Link to family table
PATIENT	FIN_CLASS_XID	VARCHAR (20)	NULL	Code for Financial Class - Link to finance_class table
PATIENT	FIN_SUB_XID	VARCHAR (20)	NULL	Unique code for the Financial Sub class, for the site
PATIENT	GUAR_ADDR_1	VARCHAR (40)	NULL	Patient Guarantor Address 1
PATIENT	GUAR_ADDR_2	VARCHAR (40)	NULL	Patient Guarantor Address 2
PATIENT	GUAR_ADDR_3	VARCHAR (40)	NULL	Patient Guarantor Address 3
PATIENT	GUAR_ADDR_4	VARCHAR (40)	NULL	Patient Guarantor Address 4
PATIENT	GUAR_CNTRY	VARCHAR (30)	NULL	Patient Guarantor Country
PATIENT	GUAR_FIRST_NAME	VARCHAR (255)	NULL	Patient Guarantor First Name
PATIENT	GUAR_PHONE_1	VARCHAR (15)	NULL	Patient Guarantor Phone number 1
PATIENT	GUAR_PHONE_2	VARCHAR (15)	NULL	Patient Guarantor Phone number 2
PATIENT	GUAR_PHONE_3	VARCHAR (15)	NULL	Patient Guarantor Phone number 3
PATIENT	GUAR_POSTCODE	VARCHAR (10)	NULL	Patient Guarantor Post Code
PATIENT	GUAR_SURNAME	VARCHAR (255)	NULL	Patient Guarantor Surname
PATIENT	HR_CONSENT_WITHDRAWN_IND	CHAR(1)	NOT NULL	Health Record Consent withdrawn indicator.
PATIENT	INDIG_STAT_CD	VARCHAR(5)	NULL	Indigenous status code
PATIENT	INS_TBL_ID	INT	NULL	Insurer table ID
PATIENT	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PATIENT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PATIENT	LMO_DOCT_XID	VARCHAR (20)	NULL	Code for Local Medical Officer - Link to the doctor table
PATIENT	MEDICARE_EXP_DT	DATETIME	NULL	Medicare Expiry Date
PATIENT	MEDICARE_NBR	VARCHAR (15)	NULL	Medicare Number
PATIENT	MEDICARE_SUBNBR	CHAR (1)	NULL	Medicare Sub-Number
	MYSL_PAT_XID	VARCHAR(255)	NULL	Unique ID for the Patient resource in MySQL. Returned following GET Patient call and used in subsequent API calls. Indicates that the patient exists in MySQL.
PATIENT	NHS_NBR_ID	Decimal(10,0)	NULL	NHS Number
PATIENT	NHS_STAT_CD	VARCHAR (5)	NULL	NHS status code

PATIENT	NO_FIRST_NAME_IND	CHAR (1)	NOTNULL	Indicates if the patient has no First Name.
PATIENT	NO_KNOWN_ALG_IND	CHAR (1)	NOT NULL	Indicator for no known allergies
PATIENT	NOALLERGY_UPDATE_BY	VARCHAR(30)	NULL	User code for who ticked the No Known Allergy check box
PATIENT	NOALLERGY_UPDATE_DT	DATETIME	NULL	Date and time when the No Known Allergy check box is checked.
PATIENT	PAT_ADDR_1	VARCHAR (40)	NULL	Patient Address 1
PATIENT	PAT_ADDR_2	VARCHAR (40)	NULL	Patient Address 2
PATIENT	PAT_ADDR_3	VARCHAR (40)	NULL	Patient Address 3
PATIENT	PAT_ADDR_4	VARCHAR (40)	NULL	Patient Address 4
PATIENT	PAT_ADMIT_DT	DATETIME	NULL	Patient Admit Date
PATIENT	PAT_ADMIT_PREV_DT	DATETIME	NULL	Patient Previous Admit Date
PATIENT	PAT_BIRTH_DT	DATETIME	NULL	Patient Birth Date
PATIENT	PAT_CLAIM_REF	VARCHAR (20)	NULL	Patient Claim Reference Number
PATIENT	PAT_CNTRY	VARCHAR (30)	NULL	Patient Country
PATIENT	PAT_DCSD_DT	DATETIME	NULL	Patient Deceased Date
PATIENT	PAT_DISCH_DT	DATETIME	NULL	Patient Discharge Date
PATIENT	PAT_EPS_XID	VARCHAR (20)	NULL	Patient Episode Number
PATIENT	PAT_FIRST_NAME	VARCHAR (255)	NULL	Patient First name
PATIENT	PAT_HI_XID	VARCHAR(20)	NULL	Individual Healthcare Identifier (IHI)
PATIENT	PAT_ID	INT	NOT NULL	Unique ID for Patient, for the site
PATIENT	PAT_LANG_CD	VARCHAR (5)	NULL	Patient Language Code
PATIENT	PAT_LOC_BED_DESC	VARCHAR (40)	NULL	Patient Location Bed Description
PATIENT	PAT_LOC_BUILD_DESC	VARCHAR (40)	NULL	Patient Location Building Description
PATIENT	PAT_LOC_DESC	VARCHAR (40)	NULL	Patient Location Description
PATIENT	PAT_LOC_FLOOR_DESC	VARCHAR (40)	NULL	Patient Location Floor Description
PATIENT	PAT_LOC_ROOM_DESC	VARCHAR (40)	NULL	Patient Location Room Description
PATIENT	PAT_NOTE	VARCHAR (255)	NULL	Patient note
PATIENT	PAT_PHONE_1	VARCHAR (15)	NULL	Patient Phone Number 1
PATIENT	PAT_PHONE_2	VARCHAR (15)	NULL	Patient Phone Number 2
PATIENT	PAT_PHONE_3	VARCHAR (15)	NULL	Patient Phone Number 3
PATIENT	PAT_POSTCODE	VARCHAR (10)	NULL	Patient Post Code
PATIENT	PAT_SALUTATION	VARCHAR (10)	NULL	Patient Salutation
PATIENT	PAT_SEX	CHAR (1)	NULL	Patient Sex
PATIENT	PAT_SOURCE_CD	VARCHAR (5)	NOT NULL	Patient Source Code - Link to list_of_val table
PATIENT	PAT_SURNAME	VARCHAR (255)	NULL	Patient Surname

PATIENT	PAT_SURNAME_UC	VARCHAR (255)	NULL	Patient Surname upper case
PATIENT	PAT_XID	VARCHAR (20)	NOT NULL	Patient identifier - Link to patient table
PATIENT	REF_SITE_SID	SMALLINT	NOT NULL	ID for site used for Reference information - Link to site table
PATIENT	SAFETY_NET_NBR	VARCHAR (15)	NULL	Patient Safety Net Number
PATIENT	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
PATIENT	PRES_BAG_IND	CHAR (1)	NOT NULL	Indicates the Patient Details will in fact be Prescriber Details, so that Prescriber Bag items will be dispensed to the actual Prescriber for immediate administration or emergency use.
PATIENT	TEAM_XID	VARCHAR (20)	NULL	Code for Team - Link to the team table.
PBS_CLAIM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_CLAIM	EDIT_USER_CD	VARCHAR (30)	NULL	Code for the user who Edited the PBS Claim record
PBS_CLAIM	GENERATED_DT	DATETIME	NULL	Date and time the PBS Claim was generated
PBS_CLAIM	GENERATED_USER_CD	VARCHAR (30)	NULL	Code for the user who Generated the PBS Claim record
PBS_CLAIM	HIC_PBS_CLAIM_XID	VARCHAR (20)	NULL	PBS Claim period
PBS_CLAIM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PBS_CLAIM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_CLAIM	PBS_CLAIM_ID	INT	NOT NULL	Unique ID for the PBS claim
PBS_CLAIM	PBS_CLAIM_NOTE	VARCHAR (255)	NULL	PBS Claim Notes
PBS_CLAIM	PBS_CLAIM_STAT_CD	VARCHAR (5)	NOT NULL	Code for PBS Claim Status - Link to list_of_val table
PBS_CLAIM	PHARM_APPROVAL_NBR	VARCHAR (15)	NOT NULL	Pharmacy Approval Number
PBS_CLAIM	PREPARED_DT	DATETIME	NULL	Preparation Date
PBS_CLAIM	PREPARED_USER_CD	VARCHAR (30)	NULL	Code for the user who Prepared the PBS Claim record
PBS_CLAIM	STATEMENT_TYPE	VARCHAR (5)	NULL	Statement Type
PBS_CODE	AMT_MP_DESCLONG	VARCHAR (255)	NULL	Description of Medicinal Product.

PBS_CODE	AMT_MP_XID	VARCHAR (20)	NULL	Medicinal Product ID.
PBS_CODE	AMT_MPP_DESCLONG	VARCHAR (255)	NULL	Description of Medicinal Product Pack.
PBS_CODE	AMT_MPP_XID	VARCHAR (20)	NULL	Medicinal Product Pack ID.
PBS_CODE	AMT_TPP_DESCLONG	VARCHAR (255)	NULL	Description of Trade Product Pack.
PBS_CODE	AMT_TPP_XID	VARCHAR (20)	NULL	Trade Product Pack ID.
PBS_CODE	ATC_CODE	VARCHAR (15)	NOT NULL	PBS ATC Code
PBS_CODE	AUTH_IND	CHAR (1)	NOT NULL	Authoirty Indicator
PBS_CODE	BIOEQUIV_CODE	VARCHAR (15)	NULL	Bio Equivalent Code
PBS_CODE	CAUTION_NOTE_IND	CHAR (1)	NOT NULL	Caution Note Indicator
PBS_CODE	CHECK_CURRIND	CHAR(1)	NULL	Current PBS Code Check Indicator
PBS_CODE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_CODE	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PBS_CODE	DANG_DRUG_IND	CHAR (1)	NOT NULL	Dangerous Drug Indicator
PBS_CODE	DRUG_FORM_CODE	VARCHAR (15)	NULL	Drug form Code
PBS_CODE	DRUG_FORM_DESC	VARCHAR (40)	NULL	Drug Form Description
PBS_CODE	DRUG_TYPE_CD	VARCHAR (5)	NOT NULL	PBS Drug Type Code - Link to list_of_val table
PBS_CODE	EYE_PREP_IND	CHAR (1)	NOT NULL	Eye Preparation Indicator
PBS_CODE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PBS_CODE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_CODE	LM_BUILD_IND	CHAR (1)	NOT NULL	Local Manufacture Build Indicator
PBS_CODE	MANUF_CD	VARCHAR (5)	NOT NULL	Manufacturer Code - Link to list_of_val table
PBS_CODE	PACK_CONTENT_QTY	NUMERIC (18,8)	NULL	Pack content Quantity for identified items.
PBS_CODE	PBS_BRAND_DESC	VARCHAR (45)	NULL	PBS Brand Description
PBS_CODE	PBS_CODE	VARCHAR (15)	NOT NULL	PBS Code of the Item
PBS_CODE	PBS_CODE_NOTE	VARCHAR (255)	NULL	PBS Code Note
PBS_CODE	PBS_CODE_PID	INT	NOT NULL	Pharmaceutical Benefit Scheme Code Identifier
PBS_CODE	PBS_FORMSTRENGTH_DESC	VARCHAR (150)	NOT NULL	PBS Form Strength Description
PBS_CODE	PBS_GENERIC_DESC	VARCHAR (80)	NOT NULL	PBS Generic Description
PBS_CODE	PBS_MAX_AMT_QTY	NUMERIC (18,8)	NULL	Maximum Quantity for identified items.
PBS_CODE	PBS_UOM_DESC	VARCHAR (40)	NULL	Description of UOM for identified items.

PBS_CODE	PFD_INCENT	NUMERIC(18,8)	NULL	Premium Fee Dispensing Incentives
PBS_CODE	PRES_TYPE_CD	VARCHAR (5)	NULL	Prescriber Type code - Link to list_of_val table
PBS_CODE	REG25DAYS_NBR	SMALLINT	NOT NULL	Register 25days number
PBS_CODE	REST_IND	CHAR (1)	NOT NULL	Restriction Indicator
PBS_CODE	REST_NOTE_IND	CHAR (1)	NOT NULL	Restricted Note Indicator
PBS_CODE	SN_EXCLUDE_IND	CHAR (1)	NOT NULL	Safety net exclude indicator
PBS_CODE	STREAMLINE_IND	CHAR (1)	NOT NULL	Streamline Indicator
PBS_CODE	SUPP_PBS_MAX_QTY_IND	CHAR (1)	NOT NULL	Max quantity Supplied by the PBS Supplier
PBS_CODE	WATER_DSPN_IND	CHAR (1)	NOT NULL	Water Dispensing Indicator
PBS_CUSTO M_ERROR_C ODES	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_CUSTO M_ERROR_C ODES	DSPN_PBS_ID	INT	NULL	ID for dispensed PBS item - Link to dispense_pbs table
PBS_CUSTO M_ERROR_C ODES	DSPN_PBS_MANUF_ID	INT	NULL	ID of PBS manufacturer - Link to dispense_pbs_manuf table.
PBS_CUSTO M_ERROR_C ODES	ERROR_CD	VARCHAR (5)	NOT NULL	Code for the error
PBS_CUSTO M_ERROR_C ODES	ERROR_NOTE	VARCHAR (255)	NULL	Notes for the error
PBS_CUSTO M_ERROR_C ODES	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PBS_CUSTO M_ERROR_C ODES	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_CUSTO M_ERROR_C ODES	MANUF_UPPN_XID	VARCHAR (20)	NULL	UPPN value - Link to the dispense_pbs_manuf table.
PBS_CUSTO M_ERROR_C ODES	SITE_SID	SMALLINT	NULL	Site identifier - Link to site table
PBS_ERROR _CODES	CONTACT_DTL_TEXT	TEXT	NULL	Contact detail text
PBS_ERROR _CODES	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_ERROR _CODES	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PBS_ERROR _CODES	ERROR_CD	VARCHAR (5)	NOT NULL	Code for the error

PBS_ERROR_CODES	ERROR_NOTE	VARCHAR (255)	NULL	Notes for the error
PBS_ERROR_CODES	FIX_INST_TEXT	TEXT	NULL	Instructions to fix the error
PBS_ERROR_CODES	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PBS_ERROR_CODES	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_ITEM	ANS_IND	CHAR (1)	NOT NULL	ANS Indicator
PBS_ITEM	ANS_MAX_QTY_MULT	SMALLINT	NOT NULL	Maximum Quantity for ANS
PBS_ITEM	ANS_REPEAT_NBR	SMALLINT	NOT NULL	ANS Repeat Number
PBS_ITEM	ANS_SCHED_FLAG	CHAR (1)	NULL	ANS Schedule Flag Indicator
PBS_ITEM	BPP_PRICE	NUMERIC(18,8)	NOT NULL	Brand Price Premium
PBS_ITEM	CEMP_PRICE	NUMERIC (18,8)	NULL	Commonwealth EX Manufacturers Price for identified chemo items.
PBS_ITEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_ITEM	HIC_MAX_QTY_PRICE	NUMERIC(18,8)	NOT NULL	PBS Maximum quantity price
PBS_ITEM	HIC_PRICE	NUMERIC(18,8)	NOT NULL	PBS Price
PBS_ITEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PBS_ITEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_ITEM	MANUF_MAX_QTY_PRICE	NUMERIC(18,8)	NOT NULL	Manufacture Maximum quantity Price
PBS_ITEM	MANUF_PRICE	NUMERIC(18,8)	NOT NULL	Manufacture Price
PBS_ITEM	MAX_SAFETY_NET_PRICE	NUMERIC(18,8)	NOT NULL	Maximum Safety net Price
PBS_ITEM	MEMP_PRICE	NUMERIC (18,8)	NULL	MEMP price for identified chemo items.
PBS_ITEM	PACK_SIZE_QTY	NUMERIC(18,8)	NOT NULL	Pack Size Quantity
PBS_ITEM	PBS_CODE_PID	INT	NOT NULL	PBS Code Identifier - Link to pbs_code table
PBS_ITEM	PBS_INVEN_QTY	NUMERIC (18,8)	NULL	Inventory quantity for identified Chemo items.
PBS_ITEM	PBS_ITEM_NOTE	VARCHAR (255)	NULL	PBS Item Notes
PBS_ITEM	PBS_ITEM_PID	INT	NOT NULL	Unique PBS Item Identifier
PBS_ITEM	PBS_MAX_QTY	NUMERIC(18,8)	NOT NULL	PBS maximum Quantity
PBS_ITEM	PBS_REPEAT_NBR	SMALLINT	NOT NULL	PBS Repeat Number

PBS_ITEM	PUOMP_PRICE	NUMERIC (18,8)	NULL	price of the UOM for identified Chemo items.
PBS_ITEM	SPC_PRICE	NUMERIC(18,8)	NOT NULL	Special Patient Contribution
PBS_ITEM	START_DT	DATETIME	NOT NULL	Start date
PBS_ITEM	STOP_DT	DATETIME	NOT NULL	Stop date
PBS_ITEM	TGM_MAX_QTY_PRICE	NUMERIC(18,8)	NOT NULL	TGM Maximum Quantity Price
PBS_ITEM	TGM_PRICE	NUMERIC(18,8)	NOT NULL	TFM Price
PBS_ITEM	TGP_PRICE	NUMERIC(18,8)	NOT NULL	Therapeutic Group Premium
PBS_LINK	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_LINK	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PBS_LINK	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_LINK	PBS_CODE_PID	INT	NOT NULL	PBS Code Identifier - Link to pbs_code table
PBS_LINK	PBS_LINK_NOTE	VARCHAR (255)	NULL	PBS Link Notes
PBS_LINK	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
PBS_LINK	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
PBS_PAYM ENT_STATEM ENT	ADJUSTED_PRICE	NUMERIC(18,8)	NULL	Adjusted price from MCA
PBS_PAYM ENT_STATEM ENT	BRAND	VARCHAR (15)	NULL	Brand name
PBS_PAYM ENT_STATEM ENT	CLAIM_PERIOD	VARCHAR (5)	NOT NULL	PBS Claim period
PBS_PAYM ENT_STATEM ENT	CLAIM_PRICE	NUMERIC(18,8)	NULL	Claim price for the dispense
PBS_PAYM ENT_STATEM ENT	CLAIM_REFERENCE	INT	NOT NULL	Claim reference number
PBS_PAYM ENT_STATEM ENT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_PAYM ENT_STATEM ENT	CTG_CODE	VARCHAR (15)	NULL	CTG code
PBS_PAYM ENT_STATEM ENT	DISPEN_INCENT_ADJ	NUMERIC(18,8)	NULL	Dispense incentive adjust

PBS_PAYM ENT_STATEM ENT	DISPEN_INCENT_AMT	NUMERIC(18,8)	NULL	Dispense incentive amount
PBS_PAYM ENT_STATEM ENT	DSPN_ID	INT	NOT NULL	ID to link to the dispense table
PBS_PAYM ENT_STATEM ENT	DSPN_PBS_ID	INT	NULL	Unique ID used to identify dispensed PBS item
PBS_PAYM ENT_STATEM ENT	DSPN_PBS_MANUF_ID	INT	NULL	ID to link with dispense_pbs_manuf table
PBS_PAYM ENT_STATEM ENT	ELECT_PRESC_FEE_AMT	NUMERIC(18,8)	NULL	Electronic prescription fee amount
PBS_PAYM ENT_STATEM ENT	ELECT_PRESC_FEE_AMT_ADJ	NUMERIC(18,8)	NULL	Electronic Prescription Fee Amount Adjustment
PBS_PAYM ENT_STATEM ENT	FAMILY_NAME	VARCHAR (255)	NULL	Person's Family Name
PBS_PAYM ENT_STATEM ENT	GIVEN_NAME	VARCHAR (255)	NULL	Person's given name
PBS_PAYM ENT_STATEM ENT	GLOBAL_SALES_TAX	NUMERIC(18,8)	NULL	Global sales tax
PBS_PAYM ENT_STATEM ENT	HIC_REF_NBR	VARCHAR (15)	NOT NULL	Health Insurance Price reference number
PBS_PAYM ENT_STATEM ENT	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	The User who last modified this record
PBS_PAYM ENT_STATEM ENT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_PAYM ENT_STATEM ENT	MANUF_UPPN_XID	VARCHAR (20)	NULL	UPPN value - Link to dispense_pbs_manuf table.
PBS_PAYM ENT_STATEM ENT	ONLINE_INCENT_ADJ	NUMERIC(18,8)	NULL	Online incentive adjust
PBS_PAYM ENT_STATEM ENT	ONLINE_INCENT_AMT	NUMERIC(18,8)	NULL	Online incentive amount
PBS_PAYM ENT_STATEM ENT	PAYMENT_CATEGORY	VARCHAR (5)	NULL	Ppayment category for the dispense
PBS_PAYM ENT_STATEM ENT	PAYMENT_DT	DATETIME	NULL	Payment Date

PBS_PAYM ENT_STATEM ENT	PBS_CLAIM_ID	INT	NOT NULL	ID of PBS claim - Link to pbs_claim table
PBS_PAYM ENT_STATEM ENT	PBS_CODE	VARCHAR (15)	NULL	PBS Code of the Item
PBS_PAYM ENT_STATEM ENT	PBS_PAYMENT_NBR	VARCHAR (15)	NULL	Payment id (unique id) for the payment
PBS_PAYM ENT_STATEM ENT	PBS_REF_NBR	VARCHAR (15)	NULL	PBS Reference number of the script
PBS_PAYM ENT_STATEM ENT	PBS_STMNT_ID	INT	NOT NULL	PBS statement ID
PBS_PAYM ENT_STATEM ENT	PRESCRIPTION_FORMAT	VARCHAR(2)	NULL	Prescription Format ('E' electronic or 'P' paper)
PBS_PAYM ENT_STATEM ENT	RBA_NBR	VARCHAR (15)	NULL	Reserve Bank account number
PBS_PAYM ENT_STATEM ENT	SCRIPT_CLAIM_PERIOD_NBR	VARCHAR (15)	NULL	Script claim period number
PBS_PAYM ENT_STATEM ENT	SERIAL_NUMBER	VARCHAR (15)	NULL	Serial of the script
PBS_PAYM ENT_STATEM ENT	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
PBS_PAYM ENT_STATEM ENT	UCP_IND	CHAR (1)	NOT NULL	UCP indicator
PBS_RECON CILIATION	CLAIM_PERIOD	VARCHAR (5)	NOT NULL	Stores the period of the claim
PBS_RECON CILIATION	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_RECON CILIATION	DSPN_ID	INT	NULL	ID to link to the dispense table
PBS_RECON CILIATION	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PBS_RECON CILIATION	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_RECON CILIATION	PBS_CLAIM_ID	INT	NOT NULL	Identification key for PBS claims of pharmacy

PBS_RECONCILIATION	PHARMAPPROVALNUMBER	VARCHAR (15)	NOT NULL	Stores the pharmacy approval number
PBS_RECONCILIATION	SITE_SID	SMALLINT	NULL	Site identifier - Link to site table
PBS_RECONCILIATION	TOTCONBENEFITPRESCRIPTIONS	NUMERIC(18,8)	NULL	Stores the total concessions benefit for the prescription
PBS_RECONCILIATION	TOTCONBENEFITREBATE	NUMERIC(18,8)	NULL	Stores the total concessions benefit rebate for the prescription
PBS_RECONCILIATION	TOTDISPENINCENTPRESCRIPTIONS	NUMERIC(18,8)	NULL	Stores the total number of the dispense incentive prescriptions
PBS_RECONCILIATION	TOTDISPENINCENTREBATE	NUMERIC(18,8)	NULL	Stores the total number of the dispense incentive rebate prescription
PBS_RECONCILIATION	TOTDOCTBAGBENEFITPRESCRIPTIONS	NUMERIC(18,8)	NULL	Stores the total doctor concessions benefit for the prescription
PBS_RECONCILIATION	TOTDOCTBAGBENEFITREBATE	NUMERIC(18,8)	NULL	Stores the total doctor rebate benefit for the prescription
PBS_RECONCILIATION	TOTENTBENEFITPRESCRIPTIONS	NUMERIC(18,8)	NULL	Stores the total Entitlement benefit for the prescription
PBS_RECONCILIATION	TOTENTBENEFITREBATE	NUMERIC(18,8)	NULL	Stores the total Entitlement rebate benefit for the prescription
PBS_RECONCILIATION	TOTGENBENEFITREBATE	NUMERIC(18,8)	NULL	Stores the total number of the general prescription
PBS_RECONCILIATION	TOTGENPRESCRIPTIONS	NUMERIC(18,8)	NULL	Stores the total number of the general rebate prescription
PBS_RECONCILIATION	TOTNUMPRESCRIPTIONS	NUMERIC(18,8)	NULL	Stores the total number of the prescriptions
PBS_RECONCILIATION	TOTONLINEINCENTEREBATE	NUMERIC(18,8)	NULL	Stores the total number of the online incentive rebate prescription
PBS_RECONCILIATION	TOTONLINEINCENTPRESCRIPTIONS	NUMERIC(18,8)	NULL	Stores the total number of the online incentive prescriptions
PBS_RECONCILIATION	TOTREBATES	NUMERIC(18,8)	NULL	Stores the total rebates
PBS_RECONCILIATION	TOTREPATBENEFITPRESCRIPTIONS	NUMERIC(18,8)	NULL	Stores the total repat benefit for the prescriptions

PBS_RECONCILIATION	TOTREPATBENEFITREBATE	NUMERIC(18,8)	NULL	Stores the total repat benefit
PBS_RECONCILIATION	TOTALELECTRONICPRESCRIPTIONS	INT	NULL	Stores the total number of electronic prescriptions
PBS_RECONCILIATION	TOTALELECTRONICPRESCRIPTIONFEEREbate	NUMERIC(18,8)	NULL	Stores the total number of the electronic rebate prescription
PBS_RESTRICTION	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_RESTRICTION	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PBS_RESTRICTION	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_RESTRICTION	PBS_ANS_DT_REQ_IND	CHAR (1)	NOT NULL	PBS ANS Date Required Indicator
PBS_RESTRICTION	PBS_ANS_REST_FLAG	CHAR (1)	NOT NULL	PBS ANS Reset Flag
PBS_RESTRICTION	PBS_ANS_TEXT_REQ_IND	CHAR (1)	NOT NULL	PBS ANS Text Required Indicator
PBS_RESTRICTION	PBS_REST_CODE	VARCHAR (15)	NOT NULL	PBS Restriction Code
PBS_RESTRICTION	PBS_REST_PID	INT	NOT NULL	PBS Drug Restriction Identifier
PBS_RESTRICTION_LINK	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PBS_RESTRICTION_LINK	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PBS_RESTRICTION_LINK	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PBS_RESTRICTION_LINK	PBS_CODE	VARCHAR (15)	NOT NULL	PBS Code of the Item
PBS_RESTRICTION_LINK	PBS_REST_LINK_FLAG	CHAR (1)	NOT NULL	PBS Reset Link Flag Indicator
PBS_RESTRICTION_LINK	PBS_REST_LINK_PID	INT	NOT NULL	PBS Drug Restriction Link
PBS_RESTRICTION_LINK	PBS_REST_PID	INT	NOT NULL	PBS Drug Restriction Identifier
PBS_RESTRICTION_LINK	START_DT	DATETIME	NULL	start date
PBS_RESTRICTION_LINK	STOP_DT	DATETIME	NULL	Stop date

PBS_RESTRICTION_NOTE	PBS_REST_NOTE	VARCHAR (255)	NULL	PBS Restriction Notes
PBS_RESTRICTION_NOTE	PBS_REST_NOTE_PID	INT	NOT NULL	PBS Drug Restriction Note Id
PBS_RESTRICTION_NOTE	PBS_REST_NOTE_SEQ	INT	NOT NULL	PBS Reset Note
PBS_RESTRICTION_NOTE	PBS_REST_PID	INT	NOT NULL	PBS Drug Restriction Identifier
PBS_WASTAGE_FACTOR	CHRG_PCT	DECIMAL(8,6)	NOT NULL	Charge Percentage
PBS_WASTAGE_FACTOR	SUPP_PCT	DECIMAL(8,6)	NOT NULL	Supply Percentage as part of PBS wastage Factor
PHARMACY	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PHARMACY	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PHARMACY	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PHARMACY	LAST_UPDATED_DT	DATETIME	NOT NULL	The date when this record was last modified
PHARMACY	PES_ENTITY_XID	VARCHAR (20)	NULL	Prescription Exchange Service ID's
PHARMACY	PHARM_ADDR_1	VARCHAR(40)	NULL	pharmacy address 1
PHARMACY	PHARM_ADDR_2	VARCHAR(40)	NULL	pharmacy address 2
PHARMACY	PHARM_ADDR_3	VARCHAR(40)	NULL	pharmacy address 3
PHARMACY	PHARM_ADDR_4	VARCHAR(40)	NULL	pharmacy address 4
PHARMACY	PHARM_CNTRY	VARCHAR(30)	NULL	pharmacy country
PHARMACY	PHARM_DESC	VARCHAR (40)	NOT NULL	PharmacyDescription
PHARMACY	PHARM_FAX_PHONE	VARCHAR(15)	NULL	pharmacy fax phone number
PHARMACY	PHARM_NOTE	VARCHAR (255)	NULL	Pharmacy Note
PHARMACY	PHARM_PHONE	VARCHAR(15)	NULL	pharmacy phone number
PHARMACY	PHARM_POSTCODE	VARCHAR(10)	NULL	pharmacy postal code
PHARMACY	PHARM_XID	VARCHAR (20)	NOT NULL	Unique code for Pharmacy, for the site

PHARMACY	PREP_DT_IND	CHAR(1)	NOT NULL	Indicator to display Preparation Date of a manufactured item in the Current Prescription Area and Dispensing History Areas
PHARMACY	SAME_ASEPTIC	VARCHAR(5)	NOT NULL	Enable/Disable 'Same' button for ASEPTIC Dispensing. This will default from the setting in the site table
PHARMACY	SAME_CYTOTOXIC	VARCHAR(5)	NOT NULL	Enable/Disable 'Same' button for CYTOTOXIC Dispensing. This will default from the setting in the site table
PHARMACY	SAME_EXTEMP	VARCHAR(5)	NOT NULL	Enable/Disable 'Same' button for EXTEMP Dispensing. This will default from the setting in the site table
PHARMACY	SAME_NORMAL	VARCHAR(5)	NOT NULL	Enable/Disable 'Same' button for NORMAL Dispensing. This will default from the setting in the site table
PHARMACY	SAME_TPN	VARCHAR(5)	NOT NULL	Enable/Disable 'Same' button for TPN Dispensing. This will default from the setting in the site table
PHARMACY	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
PROD_FORM	AMT_FORM_ID	BIGINT	NULL	AMT Form ID
PROD_FORM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_FORM	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PROD_FORM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROD_FORM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_FORM	PLURAL_DIR_UOM	VARCHAR(40)	NOT NULL	Pural form for Dispensing Directions
PROD_FORM	PLURAL_FORM	VARCHAR (20)	NOT NULL	Plural Form used in product description
PROD_FORM	PROD_FORM_NOTE	VARCHAR (255)	NULL	Product form Note
PROD_FORM	PROD_FORM_XID	VARCHAR (20)	NOT NULL	Unique code for Product form
PROD_FORM	SINGULAR_DIR_UOM	VARCHAR(40)	NOT NULL	Singular form for Dispensing Directions

PROD_FORM	SINGULAR_FORM	VARCHAR (20)	NOT NULL	Singular Form used in product description
PROD_FORM	VERB	VARCHAR (20)	NOT NULL	Verb relating to a Product
PROD_MIMS_GENERIC	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_MIMS_GENERIC	GENERIC_CODE	BIGINT	NOT NULL	MIMS generic code - linke to MIMS_GENERIC
PROD_MIMS_GENERIC	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
PROD_MIMS_GENERIC	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_MIMS_GENERIC	PROD_ID	INT	NOT NULL	Product Identifier - Link to PRODUCT
PROD_PROP	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_PROP	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROD_PROP	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_PROP	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
PROD_PROP	PROP_ID	INT	NOT NULL	Property Identifier - Link to property table
PROD_PROP	PROP_UNIT_QTY	NUMERIC(18,10)	NULL	Property quantity
PROD_PROP	UNIT_CATG_XID	VARCHAR (20)	NOT NULL	Unit Category identifier - Link to unit table
PROD_PROP	UNIT_PID	INT	NULL	Unit identifier - Link to unit table
PROD_RESOURCE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_RESOURCE	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PROD_RESOURCE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROD_RESOURCE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_RESOURCE	MAX_MASS_GM	NUMERIC(6,2)	NULL	Maximum Weight quantity
PROD_RESOURCE	MAX_VOL_ML	NUMERIC(18,8)	NULL	Maximum Volume quantity
PROD_RESOURCE	OVERAGE_QTY	NUMERIC(18,8)	NULL	Overage quantity
PROD_RESOURCE	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
PROD_RESOURCE	RES_PHASETYPE_CD	VARCHAR (5)	NOT NULL	Phase detail - Link to list_of_val table
PROD_RESOURCE	RESOURCE_ID	INT	NOT NULL	Resource identifier - Link to resource table
PROD_RESOURCE	WASTAGE_QTY	NUMERIC(18,8)	NULL	Wastage quantity

PROD_ROUTE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_ROUTE	DFLT_IND	CHAR (1)	NOT NULL	Default indicator
PROD_ROUTE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROD_ROUTE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_ROUTE	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
PROD_ROUTE	ROUTE_ID	INT	NOT NULL	Unique Route identifier
PROD_SCHEDULE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_SCHEDULE	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current.
PROD_SCHEDULE	DISP_TAX	CHAR(1)	NOTNULL	Indicates that GST applies
PROD_SCHEDULE	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
PROD_SCHEDULE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_SCHEDULE	PRES_VALID_MTH	SMALLINT	NULL	Prescription valid months
PROD_SCHEDULE	RPT_INT	CHAR(1)	NOTNULL	Indicates that a repeat interval will be required in the Prescription Details window
PROD_SCHEDULE	RTPM_MONITOR_IND	CHAR (1)	NOT NULL	Indicates RTPM monitored against schedule
PROD_SCHEDULE	SCHEDULE_DESC	VARCHAR(40)	NOT NULL	Schedule description
PROD_SCHEDULE	SCHEDULE_NOTE	VARCHAR(255)	NULL	Schedule note
PROD_SCHEDULE	SCHEDULE_SHORT	VARCHAR(10)	NOT NULL	Unique Schedule Short Code
PROD_SITE	ADC_PROD_IND	CHAR(1)	NOT NULL	indicates ADC product
PROD_SITE	ALLOW_NEG_BAL_IND	INT	NOT NULL	Controls the ability for stock levels to go negative at the site level.
PROD_SITE	CONTROL_DRUG_IND	CHAR (1)	NOT NULL	Controlled Drug Indicator
PROD_SITE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_SITE	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PROD_SITE	FORMULARY_IND	CHAR (1)	NOT NULL	Formulary Indicator
PROD_SITE	INVEN_IND	CHAR (1)	NOT NULL	If set to N, the bin quantity will not be adjusted for transactions.

PROD_SITE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROD_SITE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_SITE	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
PROD_SITE	PROD_QID	VARCHAR(10)	NULL	Quick code
PROD_SITE	PROD_SHORT_CODE	VARCHAR(10)	NULL	Short code
PROD_SITE	ROBOT_GTIN_ID	INT	NULL	Allow a different Pack GTIN to be specified for a Site when compared to the global default
PROD_SITE	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
PROD_SITE	SITE_STORE_NOTE	VARCHAR(1024)	NULL	store notes in site
PROD_SITE	SPEC_PROD_CD	VARCHAR (5)	NULL	Special Product Code
PROD_SITE	STD_MANUF_LBL	VARCHAR (255)	NULL	Standard Manufacture Label text
PROD_SITE	STRTRF_SHIPPER_QTY	NUMERIC (18,8)	NOT NULL	Store Transfer Shipper Quantity used in Suggested Store Transfer
PROD_SUBS TITUTE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_SUBS TITUTE	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current..
PROD_SUBS TITUTE	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
PROD_SUBS TITUTE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_SUBS TITUTE	MESSAGE	VARCHAR(255)	NOT NULL	Substitution message.
PROD_SUBS TITUTE	PROD_ID	INT	NOT NULL	Original prod_id - Link to product table
PROD_SUBS TITUTE	SEQ_NUMBER	INT	NULL	Substitution sequence number
PROD_SUBS TITUTE	SITE_SID	SMALLINT	NOT NULL	Unique ID used to idenfiy site
PROD_SUBS TITUTE	SUBST_COMM_DATE	DATETIME	NOT NULL	Substitution date
PROD_SUBS TITUTE	SUBST_ID	INT	NOT NULL	Unqie Substitution ID, for the site
PROD_SUBS TITUTE	SUBST_PROD_ID	INT	NULL	Substituted prod_id - Link to product table
PROD_SUPP _PREF	CONTRACT_IND	CHAR (1)	NOT NULL	Contract Indicator
PROD_SUPP _PREF	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_SUPP _PREF	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROD_SUPP _PREF	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.

PROD_SUPP_PREF	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
PROD_SUPP_PREF	PROD_SUPP_PREF_SEQ	INT	NOT NULL	Preferred Supplier Sequence
PROD_SUPP_PREF	PSI_SITE_SID	SMALLINT	NULL	Preffered supplier site ID - Link to site table
PROD_SUPP_PREF	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
PROD_SUPP_PREF	SUPP_XID	VARCHAR (20)	NOT NULL	Code used to link to the Supplier record
PROD_UOM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_UOM	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PROD_UOM	INVERSE_UOM_QTY	NUMERIC(18,10)	NOT NULL	Inverse of UOM Qty
PROD_UOM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROD_UOM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_UOM	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
PROD_UOM	PROD_UOM_APN	VARCHAR (13)	NULL	EAN Code
PROD_UOM	SUB_PACK_IND	CHAR (1)	NOT NULL	Subpack Indicator
PROD_UOM	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
PROD_UOM	UOM_QTY	NUMERIC(18,10)	NOT NULL	UOM Quantity
PROD_WAR_N_CODE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROD_WAR_N_CODE	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PROD_WAR_N_CODE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROD_WAR_N_CODE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROD_WAR_N_CODE	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
PROD_WAR_N_CODE	WARN_CODE_XID	VARCHAR (20)	NOT NULL	Warning Code text
PRODUCT	AMB_PUMP_IND	CHAR(1)	NOT NULL	Ambulatory Pump Indicator
PRODUCT	AMT_MAP_AUTH_IND	CHAR(1)	NOT NULL	AMT Map Authorised Indicator
PRODUCT	AMT_MAP_EXCL_IND	CHAR(1)	NOT NULL	AMT Exclude Indicator
PRODUCT	AMT_MAP_STAT_CD	VARCHAR (5)	NULL	AMT Map Status code
PRODUCT	ASEP_AUTHORISED_BY	VARCHAR (30)	NULL	Code of the User who authorised Aseptic changes

PRODUCT	ASEP_AUTHORIZED_DT	DATETIME	NULL	Aseptic changes authorised by
PRODUCT	BRAND_DESC	VARCHAR (40)	NULL	Brand description
PRODUCT	BRAND_DESC_UC	VARCHAR (40)	NULL	Brand description , in upper case
PRODUCT	CMI_XID	VARCHAR (20)	NULL	CMI Identifier
PRODUCT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PRODUCT	CRIT_STOCK_IND	CHAR (1)	NOT NULL	Critical Stock Indicator
PRODUCT	CTPP_XID	VARCHAR(20)	NULL	CTPP code for the AUS locale.
PRODUCT	CYTO_IND	CHAR (1)	NOT NULL	Cytotoxic indicator
PRODUCT	DISCONT_INVALID_PROD_IND	CHAR(1)	NOT NULL	Discontinues invalid product indicator
PRODUCT	DISPLAY_DAV_IND	CHAR (1)	NOT NULL	Display Availability Notes indicator
PRODUCT	DRG_PHASETYPE_CD	VARCHAR (5)	NOT NULL	Drug Phase type - Link to list_of_val table
PRODUCT	DRUG_CODE_ID	INT	NOT NULL	Drug code ID - Link to drug_code table
PRODUCT	DRUG_UTIL_IND	CHAR (1)	NOT NULL	Drug Utility Indicator
PRODUCT	DSPN_MANUF_UOM_ID	INT	NULL	Unit of measurement Identifier for manufactured item- Link to UOM table
PRODUCT	FDB_DMD_SID	SMALLINT	NULL	FDB dm+d type identifier
PRODUCT	FDB_DMD_XID	VARCHAR (20)	NULL	FDB dm+d code identifier
PRODUCT	FDB_PROD_ID	INT	NULL	FDB product identifier
PRODUCT	FORMULARY_CODE	VARCHAR (10)	NULL	Formulary code
PRODUCT	FRED_CODE	VARCHAR (15)	NULL	FRED Code
PRODUCT	FRIDGE_IND	CHAR (1)	NOT NULL	Refridgerate indicator
PRODUCT	GENERIC_DESC	VARCHAR (255)	NOT NULL	Generic description
PRODUCT	GENERIC_DESC_UC	VARCHAR (40)	NOT NULL	Generic Description in upper case
PRODUCT	INGR_AUTHORIZED_BY	VARCHAR (30)	NULL	Code of the User who authorised Ingredient changes
PRODUCT	INGR_AUTHORIZED_DT	DATETIME	NULL	Ingredient changes authorised date
PRODUCT	INVC_CODE	VARCHAR (10)	NULL	Invoice code
PRODUCT	INVEN_UOM_ID	INT	NOT NULL	Inventory UOM ID - Link to UOM table
PRODUCT	ITEM_NBR	VARCHAR(15)	NULL	Ambulatory Pump Item number
PRODUCT	IV_ADDITIVE_IND	CHAR (1)	NOT NULL	IV Additive Indicator
PRODUCT	IV_DILUENT_IND	CHAR (1)	NOT NULL	IV Diluent Indicator

PRODUCT	IV_FLUID_IND	CHAR (1)	NOT NULL	IV Fluid Indicator
PRODUCT	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PRODUCT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PRODUCT	LEAFLET_AVAIL_IND	CHAR (1)	NOT NULL	Leaflet available Indicator - no longer used.
PRODUCT	MANUF_AUTHORISED_BY	VARCHAR (30)	NULL	Code of the User who authorised Manufacturing changes
PRODUCT	MANUF_AUTHORISED_DT	DATETIME	NULL	Manufacturing changes authorised date
PRODUCT	MANUF_XID	VARCHAR (20)	NULL	Manufacturer code - Link to manufactuer table
PRODUCT	MAX_TEMP_ID	INT	NOT NULL	Maximum Temperature
PRODUCT	MEASURE_TYPE_CD	VARCHAR (5)	NULL	Measure Type Code - Link to list_of_val table
PRODUCT	METHNOTE_AUTHORISED_BY	VARCHAR (30)	NULL	Code of the User who authorised Method note changes
PRODUCT	METHNOTE_AUTHORISED_DT	DATETIME	NULL	Method note changes authorised date
PRODUCT	MIMS_MANUAL_MAP_IND	CHAR(1)	NOT NULL	Manual MIMS mapped product
PRODUCT	MIN_TEMP_ID	INT	NOT NULL	Minimum Temperature
PRODUCT	MPP_ID	BIGINT	NULL	AMT Medicinal Product Pack identifier, referenced for Order Worksheet preferred brand functionality.
PRODUCT	MIMS_ROUTE_CD	BIGINT	NULL	Column to save mims route code
PRODUCT	MIMS_ROUTE_ID	BIGINT	NULL	Column to save mims route id
PRODUCT	MIMS_GENERIC_EXCLUDE_IND	CHAR (1)	NULL	Column to save mims generic exclude indicator
PRODUCT	NAT_PROD_CD	VARCHAR (15)	NULL	National product code
PRODUCT	PACK_DESC	VARCHAR (40)	NOT NULL	Pack Description
PRODUCT	PACK_UOM_ID	INT	NOT NULL	Pack UOM ID - Link to UOM table
PRODUCT	PFL_IND	CHAR (1)	NOT NULL	Protect from Light indicator
PRODUCT	POS_IND	CHAR (1)	NOT NULL	Point of Sale Indicator
PRODUCT	PROD_FORM_XID	VARCHAR (20)	NOT NULL	Product form code - Link to prod_form table
PRODUCT	PROD_GRP_CODE	VARCHAR (10)	NULL	User defined product group code

PRODUCT	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
PRODUCT	PROD_LBL	VARCHAR (255)	NULL	Text for product label
PRODUCT	PROD_QID	VARCHAR (10)	NULL	Quick code
PRODUCT	PROD_SCHED_SHORT	VARCHAR(10)	NULL	Product schedule code (previoulsy named as forensic_code).
PRODUCT	PROD_SHORT_CODE	VARCHAR (10)	NULL	Product Short Code
PRODUCT	PROD_STORE_NOTE	VARCHAR (1024)	NULL	Product Store Note
PRODUCT	PROD_TYPE_CD	VARCHAR (5)	NOT NULL	Product type code - Link to list_of_val table
PRODUCT	PROD_VERB	VARCHAR (20)	NULL	Product verb
PRODUCT	RESOURCE_IND	CHAR (1)	NOT NULL	Resource indicator
PRODUCT	RTPM_MONITOR_IND	CHAR (1)	NOT NULL	Indicates RTPM monitored against product
PRODUCT	SALES_TAX_XID	VARCHAR (20)	NOT NULL	Sales Tax Code
PRODUCT	SHELF_LIFE_HRS	INT	NULL	Shelf Life in Hrs
PRODUCT	STD_IV_IND	CHAR (1)	NOT NULL	Standard IV Drug Indicator
PRODUCT	STD_IV_QTY	NUMERIC(18,8)	NULL	Formula quantity for Aseptic products
PRODUCT	STD_IV_UOM_ID	INT	NULL	Formula UOM ID for Aseptic products
PRODUCT	STD_MANUF_BATCH_QTY	NUMERIC(18,8)	NULL	Standard manufacture batch quantity
PRODUCT	STD_MANUF_IND	CHAR (1)	NOT NULL	Standard Manufacture Indicator
PRODUCT	STD_MANUF_LFE_DAYS	SMALLINT	NULL	Standard Manufacture Life Days
PRODUCT	STD_MANUF_QTY	NUMERIC(18,8)	NULL	Standard Manufacture quantity
PRODUCT	STD_MANUF_UOM_ID	INT	NULL	Standard Manufacture UOM identifier - Link to UOM table
PRODUCT	STD_TPN_IND	CHAR (1)	NOT NULL	Standard TPN Indicator
PRODUCT	STD_TPN_QTY	NUMERIC(18,8)	NULL	Formula quantity for TPN products
PRODUCT	STD_TPN_UOM_ID	INT	NULL	Formula UOM ID for TPNproducts
PRODUCT	STRENGTH	VARCHAR (255)	NULL	Strength
PRODUCT	TPN_AUTHORISED_BY	VARCHAR (30)	NULL	Code of the User who authorised TPN changes
PRODUCT	TPN_AUTHORISED_DT	DATETIME	NULL	TPN changes authorised date
PRODUCT	TPN_IND	CHAR (1)	NOT NULL	TPN Indicator
PRODUCT	TPP_AMPP_XID	VARCHAR (20)	NULL	TPP for the AUS locale, AMPP for UK locale

PRODUCT	WATER_ML	NUMERIC(18,8)	NULL	Water Ingredients in ml
PROFILE	APPLICATION_CD	VARCHAR (15)	NOT NULL	Name of the application - always includes 'STOCCA'
PROFILE	CREATED_BY	VARCHAR (30)	NULL	Code of the user who created the record
PROFILE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROFILE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	The User who last modified this record
PROFILE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROFILE	PROFILE_CD	VARCHAR (15)	NOT NULL	Unqiue Profile code
PROFILE	PROFILE_DSC	VARCHAR (30)	NOT NULL	Profile Description
PROFILE_ACCESS	AMEND_FL	CHAR (1)	NOT NULL	Amendment indicator
PROFILE_ACCESS	APP_FUNCTION_CD	VARCHAR (30)	NOT NULL	Gives the name of the object for the application
PROFILE_ACCESS	APPLICATION_CD	VARCHAR (15)	NOT NULL	Name of the application - always includes 'STOCCA'
PROFILE_ACCESS	CREATE_FL	CHAR (1)	NOT NULL	Creation indicator
PROFILE_ACCESS	CREATED_BY	VARCHAR (30)	NULL	Code of the user who created the record.
PROFILE_ACCESS	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROFILE_ACCESS	DELETE_FL	CHAR (1)	NOT NULL	Deletion indicator
PROFILE_ACCESS	ENQUIRE_FL	CHAR (1)	NOT NULL	Enquiry Indicator
PROFILE_ACCESS	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROFILE_ACCESS	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROFILE_ACCESS	PROFILE_CD	VARCHAR (15)	NOT NULL	Profile Type - Link to profile table
PROFILE_RPT_ACCESS	APPLICATION_CD	VARCHAR (15)	NOT NULL	Name of the application - always includes 'STOCCA'
PROFILE_RPT_ACCESS	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROFILE_RPT_ACCESS	ENQUIRE_FLG	CHAR (1)	NOT NULL	Enquire flag
PROFILE_RPT_ACCESS	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROFILE_RPT_ACCESS	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.

PROFILE_RPT_ACCESS	PROFILE_CD	VARCHAR (15)	NOT NULL	Profile Type - Link to profile table
PROFILE_RPT_ACCESS	RPT_SID	SMALLINT	NOT NULL	Report identifier - Link to crystal_report table
PROP_ATTR	ATTR_ID	INT	NOT NULL	Attribute identifier - Link to attribute table
PROP_ATTR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROP_ATTR	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PROP_ATTR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROP_ATTR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROP_ATTR	PAT_ATTR_L	NUMERIC	NULL	Patient attribute lower
PROP_ATTR	PAT_ATTR_U	NUMERIC	NULL	Patient attribute upper
PROP_ATTR	PROP_ATTR_ID	INT	NOT NULL	Unique Property attribute Identifier
PROP_ATTR	PROP_DOSE_ID	INT	NOT NULL	Property Dose Range Identifier - Link to prop_dose table
PROP_ATTR	UNIT_PID	INT	NULL	Unit identifier - Link to unit table
PROP_ATTR	UNIT_QLF_PID	INT	NULL	Unit qualifier identifier - Link to unit table
PROP_ATTR	USER_DEFINED_IND	CHAR (1)	NULL	User Defined Indicator
PROP_DOSE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROP_DOSE	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current.
PROP_DOSE	DOSE_UNIT_PID	INT	NOT NULL	Dose Range unit identifier - Link to unit table
PROP_DOSE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROP_DOSE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROP_DOSE	LEVEL_XID	VARCHAR (20)	NULL	Level xid - link to list_of_val table
PROP_DOSE	PROP_DOSE_ID	INT	NOT NULL	Unique property dose Range identifier
PROP_DOSE	PROP_ID	INT	NOT NULL	Property Identifier - Link to property table
PROP_DOSE	RANGE_L	NUMERIC	NULL	Range lower
PROP_DOSE	RANGE_U	NUMERIC	NULL	Range upper
PROP_DOSE	TOLERANCE_PCT	DECIMAL(8,6)	NULL	Tolerance Percentage

PROP_DOSE	UNIT_QLF_PID	INT	NOT NULL	Unit qualifier identifier - Link to unit table
PROP_UNIT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROP_UNIT	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PROP_UNIT	DEF_CATG_IND	CHAR (1)	NOT NULL	Default category Indicator
PROP_UNIT	DEF_UNIT_PID	INT	NULL	Default unit identifier
PROP_UNIT	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROP_UNIT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROP_UNIT	PROP_ID	INT	NOT NULL	Property Identifier - Link to property table
PROP_UNIT	UNIT_CATG_XID	VARCHAR(20)	NOT NULL	Unit Category identifier - Link to unit table
PROPERTY	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PROPERTY	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
PROPERTY	DRUG_CODE_ID	INT	NULL	Drug code identifier - Link to drug_code table
PROPERTY	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PROPERTY	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PROPERTY	PROP_DESC	VARCHAR(40)	NOT NULL	Property description
PROPERTY	PROP_ID	INT	NOT NULL	Property Identifier - Link to property table
PROPERTY	PROP_NOTE	VARCHAR (255)	NULL	Property notes
PROPERTY	PROP_TYPE_CD	VARCHAR(5)	NOT NULL	Property type - Link to list_of_val table
PROPERTY	PROP_XID	VARCHAR(20)	NOT NULL	Property Xid
GOODS_RECEIPT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
GOODS_RECEIPT	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current.
GOODS_RECEIPT	GR_AP_EXTRACT	INT	NULL	Goods Receipt extract
GOODS_RECEIPT	GR_AUTH_BY	VARCHAR(30)	NULL	Code of the user who authorise the supplier invoice
GOODS_RECEIPT	GR_DELIV_REF	VARCHAR (20)	NULL	Goods Receipt Delivery Reference No.
GOODS_RECEIPT	GR_DESP_NBR	VARCHAR(15)	NULL	Despatch number for the goods receipt
GOODS_RECEIPT	GR_DIR_CD	VARCHAR (5)	NOT NULL	Goods Receipt Direction Code

GOODS_RECEIPT	GR_DT	DATETIME	NOT NULL	Goods Receipt Date
GOODS_RECEIPT	GR_EXT_FREIGHT_COST	NUMERIC(18,8)	NULL	Goods Receipt freight cost with Tax
GOODS_RECEIPT	GR_FREIGHT_COST	NUMERIC(18,8)	NULL	Goods Receipt Freight cost
GOODS_RECEIPT	GR_FREIGHT_TAX_AMT	NUMERIC(18,8)	NULL	Goods Receipt Tax Amount
GOODS_RECEIPT	GR_ID	INT	NOT NULL	Unique ID of Goods Receipt, for the site
GOODS_RECEIPT	GR_INVC_REF	VARCHAR (20)	NULL	Goods Receipt Invoice Reference
GOODS_RECEIPT	GR_INVC_TAX_AMT	NUMERIC(18,8)	NULL	Goods Receipt Tax amount
GOODS_RECEIPT	GR_INVC_TOT_COST	NUMERIC(18,8)	NULL	Goods Receipt / Invoice Total Cost
GOODS_RECEIPT	GR_INVC_TOT_EXT_COST	NUMERIC(18,8)	NULL	Goods Receipt / Invoice Total Cost with Tax
GOODS_RECEIPT	GR_NOTE	VARCHAR (255)	NULL	Goods Receipt Note
GOODS_RECEIPT	GR_ROB_IND	CHAR(1)	NOT NULL	Column to save the robot indicator
GOODS_RECEIPT	GR_STAT_CD	VARCHAR (5)	NOT NULL	Goods Receipt Status Code
GOODS_RECEIPT	GR_TYPE_CD	VARCHAR (5)	NOT NULL	Types of Goods Receipt
GOODS_RECEIPT	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
GOODS_RECEIPT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
GOODS_RECEIPT	LOC_TYPE_CD	VARCHAR(5)	NULL	Location type (robot, non robot or both) - link to list_of_val table
GOODS_RECEIPT	ORD_ID	INT	NOT NULL	Link to Orders table
GOODS_RECEIPT	PDE_IND	CHAR (1)	NOT NULL	PDE indicator
GOODS_RECEIPT	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
GOODS_RECEIPT	SSCC_NBR	VARCHAR(20)	NULL	SSCC number for the goods receipt
GOODS_RECEIPT	VERIFIED_BY	VARCHAR (30)	NULL	Code of the User who verifies
GOODS_RECEIPT_EXTR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
GOODS_RECEIPT_EXTR	EXTR_ID	INT	NOT NULL	Unique ID of the Extract, for the site
GOODS_RECEIPT_EXTR	GR_ID	INT	NOT NULL	Link to Goods Receipt table

GOODS_RECEIPT_EXTR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
GOODS_RECEIPT_EXTR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
GOODS_RECEIPT_EXTR	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
GR_ITEM	BIN_BATCH_ID	INT	NULL	Bin batch identifier
GR_ITEM	BIN_TRAN_ID	INT	NULL	Unique ID used to link the bin transaction record
GR_ITEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
GR_ITEM	FIN_TRAN_ID	INT	NULL	Financial Transaction Identifier
GR_ITEM	GR_COST_EXTN_AMT	NUMERIC(18,8)	NOT NULL	Goods Receipt Total Cost
GR_ITEM	GR_DEL_ITEM_ID	INT	NULL	ID of the Goods Receipt Item that has been Deleted
GR_ITEM	GR_EXT_COST	NUMERIC(18,8)	NOT NULL	Goods Receipt cost with tax
GR_ITEM	GR_EXT_PRICE	NUMERIC(18,8)	NULL	Goods Receipt price with tax
GR_ITEM	GR_ID	INT	NOT NULL	Link to the Goods Receipt table
GR_ITEM	GR_ITEM_BATCH	VARCHAR (10)	NULL	Goods Receipt Item batch no.
GR_ITEM	GR_ITEM_ID	INT	NOT NULL	Unique ID of the Goods Receipt Item, for the site
GR_ITEM	GR_ITEM_STAT_CD	VARCHAR (5)	NOT NULL	Goods Receipt Status code
GR_ITEM	GR_PRICE	NUMERIC(18,8)	NULL	Goods Receipt Price
GR_ITEM	GR_QTY	NUMERIC(18,8)	NOT NULL	Goods Receipt quantity
GR_ITEM	GRI_BATCH_EXP_DT	DATETIME	NULL	Goods Receipt Item Batch Expiry Date
GR_ITEM	GRI_FREIGHT_COST	NUMERIC(18,8)	NULL	Goods receipt item freight cost
GR_ITEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
GR_ITEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
GR_ITEM	LOC_ID	INT	NULL	Store Location ID - Link to location table
GR_ITEM	ORD_ITEM_ID	INT	NOT NULL	Link to the Order Item table
GR_ITEM	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
GR_ITEM	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table

GR_ITEM	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
GR_WORK	COST_CNTR_XID	VARCHAR(20)	NULL	Cost Centre Code - Link to the Cost centre table
GR_WORK	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
GR_WORK	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current.
GR_WORK	GR_NOTE	TEXT	NULL	Goods Receipt worksheet note
GR_WORK	GR_WORK_DESC	VARCHAR(40)	NULL	Goods Receipt worksheet description
GR_WORK	GR_WORK_DT	DATETIME	NOT NULL	Date of the gr worksheet
GR_WORK	GR_WORK_ID	INT	NOT NULL	Unique ID of Goods Receipt worksheet, for the site
GR_WORK	GR_WORK_STAT_CD	VARCHAR(5)	NOT NULL	Goods Receipt worksheet status code
GR_WORK	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
GR_WORK	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
GR_WORK	ORD_TYPE_CD	VARCHAR (5)	NOT NULL	Order type
GR_WORK	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
GR_WORK	SSCC_NBR	VARCHAR(20)	NULL	SSCC code for the Goods Receipt worksheet
GR_WORK	STORE_XID	VARCHAR(20)	NULL	Code to link to the Store table
GR_WORK	VERIFIED_BY	VARCHAR (30)	NULL	The User who has verified this record.
GR_WORK_ITEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
GR_WORK_ITEM	EDI_ID	INT	NOT NULL	Unique EDI identifier
GR_WORK_ITEM	GR_ITEM_ID	INT	NULL	Link to gr_item table
GR_WORK_ITEM	GR_WORK_ID	INT	NOT NULL	Link to Goods Receipt worksheet table
GR_WORK_ITEM	GR_WORK_ITEM_ID	INT	NOT NULL	Unique ID of Goods Receipt worksheet item, for the site
GR_WORK_ITEM	GR_WORK_TYPE	VARCHAR(15)	NULL	Goods Receipt worksheet item work type
GR_WORK_ITEM	GWI_STAT_CD	VARCHAR(5)	NOT NULL	Goods Receipt worksheet item status code
GR_WORK_ITEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
GR_WORK_ITEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
GR_WORK_ITEM	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table

GR_WORK_ITEM	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
GR_WORK_ITEM	SUPP_XID	VARCHAR(20)	NULL	Code used to link to the Supplier record
GR_WORK_ITEM	UOM_ID	INT	NOT NULL	UOM identifier for the product
GTIN	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
GTIN	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current.
GTIN	GTI_ID	INT	NOT NULL	Unique gtin identifier
GTIN	GTI_ROBOT_IND	CHAR(1)	NOT NULL	No longer used
GTIN	GTIN_XID	VARCHAR(20)	NOT NULL	GTIN / EAN code value
GTIN	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
GTIN	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
GTIN	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
GTIN	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier for a product
GTIN_DESC	GTIN_XID	VARCHAR(20)	NOT NULL	Description
GTIN_DESC	LOCALE_CD	VARCHAR(5)	NOT NULL	Locale Information
BIN	AUTHORISED_BY	VARCHAR(30)	NULL	Code of the User who authorised the bin record
BIN	BIN_COMMIT_QTY	NUMERIC(18,8)	NULL	Committed quantity in the bin
BIN	BIN_COST	NUMERIC(18,8)	NOT NULL	AWP Cost Per Inventory Unit
BIN	BIN_DFLT_IND	CHAR (1)	NOT NULL	Default indicator for bin
BIN	BIN_IMP_PRICE	NUMERIC(18,8)	NOT NULL	Not used in this version of i.Pharmacy
BIN	BIN_LOCK_IN_IND	CHAR (1)	NOT NULL	Indicator specifying the bin to be locked for inward transaction
BIN	BIN_LOCK_OUT_IND	CHAR (1)	NOT NULL	Indicator specifying the bin to be locked for outward transaction
BIN	BIN_RESUPP_METH_CD	VARCHAR (5)	NOT NULL	Code for bin resupply method
BIN	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
BIN	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
BIN	IOH_BF_QTY	NUMERIC(18,8)	NOT NULL	Not used in this version of i.Pharmacy

BIN	IOH_CURR_QTY	NUMERIC(18,8)	NOT NULL	Quantity of current Inventory on hand
BIN	IOH_MAX_QTY	NUMERIC(18,8)	NOT NULL	Maximum inventory on hand quantity
BIN	IOH_MIN_QTY	NUMERIC(18,8)	NOT NULL	Minimum inventory on hand quantity
BIN	LAST_BATCH	VARCHAR (10)	NULL	Last Batch Number
BIN	LAST_BATCH_EXP_DT	DATETIME	NULL	Expiry date for last batch
BIN	LAST_PURCHASE_COST	NUMERIC(18,8)	NULL	Cost of last purchase
BIN	LAST_STK_TAKE_DT	DATETIME	NULL	Last stock take date
BIN	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
BIN	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
BIN	LOC_ID	INT	NOT NULL	Store Location ID - Link to location table
BIN	MAN_BIN_LOCK_IN_IND	CHAR(1)	NOT NULL	Colum to save bin lock indicator of man_bin_lock_in_ind
BIN	MAN_BIN_LOCK_OUT_IND	CHAR(1)	NOT NULL	Column to save bin lock indicator of man_bin_lock_out_ind
BIN	ORD_PREF_BRAND_IND	CHAR(1)	NOT NULL	Indicator specifying the product is the preferred brand for the Store with regard to Order Worksheet.
BIN	PRICE_VAR_PCT	DECIMAL(8,6)	NULL	Price Variance Percentage
BIN	PRICE_VAR_VAL	NUMERIC(18,8)	NULL	Price Variance Value
BIN	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
BIN	ROBOT_ID	INT	NULL	Robot Identifier - Link to robot table
BIN	ROBOT_IOH_ADJ	NUMERIC(18,8)	NULL	Robot inventory on hand adjustment quantity. No longer used from v8 onwards.
BIN	ROBOT_IOH_IND	CHAR(1)	NOT NULL	Indicator specifying that a request for Robot IOH has been sent to robot, but response has not yet been received.
BIN	ROBOT_IOH_INVEN_QTY	NUMERIC(18,8)	NULL	Column to save robot ioh inventory quantity value
BIN	ROBOT_IOH_QTY	CHAR(1)	NOT NULL	
BIN	ROBOT_TYPE_CD	VARCHAR (5)	NOT NULL	Robot type / model - Link to list_of_val table using robot_type_cd
BIN	ROBOT_XID	VARCHAR (20)	NULL	User created code to indicate the code for the robot.

BIN	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
BIN	STK_TAKE_GRP_SID	SMALLINT	NULL	Stock take group for the product against the Store
BIN	STK_TAKE_OVERR_IND	CHAR(1)	NOT NULL	Stock Take Group Override Indicator
BIN	STK_TAKE_OVERRGRP_SID	SMALLINT	NULL	Stock take group if the the stock take group has been overridden
BIN	SUB_LOC_XID	VARCHAR (20)	NULL	Identifier for sub location
BIN	SUPP_SITE_SID	SMALLINT	NULL	Supplier Site Identifier
BIN	SUPP_STORE_XID	VARCHAR (20)	NULL	Code to link to the Store table
BIN_BATCH	BATCH_EXP_DT	DATETIME	NULL	Batch expiry date
BIN_BATCH	BATCH_INV_COST	NUMERIC(18,8)	NOT NULL	Batch inventory cost
BIN_BATCH	BATCH_INV_PRICE	NUMERIC(18,8)	NOT NULL	Batch inventory price
BIN_BATCH	BATCH_INV_RECQTY	NUMERIC(18,8)	NOT NULL	Batch inventory received quantity
BIN_BATCH	BATCH_IOH_QTY	NUMERIC(18,8)	NOT NULL	Batch inventory received quantity
BIN_BATCH	BIN_BATCH_ID	INT	NOT NULL	Bin batch identifier
BIN_BATCH	BIN_BATCH_NO	VARCHAR (10)	NULL	Bin batch number
BIN_BATCH	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
BIN_BATCH	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
BIN_BATCH	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
BIN_BATCH	LOC_ID	INT	NOT NULL	Store Location ID - Link to location table
BIN_BATCH	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
BIN_BATCH	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
BIN_TRAN	BIN_BATCH_ID	INT	NULL	Bin batch identifier
BIN_TRAN	BIN_TRAN_BATCH	VARCHAR (10)	NULL	Batch number of the item if Bin batch is active
BIN_TRAN	BIN_TRAN_COST	NUMERIC(18,8)	NULL	Cost of a pack, based on the multiplier in the prod_uom table, and the AWP
BIN_TRAN	BIN_TRAN_DT	DATETIME	NOT NULL	Date of the transaction recorded in the window. This is the date entered in the transaction window.
BIN_TRAN	BIN_TRAN_EXT_COST	NUMERIC(18,8)	NULL	Transaction UOM cost pus tax

BIN_TRAN	BIN_TRAN_EXT_PRICE	NUMERIC(18,8)	NULL	Transaction UOM selling price, including n
BIN_TRAN	BIN_TRAN_ID	INT	NOT NULL	Unique ID used to identify the bin transaction
BIN_TRAN	BIN_TRAN_INVEN_QTY	NUMERIC(18,8)	NOT NULL	Number of inventory units for bin transaction
BIN_TRAN	BIN_TRAN_PACK_QTY	NUMERIC(18,8)	NOT NULL	Number of transaction UOM's, as identified above
BIN_TRAN	BIN_TRAN_PRICE	NUMERIC(18,8)	NULL	Transaction UOM selling price, including n
BIN_TRAN	BIN_TRAN_PVV_AMT	NUMERIC(18,8)	NULL	Amount of Price Value Variance applied
BIN_TRAN	BT_BATCH_EXP_DT	DATETIME	NULL	Expiry date of the item if Bin batch is active
BIN_TRAN	BTR_INVEN_COST	NUMERIC(18,8)	NULL	The bin_cost (AWP) of inventory unit
BIN_TRAN	BTR_INVEN_EXT_COST	NUMERIC(18,8)	NULL	The AWP plus tax, of inventory unit
BIN_TRAN	BTR_INVEN_EXT_PRICE	NUMERIC(18,8)	NULL	Selling price, plus tax, of Inventory UOM
BIN_TRAN	BTR_INVEN_PRICE	NUMERIC(18,8)	NULL	Selling price of Inventory UOM, including mark up
BIN_TRAN	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
BIN_TRAN	INVEN_UOM_ID	INT	NOT NULL	Inventory UOM identifier at the time of the transaction
BIN_TRAN	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
BIN_TRAN	LAST_UPDATED_DT	DATETIME	NOT NULL	Always the same as created_dt, EXCEPT for Goods Receipt when a Supplier Invoice can update the Bin_tran_price and Bin_tran_ext_price columns.
BIN_TRAN	LOC_ID	INT	NOT NULL	Store Location ID - Link to location table
BIN_TRAN	PACK_UOM_ID	INT	NOT NULL	Transaction UOM. (This is often, pack_uom, but not necessarily on every occasion)
BIN_TRAN	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
BIN_TRAN	RECV_ABN	VARCHAR (14)	NULL	ABN number of the Receiver
BIN_TRAN	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
BIN_TRAN	SUPP_ABN	VARCHAR (14)	NULL	ABN number of the supplier
BIN_TRAN	TRAN_TYPE_CD	VARCHAR (5)	NOT NULL	Transaction Type Code identifier
BIN_TRAN_E XTR	BIN_TRAN_ID	INT	NOT NULL	Unique ID used to link the bin transaction record
BIN_TRAN_E XTR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.

BIN_TRAN_EXTR	EXTR_ID	INT	NOT NULL	Unique ID used to identify the extract
BIN_TRAN_EXTR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
BIN_TRAN_EXTR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
BIN_TRAN_EXTR	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
CHARGE_CENTRE	CHRG_CNTR_ADDR_1	VARCHAR (40)	NULL	Charge centre address1
CHARGE_CENTRE	CHRG_CNTR_ADDR_2	VARCHAR (40)	NULL	Charge centre address2
CHARGE_CENTRE	CHRG_CNTR_ADDR_3	VARCHAR (40)	NULL	Charge centre address3
CHARGE_CENTRE	CHRG_CNTR_ADDR_4	VARCHAR (40)	NULL	Charge centre address4
CHARGE_CENTRE	CHRG_CNTR_CNTRY	VARCHAR (30)	NULL	Charge centre Country
CHARGE_CENTRE	CHRG_CNTR_DESC	VARCHAR (40)	NOT NULL	Description of charge centre
CHARGE_CENTRE	CHRG_CNTR_NOTE	VARCHAR (255)	NULL	Notes for the charge centre
CHARGE_CENTRE	CHRG_CNTR_POSTCODE	VARCHAR (10)	NULL	Charge centre postal code
CHARGE_CENTRE	CHRG_CNTR_XID	VARCHAR (20)	NOT NULL	ID used to identify Charge centre
CHARGE_CENTRE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
CHARGE_CENTRE	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
CHARGE_CENTRE	DEBTOR_NBR	VARCHAR (20)	NULL	Number of the Debtor
CHARGE_CENTRE	HOSP_IND	CHAR (1)	NOT NULL	Indicator for hospital
CHARGE_CENTRE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
CHARGE_CENTRE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
CHARGE_CENTRE	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
COC_ACC_COMP	ACC_COMP_ID	INT	NOT NULL	Unique ID used to identify the account component
COC_ACC_COMP	COC_ACC_COMP_XID	VARCHAR (20)	NULL	Cost centre Account Code value
COC_ACC_COMP	COST_CNTR_XID	VARCHAR (20)	NOT NULL	Cost Centre Code - Link to the Cost centre table
COC_ACC_COMP	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
COC_ACC_COMP	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
COC_ACC_COMP	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.

COC_ACC_C OMP	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
COMPOUN DERS	ADDRESS	VARCHAR (255)	NULL	Compounders Address
COMPOUN DERS	COMPOUNDER_ABN	VARCHAR (14)	NOT NULL	Compounders ABN Number
COMPOUN DERS	COMPOUNDER_NAME	VARCHAR (255)	NOT NULL	Compounders Name
COMPOUN DERS	COMPOUNDER_XID	VARCHAR (20)	NOT NULL	Compounders ID
COMPOUN DERS	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
COMPOUN DERS	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current.
COMPOUN DERS	FAX	VARCHAR (15)	NULL	Compounders Fax
COMPOUN DERS	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
COMPOUN DERS	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
COMPOUN DERS	PHONE	VARCHAR (15)	NULL	Compounders Phone
COMPOUN DERS	TGA_LIC_STATUS	VARCHAR (5)	NULL	TGA Licence Status
COMPOUN DER_SITE	ADDRESS	CHAR(255)	NULL	Column for address field in compounder maintenance
COMPOUN DER_SITE	COMPOUNDER_ABN	CHAR(14)		Column for Compounder Abn in compounder maintenance
COMPOUN DER_SITE	COMPOUNDER_NAME	CHAR(255)	NOT NULL	Column to save Description in compounder Maintenance
COMPOUN DER_SITE	COMPOUNDER_XID	CHAR(20)	NOT NULL	Column to store compounder_xid in compounder Maintenance
COMPOUN DER_SITE	CREATED_DT	DATETIME	NOT NULL	Column to update Created date in compounder_site table
COMPOUN DER_SITE	CURR_IND	CHAR(1)	NOT NULL	Column for Current indicator in compounder maintenance
COMPOUN DER_SITE	DEF_NON_NORM	CHAR(1)	NOT NULL	Column for default Non Normal Indicator in compounder Maintenance
COMPOUN DER_SITE	LAST_UPDATED_BY	CHAR(30)	NOT NULL	Column to save last updated by in compounder_site table
COMPOUN DER_SITE	LAST_UPDATED_DT	DATETIME	NOT NULL	Column to save last Updated date in compounder_site table
COMPOUN DER_SITE	SITE_SID	LONG	NOT NULL	Column to store site in compounder_site table

COMPOUN DER_SITE	TGA_LIC_STATUS	CHAR(5)	NULL	Column to save tga_lic_status in compouder_site against the compouder_xid
CONV_FACT OR	CONV_QTY	NUMERIC(18,8)	NOT NULL	Conversion quantity
CONV_FACT OR	CONV_UNIT_PID	INT	NOT NULL	Conversion Unit identifier
CONV_FACT OR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
CONV_FACT OR	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
CONV_FACT OR	INVERSE_QTY	NUMERIC(18,8)	NOT NULL	Inverse quantity
CONV_FACT OR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
CONV_FACT OR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
CONV_FACT OR	UNIT_CATG_XID	VARCHAR(20)	NOT NULL	Unit Category identifier - Link to unit table
CONV_FACT OR	UNIT_PID	INT	NOT NULL	Unit identifier - Link to unit table
COST_CENT RE	ACCOUNT_1_REF	VARCHAR(20)	NULL	Reference for account - Or as indicated in parameters
COST_CENT RE	ACCOUNT_2_REF	VARCHAR(20)	NULL	Reference for account - Or as indicated in parameters
COST_CENT RE	ACCOUNT_3_REF	VARCHAR(20)	NULL	Reference for account - Or as indicated in parameters
COST_CENT RE	ACCOUNT_4_REF	VARCHAR(20)	NULL	Reference for account - Or as indicated in parameters
COST_CENT RE	ADC_SUPP_STORE_XID	VARCHAR(20)	NULL	Column for ADC supplying store
COST_CENT RE	REQN_REQU_IND	CHAR(1)	NOT NULL	Column for Request creation indicator
COST_CENT RE	CHARGE_IND	CHAR (1)	NOT NULL	Charge indicator
COST_CENT RE	CHRG_CNTR_XID	VARCHAR(20)	NOT NULL	ID used to link to the Charge centre record
COST_CENT RE	COST_CNTR_ABN	VARCHAR(14)	NULL	ABN number for the cost centre
COST_CENT RE	COST_CNTR_ADDR_1	VARCHAR(40)	NULL	Cost centre address1
COST_CENT RE	COST_CNTR_ADDR_2	VARCHAR(40)	NULL	Cost centre address2
COST_CENT RE	COST_CNTR_ADDR_3	VARCHAR(40)	NULL	Cost centre address3
COST_CENT RE	COST_CNTR_ADDR_4	VARCHAR(40)	NULL	Cost centre address4
COST_CENT RE	COST_CNTR_CNTRY	VARCHAR(30)	NULL	Cost centre country
COST_CENT RE	COST_CNTR_CONT_NM	VARCHAR(255)	NULL	Cost centre Contact Information

COST_CENT RE	COST_CNTR_DESC	VARCHAR(40)	NOT NULL	Description for the cost centre
COST_CENT RE	COST_CNTR_HI_XID	VARCHAR(20)	NULL	To store Healthcare Provider Identifier value
COST_CENT RE	COST_CNTR_INVADDR_1	VARCHAR(40)	NULL	Invoice address 1
COST_CENT RE	COST_CNTR_INVADDR_2	VARCHAR(40)	NULL	Invoice address 2
COST_CENT RE	COST_CNTR_INVADDR_3	VARCHAR(40)	NULL	Invoice address 3
COST_CENT RE	COST_CNTR_INVADDR_4	VARCHAR(40)	NULL	Invoice address 4
COST_CENT RE	COST_CNTR_INVCNTRY	VARCHAR(30)	NULL	Invoice address country name
COST_CENT RE	COST_CNTR_INVPOSTCODE	VARCHAR(10)	NULL	Invoice address post code
COST_CENT RE	COST_CNTR_NOTE	VARCHAR(255)	NULL	Notes for cost centre
COST_CENT RE	COST_CNTR_POSTCODE	VARCHAR(10)	NULL	Cost centre postal code
COST_CENT RE	COST_CNTR_QID	VARCHAR(10)	NULL	Finance Cost Centre code
COST_CENT RE	COST_CNTR_XID	VARCHAR(20)	NOT NULL	Cost Centre Code - Link to the Cost centre table
COST_CENT RE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
COST_CENT RE	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current.
COST_CENT RE	DELVADDR_AS_INVADDR_IND	CHAR(1)	NOT NULL	This column is included in Cost Centre Maintenance screen to use delivery address as a invoice address
COST_CENT RE	DEPT_DESC	VARCHAR(40)	NULL	Department description
COST_CENT RE	EXT_IND	CHAR (1)	NOT NULL	External indicator
COST_CENT RE	FIN_STRUCT_ID	INT	NULL	Financial Structure Identifier
COST_CENT RE	GLOBAL_LOCATION_NBR	VARCHAR(13)	NULL	Global Location Number (GLN)
COST_CENT RE	HAND_FEE_AMT	NUMERIC(18,8)	NULL	Handling Fees Amount
COST_CENT RE	IN_PAT_DSPN_IND	CHAR (1)	NOT NULL	Indicator for inpatient
COST_CENT RE	LAST_PURCHASE_COST_IND	CHAR(1)	NOT NULL	Indicator for last purchase cost functionality
COST_CENT RE	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
COST_CENT RE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
COST_CENT RE	MARK_UP_PCT	DECIMAL(8,6)	NULL	Mark Up Percentage

COST_CENTRE	OUT_PAT_DSPN_IND	CHAR (1)	NOT NULL	Indicator for out patient
COST_CENTRE	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
COST_CENTRE	SORT_SEQ	INT	NULL	Sort sequence
COST_CENTRE	SUPP_CHG_AMT	NUMERIC(18,8)	NOT NULL	Supply charge amount
COST_CENTRE	SUPP_XID	VARCHAR(20)	NULL	Code used to link to the Supplier record
COST_CENTRE	WRKSHT_SUPP_STORE_XID	VARCHAR(20)	NULL	Column for Worksheet Supplying Store
CREDIT_NOTE	CR_FREIGHT_COST	NUMERIC(18,8)	NULL	Freight cost for credit note
CREDIT_NOTE	CR_FREIGHT_EXT_COST	NUMERIC(18,8)	NULL	Freight Cost With Tax
CREDIT_NOTE	CR_FREIGHT_TAX_AMT	NUMERIC(18,8)	NULL	Freight tax amount credit for UK locale
CREDIT_NOTE	CR_INVC_TAX_AMT	NUMERIC(18,8)	NULL	Tax amount fro credit invoice for UK locale
CREDIT_NOTE	CR_INVC_TOT_COST	NUMERIC(18,8)	NULL	Total cost of credit invoice for UK locale
CREDIT_NOTE	CR_INVC_TOT_EXT_COST	NUMERIC(18,8)	NULL	Total Cost of Credit Invoice with Tax for UK locale
CREDIT_NOTE	CR_NOTE_AUTH_REF	VARCHAR(20)	NULL	Reference for credit note authority
CREDIT_NOTE	CR_NOTE_CONF_REF	VARCHAR(20)	NULL	Reference for credit note Confirmation
CREDIT_NOTE	CR_NOTE_DT	DATETIME	NOT NULL	Date entered in application
CREDIT_NOTE	CR_NOTE_ID	INT	NOT NULL	Unique ID used to identify the credit note
CREDIT_NOTE	CR_NOTE_NOTE	VARCHAR (255)	NULL	Notes for the credit note
CREDIT_NOTE	CR_NOTE_REASON_CD	VARCHAR(5)	NOT NULL	Code for the credit note reason type
CREDIT_NOTE	CR_NOTE_STAT_CD	VARCHAR (5)	NOT NULL	Code for credit note status
CREDIT_NOTE	CR_NOTE_TYPE_CD	VARCHAR (5)	NOT NULL	Code for the credit note type
CREDIT_NOTE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
CREDIT_NOTE	CRN_AP_EXTRACT	INT	NULL	Not used in this version of i.Pharmacy
CREDIT_NOTE	CRN_REASON_DESC	VARCHAR(40)	NULL	Description for the credit note reason
CREDIT_NOTE	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
CREDIT_NOTE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
CREDIT_NOTE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.

CREDIT_NO TE	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
CREDIT_NO TE	SUPP_XID	VARCHAR (20)	NOT NULL	Code used to link to the Supplier record
CREDIT_NO TE_EXTR	CR_NOTE_ID	INT	NOT NULL	Unique ID used to identify the credit note
CREDIT_NO TE_EXTR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
CREDIT_NO TE_EXTR	EXTR_ID	INT	NOT NULL	Unique ID used to identify the extract
CREDIT_NO TE_EXTR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
CREDIT_NO TE_EXTR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
CREDIT_NO TE_EXTR	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
CREDIT_NO TE_ITEM	BIN_BATCH_ID	INT	NULL	Bin batch identifier
CREDIT_NO TE_ITEM	BIN_TRAN_ID	INT	NULL	Unique ID used to link the bin transaction record
CREDIT_NO TE_ITEM	CR_FREIGHT_COST	NUMERIC(18,8)	NULL	Freight cost for credit note
CREDIT_NO TE_ITEM	CR_NOTE_ID	INT	NOT NULL	Unique ID used to link to the credit note
CREDIT_NO TE_ITEM	CR_NOTE_ITEM_AMT	NUMERIC(18,8)	NOT NULL	Cost of credit note item
CREDIT_NO TE_ITEM	CR_NOTE_ITEM_EXT_AMT	NUMERIC(18,8)	NOT NULL	Cost of Credit Note Item with Tax
CREDIT_NO TE_ITEM	CR_NOTE_ITEM_EXT_PRICE	NUMERIC(18,8)	NULL	Column to save credit price with tax
CREDIT_NO TE_ITEM	CR_NOTE_ITEM_ID	INT	NOT NULL	Unique ID used to identify credit note item
CREDIT_NO TE_ITEM	CR_NOTE_ITEM_PRICE	NUMERIC(18,8)	NULL	Column to save Credit price
CREDIT_NO TE_ITEM	CR_NOTE_ITEM_QTY	NUMERIC(18,8)	NULL	Quantity of credit note item
CREDIT_NO TE_ITEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
CREDIT_NO TE_ITEM	CRI_BATCH	VARCHAR (10)	NULL	Batch number for credit invoice item
CREDIT_NO TE_ITEM	CRI_BATCH_EXP_DT	DATETIME	NULL	Expiry date for credit invoice item
CREDIT_NO TE_ITEM	CRI_ROBOT_ADJ_IND	CHAR(1)	NOT NULL	Robot adjust indicator
CREDIT_NO TE_ITEM	CRI_STAT_CD	VARCHAR (5)	NOT NULL	Code for credit invoice status
CREDIT_NO TE_ITEM	CRI_TOT_EXT_PRICE	NUMERIC(18,8)	NULL	Colum to save credit total extra price value
CREDIT_NO TE_ITEM	CRI_TOT_PRICE	NUMERIC(18,8)	NULL	Column to save credit total price value
CREDIT_NO TE_ITEM	FIN_TRAN_ID	INT	NULL	Used to link to the Financial Transaction Identifier

CREDIT_NO TE_ITEM	GR_ITEM_ID	INT	NOT NULL	This is used to identify the Goods Receipt Item Id
CREDIT_NO TE_ITEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
CREDIT_NO TE_ITEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
CREDIT_NO TE_ITEM	LOC_ID	INT	NULL	Store Location ID - Link to location table
CREDIT_NO TE_ITEM	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
CREDIT_NO TE_ITEM	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
CREDIT_NO TE_ITEM	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
CRYSTAL_RE PORTS	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
CRYSTAL_RE PORTS	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
CRYSTAL_RE PORTS	DATE_TIME_IND	CHAR(1)	NOT NULL	This column will record the datetime indicator for all the reports
CRYSTAL_RE PORTS	HARD_COPY_AUDIT_REPT_ID	INT	NULL	Unique ID used to identify the Hard Copy Audit Report
CRYSTAL_RE PORTS	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
CRYSTAL_RE PORTS	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
CRYSTAL_RE PORTS	RPT_NAME	VARCHAR (255)	NOT NULL	Report name
CRYSTAL_RE PORTS	RPT_SID	SMALLINT	NOT NULL	Report identifier
EDI_INV_DE SP	ALLOWANCE_CHRG_TYPE	VARCHAR (15)	NULL	Allowance charge type
EDI_INV_DE SP	BATCH_NBR	VARCHAR(10)	NULL	Batch Number
EDI_INV_DE SP	CHILD_PACK_CD	VARCHAR (5)	NULL	Child Pack Code
EDI_INV_DE SP	CHILD_PACK_NBR	VARCHAR (15)	NULL	ChildPack Number
EDI_INV_DE SP	COST_CNTR_XID	VARCHAR(20)	NULL	Cost Centre Code - Link to the Cost centre table
EDI_INV_DE SP	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
EDI_INV_DE SP	CURRENCY_CD	VARCHAR(5)	NULL	Currency Code
EDI_INV_DE SP	DELIVERY_REF	VARCHAR (20)	NULL	Delivery Reference Number
EDI_INV_DE SP	DESP_DT	DATETIME	NULL	Despatch Date
EDI_INV_DE SP	DESP_LINE_NBR	VARCHAR (15)	NULL	Despatch Line Number

EDI_INV_DE SP	DESP_QTY	NUMERIC(18,8)	NULL	Despatch Quantity
EDI_INV_DE SP	DESP_REF_NBR	VARCHAR (15)	NULL	Despatch Number
EDI_INV_DE SP	EDI_ID	INT	NOT NULL	Unique edi identifier
EDI_INV_DE SP	EDI_RECV_REF	VARCHAR (255)	NULL	EDI receipt reference number
EDI_INV_DE SP	EDI_SEND_REF	VARCHAR (255)	NULL	EDI send reference number
EDI_INV_DE SP	EID_STAT_CD	VARCHAR (5)	NULL	Edi status code
EDI_INV_DE SP	ERROR_DESC	TEXT	NULL	Error description
EDI_INV_DE SP	ERROR_STAT_CD	VARCHAR (5)	NULL	Error status code
EDI_INV_DE SP	EXPIRY_DT	DATETIME	NULL	Expiry Date
EDI_INV_DE SP	FREIGHT_AMT	NUMERIC(18,8)	NULL	Freight amount
EDI_INV_DE SP	FREIGHT_TAX	NUMERIC(18,8)	NULL	Freight Tax
EDI_INV_DE SP	GR_ID	INT	NULL	Link to goods receipt table
EDI_INV_DE SP	GR_TYPE	VARCHAR (5)	NULL	Goods receipt type
EDI_INV_DE SP	GTIN_XID	VARCHAR (20)	NULL	GTIN Value
EDI_INV_DE SP	INV_DT	DATETIME	NULL	Invoice Date
EDI_INV_DE SP	INV_LINE_NBR	VARCHAR(15)	NULL	Invoice Line Number
EDI_INV_DE SP	INV_QTY	NUMERIC(18,8)	NULL	Invoice Quantity
EDI_INV_DE SP	INV_TOTAL_AMT	NUMERIC(18,8)	NULL	Invoice total amount
EDI_INV_DE SP	INV_TOTEXC_AMT	NUMERIC(18,8)	NULL	Invoice total amount excluding tax
EDI_INV_DE SP	INV_TOTINC_AMT	NUMERIC(18,8)	NULL	Invoice total amount including tax
EDI_INV_DE SP	INV_TYPE_CD	VARCHAR (15)	NULL	InvoiceType
EDI_INV_DE SP	INVOICE_REF	VARCHAR(20)	NULL	invoice reference
EDI_INV_DE SP	ITEM_CHRG_AMT	NUMERIC(18,8)	NULL	Line item Charge amount
EDI_INV_DE SP	ITEM_CHRG_TAX	NUMERIC(18,8)	NULL	Line Item Charge Tax
EDI_INV_DE SP	ITEM_COST	NUMERIC(18,8)	NULL	Item cost
EDI_INV_DE SP	ITEM_TAX	NUMERIC(18,8)	NULL	Line Item total Charge amount

EDI_INV_DE SP	LAST_UPDATED	DATETIME	NULL	last updated date for the edi invoice desp field
EDI_INV_DE SP	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
EDI_INV_DE SP	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
EDI_INV_DE SP	LINE_NBR	VARCHAR(15)	NULL	Line number
EDI_INV_DE SP	MSG_FUNC_DESC	VARCHAR (40)	NULL	Message Function Description
EDI_INV_DE SP	MSG_TYPE_XID	VARCHAR (20)	NULL	Message Type
EDI_INV_DE SP	ORD_DT	DATETIME	NULL	Despatch Date
EDI_INV_DE SP	ORD_ID	INT	NULL	Link to Orders table
EDI_INV_DE SP	ORD_LINE_NBR	VARCHAR (15)	NULL	Order Line Number
EDI_INV_DE SP	ORD_TYPE_CD	VARCHAR (5)	NULL	Order type
EDI_INV_DE SP	PACK_CD	VARCHAR (5)	NULL	Pack Code
EDI_INV_DE SP	PACK_LEVEL_NBR	VARCHAR (15)	NULL	Pack Level Number for
EDI_INV_DE SP	PARENT_PACK_NBR	VARCHAR (15)	NULL	Parent Pack Number
EDI_INV_DE SP	REC_SITE_ABN	VARCHAR(14)	NULL	Receiving Site ABN
EDI_INV_DE SP	RECEIVER_GLN	VARCHAR (13)	NULL	Receiver GLN
EDI_INV_DE SP	SHIPTO_GLN	VARCHAR(13)	NULL	Ship To GLN
EDI_INV_DE SP	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EDI_INV_DE SP	SSCC_NBR	VARCHAR (20)	NULL	Serial shipment container code
EDI_INV_DE SP	STORE_XID	VARCHAR(20)	NULL	Code to link to the Store table
EDI_INV_DE SP	SUPP_ABN	VARCHAR(14)	NULL	Supplier ABN
EDI_INV_DE SP	SUPP_PROD_XID	VARCHAR (255)	NULL	Product Identifier used by the supplier
EDI_INV_DE SP	SUPP_XID	VARCHAR (20)	NULL	Code used to link to the Supplier record
EDI_INV_DE SP	SUPPLIER_GLN	VARCHAR (13)	NULL	Supplier GLN
EDI_INV_DE SP	TRANS_OWNERSHIP_DT	DATETIME	NULL	Column to save trans ownership date
EDI_ORD	CONTRACT_NBR_REF	VARCHAR(20)	NULL	Contract Number Reference
EDI_ORD	COST_CNTR_XID	VARCHAR(20)	NULL	Cost Centre Code - Link to the Cost centre table

EDI_ORD	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
EDI_ORD	DELIV_INST	VARCHAR(255)	NULL	Delivery instructions
EDI_ORD	EDI_ID	INT	NOT NULL	Electronic Data Interchange ID
EDI_ORD	EDI_INVC_DT	DATETIME	NULL	EDI Invoice Date
EDI_ORD	EDI_METH_CD	VARCHAR(5)	NOT NULL	EDI Method Code
EDI_ORD	EDI_ORD_SEQ	INT	NULL	EDI Order Sequence
EDI_ORD	EDI_RECV_REF	VARCHAR(255)	NULL	Name of EDI received file
EDI_ORD	EDI_SEND_REF	VARCHAR(255)	NULL	Name of EDI file sent
EDI_ORD	EDI_STAT_CD	VARCHAR(5)	NOT NULL	EDI Status Code
EDI_ORD	ERROR_DESC	VARCHAR(40)	NULL	Error Description
EDI_ORD	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
EDI_ORD	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
EDI_ORD	LOC_ID	INT	NULL	Store Location ID - Link to location table
EDI_ORD	ORD_COST	NUMERIC(18,8)	NULL	Order Cost
EDI_ORD	ORD_DT	DATETIME	NULL	Date the Order was placed
EDI_ORD	ORD_EXT_COST	NUMERIC(18,8)	NULL	Order Cost with Tax
EDI_ORD	ORD_ID	INT	NULL	Link to the Orders table
EDI_ORD	ORD_ITEM_ID	INT	NULL	Order Item Number
EDI_ORD	ORD_NOTE	VARCHAR(255)	NULL	Order Notes
EDI_ORD	ORD_QTY	NUMERIC(18,8)	NULL	Order Quantity
EDI_ORD	PROD_ID	INT	NULL	Product Identifier - Link to product table
EDI_ORD	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EDI_ORD	STORE_XID	VARCHAR(20)	NULL	Code to link to the Store table
EDI_ORD	SUPP_CATL_XID	VARCHAR(20)	NULL	Supplier Catalogue Identifier
EDI_ORD	SUPP_XID	VARCHAR(20)	NULL	Code used to link to the Supplier record
EDI_ORD	UOM_ID	INT	NULL	Unit of Measurement Identifier - Link to UOM table
EDI_SUPPLIER	EDI_SUPP_DESC	VARCHAR (40)	NOT NULL	EDI Supplier Description
EDI_SUPPLIER	FROM_IND	CHAR (1)	NOT NULL	Indicator to flag if EDI from supplier is allowed
EDI_SUPPLIER	SUPP_EAN	CHAR (13)	NOT NULL	Supplier EAN Code
EPRESCRIPTION	CONCESSION_PENSIONNUMBER	VARCHAR(20)	NULL	ePrescription Patient Entitlement Number
EPRESCRIPTION	CLINICIAN_RESERVED_01	VARCHAR(50)	NULL	Practitioner Qualifications

EPRESCRIPTION	CLINICIAN_RESERVED_02	VARCHAR(50)	NULL	Hospital Provider Number
EPRESCRIPTION	CLINICIAN_RESERVED_03	VARCHAR(50)	NULL	AIP (Active Ingredient Prescribing) compliant prescription item description for the display to Dispenser
EPRESCRIPTION	CLINICIAN_RESERVED_04	VARCHAR(50)	NULL	The name of the pharmacy the prescription is to be dispensed (if required by NSW health)
EPRESCRIPTION	CLINICIAN_RESERVED_05	VARCHAR(50)	NULL	Field included for future uses
EPRESCRIPTION	CREATORCONFORMANCEID	VARCHAR(255)	NULL	The conformance ID of the software creating the prescription
EPRESCRIPTION	CREATEDDATE	DATETIME	NULL	Date and time from the ERX004 prescription message.
EPRESCRIPTION	CREATED_DT	DATETIME	NOT NULL	Date and time that the record was created.
EPRESCRIPTION	DISPENSERCONFORMANCEID	VARCHAR(255)	NULL	The conformance ID of the software creating the record of dispense
EPRESCRIPTION	DISPPAT_PATIENTHOSPITALCATEGORY	VARCHAR(5)	NULL	Indicates if the patient is Inpatient or all other options (outpatient, ED, Nursing Home, Jail). True indicates inpatient, false indicates all other values. Value is only required in non-community settings (dispensing system).
EPRESCRIPTION	DISPENSEDPATIENTCONCESSION_PENSIONNUMBER	VARCHAR(20)	NULL	Patient Entitlement Number (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTDVACARDCOLOUR	VARCHAR(10)	NULL	DVA card colour (G, W, O) (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTDVANUMBER	VARCHAR(10)	NULL	DVA number for patient (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTENTITLEMENTNUMBER	VARCHAR(20)	NULL	Safety Net Number (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENTADDRESS1	VARCHAR(50)	NULL	address1 (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENTADDRESS2	VARCHAR(50)	NULL	address2 (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENTBIRTHDATE	DATE	NULL	Birthdate (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENTCTGFLAG	VARCHAR(5)	NULL	Flag to denote patient eligibility for Closing the Gap (CTG) (dispensing system)

EPRESCRIPTION	DISPENSEDPATIENTPATIENT EMAIL	VARCHAR(50)	NULL	Patient email (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT FAMILYNAME	VARCHAR(50)	NULL	Patient family/surname (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT FIRSTNAME	VARCHAR(50)	NULL	Patient firstname (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT IHI	VARCHAR(50)	NULL	Patient Individual Health Identifier (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT MEDICAREFAMILYNAME	VARCHAR(50)	NULL	Medicare family name (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT MEDICAREFIRSTNAME	VARCHAR(50)	NULL	Medicare first name (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT MEDICARENUMBER	VARCHAR(15)	NULL	Medicare number excluding subnumerate (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT MEDICARESUBNUMERATE	CHAR(1)	NULL	Medicare number Including subnumerate (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT MEDICAREVALIDTO	DATE	NULL	Medicare number - Valid to date (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT MOBILENUMBER	VARCHAR(20)	NULL	patient mobile number (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT PHONENUMBER	VARCHAR(20)	NULL	patient phone number (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT POSTCODE	VARCHAR(10)	NULL	patient postcode (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT SEX	CHAR(1)	NULL	Uppercase choice of M, F, O, U (Male, Female, Other, Undefined) (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT STATE	CHAR(3)	NULL	Uppercase choice of - VIC NSW ACT QLD NT WA SA TAS (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT SUBURUB	VARCHAR(50)	NULL	Patient suburb (dispensing system)
EPRESCRIPTION	DISPENSEDPATIENTPATIENT TITLE	VARCHAR(30)	NULL	Patient Title (dispensing system)
EPRESCRIPTION	DISPENSINGSYSTEMUSED	VARCHAR(255)	NULL	Dispensing software name (dispensing system)
EPRESCRIPTION	DOCTOREMAIL	VARCHAR(50)	NULL	Doctor email
EPRESCRIPTION	DOCTORFAMILYNAME	VARCHAR(30)	NOT NULL	Doctor Family name
EPRESCRIPTION	DOCTORFIRSTNAME	VARCHAR(30)	NULL	Doctor First name
EPRESCRIPTION	DOCTORFAXNUMBER	VARCHAR(20)	NULL	Doctor Fax Number
EPRESCRIPTION	DOCTORMOBILENUMBER	VARCHAR(20)	NULL	Doctor Mobile Number

EPRESCRIPTION	DOCTORPHONENUMBER	VARCHAR(20)	NULL	Doctor Phone Number
EPRESCRIPTION	DOCTORPRESCRIBERNUMBER	VARCHAR(15)	NULL	Doctor Prescriber Number
EPRESCRIPTION	DOCTORPROVIDERNUMBER	VARCHAR(10)	NULL	Doctor Provider Number
EPRESCRIPTION	DVACARDCOLOUR	VARCHAR(10)	NULL	Uppercase, choice of : G, W or O (for Gold, White or Orange (or any other colour as legislated))
EPRESCRIPTION	DVANUMBER	VARCHAR(10)	NULL	DVA number
EPRESCRIPTION	DOCT_XID	VARCHAR(20)	NULL	Prescriber code - Link to doctor table
EPRESCRIPTION	EMAIL	VARCHAR(60)	NULL	The email Value (Electronic Address) for use when sending an ePrescription token to the patient.
EPRESCRIPTION	ENTITLEMENTNUMBER	VARCHAR(20)	NULL	Safety Net Number
EPRESCRIPTION	EPRESUNIQUENUMBER	VARCHAR(20)	NULL	The SCID for the original prescription (equivalent to dispense UPPN)
EPRESCRIPTION	GUID	VARCHAR(255)	NULL	GUID values sent and received for ERX messages in <GUID> tag
EPRESCRIPTION	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
EPRESCRIPTION	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
EPRESCRIPTION	ORIGINALGUID	VARCHAR(255)	NULL	Original GUID values sent and received for ERX messages in <OriginalGUID> tag
EPRESCRIPTION	ORIGINALREPOSITORYSOFTWAREID	VARCHAR(255)	NULL	Conformance ID of the PES where original prescription by prescriber is uploaded
EPRESCRIPTION	ORIGINALSCID	VARCHAR(20)	NULL	Original SCID values sent and received for ERX messages in <OriginalSCID> tag
EPRESCRIPTION	PATIENTADDRESS1	VARCHAR(50)	NULL	Patient Address1
EPRESCRIPTION	PATIENTADDRESS2	VARCHAR(50)	NULL	Patient Address2
EPRESCRIPTION	PATIENTBIRTHDATE	DATE	NULL	Birth date of patient
EPRESCRIPTION	PATIENTCTGFLAG	VARCHAR(5)	NOT NULL	Flag to denote patient eligibility for Closing the Gap (CTG). Values are: True or false
EPRESCRIPTION	PATIENTEMAIL	VARCHAR(50)	NULL	Patient email address

EPRESCRIPTION	PATIENTFAMILYNAME	VARCHAR(255)	NULL	Patient family/surname
EPRESCRIPTION	PATIENTFIRSTNAME	VARCHAR(255)	NULL	Patient First name
EPRESCRIPTION	PATIENTHOSPITALCATEGORY	VARCHAR(5)	NOT NULL	Indicates if the patient is Inpatient or all other options (outpatient, ED, Nursing Home, Jail). True indicates inpatient, false indicates all other values. Value is only required in non-community settings
EPRESCRIPTION	PATIENTIHI	VARCHAR(50)	NULL	Patient Individual Health Identifier
EPRESCRIPTION	PATIENTMEDICAREFAMILYNAME	VARCHAR(255)	NULL	Family Name on Medicare Card
EPRESCRIPTION	PATIENTMEDICAREFIRSTNAME	VARCHAR(255)	NULL	First name on Medicare card
EPRESCRIPTION	PATIENTMEDICARENUMBER	VARCHAR(15)	NULL	Medicare number excluding subnumerate
EPRESCRIPTION	PATIENTMEDICARESUBNUMERATE	CHAR(1)	NULL	Medicare number Including subnumerate
EPRESCRIPTION	PATIENTMEDICAREVALIDTO	DATE	NULL	Medicare number Valid to date
EPRESCRIPTION	PATIENTMOBILENUMBER	VARCHAR(20)	NULL	Patient mobile number
EPRESCRIPTION	PATIENTNUMBER	VARCHAR(20)	NULL	Patient number from local pharmacy database
EPRESCRIPTION	PATIENTPHONENUMBER	VARCHAR(20)	NULL	Patient Phone Number
EPRESCRIPTION	PATIENTPOSTCODE	VARCHAR(10)	NULL	Patient PostCode
EPRESCRIPTION	PATIENT_RESERVED_01	VARCHAR(50)	NULL	RACFID (Residential Aged Care Facility ID)
EPRESCRIPTION	PATIENT_RESERVED_02	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION	PATIENT_RESERVED_03	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION	PATIENT_RESERVED_04	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION	PATIENT_RESERVED_05	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION	PATIENTSEX	CHAR(1)	NULL	M, F, O, U (Male, Female, Other, Undefined)
EPRESCRIPTION	PATIENTSTATE	VARCHAR(40)	NULL	VIC NSW ACT QLD NT WA SA TAS
EPRESCRIPTION	PATIENTSUBURB	VARCHAR(50)	NULL	Patient Suburb
EPRESCRIPTION	PATIENTTITLE	VARCHAR(30)	NULL	Patient salutation
EPRESCRIPTION	PATIENTUNIQUEID	VARCHAR(20)	NULL	Indicates patient unique id

EPRESCRIPTION	PAT_ID	INT	NULL	Patient ID - Link to patient table
EPRESCRIPTION	PAT_SITE_SID	SMALLINT	NULL	To match i.Pharmacy patient site
EPRESCRIPTION	PHARMACISTFAMILYNAME	VARCHAR(255)	NULL	Surname of dispensing pharmacist
EPRESCRIPTION	PHARMACISTFIRSTNAME	VARCHAR(255)	NULL	First name of dispensing pharmacist
EPRESCRIPTION	PHARMACYADDRESS1	VARCHAR(50)	NULL	Address1 of pharmacy
EPRESCRIPTION	PHARMACYADDRESS2	VARCHAR(50)	NULL	Address2 of Pharmacy
EPRESCRIPTION	PHARMACYAPPROVALNUMBER	VARCHAR(20)	NULL	PBS Approval Number.
EPRESCRIPTION	PHARMACYDISPENSERAHPRANUMBER	VARCHAR(50)	NULL	Pharmacist AHPRA Number (unique Registration identifier)
EPRESCRIPTION	PHARMACYDISPENSERHPII	VARCHAR(50)	NULL	Pharmacist Health Provider Identifier (Individual) (HPI-I)
EPRESCRIPTION	PHARMACYEMAIL	VARCHAR(50)	NULL	Pharmacy email address
EPRESCRIPTION	PHARMACYHPIO	VARCHAR(50)	NULL	Pharmacy Health Provider Identifier (Organisation) (HPI-O)
EPRESCRIPTION	PHARMACYNAME	VARCHAR(255)	NULL	Name of pharmacy
EPRESCRIPTION	PHARMACYPHONENUMBER	VARCHAR(20)	NULL	Pharmacy phonenumber
EPRESCRIPTION	PHARMACYPOSTCODE	VARCHAR(10)	NULL	Pharmacy postcode
EPRESCRIPTION	PHARMACY_RESERVED_01	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION	PHARMACY_RESERVED_02	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION	PHARMACY_RESERVED_03	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION	PHARMACY_RESERVED_04	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION	PHARMACY_RESERVED_05	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION	PHARMACYSTATE	VARCHAR(40)	NULL	VIC NSW ACT QLD NT WA SA TAS
EPRESCRIPTION	PHARMACYSUBURB	VARCHAR(50)	NULL	Pharmacy Suburb
EPRESCRIPTION	PRACTICEADDRESS1	VARCHAR(50)	NULL	Indicates prescriber Address1
EPRESCRIPTION	PRACTICEADDRESS2	VARCHAR(50)	NULL	Indicates prescriber Address2
EPRESCRIPTION	PRACTICEEMAIL	VARCHAR(50)	NULL	Indicates prescriber email
EPRESCRIPTION	PRACTICENAME	VARCHAR(50)	NULL	Indicates prescriber name

EPRESCRIPTION	PRACTICEPOSTCODE	VARCHAR(5)	NULL	Indicates prescriber Postcode
EPRESCRIPTION	PRACTICESTATE	VARCHAR(3)	NULL	VIC NSW ACT QLD NT WA SA TAS
EPRESCRIPTION	PRACTICESUBURB	VARCHAR(50)	NULL	Indicates prescriber suburb
EPRESCRIPTION	PRESCRIBERAHPRANUMBER	VARCHAR(50)	NULL	Prescriber AHPRA Number (unique Registration identifier)
EPRESCRIPTION	PRESCRIBERHPID	VARCHAR(50)	NULL	Prescriber Health Provider Identifier (Individual) (HPI-I)
EPRESCRIPTION	PRESCRIBERHPID_O	VARCHAR(50)	NULL	Prescriber Health Provider Identifier (Organisation) (HPI-O)
EPRESCRIPTION	PRESCRIBINGSYSTEMUSED	VARCHAR(30)	NULL	Prescribing software used to create prescription
EPRESCRIPTION	PRESCRIBERTYPE	VARCHAR(5)	NOTNULL	Prescriber Type - M=Medical Practitioner ; E = Eye/Optomestrist ; U=nurse ; F=midwife ; D=Dentist ; V=Veterinarian ; T=Podiatrist; C=pharmacist
EPRESCRIPTION	PRIVACY_STAT_IND	CHAR(1)	NOTNULL	Indicates ETP1 (paper ePrescription) or ETP2 (paperless ePrescription)
EPRESCRIPTION	REPEATCREATORCONFORMANCEID	VARCHAR(255)	NULL	The conformance ID of the software creating the Repeat Authorisation.
EPRESCRIPTION	REPOSITORYSOFTUNIQUEID	VARCHAR(255)	NULL	The conformance ID of the PES from where prescription is downloaded by Dispense system.
EPRESCRIPTION	SCID_XID	VARCHAR(20)	NOTNULL	Script identifier (SCID) - uniquely identifies an ePrescription in eRx.
EPRESCRIPTION	SITE_SID	SMALLINT	NOTNULL	Dispensing site ID - Link to dispense table
EPRESCRIPTION	SMS	VARCHAR(15)	NULL	The mobile phone Value (Electronic Address) for use when sending an ePrescription token to the patient via SMS.
EPRESCRIPTION	SOURCETYPE	VARCHAR(20)	NULL	'Prescriber' or 'Dispenser'.
EPRESCRIPTION	URI	VARCHAR(1024)	NULL	The unique resource identifier URL for the ePrescription.
EPRESCRIPTION_ANNOTATION	ANNO_VALUE	VARCHAR(8000)	NULL	To allow user to provide details in annotation

EPRESCRIPTION_ANNOTATION	CREATED_DT	DATETIME	NOTNULL	Date and time that the record was created.
EPRESCRIPTION_ANNOTATION	ESCRPT_ANNOT_ID	INT	NOTNULL	Unique annotation identifier
EPRESCRIPTION_ANNOTATION	ESCRPT_ITEM_ID	INT	NOTNULL	Link to the ePrescription item
EPRESCRIPTION_ANNOTATION	LAST_UPDATED_BY	VARCHAR(30)	NOTNULL	Code of the user who last modified the record.
EPRESCRIPTION_ANNOTATION	LAST_UPDATED_DT	DATETIME	NOTNULL	Date and time that the row was last modified.
EPRESCRIPTION_ANNOTATION	SITE_SID	SMALLINT	NOTNULL	Site identifier - Link to site table
EPRESCRIPTION_ANNOTATION	SUPPLY_NBR	INT	NOTNULL	0 for original Prescription and sequence number for Dispensing (e.g. 1 for original dispense, 2 for first repeat)
EPRESCRIPTION_BASKET	BSKT_NOTE	VARCHAR(1024)	NULL	Basket Notes
EPRESCRIPTION_BASKET	BSKT_STAT_CD	VARCHAR(5)	NULL	'AVAIL' (Available) when the record is created. 'PART' (Partially Available) where EPRESCRIPTION_ITEM.avail_ind=Y for at least one item and the other item(s) have EPRESCRIPTION_ITEM.avail_ind=N. 'NAV' when all item(s) for the basket have EPRESCRIPTION_ITEM.avail_ind=N.
EPRESCRIPTION_BASKET	CREATED_DT	DATETIME	NOTNULL	Date and time that the row was created.
EPRESCRIPTION_BASKET	ESCRPT_BSKT_ID	INT	NOTNULL	escript basket id
EPRESCRIPTION_BASKET	LAST_UPDATED_BY	VARCHAR(30)	NOTNULL	Code of the user who last modified the record.
EPRESCRIPTION_BASKET	LAST_UPDATED_DT	DATETIME	NOTNULL	Date and time that the row was last modified.

EPRESCRIPTION_BASKET	PICKUP_DT	DATETIME	NULL	To store Pickup date from Queued eprescription search and select
EPRESCRIPTION_BASKET	PICKUP_HRS	DATETIME	NULL	To store Pickup date from Queued eprescription search and select
EPRESCRIPTION_BASKET	PICKUP_MINS	INT	NULL	Number of minutes before patient will pick up dispensed items
EPRESCRIPTION_BASKET	PICKUP_TYPE	VARCHAR(20)	NOTNULL	To store pickup type as 'Waiting' or 'Later'
EPRESCRIPTION_BASKET	SITE_SID	SMALLINT	NOTNULL	Site identifier - Link to site table
EPRESCRIPTION_BASKET	URGENT_IND	CHAR(1)	NOTNULL	Indicates urgent basket
EPRESCRIPTION_ITEM	AVAIL_IND	CHAR(1)	NULL	Created as 'Y' when the item is downloaded and queued, then 'N' when processing is started.
EPRESCRIPTION_ITEM	BRANDSUBSTITUTIONALLOWED	VARCHAR(5)	NOTNULL	Indicates whether brand substitution is allowed or not by the prescriber
EPRESCRIPTION_ITEM	CONTROLLEDSUBSTANCEREFERENCE	VARCHAR(30)	NULL	The jurisdictional reference number related to provision of certain controlled substances
EPRESCRIPTION_ITEM	CREATED_DT	DATETIME	NOTNULL	Date and time that the row was created.
EPRESCRIPTION_ITEM	DISPENSEDATE	DATE	NULL	Date of dispensing
EPRESCRIPTION_ITEM	DISPENSEDITEMDESCRIPTION	VARCHAR(300)	NULL	The Product Description for the dispensed item
EPRESCRIPTION_ITEM	DISPENSEDITEMFORM	VARCHAR(50)	NULL	The Form for the dispensed item
EPRESCRIPTION_ITEM	DISPENSEDITEMGENERICNAME	VARCHAR(280)	NULL	The Generic Description for the dispensed item
EPRESCRIPTION_ITEM	DISPENSEDQUANTITY	NUMERIC(18,8)	NULL	Quantity of dispensing
EPRESCRIPTION_ITEM	DISPENSEDITEMSTRENGTH	VARCHAR(100)	NULL	The Strength for the dispensed item, as it relates to Quantity
EPRESCRIPTION_ITEM	DISPENSEDITEMTRADENAME	VARCHAR(280)	NULL	The Brand Description for the dispensed item

EPRESCRIPTION_ITEM	DISPENSEDITEMUNIQUEID	VARCHAR(20)	NULL	orig_dspn_id
EPRESCRIPTION_ITEM	DISPENSEDITEM_RESERVED_01	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION_ITEM	DISPENSEDITEM_RESERVED_02	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION_ITEM	DISPENSEDITEM_RESERVED_03	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION_ITEM	DISPENSEDITEM_RESERVED_04	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION_ITEM	DISPENSEDITEM_RESERVED_05	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION_ITEM	DISP_AMT_CODE_SYSTEM	VARCHAR(255)	NULL	Australian Medicines Terminology - Version used
EPRESCRIPTION_ITEM	DISP_AMT_CTPP	VARCHAR(50)	NULL	Australian Medicines Terminology - Containered Trade Product Pack
EPRESCRIPTION_ITEM	DISP_AMT_MP	VARCHAR(50)	NULL	Australian Medicines Terminology - Medicinal Product
EPRESCRIPTION_ITEM	DISP_AMT_MPP	VARCHAR(50)	NULL	Australian Medicines Terminology - Medicinal Product Pack
EPRESCRIPTION_ITEM	DISP_AMT_MPUU	VARCHAR(50)	NULL	Australian Medicines Terminology - Medicinal Product Unit of Use
EPRESCRIPTION_ITEM	DISP_AMT_TP	VARCHAR(50)	NULL	Australian Medicines Terminology - Trade Product
EPRESCRIPTION_ITEM	DISP_AMT_TPP	VARCHAR(50)	NULL	Australian Medicines Terminology - Trade Product Pack
EPRESCRIPTION_ITEM	DISP_AMT_TPUU	VARCHAR(50)	NULL	Australian Medicines Terminology - Trade Product Unit of Use
EPRESCRIPTION_ITEM	DISP_AMT_VERSION	VARCHAR(255)	NULL	Each AMTv3 release is versioned based on a date and has a version identifier
EPRESCRIPTION_ITEM	DISP_EXTEMPORANEOUSDESCRIPTION	VARCHAR(400)	NULL	Description of extemporaneous item
EPRESCRIPTION_ITEM	DISP_ISEXTEMP	VARCHAR(5)	NULL	True or false. Flag to denote if item is a PBS extemp item

EPRESCRIPTION_ITEM	DISP_ITEMBARCODE	VARCHAR(30)	NULL	Current barcode/EAN/APN/UPN for the item
EPRESCRIPTION_ITEM	DISP_PATIENTINSTRUCTIONS	VARCHAR(250)	NULL	Directions for the dispensed item
EPRESCRIPTION_ITEM	DISP_PBSCODE	VARCHAR(6)	NULL	PBS Code for the dispensed item if available
EPRESCRIPTION_ITEM	DISP_PBSMANUFACTURERCODE	VARCHAR(2)	NULL	PBS Manuf Code for the dispensed item if available
EPRESCRIPTION_ITEM	DISP_PRIMARY_MEDICATION_CODE	VARCHAR(255)	NULL	A primary code is the code associated with a native (or interface) terminology implementation
EPRESCRIPTION_ITEM	DISP_THERAPEUTICGOODIDENTIFICATIONCODE	VARCHAR(255)	NULL	The plain code symbol defined by the Therapeutic Good code system, or an expression in a syntax defined by the code system which describes the concept
EPRESCRIPTION_ITEM	DISP_THERAPEUTICGOODIDENTIFICATIONCODESYSTEMNAME	VARCHAR(255)	NULL	The common name of the Therapeutic Good coding system
EPRESCRIPTION_ITEM	DISP_THERAPEUTICGOODIDENTIFICATIONCODESYSTEM	VARCHAR(255)	NULL	Specifies the Therapeutic Good Code system that defines the code. Code systems shall be referred to by an Object Identifier, which allows unambiguous reference to standard code systems and other local codeSystems
EPRESCRIPTION_ITEM	DISP_THERAPEUTICGOODIDENTIFICATIONCODESYSTEMVERSION	VARCHAR(255)	NULL	If applicable, a version descriptor defined specifically for the given Therapeutic Good Code system
EPRESCRIPTION_ITEM	DISP_THERAPEUTICGOODIDENTIFICATIONDISPLAYNAME	VARCHAR(255)	NULL	A name or title for the Therapeutic Good code, under which the sending system shows the code value to its users
EPRESCRIPTION_ITEM	DOCTORNOTES	VARCHAR(255)	NULL	Freeform message from Doctor to Pharmacist
EPRESCRIPTION_ITEM	EMERGENCYSUPPLY	VARCHAR(5)	NULL	True if prescription is supplied for an Owing Script dispensing

EPRESCRIPTION_ITEM	ESCRPT_BSKT_ID	INT	NULL	escript basket id, links item to basket number
EPRESCRIPTION_ITEM	ESCRPT_ITEM_ID	INT	NOTNULL	Unique eprescription item identifier
EPRESCRIPTION_ITEM	HOSPITALPROVIDERNUMBER	VARCHAR(15)	NULL	Hospital provider number for dispensed item
EPRESCRIPTION_ITEM	ITEMFORM	VARCHAR(50)	NULL	Form of prescribed item
EPRESCRIPTION_ITEM	ITEMGENERICNAME	VARCHAR(280)	NULL	1 - Name of chemical/generic ingredient(s). For PBS items, as defined by PBS Schedule. For non-PBS items, no universal standard exists, so at this point in time is just as it appears in each vendor's software. 2 - Extemporaneous Description if prescribing as Compounding item.
EPRESCRIPTION_ITEM	ITEMGENERICINTENTION	VARCHAR(1)	NOTNULL	Item written by Brand/Trade name or generically. B=Brand, G=Generic
EPRESCRIPTION_ITEM	ITEMSTATUS	VARCHAR(5)	NULL	Item Status is populated i.e A=Active, O=Owing, X=Cancelled, D=Deferred
EPRESCRIPTION_ITEM	ITEMSTRENGTH	VARCHAR(100)	NULL	Strength of item. For PBS items, as defined by PBS Schedule. For non-PBS items, no universal standard exists, so at this point in time is just as it appears in each vendor's software

EPRESCRIPTION_ITEM	ITEMTRADENAME	VARCHAR(280)	NULL	1- Item trade name. For PBS items, as defined by PBS Schedule. For non-PBS items, no universal standard exists, so at this point in time is just as it appears in each vendor's software. 2 - Item Generic name if prescribing as Ingredient/Generically. (Item Trade name in the bracket at the end if needs to specify brand name) - AIP Compliant 3 - Extemporaneous Description if prescribing as Compounding item.
EPRESCRIPTION_ITEM	ITEMUNIQUEID	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION_ITEM	LAST_UPDATED_BY	VARCHAR(30)	NOTNULL	Code of the user who last modified the record.
EPRESCRIPTION_ITEM	LAST_UPDATED_DT	DATETIME	NOTNULL	Date and time that the row was last modified.
EPRESCRIPTION_ITEM	LOCALSCRIPTNUMBER	VARCHAR(20)	NULL	Local identifier for the dispensed item
EPRESCRIPTION_ITEM	MYSLCONSENT	CHAR(1)	NOTNULL	Indicates where the patient has consented to Active original/repeat/deferred item being sent to My Script List or not
EPRESCRIPTION_ITEM	NUMBEROFREPEATSAUTHORIZED	INT	NOTNULL	Number of Repeats
EPRESCRIPTION_ITEM	ORIGINALPHARMACYAPPROVALNUMBER	VARCHAR(20)	NULL	Pharmacy approval number which first processed the original script (as per repeat form)
EPRESCRIPTION_ITEM	ORIGINALSCRIPTNUMBER	VARCHAR(20)	NULL	Script number of first dispensing, as per repeat form
EPRESCRIPTION_ITEM	PATIENTSAFETYNETCONTRIBUTION	VARCHAR(50)	NULL	PRF value for PBS items
EPRESCRIPTION_ITEM	PBS_DVAAUTHORITYNUMBER	VARCHAR(10)	NULL	Prescription Authority Number

EPRESCRIPTION_ITEM	PHARMACYAPPROVALNUMBER	VARCHAR(20)	NULL	Pharmacy approval number which first processed the original script
EPRESCRIPTION_ITEM	PHARMACISTINITIALS	VARCHAR(30)	NULL	Initials of dispensing pharmacist
EPRESCRIPTION_ITEM	PHARMACYNOTES	VARCHAR(255)	NULL	Freeform notes from Pharmacist for Doctor or subsequent Pharmacist - not currently used
EPRESCRIPTION_ITEM	PHONEAPPROVALAUTHORITYNUMBER	VARCHAR(10)	NULL	Streamline Authority Number where applicable
EPRESCRIPTION_ITEM	PHARM_XID	VARCHAR(20)	NOTNULL	Indicates dispensing Pharmacy
EPRESCRIPTION_ITEM	PRESCRIPTIONDATE	DATETIME	NOTNULL	Date of prescribing/original prescribing date
EPRESCRIPTION_ITEM	PRESCRIBERSCRIPTNUMBER	VARCHAR(255)	NULL	The prescription number of script. Printed on the paper prescription and is the script number issued from the prescribing software
EPRESCRIPTION_ITEM	PRESC_AMT_CODE_SYSTEM	VARCHAR(255)	NULL	Australian Medicines Terminology - Version used (1.2.36.1.2001.1004.100)
EPRESCRIPTION_ITEM	PRESC_AMT_CTPP	VARCHAR(50)	NULL	Australian Medicines Terminology - Containered Trade Product Pack Code
EPRESCRIPTION_ITEM	PRESC_AMT_MP	VARCHAR(50)	NULL	Australian Medicines Terminology - Medicinal Product Code
EPRESCRIPTION_ITEM	PRESC_AMT_MPP	VARCHAR(50)	NULL	Australian Medicines Terminology - Medicinal Product Pack Code
EPRESCRIPTION_ITEM	PRESC_AMT_MPUU	VARCHAR(50)	NULL	Australian Medicines Terminology - Medicinal Product Unit of Use Code
EPRESCRIPTION_ITEM	PRESC_AMT_TP	VARCHAR(50)	NULL	Australian Medicines Terminology - Trade Product Code
EPRESCRIPTION_ITEM	PRESC_AMT_TPP	VARCHAR(50)	NULL	Australian Medicines Terminology - Trade Product Pack Code
EPRESCRIPTION_ITEM	PRESC_AMT_TPUU	VARCHAR(50)	NULL	Australian Medicines Terminology - Trade Product Unit of Use Code

EPRESCRIPTION_ITEM	PRESC_AMT_VERSION	VARCHAR(255)	NULL	Each AMTv3 release is versioned based on a date and has a version identifier
EPRESCRIPTION_ITEM	PRESC_EXTEMPORANEOUSDESCRIPTION	VARCHAR(400)	NULL	Description of extemporaneous item (e.g. Olive Oil 10% in Aqueous Cream)
EPRESCRIPTION_ITEM	PRESC_ISEXTEMP	VARCHAR(5)	NOTNULL	true or false. Flag to denote if item is written extemporaneously (e.g. Olive Oil 10% in Aqueous Cream)
EPRESCRIPTION_ITEM	PRESC_ITEMBARCODE	VARCHAR(30)	NULL	Current barcode/EAN/APN/UPN for the item
EPRESCRIPTION_ITEM	PRESC_PATIENTINSTRUCTIONS	VARCHAR(250)	NULL	Directions for the prescribed item
EPRESCRIPTION_ITEM	PRESC_PBSCODE	VARCHAR(6)	NULL	As defined in PBS Schedule. If item is written privately but is a PBS item, will still have a PBS Code, and field PrivatePrescription should be TRUE. If item is private and no PBS Code is available, will be blank
EPRESCRIPTION_ITEM	PRESC_PBSMANUFACTURERCODE	VARCHAR(2)	NULL	PBS Manuf Code for prescribed item
EPRESCRIPTION_ITEM	PRESC_PRIMARY_MEDICATION_CODE	VARCHAR(255)	NULL	A primary code is the code associated with a native (or interface) terminology implementation
EPRESCRIPTION_ITEM	PRESC_THERAPEUTICGOODIDENTIFICATIONCODE	VARCHAR(255)	NULL	The plain code symbol defined by the Therapeutic Good code system, or an expression in a syntax defined by the code system which describes the concept
EPRESCRIPTION_ITEM	PRESC_THERAPEUTICGOODIDENTIFICATIONCODESYSTEMNAME	VARCHAR(255)	NULL	The common name of the Therapeutic Good coding system

EPRESCRIPTION_ITEM	PRESC_THERAPEUTICGOODIDENTIFICATIONCODESYSTEM	VARCHAR(255)	NULL	Specifies the Therapeutic Good Code system that defines the code. Code systems shall be referred to by an Object Identifier, which allows unambiguous reference to standard code systems and other local codeSystems
EPRESCRIPTION_ITEM	PRESC_THERAPEUTICGOODIDENTIFICATIONCODESYSTEMVERSION	VARCHAR(255)	NULL	If applicable, a version descriptor defined specifically for the given Therapeutic Good Code system
EPRESCRIPTION_ITEM	PRESC_THERAPEUTICGOODIDENTIFICATIONDISPLAYNAME	VARCHAR(255)	NULL	A name or title for the Therapeutic Good code, under which the sending system shows the code value to its users
EPRESCRIPTION_ITEM	PRESCRIBEDITEM_RESERVE_D_01	VARCHAR(50)	NULL	Maximum quantity authorised to dispense (in words if a controlled drug)
EPRESCRIPTION_ITEM	PRESCRIBEDITEM_RESERVE_D_02	VARCHAR(50)	NULL	Hospital Provider Number
EPRESCRIPTION_ITEM	PRESCRIBEDITEM_RESERVE_D_03	VARCHAR(400)	NULL	AIP (active ingredient prescribing) compliant Drug Description for display to Dispenser
EPRESCRIPTION_ITEM	PRESCRIBEDITEM_RESERVE_D_04	VARCHAR(50)	NULL	The name of the pharmacy the prescription is to be dispensed (if required by NSW health)
EPRESCRIPTION_ITEM	PRESCRIBEDITEM_RESERVE_D_05	VARCHAR(50)	NULL	Field included for future use
EPRESCRIPTION_ITEM	PRIVATENONSWITCHABLE	VARCHAR(5)	NULL	Used to indicate a PBS prescription that has been dispensed at a non-PBS pharmacy. It cannot be changed back to a PBS claimable prescription after that point.
EPRESCRIPTION_ITEM	PRIVATEPRESCRIPTION	VARCHAR(5)	NOTNULL	Describes if item is a private (non-PBS) item. True or false. If item is a PBS item but prescribed privately, this field should be TRUE, and field PBSCode should be populated

EPRESCRIPTION_ITEM	PRIVACYSTatement	VARCHAR(5)	NULL	To indicate paperless ePrescription item ('true') versus paper ePrescription item ('false')
EPRESCRIPTION_ITEM	QUANTITY	NUMERIC(18,8)	NOTNULL	Quantity of item on prescription as an integer
EPRESCRIPTION_ITEM	QUANTITYEXTENDED	VARCHAR(1024)	NULL	Quantity field for prescribing systems that use unusual values (quantity should normally be provided in the Quantity field unless advised otherwise), as text
EPRESCRIPTION_ITEM	REASONFORPRESCRIBING	VARCHAR(255)	NULL	Indicates prescribing reason
EPRESCRIPTION_ITEM	REGULATION24	VARCHAR(5)	NOTNULL	Indicates original and all repeats can be dispensed at same time
EPRESCRIPTION_ITEM	REPEATINTERVALS	INT	NULL	Number of days that must elapse before item can be re-dispensed
EPRESCRIPTION_ITEM	ROUTEADMINISTRATION	VARCHAR(20)	NULL	Prescribed Route of Administration
EPRESCRIPTION_ITEM	RTACID	VARCHAR(10)	NULL	RTACid identifies the IVF Reproductive Technology Accreditation Committee (RTAC) accredited unit number supplied for S100 IVF claims
EPRESCRIPTION_ITEM	SCHEDULENUMBER	VARCHAR(2)	NULL	Indicates prescribed Schedule Number
EPRESCRIPTION_ITEM	SCID_XID	VARCHAR(20)	NOTNULL	Unique Script Identifier (SCID) - scanned from token/barcode and used to download ePrescription from eRx
EPRESCRIPTION_ITEM	SCRIPTCLASS	VARCHAR(5)	NULL	Indicates Script class i.e P=Private ; T=ScheduleThree ; N=PBSEntitlement ; G=PBSEntitlement ; C=PBSEntitlement ; E=PBSEntitlement ; B=DrsBag ; R=Repat ; D=Dental

EPRESCRIPTION_ITEM	SCRIPTCTGANNOTATION	VARCHAR(255)	NULL	Script annotation for Closing the Gap (CTG). Values are: Non-CTG=NULL ; Handwritten=CTG00B (zero zero B) ; CTG Annotation=CTGnnX
EPRESCRIPTION_ITEM	SCRIPTTYPE	VARCHAR(10)	NULL	Indicates Script type B = Dr'sBag ; E = Eye/Optom ; D = Dental ; P = Private ; N = NHS ; R = Repeat ; T = Schedule3 ; U = Nurse ; F = Midwife
EPRESCRIPTION_ITEM	SENDTOPHARMACY	VARCHAR(255)	NULL	'DosingPoint', 'StagedSupply' or 'RepeatOnFile' as received in the ePrescription from eRx
EPRESCRIPTION_ITEM	SEQUENCE_ID	INT	NOT NULL	Sequential number which differentiates multiple items which have the same SCID
EPRESCRIPTION_ITEM	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EPRESCRIPTION_ITEM	SNOMED_CTREASONFORPRESCRIBE	VARCHAR(15)	NULL	A clinical indication or reason to prescribe a medicine. Should contain the SNOMED- CT coded indication if selected by a prescriber during their workflow
EPRESCRIPTION_ITEM	STATE_XID	VARCHAR(20)	NOTNULL	The State value as present in eRx e.g. Active, Pending, Dispensed or Deferred.
EPRESCRIPTION_ITEM	SUPPLYNUMBER	INT	NULL	Number of times dispensed - 0 for deferred, 1 for original, 2 for first repeat,...
EPRESCRIPTION_ITEM	TAXINVOICEVALUE	VARCHAR(50)	NULL	Patient medications for tax invoice rebates.
EPRESCRIPTION_ITEM	UNLISTEDITEMREPATAUTHORITY	VARCHAR(5)	NOTNULL	Flag to denote item is an unlisted repeat authority - true or false
EPRESCRIPTION_ITEM	UNUSUALDOSEFLAG	VARCHAR(5)	NOTNULL	Unusual dose indicator (true or false) where dose is outside recommended range.
EPRESCRIPTION_ITEM	UNUSUALQTYFLAG	VARCHAR(5)	NOTNULL	Replicates the underlining of a quantity on a paper prescription. Currently defined as any quantity that differs from PBS quantity - true or false

EPRESCRIPTION_ITEM	URGENT_IND	CHAR(1)	NOTNULL	Urgency indicator
EPRESCRIPTION_ITEM	USER_CD	VARCHAR(5)	NULL	User code for logged on user
EPRESCRIPTION_ITEM	VERIFIED_BY	VARCHAR(30)	NULL	Indicates Verified By user who processed the item
EPRESCRIPTION_ITEM	VERIFIED_DT	DATETIME	NULL	Indicates Verified Date for processing the item
ERROR_LOG	APPLICATION_CD	VARCHAR (15)	NOT NULL	Name of the application/function
ERROR_LOG	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
ERROR_LOG	ERR_COMMENT_NOTE	VARCHAR (255)	NULL	Error Comment Note
ERROR_LOG	ERR_MSG_NOTE	VARCHAR (255)	NOT NULL	Error Message Note
ERROR_LOG	ERR_TITLE_DESC	VARCHAR (40)	NOT NULL	Error Title Description
ERROR_LOG	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
ERROR_LOG	USER_CD	VARCHAR (15)	NULL	Code to identify the user
EXTERNAL_LINK	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
EXTERNAL_LINK	CURR_IND	CHAR(1)	NOT NULL	Indicates if the record is current.
EXTERNAL_LINK	EXL_ACCESS_CD	VARCHAR (5)	NOT NULL	Access type of external link
EXTERNAL_LINK	EXL_LINK_ID	INT	NOT NULL	External link identifier
EXTERNAL_LINK	EXL_LINK_NOTE	VARCHAR (255)	NULL	Notes for the external link
EXTERNAL_LINK	FILE_PATH	VARCHAR(2500)	NULL	File path from which the external link is invoked
EXTERNAL_LINK	FUNC_KEY_XID	VARCHAR (20)	NOT NULL	Function key details for the external link
EXTERNAL_LINK	INVOCATE_PARM	VARCHAR(2500)	NULL	Invocation parameters for the external link
EXTERNAL_LINK	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
EXTERNAL_LINK	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
EXTERNAL_LINK	NAME_XID	VARCHAR (20)	NOT NULL	Name details for the external link
EXTERNAL_LINK	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EXTERNAL_MESSAGE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.

EXTERNAL_MESSAGE	EXT_MSG_ID	INT	NOT NULL	Unique External Message ID
EXTERNAL_MESSAGE	EXT_MSG_STAT_CD	VARCHAR (5)	NOT NULL	External Message Status Code - link to list_of_val
EXTERNAL_MESSAGE	EXT_MSG_TYPE_CD	VARCHAR (5)	NOT NULL	Message type
EXTERNAL_MESSAGE	KEY_1_ID	INT	NULL	unique ID of Message Reference Table1
EXTERNAL_MESSAGE	KEY_1_SID	SMALLINT	NULL	Unique Site Id for Message Reference Table1
EXTERNAL_MESSAGE	KEY_1_XID	VARCHAR (20)	NULL	Unique short code for Message Reference Table1
EXTERNAL_MESSAGE	KEY_2_ID	INT	NULL	unique ID of Message Reference Table2
EXTERNAL_MESSAGE	KEY_2_SID	SMALLINT	NULL	Unique Site Id for Message Reference Table2
EXTERNAL_MESSAGE	KEY_2_XID	VARCHAR (20)	NULL	Unique short code for Message Reference Table2
EXTERNAL_MESSAGE	KEY_3_ID	INT	NULL	unique ID of Message Reference Table3
EXTERNAL_MESSAGE	KEY_3_SID	SMALLINT	NULL	Unique Site Id for Message Reference Table3
EXTERNAL_MESSAGE	KEY_3_XID	VARCHAR (20)	NULL	Unique short code for Message Reference Table3
EXTERNAL_MESSAGE	KEY_4_ID	INT	NULL	unique ID of Message Reference Table4
EXTERNAL_MESSAGE	KEY_4_SID	SMALLINT	NULL	Unique Site Id for Message Reference Table4
EXTERNAL_MESSAGE	KEY_4_XID	VARCHAR (20)	NULL	Unique short code for Message Reference Table4
EXTERNAL_MESSAGE	KEY_5_ID	INT	NULL	unique ID of Message Reference Table5
EXTERNAL_MESSAGE	KEY_5_SID	SMALLINT	NULL	Unique Site Id for Message Reference Table5
EXTERNAL_MESSAGE	KEY_5_XID	VARCHAR (20)	NULL	Unique short code for Message Reference Table5
EXTERNAL_MESSAGE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
EXTERNAL_MESSAGE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
EXTERNAL_MESSAGE	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EXTERNAL_MESSAGE_ADC	ADC_BRAND_DESC	VARCHAR(40)	NULL	ADC Brand Description
EXTERNAL_MESSAGE_ADC	ADC_CONC_UNIT_DESC	VARCHAR(8000)	NULL	ADC Concentration Unit Description
EXTERNAL_MESSAGE_ADC	ADC_CONC_VAL	VARCHAR(255)	NULL	ADC Concentration Value

EXTERNAL_MESSAGE_A DC	ADC_FORM_DESC	VARCHAR(255)	NULL	ADC Form Description
EXTERNAL_MESSAGE_A DC	ADC_GENERIC_DESC	VARCHAR(1024)	NULL	ADC Generic Description
EXTERNAL_MESSAGE_A DC	ADC_GRP_ID	INT	NOT NULL	ADC Group id - Link to adc_group table
EXTERNAL_MESSAGE_A DC	ADC_IDENT_XID	VARCHAR(20)	NULL	ADC ident Xid
EXTERNAL_MESSAGE_A DC	ADC_MSG_CD	VARCHAR(5)	NOT NULL	To Update MAD,MDL,MUP,OMS,ZPM which type of transaction - Link to list_of_val table
EXTERNAL_MESSAGE_A DC	ADC_POCKET_CD	VARCHAR(5)	NULL	To Update Count,Assigned,De-assigned - Link to list_of_val table
EXTERNAL_MESSAGE_A DC	ADC_PROD_UPD_CD	VARCHAR(5)	NULL	To Update PROD,GTIN
EXTERNAL_MESSAGE_A DC	ADC_STR_UNIT_DESC	VARCHAR(8000)	NULL	ADC Strength Unit Description
EXTERNAL_MESSAGE_A DC	ADC_STR_VAL	VARCHAR(255)	NULL	ADC Strength Value
EXTERNAL_MESSAGE_A DC	ADC_STRENGTH_DESC	VARCHAR(255)	NULL	ADC Strength Description
EXTERNAL_MESSAGE_A DC	ADC_TOT_VOL_UNIT_DESC	VARCHAR(8000)	NULL	ADC Total Volume Unit Description
EXTERNAL_MESSAGE_A DC	ADC_TOT_VOL_VAL	VARCHAR(255)	NULL	ADC Total Volume Value
EXTERNAL_MESSAGE_A DC	ADC_TYPE_CD	VARCHAR(5)	NOT NULL	To Update MDDSP,OMNCL,PYXIS
EXTERNAL_MESSAGE_A DC	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
EXTERNAL_MESSAGE_A DC	EXT_MSG_ADC_ID	INT	NOT NULL	External Message ADC ID
EXTERNAL_MESSAGE_A DC	EXT_MSG_STAT_CD	VARCHAR(5)	NOT NULL	External Message Status Code - link to list_of_val
EXTERNAL_MESSAGE_A DC	GTIN_XID	VARCHAR(20)	NULL	GTIN - link to gtin table

EXTERNAL_ MESSAGE_A DC	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
EXTERNAL_ MESSAGE_A DC	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
EXTERNAL_ MESSAGE_A DC	MESSAGE_CONTROLID_NOT E	VARCHAR(255)	NULL	The unique identifier from the InputRequest message, found in MSH-10.
EXTERNAL_ MESSAGE_A DC	PROD_ID	INT	NULL	Product Identifier - Link to product table
EXTERNAL_ MESSAGE_A DC	SCHEDULE_SHORT	VARCHAR(10)	NULL	Product Schedule Short Description
EXTERNAL_ MESSAGE_A DC	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EXTERNAL_ MESSAGE_B ILL	CHARGE_TYPE_CD	VARCHAR(5)	NOT NULL	Charge Type code
EXTERNAL_ MESSAGE_B ILL	CLAIMABLE_IND	CHAR(1)	NOT NULL	Claimable Indicator value
EXTERNAL_ MESSAGE_B ILL	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
EXTERNAL_ MESSAGE_B ILL	DSPN_CRE_TYPE_CD	VARCHAR(5)	NOT NULL	Dispense credit Type code
EXTERNAL_ MESSAGE_B ILL	DSPN_DT	DATETIME	NOT NULL	Dispense Date
EXTERNAL_ MESSAGE_B ILL	DSPN_ID	INT	NOT NULL	ID to link to the dispense table
EXTERNAL_ MESSAGE_B ILL	DSPN_REV_TYPE_CD	VARCHAR(5)	NULL	Dispense Reversal Type code
EXTERNAL_ MESSAGE_B ILL	DSPN_STAT_CD	VARCHAR(5)	NOT NULL	Dispense Status code
EXTERNAL_ MESSAGE_B ILL	EXT_MSG_BILL_ID	INT	NOT NULL	unique ID of External Message Bill table, for the site
EXTERNAL_ MESSAGE_B ILL	EXT_MSG_STAT_CD	VARCHAR(5)	NOT NULL	Link to list_of_val table for status
EXTERNAL_ MESSAGE_B ILL	EXT_MSG_TYPE_CD	VARCHAR(5)	NOT NULL	Message type is either BILLD or BILLC.

EXTERNAL_MESSAGE_BILL	INVC_STAT_CD	VARCHAR(5)	NULL	Patient Invoice Status code
EXTERNAL_MESSAGE_BILL	INVC_TYPE_CD	VARCHAR(5)	NULL	Patient Invoice Type code
EXTERNAL_MESSAGE_BILL	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
EXTERNAL_MESSAGE_BILL	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
EXTERNAL_MESSAGE_BILL	ORIG_DSPN_ID	INT	NOT NULL	Original Dispense Identifier
EXTERNAL_MESSAGE_BILL	RECORD_UPD_IND	CHAR(1)	NOT NULL	Indicator to reset the record for processing
EXTERNAL_MESSAGE_BILL	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EXTERNAL_MESSAGE_PES	CONVERSATION_ID	VARCHAR(255)	NULL	GUID value to link the PES request and response messages
EXTERNAL_MESSAGE_PES	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
EXTERNAL_MESSAGE_PES	DSPN_ID	INT	NULL	ID to link to the dispense table
EXTERNAL_MESSAGE_PES	EXT_MSG_PES_ID	INT	NOT NULL	Unique ID of External Message Pes table, for the site
EXTERNAL_MESSAGE_PES	EXT_MSG_STAT_CD	VARCHAR(5)	NOT NULL	Status code - Link to list_of_val table for ext_msg_stat_cd
EXTERNAL_MESSAGE_PES	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
EXTERNAL_MESSAGE_PES	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
EXTERNAL_MESSAGE_PES	PES_OPERATION	VARCHAR(20)	NULL	Message type sent to PES
EXTERNAL_MESSAGE_PES	PES_OPERATION_RESULT	VARCHAR(20)	NULL	Column result of the operation
EXTERNAL_MESSAGE_PES	PHARM_XID	VARCHAR(20)	NULL	Pharmacy Identifier - link to pharmacy table

EXTERNAL_MESSAGE_PES	RESPONSE_DT	DATETIME	NULL	Date and time that the response was received from e-Rx.
EXTERNAL_MESSAGE_PES	RESPONSE_DTZ	DATETIMEOFFSET(3)	NULL	Store the date and time of response was received from e-RX(ePrescription)
EXTERNAL_MESSAGE_PES	SCID_XID	VARCHAR(20)	NULL	Unique Script Identifier (SCID) - links later dispensing actions back to original dispensing. Obtained from PES adapter via scid_cache table.
EXTERNAL_MESSAGE_PES	SENT_DT	DATETIME	NULL	Date and time that the request was sent to e-Rx.
EXTERNAL_MESSAGE_PES	SEQUENCE_ID	INT	NULL	Sequence value for ePrescription item
EXTERNAL_MESSAGE_PES	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EXTERNAL_MESSAGE_ROBOT	BATCH_NBR	VARCHAR(20)	NULL	Column to save batch number
EXTERNAL_MESSAGE_ROBOT	BATCH_EXP_DT	DATETIME	NULL	Column to save batch experianace date
EXTERNAL_MESSAGE_ROBOT	CHUTE_XID	VARCHAR(20)	NULL	Chute identifier - link to chute table
EXTERNAL_MESSAGE_ROBOT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
EXTERNAL_MESSAGE_ROBOT	EXT_MSG_ROB_ID	INT	NOT NULL	Unique ID of External Message Robot table, for the site
EXTERNAL_MESSAGE_ROBOT	EXT_MSG_STAT_CD	VARCHAR(5)	NOT NULL	Status code - Link to list_of_val table for ext_msg_stat_cd
EXTERNAL_MESSAGE_ROBOT	GTIN_XID	VARCHAR(20)	NULL	GTIN - link to gtin table
EXTERNAL_MESSAGE_ROBOT	INPUT_DELIVERY_NBR	VARCHAR(20)	NULL	Column to save input delivery number
EXTERNAL_MESSAGE_ROBOT	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
EXTERNAL_MESSAGE_ROBOT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.

EXTERNAL_MESSAGE_ROBOT	MESSAGE_CONTROLID_NOT E	VARCHAR(255)	NULL	The unique identifier from the InputRequest message, found in MSH-10.
EXTERNAL_MESSAGE_ROBOT	NEW_DELIVERY_IND	CHAR(1)	NULL	Whether the an InputRequest message is for a goods receipt item ('Y'), or a stock return item ('N').
EXTERNAL_MESSAGE_ROBOT	ORDER_QTY	NUMERIC(18, 8)	NULL	Order quantity, for Input Request messages.
EXTERNAL_MESSAGE_ROBOT	PACKAGE_INDEX_ID	INT	NULL	The package index id from the InputRequest message, if present.
EXTERNAL_MESSAGE_ROBOT	PART_PACK_QTY	NUMERIC(18,8)	NULL	Column to save part pack quantity value
EXTERNAL_MESSAGE_ROBOT	PRIORITY_ID	INT	NULL	Transaction priority for sending and receiving of interface messages - link to robot_interface table.
EXTERNAL_MESSAGE_ROBOT	PROD_ID	INT	NULL	Product Identifier - Link to product table
EXTERNAL_MESSAGE_ROBOT	ROBOT_ID	INT	NOT NULL	Robot Identifier - Link to robot table
EXTERNAL_MESSAGE_ROBOT	ROBOT_SERVICE_EXT_XID	VARCHAR(20)	NULL	robot service external xid value
EXTERNAL_MESSAGE_ROBOT	ROBOT_STORE_EXT_XID	VARCHAR(20)	NULL	robot store Id value
EXTERNAL_MESSAGE_ROBOT	ROBOT_TYPE_CD	VARCHAR(5)	NOT NULL	Robot type / model - Link to list_of_val table using robot_type_cd
EXTERNAL_MESSAGE_ROBOT	ROBOT_XID	VARCHAR(20)	NOT NULL	User created code to indicate the code for the robot.
EXTERNAL_MESSAGE_ROBOT	SERIAL_NBR	VARCHAR(20)	NULL	Column to save serial number
EXTERNAL_MESSAGE_ROBOT	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EXTERNAL_MESSAGE_ROBOT	SITE_XID	VARCHAR(20)	NULL	site xid value
EXTERNAL_MESSAGE_ROBOT	STORE_XID	VARCHAR(20)	NULL	store xid value

EXTERNAL_ MESSAGE_R OBOT	TRAN_ID	INR	NOT NULL	Transaction Identifier for OutputRequest message. A single transaction e.g. Distribution may have >1 item, based on Items per Message value. For InputRequests the ord_id is present where the Type is 'Goods Receipt'
EXTERNAL_ MESSAGE_R OBOT	TRAN_TYPE_CD	VARCHAR(5)	NOT NULL	Transaction type - link to list_of_val table for rob_tran_type_cd
EXTERNAL_ MESSAGE_R OBOT	URGENT_IND	CHAR(1)	NOT NULL	Urgency indicator
EXTERNAL_ MESSAGE_R OBOT	WKSTN_ID	VARCHAR(5)	NOT NULL	Workstation ID - link to workstation table.
EXTERNAL_ ORG	COST_CNTR_XID	VARCHAR (20)	NULL	Cost Centre Code - Link to the Cost centre table
EXTERNAL_ ORG	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
EXTERNAL_ ORG	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
EXTERNAL_ ORG	EXT_ORG_ADDR_1	VARCHAR (40)	NULL	External Organisation Address 1
EXTERNAL_ ORG	EXT_ORG_ADDR_2	VARCHAR (40)	NULL	External Organisation Address 2
EXTERNAL_ ORG	EXT_ORG_ADDR_3	VARCHAR (40)	NULL	External Organisation Address 3
EXTERNAL_ ORG	EXT_ORG_ADDR_4	VARCHAR (40)	NULL	External Organisation Address 4
EXTERNAL_ ORG	EXT_ORG_CNTRY	VARCHAR (30)	NULL	External Organisation Country
EXTERNAL_ ORG	EXT_ORG_CONT_NAME	VARCHAR (255)	NULL	External Organisation Contact Name
EXTERNAL_ ORG	EXT_ORG_FAX	VARCHAR (15)	NULL	External Organisation Fax Number
EXTERNAL_ ORG	EXT_ORG_NAME	VARCHAR (255)	NULL	External Organisation Name
EXTERNAL_ ORG	EXT_ORG_NOTE	VARCHAR (255)	NULL	External Organisation Note
EXTERNAL_ ORG	EXT_ORG_PHONE	VARCHAR (15)	NULL	External Organisation Phone number
EXTERNAL_ ORG	EXT_ORG_POSTCODE	VARCHAR (10)	NULL	External Organisation Postal Code
EXTERNAL_ ORG	EXT_ORG_XID	VARCHAR (20)	NOT NULL	Unique identifier for External Organisation
EXTERNAL_ ORG	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
EXTERNAL_ ORG	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.

EXTERNAL_	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
ORG				
EXTERNAL_	EXT_PYMT_ID	INT	NOT NULL	This is used to identify the External Payment ID
PAYMENT				
EXTERNAL_	PAT_ID	INT	NOT NULL	Patient identifier - Link to patient table
PAYMENT				
EXTERNAL_	PAT_SITE_SID	SMALLINT	NOT NULL	Site associated with patient record - Link to site table
PAYMENT				
EXTERNAL_	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
PAYMENT				
EXTERNAL_	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
PRF				
EXTERNAL_	EXT_PRF_AMT	NUMERIC(18,8)	NOT NULL	External PRF Amount
PRF				
EXTERNAL_	EXT_PRF_DT	DATETIME	NOT NULL	External PRF Date
PRF				
EXTERNAL_	EXT_PRF_ID	INT	NOT NULL	Unique identifier for External Prescription Record Form (PRF)
PRF				
EXTERNAL_	EXT_PRF_NOTE	VARCHAR (255)	NULL	External PRF note
PRF				
EXTERNAL_	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
PRF				
EXTERNAL_	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
PRF				
EXTERNAL_	PAT_ID	INT	NOT NULL	Patient identifier - Link to patient table
PRF				
EXTERNAL_	PAT_SITE_SID	SMALLINT	NOT NULL	Site associated with patient record - Link to site table
PRF				
SITE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
SITE	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
SITE	GLOBAL_LOCATION_NBR	VARCHAR (13)	NULL	Global Location Number
SITE	HOSP_PROVIDER_NBR	VARCHAR (15)	NULL	Used by Community Pharmacies; allows PBS Hospital Medication Chart dispensings for Private Hospitals
SITE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
SITE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
SITE	ORIG_SITESHORT_XID	VARCHAR (20)	NULL	Original Site Short code
SITE	PAT_REF_SITE_SID	SMALLINT	NOT NULL	Patient Reference site id - Link to site table
SITE	SITE_ABN	VARCHAR (14)	NULL	ABN No. for the Site
SITE	SITE_ADDR_1	VARCHAR (40)	NULL	Site Address 1
SITE	SITE_ADDR_2	VARCHAR (40)	NULL	Site Address 2
SITE	SITE_ADDR_3	VARCHAR (40)	NULL	Site Address 3
SITE	SITE_ADDR_4	VARCHAR (40)	NULL	Site Address 4
SITE	SITE_CNTRY	VARCHAR (30)	NULL	Site Country

SITE	SITE_DESC	VARCHAR (40)	NOT NULL	Site Description
SITE	SITE_FAX_PHONE	VARCHAR (15)	NULL	Site Fax No.
SITE	SITE_HI_XID	VARCHAR(20)	NULL	Healthcare Provider Identifier - Organisation (HPI-O)
SITE	SITE_NOTE	VARCHAR (255)	NULL	Note for the Site
SITE	SITE_PHONE	VARCHAR (15)	NULL	Site Phone No.
SITE	SITE_POSTCODE	VARCHAR (10)	NULL	Site Postal Code
SITE	SITE_SHORT	VARCHAR (10)	NOT NULL	Short Name for Site
SITE	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
SITE	SITE_XID	VARCHAR (20)	NOT NULL	Unique Code for Site
SITE	TAX_GROUP_ABN	VARCHAR (14)	NULL	Group ABN no. for Taxation
STOCK_ADJ UST	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
STOCK_ADJ UST	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
STOCK_ADJ UST	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
STOCK_ADJ UST	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
STOCK_ADJ UST	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
STOCK_ADJ UST	STK_ADJ_DT	DATETIME	NOT NULL	Stock Adjustment Date
STOCK_ADJ UST	STK_ADJ_ID	INT	NOT NULL	Stock Adjustment Identifier
STOCK_ADJ UST	STK_ADJ_NOTE	VARCHAR (255)	NULL	Stock Adjustment Notes
STOCK_ADJ UST	STK_ADJ_STAT_CD	VARCHAR (5)	NOT NULL	Stock Adjustment Status Code - Link to list_of_val table
STOCK_ADJ UST	STK_ADJ_TYPE_CD	VARCHAR (5)	NOT NULL	Stock Adjustment Type Code - Link to list_of_val table
STOCK_ADJ UST	STORE_XID	VARCHAR (20)	NOT NULL	Code to link to the Store table
STOCK_ADJ UST	VERIFIED_BY	VARCHAR (30)	NULL	Code of the User who verifies
STOCK_ADJ UST_EXTR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
STOCK_ADJ UST_EXTR	EXTR_ID	INT	NOT NULL	Unique ID used to identify the extraction
STOCK_ADJ UST_EXTR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
STOCK_ADJ UST_EXTR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
STOCK_ADJ UST_EXTR	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table

STOCK_ADJ UST_EXTR	STK_ADJ_ID	INT	NOT NULL	Stock Adjustment Identifier - Link to stock_adjust table
STOCK_TAK E	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
STOCK_TAK E	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
STOCK_TAK E	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
STOCK_TAK E	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
STOCK_TAK E	PDE_IND	CHAR (1)	NOT NULL	PDE indicator
STOCK_TAK E	ROBOT_XID	VARCHAR (20)	NULL	User created code to indicate the code for the robot.
STOCK_TAK E	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
STOCK_TAK E	ST_ROBOT_IND	CHAR (1)	NOT NULL	Stcok take Robot indicator
STOCK_TAK E	STK_TAKE_DT	DATETIME	NOT NULL	Stock Take Date
STOCK_TAK E	STK_TAKE_ID	INT	NOT NULL	Unique Stock Take Identifier, for the site
STOCK_TAK E	STK_TAKE_NOTE	VARCHAR (255)	NULL	Stock Take Notes
STOCK_TAK E	STK_TAKE_STAT_CD	VARCHAR (5)	NOT NULL	Stock Take Status Code - Link to list_of_val table
STOCK_TAK E	STK_TAKE_TYPE_CD	VARCHAR (5)	NOT NULL	Stock Take type Code - Link to list_of_val table
STOCK_TAK E	STORE_XID	VARCHAR (20)	NOT NULL	Code to link to the Store table
STOCK_TAK E	VERIFIED_BY	VARCHAR (30)	NULL	Code of the User who verifies
STOCK_TAK E_EXTR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
STOCK_TAK E_EXTR	EXTR_ID	INT	NOT NULL	Unique ID for the extract, for the site
STOCK_TAK E_EXTR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
STOCK_TAK E_EXTR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
STOCK_TAK E_EXTR	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
STOCK_TAK E_EXTR	STK_TAKE_ID	INT	NOT NULL	Stock Take Identifier - Link to stock_take table
STOCK_VAL UATION	AWP_PACK_COST	NUMERIC(18,8)	NULL	AWP cost
STOCK_VAL UATION	LOC_ID	INT	NOT NULL	Location ID - link to location table
STOCK_VAL UATION	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
STOCK_VAL UATION	PVV_VALUE	NUMERIC(18,8)	NULL	PVV value

STOCK_VAL UATION	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
STOCK_VAL UATION	TRAN_DT	DATETIME	NOT NULL	Transaction date
STOCK_VAL UATION	TRAN_INVEN_QTY	NUMERIC(18,8)	NULL	Transaction inventory quantity
STORE	ABC_ANALYSIS_DAYS	SMALLINT	NULL	ABC analysis (days)
STORE	ANNIVERSARY_DT	DATETIME	NULL	Date at ABC analysis done
STORE	COST_CNTR_XID	VARCHAR (20)	NULL	Cost Centre Code - Link to the Cost centre table
STORE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
STORE	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
STORE	CYC_STKTAK_FRQ_CD	VARCHAR(5)	NULL	Type of Stock take frequency - Link to list_of_val table
STORE	CYC_STKTAK_FRQ_DAYS	SMALLINT	NOT NULL	Stock take Frequency (days)
STORE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
STORE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
STORE	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
STORE	STORE_DESC	VARCHAR (40)	NOT NULL	Store Description
STORE	STORE_NOTE	VARCHAR (255)	NULL	Store notes
STORE	STORE_XID	VARCHAR (20)	NOT NULL	Unique code for store, for the site
STORE	STR_ADDR_1	VARCHAR (40)	NULL	Address detail for a store
STORE	STR_ADDR_2	VARCHAR (40)	NULL	Address detail for a store
STORE	STR_ADDR_3	VARCHAR (40)	NULL	Address detail for a store
STORE	STR_ADDR_4	VARCHAR (40)	NULL	Address detail for a store
STORE	STR_COUNTRY	VARCHAR (30)	NULL	Country detail for a store
STORE	STR_FAX	VARCHAR (15)	NULL	Fax detail for a store
STORE	STR_LOCK_IND	CHAR (1)	NOT NULL	Store Lock Indicator
STORE	STR_PHONE	VARCHAR (15)	NULL	Phone detail for a store
STORE	STR_POSTCODE	VARCHAR (10)	NULL	Post code detail for a store
STORE	STR_RESUPP_METH_CD	VARCHAR (5)	NOT NULL	Store Resupply Method Code - Link to list_of_val table
STORE	SUPP_SITE_SID	SMALLINT	NULL	Supplier Site Identifier
STORE	SUPP_STORE_XID	VARCHAR (20)	NULL	Supplier Store Xid
SUPP_CATL	CONTRACT_REF_XID	VARCHAR (20)	NULL	Contract Reference Number
SUPP_CATL	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
SUPP_CATL	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.

SUPP_CATL	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
SUPP_CATL	PRICE_BRK_SIZE	INT	NULL	Price Break Size
SUPP_CATL	PRICE_START_DT	DATETIME	NULL	Price Start Date
SUPP_CATL	PRICE_STOP_DT	DATETIME	NULL	Price Stop Date
SUPP_CATL	PROD_ID	INT	NULL	Product Identifier - Link to product table
SUPP_CATL	PROD_IND	CHAR (1)	NULL	Not used in this version
SUPP_CATL	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
SUPP_CATL	SUPP_CATL_DESC_NOTE	VARCHAR (255)	NULL	Supplier Catalogue Description
SUPP_CATL	SUPP_CATL_ID	INT	NOT NULL	Unique Supplier Catalog Identifier, for the site
SUPP_CATL	SUPP_CATL_NOTE	VARCHAR (255)	NULL	Supplier Catalogue Note
SUPP_CATL	SUPP_CATL_XID	VARCHAR (20)	NOT NULL	Supplier's Catalogue Code
SUPP_CATL	SUPP_EXT_PRICE	NUMERIC(18,8)	NOT NULL	Supplier Price with Tax
SUPP_CATL	SUPP_PRICE	NUMERIC(18,8)	NOT NULL	Supplier Price
SUPP_CATL	SUPP_XID	VARCHAR (20)	NOT NULL	Code used to link to the Supplier record
SUPP_CATL	TAX_AMT	NUMERIC(18,8)	NOT NULL	Tax amount
SUPP_CATL	UOM_ID	INT	NULL	Unit of Measurement Identifier - Link to UOM table
SUPP_COST_CNTR	COST_CNTR_ACC_NBR	VARCHAR (20)	NOT NULL	Cost Center Account Number
SUPP_COST_CNTR	COST_CNTR_XID	VARCHAR (20)	NOT NULL	Cost Centre Code - Link to the Cost centre table
SUPP_COST_CNTR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
SUPP_COST_CNTR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
SUPP_COST_CNTR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
SUPP_COST_CNTR	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
SUPP_COST_CNTR	SUPP_XID	VARCHAR (20)	NOT NULL	Code used to link to the Supplier record
SUPP_MAST	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
SUPP_MAST	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
SUPP_MAST	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.

SUPP_MAST	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
SUPP_MAST	SUPP_MAST_ADDR_1	VARCHAR (40)	NULL	Supplier Master Address 1
SUPP_MAST	SUPP_MAST_ADDR_2	VARCHAR (40)	NULL	Supplier Master Address 2
SUPP_MAST	SUPP_MAST_ADDR_3	VARCHAR (40)	NULL	Supplier Master Address 3
SUPP_MAST	SUPP_MAST_ADDR_4	VARCHAR (40)	NULL	Supplier Master Address 4
SUPP_MAST	SUPP_MAST_CNTRY	VARCHAR (30)	NULL	Supplier Master country
SUPP_MAST	SUPP_MAST_EMAIL	VARCHAR	NULL	Supplier Master email address
SUPP_MAST	SUPP_MAST_FAX	VARCHAR (15)	NULL	Supplier Master Fax
SUPP_MAST	SUPP_MAST_NAME	VARCHAR (255)	NULL	Supplier Master name
SUPP_MAST	SUPP_MAST_NOTE	VARCHAR (255)	NULL	Supplier Master note
SUPP_MAST	SUPP_MAST_PHONE	VARCHAR (15)	NULL	Supplier Master Phone
SUPP_MAST	SUPP_MAST_POSTCODE	VARCHAR (10)	NULL	Supplier Master Postcode
SUPP_MAST	SUPP_MAST_XID	VARCHAR (20)	NOT NULL	Supplier Master code
SUPPLIER	ACC_NBR_WITH_SUPP	VARCHAR (20)	NULL	Account with supplier
SUPPLIER	ACC_PAY_NBR	VARCHAR (20)	NULL	Accounts Payable Number
SUPPLIER	ACK_ACCESS_CD	VARCHAR (5)	NULL	Acknowledgement Access type - Link to list_of_val table
SUPPLIER	ACK_ACCESS_PATH	VARCHAR (255)	NULL	Acknowledgement Access path
SUPPLIER	ACK_FILE_PATH	VARCHAR (255)	NULL	EDI from File Location
SUPPLIER	ACK_METHOD_CD	VARCHAR (5)	NULL	Acknowledgement method code - Link to list_of_val table
SUPPLIER	ALT_ACC_PAY_NBR	VARCHAR (15)	NULL	Alternate A/C Payable
SUPPLIER	CATL_DEC_PLACE_SID	SMALLINT	NOT NULL	Catalog Decimal Places. The number of decimal places to be stored in <u>supp_catl.suppl_price</u> .
SUPPLIER	COMPOUNDER_XID	VARCHAR(20)	NULL	Column to list the compounder_xid dropdown in prescription details
SUPPLIER	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
SUPPLIER	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
SUPPLIER	DESP_ACCESS_CD	VARCHAR (5)	NULL	Despatch Access type - Link to list_of_val table

SUPPLIER	DESP_ACCESS_PATH	VARCHAR (255)	NULL	Despatch Access path
SUPPLIER	DESP_FILE_PATH	VARCHAR (255)	NULL	Despatch from File Location
SUPPLIER	DESP_METHOD_CD	VARCHAR (5)	NULL	Despatch method code - Link to list_of_val table
SUPPLIER	EDI_ACCESS_CD	VARCHAR (5)	NULL	EDI Access type - Link to list_of_val table
SUPPLIER	EDI_ACCESS_PATH	VARCHAR (255)	NULL	EDI Access Path
SUPPLIER	EDI_FILE	VARCHAR (255)	NULL	EDI File stores the executable
SUPPLIER	EDI_FILE_PATH	VARCHAR (255)	NULL	EDI to file location
SUPPLIER	EDI_METHOD_CD	VARCHAR (5)	NULL	EDI method code - Link to list_of_val table
SUPPLIER	GEN_SUPP_CATL_IND	CHAR (1)	NOT NULL	Generate supplier Catalog indicator
SUPPLIER	INV_ACCESS_CD	VARCHAR (5)	NULL	Invoice Access type - Link to list_of_val table
SUPPLIER	INV_ACCESS_PATH	VARCHAR (255)	NULL	invoice Access path
SUPPLIER	INV_DEC_PLACE_SID	SMALLINT	NOT NULL	Invoice Decimal Places. The number of decimal places to be stored in the gr_item table.
SUPPLIER	INV_FILE_PATH	VARCHAR (255)	NULL	Invoice from File Location
SUPPLIER	INV_METHOD_CD	VARCHAR (5)	NULL	Invoice method code - Link to list_of_val table
SUPPLIER	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
SUPPLIER	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
SUPPLIER	MIN_ORD_AMT	NUMERIC(18,8)	NOT NULL	Minimum Order Amount
SUPPLIER	NAT_SUPP_CD	VARCHAR (15)	NULL	National supplier code
SUPPLIER	OVERSEAS_IMPORT_IND	CHAR (1)	NOT NULL	Overseas Import indicator
SUPPLIER	SALES_TAX_INC_IND	CHAR (1)	NOT NULL	Sales Tax Indicator
SUPPLIER	SCT_AUTO_AMD_IND	CHAR (1)	NOT NULL	Auto Update Catalog indicator
SUPPLIER	SCT_AUTO_CRE_IND	CHAR (1)	NOT NULL	Auto Create Catalog indicator
SUPPLIER	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
SUPPLIER	SUP_PREF_SEQ	INT	NULL	Preferred Supplier sequence
SUPPLIER	SUPP_ABN	VARCHAR (14)	NULL	ABN number of the supplier
SUPPLIER	SUPP_ADDR_1	VARCHAR (40)	NULL	Supplier Address 1
SUPPLIER	SUPP_ADDR_2	VARCHAR (40)	NULL	Supplier Address 2
SUPPLIER	SUPP_ADDR_3	VARCHAR (40)	NULL	Supplier Address 3
SUPPLIER	SUPP_ADDR_4	VARCHAR (40)	NULL	Supplier Address 4
SUPPLIER	SUPP_CNTRY	VARCHAR (30)	NULL	Supplier Country
SUPPLIER	SUPP_CONT_NAME	VARCHAR (255)	NULL	Supplier Contact Name

SUPPLIER	SUPP_EAN	VARCHAR (13)	NULL	Supplier EAN Code
SUPPLIER	SUPP_EMAIL	STRING	NULL	Supplier email address
SUPPLIER	SUPP_FAX	VARCHAR (15)	NULL	Supplier Fax
SUPPLIER	SUPP_LEAD_TIME	SMALLINT	NOT NULL	Identify the supplier takes the no. of days to deliver the items
SUPPLIER	SUPP_MAST_XID	VARCHAR (20)	NULL	Supplier Master code - Link to supp_master table
SUPPLIER	SUPP_NAME	VARCHAR (255)	NULL	Supplier Name
SUPPLIER	SUPP_NOTE	VARCHAR (255)	NULL	Supplier Note
SUPPLIER	SUPP_PHONE	VARCHAR (15)	NULL	Supplier Phone
SUPPLIER	SUPP_POSTCODE	VARCHAR (10)	NULL	Supplier Postcode
SUPPLIER	SUPP_SET_CD	VARCHAR (5)	NULL	Supplier category - Link to list_of_val table
SUPPLIER	SUPP_XID	VARCHAR (20)	NOT NULL	Code used to link to the Supplier record
SUPPLIER	TFR_METHOD_CD	VARCHAR (5)	NULL	Send Process - Link to list_of_val table
TEAM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
TEAM	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
TEAM	FIN_STRUCT_ID	INT	NULL	Financial Structure Identifier - Link to fin_struct table
TEAM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
TEAM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
TEAM	OTHER_NAME	VARCHAR (255)	NULL	Other name
TEAM	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
TEAM	TEAM_NAME	VARCHAR (255)	NULL	Team Name
TEAM	TEAM_NOTE	VARCHAR (255)	NULL	Team note
TEAM	TEAM_XID	VARCHAR (20)	NOT NULL	Unique code for Team, for the site
TFR_ITEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
TFR_ITEM	INPUT_INVEN_QTY	NUMERIC (18,8)	NULL	Column to save inventory input quantity for robotic store transfer
TFR_ITEM	INPUT_PACK_QTY	NUMERIC(18,8)	NULL	Column to save pack quantity
TFR_ITEM	INPUT_STAT_CD	VARCHAR (5)	NULL	Column to save input status for robotic store transfer
TFR_ITEM	INVEN_DELIVERED_QTY	NUMERIC(18,8)	NULL	Column to save inventory delivered quantity value
TFR_ITEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
TFR_ITEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.

TFR_ITEM	NR_LOC_ID	INT	NULL	Non-robot Store Location ID - Link to location table; to accept remainder stock for a part pack robot transfer.
TFR_ITEM	PACK_DELIVERED_QTY	NUMERIC(18,8)	NULL	Pack Delivered Quantity
TFR_ITEM	PICK_MSG_COUNT	INT	NULL	Count of successful OutputMessages received from PillPick robot.
TFR_ITEM	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
TFR_ITEM	RANEG_BIN_TRAN_ID	INT	NULL	Robot adjustment (negative) - link to bin_tran table; to record the movement of part pack remainder amount out of robot bin.
TFR_ITEM	RAPOS_BIN_TRAN_ID	INT	NULL	Robot adjustment (positive) - link to bin_tran table; to record the movement of part pack remainder amount into a non-robot bin.
TFR_ITEM	RECV_BIN_BATCH_ID	INT	NULL	Receive Bin batch identifier
TFR_ITEM	RECV_BIN_TRAN_ID	INT	NULL	Receiving Bin Transaction ID - Link to bin_tran table
TFR_ITEM	RECV_LOC_ID	INT	NULL	Receiving Location ID - Link to location table
TFR_ITEM	RECV_SITE_SID	SMALLINT	NOT NULL	Receiving Site identifier - Link to site table
TFR_ITEM	REPLACE_FLAG	CHAR(1)	NULL	Replacement flag
TFR_ITEM	ROB_RETURN_QTY	NUMERIC(18,8)	NULL	Part pack amount to be returned to robot
TFR_ITEM	ROB_ROUNDED_QTY	NUMERIC(18,8)	NULL	Rounded up pack quantity for transfer using a robot bin.
TFR_ITEM	ROBOT_STAT_CD	VARCHAR(5)	NOT NULL	Code used to identify whether the item uses a robot bin or not (R/NR).
TFR_ITEM	ROBOT_TRAN_ID	INT	NULL	Robot transaction Identifier - Link to external_message_robot table for the particular Request message.
TFR_ITEM	SUBST_IND	CHAR(1)	NULL	Substitution flag
TFR_ITEM	SUPP_BIN_BATCH_ID	INT	NULL	Supply Bin batch identifier
TFR_ITEM	SUPP_BIN_TRAN_ID	INT	NULL	Supplying Bin Transaction ID - Link to bin_tran table
TFR_ITEM	SUPP_LOC_ID	INT	NULL	Location code for supplying site - Link to location table
TFR_ITEM	SUPP_SITE_SID	SMALLINT	NOT NULL	Supplier Site Identifier - Link to site table

TFR_ITEM	TFR_ID	INT	NOT NULL	Unique Store Transfer Identifier, for the site
TFR_ITEM	TFR_ITEM_BATCH	VARCHAR (10)	NULL	Transfer Item Batch
TFR_ITEM	TFR_ITEM_ID	INT	NOT NULL	Unique ID for Transfer Item, for the site
TFR_ITEM	TFR_ITEM_STAT_CD	VARCHAR (5)	NOT NULL	Transfer Item Status code - Link to list_of_val table
TFR_ITEM	TFR_ITEM_TYPE_CD	VARCHAR (5)	NOT NULL	Transfer Item Type code - Link to list_of_val table
TFR_ITEM	TFR_QTY	NUMERIC(18,8)	NOT NULL	Transfer Quantity
TFR_ITEM	TFR_RQST_ITEM_ID	INT	NULL	Transfer Request Item Identifier
TFR_ITEM	TI_BATCH_EXP_DT	DATETIME	NULL	Transfer Item Batch Expiry Date
TFR_ITEM	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
TFR_ITEM	URGENT_IND	CHAR (1)	NOT NULL	Urgency Indicator
TFR_ITEM	WARD_BOX_NBR	VARCHAR(255)	NULL	The box numbers for the boxes that the ward stock is delivered in, as received from the robot Output message.
TFR_REQUE ST	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
TFR_REQUE ST	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
TFR_REQUE ST	CUST_REF	VARCHAR (20)	NULL	Customer Reference
TFR_REQUE ST	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
TFR_REQUE ST	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
TFR_REQUE ST	PDE_IND	CHAR (1)	NOT NULL	PDE indicator
TFR_REQUE ST	RQST_SITE_SID	SMALLINT	NOT NULL	Requesting Site ID - Link to site table
TFR_REQUE ST	RQST_STORE_XID	VARCHAR (20)	NOT NULL	Requesting Store Code - Link to store table
TFR_REQUE ST	SUGG_IND	CHAR (1)	NOT NULL	Suggested Transfer Indicator
TFR_REQUE ST	SUPP_SITE_SID	SMALLINT	NOT NULL	Supplier Site Identifier - Link to site table
TFR_REQUE ST	SUPP_STORE_XID	VARCHAR (20)	NOT NULL	Suppling Store code - Link to store table
TFR_REQUE ST	TFR_RQST_AUTH_BY	VARCHAR (30)	NULL	Code of the user who authorised the transfer request
TFR_REQUE ST	TFR_RQST_AUTH_DT	DATETIME	NULL	Transfer Request Authorised Date

TFR_REQUE ST	TFR_RQST_DT	DATETIME	NOT NULL	Transfer Request Date
TFR_REQUE ST	TFR_RQST_ID	INT	NOT NULL	Unique Transfer Request ID, for the site
TFR_REQUE ST	TFR_RQST_NOTE	VARCHAR (255)	NULL	Transfer Request Note
TFR_REQUE ST	TFR_RQST_STAT_CD	VARCHAR (5)	NOT NULL	Transfer Request Status Code - Link to list_of_val table
TFR_REQUE ST	TFR_RQST_TYPE_CD	VARCHAR (5)	NOT NULL	Transfer Request Type Code - Link to list_of_val table
TFR_REQUE ST	URGENT_IND	CHAR (1)	NOT NULL	Urgency Indicator
TFR_REQUE ST	VERIFIED_BY	VARCHAR (30)	NULL	Code of the User who verifies
TFR_REQUE ST_EXTR	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
TFR_REQUE ST_EXTR	EXTR_ID	INT	NOT NULL	Unique ID used to identify the extract, for the site
TFR_REQUE ST_EXTR	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
TFR_REQUE ST_EXTR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
TFR_REQUE ST_EXTR	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
TFR_REQUE ST_EXTR	TFR_RQST_ID	INT	NOT NULL	Transfer Request ID - Link to transfer request table
TFR_RQST_I TEM	COMMIT_LOC_ID	INT	NULL	Commit location ID - Link to location table
TFR_RQST_I TEM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
TFR_RQST_I TEM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
TFR_RQST_I TEM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
TFR_RQST_I TEM	LOC_ID	INT	NOT NULL	Store Location ID - Link to location table
TFR_RQST_I TEM	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
TFR_RQST_I TEM	REPLACE_FLAG	CHAR(1)	NULL	Replacement flag
TFR_RQST_I TEM	RQST_SITE_SID	SMALLINT	NOT NULL	Requesting Site ID - Link to site table
TFR_RQST_I TEM	SUBST_IND	CHAR(1)	NULL	Substitute flag
TFR_RQST_I TEM	TFR_RQST_ID	INT	NOT NULL	Unique Transfer Request ID, for the site
TFR_RQST_I TEM	TFR_RQST_ITEM_ID	INT	NOT NULL	Transfer Request Item Identifier
TFR_RQST_I TEM	TFR_RQST_QTY	NUMERIC(18,8)	NOT NULL	Transfer Request Quantity

TFR_RQST_ITEM	TRI_STAT_CD	VARCHAR (5)	NOT NULL	Transfer Item status code - Link to list_of_val table
TFR_RQST_ITEM	UOM_ID	INT	NOT NULL	Unit of Measurement Identifier - Link to UOM table
TFR_RQST_ITEM	URGENT_IND	CHAR (1)	NOT NULL	Urgency Indicator
TPN_COMP_RULES	COMP_A_OPERATOR	CHAR (1)	NULL	Component 'A' operator
TPN_COMP_RULES	COMP_A_QTY	NUMERIC(18,8)	NULL	Component 'A' quantity
TPN_COMP_RULES	COMP_A_UOM_XID	VARCHAR (20)	NULL	Component 'A' UOM
TPN_COMP_RULES	COMP_A_XID	VARCHAR (20)	NULL	Component 'A' short description
TPN_COMP_RULES	COMP_B_OPERATOR	CHAR (1)	NULL	Component 'B' operator
TPN_COMP_RULES	COMP_B_QTY	NUMERIC(18,8)	NULL	Component 'B' quantity
TPN_COMP_RULES	COMP_B_UOM_XID	VARCHAR (20)	NULL	Component 'B' UOM - Link to UOM table
TPN_COMP_RULES	COMP_B_XID	VARCHAR (20)	NULL	Component 'B' short description
TPN_COMP_RULES	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
TPN_COMP_RULES	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
TPN_COMP_RULES	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
TPN_COMP_RULES	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
TPN_COMP_RULES	TPNRULES_NOTES	VARCHAR (255)	NULL	TPN rules notes
TPN_COMP_RULES	WARNING_MSG	VARCHAR (255)	NOT NULL	Warning message
TRAN_ADD_VAL	ADD_VAL_AMT	NUMERIC(18,8)	NOT NULL	Added Value Amount
TRAN_ADD_VAL	ADD_VAL_DESC	VARCHAR (40)	NULL	Added Value description
TRAN_ADD_VAL	ADD_VAL_NOTE	VARCHAR (255)	NULL	Added Value Note
TRAN_ADD_VAL	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
TRAN_ADD_VAL	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
TRAN_ADD_VAL	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
TRAN_ADD_VAL	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
TRAN_ADD_VAL	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
TRAN_ADD_VAL	TRAN_ADD_VAL_ID	INT	NOT NULL	Unique ID for Added value, for a site

TRAN_ADD_VAL	TRAN_TYPE_CD	VARCHAR (5)	NOT NULL	Transaction Type Code - Link to list_of_val table
TRAN_TYPE	CALC_BIN_COST_IND	CHAR (1)	NOT NULL	Indicator of Bin Cost calculation
TRAN_TYPE	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
TRAN_TYPE	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
TRAN_TYPE	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
TRAN_TYPE	TRAN_DIR_CD	VARCHAR (5)	NOT NULL	Transaction direction code - Link to list_of_val table
TRAN_TYPE	TRAN_TYPE_CD	VARCHAR (5)	NOT NULL	Transaction Type Code
TRAN_TYPE	TRAN_TYPE_DESC	VARCHAR (40)	NOT NULL	Transaction type description
TRANSFER	BULK_STOCK_IND	CHAR(1)	NOT NULL	Indicates that a bulk stock (ward box) chute was used.
TRANSFER	CHUTE_XID	VARCHAR(20)	NULL	Chute code for robot delivery of the item - link to robot_chute table.
TRANSFER	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
TRANSFER	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
TRANSFER	CUST_REF	VARCHAR (20)	NULL	Customer Reference
TRANSFER	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
TRANSFER	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
TRANSFER	PDE_IND	CHAR (1)	NOT NULL	PDE indicator
TRANSFER	PICK_NTRQ_IND	CHAR(1)	NOT NULL	Pick Not Required Indicator - indicators whether the robot picking step was bypassed or not.
TRANSFER	RECV_PRINT_IND	CHAR (1)	NOT NULL	Flag for Store transfer Picking Slip (RECEIVE) report being printed
TRANSFER	RECV_SITE_SID	SMALLINT	NOT NULL	Receiving Site ID - Link to site table
TRANSFER	RECV_STORE_XID	VARCHAR (20)	NOT NULL	Receiving Store Code - Link to store table
TRANSFER	RECV_VERIFIED_BY	VARCHAR (30)	NULL	Code of the user who Verified the receipt
TRANSFER	ROBOT_STAT_CD	VARCHAR(5)	NULL	Code used to identify whether the item uses a robot bin or not (R/NR).
TRANSFER	SEND_PRINT_IND	CHAR (1)	NOT NULL	Flag for Store transfer Picking Slip (SUPPLY) report being printed
TRANSFER	SEND_VERIFIED_BY	VARCHAR (30)	NULL	Code of user who Verifies the sending

TRANSFER	SUPP_SITE_SID	SMALLINT	NOT NULL	Supplying Site ID - Link to site table
TRANSFER	SUPP_STORE_XID	VARCHAR (20)	NOT NULL	Supplying Store code - Link to store table
TRANSFER	TFR_DT	DATETIME	NOT NULL	Transfer Date
TRANSFER	TFR_ID	INT	NOT NULL	Unique Store Transfer ID, for the site
TRANSFER	TFR_NOTE	VARCHAR (255)	NULL	Transfer Notes
TRANSFER	TFR_STAT_CD	VARCHAR (5)	NOT NULL	Transfer status Code - Link to list_of_val table
TRANSFER	URGENT_IND	CHAR (1)	NOT NULL	Urgency Indicator
TRANSFER	WARD_BOX_NBR	VARCHAR(255)	NULL	The box numbers for the boxes that the ward stock is delivered in, as received from the robot Output message.
TRANSFER_	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
EXTR	EXTR_ID	INT	NOT NULL	Unique ID for the extract, for the site
TRANSFER_	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
EXTR	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
TRANSFER_	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
EXTR	TFR_ID	INT	NOT NULL	Store Transfer ID - Link to transfer table
UNIT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
UNIT	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
UNIT	DISPLAY_SEQ	INT	NOT NULL	Display Sequence
UNIT	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
UNIT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
UNIT	UNIT_CATG_XID	VARCHAR (20)	NOT NULL	Unit Category identifier
UNIT	UNIT_CLASS_CD	VARCHAR (5)	NOT NULL	Unit class - the Unit either relates to Properties or to Attributes.
UNIT	UNIT_DESC	VARCHAR (40)	NOT NULL	Unit description
UNIT	UNIT_PID	INT	NOT NULL	Unit identifier - Link to unit table
UNIT	UNIT_TYPE_CD	VARCHAR (5)	NOT NULL	Unit type - Link to list_of_val table
UNIT	UNIT_XID	VARCHAR (20)	NOT NULL	Unit Code

UOM	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
UOM	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
UOM	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
UOM	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
UOM	UOM_DESC	VARCHAR (40)	NOT NULL	Unit of Measurement description
UOM	UOM_ID	INT	NOT NULL	Unique Unit of Measurement Identifier
UOM	UOM_NOTE	VARCHAR (255)	NULL	Unit of Measurement note
UOM	UOM_SHORT	VARCHAR (10)	NOT NULL	Unit of Measurement Short code
USER_LIST_OF_VAL	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
USER_LIST_OF_VAL	CURR_IND	CHAR (1)	NOT NULL	Indicates if the record is current.
USER_LIST_OF_VAL	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
USER_LIST_OF_VAL	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
USER_LIST_OF_VAL	USER_VALUE_DESC	VARCHAR (40)	NOT NULL	User value Description
USER_LIST_OF_VAL	USER_VALUE_TYPE_CD	VARCHAR (5)	NOT NULL	Value Type Code - Link to list_of_val table
USER_LIST_OF_VAL	USER_VALUE_XID	VARCHAR (20)	NOT NULL	Unqie Value code
USER_LOV_PAT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
USER_LOV_PAT	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
USER_LOV_PAT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
USER_LOV_PAT	PAT_ID	INT	NOT NULL	Patient identifier - Link to patient table
USER_LOV_PAT	PAT_SITE_SID	SMALLINT	NOT NULL	Site associated with patient record - Link to site table
USER_LOV_PAT	USER_VALUE_XID	VARCHAR (20)	NOT NULL	Code for patient - Link to User_list_of_val table
USER_LOV_PROD	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
USER_LOV_PROD	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
USER_LOV_PROD	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
USER_LOV_PROD	PROD_ID	INT	NOT NULL	Product Identifier - Link to product table
USER_LOV_PROD	USER_VALUE_XID	VARCHAR (20)	NOT NULL	Code for product - Link to User_list_of_val table
USER_PWD	ACTIVE_IND	CHAR(1)	NOT NULL	Active flag.

USER_PWD	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
USER_PWD	LAST_UPDATED_BY	VARCHAR(30)	NOT NULL	Code of the user who last modified the record.
USER_PWD	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
USER_PWD	PWD	VARCHAR(15)	NOT NULL	User password in encrypted format
USER_PWD	PWD_ID	INT	NOT NULL	Unique ID used to identify User and password combination
USER_PWD	PWD_SEQ	INT	NOT NULL	Sequence number for the user password.
USER_PWD	USER_CD	VARCHAR(15)	NOT NULL	Code for the user - Link to users table
USER_SETTINGS	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
USER_SETTINGS	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
USER_SETTINGS	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
USER_SETTINGS	PREF_KEY	VARCHAR (20)	NOT NULL	Preference Key name of frame
USER_SETTINGS	PREF_VALUE	VARCHAR (255)	NULL	Preference Key value
USER_SETTINGS	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
USER_SETTINGS	USER_CD	VARCHAR (15)	NOT NULL	Code for the user - Link to users table
USER_SETTINGS	WKSTN_ID	INT	NOT NULL	Workstation identifier - Link to workstation table
USER_SITE_SETTINGS	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
USER_SITE_SETTINGS	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
USER_SITE_SETTINGS	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
USER_SITE_SETTINGS	PREF_KEY	VARCHAR (20)	NOT NULL	Preference Key name of frame
USER_SITE_SETTINGS	PREF_VALUE	VARCHAR (255)	NULL	Preference Key value
USER_SITE_SETTINGS	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
USER_SITE_SETTINGS	USER_CD	VARCHAR (15)	NOT NULL	Code for the user - Link to users table
USER_SITE_SETTINGS	WKSTN_ID	INT	NOT NULL	Workstation identifier - Link to workstation table
USER_WORKSTATION_AUDIT	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
USER_WORKSTATION_AUDIT	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.

USER_WORKSTATION_AUDIT	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
USER_WORKSTATION_AUDIT	LOGGED_IN_DT	DATETIME	NOT NULL	The Date on which the user has logged-in
USER_WORKSTATION_AUDIT	LOGGED_OUT_DT	DATETIME	NULL	The Date on which the user has logged-out
USER_WORKSTATION_AUDIT	PROFILE_CD	VARCHAR (15)	NOT NULL	Profile Type of User
USER_WORKSTATION_AUDIT	SESSION_ID	INT	NOT NULL	Unique ID used to identify the session
USER_WORKSTATION_AUDIT	SITE_SID	SMALLINT	NOT NULL	Site identifier - Link to site table
USER_WORKSTATION_AUDIT	USER_CD	VARCHAR (15)	NOT NULL	Code for the user - Link to users table
USER_WORKSTATION_AUDIT	WKSTN_ID	INT	NOT NULL	Workstation identifier - Link to workstation table
USER_WORKSTATION_AUDIT	WORKGROUP_CD	VARCHAR (255)	NULL	Identifies workgroup
USERS	ACTIVE_FL	CHAR (1)	NOT NULL	Active indicator
USERS	ACTIVE_IND	CHAR(1)	NOT NULL	Active Directory flag
USERS	AD_NAME	VARCHAR (255)	NULL	Active Directory User Name
USERS	CREATED_BY	VARCHAR (30)	NULL	Code of the user who created the record
USERS	CREATED_DT	DATETIME	NOT NULL	Date and time that the row was created.
USERS	CURRENT_PWD	VARCHAR (15)	NOT NULL	Current Password
USERS	DOMAIN_CD	VARCHAR(30)	NULL	Domain name of the Active Directory user
USERS	EARLIEST_PWD	VARCHAR (15)	NULL	Earliest Password
USERS	EMAIL	VARCHAR (60)	NULL	Email
USERS	FIRST_NM	VARCHAR (255)	NULL	First Name
USERS	LAST_UPDATED_BY	VARCHAR (30)	NOT NULL	Code of the user who last modified the record.
USERS	LAST_UPDATED_DT	DATETIME	NOT NULL	Date and time that the row was last modified.
USERS	MED_CHART_USER_CD	VARCHAR(15)	NULL	MedChart user code for use when connecting to MedChart via Secure Invocation in patient windows .

USERS	NHS_USER_IND	CHAR (1)	NOT NULL	NHS User Indicator
USERS	PHONE	VARCHAR (15)	NULL	Phone Number
USERS	PREVIOUS_PWD	VARCHAR (15)	NULL	Previous Password
USERS	PWD_EXPIRY_DT	DATETIME	NOT NULL	Password Expiry date
USERS	REG_HEALTH_PROF_XID	VARCHAR(20)	NULL	Registered Health Professional number i.e. AHPRA number
USERS	SALUTATION	VARCHAR (10)	NULL	Salutation
USERS	SURNAME	VARCHAR (255)	NULL	Surname
USERS	USER_CD	VARCHAR (15)	NOT NULL	Code for the user
USERS	USER_HI_XID	VARCHAR(20)	NULL	Healthcare Provider Identifier - Individual (HPI-I)
USERS	USER_NOTE	VARCHAR (255)	NULL	User Note

