

Parametrix

MX60 FIELD HOW TO

Preflight Checklist

Trimble MX60 · Trimble Mobile Imaging

Printable. One per mission.

Date _____ Operator _____ Vehicle _____

A1 · Before leaving the yard

☐		\$
☐	Mission plan read — route, passes and directions, overlap, hostile stretches	2
☐	Two initialization locations identified	2
☐	Calibration currency confirmed	2
☐	Field record form and this guide on board	2

A2 · Equipment

☐		\$
☐	Optics clean — scanner windows, camera dome	3
☐	Cables sound, no chafe or damage	3
☐	Rack and fixings secure, per the rack's own guide	3
☐	Sensor Unit seated as measured — two people to mount	3, 4
☐	GAMS secure and same antenna type, if fitted	13
☐	DMI secure on a non-steering wheel, if fitted	3
☐	Cables routed clear of doors and moving parts	5

A3 · Power

☐		\$
☐	Supply rated 30 A or more , fused 35 A near the battery	6
☐	Battery healthy and charged	6
☐	Auxiliary battery healthy, if fitted	6
☐	No Battery Protect alarm during preflight	7

A4 • Start-up

☐		\$
☐	Ignition on, supply live	8
☐	Power button held ≥ 15 s	8
☐	LEDs settled to ready	8
☐	TMI reached in Chrome at <code>tmi.mx-scan.net</code>	9
☐	Every sensor present in the device list	9.3

A5 • Settings

☐		\$
☐	DMI activated in Vehicle Settings , lever arm and side set — if fitted	10.1
☐	GAMS activated in Vehicle Settings , lever arm set — if fitted	10.1
☐	Install Height preset correct for this vehicle	10.1
☐	Capture settings set — and which presentation you saw recorded	10.2
☐	Dust filter set deliberately	10.2

A6 • Disk

☐		\$
☐	Correct disk, seated	11
☐	Free space sufficient for the planned mission, with margin	11
☐	USB cable not connected with the disk inside	11

A7 • Initialization

☐		\$
☐	Parked in genuinely open sky	12
☐	Mission started	12
☐	2–3 minutes static	12
☐	Straight ~20 m	12
☐	Speed varied and dynamic steering performed	12
☐	Status reached green — time recorded	14.5

☐		§
☐	Settling time allowed — up to 10 minutes	14.2
☐	Time significant recording began — recorded	14.5

Signed _____