


Algebraic Graphs with Class

by Andrey Mokhov

Christoph Madlener


01.06.2021

Introduction



G_1


Introduction



G_1

$$G = (V, E) \text{ s.t. } E \subseteq V \times V$$


Introduction



$$G_1 = \left(\{1, 2, 3\}, \{(1, 2), (1, 3), (2, 1)\} \right)$$

$$G = (V, E) \text{ s.t. } E \subseteq V \times V$$

Introduction




$$G = (V, E) \text{ s.t. } E \subseteq V \times V$$

$$G_1 = \left(\{1, 2, 3\}, \{(1, 2), (1, 3), (2, 1)\} \right)$$

In Haskell?

```
data G a = G { vs :: Set a, es :: Set (a,a) }
```

Introduction



$$G = (V, E) \text{ s.t. } E \subseteq V \times V$$


$$G_1 = \left(\{1, 2, 3\}, \{(1, 2), (1, 3), (2, 1)\} \right)$$

In Haskell?

```
data G a = G { vs :: Set a, es :: Set (a,a) }
```

```
g1 = G [1,2,3] [(1,2), (1,3), (2,1)]
```

Introduction



$$G = (V, E) \text{ s.t. } E \subseteq V \times V$$

$$G_1 = \left(\{1, 2, 3\}, \{(1, 2), (1, 3), (2, 1)\} \right)$$

In Haskell?


```
data G a = G { vs :: Set a, es :: Set (a,a) }
```

```
g1 = G [1,2,3] [(1,2), (1,3), (2,1)]
```

```
g2 = G [1,2] [(1,3)]
```


$E \not\subseteq V \times V$

containers
adjacency lists



containers

adjacency lists




fgl

inductive graphs

- inductive datatype: Context of a vertex + Graph

containers

adjacency lists



$E \subseteq V \times V?$


fgl

inductive graphs

- inductive datatype: Context of a vertex + Graph

containers

adjacency lists



$E \subseteq V \times V?$

- partial functions \rightarrow runtime errors

fgl

inductive graphs

- inductive datatype: Context of a vertex + Graph

- simple construction primitives (*“the core”*):

- simple construction primitives (*“the core”*):
 1. *empty* graph

- simple construction primitives (*“the core”*):
 1. *empty* graph
 2. single *vertex* graphs

- simple construction primitives (*“the core”*):
 1. *empty* graph
 2. single *vertex* graphs
 3. *overlaying* two graphs

- simple construction primitives (*“the core”*):
 1. *empty* graph
 2. single *vertex* graphs
 3. *overlaying* two graphs
 4. *connecting* two graphs

- simple construction primitives (*“the core”*):
 1. *empty* graph
 2. single *vertex* graphs
 3. *overlaying* two graphs
 4. *connecting* two graphs
- complete and **consistent** graph representation

Algebraic Graphs


- simple construction primitives (*“the core”*):
 1. *empty* graph
 2. single *vertex* graphs
 3. *overlaying* two graphs
 4. *connecting* two graphs
- complete and **consistent** graph representation
- algebraic structure → formal verification

Algebraic Graphs

- simple construction primitives (*“the core”*):
 1. *empty* graph
 2. single *vertex* graphs
 3. *overlaying* two graphs
 4. *connecting* two graphs
- complete and **consistent** graph representation
- algebraic structure → formal verification
- compact representation for dense graphs

Empty Graph & Vertex Graphs


Empty - ε



$$\varepsilon = (\emptyset, \emptyset)$$


Empty Graph & Vertex Graphs

Empty - ε




$$\varepsilon = (\emptyset, \emptyset)$$

Vertex




$$1 = (\{1\}, \emptyset)$$

Overlay (+)



$$(V_1, E_1) + (V_2, E_2) := (V_1 \cup V_2, E_1 \cup E_2)$$

Connect (\rightarrow)



$$(V_1, E_1) \rightarrow (V_2, E_2) := (V_1 \cup V_2, E_1 \cup E_2 \cup V_1 \times V_2)$$

Graph Construction

- for a graph $G = (V, E)$:


$$\sum_{v \in V} v + \sum_{(u,v) \in E} u \rightarrow v$$

Graph Construction

- for a graph $G = (V, E)$:

$$\sum_{v \in V} v + \sum_{(u,v) \in E} u \rightarrow v$$

- for $V = \{1\}$ and $E = \{(3, 4)\}$:



Overlay (+) and connect (\rightarrow) form an algebra abiding the following axioms

Overlay (+) and connect (\rightarrow) form an algebra abiding the following axioms

- + is commutative and associative
 - $x + y = y + x$
 - $x + (y + z) = (x + y) + z$

Overlay (+) and connect (\rightarrow) form an algebra abiding the following axioms


- + is commutative and associative
 - $x + y = y + x$
 - $x + (y + z) = (x + y) + z$
- $(\mathcal{G}, \rightarrow, \varepsilon)$ is a monoid
 - $\varepsilon \rightarrow x = x \rightarrow \varepsilon = x$
 - $x \rightarrow (y \rightarrow z) = (x \rightarrow y) \rightarrow z$

An ALGEBRA of Graphs - Distributivity

- \rightarrow distributes over $+$
 - $x \rightarrow (y + z) = x \rightarrow y + x \rightarrow z$
 - $(x + y) \rightarrow z = x \rightarrow z + y \rightarrow z$

An ALGEBRA of Graphs - Distributivity


- \rightarrow distributes over $+$
 - $x \rightarrow (y + z) = x \rightarrow y + x \rightarrow z$
 - $(x + y) \rightarrow z = x \rightarrow z + y \rightarrow z$



$$1 \rightarrow (2 + 3)$$

An ALGEBRA of Graphs - Distributivity


- \rightarrow distributes over $+$
 - $x \rightarrow (y + z) = x \rightarrow y + x \rightarrow z$
 - $(x + y) \rightarrow z = x \rightarrow z + y \rightarrow z$



$$1 \rightarrow (2 + 3)$$


An ALGEBRA of Graphs - Distributivity

- \rightarrow distributes over $+$
 - $x \rightarrow (y + z) = x \rightarrow y + x \rightarrow z$
 - $(x + y) \rightarrow z = x \rightarrow z + y \rightarrow z$




$1 \rightarrow (2 + 3)$

=



=




$1 \rightarrow 2 + 1 \rightarrow 3$

An ALGEBRA of Graphs - Decomposition

- $x \rightarrow y \rightarrow z = x \rightarrow y + x \rightarrow z + y \rightarrow z$

An ALGEBRA of Graphs - Decomposition


- $x \rightarrow y \rightarrow z = x \rightarrow y + x \rightarrow z + y \rightarrow z$



$$1 \rightarrow 2 \rightarrow 3$$

An ALGEBRA of Graphs - Decomposition


- $x \rightarrow y \rightarrow z = x \rightarrow y + x \rightarrow z + y \rightarrow z$



$$1 \rightarrow 2 \rightarrow 3$$

An ALGEBRA of Graphs - Decomposition

- $x \rightarrow y \rightarrow z = x \rightarrow y + x \rightarrow z + y \rightarrow z$



An ALMOST Semiring on Graphs

Under these axioms $+$ and \rightarrow almost form a semiring

Under these axioms $+$ and \rightarrow almost form a semiring

- $(\mathcal{G}, +, \varepsilon)$ is a commutative, idempotent monoid

Under these axioms $+$ and \rightarrow almost form a semiring

- $(\mathcal{G}, +, \varepsilon)$ is a commutative, idempotent monoid
- $(\mathcal{G}, \rightarrow, \varepsilon)$ is a monoid

Under these axioms $+$ and \rightarrow almost form a semiring

- $(\mathcal{G}, +, \varepsilon)$ is a commutative, idempotent monoid
- $(\mathcal{G}, \rightarrow, \varepsilon)$ is a monoid
- \rightarrow distributes over $+$

An ALMOST Semiring on Graphs

Under these axioms $+$ and \rightarrow almost form a semiring

- $(\mathcal{G}, +, \varepsilon)$ is a commutative, idempotent monoid
- $(\mathcal{G}, \rightarrow, \varepsilon)$ is a monoid
- \rightarrow distributes over $+$
- Missing: annihilating zero for connect ($x \rightarrow \varepsilon \neq \varepsilon$)

An ALMOST Semiring on Graphs

Under these axioms $+$ and \rightarrow almost form a semiring

- $(\mathcal{G}, +, \varepsilon)$ is a commutative, idempotent monoid
- $(\mathcal{G}, \rightarrow, \varepsilon)$ is a monoid
- \rightarrow distributes over $+$
- Missing: annihilating zero for connect ($x \rightarrow \varepsilon \neq \varepsilon$)
- Unusual: shared identity ε of $+$ and \rightarrow

Obtain other classes of graphs by modifying the set of axioms:

Obtain other classes of graphs by modifying the set of axioms:

- Undirected graphs: \rightarrow is commutative ($x \rightarrow y = y \rightarrow x$)

Obtain other classes of graphs by modifying the set of axioms:

- Undirected graphs: \rightarrow is commutative ($x \rightarrow y = y \rightarrow x$)
- Reflexive graphs: $v = v \rightarrow v$ for any vertex v

Obtain other classes of graphs by modifying the set of axioms:

- Undirected graphs: \rightarrow is commutative ($x \rightarrow y = y \rightarrow x$)
- Reflexive graphs: $v = v \rightarrow v$ for any vertex v
- Transitive graphs:

$$y \neq \varepsilon \Rightarrow (x \rightarrow y) + (y \rightarrow z) + (x \rightarrow z) = (x \rightarrow y) + (y \rightarrow z)$$

Obtain other classes of graphs by modifying the set of axioms:

- Undirected graphs: \rightarrow is commutative ($x \rightarrow y = y \rightarrow x$)
- Reflexive graphs: $v = v \rightarrow v$ for any vertex v
- Transitive graphs:

$$y \neq \varepsilon \Rightarrow (x \rightarrow y) + (y \rightarrow z) + (x \rightarrow z) = (x \rightarrow y) + (y \rightarrow z)$$

- Preorders (reflexive + transitive), equivalence relations (preorder + undirected)

Obtain other classes of graphs by modifying the set of axioms:

- Undirected graphs: \rightarrow is commutative ($x \rightarrow y = y \rightarrow x$)
- Reflexive graphs: $v = v \rightarrow v$ for any vertex v
- Transitive graphs:

$$y \neq \varepsilon \Rightarrow (x \rightarrow y) + (y \rightarrow z) + (x \rightarrow z) = (x \rightarrow y) + (y \rightarrow z)$$

- Preorders (reflexive + transitive), equivalence relations (preorder + undirected)
- Hypergraphs

A Type Class for Algebraic Graphs

```
class Graph g where
  type V g
  empty    :: g
  vertex   :: V g -> g
  overlay  :: g -> g -> g
  connect  :: g -> g -> g
```

A Type Class for Algebraic Graphs

```
class Graph g where
```

```
  type V g
```

```
  empty    :: g
```

```
  vertex   :: V g -> g
```

```
  overlay  :: g -> g -> g
```

```
  connect  :: g -> g -> g
```

```
graph :: Graph g => [V g] -> [(V g, V g)] -> g
```

```
graph vs es = overlay (vertices vs) (edges es)
```

A Type Class for Algebraic Graphs

```
class Graph g where
```

```
  type V g
```

```
  empty    :: g
```

```
  vertex   :: V g -> g
```

```
  overlay  :: g -> g -> g
```

```
  connect  :: g -> g -> g
```

```
graph :: Graph g => [V g] -> [(V g, V g)] -> g
```

```
graph vs es = overlay (vertices vs) (edges es)
```

→ Graph construction & transformation library – independent of concrete graph representation

Using Isabelle/HOL

- (type class + axioms) \sim *locale* in Isabelle

```
locale algebraic_pre_graph =  
  fixes empty :: 'g ("ε")  
    and vertex :: "'v ⇒ 'g"  
    and overlay :: "'g ⇒ 'g ⇒ 'g" (infixl ⟨+⟩ 75)  
    and connect :: "'g ⇒ 'g ⇒ 'g" (infixl ⟨→⟩ 80)
```

Using Isabelle/HOL

- (type class + axioms) \sim *locale* in Isabelle

```
locale algebraic_pre_graph =  
  fixes empty :: 'g ("ε")  
    and vertex :: "'v ⇒ 'g"  
    and overlay :: "'g ⇒ 'g ⇒ 'g" (infixl ⟨+⟩ 75)  
    and connect :: "'g ⇒ 'g ⇒ 'g" (infixl ⟨→⟩ 80)
```

- instantiation with $G = (V, E)$ representation \rightarrow formal proof of completeness and consistency

Challenge: graph type ' g '

Challenge: graph type 'g

- subgraph relation $x \sqsubseteq y :\Leftrightarrow x + y = y$

Challenge: graph type 'g

- subgraph relation $x \sqsubseteq y :\Leftrightarrow x + y = y$

definition *has_vertex* :: "'g \Rightarrow 'v \Rightarrow bool" where

"has_vertex g u \equiv vertex u \sqsubseteq g"

definition *has_edge* :: "'g \Rightarrow 'v \Rightarrow 'v \Rightarrow bool" where

"has_edge g u v \equiv edge u v \sqsubseteq g"

Define walks inductively

inductive *vwalk* where

vwalk_Nil: "*vwalk g []*" |

vwalk_single: "*has_vertex g u \implies vwalk g [u]*" |

vwalk_Cons: "*vwalk g (v#xs) \implies has_edge g u v*
 \implies vwalk g (u#v#xs)"

Define walks inductively

inductive *vwalk* where

vwalk_Nil: "*vwalk g []*" |

vwalk_single: "*has_vertex g u* \implies *vwalk g [u]*" |

vwalk_Cons: "*vwalk g (v#xs)* \implies *has_edge g u v*
 \implies *vwalk g (u#v#xs)*"

- Appending/splitting walks, reachability

Define walks inductively

inductive *vwalk* where

vwalk_Nil: "*vwalk g []*" |

vwalk_single: "*has_vertex g u* \implies *vwalk g [u]*" |

vwalk_Cons: "*vwalk g (v#xs)* \implies *has_edge g u v*
 \implies *vwalk g (u#v#xs)*"

- Appending/splitting walks, reachability
- \rightarrow Polymorphic graph *formalization* library

Compact Representation for Dense Graphs


$$1 \rightarrow 2 \rightarrow \dots \rightarrow n$$

is a linear size representation of a graph with a quadratic number of edges

Compact Representation for Dense Graphs

$$1 \rightarrow 2 \rightarrow \dots \rightarrow n$$

is a linear size representation of a graph with a quadratic number of edges




$$1 \rightarrow 2 \rightarrow 3 \rightarrow 4 \rightarrow 5$$

Compact Representation for Dense Graphs

$$1 \rightarrow 2 \rightarrow \dots \rightarrow n$$

is a linear size representation of a graph with a quadratic number of edges



$$1 \rightarrow 2 \rightarrow 3 \rightarrow 4 \rightarrow 5$$

Open question

- Can we exploit this compact representation, i.e. find algorithms that work directly on algebraic graphs expressions?

```
data Graph a = Empty
              | Vertex a
              | Overlay (Graph a) (Graph a)
              | Connect (Graph a) (Graph a)
```

Deep Embedding

```
data Graph a = Empty
             | Vertex a
             | Overlay (Graph a) (Graph a)
             | Connect (Graph a) (Graph a)
```

- Custom `Eq` instance required!
(`Empty == Overlay Empty Empty`)

Reuse well-known Haskell abstractions for Graph transformation

Reuse well-known Haskell abstractions for Graph transformation

- `instance Functor Graph` → contracting vertices

Reuse well-known Haskell abstractions for Graph transformation

- `instance Functor Graph` → contracting vertices
- `instance Monad Graph` → splitting vertices, inducing subgraphs

Conclusion

- alternative approach to graph construction/transformation
 - small core of primitives - safe and complete
 - suitable for functional programming and formal verification
 - available on `hackage`¹

¹<http://hackage.haskell.org/package/algebraic-graphs>

Conclusion

- alternative approach to graph construction/transformation
 - small core of primitives - safe and complete
 - suitable for functional programming and formal verification
 - available on `hackage`¹
- two main directions for future work
 1. exploit compact representation/other applications of algebraic graph expressions
 2. exploit “polymorphism” of type class/locale

¹<http://hackage.haskell.org/package/algebraic-graphs>

Graph Construction - Vertices

- Graph with only vertices:


$$\sum_{v \in V} v$$

Graph Construction - Vertices

- Graph with only vertices:

$$\sum_{v \in V} v$$

- for $V = \{1, 2, 3, 4\}$:



Graph Construction - Edges

- Graph from a set of edges:


$$\sum_{(u,v) \in E} u \rightarrow v$$

Graph Construction - Edges

- Graph from a set of edges:

$$\sum_{(u,v) \in E} u \rightarrow v$$

- for $E = \{(1,2), (3,4)\}$:




Graph Construction

```
vertices :: [a] -> Graph a  
vertices = foldr Overlay Empty . map Vertex
```

Graph Construction

```
vertices :: [a] -> Graph a  
vertices = foldr Overlay Empty . map Vertex
```

`vertices [1,2,3,4]` $=$



Graph Construction

```
edge :: a -> a -> Graph a
```

```
edge u v = Connect (Vertex u) (Vertex v)
```

Graph Construction

```
edge :: a -> a -> Graph a
```

```
edge u v = Connect (Vertex u) (Vertex v)
```

```
edges :: [(a,a)] -> Graph a
```

```
edges = foldr Overlay Empty . map (uncurry edge)
```

Graph Construction


```
edge :: a -> a -> Graph a
```

```
edge u v = Connect (Vertex u) (Vertex v)
```

```
edges :: [(a,a)] -> Graph a
```

```
edges = foldr Overlay Empty . map (uncurry edge)
```

```
edges [(1,2),(3,4)] =
```




Graph Construction

```
graph :: [a] -> [(a,a)] -> Graph a  
graph vs es = Overlay (vertices vs) (edges es)
```

Graph Construction

```
graph :: [a] -> [(a,a)] -> Graph a  
graph vs es = Overlay (vertices vs) (edges es)
```

`graph [1] [(3,4)]` `=`



Graph Transformation - Functor

Functor

```
instance Functor Graph where
    ...
    fmap f (Vertex u) = Vertex (f u)
    ...
```

Graph Transformation - Functor

Functor


```
instance Functor Graph where
```

```
...
```


```
fmap f (Vertex u) = Vertex (f u)
```

```
...
```

`fmap (+1)`



=



Graph Transformation - Merging Vertices


```
mergeVs :: (a -> Bool) -> a -> Graph a -> Graph a  
mergeVs p v = fmap $ \u -> if p u then v else u
```

Graph Transformation - Merging Vertices


```
mergeVs :: (a -> Bool) -> a -> Graph a -> Graph a
```

```
mergeVs p v = fmap $ \u -> if p u then v else u
```

```
mergeVs (>1) 4
```



=



Graph Transformation - Monad

```
instance Monad Graph where
```

```
...
```

```
(Vertex u) >>= f = f u
```

```
...
```

Graph Transformation - Monad

```
instance Monad Graph where
    ...
    (Vertex u) >>= f = f u
    ...

splitVertex :: (a -> Bool) -> [a] -> Graph a
splitVertex p vs = g >>= \u -> if p u
                                then vertices vs
                                else Vertex u
```

Graph Transformation - Monad

```
instance Monad Graph where
```

```
...
```


```
(Vertex u) >>= f = f u
```

```
...
```


```
splitVertex :: (a -> Bool) -> [a] -> Graph a
```

```
splitVertex p vs = g >>= \u -> if p u  
                        then vertices vs  
                        else Vertex u
```

```
splitVertex 4 [2,3]
```



=



Graph Transformation - MonadPlus

```
instance Graph MonadPlus where
  mzero = Empty
  mplus = Overlay
```


Graph Transformation - MonadPlus

```
instance Graph MonadPlus where
    mzero = Empty
    mplus = Overlay

induce :: (a -> Bool) -> Graph a -> Graph a
induce = mfilter
```

Graph Transformation - MonadPlus

```
instance Graph MonadPlus where
```


```
  mzero = Empty
```

```
  mplus = Overlay
```


```
induce :: (a -> Bool) -> Graph a -> Graph a
```

```
induce = mfilter
```

`induce even`



=



Graph Equality

Structural equality is not suitable:

```
Overlay (Vertex 1) Empty == Vertex 1
```

Graph Equality

Structural equality is not suitable:

```
Overlay (Vertex 1) Empty == Vertex 1
```

Eq instance for Algebraic Graphs

- Current implementation: build adjacency map

Graph Equality

Structural equality is not suitable:

```
Overlay (Vertex 1) Empty == Vertex 1
```

Eq instance for Algebraic Graphs

- Current implementation: build adjacency map
- Possible approach: *minimize* graph expressions → *Modular Graph Decomposition*

Compact Representation for Dense Graphs

Fully connected (undirected) graph

```
clique :: [a] -> Graph a
```

```
clique = foldr Connect Empty . map Vertex
```

Compact Representation for Dense Graphs

Fully connected (undirected) graph

```
clique :: [a] -> Graph a
```

```
clique = foldr Connect Empty . map Vertex
```

- Linear size representation
- quadratic in size when using e.g. adjacency map

Compact Representation for Dense Graphs

Fully connected (undirected) graph

```
clique :: [a] -> Graph a
```

```
clique = foldr Connect Empty . map Vertex
```

- Linear size representation
- quadratic in size when using e.g. adjacency map

Open question

- Can we exploit this compact representation, i.e. find algorithms that work directly on algebraic graphs?

- using Isabelle/HOL

Formal Verification

- using Isabelle/HOL
- inductive datatype \rightarrow proofs by induction, `auto`

Formal Verification

- using Isabelle/HOL
- inductive datatype → proofs by induction, `auto`
- `quotient_type` (think `Eq` instance) based on tuple representation

Formal Verification

- using Isabelle/HOL
- inductive datatype → proofs by induction, `auto`
- `quotient_type` (think `Eq` instance) based on tuple representation

Future work

- Minimization
- Algorithms, applications beyond graph construction/transformation