

# Quintessential Unix Shell commands

- **ls - list files**
  - `ls -al` - list all files with extra information
- `mv` - move file/folder
- **cp - copy file/folder**
  - `cp -r` - copy folder recursively
- `pwd` - gives u the current directory, like which, full path
- `rm` - delete file
- `rm -rf` - remove folder recursively and force, IE, ignore all warnings. yes it will delete the whole drive if run as sudo on /
- `mkdir` -makes an empty directory
- `touch` -makes an empty file
- `rmdir` -remove empty directory only(safety feature)
- `less` -read a file that is longer than the screen. scroll by hitting enter, space, arrows, pgdown, search with / use q to quit
- `su` - setuser/superuser its supposed to stand for, su bob will make your user bob, you need his password. su makes u root(if you have a root password)
- `sudo` - run a command as root, became the normal way to do things in administration after a while. before it was just get a root shell with su. it will ask for a password and if you are an admin user yours will work. you have to be in the group sudoers.
- `more` - basically the same as less but slightly different in an unmemorable and barely perceivable way
- `top` - like task manager, list everything. full featured interface, can kill things, sort everything, etc
- **ps -list processes defaults to ones in your shell**
  - `ps aux` - lists processes from all users with more information
- **grep - search files for string or regular expression, print whole line**
  - `grep -v` - exclude files
  - `grep -A n -B m` - print lines n after matching line and m before matching line
- **kill -end process with signal 15, smooth exit**
  - `kill -s 9` - end it right now, no shutdown sequence
- `cat` -spit entire file to stout
- `curl` -send http request and spit output to stdout
- **nc -netcat, same as cat but uses raw tcp socket. can work on udp too**
  - `nc -l n` - liston on port n, add -u for udp
- `sed` -more advanced regular expression oriented grep with in-place editing focus
- `awk` -similar to sed, complex grep type thing regexps in-place editing etc
- `perl` -a whole language like python, partially specialized for the tasks sed and awk do, can write one liners in shell. regexps

- **chmod -modify permissions, uses a number code of 3 digits or letter**
  - `cmod +x file` - set file to be executable
  - `chmod 777` - let all users read write and execute. don't do it
  - `chmod 666` - all users read and write,
  - `chmod 770` owner user and group for owner user can w r ex
- `man` -manual page, `man <command>` shows the page, it is the help files, it is the best reference for arguments of commands. YOU SHOULD REFERENCE THE MAN PAGE COMMANDS. it is the only source you need for these base commands u see here, and old software. it is not necessarily the best way to learn how to use vim.
- `screen` -make a new screen. `ctrl-a (release) d` detaches/exits from it, `ctl-a c` closes. this is one way you run things in the background
- `nohup` - precedes command and prevents hangup signals from hitting it so it will run until killed or closed from internal logic. alternative to `screen` for background process that will persist on logout
- `md5sum` -jsut called md5 on mac/bsd just does an md5 checksum hash of a file. for comparison of files of any size
- `sha256sum` -same as above with sha256 algorithm. also exists others.
- `who` -lists out the current logins/screens. shows u who is logged in(which users and where)
- `whoami` -tells u which user u are. used to check if you've successfully hacked things and became root. or in innocent shell scripts
- `lsof` -spit out data about various things going on with processes and devices and filesystem. example `lsof -i:8000` gives u info about proc using port 8000
- `lsusb` -list the usb devs. good to check if it can see a device
- `lspci` -same but for pci devices
- `sort` -sorts text file line by line
- `find` -for searching the file system. most stupid way can be done like `find . |grep filenameiwant`. recursive list of full dir tree is the default behavior
- `uniq` -deletes duplicate lines that appear next to eachother in text.
- `echo` -prints whatever is in its args to stdout
- `which` -gives total path to an executable in the shell path
- `strings` -spits strings out from binary file
- `hexdump` -spits out hex of a file
- `diff` -gives u the difference of 2(text) files line by line. yes this is where the term diff comes from in git repos etc
- `tar` -deals with tar archives. to untar a tar.gz `tar xvf file.tar.gz`, for tar.bz2, `tar xvf`
- `gzip` -compression. works on one file, takes input from file or stdout(!) good on text, fast
- `bzip2` -slower more intense compression
- `gunzip` -un-gzipps file
- `bunzip2` -unbz2 a file
- `zcat` - gunzip and contents to stdout
- `zgrep` - greps compressed data, IE same as `zcat <file> |grep <word>`
- `bzgrep` -grep a bzfile, handy, exists also `bzless bzcat bzexe...` same as with above

- `lsblk` -list block devices. handy to see drives that are not mounted
- `df -h` - lists mounted drives with size and free space in human readable format
- `du -h` - check file size. it is recursive by default so it is good to set the max view depth with `-d 0`.  
`du -h -d 0 file`
- `lsmod` -list kernel modules(generally are drivers), which are code that can be hotplugged into the kernel. this is used when troubleshooting hardware and driver issues
- `modprobe` -load up a module, they have a path thing built in so you can tab tab to see whats available
- `time` -TIMES A COMMAND in human readable down to ms
- `date` -the timestamp in a human readable format, can spit out other formats check man page
- `ln` -typically invoked as `ln -s`, which creates a symbolic link
- `fsck` -checks hard drives
- `fdisk` -partition hard drives
- `mkfs` -makes the default fs, ext4 or whatever your system thinks is the default, for other fs do `mkfs.<x>` or `mkfs -t <x>` - make other kinds of fs <x>, IE format partitions
- `yes` -endless loop of 'y'... for dealing with annoying menus with the y/n? prompts using pipe
- `wipefs` -removed disk label
- `shred` - destroy files by writing random data to the location they were stored on disk(doesnt work on some filesystems) or write random data to a whole disk
- `cryptsetup` - setup luks volumes
- `cron` -service for running periodic tasks.
- `ranger` - file explorer command line tool. vim bindings, written in python. navigate filesystem in ncurses text interface
- `lfm` - shitty version of ranger seems really old
- `lf` - newer unfinished version of ranger lighter and focused on the use of external tools to open things, not in repos <https://github.com/gokcehan/lf>
- `head` - get top 10 lines of the file, use `-n` to specify numlines
- `tail` - some as above, last 10 lines as default
- `cut` - more general than the 2 above, check the manpage, cuts chars bytes lines....

## Notation

this is notation used in this document and others like it, not syntax for the shell or anything else, and some general notes on style, common themes in this environment

- `<x>` - a variable named x, this is common parlance in documents like this, not sure why, its old school and not syntax in any shell or scripting language i know, for example `ls <folder>` is saying that putting a folder in that place makes sense.
- `<cmd> --help` - common, quite standard, basically all modern command line utils have this arg to give you a refresh on the syntax, args available
- `<cmd> --<arg-name> -a` - it is very common for single character args to use a single `-` and multi-char to use two like `--arg`, and use another `-` to separate words. these are community habits for many decades and not technical limitations or hard rules. command line args can be anything but are generally tokenized by splitting on the whitespace

- **RTFM** - means read the fucking manual IE check `man`, common use context is in a response to someone who wants to be spoon fed like a baby and cant read his own error messages...
- `ctrl-x` - hold control and x both for a moment, `x-y z` hold x and y for a moment, release both, hit z
- `[BUTTON]` - hit a button labeled BUTTON on your keyboard

## editors:

- `vi` -the old version of vim. it sucks. if u have a new install and type `vi` this is what is usually there. it makes people hate vim. dont use it. install vim and it will clobber the path to this
- `vim` -the new version of vi, if installed will alias as `vi` overriding above command, for serious people only. perfect for people that hate their mouse. extensible to the point of absurdity. it is a modal editor, meaning it has modes of interaction with the file. hit escape to dissasociate from a mode, hit a letter to change to that mode. in this case the letter `i` is insert (normal edit mode), `v` is visual(select and delete copy and stuff large blocks to text). in the default mode and in visual `d` is delete, hit it twice to delete a line. visual mode `d` deletes selection. `u` is undo. the `:` char (yes use shift) lets u type in commands for user defined things and interactions with filesystem. `:w` is write. `:wq` is write and quit. `:q` is quit. `q!` is quit RTFM with no confirmation. `:r <file>` is read(a file and output it at current cursor position). `:read !<commands>` does the same for a shell command `! <cmd>` opens the shell and hides the editor, returning when you exit
- `elvis` - this is another editor, a better version of vi, lighter than vim(if i remember correctly)
- `neovim` - a new and cooler vim that people who think theyre cool use. also has qt graphical `neovim-qt`, aparently feature-rich and more efficient cleaner codebase as it was written more recently
- `pico` -simple old editor not sure its ever used anymore.
- `nano` -a fork/copy/something of pico, newer, good for noobs, often used and well respected. commands are on the screen when using it and `ctrl-X` based.
- `emacs` -a complex and extensible editor, bulky for a command line utility. generally serious editor nerds that use stuff in this section use either emacs or vim, and have strong convictions about it.
- `ed` -the simplest editor from extremely long time ago, only used in extreme emergencies. the kind of editor a eunich would use.
- `gedit` - simple graphical editor, good, basically notepad with syntax highlighting.

## system things(debian based mint/ubuntu):

- `sudo` -run following command as root (admin)
- `su` -set user, defaults to root. can specify shell with `-s`
- `service` -control a service. `service <name of it> <start, stop, restart, reload>` ex: `sudo service postgresql restart`
- `hostname` -prints hostname, if given arg it will set the hostname to the arg. if u do this, should also manually change `/etc/hostname` and make sure `/etc/hosts` reflects that change if necessary
- `adduser` -`adduser <newusername>` maeks a new user. many options. none are really required, even a password.
- `usermod` -mod shell and stuff of a givemn user `usermod -aG` common for adding group
- `passwd` -password change, `passwd <user>` does it for user when u are admin
- `dd` -writes raw data. `dd if=indevice of=outdevice bs=1M`. if is a filesystem object to be read, of is the filesystem object to be written and bs is the block size which can be written human readable like 1M 2M 4M and in bytes like 1024(the old way). you use this when wipeing disks with random data. you

use it when 'burning' a flash drive with a disk image like `dd if=linux.iso of=/dev/sdc bs=4M`. If you mess up with this as root you can easily overwrite your hard drive. do not do it to mounted filesystem

- `chsh`- change the shell for a user
- `chgroup`- change group of file... group ownership
- `chmod`- change permissions of file `chmod 777` file makes everyone read write ex it, `chmod 666` is read write for all.... `chmod 600` is another common one `ls -al` will show the perms
- `mount` - attaches a block device to a folder, allowing you to browse the filesystem
- `umount`- unmounts something takes mountpoint or `/dev /device` as target
- `dmesg`- prints messages generated at boot
- `env`- show ur environment vars, set them then run command(too)
- `uptime`- time up
- `wipefs`- removed disk label
- `cryptsetup` - setup luks volumes
- `cron`- service for running periodic tasks.

## shells:

- `bash` -common, youre prob on it. "bourne again shell" whatever that means
- `cs`h -different, advanced too - C shell
- `tc`sh -mac uses it? freebsd? its good too
- `zsh` - another shell that some nerds are all about, like the previous 2
- `sh` - the most simple bare bones one used when there is nothing else in some broke-ass embedded system or something, no tab to complete, no features, you run it because its always there on every system, common hack entrypoint to spawn a shell in a priv upgrade or somesort of remote code exe sploit

## env vars:

the shell and other software uses many environment vars

these give background information about your system and things to software that needs it

this information is stored here because it doesnt need to be changed often, but always needs to be specified

type `env` to see them all. `echo $VAR` to see `VAR`. `export VAR=sgfsgs` to set `VAR` to `sgfsgs` for your session. setting `VAR=5 someprogram`, will modify `VAR` for that single line running `someprogram`.

shell vars in general have a `$` in front of them when you access them. but not when you set them

- `$PATH` - path to binaries, default is `/bin /usr/bin /usr/local/bin` etc
- `$DISPLAY` - x11/xorg display, typically `:0`. machines can have multiple displays, like all unix things, its multiuser
- `$PYTHONPATH` - where python looks for modules
- `$USER`, `$HOME`, - username and home directory path
- `$_` - arguments of last program ran?

- `alias` - it is a command that tells the shell to make a macro for other commands, generally default `bashrc` will have some use of it and generally anything you want to do like this is done better with a function `def`
- `env` shows your env
- `export` - declare env var for remainder of session until u close this shell
- `jobs` - lists the jobs in shell(if you have paused with `ctrl-z`) with `jobid`
- `bg <jobid>` and `fg <jobid>` - background a paused job or foreground a paused job respectively.

advanced

## strange obscure barely useful:

- `motd` - message of the day, displayed on login, not all systems have this command, its old school, but having an MOTD is not a dead art.
- `links` - text only browser
- `lynx` - older more useless text only browser
- `irssi` - irc client ncurses flavor. leet af
- `rexima` - command line sound volume control mixer thingy
- `beep` - makes a console beep

## graphical, featureful

- `xterm` -old school bare bones terminal emulator for x11
- `xorg/x11` - always started by scripts, but it is the name of the service that runs the GUI in linux generally. `x1` was the old name `xorg` is the new one. there are forks...
- `xv` -old and simple image viewer
- `mplayer` -old simple and great media player. no GUI, just do `mplayer file.mp4` or whatnot
- `mpv` - like `mplayer` but better, has no interface other than key bindings and cmdline
- `gimp` - powerful image editing, old school MIT project, shit interface, opens any format basically
- `ibus` - this is a package for controlling advanced input methods that are a lot more than a change of layout; like Chinese, Korean,
- `xviewer` -seems to be the version of `xv/xview` available in modern ubuntu? stupid name

## high tier suckless

- `tmux` - terminal multiplexer, lets you squeeze multiple terminals into one screen. like a super old school window manager=
- `pass` - password manager that uses `gnupg`. integrates with `git`, can be used to run google auth type 2fa, responds to tab to complete well

## network & hax

- `nmap` -port scanner highly advanced, many modes and options
- `masscan` -speed optimized port scanner for large volume scanning, target acquisition. usually preceeds the use of `nmap` whcih yields more detailed information

- `nc` -previously mentioned, netcat, raw conns
- `ettercap` -manipulation of ARP, DNS, other protocols, generally for the purpose of man in the middle attack
- `wireshark` -watch network packets go by. need to change group to work properly. can run as root and always works that way, but not recommended. used to be called ethereal - the new name sucks. still hate them for it. the new name reads like it should be the name of a chinese electrician tool or a korean children's cartoon
- `ngrep` -network grep, just reads packets going by your box and spits that out to stdout if it matches what ur looking for
- `tcpdump` -captures and dumps packets, dump files can be reloaded, minor dissection available with some classification, can load the dumps up with anything
- `ifconfig` -old network interface config command line utility. windows ipconfig is the ripoff version with a weird name
- `ip` -the newer, 'better' network interface and routing table configuration tool
- `route` -routing table edit and explore
- `httping` -sends a http packet to a server on default port of 80, gives response time
- `ping` -normal old school icmp ping. not what it used to be
- `telnet` -old school shell/terminal over the wire. completely unencrypted, not much more complex than netcat. helpful for testing connections, manual single port probing like `telnet <host> 80` to connect to port 80 on <host>
- `nslookup` -look up an ip or hostname in DNS
- `john` -old school powerful password hash cracker. supports extensions and a lot of hash algorithms. parallelism exists too, not sure about GPU kernels. likely better things these days. called john the ripper(after the famous amateur serial hooker-dissection enthusiast)
- `whois` -information on domain ownership, reverse look up of IP addresses. just an entry from a database about the owner and registrar stuff for IPs and domains.
- `traceroute` -old school packet routing trace, not sure if it really works the same anymore, but shows you the path packets take to a server. seems like maybe routers out in the wild drop the packets it uses now often? not sure. don't use it much and it's not what it used to be is the word
- `arping` -executes a ping-analogous function using the arp protocol. v nice.
- `tssocks` -wrap any protocol through socks
- `httping` - ping a http server. IE, give the response time to a http service
- `aircrack-ng` - a suite of utilities for security analysis of wifi networks
- `iwconfig` -like ifconfig but with specific features for wifi adapters/driver interfaces. it is old school
- `iw` - same as above but not as old school
- `bluetoothctl` - shell style interface to bluetooth hardware. quite good
- `yersinia` - a powerful security analysis tool that i am not too familiar with, but worth a mention. some kid in vegas looked at me like i was insane for not using it. appears very powerful.
- `netstat` - usually i invoke as `netstat -n`, lists the connections in and out of the machine. godo stuff is by the top so try `netstat -n|head`

## SSH STUFF

- `ssh` -secure shell, replaced telnet when people realized u could ngrep peoples files out off the network

- `ssh-keygen` - generates keypairs for ssh auth
- `scp` - copies files over ssh, will default to copy locally for composability and uses same args generally. typical use `scp user@host:/home/user/stuff stuff`. username is often needed. tab to complete works if you have passwordless ssh set up. USE IT PASSWORDLESS AND USE TAB to complete. tab is slow though. remember you can copy to `/tmp` always, too.
- `ssh -X` - this arg will forward x11, IE, let u run graphical programs over ssh (if u have x11 on both sides)
- `ssh -D 8888` - runs a socks5 proxy on port 8888 that tunnels connections from localhost through the remote host
- `ssh -L8888:host:8888` - tunnel localhost 8888 to remote host's view of host:8888
- `ssh -R8888:host:8888` - reverse tunnel, goes from remote host to localhost's view of host:8888
- `sftp` - ftp like client thingy for scp. never use it, might be the original client and actual protocol name for the machinery that does scp
- `sshfs` - smount - use the above sftp facilities to emulate a mounted filesystem

## operators in shell(bash)

- `|` pipe, puts stdout into stdin like `cat bob | grep <word>`
- `&` - runs concurrently with following command.
- `&&` - run next program sequentially
- `>` - stdout into a file `cat bob > bobfile`. OVERWRITES THE FILE
- `>>` - APPENDS TO THE FILE like `ls >> listfile` will append to the bottom of listfile the folder contents
- `2>` - same as `>` but does stderr,
- `<` file on right into stdin of command on left
- `<<<` - string on the right into stdin on the left
- `ctrl-z` - pause - immediate effect always
- `ctrl-c` exit, doesn't leave shell (that's logout) clears the line though. sends a `kill -s 15` to the thread in foreground
- `ctrl-d` logout
- `[TAB]` - tab - hit this key a lot, it works to complete MANY things. used to just be files, now almost anything. `git add [TAB] [TAB]` lists your changed files, for instance
- back quotes - `kill `pgrep firefox`` - inserts stdout from the command in backquotes into the shell as if you had typed it. `pgrep` outputs a list of pids that match the string you give it, here that is being picked up by `kill` so that it kills anything that matches firefox
- `*` - wildcard, `ls *.py` gives list of python scripts in current directory
- `[0-9]` - matches digits in shell, `ls [0-9]*` list everything that starts with a digit. can use comma separated singletons, works with letters too `[a-z]...`

## root filesystem synopsis

In the past many of these were separate partitions, hence some of the seemingly redundant things. Now this is not as important with solid state drives and (i supposed) more modern file systems



- `/tmp` - temp folder, anyone can write in it. it is there on every system and great place to copy things to if you are not sure where to do it
- `/etc` - pronounced et-SEE. all the configuration files and global settings are in here by default. in the past administration could be done exclusively by modification of files here, more or less. programs like `passwd` are tools to automatically edit files here
- `/var` - various data here, `var/log` is a default global spot for logs. often home to global data storage, such as the root of a webserver with static content, or database disk footprint.
- `/usr` - user installed things generally.... comes with a lot in it these days. it is like an alternative root where you generally would modify things for system wide access. has the same directory structure as `/`
- `/proc` - process information emulated as block storage devices and stuff like this. can get info about some hardware from drivers, and access some other weird low level things, dynamic emulated files that are read from live executing daemons
- `/dev` - devices, filesystem emulation of actual hardware. all disks are here, your sound devices, usb devices, all accessed from here if you want to do it directly. it is a virtualized/emulated filesystem integrated representation of a group of non-file objects(very cool) like `proc`. these are not actual files, but dynamic emulated files that make access to devices like accessing a file. reading and writing to them is the same as a file
- `/opt` - not sure what it is supposed to be but it is often used to store globally accessed proprietary software that doesn't have facility to install in the typical global directory structure(where things are in `/bin` and `/lib` and prstuff)
- `/bin` - binaries, these are where the commands are stored for the base system. most of the higher level stuff is in `/usr/bin` and `/usr/local/bin`
- `/home` - home directories for each user here. all user settings and information and data are in their home folder. copy it to a new system and it will all be there
- `/root` - home directory for admin/root user
- `/boot` - contains the kernel and initial root disk, boot loader stuff IE GRUB. is more commonly a separate partition still
- `/cdrom` - vestigial artifact of a time when people used cdrom
- `/mnt` - this was originally where you would mount drives, IE, any drive that was not hosting system critical contents, like removable media, was mounted here. you added these to be automounted using `/etc/fstab`, and mounting had to be done by root
- `/media` - this is where things are mounted now, on a path like `/media/<username>/<uuid serial thing>`

## notable filesystem objects, global

- `/proc/cpuinfo` - cpu core info, pretty great
- `/dev/random` - random data from hardware. cat this and you get a dump of real physical entropy
- `/dev/urandom` - output of a prng using above as seed. cat this and get infinite 'random' data generated from finite entropy harvested from hardware
- `/etc/passwd` - old school place where some user info is stored, originally included encrypted passwords
- `/etc/shadow` - where they moved the encrypted passwords from `passwd` to hide them from users when they realized they could be cracked
- `/etc/hosts` - list of hosts that are basically added to DNS, can put some of your servers here so you don't type ip

- `/etc/hostname` - your hostname, for some reason i feel i usually must edit this and use the `hostname` command at the same time/session
- `/etc/rc.local` - old school place to put commands to have them run on boot, on many linux systems.
- `/etc/resolv.conf` - old way of keeping global nameservers. depends on the system now....
- `/etc/motd` - text displayed at login. put stuff here if you have users, info about the system, advertisements, cuss them out, etc

## notable filesystem objects, local

- `~` - alias to your homefolder `/home/username`
- `~/.ssh/authorized_keys` - put in a copy of someones `id_rsa.pub` file as a line, and it allows anyone with the corresponding private key to log into said account to whom `~` belongs.
- `~/.ssh/config` - lets you preconfig defaults for various servers and things, pivotal when using `scp` and `git` regularly. `man ssh_config` exists and shows syntax
- `~/.ssh/id_rsa.pub` - default place for public ssh key, without the `.ssh/id_rsa` is default for private, which, should be `chmod 600` for the perms
- `~/.bashrc` - i use bash, this is a place you can add commands that run on login. such as adding things to your `$PATH`
- `~/.bash_history` - history of commands in bash, some cap length by default, grep this to find stuff you did and need the command for
- `.profile` - this is like `.bashrc` but not specific to bash. on many systems, mac OSX and i believe other BSD. definitely check if you are not using bash
- `~/local/` - has a root filesystem mirror structure that user installed things (like pip packages) can sit in. like a personal `/usr/local`. pip user installed stuff goes here
- `~/.config/` - it is now considered best practice for packages to put their user config files in here rather than randomly as a hidden file or folder in `~`

## some good config file lines

`.ssh/config` This is an important config file, sometimes it is absolutely necessary if you are using `scp` and other ssh based utilities like `git` that sometimes do not have the ability to take the more advanced arguments you may need to give them, in the case of having multiple users at the same host with multiple keys and things like this

```
>>>
Host bob
  HostName bob.com
  User userb
  IdentityFile ~/.ssh/id_rsa_bob
```

this enables you to simply `ssh bob`, and tab to complete works on this alias for the host. `HostName` is the actual network address, dns or ip, and the alias you are giving it which will follow this setup every time is the first line in each entry `Host`

## host a git, barebones

simple and dirty instructions always use passwordless SSH or this makes git user on server. no password on it. NO PASSWORD ON IT. no way to log in with password

```
>>>
which git-shell #find path to git shell - comes with git, set this as the shell for the git user on the server. this prevents users from logging in with ssh but they can do the git operations
adduser # set git-shell full path to the shell as you go through the menu and set no password. SET NO PASSWORD
sudo su -s /bin/bash git# makes u git user and override shell so u can have an interactive session
#make folders as you need them in /home/git. cd into the folder. do:
mkdir package # to make git called package
git init
git config receive.denyCurrentBranch ignore # over rides some annoying check that make the first commit a pain
```

put public keys in /home/git/.ssh/authorized\_keys as a line, on the host n

on clients: git clone <ssh://git@server:/home/git/package>

then make an initial commit to master to make sure it works

pull requests seem like a thing you dont want to do without a web interface like github

## git client side

process of creating branch and merge:

```
>>>
git checkout master
git pull# - make sure its up to date
git branch mybranchname #- make a branch
git cheeckout mybranchname #- now you are on it, it is forekd off main
#do stuff
git add stuff
git commit -m"new stuff"
git push #- upload it to the remove server
#keep doing stuff, eventually ready to merge
git checkout master
git pull #-make sure its up todate
git merge mybranchname
#now if theres conflicts, you make sure it works, correct them.
#you can checkout a file from master by git checkout file, and add that one, to
#blidnly tke the master verion of file
git push
```

#there are other commands in between sometimes, but it will tell you waht they are git is very user friendly for a command line interface but remember to push after you merge, push and pull and clone are remote commands. rest are local

## docker

docker is super helpful, especially if youre a noob. It allows you to do things as root but not destroy your baremetal system.

It was originally to make back end services scaleable, reproducible, and sandboxed while avoiding the use of a VM

docker has a built in management system for images shared by project teams and the community

stuff in docker runs on your kernel but network and disk is sandboxed and communicates through whatever avenues you specify(shared folders and port forwards)

you can run things in docker like any other program

if you dont use it youre basically failing at life

also a good way to give people root-like power on servers, without allowing them to trash the system and spy on people through unfettered hardware access

- `docker-compose` - utility for launching a few differentd ocker containers of different services, allowig you to easily config them to be interconnected in one file. simply put `docker-compose.yml`

in an empty folder and edit/generate/write it to your specs. editing yaml can be kind of annoying due to autistic standards with whitespace and stuff. so work off of a cypypaste

- `docker` - the normal interface to docker to run one container
- `docker stats` shows current running containers wioth resource use