

“One Plug, All IP” Full HD Network
Video Recorder

myNVRxx Series



KEY FEATURES

- H.264/MPEG4/MJPEG Codec Acceptable
- Manage Video & Audio from IP Camera incl. IP Speed Dome
- Max. 16Ch 1080P Decoding & Display
- Auto Searching & Setting IP Camera in LAN
- Network Access up to 25 users
- HDD*2 up to 6TB

VIDEO

	myNVR08(P)	myNVR04(P)
Camera Input	Max 8ch (4ch@1080p or 8ch@720p/D1)	Max 16ch (4ch@1080p or 4ch@720p/D1)
Output	16:9 Progressive	

AUDIO

Input via network/Output	8/1	4/1
--------------------------	-----	-----

SENSOR

Sensor In / Alarm Out	4/1	4/1
-----------------------	-----	-----

DISPLAY

HDMI Resolution	1920x1080P , 1920x1080i	
VGA Resolution	1024x768, 1280x720, 1280x1024, 1440x900, 1920x1080	
Split Display	1/4/9 way	1/4 way

RECORDING

Compression	H.264 / MPEG4 / JPEG	
Resolution (Pixel)	1080P(1920x1080) / 720P(1280x720) / D1(720x480/720x576)	
Mode	Normal, Event(Alarm/Motion), Schedule	
Rec Frame	120fps@1080p 240fps@720p 240fps@D1	120fps@1080p 120fps@720p 120fps@D1

PLAYBACK

Split Display	1/4/9 way Split	1/4 way Split
Search Mode	Date & Time, Calendar, Event(Alarm/Motion), Bookmark	
Mode	Normal, REW(*1,*2,*4,*8,*16) & FF(*1,*2,*4,*8,*16,*32),Frame to Frame, Pause, Slow REW/FF91/2, 1/4, 1/8, 1/16, 1/32)	

NETWORK

Network Interface	Ethernet*2 (for IP Camera, Client PC)
Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPOE(ADSL), RTP/RTSP
Serial Communication	RS-232 x1, RS-485 x2 (PTZ & Keyboard Control)
Application	Windows 2000 / XP(PC Client System) / Windows Vista
Web Browser	Internet Explorer 5.0 Higher (NVR Control or Monitoring)
Event Transport	E-mail notification when Event occurs
Viewing / User Access	PC Client, CMS, Mobile Viewer / Up to 25 users

ARCHIVE

Interface	USB 2.0x2 , e-SATA
Archive Device	Internal DVDRW, Network, USB Memory Stick, e-SATA Storage

EVENT

Motion Detection	Area : Programmable motion detection area for each camera Sensitivity : 10 Steps for each channel
Event Log	Up to 5000 events logs (Alarm, Motion, Video & Power Loss, Power & Record On/Off)

CONTROL

Controller	IR Remote Control / Mouse
PTZ Camera	Control From RS485 Interface / Via Network

OTHERS

Operating System	Embedded Linux OS
HDD/ODD	Support Max. 2 HDDs up to 6TB
Power Source	D12V/3.5A
Power Consumption	40W
Weight	3Kg(Net) / 4Kg(Gross)
Dimension	350(W)x250(D)x72(H)mm/Net , 400(W)x340(D)x150(H)mm/Box