

# Fire Detection Equipment

## UNIQUE Twin Flashing Lights



### TECHNICAL DATA

<b>Model No.</b>	KP305B (BULB), KP305L (LED)
<b>Code No.</b>	FAE-FLO-BU, FAE-FLO-LED
<b>Lens</b>	High efficient prismatic polycarbonate lens optimized for omnidirectional viewing.
<b>Luminary</b>	Filament Bulb/Ultra Bright LED
<b>Size</b>	210mm(W) x 77mm(D) x 108mm(H)
<b>Material (Casing &amp; Hood)</b>	Mild Steel
<b>Weight</b>	Epoxy Powder Red
<b>Finishing</b>	Black casing with green and red lens

## PROGRAM Gas Fire Extinguishing Panel



SIZE				
No. of Zones	Model no.	Code no.	Size (mm) (W x D x H)	
			Normal	Weatherproof
2	PE-HP2000	FAP-02ZCP-N	430 x 195 x 370	435 x 195 x 410
4	PE-HP4000	FAP-04ZCP-N	525 x 178 x 380	540 x 178 x 420
TECHNICAL DATA				
<b>Power Supply Input</b>			240V AC 50Hz	
<b>Operating System</b>			24V DC	
<b>Charger</b>			Automatic/Trickle Type	
<b>Charging Rate</b>			300mA (Trickle) 2.5A (Boost)	
STANDBY MODE				
<b>Master</b>			75mA	
<b>Per zone (with detectors)</b>			5mA	
<b>Flashing Lights (Red LED)</b>			75mA	
ALARM MODE				
<b>Master</b>			120mA	
<b>Per Trigger Zone</b>			70mA	
<b>Output Devices</b>			100mA	
<b>Flashing Lights (Red LED)</b>			75mA	
<b>Per Bell</b>			30mA	