
Problem: Determine an array of y for x = 0 to $\pi/2$ in increments of $\pi/40$. Also, calculate an array of values for $z = y ^2$ for each value of x.

$$y = be^{-ax} \sin(bx) (0.012 x^4 - 0.15 x^3 + 0.075 x^2 + 2.5 x)$$
$$z = y^2$$

Plot both functions on the same graph with y as a solid line and z as symbols only. Add labels to each axis, a title, and a legend.

Solution: I used Matlab for the solution.

```
%% Problem #1
% References fuction to compute values of y based on x, and values of z based
% Graphs functions y and z versus x on the same graph.
% Differentiates with legend and different line styles for y and z.
% Reset Matlab variables, command window, and figures.
clear all; close all; clc
%Constants
a = 2i
b = 5;
%Array of X values created
x = 0:pi/40:pi/2;
Solve for an array of y values based on x
y = b.*exp(-a.*x).*sin(b.*x).*(0.012.*x.^4-0.15.*x.^3+0.075.*x.^2+2.5.*x);
%Solve for an array of z values based on y based on x
z = y.^2;
%Plot graph of z and y versus x
plot(x,y,x,z,'o'); grid on;set(gca,'GridLineStyle','-');xlabel('X');
ylabel('Y and Z'); title('Cunningham Problem #1');
legend('Y', 'X', 'Location', 'NorthEast');
```



PROBLEM: Use Manning's equation to compute the velocity of water in five rectangular open channels:

$$U = \frac{\overline{S}}{n} \left(\frac{BH}{B + 2H} \right)^{0.667}$$

where U = velocity(m/s), S = channel slope, n = roughness coefficient, B = width(m), and H = depth(m). The data to calculate the velocity follows:

n	S	В	H
0.035	0.0001	10	2
0.020	0.0002	8	1
0.015	0.0010	20	1.5
0.030	0.0007	24	3
0.022	0.0003	15	2.5

Create and a matrix for the data and compute the velocities so that output will be in a column vector where each row represents a different channel.

SOLUTION:

Here is my script:

```
%% Problem 2
% Using Manning equation compute the velocity given a 4x4 matrix of values.
% The following symbols are noted with the terms they represent
% U = velocity(m/s), S = channel slope, n = roughness coefficient, B =
width(m), and H = depth(m)
% n all rows, column 1; S all rows, column 2; B all rows, column 3; H all
rows column 4
clear all; close all; clc;
 % Creates data matrix of all values
param = [0.035 0.0001 10 2; 0.020 0.0002 8 1; 0.015 0.0010 20 1.5; 0.030
0.0007 24 3; 0.022 0.0003 15 2.5];
 % Assigns the corresponding column with its variable to streamline
n = 1; s = 2; b = 3; h = 4;
 % Create row matrix of variables to allow for single line running.
y = [1, 2, 3, 4, 5];
 % Single matlab line that creates a column vector of velocities.
(sqrt(param(y,s))./param(y,n)).*(param(y,b).*param(y,h)./(param(y,b)+2.*param
(y,h))).^0.667;
 fprintf('Velocities\n %f \n %f \n %f \n %f \n',U);
```

3

And it's output:

Velocities

0.362453

0.609321

2.516959

1.581352

1.197374

PROBLEM: Use the following data to solve the equation describing the relationship for a chemical reaction and compare the recorded versus computed data:

t (min)	10	20	30	40	50	60
c (ppm)	3.4	2.6	1.6	1.3	1.0	0.5


$$c = 4.84 e^{-0.034 t}$$

Use Matlab to create and plot both the calculated(dotted line) and recorded(diamonds) value c(ppm). Plot the function for t = 0 to 70. Add a labels for both axes and title.

SOLUTION:

```
%% Problem 3
% Creates a plot displaying data and a function based on the data.
% Creates two arrays of already obtained data, one for the time(t) and one
for the ppm(cdat)
clear all; close all; clc;
tdata = [10 20 30 40 50 60];
cdat = [3.4 2.6 1.6 1.3 1.0 0.5];
% Calculates the predicted ppm(ccalc)
tcalc = [0 10 20 30 40 50 60 70];
ccalc = 4.84 * exp(-0.034.*tcalc);
plot(tdata, cdat,'d', tcalc, ccalc,'--'); grid on; set(gca, 'GridLineStyle',
'-');xlabel('Time(sec)'); ylabel('Parts Per Million(PPM)'); title('Chemical
Reaction');
legend('PPM Recorded', 'PPM Calculated', 'Location', 'North');
```

And it's output:



PROBLEM: Create the following equation in Matlab and test it using P = \$55,000, i = 0.066, n from 1 to 5

$$A = P \frac{i(1+i)^n}{(1+i)^n - 1}$$

Display the results as a table with headings and columns for n and A.

SOLUTION:

Here is my script:

```
%% Problem 4(Book 2.9)
% Computes the value of function 'A' based on 'i','n','P'
% Clears all windows, commands, and variables
clear all; close all; clc;
% Set the constants and given values
P = 55000; i = 0.066; narray = [1 2 3 4 5];
A(5) = 0;
fprintf('Year \t Annual Payment\n');
for n = 1:5
    A(n,1) = P*i*(1+i)^n/((1+i)^n-1);
    fprintf('%d \t\t %0.2f\n',n,A(n,1));
end
```

And it's output is:

Year	Annual Payment
1	58630.00
2	30251.49
3	20804.86
4	16091.17
5	13270.64

PROBLEM: Create a well-structured function to compute v as a function of t in Matlab for t = -5 to 50 at increments of 0.5


$$v(t) = \begin{cases} 11t^2 - 5t & 0 \le t \le 10\\ 1100 - 5t & 10 \le t \le 20\\ 50t + 2(t - 20)^2 & 20 \le t \le 30\\ 1520e^{-0.2(t - 30)} & 20 \le t \le 30\\ 0 & Otherwise \end{cases}$$

Output the solution in graph form(saves space).

SOLUTION:

```
%% Problem 5(Book 2.18)
% Computes velocity of a rocket as a fuction of time using logical
elimination of options in a piecewise function
% Clears all windows, commands, and variables
clear all; close all; clc;
% Creates the range of time(t)
tarray = -5:0.5:50;
t = -5;
n = 1;
v(111) = 0;
%Call up table header
fprintf('Time \t Rocket Velocity\n');
for i = 1:0.5:56
if t>30
   v(n) = 1520*exp(-0.2*(t-30));
    elseif t<=30 && t>=20
       v(n) = 50*t+2*(t-20)^2;
       elseif t<=20 && t>=10
           v(n) = 1100 - 5*t;
           elseif t<=10 && t>=0
               v(n) = 11*t^2 - 5*t;
               else
                   v(n) = 0;
end
t = t+0.5;
n = n+1;
end
%Create plot referenced from data and table.
plot(tarray, v); xlabel('Time(sec)'); ylabel('Rocket Velocity');
title('Rocket Velocity from Blast Off');
```

And its output in graph form(Matlab will also output in table form):



PROBLEM: Use the following singularity function and the expressed function of singularity to solve for the displacement of a beam 10 feet long. X = 0 at the left end.

$$(x-a)^n \begin{cases} (x-a)^n & when \ x > a \\ 0 & when \ x \le a \end{cases}$$
 (1)

$$u_y(x) = -\frac{5}{6}[(x-0)^4 - (x-5)^4] + \frac{15}{6}(x-8)^3 + 75(x-7)^2 + \frac{57}{6}x^3 - 238.25x$$
 (2)

SOLUTION:

```
%% Problem 6(Book 2.22)
% Creates of a plot of displacement versus distance along a simply supported
% Clears all windows, commands, and variables
clear all; close all; clc;
%Set starting variables and constants
x = 1;
y(11) = 0;
while x<=10
    if x <= 0
        a0 = 0;
        a0 = x^4;
    end
    if x<=5
        a5 = 0;
    else
        a5 = (x-5)^4;
    end
    if x<=8
        a8 = 0;
        a8 = (x-8)^3;
    end
    if x <= 7
       a7 = 0;
    else
        a7 = (x-7)^2;
    y(x+1) = -5/6*(a0-a5)+15/6*a8+75*a7+57/6*x^3-238.25*x;
    x = x + 1;
end
xplot = 0:10;
plot(xplot,y); xlabel('Distance along beam (ft.)'); ylabel('Displacemnt
(ft.)'); title('Displacement of Simply Supported Beam');
```

And its output:

