

A Brief Introduction to *MATLAB*[®]

References: The Student Edition of MATLAB[®] Version 4 and 5 User's Guides
Introduction to MATLAB[®] 6 by DM Etter and DC Kuncicky, with D Hull
Feedback Control of Dynamic Systems, 4th Ed., by GF Franklin,
JD Powell, and A Emami-Naeini

The *MATLAB* User Interface

You launch *MATLAB* from either the computer desktop icon or the >Start>Programs>Matlab 6.x>Matlab 6.x pull-up list. The launch may be delayed due to virus-scanning, so be patient.

The *MATLAB* window will be displayed, and contain three major sub-windows labeled: Command Window along the right side, Workspace/Launch Pad in the upper-left corner, and Current Directory/Command History in the lower-left corner.

Change the current directory from the default to E:\Student Files, so that you may easily access your data/script files. This change can be done from either the *MATLAB* window toolbar or the Current Directory window toolbar.

Much of the following “tutorial” will focus our attention on typing script commands within the Command Window at the user-command prompt indicated by the >> symbol. Additional Figure windows may pop-up when plotting of data occurs.

Vector definition and addressing

Explicit definition

```
»x=[0.0,0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9,1.0] % commas
```

or

```
»x=[0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0] % spaces
```

Implicit definition (colon notation)

```
»x=(0:0.1:1.0) % format: x=(start_value:D_value:end_value)
```

or

```
»x=linspace(0,1.0,11)
% x=linspace(first_value,last_value,# of values)
```

or

```
»x=logspace(0,2,100); % the ; suppresses on-screen echo
% x= logspace(first_exponent,last_exponent,# of values)
% here the the values go from 100 to 102 with 200
% increments inclusive
```

Vector element addressing

```

»x(4) % 4th element of x
or
»x(1:5) % elements 1 through 5 of x
or
»x(1:3:10) % increment by 3 from element 1 through 10 of x
»x=(0:0.1:1.0) % generates a row vector

                    % transposing x will give a column
                    % vector

»y=x' % the ' operator transposes an array (using .'
      % operator gives the non-complex-conjugate transpose)
or
»y=[1;2;3;4;5;6;7;8;9;10] % here the ; separating the
                        % elements inserts the next
                        % element on a new row.
                        % Hence, y is a column vector.


```

Array definition and addressing

```

»A=[1,2,3,4,5;6,7,8,9,10]

```



 The semi-colon separates the first row from the second row. Each row has 5 elements separated by commas.

or

```

»A=[1 2 3 4 5 <CR> 6 7 8 9 10 ]

```


 The <CR> separates the first row from the second row. Each row has 5 elements separated by spaces.

```

»A(2,4) % 4th element of row 2 of A
»A(1:2,2:3) % sub-array of A containing elements in the
            % first two rows of A in columns 2 and 3

```

*Note: given an array **A***

```

»A.^3 % raises each element of A to the power of 3
      % (Note the period before the ^)

»A^3 % raises matrix A to the power of 3

»whos % displays the variables and their size

```

2D Plotting

```
»x=(0:pi/100:2*pi); % create 201 x values from 0 to 2π
»y=sin(x);
»plot(x,y) % single plot on a single set of axis
```

or

```
»figure(2) % creates second figure window
»z=cos(x*4);
»plot(x,y,x,z) % two plots on a single set of axis
                % (Note that they both share the same
                % independent variable, x)
```

Axis labeling

```
»xlabel('x axis')
»ylabel('y axis')
»title ('My title')
»grid
```

or, use a “command cascade”

```
»xlabel('new x'),ylabel('new y'), title ('new title'), grid
```

Polar plots can be obtained as follows

```
»figure(3) % creates third figure window
»theta=x; % theta is the polar “angle” in radians
»sigma=y; % sigma is the polar “radius”
»polar(theta,sigma) % plot sin(x) vs x in polar coords
```

2D Sub-Plotting

To create multiple plot windows within a single figure, use the `>>subplot` command. As an example, generate a quadratic polynomial to be displayed four different ways

```
»clc % clears the “command window”
»clf % clears the current figure

»clear % THIS COMMAND NUKES ALL VARIABLES FROM MEMORY
        % there is no “Are you sure? <y or n>” safety net
```

```
% generate new data
```

```
»x=(0:0.5:50); % create 101 x values from 0 to 50
»y=5*x.^2;
```

(continued)

```

»subplot(2,2,1), plot(x,y),
    title('Polynomial – linear/linear axes'),
    ylabel('y'), grid
»subplot(2,2,2), semilogx(x,y),
    title('Polynomial – log/linear axes'),
    ylabel('y'), grid
»subplot(2,2,3), semilogy(x,y),
    title('Polynomial – linear/log axes'),
    xlabel('x'), ylabel('y'), grid
»subplot(2,2,4), loglog(x,y),
    title('Polynomial – log/log axes'),
    xlabel('x'), ylabel('y'), grid

```

Note that »subplot (u,v,w) sets up a u-by-v “plot matrix” within the figure window. Each respective sub-figure is addressed by parameter w starting at the upper-left position in the grid.

Data Formats

Display formatting is by default “short” which means fixed-format with 4 decimal digits, and with “loose” organization that employs extra line-feeds when displaying matrix contents. These conditions are specified within the MATLAB “Command Window” via the >File>Preferences pull down menu. To change these preferences from the command line specify

```

»format short      % example 16.1234 (4 decimal digits)

»format long       % example 16.12345678901234
                  % (14 decimal digits)

»format short e    % e-format 1.6123e+01

»format long e     % e-format 1.612345678901234e+01

»format blank      % 16.12 (2 decimal digits)

»format compact    % reduces extra line-feeds in matrix
                  % displays

»format loose      % returns extra line-feeds in matrix
                  % displays

```

Differential equations

Suppose we have the following differential equation

$$\ddot{x} + \dot{x} + x = f(t) \quad (1)$$

where

$f(t)$ = unit step input

Note

$\ddot{x} + 2\zeta\omega_n \dot{x} + \omega_n^2 x = f(t)$
therefore in the above example
 $\omega_n = 1$ and $\zeta = 0.5$
hence the system is underdamped!

1. convert Eq.(1) in *state-space equation* format

Let $x_1 = x$

$$\begin{aligned} \dot{x}_1 &= x_2 \\ \dot{x}_2 &= f(t) - x_1 - x_2 \end{aligned} \quad (2)$$

2. putting Eq.(2) into *state-space vector* (ss) format

$$\begin{aligned} \begin{Bmatrix} \dot{x} \\ x \end{Bmatrix} &= [A]\begin{Bmatrix} x \\ x \end{Bmatrix} + [B]\begin{Bmatrix} u \end{Bmatrix} \\ \begin{Bmatrix} y \end{Bmatrix} &= [C]\begin{Bmatrix} x \\ x \end{Bmatrix} + [D]\begin{Bmatrix} u \end{Bmatrix} \end{aligned}$$

we get

$$\begin{aligned} \begin{bmatrix} \dot{x}_1 \\ \dot{x}_2 \end{bmatrix} &= \begin{bmatrix} 0 & 1 \\ -1 & -1 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} + \begin{bmatrix} 0 \\ 1 \end{bmatrix} f(t) \\ \begin{bmatrix} y_1 \\ y_2 \end{bmatrix} &= \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \end{bmatrix} f(t) \end{aligned}$$

3. Eq.(1) in *transfer function* (tf) format

$$\frac{X(s)}{F(s)} = \frac{1}{s^2 + s + 1}$$

for $f(t)$ = unit step input

$$X(s) = \frac{1}{s^2 + s + 1} \left(\frac{1}{s} \right)$$

Solution scenarios

1. Using the Runge-Kutta method

Define a *function m-file* from the *MATLAB* Window toolbar by choosing **File** menu, then **New> m-File**, then type the following

```
function xdot = xdeqns(t,x);
xdot = [x(2)
        1-x(1)-x(2)];      % xdot equation column
                           % vector
```

Once your function is entered choose **Save** from the **File** menu and *accept* the default name.

To solve the function use the Runge-Kutta solver built within MATLAB called **ODE23** or **ODE45**

- generic format » `[t,x]=ode45('function name',tspan,y0);`
- for our example
 » `tspan=[0 10];` Start time Stop time
 » `y0=[0;0];` $x(1)_{IC}; x(2)_{IC}$
 » `[t,x]=ode45('xdeqns',tspan,y0);`

The ODE solver returns a time vector, *t*, and a solution array, *x*. To parse the solution array

```
»x1=x(:,1); % 1st column x(1)
»x2=x(:,2); % 2nd column x(2)
»figure(1) % define active figure window
»plot(t,x1,t,x2,'--') % where '--' represents line style
```

Alternatively, you may define the A, B, C, D arrays from the **state space** representation

```
»A=[0 1;-1 -1];
»B=[0;1];
»C=[1 0;0 1];
»D=[0;0];
»sys=ss(A,B,C,D); % state vector system definition
```

```

»t2=linspace(0,10,100);           % generate a time vector
»[yy,xx]=step(sys,t2);           % simulate the system using a
                                % unit step input
»yy1=yy(:,1);
»yy2=yy(:,2);
»figure(2)                        % define second figure window
»plot(t2,yy1,t2,yy2)

```

2. Solution via Laplace transforms in the **s-domain**

```

»num=[1];                        %  $0s^2+0s+1$ 
»den=[1 1 1];                   %  $1s^2+1s+1$ 
»sys=tf(num,den);               % transfer function system definition
»t3=linspace(0,10,100);
»[yyy,xxx]=step(sys,t3);
»figure(3)                      % define third figure window
»plot(t3,yyy,'+')

```

3. Solution via “block diagrams” using the *MATLAB* add-on program called *SIMULINK*®.

In brief, the *SIMULINK* environment is a graphical approach to system definition, response simulation, and graphing. And simulation data may be routed from the *SIMULINK* environment to the *MATLAB* Command Window for further analysis, graphing, export, etc.

To use *SIMULINK*® see the separate tutorial.

Further Scripting

The Runge-Kutta method of differential equation solution noted previously employed a *MATLAB* “function” or “*m*-file” to hold important state-equations (i.e., *xdeqns.m*). This function was repeatedly called from within “master” solution routine (i.e., *ode23.m*) sever dozen to several thousand times. We might also create *m*-files to assist other calculations and save ourselves repeated keyboard entries within the Command Window.

By way of example, suppose we wish to create our own solution to evaluate the “sinc” function $\frac{\sin(x)}{x}$ which we will call “*sinc_x.m*”. (Note here that the *MATLAB* “canned” routine *sinc.m* is available to evaluate the function $\frac{\sin(\pi x)}{\pi x}$, and we could have employed *sinc.m* pre-scaling our input vector *x* by $1/\pi$.) In crafting our *m*-file *sinc_x* note that the function $\frac{\sin(x)}{x}$ may introduce a divide-by-zero error if the vector *x* contains one or more zero values. Hence, we will need to employ the *MATLAB* logical functions *find.m* and *abs.m* along with Boolean arguments for “less-than” (<) and “greater-than-or-equal-to” (>=) within our script-file.

From the *MATLAB* Window toolbar choose the **File** menu, then **New> m-File**

```
function s = sinc_x(x);
%
%SINC_X computes the values of (sin(x))/x
%
s=x;
set1=find(abs(x) < 0.001); % abs(x) computes magnitudes
                           % of input vector elements,
                           % find() returns a vector of
                           % indices of the nonzero
                           % elements of the argument
                           % vector (),
                           % here that is the elements of x near
                           % zero (0.001) magnitude
set2=find(abs(x) >= 0.001); % elements of x with magnitudes
                           % greater than zero (0.001)
s(set1)=ones(size(set1)); % ones() creates a vector
                           % containing all unit values
                           % at matched indices where the
                           % vector x is near zero mag
                           % Note via L'Hopital's Rule (sin(x))/x =1 for x=0
                           %
s(set2)=sin(x(set2))./x(set2);
                           % evaluates (sin(x))/x at
                           % indices where x is non-zero
% Note that the entire vector s is returned by
% our sinc_x.m routine to the calling routine or
% command line
```


To utilize `sinc_x.m` from the *MATLAB* command line enter the following

```
»clf
»x=(-15:0.1:15);
»y=sinc_x(x);
»plot(x,y), xlabel('x'),ylabel('y')
»title('My Sinc Function'), grid, pause
    % pause requires user <cr> to return control
```

Saving Data to File

To create an *Excel* or *Wordpad* readable 2-column data file from *MATLAB* commands:

Using *MATLAB* row-dominant data vectors

```
% create x and y data

»xr=[0:0.1:10];      % independent variable
»yr=sin(2*pi*xr);    % dependent variable
»figure(1)           % first figure window
»plot(xr,yr)

% to combine xr and yr data as a matrix with
% synchronous x y values

% in adjacent columns, such as  $\begin{bmatrix} x_1 & y_1 \\ x_2 & y_2 \\ \vdots & \vdots \\ x_n & y_n \end{bmatrix}$ , we need to define a

% new array

»z=[xr;yr]';          % where the apostrophe
                      % signifies "matrix transpose"

% save the z array to the file "myfile1.xls" in
% the "current directory" as a two-column,
% tab-delimited ASCII readable file suitable for
% direct Excel open/importation

»save('myfile1.xls','z','-ascii','-tabs');
```

Using *MATLAB* column-dominant data vectors

```
% create x and y data
```

```

»xc=[0:0.1:10]';          % note the apostrophe
»yc=sin(2*pi*xc);
»figure(2)                % second figure window
»plot(xc,yc)

% to combine the xc and yc data as a matrix with
% synchronous x y values in adjacent
% columns (as above), we need another new array

»zz=[xc,yc];              % note change in syntax from above
                           % formulation for array "z"

% save the zz array to file "myfile2.xls" in
% the "current directory" as a two-column,
% tab-delimited ASCII readable file suitable for
% direct Excel open/importation

»save('myfile2.xls','zz','-ascii','-tabs');

```

Loading Data from File

It is possible create a **MATLAB** “workspace” variable from data contained in an ascii, tab delimited file created in **Excel**, **Wordpad**, or **LabVIEW**. The file must contain *numbers only* without alpha headers and reside in the “current directory”.

To import data from a file using a ‘.txt’ extension use the following **MATLAB** command example:

```

% save the data from the file "myfile2.txt" to the array v:

»v=load('myfile1.txt');

```

To import a **LabVIEW** data file (no header) using a ‘.lvm’ extension use:

```

% save the data from the file "myfile42.lvm" to the array vv:

»vv=load('myfile1.txt');

```

To import data from an ascii, tab delimited file that is *sans* extension use:

```

% save the data from the file "myfileXYZ" to the array vXYZ:

»vXYZ=load('myfileXYZ');

```

Direct importation of **Excel** ‘.xls’ or ‘.wbk’ files will NOT work by the methods noted above. Use the direct *cut & paste* approach between selected **Excel** workbook or worksheet files and the **MATLAB** array editor.

System Polynomials

MATLAB polynomial manipulations of $G(s) = \frac{3s^2 + 5s + 1}{s^2 + 1s + 1} = \frac{n(s)}{d(s)}$ are done as follows:

To find polynomial factors:

```
>> n=[3 5 1];
>> roots(n)
ans =
    -1.4343
    -0.2324

>> d=[1 1 1];
>> roots(d)
ans =
   -0.5000 + 0.8660i
   -0.5000 - 0.8660i
```

To multiply two polynomials $n(s)*d(s)$ use the “convolution” command:

```
>> conv(n,d)
```

```
ans =
     3     8     9     6     1
```

which means $n(s) * d(s) = 3s^4 + 8s^3 + 9s^2 + 6s + 1$

MATLAB command-line help yields the following info:

```
>> help conv
```

CONV Convolution and polynomial multiplication.

C = CONV(A, B) convolves vectors A and B. The resulting vector is length LENGTH(A)+LENGTH(B)-1.

If A and B are vectors of polynomial coefficients convolving them is equivalent to multiplying the two polynomials.

See also DECONV, CONV2, CONVN, FILTER and, in the Signal Processing Toolbox, XCORR, CONVMTX.

Note the “See also” is particularly helpful since it reveals the following:

```
>> help deconv
```

DECONV Deconvolution and polynomial division.

[Q,R] = DECONV(B,A) deconvolves vector A out of vector B. The result

is returned in vector Q and the remainder in vector R such that
 $B = \text{conv}(A, Q) + R$.

If A and B are vectors of polynomial coefficients, deconvolution is equivalent to polynomial division. The result of dividing B by A is quotient Q and remainder R.

See also CONV, RESIDUE.

Here we can easily perform “long division” of $n(s)/d(s)$ as follows:

```
>> deconv(n,d)
```

```
ans = 3
```

Where this means the division yields the “quotient” factor “3” plus an unspecified “remainder”.

To get explicit quotient Q and remainder R use the explicit output form:

```
>> [Q,R]=deconv(n,d)
```

```
Q = 3
```

```
R = 0      2      -2
```

which means
$$G(s) = \frac{3s^2 + 5s + 1}{s^2 + 1s + 1} = \frac{n(s)}{d(s)} = Q + \frac{R(s)}{d(s)} = 3 + \frac{2s - 2}{s^2 + 1s + 1}$$

To perform Partial Fraction Expansion (PFE) use the explicit output form:

```
>> [r,p,k]=residue(n,d)
```

```
r = 1.0000 + 1.7321i  
    1.0000 - 1.7321i
```

```
p = -0.5000 + 0.8660i  
    -0.5000 - 0.8660i
```

```
k = 3
```

which means

$$G(s) = \frac{r(1)}{s - p(1)} + \frac{r(2)}{s - p(2)} + k(s) = \frac{1 + 1.7321j}{s - (-0.5 + 0.866j)} + \frac{1 - 1.7321j}{s - (-0.5 - 0.866j)} + 3s^0$$

See textbook: Palm, “System Dynamics”, McGraw-Hill, 2005, Section 3.8 for more details.