

DISCRIMINATIVE MANIFOLD EMBEDDING WITH IMPRECISE, UNCERTAIN, AND  
AMBIGUOUS DATA

By

CONNOR H. MCCURLEY

A ORAL QUALIFYING EXAM PROPOSAL PRESENTED TO THE GRADUATE SCHOOL  
OF THE UNIVERSITY OF FLORIDA IN PARTIAL FULFILLMENT  
OF THE REQUIREMENTS FOR THE DEGREE OF  
DOCTOR OF PHILOSOPHY

UNIVERSITY OF FLORIDA

2020

© 2020 Connor H. McCurley

# TABLE OF CONTENTS

	<u>page</u>
LIST OF TABLES . . . . .	5
LIST OF FIGURES . . . . .	6
CHAPTER	
LIST OF ABBREVIATIONS . . . . .	7
LIST OF SYMBOLS . . . . .	8
1 INTRODUCTION . . . . .	9
2 BACKGROUND . . . . .	21
2.1 Multiple Instance Learning . . . . .	21
2.1.1 Multiple Instance Space Paradigm . . . . .	22
2.1.2 Multiple Instance Concept Learning . . . . .	22
2.1.3 Multiple Instance Classification . . . . .	22
2.1.4 Multiple Instance Boosting . . . . .	22
2.1.5 Multiple Instance Learning with Manifold Bags? . . . . .	22
2.2 Manifold Learning . . . . .	23
2.2.1 Definition and General Notation . . . . .	25
2.2.2 Comparison Table of Manifold Learning Methods . . . . .	26
2.2.3 Geneology Image of Manifold Learning Methods from van der Maaten 2009, page 2 . . . . .	26
2.2.4 Linear Manifold Learning . . . . .	26
2.2.4.1 Principal Component Analysis (PCA) . . . . .	26
2.2.4.2 Multi-Dimensional Scaling (MDS) . . . . .	29
2.2.4.3 Non-negative Matrix Factorization (NMF) . . . . .	32
2.2.4.4 Fisher's Linear Discriminant Analysis (LDA) . . . . .	32
2.2.4.5 Locality Preserving Projection (LPP) . . . . .	35
2.2.5 Nonlinear Manifold Learning . . . . .	35
2.2.5.1 Kernelization . . . . .	36
2.2.5.2 Graph-based Methods . . . . .	38
2.2.5.3 General Graph Embedding Framework . . . . .	42
2.2.5.4 Isomap . . . . .	42
2.2.5.5 Locally Linear Embedding (LLE) . . . . .	45
2.2.5.6 Laplacian Eigenmaps (LE) . . . . .	45
2.2.5.7 Hessian Eigenmaps . . . . .	50
2.2.5.8 Diffusion Maps . . . . .	50
2.2.5.9 Sammon Mapping . . . . .	50
2.2.5.10 Maximum Variance Unfolding (MVU) . . . . .	50
2.2.6 Latent Variable Models . . . . .	50
2.2.6.1 General Latent Variable Model (GLVM) . . . . .	50

2.2.6.2	Generative Topographic Mapping (GTM)	52
2.2.7	Competitive Hebbian Learning	52
2.2.8	Deep Learning	52
2.2.9	Current State of the Art	52
2.2.10	UMAP	52
2.2.11	Stochastic Neighbor Embedding (SNE and t-SNE)	52
2.2.12	NCA	52
2.2.13	Weak Learning on Manifolds	52
2.3	Metric Embedding	56
2.3.0.1	Metric Learning	57
2.3.1	Ranking Loss	57
2.3.1.1	Pairwise Loss	57
2.3.1.2	Contrastive Loss	57
2.3.1.3	Triplet Loss	58
2.3.1.4	Large-Margin K-Nearest Neighbors (LMNN)	58
2.3.1.5	FaceNet	58
2.3.1.6	Siamese Neural Networks	58
2.3.2	Manifold Regularization	58
2.3.3	Multiple Instance Metric Learning	58
3	PROBLEM DESCRIPTION	59
4	EXPERIMENTAL DESIGN	60
5	PRELIMINARY WORK	61
6	FUTURE TASKS	62
7	CONCLUSIONS	63

## APPENDIX

## LIST OF TABLES

Table

page

## LIST OF FIGURES

<u>Figure</u>	<u>page</u>
1-1 Example of bounding box imprecision. . . . .	11
1-2 Forms of weak labels. . . . .	12
1-3 Examples of image-level labels. . . . .	12
1-4 Swiss Roll manifold unfolding. . . . .	16
1-5 Unsupervised embedding of quadratic surfaces . . . . .	17
1-6 Supervised embedding of quadratic surfaces . . . . .	18
2-1 Multiple instance learning bags. . . . .	22
2-2 Example pose data manifold. . . . .	24
2-3 PCA Example. . . . .	28
2-4 Example of MDS distance preservation. . . . .	29
2-5 LDA Example. . . . .	34
2-6 Example of a nonlinear manifold. . . . .	35
2-7 Examples of graphs. . . . .	40
2-8 Demonstration of geodesic distance . . . . .	42

## LIST OF ABBREVIATIONS

CT	Computed Tomography
CHL	Competitive Hebbian Learning
DR	Dimensionality Reduction
DSIAC	Defense Systems Information Analysis Center
EM	Expectation-Maximization
FA	Factor Analysis
FP	False Positive
FPS	Frames per Second
GLVM	General Latent Variable Model
GTM	Generative Topographic Mapping
GPS	Global Positioning System
HS	Hyperspectral
HSI	Hyperspectral Image
Isomap	Isometric Feature Mapping
LDA	Fisher's Linear Discriminant Analysis
LE	Laplacian Eigenmaps
LiDAR	Light Detection and Ranging
LFW	Labeled Faces in the Wild Dataset
LLE	Locally Linear Embedding
LMNN	Large-Margin K-Nearest Neighbors
LPP	Locality Preserving Projections
MDS	Multi-dimensional Scaling
MIL	Multiple Instance Learning
MIDR	Multiple Instance Dimensionality Reduction
MWIR	Mid-wave Infrared
NCA	Neighborhood Component Analysis
PCA	Principal Component Analysis
RBF	Radial Basis Function
ROI	Region of Interest
S-LE	Supervised Laplacian Eigenmaps
SOA	State-of-the-Art
SOM	Self-organizing Feature Map
SVD	Singular Value Decomposition
TP	True Positive
t-SNE	t-Distributed Stochastic Neighbor Embedding
UMAP	Uniform Manifold Approximation and Projection

## LIST OF SYMBOLS AND NOMENCLATURE

$\mathcal{E}$	Set of edges of an undirected, weighted graph
$G$	Undirected, weighted graph
$\mathcal{V}$	Set of vertices in an undirected, weighted graph
$\mathbf{W}$	Adjacency of affinity matrix
$\mathbf{X}$	Data matrix
$\mathcal{X}$	Riemannian manifold



## CHAPTER 1 INTRODUCTION

Target detection is a paramount area of research in the field of remote sensing which aims to locate an object or region of interest while suppressing unrelated objects and information. (Geng et al., 2017; Chaudhuri and Parui, 1995). Target detection can be formulated as a two-class classification problem where samples belonging to a class of interest are discriminated from a background distribution (Zare et al., 2018). The goal of target detection in remote sensing is to correctly classify every true positive instance (TP) in a given scene while indicating no false alarms (FA) (non-target samples predicted as targets). However, there is always a trade-off in performance, and one might actually choose to miss targets to achieve a lower false-alarm rate (Weinberger), and vice versa. Many remote sensing target detection techniques in the literature involve learning generative models which describe the target and background distributions or learning a labeling function which can differentiate between classes at test (Geng et al., 2017; Chaudhuri and Parui, 1995). Traditional supervised learning approaches such as these require extensive amounts of highly precise, sample- or pixel-level groundtruth to guide algorithmic training. However, acquiring large quantities of accurately labeled training data can be expensive both in terms of time and resources, and in some cases, may even be infeasible to obtain. To demonstrate these inherent labeling problems, consider the following real-world remote sensing examples, beginning with the hyperspectral target detection scenario described in (Du, 2017) and (Bocinsky, 2019):

Hyperspectral (HS) sensors collect spatial and spectral information of a scene by receiving radiance data in hundreds of contiguous wavelengths (Zare, 2008). Due to their inherent properties, HS cameras can provide a broad range of spectral information about the materials present in a scene, and are thus useful for detecting targets whose spectral signatures vary from the background. Such examples include airplanes on a tarmac or weeds in a cornfield. While HS provides nice properties for target detection, there are significant challenges when

utilizing this modality. First, the spatial resolution of HS cameras can be low. As an example, some HS cameras have spatial resolution of  $30m^2$  when capturing scenes from the air. This implies that objects of interest in a scene, such as an airplane, will actually be contained in a single pixel along with other materials, such as asphalt. When performing target detection/recognition on that pixel, the HS spectra will not be distinguishable as a single, pure material, but as a sub-pixel mixture where the actual materials present as well as their corresponding proportions are unknown. Second, assuming pure target pixels are available, accurate positioning at the desired resolution may not be. For example, when analyzing a scene from an airplane or satellite, it is necessary to denote the true locations of targets on the ground using a global positioning system (GPS). It is not uncommon, however, to experience GPS error of greater magnitude than the HS pixel-level spatial resolution. This implies that a halo of uncertainty potentially surrounds every target pixel in the hyperspectral image (HSI), thus making labeling on the pixel-level difficult.

This example demonstrates inherent infeasibility to obtain accurate sample-level labels due to sensor restrictions on both resolution and accuracy. Furthermore, label imprecision and ambiguity can often be presented from subjectivity between annotators. Many applications such as medical diagnosis and wildlife identification require domain experts to provide accurate data labels [Cheplygina et al. \(2019\)](#); [Ruiz-Muñoz et al. \(2015\)](#). However, there might not always be agreement between expert annotators and humans are prone to making mistakes. For example, when looking at computed tomography (CT) scans for malignant/benign tumors, many doctors would likely determine different pixel-level boundaries denoting a tumor, and in some cases, might even misclassify the detriment of the growth. Similarly, expert wildlife ecologists determining the identity of birds solely from their songs might be uncertain of a species due to corruptive background noise in the audio segment.

Finally, consider the scenarios shown in Figures [1-1](#) and [1-2](#). These figures show frames taken from the DSIAC MS-003-DB dataset ([DSIAC, 2014](#)) which demonstrates mid-wave infrared (MWIR) video segments of moving military vehicles taken at approximately 30 frames

per second (FPS). Many computer vision algorithms have already been developed to perform target detection using canonical bounding boxes (shown in green in Figure 1-1) (Redmon and Farhadi, 2018). However, drawing tight boxes around targets in each video frame is extremely tedious and time consuming. It would be beneficial if an annotator could provide a less-restrictive form of label, such as a relaxed bounding box (shown in blue in Figure 1-1 and bottom left in Figure 1-2) or as a small subset of target pixels such as single dot or scribble as shown in Figure 1-2. Labeling burden could be reduced even further if a single frame could be labeled at a high level as “including” or “excluding” target pixels, as shown in Figure 1-3.



Figure 1-1: A sample frame from the DSIAC MS-003-DB MWIR dataset. Two targets are shown with canonical bounding boxes (green) and relaxed bounding boxes (blue). Red dots represent the centers of the target objects.

Techniques which can address these forms of label ambiguity while achieving comparable or better target detection than standard supervised methods can greatly ease the burdens associated with many remote sensing labeling tasks and allow for the application of pattern recognition techniques which would otherwise be infeasible.

Learning from uncertain, imprecise and ambiguous data has been an active area of research since the late 1990s and is known as *multiple instance learning* (MIL) or *weak learning*



Figure 1-2: Examples of weakly-labeled infrared imagery. The images demonstrate various forms of weak groundtruth around a pickup truck taken with a mid-wave infrared camera. The images show spot, scribble, imprecise bounding box and image-level labels, respectively.



Figure 1-3: Example of image-level labels for binary target detection. Image (a) is denoted to contain pixels belonging to the target class somewhere within the image, while image (b) clearly contains samples solely from the background distribution.

(Bocinsky, 2019). Supervised learning assumes that each training sample is paired with a corresponding classification label. In multiple instance learning, however, the label of each sample is not necessarily known. Instead, MIL approaches learn from groups of data points called *bags*, and each bag concept is paired with a label (Cook, 2015). Under the two-class classification scenario the bags are labeled as *negative* if all data points (or *instances*) are known to belong to the background class (not the class of interest). While the actual number of positive and negative instances may be unknown, bags are labeled *positive* if *at least one*

instance is known to belong to the target class (also called a “true positive”) (Zare et al., 2018) or to contain a proportion of true target. The goal of learning under the MIL framework is to train a model which can classify a bag as positive or negative (bag-level classification) or to predict the class labels of individual instances (instance-level classification). Consider again the example shown in Figure 1-3. The figure labeled as “Target” could be considered as a positive bag because, while the image is not accompanied with pixel-level labels, it is known that a true target pixel exists somewhere within the set. Additionally, the image denoted as “Background” could be considered as a negative bag, since it does not contain any pure target pixels. Another way to formulate this problem would be to consider sets of these image patches, where a negative bag would only include samples of background patches, while a positive bag would contain at least one patch that held target or part of a target. Given data of this type, multiple instance learning could be used to discover target and/or background class representatives which could be used for class discrimination, or a classifier could be trained to label and unseen test image as containing or excluding target pixels (bag-level classification) or to label each individual pixel as belonging to the target class (instance-level classification). As with this example, the MIL problem formulation fits many remote sensing scenarios and is thus an important area of investigation (Du, 2017).

Multiple instance learning approaches in the literature can be broadly generalized into two categories: learning a generative model which effectively describes the positive and/or negative classes, or training a classifier to discriminate between target and background samples or bags. The success of both learning frameworks, however, is highly dependent on the feature representations of the data and the metrics used to measure dissimilarity. Many feature learning approaches in the literature use supervised learning to obtain discriminative feature representations, or use supervised methods to fine-tune unsupervised feature extraction. *However, this cannot be done directly in MIL because of the uncertainty on the labels* (Carbonneau et al., 2016).

Another approach to obtain useful feature representations is through the application of *manifold learning*, also commonly referred to as *dimensionality reduction* (DR), *feature embedding*, *geometric machine learning* or *representation learning* in the literature. The goal of manifold learning can be posed as discovering intrinsic (often lower-dimensional) features from the data which meet an overarching objective, such as: preserving variance, finding compressed representations of data, maintaining global or local structure or promoting discriminability in the embedded space (van der Maaten et al., 2007; Bengio et al., 2012; X. Geng et al., 2005; Thorstensen, 2009). Manifold learning and dimensionality reduction have been studied extensively in the literature and have been used for visualization, classification, redundancy removal, compression and data management, improving computational tractability and efficiency, combating the curse of dimensionality and obtaining more appropriate measures of dissimilarity (Bishop et al., 1998; Nickel and Kiela, 2017; Talmon et al., 2015; Tenenbaum et al., 2000; X. Geng et al., 2005; Palomo and Lopez-Rubio, 2017; Kohonen, 1990; Kegl et al., 2008; Bengio et al., 2012).

Dimensionality plays a significant role in determining class separability. Enough features should be incorporated as to adequately describe a class of interest, yet too many features may introduce redundancy, and thus be detrimental to the learning process. The curse of dimensionality states that the number of samples needed to characterize the space spanned by an entity grows exponentially with dimensionality (Murphy, 2012; Theodoridis and Koutroumbas, 2008). This fact is overwhelming in the context of remote sensing, as it is often both difficult to acquire large quantities of labeled data and there are often only few samples available to describe the target class (such as in air- or space-born HSI target detection). Additionally, dissimilarity metrics often break down in high dimensional spaces, making application of traditional classifiers difficult. *Therefore, it is intuitive that approaches should be developed which can combat the curse of dimensionality and provide more appropriate similarity metrics while also addressing the problems associated with uncertain, imprecise, and ambiguously labeled training data.*

The underlying assumption in using manifold learning for discrimination is that opposing classes either reside on separate manifolds or different regions of a joint, intrinsic manifold, where samples of the same class are close and samples from disparate classes are metrically far. Essentially, the governing class distributions can be described by hyper-surfaces which follow constraints on properties such as continuity and smoothness (Belkin and Niyogi, 2004). The goal of learning in this scenario is to discover embedding functions from the input feature space to a lower-dimensional embedding space where the transformed feature representations allow for improved class discrimination.

Methods for representation learning have recently gained in popularity because they typically result in high levels of classification accuracy. Some of these methods learn features in a supervised manner to obtain more discriminative representations. As mentioned previously, this learning cannot be done directly in MIL because of the uncertainty on the labels. Thus, *adaptation of discriminative feature learning methods would be beneficial to MIL* (Carboneau et al., 2016), yet this area of research has scarcely been explored. The first true experimentation was performed in (Sun et al., 2010). In this work, Sun et al. showed that Principal Component Analysis (PCA) failed to incorporate bag-level label information and thus provided poor separation between positive and negative bags. Additionally, Linear Discriminant Analysis (LDA) was used to project bags into a latent space which maximized between-bag separation, while minimizing within-bag dissimilarity. However, LDA often mixed the latent bag representations due to the uncertainty of negative sample distributions in the positive bags. To address these issues, Sun proposed Multiple Instance Dimensionality Reduction (MIDR) which optimized an objective through gradient descent to discover sparse, orthogonal projection vectors in the latent space. Their approach relied on fitting a distribution of negative instances and applying maximum likelihood estimation. This approach was later extended in (Zhu et al., 2018) in attempt to improve sparsity. Both of these methods rely on fitting a distribution of negative instances and determining positive instances as samples which have low likelihood of belonging to the distribution. However, these approaches fail when the the target and






Figure 1-4: (a) This dataset is known as the Swiss Roll and it depicts a 2-dimensional manifold embedded in 3 dimensions. (b) The Swiss Roll unfolded according to the geodesic path around the manifold.

background instances are metrically similar in the feature space. For example, consider the data shown in Figure 1-4. This image demonstrates the popular Swiss Roll dataset, which is a 2-dimensional manifold folded in 3-dimensions. Assume that the data classes lie on separate ends of the manifold, and that samples are governed by a smooth labeling function. In Figure 1-4a, the red samples denote one class while the blue represent another. If using Euclidean (straight line) distance to measure dissimilarity, it would appear that many red samples are (untrue) close to the blue. However, if an alternative distance metric such as geodesic distance (around the curve) is used to measure dissimilarity between samples, the true class distributions are better represented. Figure 1-4b shows the unfolding of the manifold according to geodesic distance. It can be observed that, after the unfolding, the classification problem was transformed from a nonlinear to a linear one. Additionally, a dimension of the data was deemed unnecessary. It would, therefore, be beneficial to first transform the instance representations into more discriminable forms. Most existing approaches in the literature extend LDA to distinguish between positive and negative bags (Chai et al., 2014; Zhu et al., 2018). These methods typically rely on costly optimization procedures to maximize an objective for orthogonal and sparse projection vectors. The work in (Xu et al.) investigated metric learning on sets of data







(a) Separable 3-dimensional quadratic surfaces.



(b) Non-separable 3-dimensional quadratic surfaces.




(c) 1-dimensional embedding of separable quadratic surfaces.




(d) 1-dimensional embedding of non-separable quadratic surfaces.

Figure 1-5: Unsupervised embedding of quadratic surfaces using Laplacian Eigenmaps with a  $K$ -nearest neighbors graph.


(where each bag was a set) to learn an appropriate similarity metric to compare bags. They do not go as far as to discriminate positive instances within the positive bags, nor do they propose positive target concepts. *In fact, virtually all MIL DR methods in the literature are applied, solely, to predict bag-level labels.* While bag-level label prediction is useful in many remote sensing applications, such as region of interest (ROI) proposal for anomaly detection, they limit the the ability of learners to classify on the pixel or sample level. To this end, methods for instance-level discriminative dimensionality reduction should be developed. This point is demonstrated in by the embeddings of 3-dimensional quadratic surfaces as shown in Figures 1-5 and 1-6. Figures 1-5a and 1-5b demonstrate a set of separable and non-separable quadratic




(a) Separable 3-dimensional quadratic surfaces and examples potential bag splits. Blue circles represent negative bags while red circle denote positive bags.



(b) Non-separable 3-dimensional quadratic surfaces and examples potential bag splits. Blue circles represent negative bags while red circle denote positive bags.



(c) 1-dimensional embedding of separable quadratic surfaces using Supervised Laplacian Eigenmaps.



(d) 1-dimensional embedding of non-separable quadratic surfaces using Supervised Laplacian Eigenmaps.

Figure 1-6: Embedding of quadratic surfaces using Supervised Laplacian Eigenmaps.

surfaces, respectively. The use of a traditional, unsupervised dimensionality reduction method to project the data into a 1-dimensional space managed to retain topological ordering of the samples, but failed to promote class discriminability, as shown in Figures 1-5c and 1-5d. However, using a supervised version of the same algorithm demonstrated the enforcement of class separability in the latent embedding space for both the separable and non-separable quadratic surfaces, as shown by Figures 1-6c and 1-6d. This embedding used sample-level labels. However, the proposed work will relax the precision of the labels to bags as to comply with the labeling needs of many remote sensing problems. This notion can be conceptualized

by Figures 1-6a and 1-6b, where sets of data samples are used to form bags. While Xu et al. proposed an importance term to weight samples believed to be true target exemplars, as those instances are more important in determining the bag-level label (Xu et al.), to the author's knowledge, no work has been done to investigate instance-level discrimination through manifold learning/ dimensionality reduction.

To address these points, I propose the following. During this project, techniques will be explored for use in instance-level classification given uncertain and imprecise groundtruth. These methods will be developed as universal approaches for discriminative manifold/feature representation learning and dimensionality reduction and will be evaluated on a variety of sensor modalities, including: mid-wave IR, visible, hyperspectral and multispectral imagery, LiDAR and more. *The aim of this project is to develop dimensionality reduction methods which promote class discriminability and are simultaneously capable of addressing uncertainty and imprecision in training data groundtruth.* The motivating idea is to facilitate instance/concept proposition by increasing instance discriminability under the constraints of multiple instance learning. Roughly, the following research questions will be addressed during the scope of this project:

1. Supervised and semi-supervised manifold learning have proven effective at discovering low-dimensional data representations which provide adequate class separation in the latent space. However, only a handful of manifold learning procedures consider data that is weakly or ambiguously labeled. To address this gap in the literature, a method for weakly-supervised manifold learning will be developed. How does this method of manifold construction compare to state-of-the-art (SOA) manifold learning techniques as well as alternative ML dimensionality reduction methodologies for instance-level label prediction?
2. In conjunction with dimensionality, the use of metric embedding has been shown to promote class separability in the latent space. However, metric embedding typically requires knowledge of instance-level labels. Using only weak, bag-level labels, a method for metric embedding will be developed and utilized with the manifold learning approach in Objective 1 to potentially improve class separation of individual instances. Additionally, a procedure to select the most influential examples for training will be developed.
3. Do the proposed methods facilitate concept learning/selection? Using alternative state-of-the-art MIL approaches, are the selected target instances/concepts more discriminable with the proposed methods than without? How do the proposed methods compare to

the alternatives in terms of representation dimensionality, computational complexity, and promotion of discriminability?

Experiments will be conducted on both synthetic data and real applications such as target detection, scene understanding and semantic segmentation in remote sensing imagery. Datasets will include the DSIAC MS-003-DB Algorithm Development Database, MUUFL Gulfport, Faces in the Wild (LFW) and benchmark MIL classification datasets ([DSIAC, 2014](#); [Gader et al., 2013](#); [Du and Zare, 2017](#); [Glenn et al.](#); [Huang et al., 2007](#)). Initial results demonstrate the aptitude of the proposed approaches and suggest further development and evaluation of these methods.

## CHAPTER 2 BACKGROUND

This chapter provides a literature review of the Multiple Instance Learning framework for learning from weak and ambiguous annotations. A review is provided on Manifold Learning, including classic approaches, supervised and semi-supervised methods and uses of manifolds for functional regularization. Additionally, this chapter reviews the existing literature on metric embedding, focusing heavily on the utilization of contrastive and triplet-based loss evaluation. Reviews describe basic terminology and definitions. Foundational approaches are elaborated and advances are addressed.

### 2.1 Multiple Instance Learning

Multiple Instance Learning (MIL) was originally proposed in (Dietterich et al., 1997) as a method to handle inherent observation difficulties associated with drug activity prediction. This problem, among many others, fits well into the framework of MIL where training labels are associated with sets of data points, called *bags* instead of each individual data points, or *instances*. Under the *standard MIL assumption*, a bag is given a “positive” label if it is known that *at least one* sample in the set represents pure or partial target. Alternatively, a bag is labeled as “negative” if does not contain any positive instances (Carbonneau et al., 2016). Let  $\mathbf{X} = [\mathbf{x}_1, \dots, \mathbf{x}_N] \in \mathbb{R}^{D \times N}$  be training data where  $D$  is the dimensionality of an instance,  $\mathbf{x}_n$ , and  $N$  is the total number of training instances. The data is grouped into  $K$  bags,  $\mathbf{B} = \{\mathbf{B}_1, \dots, \mathbf{B}_K\}$ , with associated binary bag-level labels,  $\mathcal{L} = \{L_1, \dots, L_K\}$  where

$$L_k = \begin{cases} 1, & \exists \mathbf{x}_{kn} \in \mathbf{B}_k^+ \ni l_{kn} = 1 \\ -1, & l_{kn} = -1 \quad \forall \mathbf{x}_{kn} \in \mathbf{B}_k^- \end{cases} \quad (2-1)$$

and  $\mathbf{x}_{kn}$  denotes the  $n^{th}$  instance in positive bag  $\mathbf{B}_k^+$  or negative bag  $\mathbf{B}_k^-$  (Zare et al., 2018) and  $l_{kn}$  denotes the instance-level label on instance  $\mathbf{x}_{kn}$ . Figure 2-1 demonstrates the concept of MIL bags. The objective of learning under MIL is, given only bag-level label information, to

fit a model which can classify bags as either being positive or negative (bag-level classification) or to predict the class labels of individual instances (instance-level classification).




Figure 2-1: Placeholder for examples of positive and negative bag concepts

### 2.1.1 Multiple Instance Space Paradigm

Multiple Instance Learning via Embedded Instance Selection

### 2.1.2 Multiple Instance Concept Learning

### 2.1.3 Multiple Instance Classification

citation-KNN, RIPPER-MI, BP-MIP, ID3-MI, MI-SVM [Zhu et al. \(2018\)](#)

[Wei and Zhou \(2016\)](#)

### 2.1.4 Multiple Instance Boosting

### 2.1.5 Multiple Instance Learning with Manifold Bags?

Baenko et al. introduced the framework of MIL fusing manifold bags [Babenko et al. \(2011\)](#). Their work claimed that instead of finite sets of instances, bags are inherently better represented as low-dimensional manifolds in a high-dimensional feature space. They considered the scenario of classifying whether or not an image contained a face. In this scenario, the entire image was considered to be a bag, and patches of the image were considered as

individual instances. It was assumed that the collection of instances collectively formed a low-dimensional manifold. This work laid the groundwork for learning with manifold bags as well as proved PAC learnability under this framework.

## 2.2 Manifold Learning

Real-world remote sensing data such as hyperspectral imagery, ground-penetrating radar scans and sonar signals are naturally represented by high-dimensional feature vectors. However, in order to handle such real-world data adequately, its dimensionality usually needs to be reduced ([van der Maaten et al., 2007](#); [Belkin and Niyogi, 2004](#)). The problem considered in this work is discovering feature representations that promote class discriminability for target or anomaly detection. This is typically achieved in one of two ways. First, features can be projected into a high-dimensional space (such as a Kernel Hilbert Space) using a kernel function. The second option, which is the focus of this work, is to transform the data into a new (often lower-dimensional) coordinate system which optimizes feature representations for discrimination ([Vural and Guillemot, 2018](#)).

The application of *dimensionality reduction* (DR) has proven useful in myriad applications in the literature, such as: visualization of high-dimensional data, classification, redundancy removal, compression and data management, improving computational tractability and efficiency, and reducing the effects of the Curse of Dimensionality ([Bishop et al., 1998](#); [Nickel and Kiela, 2017](#); [Talmon et al., 2015](#); [Tenenbaum et al., 2000](#); [X. Geng et al., 2005](#); [Palomo and Lopez-Rubio, 2017](#); [Kohonen, 1990](#); [Kegl et al., 2008](#); [Bengio et al., 2012](#)). In classification of object entities, it is often assumed that classes can be described by an *intrinsic* subset of representative features which demonstrate geometrical structure ([Belkin et al., 2006](#)). These structures are called intrinsic *manifolds*, and they represent the generating distributions of class objects exactly by the number of degrees of freedom in a dataset ([Thorstensen, 2009](#); [Belkin and Niyogi, 2004](#)). Consider the example shown in Figure 2-2. This classic example demonstrated in ([Thorstensen, 2009](#)) shows samples from a pose-estimation dataset **CITE**. While each individual image is represented by a vector of features (pixel intensities in this case)

in  $\mathbb{R}^{4096}$ , the dataset only exhibits three degrees of freedom: 1 light variation parameter and 2 rotation angles. Thus, it is intuitive that the dataset lies on a smooth, intrinsic submanifold spanning three dimensions which inherently capture the degrees of freedom in the data.




Figure 2-2: Placeholder for example of high D data lying on a low-dimensional sub-manifold.

The goal of manifold Learning is then to discover embedding functions which take data from the input feature space and transform it into a lower-dimensional (ideally intrinsic) coordinate system (also called a *latent space* in the literature) which captures the “useful” properties of the data, while enforcing constraints such as smoothness (the transformation function should not produce sporadic images), continuity (no discontinuous points on the hyper-surface), topological ordering (neighbors in the input space should also be neighbors in the embedded space ) or class separability (samples from the same class should fall metrically close to each other in the embedded space and disparate classes should be distinctly far) ([Vural and Guillemot, 2018](#)).

This dissertation focuses on investigating the use of manifold learning to increase instance discriminability in the latent space, where labels are solely provided at the bag-level. While there is an expansive literature in unsupervised manifold learning methods, this document will



pay special attention to both strictly- and semi-supervised methods, since they are typically adaptations of unsupervised approaches, as well as manifold learning under the MIL framework.

### 2.2.1 Definition and General Notation

Most studies perform classification or regression after applying unsupervised dimensionality reduction. However, it has been shown that there are advantages of learning the low-dimensional representations and classification/regression models simultaneously (Chao et al., 2019; Rish et al., 2008). Considering classification as the main goal of dimensionality reduction, this section provides a summary of the current literature in the area.

Given a data matrix  $\mathbf{X} = [\mathbf{x}_1, \dots, \mathbf{x}_N] \in \mathbb{R}^{D \times N}$  where  $N$  is the total number of samples and  $D$  is the dimensionality of the input feature space, general dimensionality reduction seeks to find a representation  $\mathbf{Z} \in \mathbb{R}^{d \times N}$  with  $d \ll D$  that enhances the between-class separation while preserving the intrinsic geometric structure of the data (Vural and Guillemot, 2018). In other words, it is assumed that the data lie on a smooth manifold  $\mathcal{X}$ , which is the image of some parameter domain  $\mathcal{Z} \subset \mathbb{R}^d$  under a smooth mapping  $\Psi : \mathcal{Z} \rightarrow \mathbb{R}^D$ . The goal of manifold learning is to discover an inverse mapping to the low-dimensional pre-image coordinates  $\mathbf{z}_n \in \mathcal{Z}$  corresponding to points  $\mathbf{x}_n \in \mathbf{X}$ . The data matrices  $\mathbf{X} = [\mathbf{x}_1^T, \dots, \mathbf{x}_N^T]$  and  $\mathbf{Z} = [\mathbf{z}_1^T, \dots, \mathbf{z}_N^T]$  are of size  $N \times D$  and  $N \times d$ , respectively. Since these low-dimensional data representations are unknown, they are often referred to as *latent* vectors and the span in  $\mathbb{R}^d$  is sometimes called the *latent feature space* or *latent space* for brevity (Murphy, 2012). The primary difference between traditional, unsupervised manifold learning and supervised approaches is that, in supervised manifold learning, data matrix  $\mathbf{X}$  is accompanied with a corresponding label vector  $\mathbf{l} = [l_1, \dots, l_N]$  indicating the corresponding class labels of each sample in  $\mathbf{X}$ .

Manifold learning methods can be subdivided into a wide taxonomy of approaches, with *linear* and *nonlinear* at the root. Nonlinear approaches can be further divided into purely global methods and approaches that capture global structure solely from local information. We begin with a review of popular linear manifold learning techniques before moving into the realm of

nonlinear approaches. Base, unsupervised methods are reviewed along with corresponding supervised and semi-supervised adaptations.

## 2.2.2 Comparison Table of Manifold Learning Methods

## 2.2.3 Geneology Image of Manifold Learning Methods from van der Maaten 2009, page 2

## 2.2.4 Linear Manifold Learning

A review of linear manifold learning approaches is provided. Linear approaches are advantageous over nonlinear because they allow for out-of-sample extensions. In other words, linear transformation matrices are learned which can be easily applied on data not included in the training set. However, linear approaches are limited in their abilities to capture irregular data surfaces ([Kegl et al., 2008](#)). Principal Component Analysis (PCA), Multi-dimensional Scaling (MDS) and Fisher's Linear Discriminant Analysis (LDA) are reviewed. General approaches are discussed and supervised as well as nonlinear extensions are elaborated. Special focus is given to (LDA), as it is the only inherently supervised technique out of the included approaches.

### 2.2.4.1 Principal Component Analysis (PCA)

**Unsupervised PCA.** Principal Component Analysis (PCA) is arguably the most popular (and best-studied) technique for dimensionality reduction and manifold learning. It attempts to learn an orthogonal projection of the input data into a lower-dimensional space, known as the principal subspace, such that the variance of the projected data is maximized ([Chao et al., 2019](#)). In other words, each *principal axis*, or *principal component*, of the learned coordinate system is orthogonal to the other principal components. In summary, the problem of PCA is to discover basis vectors which linearly combine to reconstruct the data. In practice, data in the input feature space are projected into a new coordinate system of  $d$  dimensions, such that the variance along each principal axis is maximized and the reconstruction errors of the data are minimized in the mean-square sense ([Thorstensen, 2009](#)). Let  $V$  be a  $d$ -dimensional subspace of  $\mathbb{R}^D$  and let  $\mathbf{w}_1, \dots, \mathbf{w}_D$  be an orthonormal basis of  $\mathbb{R}^D$  such that  $\mathbf{w}_1, \dots, \mathbf{w}_d$  is a basis of

V. The goal of PCA is to find an orthogonal set of basis vectors  $\mathbf{w}_n \in \mathbb{R}^D$  and corresponding latent coordinates  $\mathbf{x}_n \in \mathbb{R}^d$  such that the average reconstruction error is minimized (Murphy, 2012)

$$J(\mathbf{W}, \mathbf{Z}) = \frac{1}{N} \sum_{n=1}^N \|\mathbf{x}_n - \hat{\mathbf{x}}_n\|^2 \quad (2-2)$$

where  $\hat{\mathbf{x}}_n = \mathbf{W}\mathbf{z}_n$ , subject to the constraint that  $\mathbf{W}$  is *orthonormal*, or that  $\mathbf{w}_i^T \mathbf{w}_j = 0, \forall i \neq j$  and  $\mathbf{w}_i^T \mathbf{w}_i = 1$ . This is equivalently written as

$$J(\mathbf{W}, \mathbf{Z}) = \|\mathbf{X} - \mathbf{W}\mathbf{Z}\|_F^2 \quad (2-3)$$

where  $\mathbf{Z}$  is a  $N \times d$  matrix with the  $\mathbf{z}_n$  in its rows and  $\|\mathbf{A}\|_F$  is the *Frobenius norm* of matrix  $\mathbf{A}$ , defined by

$$\|\mathbf{A}\|_F = \sqrt{\sum_{m=1}^M \sum_{n=1}^N a_{mn}^2} = \sqrt{\text{tr}(\mathbf{A}^T \mathbf{A})} = \|\mathbf{A}(\cdot)\|_2 \quad (2-4)$$

As noted by Murphy (Murphy, 2012), the optimal solution is obtained by setting  $\hat{\mathbf{W}} = \mathbf{U}_d$ , where  $\mathbf{U}_d$  contains the eigenvectors corresponding to the  $d$  largest eigenvalues of the mean-subtracted, empirical data covariance matrix,  $\hat{\mathbf{S}} = \frac{1}{N} \sum_{n=1}^N (\mathbf{x}_n - \hat{\boldsymbol{\mu}})(\mathbf{x}_n - \hat{\boldsymbol{\mu}})^T$ , where  $\hat{\boldsymbol{\mu}}$  is the empirical data mean. Therefore, the low-dimensional encoding of the data is given by  $\mathbf{z}_n = \hat{\mathbf{W}}^T \mathbf{x}_n$ , which is the orthogonal, linear projection of the data onto the column space spanned by the eigenvectors of the  $d$  largest eigenvalues of the empirical data covariance.

Alternatively,

Assumes Gaussian distributions Typically, the data is standardized before applying PCA, as it can be misled by directions in which the variance is high simply because of the measurement scale.

The example shown in figure 2-3 demonstrates the projection of 2-dimensional data onto the first principal axis. As can be seen from the figure, the first principal axis corresponds to the direction of maximal variance of the data. PCA from the viewpoint of variance maximization is often called the *analysis view* of PCA (Murphy, 2012).




Figure 2-3: Placeholder for PCA projection example.

PCA has been successfully applied to a large number of domains such as face recognition, coin classification and seismic series analysis (van der Maaten et al., 2007). However PCA suffers from a few drawbacks. First, the dimensionality of the covariance matrix is proportional to the dimensionality of the data points. As a result, the computation of the eigenvectors may be infeasible or untrustworthy (singularity) for high-dimensional data. Additionally, PCA focuses mainly on preserving large pairwise distances between data samples instead of retaining local relationships, which may be important in certain applications **SHOW SWISS ROLL EXAMPLE AGAIN?**

Many extensions and alternative viewpoints have been made to PCA, such as creating a nonlinear version, a supervised version and looking at it as a factor analysis problem **CITE**. A few adaptations to PCA are discussed in later sections.

#### 2.2.4.2 Multi-Dimensional Scaling (MDS)

**Unsupervised MDS.** Most modern manifold learners have theoretical and algorithmic roots in one of three basic dimensionality reduction techniques: PCA, K-means and *Multidimensional Scaling* (MDS). Whereas PCA looks for linear projection bases which are constructed from the eigenvectors of a data covariance or scatter matrix, MDS tries to find a linear projection that preserves pairwise distances as well as possible. This idea is demonstrated by Figure 2-4, where the pairwise distances between samples in the 3-dimensional space are preserved in the 2-dimensional embedding space. While MDS does not construct an embedded manifold explicitly, it holds the status of being the grandfather of “one-shot” (non-iterative) manifold learners, such as Isomap and Locally Linear Embedding (LLE), which are discussed later in this literature review (Kegl et al., 2008).




Figure 2-4: Example of MDS distance preservation.

The steps of MDS correspond exactly to those of PCA except that, instead of a scatter matrix  $\mathbf{S} = \frac{1}{N}\mathbf{X}\mathbf{X}^T$ , MDS operates with a positive semi-definite, dissimilarity matrix  $\mathbf{D} \in \mathbb{R}^{N \times N}$ , where  $N$  is the number of data samples and a real, symmetric Gram matrix  $\mathbf{K} = \mathbf{X}^T\mathbf{X}$  (inner-product matrix) where  $\mathbf{K}_{mn}$  is the inner product between  $\mathbf{x}_m$  and  $\mathbf{x}_n$ . The problem of MDS is posed as finding  $d$ -dimensional Euclidean coordinates for each sample  $\mathbf{x}_n$  in dataset  $\mathbf{X}$  such that the Euclidean distances in the low-dimensional embedding space are

proportional to the pairwise distances in the input space ([Thorstensen, 2009](#); [Sorzano et al., 2014](#)). While the literature poses several cost functions for this task, this review focuses on classical MDS, which is described as follows:

First, the pairwise distance matrix  $\mathbf{D}$  is computed such that

$$\mathbf{D}_{mn} = \mathcal{D}_{\mathcal{X}}(\mathbf{x}_m, \mathbf{x}_n) = \|\mathbf{x}_m - \mathbf{x}_n\|^2 = (\mathbf{x}_m - \mathbf{x}_n)^T (\mathbf{x}_m - \mathbf{x}_n) \quad (2-5)$$

where  $\mathcal{D}_{\mathcal{X}}(\cdot, \cdot)$  is a chosen dissimilarity metric (Euclidean distance for classical MDS). Then, the double-centered Gram matrix  $\mathbf{K}$  is computed by

$$\mathbf{K} = -\frac{1}{2} \mathbf{H} \mathbf{D} \mathbf{H} \quad (2-6)$$

where

$$\mathbf{H} = \mathbb{I}_N - \frac{1}{N} \mathbf{e} \mathbf{e}^T \quad (2-7)$$

with  $\mathbb{I}_N$  denoting the  $N \times N$  identity matrix and  $\mathbf{e} = (1, \dots, 1)^T$  the  $N \times 1$  column vector of all ones. Multiplying  $\mathbf{D}$  on both sides by  $\mathbf{H}$  performs *double centering*, which subtracts the row and column means from  $\mathbf{D}$  (and adds back the global mean which gets subtracted twice), so that both the row and column means of  $\mathbf{K}$  are equal to zero. The objective is to find  $\mathbf{Z} = \{\mathbf{z}_1, \dots, \mathbf{z}_N\} \in \mathbb{R}^d$  which minimizes the objective

$$J(\mathbf{D}_X, \mathbf{D}_Z) = \|\mathbf{K}_X - \mathbf{D}_Z\|^2 = \left\| -\frac{1}{2} \mathbf{H} (\mathbf{D}_X - \mathbf{D}_Z) \mathbf{H} \right\|^2 \quad (2-8)$$

Similarly to PCA, this can be solved by a generalized eigenvalue problem

$$\mathbf{K} \mathbf{v} = \lambda \mathbf{v} \quad (2-9)$$

such that

$$\mathbf{Z} = \mathbf{V} \mathbf{\Lambda}^{\frac{1}{2}} \quad (2-10)$$

with  $\Lambda^{\frac{1}{2}} = \text{diag}(\sqrt{\lambda_1}, \dots, \sqrt{\lambda_N})$  being a diagonal matrix with entries equal to the square roots of the eigenvalues of  $\mathbf{K}$  sorted from largest to smallest ( $\lambda_1 \geq \lambda_2 \geq \dots \geq 0$ ), and  $\mathbf{V} = \{\mathbf{v}_1, \dots, \mathbf{v}_N\}$  the corresponding eigenvectors. The low-dimensional embedding coordinates  $\mathbf{Z} \in \mathbb{R}^{N \times d}$  are obtained by  $\mathbf{Z} = \{\sqrt{\lambda_1}\mathbf{v}_1, \dots, \sqrt{\lambda_d}\mathbf{v}_d\}$  (Chao et al., 2019).

It has been proven that the eigenvalues of Gram matrix  $\mathbf{K}$  and covariance  $\mathbf{S}$  are the same, and that the space spanned by MDS and PCA are the identical for any  $d \leq \text{rank}(\mathbf{K}) = \text{rank}(\mathbf{S})$ . This implies that a rotation matrix  $\mathbf{A}$  could be found such that  $\mathbf{A}^T \mathbf{Z}_{\text{MDS}} = \mathbf{Z}_{\text{PCA}}$  (Sorzano et al., 2014). Additionally, MDS can be computed even if the data observation matrix  $\mathbf{X}$  is unknown. All that is needed is the Gram matrix or a dissimilarity matrix. This feature potentially allows MDS to be applied in a variety of data-sensitive and privacy-concerned scenarios.

A pitfall of MDS is that it focuses on retaining global pairwise distances as opposed to local distances, which are typically much more important for capturing the geometry of the data (van der Maaten et al., 2007). Several MDS variants have been proposed to address this weakness. A popular variant is known as *Sammon Mapping* and is discussed in Section 2.2.5.9.

**Supervised MDS.** As with most manifold learning methods in the literature, MDS does not inherently consider class information when learning the embedding function. In attempt to promote class separability in the low-dimensional embedding space, Witten et al. proposed a *Supervised Multidimensional Scaling* (SMDS) (Witten and Tibshirani, 2011). this method follows the idea of traditional MDS where the goal is to find low-dimensional coordinate or *configuration points*  $\mathbf{z}_n \in \mathbb{R}^d$ , such that pairwise distances in the input feature space are preserved in the embedding space. Incorporating class label information, the goal of SMDS is to not only preserve distances, but ensure the coordinate values  $z_{mk} > z_{nk}$  when  $l_m > l_n$ ,  $\forall k = 1, \dots, d$ , where  $l$  are the instance-level labels and  $d$  is the dimensionality of the embedding space. Considering the binary target classification case, SMDS can be

formulated as

$$\min_{\mathbf{Z}} \quad \frac{1}{2}(1 - \alpha) \sum_{m=1}^N \sum_{n=1}^N (\mathbf{D}_{mn} - \|\mathbf{z}_m - \mathbf{z}_n\|^2) + \alpha \sum_{m:l_m=1} \sum_{n:l_n=2} \sum_{k=1}^d \left( \frac{\mathbf{D}_{mn}}{\sqrt{d}} - (z_{nk} - z_{mk})^2 \right) \quad (2-11)$$

This objective has two terms. The first is the traditional metric MDS *stress*. This term attempts to ensure that the Euclidean distances of two points in the embedding space is the same as the dissimilarity between the points in the input feature space. The second term is the supervised term which enforces that each dimension of the embedded configuration points be larger if belonging to the class with the larger label, and smaller if belonging to the class with a smaller-valued label. The term  $\alpha \in [0, 1]$  is a tuning parameter. When  $\alpha = 0$ , the objective reduces to the MDS stress function. As  $\alpha$  increases, however, the objective becomes increasingly more supervised, focused on ensuring class separation of the training data.

A least square regression was applied to estimate the embedding function for out-of-sample test points. SMDS was successfully applied to tasks in data visualization, bipartite ranking and classification of prostate data and USPS handwritten digits.

#### 2.2.4.3 Non-negative Matrix Factorization (NMF)

#### 2.2.4.4 Fisher's Linear Discriminant Analysis (LDA)

**Classical LDA.** *Linear Discriminant Analysis* (LDA) is a popular method for supervised, linear dimensionality reduction. LDA currently forms the basis for Multiple Instance Learning dimensionality reduction methods exhibited in the literature (Sun et al., 2010; Chai et al., 2014; Zhu et al., 2018; Xu et al.). Whereas PCA tries to project data into a space which maximizes variance, LDA considers class label information and tries to find a transformation which both maximizes between-class (inter-class) dissimilarity and minimizes between-class (intra-class) compactness (Yan et al., 2007; Chao et al., 2019; Sun et al., 2010; Murphy, 2012). This is done by maximizing the ratio between the inter-class  $\mathbf{S}_b$  and intra-class  $\mathbf{S}_w$



scatter matrices, defined as:

$$\mathbf{S}_w = \sum_{k=1}^K \mathbf{S}_k \quad (2-12)$$

$$\mathbf{S}_k = \sum_{n \in C_k} (\mathbf{x}_n - \hat{\boldsymbol{\mu}}_k)(\mathbf{x}_n - \hat{\boldsymbol{\mu}}_k)^T \quad (2-13)$$

$$\mathbf{S}_b = \sum_{k=1}^K N_k (\hat{\boldsymbol{\mu}}_k - \hat{\boldsymbol{\mu}})(\hat{\boldsymbol{\mu}}_k - \hat{\boldsymbol{\mu}})^T \quad (2-14)$$

Here,  $\mathbf{S}_w$  is the global within-class scatter matrix which is defined as the sum over each individual class' scatter matrix  $\mathbf{S}_k$ , and  $\mathbf{S}_k$  is essentially an outer product between all samples belonging to class  $C_k$  after subtracting the respective empirical class mean  $\hat{\boldsymbol{\mu}}_k$ . This scatter matrix would be the class covariance if it was normalized by the number of samples  $N_k$  in class  $C_k$ . However, this normalization constant does not affect the final solution and can thus be ignored. The between-class scatter  $\mathbf{S}_b$  is defined by the sum of outer products of the differences between the empirical class means  $\hat{\boldsymbol{\mu}}_k$  and the global data mean  $\hat{\boldsymbol{\mu}}$ , weighted by the number of samples in each class. The objective of LDA is then to solve for  $\mathbf{W}^*$  which maximizes the ratio  $J(\mathbf{W})$ :

$$\mathbf{W}^* = \arg \min_{\mathbf{W}} J(\mathbf{W}) = \arg \max_{\mathbf{W}} \frac{|\mathbf{W}^T \mathbf{S}_b \mathbf{W}|}{|\mathbf{W}^T \mathbf{S}_w \mathbf{W}|} \quad (2-15)$$

It has been shown that the optimal projection matrix  $\mathbf{W}^*$  is the one whose columns are the eigenvectors corresponding to the largest eigenvalues of the generalized eigenvalue problem

$$\mathbf{S}_b \mathbf{w} = \lambda \mathbf{S}_w \mathbf{w} \Rightarrow \mathbf{S}_w^{-1} \mathbf{S}_b \mathbf{w} = \lambda \mathbf{w} \quad (2-16)$$

Since  $\mathbf{S}_b$  is the sum of  $K$  matrices of rank  $\leq 1$ , this implies that  $\mathbf{S}_b$  will be of rank  $(K - 1)$  or less and only  $(K - 1)$  of the eigenvalues  $\lambda$  will be non-zero. A low-dimensional coordinate representation  $\mathbf{z}_n \in \mathbb{R}^{(K-1)}$  of sample  $\mathbf{x}_n \in \mathbb{R}^D$  is given by the linear projection of  $\mathbf{x}_n$  onto the hyper-plane parameterized by  $\mathbf{W}^*$ ,  $\mathbf{z}_n = \mathbf{W}^{*T} \mathbf{x}_n$ . It should be noted that for LDA, the

dimensionality of the latent space is not a free-parameter, but is always fixed at  $d = (K - 1)$ , or one less than the number of classes present in the dataset. Equivalently, LDA can be derived by maximum likelihood for normal class-conditional densities where the covariances for each class are assumed to be equivalent (Murphy, 2012). For the special case of binary target classification, the LDA transformation will place every sample onto a single line in 1-dimension, and thus the LDA solution can be simplified:

$$\mathbf{w}^* = \arg \max_{\mathbf{w}} \frac{\mathbf{w}^T \mathbf{S}_b \mathbf{w}}{\mathbf{w}^T \mathbf{S}_w \mathbf{w}} = \mathbf{S}_w^{-1}(\hat{\boldsymbol{\mu}}_2 - \hat{\boldsymbol{\mu}}_1) \quad (2-17)$$

where  $\hat{\boldsymbol{\mu}}_1$  and  $\hat{\boldsymbol{\mu}}_2$  are the empirical means for classes 1 and 2, respectively. Figure 2-5 demonstrates the differences between PCA and LDA. While PCA projects data onto the axes exhibiting the maximal variation, LDA projects the data into a space which attempts to simultaneously enforce between-class separation and within-class compactness.




Figure 2-5: LDA example.

Although LDA is the basis for large number of discriminative dimensionality reduction approaches, it does not guarantee class separation in the embedding space. For example, LDA projects data into a space of at most  $(K - 1)$  dimensions, however, more features may be necessary for adequate class discrimination. Additionally, LDA is a parametric method which assumes unimodal Gaussian likelihoods. This implies that it may not be able to preserve

complex data structure. Finally, LDA will fail if the discriminatory information is contained in the variance of the data instead of the mean. Despite these pitfalls, LDA has been successfully applied to object detection and recognition tasks (Wang et al., 2016). Many variations of LDA have been developed, such as Non-parametric LDA (Fukunaga and Mantock, 1983), Orthonormal LDA (Wang et al., 2016), Generalized LDA (Baudat and Anouar, 2000) and Multilayer Perceptrons (Webb and Lowe, 1990). Additionally, LDA serves as the foundation for all of the Multiple Instance Learning dimensionality reduction approaches in the current literature (Sun et al., 2010; Chai et al., 2014; Zhu et al., 2018).

#### 2.2.4.5 Locality Preserving Projection (LPP)

#### 2.2.5 Nonlinear Manifold Learning

Linear methods such as PCA and MDS are convenient for projecting out-of-sample test points into the embedding space. However, they are unable to capture the structure of data that are sampled from nonlinear manifolds (Kegl et al., 2008). This section will discuss a variety of nonlinear dimensionality reduction and manifold learning approaches. All methods reviewed assume the data is distributed along a  $d$ -dimensional sub-manifold  $\mathcal{X}$  embedded in  $\mathbb{R}^D$ .




Figure 2-6: Example of a nonlinear manifold.

### 2.2.5.1 Kernelization

Although each of the manifold learning techniques previously discussed are inherently linear, nonlinear adaptations have been made. One easily extendable approach is to utilize kernel functions as means to provide nonlinearity in the embeddings.

**Kernels.** A *kernel function* is a real-valued function of two arguments  $\kappa(\mathbf{x}, \mathbf{x}') \in \mathbb{R}$ , for  $\mathbf{x}, \mathbf{x}' \in \mathcal{X}$ , which maps vectors from the input feature space to a single value in  $\mathbb{R}$ . The function is typically symmetric (i.e.  $\kappa(\mathbf{x}, \mathbf{x}') = \kappa(\mathbf{x}', \mathbf{x})$ ) and non-negative (i.e.  $\kappa(\mathbf{x}, \mathbf{x}') \geq 0$ ), which implies that it can be interpreted as a measure of similarity (Murphy, 2012). The notion of kernels is very useful in certain applications where data representation is not straightforward, such as representing text documents or molecular structures which can have variable length. Additionally, this allows algorithms to operate directly on the kernel representations. This is useful in data-sensitive scenarios where direct access to the data may not be available.

A popular choice of kernel in manifold learning is the *radial basis function* (RBF) kernel, defined as:

$$\kappa(\mathbf{x}, \mathbf{x}') = \exp\left(-\frac{\|\mathbf{x} - \mathbf{x}'\|^2}{\beta}\right) \quad (2-18)$$

where  $\beta$  is the bandwidth of the isotropic function. Another popular kernel for text classification is *cosine similarity*, defined by:

$$\kappa(\mathbf{x}, \mathbf{x}') = \frac{\mathbf{x}^T \mathbf{x}'}{\|\mathbf{x}\|_2 \|\mathbf{x}'\|_2} \quad (2-19)$$

This kernel measures the cosine of the angle between vectors  $\mathbf{x}$  and  $\mathbf{x}'$  after scaling them onto the unit hyper-sphere. If  $\mathbf{x}$  and  $\mathbf{x}'$  are strictly positive vectors (counts in the bag-of-words model, for example), then the kernel provides values in  $[0, 1]$ , where a value of 0 means the feature vectors are orthogonal and, therefore, have no features in common, and a value of 1 means the vectors are the same.

Some of the nonlinear manifold learning methods in the literature require the kernel function to satisfy the requirement that the *Gram matrix*

$$\mathbf{K} = \begin{bmatrix} \kappa(\mathbf{x}_1, \mathbf{x}_1) & \dots & \kappa(\mathbf{x}_1, \mathbf{x}_N) \\ \vdots & & \vdots \\ \kappa(\mathbf{x}_N, \mathbf{x}_1) & \dots & \kappa(\mathbf{x}_N, \mathbf{x}_N) \end{bmatrix} \quad (2-20)$$

be positive definite for any set of inputs  $\{\mathbf{x}_n\}_{n=1}^N$ . This type of kernel is called a *Mercer kernel* or *positive definite kernel*. The importance of the Mercer Kernel is the following result, known as *Mercer's theorem*. This theorem states that if the Gram matrix is positive definite, its eigenvector decomposition can be written as

$$\mathbf{K} = \mathbf{U}^T \mathbf{\Lambda} \mathbf{U} \quad (2-21)$$

As derived by Murphy and Liu et al. ([Murphy, 2012](#); [Liu et al., 2010](#)), it then follows that each entry of  $\mathbf{K}$  can be computed as

$$\kappa(\mathbf{x}, \mathbf{x}') = \phi(\mathbf{x})^T \phi(\mathbf{x}') = \langle \phi(\mathbf{x}), \phi(\mathbf{x}') \rangle \quad (2-22)$$

meaning that the entries of the kernel matrix can be defined by the inner product of some feature vectors that are implicitly defined by the eigenvectors  $\mathbf{U}$ . If the kernel is Mercer, then there exists a function  $\phi$  which maps  $\mathbf{x} \in \mathcal{X}$  to  $\mathbb{R}^D$  such that Equation 2-22 holds. Additionally,  $\phi$  depends on the eigenfunctions of  $\kappa$ , meaning that  $D$  is a potentially infinite dimensional space. Additionally, instead of representing feature vectors in terms of kernels  $\phi(\mathbf{x}) = [\kappa(\mathbf{x}, \mathbf{x}_1), \dots, \kappa(\mathbf{x}, \mathbf{x}_N)]$ , algorithms can instead work with the input feature vectors  $\mathbf{x}$  by replacing all inner products  $\langle \mathbf{x}, \mathbf{x}' \rangle$  with a call to the kernel function  $\kappa(\mathbf{x}, \mathbf{x}')$ . This is called the *kernel trick*, and it turns out that many algorithms can be kernelized in this way.

Kernel functions play an important role in the dimensionality reduction literature for both applying nonlinearity to inherently linear problems and in defining similarity measures for

graph-based manifold learning methods. The kernelization of three traditionally linear manifold learning methods, namely: PCA, MDS and LDA, is briefly described in the following.

**Kernel PCA.** Section 2.2.4.1 showed how PCA could be used to compute linear low-dimensional embeddings of data. This process involved finding the eigenvectors of the empirical data covariance matrix  $\hat{S} = \frac{1}{N} \sum_{n=1}^N \hat{x}_n \hat{x}_n^T = \frac{1}{N} \hat{X}^T \hat{X}$ , where  $\hat{x}_n = x_n - \hat{\mu}$  is the mean subtracted feature vector. However, PCA can also be computed by finding the eigenvectors of the inner product matrix  $X X^T$  (Murphy, 2012; Wang, 2012). This allows the production of nonlinear embeddings by taking advantage of the kernel trick. This approach is known as Kernel PCA (Schölkopf et al., 1999).

**Kernel MDS.** (Webb, 2002)

**Kernel FDA (KDA).** (Ghojogh et al., 2019)

#### 2.2.5.2 Graph-based Methods

Nonlinear dimensionality reduction methods typically rely on the use of computational graphs. These graphs represent data structure pooled from local neighborhoods of samples. *Spectral graph theory* focuses on constructing, analyzing and manipulating graphs. It has proved useful for object representation, graph visualization, spectral clustering, dimensionality reduction and numerous other applications in chemistry, physics, signal processing and computer science (Shuman et al., 2013; Bengoetxea, 2002). An overview of computational graphs as well as prominent methods for graph construction in manifold learning are presented. Additionally, geodesic distance approximation from pairwise distances is reviewed.

**Terminology.** Many dimensionality reduction methods in the literature are interested in analyzing relationships between samples defined on an undirected, weighted graph  $G = \{\mathcal{V}, \mathcal{E}, \mathbf{W}\}$ , which consists of a finite set of *vertices*  $\mathcal{V}$  (also called *nodes* or *points*) with cardinality  $|\mathcal{V}| = N$ , a set of *edges*  $\mathcal{E} \subset \mathcal{V} \times \mathcal{V} = [\mathcal{V}]^2$  (also known as *arcs* or *lines*) and a weighted *adjacency* or *affinity* matrix  $\mathbf{W}$  (Shuman et al., 2013; Livi and Rizzi, 2013; Bengoetxea, 2002). The size or *order* of a graph is defined by the number of nodes  $|\mathcal{V}|$  and edges  $|\mathcal{E}|$ . If two vertices in  $G$ , say  $u, v \in \mathcal{V}$ , are connected by an edge  $e \in \mathcal{E}$ , this is

denoted by  $e = (\mathbf{u}, \mathbf{v})$  and the two vertices are said to be *adjacent* or *neighbors*. When edges do not have a direction, they are coined as undirected. A graph solely containing this type of connection is termed as an *undirected graph*. When all edges have directions, meaning  $(\mathbf{u}, \mathbf{v})$  and  $(\mathbf{v}, \mathbf{u})$  are distinguishable, the graph is said to be *directed*. In the literature, the term *arc* is typically used to denote connections between nodes in directed graphs, while *edge* is used when they are undirected. The graph-based methods included in this literature review focus on analyzing affinities between data samples in undirected graphs. Moreover, a *path* between any two nodes in  $\mathbf{u}, \mathbf{u}' \in \mathcal{V}$  is a non-empty sequence of  $k$  different vertices  $\langle \mathbf{v}_0, \mathbf{v}_1, \dots, \mathbf{v}_k \rangle$  where  $\mathbf{u} = \mathbf{v}_0, \mathbf{u}' = \mathbf{v}_k$  and  $(\mathbf{v}_{i-1}, \mathbf{v}_i) \in \mathcal{E}, i = 1, 2, \dots, k$ . Additionally, a graph is said to be *acyclic* if there are no cycles between its edges, regardless of whether it is directed or undirected.

When using graphs for dimensionality reduction, vertices usually represent features of individual samples, and edges express relationships between them. The most straight-forward way to construct a graph is to instantiate edges between every vertex in the graph, where each edge is weighted by the distance between the vertices it connects according to a pre-defined metric. This type of graph is called *full mesh*. Weights on edges are captured in the graph adjacency matrix  $\mathbf{W}$ . When weights are not naturally defined by an application, a common way to define the weight of an edge connecting vertices  $\mathbf{u} \sim \mathbf{u}'$  is by a symmetric affinity function  $W_{\mathbf{u}, \mathbf{u}'} = K(\mathbf{u}; \mathbf{u}')$ ; typically a *radial basis function (RBF)* or *heat kernel*, defined as:

$$W_{\mathbf{u}, \mathbf{u}'} = w_{\mathbf{u}, \mathbf{u}'} = \exp\left(-\frac{\|\mathbf{u} - \mathbf{u}'\|^2}{\beta}\right) \quad (2-23)$$

where  $\beta$  is the non-negative *bandwidth* of the kernel. Vertices will have a nonzero weight only if they fall within the nonzero mapping domain of the kernel. Additionally, a threshold could be set to truncate the weights of neighbors far from individual samples.

***K*-Nearest Neighbor Graph.** In a *K*-nearest neighbor graph, every data point (vertex)  $\mathbf{x}_n \in \mathbf{X}$  is connected by edges to its *K*-nearest neighbors, where  $K \in \mathbb{Z}^+$  is fixed. An example




Figure 2-7: Examples of K-nearest neighbor and  $\epsilon$ -ball graphs

of a  $K$ -nearest neighbor graph is depicted in a of Figure 2-7. The downside of this graph is that it might impose edges between neighbors that should not actually be connected, as in the case where a sample is metrically distant from all of its nearest neighbors. Although, this feature may actually be useful in domains such as outlier detection, where low adjacency weights indicate that the sample is far from the sampling distribution. Two alternative  $K$ -nearest neighbor graphs, a symmetric and mutual neighbors, might instead be utilized. In the symmetric  $K$ -nearest neighbors graph, two vertices  $u$  and  $u'$  if  $u$  is among the  $K$ -nearest neighbors of  $u'$  or  $u'$  is among the neighbors of  $u$ . The mutual  $K$ -nearest neighbors graph, however, only connects vertices  $(u, u')$  if  $u$  is among the  $K$ -nearest neighbors of  $u'$  and  $u'$  is among the  $K$ -nearest neighbors of  $u$ . The weights on each edge are provided as the similarity of the adjacent nodes.

**$\epsilon$ -Neighborhood Graph.** Another method for graph construction is to use  $\epsilon$ -neighborhoods (or  $\epsilon$ -balls). In this graph, two vertices  $(u, u')$  are connected by an edge if and only if the distance between them is equal to or smaller than some value  $\epsilon$ ,  $\mathcal{D}_u(u, u') \leq \epsilon$ . This idea is represented in b of Figure 2-7. In both the  $K$ -nearest and  $\epsilon$ -neighborhood graphs, a parameter controlling the number of edges in the graph,  $K$  or  $\epsilon$ , must be chosen. These parameters are highly influential for graph construction and can thus greatly affect dimensionality reduction quality. Contrary to the  $K$ -nearest neighbor graph, an  $\epsilon$ -neighborhood will not create



connections between distant vertices. However, when the data is sampled sparsely from a highly-curved manifold, the  $\epsilon$ -neighbor graph will not be able to appropriately capture the geometry (Thorstensen, 2009).

**Geodesic Distance Approximation.** The ultimate goal of manifold learning is to uncover an underlying low-dimensional sub-manifold which is embedded in  $\mathbb{R}^D$ . Many dimensionality reduction methods in the literature discover projections of data into a low-dimensional space which preserve topological ordering of the data (Kegl et al., 2008). These processes require a notion of distance between samples. *Euclidean distance* is a popular metric which captures the straight-line disparity between two points. As shown in Figure 2-8, however, samples that are actually distant on the manifold may appear deceptively close in the high-dimensional input feature space, as measured by Euclidean distance (Tenenbaum et al., 2000). *Geodesic distance*, also called *curvilinear* or *shortest-path distance*, Figure 2-8, on the other hand, follows the curvature of a manifold and may provide a better measure of dissimilarity between data samples. Geodesic distance can be estimated by the shortest path through a graph constructed by assuming the distances between neighbors is locally Euclidean (Sorzano et al., 2014). This can be conceptualized by a simple example. The Earth is a sphere and naturally has curvature. Two people standing in a room, however, would estimate the distance between themselves by a straight line. Thus, in a very local region on the Earth, the measure of curvature would be negligible and the true distances between objects could be estimated with Euclidean distance. The same concept is true for manifolds where, if data is sampled densely enough, geodesic distance can be approximated by the shortest-path through a neighborhood graph where the dissimilarities between neighbors is assumed to be locally Euclidean. Geodesic distance can be estimated efficiently by methods such as Dijkstra's or Floyd's shortest-path algorithms (Tenenbaum et al., 2000).




Figure 2-8: Demonstration of geodesic distance

### 2.2.5.3 General Graph Embedding Framework

#### 2.2.5.4 Isomap

**Traditional Isomap.** While MDS has proven to be successful in a variety of applications, it suffers from the fact that it solely aims to retain pairwise Euclidean distances and does not consider the distributions of neighboring samples. This implies that MDS is not able to capture the geometry of high-dimensional data which lies on or near to a curved manifold, such as the Swiss roll dataset ([van der Maaten et al., 2007](#); [Chao et al., 2019](#)). Isometric Feature Mapping (Isomap) ([Tenenbaum et al., 2000](#)) is a technique which resolves this problem by attempting to preserve pairwise geodesic distances between datapoints. Isomap can be considered as a generalization of classical MDS in which the pairwise distance matrix is replaced by a matrix of pairwise geodesic distances approximated by distances in the graph ([Thorstensen, 2009](#)). The classic, unsupervised algorithm consists of a few steps:

1. Given a set of input data  $\mathbf{X} = \{\mathbf{x}_n\}_{n=1}^N \subset \mathbb{R}^D$ , construct a sparse neighborhood graph (such as the  $K$ -nearest or  $\epsilon$ -ball graphs discussed previously) where each edge is weighted by the Euclidean distance between the neighbors it connects:

$$\mathbf{W}_{mn} = w_{mn} = \|\mathbf{x}_m - \mathbf{x}_n\|^2 \quad (2-24)$$

where  $\mathbf{W}$  is the graph adjacency matrix.

2. Next, the geodesic distances between all pairs of samples is computed by finding the shortest paths between the points through the graph. This is commonly done with Dijkstra's or Flyod's shortest-path algorithms (Tenenbaum et al., 2000).
3. These geodesic distances form a pairwise distance matrix which is substituted into classical MDS as described in Section 2.2.4.2. This provides the low-dimensional embedding coordinates  $\mathbf{Z} = [\mathbf{z}_1^T, \dots, \mathbf{z}_N^T] \in \mathbb{R}^{N \times d}$  of high-dimensional input data  $\mathbf{X} = [\mathbf{x}_1^T, \dots, \mathbf{x}_N^T] \in \mathbb{R}^{N \times D}$ , where  $d \ll D$ .

While Isomap has been successfully applied in the areas of financial analysis (Ribeiro et al., 2008), facial and object recognition (Zhang et al., 2018), visualization and classification tasks (Vlachos et al., 2002), a few important weaknesses are prevalent. First, Isomap may be topologically unstable. That is, it may construct erroneous connections in the neighborhood graph. This is known as short-circuiting, and it can severely impair the performance of Isomap. Several approaches have been proposed to nullify the short-circuiting problem, such as removing datapoints with large total flows or by removing nearest neighbors that violate local linearity of the neighborhood graph (van der Maaten et al., 2007). Another weakness of Isomap is that it may not perform correctly if there are holes in the manifold, as this causes the geodesic distances of some samples to appear further on the manifold than they truly are. A third weakness is that Isomap can fail if the manifold is non-convex. Therefore, we see that Isomap can perform very well due to theoretical guarantees on qualities such as convergence, as long as the manifold is isometric to a convex open set of  $\mathbb{R}^d$ ,  $\mathcal{D}_{\mathcal{X}}(\mathbf{u}, \mathbf{u}') = \mathcal{D}_{\mathcal{Y}}(f(\mathbf{u}), f(\mathbf{u}'))$ , meaning that the geodesic distances in the graph are almost equal to the Euclidean distances in the embedding space  $\mathbb{R}^d$ . Continuing, an additional drawback of Isomap is the fact that it requires the decomposition of a large, dense Gram matrix which scales with the number of training data points. If the dataset grows too large, a solution will no longer be tractable. Furthermore, the constraint on  $\mathcal{X}$  to be isometric to a convex open set of  $\mathbb{R}^d$  is rarely met. As mentioned in (Thorstensen, 2009), these problems may be circumvented by sparsifying large datasets using landmarks, as with Landmark Isomap (Silva and Tenenbaum, 2003) and looking at conformal maps, as is done in Conformal Isomap (Silva and Tenenbaum, 2002). Finally, as

with most nonlinear manifold learning techniques, it is nontrivial to embed out-of-sample data points into the lower dimensional feature space.

**Supervised Isomap Approaches.** As with most traditional manifold learning methods in the literature, Isomap is not inherently well-suited for classification tasks. However, supervised approaches which consider class label information have been adopted to increase class separability in the latent embedding space. The work by Vlachos et al. (Vlachos et al., 2002) was the first to investigate a supervised adaptation of Isomap. Two supervised Isomap procedures were proposed which combine Isomap with a nearest neighbor classifier. These methods, Iso+Ada and WeightedIso take label information into consideration to scale the computed Euclidean distances utilized by Isomap by a constant factor according to class label. The idea is to make points closer in the embedding space if they have the same class label and farther if they have opposing class labels. Ribeiro et al. (Ribeiro et al., 2008) proposed an enhanced supervised Isomap (ES-Isomap) in which the dissimilarity matrix is weighted according to rules which consider class label information. The dissimilarity matrix (considered as the adjacency matrix),  $\mathbf{W}$ , which was the same used in the Supervised Isomap method (X. Geng et al., 2005), is defined as:

$$\mathbf{W}(\mathbf{x}_m, \mathbf{x}_n) = \begin{cases} \sqrt{1 - \exp \frac{-\mathcal{D}^2(\mathbf{x}_m, \mathbf{x}_n)}{\beta}}, & l_m = l_n \\ \sqrt{\exp \frac{\mathcal{D}^2(\mathbf{x}_m, \mathbf{x}_n)}{\beta} - \alpha}, & l_m \neq l_n \end{cases} \quad (2-25)$$

where  $\mathcal{D}(\mathbf{x}_m, \mathbf{x}_n)$  denotes the distance measure between samples  $\mathbf{x}_m$  and  $\mathbf{x}_n$ ,  $\beta$  is used to prevent  $\mathbf{W}(\mathbf{x}_m, \mathbf{x}_n)$  from increasing too quickly when  $\mathcal{D}(\mathbf{x}_m, \mathbf{x}_n)$  is large and is typically set according to the density of the data,  $\alpha$  is a constant in  $[0, 1]$  which controls the dissimilarity between points in different classes and keeps the graph from becoming disconnected, and  $l_m$  and  $l_n$  are the corresponding class labels of samples  $\mathbf{x}_m$  and  $\mathbf{x}_n$ , respectively. In Equation 2-25, the dissimilarity between two points is greater than or equal to one if their class labels are different and less than 1 if the points have the same class label. Therefore, the between-class

dissimilarity will always be larger than the within-class, which is an important property for classification tasks.

Li and Guo proposed Supervised Isomap with Explicit mapping (SE-Isomap) in (Chun-Guang Li and Jun Guo, 2006). SE-Isomap enforces discriminability on the matrix of geodesic distances, as compared to the Euclidean distance matrix used in the aforementioned approaches, to learn an explicit mapping to the low-dimensional embedding space. Finally, Zhang et al. (Zhang et al., 2018) developed a semi-supervised Isomap to utilize both labeled and unlabeled data points in training. This method aims at minimizing pairwise distances of within-class samples in the same manifold while maximizing the distances over different manifolds.

#### 2.2.5.5 Locally Linear Embedding (LLE)

#### 2.2.5.6 Laplacian Eigenmaps (LE)

**Classical LE.** Similar to LLE, Laplacian Eigenmaps, or *Spectral Embedding*, is a nonlinear dimensionality reduction technique which aims to preserve local structure of data (Raducanu and Dornaika, 2012; van der Maaten et al., 2007). Using *spectral graph theory*, LE computes low-dimensional representations of data in which the dissimilarities between datapoints and their neighbors (according to an affinity measure) are minimized. The name *Laplacian Eigenmaps* is derived by the use of Laplacian regularization in the optimization procedure (Thorstensen, 2009). Given a set of  $N$  samples  $\mathbf{X} = \{\mathbf{x}_n\}_{n=1}^N \subset \mathbb{R}^D$ , the first step of LE is to define a *neighborhood graph on the samples*. This graph, also called an *affinity* or *adjacency* matrix can be constructed in a variety of ways, such as  $K$ -nearest neighbor,  $\epsilon$ -ball, full mesh, or by weighting each edge  $\mathbf{x}_m \sim \mathbf{x}_n$  by a symmetric affinity function  $W_{mn} = K(\mathbf{x}_m; \mathbf{x}_n)$ , typically a radial basis or heat kernel:

$$W_{mn} = w_{mn} = \exp\left(-\frac{\|\mathbf{x}_m - \mathbf{x}_n\|^2}{\beta}\right) \quad (2-26)$$

where the kernel bandwidth  $\beta$  is typically set as the variance of the dataset (Raducanu and Dornaika, 2012; Thorstensen, 2009).

The goal is to uncover the latent data representations  $\{z_n\}_{n=1}^N \subset \mathbb{R}^d$  where  $d \ll D$  which minimizes the objective

$$J(\mathbf{W}, \mathbf{Z}) = \frac{1}{2} \sum_{m,n} \|z_m - z_n\|^2 w_{mn} = \text{tr}(\mathbf{Z}^T \mathbf{L} \mathbf{Z}) \quad (2-27)$$

with  $\mathbf{W}$  denoting the symmetric affinity matrix,  $\mathbf{D}$  the diagonal weight matrix whose entries are the sum of the rows (or columns since  $\mathbf{W}$  is symmetric) of  $\mathbf{W}$  (i.e.  $d_{mm} = \sum_n w_{mn}$ , and is 0 otherwise). The graph Laplacian matrix is provided as  $\mathbf{L} = \mathbf{D} - \mathbf{W}$ . The matrix  $\mathbf{Z} = [z_1^T, \dots, z_N^T]$  is the  $N \times d$  embedding matrix and  $\text{tr}(\cdot)$  denotes the trace of a matrix. The  $n^{\text{th}}$  row of matrix  $\mathbf{Z}$  provides the vector  $z_n$ , which is the latent representation of sample  $x_n$ . This objective discourages projecting similar points in the input feature space to disparate regions of the embedding space by enforcing heavy penalization.

The latent sample coordinates  $\mathbf{Z}$  are found as the solution to the optimization problem:

$$\min_{\mathbf{Z}} \text{tr}(\mathbf{Z}^T \mathbf{L} \mathbf{Z}) \quad \text{s.t.} \quad \mathbf{Z}^T \mathbf{D} \mathbf{Z} = \mathbf{I}, \mathbf{Z}^T \mathbf{L} \mathbf{e} = \mathbf{0} \quad (2-28)$$

where  $\mathbf{I}$  is the identity matrix and  $\mathbf{e} = (1, \dots, 1)^T$ . The first constraint eliminates the trivial solution  $\mathbf{Z} = \mathbf{0}$  (scaling) and the second constraint avoids the trivial solution  $\mathbf{Z} = \mathbf{e}$  (uniqueness). By applying the Langrange multiplier method and using the fact that  $\mathbf{L} \mathbf{e} = \mathbf{0}$ , the low-dimensional data representations can be found by solving the generalized eigenvalue problem:

$$\mathbf{L} \mathbf{v} = \lambda \mathbf{D} \mathbf{v} \quad (2-29)$$

The column vectors  $\mathbf{v}_1, \dots, \mathbf{v}_N$  are the solutions of Equation 2-29, ordered to the corresponding eigenvalues, in ascending order,  $\lambda_1 = 0 \leq \lambda_2 \leq \dots \leq \lambda_N$ . The embedding of the input samples given by the matrix  $\mathbf{Z}$ , is obtained by concatenating the eigenvectors of the  $d$  smallest non-zero eigenvalues.  $\mathbf{Z}$  is a  $N \times d$  matrix, where  $d < N$  is the dimensionality of the embedded space. From observation, it is clear that the embedding dimensionality is limited by the number of samples  $N$ .

**Supervised LE (S-LE).** In order to adopt LE for classification, Raducanu and Dornaika (Raducanu and Dornaika, 2012) proposed a supervised LE which minimizes the margin between samples with similar class labels and maximizes the margin between samples with opposing class labels. Supervised LE utilizes discriminative information contained in the class labels when finding the nonlinear embedding (spectral projection).

In order to discover both geometrical and discriminative manifold structure, supervised LE splits the global graph into two components: the within-class graph  $G_w$  and the between-class graph  $G_b$ . To define the margin, they define two subsets,  $N_w(\mathbf{x}_n)$  and  $N_b(\mathbf{x}_n)$  for each sample  $\mathbf{x}_n$ . These two subsets contain the neighbors of  $\mathbf{x}_n$  sharing the same label and having different labels, respectively, which have a similarity higher than the average.

$$N_w(\mathbf{x}_n) = \{\mathbf{x}_m | l_m = l_n, \exp\left(-\frac{\|\mathbf{x}_n - \mathbf{x}_m\|^2}{\beta}\right) > AS(\mathbf{x}_n)\} \quad (2-30)$$

$$N_b(\mathbf{x}_n) = \{\mathbf{x}_m | l_m \neq l_n, \exp\left(-\frac{\|\mathbf{x}_n - \mathbf{x}_m\|^2}{\beta}\right) > AS(\mathbf{x}_n)\} \quad (2-31)$$

where  $AS(\mathbf{x}_n) = \frac{1}{N} \sum_{n=1}^N \exp\left(-\frac{\|\mathbf{x}_n - \mathbf{x}_m\|^2}{\beta}\right)$  denotes the average similarity of the sample  $\mathbf{x}_n$  to the rest of the data. From Equations 2-30 and 2-31 it is clear that the neighborhoods for each data sample are not necessarily the same size. As a result, this function constructs the affinity graph according to both the local density and similarity between data samples in the input feature space.

With the two sets defined, the within-class and between-class weight matrices  $\mathbf{W}_w$  and  $\mathbf{W}_b$  are formed from the adjacency graphs  $G_w$  and  $G_b$ , respectively. These weight matrices are defined as:

$$W_{w,mn} = \begin{cases} \exp\left(-\frac{\|\mathbf{x}_n - \mathbf{x}_m\|^2}{\beta}\right), & \text{if } \mathbf{x}_n \in N_w(\mathbf{x}_m) \text{ or } \mathbf{x}_m \in N_w(\mathbf{x}_n) \\ 0, & \text{otherwise} \end{cases} \quad (2-32)$$

$$W_{b,mn} = \begin{cases} 1, & \text{if } \mathbf{x}_n \in N_b(\mathbf{x}_m) \text{ or } \mathbf{x}_m \in N_b(\mathbf{x}_n) \\ 0, & \text{otherwise} \end{cases} \quad (2-33)$$

and the global affinity matrix,  $\mathbf{W}$ , can be written as:

$$\mathbf{W} = \mathbf{W}_w + \mathbf{W}_b \quad (2-34)$$

In order to obtain the low-dimensional representations  $\mathbf{z}_n$  of the input data  $\mathbf{x}_n$ , the following objective functions can be optimized for  $\mathbf{Z}$ :

$$\min \frac{1}{2} \sum_{m,n} \|\mathbf{z}_m - \mathbf{z}_n\|^2 W_{w,mn} = \text{tr}(\mathbf{Z}^T \mathbf{L}_w \mathbf{Z}) \quad (2-35)$$

$$\max \frac{1}{2} \sum_{m,n} \|\mathbf{z}_m - \mathbf{z}_n\|^2 W_{b,mn} = \text{tr}(\mathbf{Z}^T \mathbf{L}_b \mathbf{Z}) \quad (2-36)$$

where  $\mathbf{L}_w = \mathbf{D}_w - \mathbf{W}_w$  and  $\mathbf{L}_b = \mathbf{D}_b - \mathbf{W}_b$  indicate the corresponding graph Laplacians of the within-class and between-class affinity graphs, respectively. The matrix  $\mathbf{Z} = [\mathbf{z}_1^T, \dots, \mathbf{z}_N^T]$  contains the low-dimensional representations of the input samples in its rows.

By merging the two objective functions, the final optimization problem is formulated as:

$$\arg \max_{\mathbf{Z}} \{ \gamma \text{tr}(\mathbf{Z}^T \mathbf{L}_b \mathbf{Z}) + (1 - \gamma) \text{tr}(\mathbf{Z}^T \mathbf{W}_w \mathbf{Z}) \} \quad s.t. \quad \mathbf{Z}^T \mathbf{D}_w \mathbf{Z} = \mathbf{I} \quad (2-37)$$

The term  $\gamma$  is a scalar value in  $[0, 1]$  which determines the trade-off between pulling similar samples toward each other in the latent space and pushing heterogeneous points away. A value of  $\gamma = 1$  forces the objective to solely focus on maximizing the margin between dissimilar points. Alternatively, a value of  $\gamma = 0$  priorities the objective on embedding homogeneous samples in close spatial proximity. By defining matrix  $\mathbf{B} = \gamma \mathbf{L}_b + (1 - \gamma) \mathbf{W}_w$ , the problem becomes:

$$\arg \max_{\mathbf{Z}} (\mathbf{Z}^T \mathbf{B} \mathbf{Z}) \quad s.t. \quad \mathbf{Z}^T \mathbf{D}_w \mathbf{Z} = \mathbf{I} \quad (2-38)$$



The low-dimensional embedding matrix  $\mathbf{Z}$  can be found by solving the generalized eigenvalue problem:

$$\mathbf{B}\mathbf{v} = \lambda\mathbf{D}_w\mathbf{v} \quad (2-39)$$

The column vectors  $\mathbf{v}_1, \mathbf{v}_2, \dots, \mathbf{v}_N$  are the generalized eigenvectors of Equation 2-39 arranged by descending eigenvalues  $\lambda_1 \geq \lambda_2 \geq \dots \lambda_d$ . Then the  $N \times d$  embedding matrix  $\mathbf{Z} = [\mathbf{z}_1^T, \dots, \mathbf{z}_N^T]$  is provided by concatenating the obtained eigenvectors  $\mathbf{Z} = [\mathbf{v}_1, \mathbf{v}_2, \dots, \mathbf{v}_d]$ .

The primary difference between the classic LE and S-LE is that traditional LE solely attempts to preserve the spatial relationships between samples, and thus, does not consider label information when learning the embeddings. Alternatively, S-LE aims at aiding discriminant analysis by collapsing the distance between samples with the same label that are in close spatial proximity and pushing away spatial neighbors with differing class labels. This is done through the utilization of two affinity graphs: the within-class and between-class graphs. As with most graph-based methods, LE results vary highly according to the choice of neighborhood size. However, choosing the size of  $K$  or  $\epsilon$  in advance can be very difficult. S-LE does not require user-defined graph parameters, other than those associated with the chosen affinity measure. Instead, graph edges are chosen according to an adaptive neighborhood for each sample. Both methods, however, suffer from inherent difficulties associated with nonlinear manifold learning, namely, selecting the intrinsic embedding dimensionality and handling out-of-sample extensions.

Despite these nuances, LE (and its variants) have been successfully applied in nonlinear dimensionality reduction tasks for facial recognition, spectral clustering and object classification [van der Maaten et al. \(2007\)](#).

Apart from S-LE, other methods have been explored to integrate label information into Laplacian Eigenmaps. A review of supervised dimensionality reduction methods by Chao et al. ([Chao et al., 2019](#)) explains that author's have optimized the affinity matrix using label information after constructing from spatial proximity, proposed deep learning-based approaches

to achieve supervised LE and integrated label information into the affinity matrix construction process.

The special feature exhibited by all Laplacian Eigenmap methods is the use of laplacian regularization, which enforces properties such as smoothness and provides a level of resistance toward the influences of outliers. This useful feature has been applied in a variety of supervised and semi-supervised tasks, such as hyperspectral and synthetic aperture radar remote sensing classification (Ratle et al., 2010; Ren et al., 2017), classification of synthetic data (Tsang and Kwok, 2007), zero-shot learning (Meng and Zhan, 2018) and reinforcement learning (Li et al., 2015).

#### 2.2.5.7 Hessian Eigenmaps

#### 2.2.5.8 Diffusion Maps

#### 2.2.5.9 Sammon Mapping

#### 2.2.5.10 Maximum Variance Unfolding (MVU)

### 2.2.6 Latent Variable Models

#### 2.2.6.1 General Latent Variable Model (GLVM)

##### Factor Analysis (FA).

**Probabilistic PCA (PPCA).** PCA can also be analyzed from the viewpoint of factor analysis (FA), which is discussed later in this literature review. The basic idea, however, is that data observations  $\mathbf{x}_n \in \mathbb{R}^D$  are realizations of a probability distribution with a prior on the lower-dimensional latent variable  $\mathbf{z}_n \in \mathbb{R}^d$ . A typical choice on this model is a Gaussian-Gaussian conjugate prior pair where the mean of the data likelihood is a linear function of the latent inputs. As an example, the prior over the hidden data representations can be expressed as Gaussian distribution

$$p(\mathbf{z}_n) = \mathcal{N}(\mathbf{z}_n | \boldsymbol{\mu}_0, \mathbf{S}_0) \quad (2-40)$$

and the data likelihood is denoted as a multivariate Gaussian

$$p(\mathbf{x}_n | \mathbf{z}_n, \boldsymbol{\theta}) = \mathcal{N}(\mathbf{W} \mathbf{z}_n + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (2-41)$$

where  $\mathbf{W}$  is a  $D \times d$  *factor loading matrix*, and  $\boldsymbol{\Psi}$  is a  $D \times D$  covariance matrix. The objective of FA is to compute the posterior over the latent factors in hopes that they will reveal something interesting about the data (Murphy, 2012). Classical PCA assumes the data covariance to be  $\boldsymbol{\Psi} = \sigma^2 \mathbf{I}$  with  $\sigma^2 \rightarrow 0$ , thus the model is deterministic. Alternatively, when  $\sigma^2 > 0$ , the projection is no longer orthogonal since it is shrunk toward the prior mean. The trade-off is that the reconstructions of  $\mathbf{x}_n$  will be closer to the data mean.

While the typical approach for fitting PCA is to use the method of eigenvectors of Singular Value Decomposition (SVD), it can also be fit with Expectation-Maximization (EM). This formulation may be more computationally efficient for high-dimensional data. By using Gaussian Processes, PPCA may also be extended to learn nonlinear mappings between the input and latent feature spaces (van der Maaten et al., 2007).

### **Supervised PCA.**

Supervision has also been applied to PCA. Two such examples, Supervised PCA and Discriminative Supervised PCA, were provided by Murphy in (Murphy, 2012). The two are briefly described.

**Supervised PCA (Latent Factor Regression)** *Supervised PCA or Bayesian factor regression* is a model like PCA, except that the target variable (or label),  $l_n$  is taken into account when learning the low-dimensional embedding. For the case of binary classification, the Bayesian model can be decomposed into the following elements:

$$p(\mathbf{z}_n) = \mathcal{N}(0, \mathbf{I}_d) \quad (2-42)$$

$$p(l_n | \mathbf{z}_n) = \text{Ber}(\text{sigm}(\mathbf{w}_l^T \mathbf{z}_n)) \quad (2-43)$$

$$p(\mathbf{x}_n | \mathbf{z}_n) = \mathcal{N}(\mathbf{W}_x \mathbf{z}_n + \boldsymbol{\mu}_x, \sigma^2 \mathbf{I}_D) \quad (2-44)$$

## **Discriminative Supervised PCA**

### **2.2.6.2 Generative Topographic Mapping (GTM)**

### **2.2.7 Competitive Hebbian Learning**

### **2.2.8 Deep Learning**

**Autoencoders.**

**Graph Convolutional Networks.**

**M3DNet.**

**Paper in Papers channel.**

### **2.2.9 Current State of the Art**

### **2.2.10 UMAP**

### **2.2.11 Stochastic Neighbor Embedding (SNE and t-SNE)**

### **2.2.12 NCA**

### **2.2.13 Weak Learning on Manifolds**

Although the specific feature vectors being used in remote sensing applications can be very high-dimensional, the underlying structure of a given dataset set is usually governed by only a few variables. Either implicitly or explicitly, most learning algorithms exploit this underlying structure to make learning and inference possible. If it is available, relevant information for a specific task can generally be incorporated to provide supervision and improve the performance of unsupervised methods. Supervised methods for nonlinear dimensionality reduction assume that the samples lie on a manifold parameterized by multiple latent factors. However, different from traditional manifold learning (where the goal is to preserve the relationships between samples), these methods find the most discriminative low-dimensional representations for classification tasks (Wu, 2015). The optimal embedding uses class label information to minimize distances between nearby points with the same class label while separating samples of different classes. Although supervised manifold learning often outperforms unsupervised

methods for classification tasks, this learning cannot be done directly in MIL because of the uncertainty on the labels (Carbonneau et al., 2016). Moreover, fully-annotated samples are often difficult or impossible to obtain in many remote sensing applications (Zare et al., 2018). Even with the successes of manifold learning, most the of the previous work has mainly focused on either fully supervised or unsupervised learning. Existing work in weakly supervised learning on manifolds has primarily considered the semi-supervised setting (Z. Zhang et al., 2008; Chen et al., 2018; Zhang et al., 2014; Hong et al., 2019; Navaratnam et al., 2007; Stanley III et al., 2018; Tuia and Camps-Valls, 2015; Wang and Mahadevan, 2010, 2011). Methods in this category usually incorporate partially provided image labels and propagate the labels over the manifold approximated by the neighborhood graph on the images. In a broad sense, however, different situations of weak supervision (specifically, Multiple Instance Learning), have not been well studied (Wu, 2015).

#### **MIL-Based.**

MIDR - Sun et al. (2010); Chai et al. (2014); Zhu et al. (2018); Ping et al. (2010); Saehoon Kim and Seungjin Choi (2010)

The existing MIL manifold learning in the literature can be broken into two paradigms: LDA-based approaches and sparse, orthogonal matrix-based techniques (Zhu et al., 2018). It should be noted that while this proposal addresses the problem of manifold learning for instance-level classification, all MIL DR approaches in the literature were developed with bag-level classification in mind. Additionally, all existing approaches are linear, meaning they may not work well if the underlying bag manifold exhibits curvature. The existing approaches are briefly described.

The first true MIL manifold learning experimentation was performed in (Sun et al., 2010) under the orthogonal matrix-based paradigm. In this work, Sun et al. showed that Principal Component Analysis (PCA) failed to incorporate bag-level label information and thus provided poor separation between positive and negative bags. Additionally, traditional Linear Discriminant Analysis (LDA) was used to project bags into a latent space which maximized

between-bag separation, while minimizing within-bag dissimilarity. However, LDA often mixed the latent bag representations due to the uncertainty of negative sample distributions in the positive bags. To address these issues, Sun et al. proposed Multiple Instance Dimensionality Reduction (MIDR) which optimized an objective through gradient descent to discover sparse, orthogonal projection vectors in the latent space. The goal of MIDR is to discover a projection matrix  $\mathbf{W} \in \mathbb{R}^{D \times d}$  which will increase discriminability between positive and negative bags in the latent embedding space. If given the  $k^{th}$  training bag,  $\mathbf{B}_k = \{\mathbf{x}_{k,1}, \dots, \mathbf{x}_{k,n_k}\}$  with corresponding binary bag-level label  $L_k \in \{0, 1\}$ , MIDR attempts to find a matrix  $\mathbf{W}$  such that the projection of  $\mathbf{B}_k \subset \mathbb{R}^D$  by  $\mathbf{W}^T \mathbf{B}_k \subset \mathbb{R}^d$  increases the separation between positive and negative bags. The intuition is that the probability of the  $k^{th}$  bag being positive  $\Pr(L_k = 1 | \mathbf{W}^T \mathbf{B}_k)$  should be close to one if it is positive and close to zero otherwise. This can be achieved by minimizing the squared loss between the actual and predicted label of each bag

$$\min_{\mathbf{W}} \sum_{k=1}^K (\Pr(L_k = 1 | \mathbf{W}^T \mathbf{B}_k) - L_k)^2 \quad (2-45)$$

Taking advantage of the standard assumption, the posterior probability of a bag can be written in terms of the posterior probabilities of its instances

$$\Pr(L_k = 1 | \mathbf{W}^T \mathbf{B}_k) = \max_n \Pr(l_{k,n} = 1 | \mathbf{W}^T \mathbf{x}_{k,n}) \quad (2-46)$$

Equation 2-45 then becomes

$$\min_{\mathbf{W}} \sum_{k=1}^K (\max_n \Pr(l_{k,n} = 1 | \mathbf{W}^T \mathbf{x}_{k,n}) - L_k)^2 \quad (2-47)$$

From the objective, it is clear that in order to minimize the squared loss, the distances between the key positive instances and all negative instances should be as large as possible. Additionally,  $\mathbf{W}$  is required to be orthogonal in order to guarantee the resulting latent features are uncorrelated (to remove redundancy) as well as sparse (to improve interpretability). This implies that the new feature representations of instances  $\mathbf{x}_{kn}$  in bag  $\mathbf{B}_k$  are formed by linear

combinations of the features in the input feature space. The MIDR optimization problem can be written succinctly as defined in (Zhu et al., 2018):

$$\min_{\mathbf{W}, \beta} f(\mathbf{W}, \alpha) + \gamma \|\mathbf{W}\|_1 \quad \text{s.t.} \quad \mathbf{W}^T \mathbf{W} = \mathbb{I}_d \quad (2-48)$$

where  $\gamma$  is a positive number which controls the balance between the sparsity term  $\|\mathbf{W}\|_1$  and the fitting term  $f(\mathbf{W}, \alpha) = \sum_{k=1}^K (P_k(\mathbf{W}, \beta) - L_k)^2$ . In this case,

$$\begin{aligned} P_k(\mathbf{W}, \beta) &= \text{softmax}_\alpha(P_{k,1}(\mathbf{W}, \beta), \dots, P_{k,n_k}(\mathbf{W}, \beta)) \\ &= \frac{\sum_{n=1}^{n_k} P_{k,n} e^{\alpha P_{k,n}(\mathbf{W}, \beta)}}{\sum_{n=1}^{n_k} e^{\alpha P_{k,n}(\mathbf{W}, \beta)}} \end{aligned} \quad (2-49)$$

is the softmax approximation over  $n$  of  $\max(P_{k,1}(\mathbf{W}, \beta), \dots, P_{k,n_k}(\mathbf{W}, \beta))$ . A popular way to estimate the posterior probability is by logistic regression

$$P_{k,n}(\mathbf{W}, \beta) = \Pr(l_{k,n} = 1 | \mathbf{W}^T, \mathbf{x}_{k,n}) = \frac{1}{1 + \exp(-\beta^T \mathbf{W}^T \mathbf{x}_{k,n})} \quad (2-50)$$

In (Sun et al., 2010), gradient descent was used to optimize the objective. It was found that the newly developed method outperformed unsupervised instance-level dimensionality reduction approaches (applied to bags) for bag-level classification. MIDR was later revisited by Zhu et al. where the optimization problem was reformulated using the inertial proximal alternating linearized minimization (iPALM) method (Zhu et al., 2018). The advantage of this approach is that the problem variables can be managed sperately and updated effectively. Additionally, the global convergence of MIDR was proved.

The other approach to dimensionality reduction with weak labels is by a LDA scheme.

MidLABS, MIDA, CLFDA

Most existing approaches in the literature extend LDA to distinguish between positive and negative bags (Chai et al., 2014; Zhu et al., 2018). These methods typically rely on costly optimization procedures to maximize an objective for orthogonal and sparse projection vectors. The work in (Xu et al.) investigated metric learning on sets of data (where each bag was a set) to learn an appropriate similarity metric to compare bags. They do not go as far as to

discriminate positive instances within the positive bags, nor do they propose positive target concepts. *In fact, virtually all MIL DR methods in the literature are applied, solely, to predict bag-level labels.* While bag-level label prediction is useful in many remote sensing applications, such as region of interest (ROI) proposal for anomaly detection, they limit the the ability of learners to classify on the pixel or sample level. To this end, methods for instance-level discriminative dimensionality reduction should be developed. This point is demonstrated in by the embeddings of 3-dimensional quadratic surfaces as shown in Figures

### **General Weak Supervision.**

Wu studied weakly supervised manifold learning for manifold factorization using image-level labels, where the labels were the variation of interest. The primary idea was to use weak labels to find image pairs that should be more similar after removing unwanted image variation. He used an alignment method constrained by Hessian regularization to learn a manifold regression, such that new test images would be projected smoothly into a space near neighboring input images. [Wu \(2015\)](#)

Xu did a thing with large margin [Xu et al. \(2014\)](#)

Dense object Correspondence [Gaur and Manjunath \(2017\)](#)

**Metric Embedding.** An alternative approach for discriminative dimensionality reduction with weak labels is through the application of metric embedding, which is discussed in detail in Section 2.3. While they can be fully supervised, metric embedding techniques often consider groups of samples (usually two or three), jointly, to learn an embedding function. Under this type of weak supervision, only a notion of semantic similarity is needed, as compared to direct class labels.

## **2.3 Metric Embedding**

The concepts of “near” and “far” are very powerful and useful utilities in everyday life. They classify the relationship between two “primitives” as being similar or dissimilar, as well as the degree of compatibility ([Thorstensen, 2009](#)). As an example, a medical doctor might consider a machine learning researcher and a software engineer as being similar (near), because



they both perform research for computer applications. However, the same researcher and engineer would likely consider their jobs as being very disparate (far) based on the details of their work. In order to capture this abstraction of distance, a *metric space* is defined as a mathematical construction of this vague generality.

**Definition 2.3.1.** Metric Space A *metric space* is an ordered pair  $(\mathcal{X}, \mathcal{D})$  where  $\mathcal{X}$  is a set and  $\mathcal{D}$  is a metric on  $\mathcal{X}$ , or  $\mathcal{D} : \mathcal{X} \times \mathcal{X} \rightarrow \mathbb{R}$  such that  $\forall \mathbf{x}, \mathbf{y}, \mathbf{z} \in \mathcal{X}$ , the following holds:

1. Non-negativity:  $\mathcal{D}(\mathbf{x}, \mathbf{y}) \geq 0$
2. Identity:  $\mathcal{D}(\mathbf{x}, \mathbf{y}) = 0 \iff \mathbf{x} = \mathbf{y}$
3. Symmetry:  $\mathcal{D}(\mathbf{x}, \mathbf{y}) = \mathcal{D}(\mathbf{y}, \mathbf{x})$
4. Triangle Inequality:  $\mathcal{D}(\mathbf{x}, \mathbf{z}) \leq \mathcal{D}(\mathbf{x}, \mathbf{y}) + \mathcal{D}(\mathbf{y}, \mathbf{z})$

**Explain more about these properties...**

The goal of *metric embedding learning* is to learn a function  $f_\theta(\mathbf{x}) : \mathbb{R}^D \rightarrow \mathbb{R}^d$  which maps semantically similar points from the data input feature space of  $\mathbb{R}^D$  onto *metrically close* points in  $\mathbb{R}^d$ . Similarly,  $f_\theta$  should map semantically different points in  $\mathbb{R}^D$  onto metrically distant points in  $\mathbb{R}^d$ . The function  $f_\theta$  is parameterized by  $\theta$  and can be anything ranging from a linear transformation to a complex non-linear mapping as in the case of deep artificial neural networks (an [Lucas Beyer and Leibe, 2017](#)). Let  $\mathcal{D}(\mathbf{x}, \mathbf{y}) : \mathbb{R}^d \times \mathbb{R}^d \rightarrow \mathbb{R}$  be a metric function measuring similarity or dissimilarity in the embedded space. For succinctness,  $\mathcal{D}_{i,j} = \mathcal{D}(f_\theta(\mathbf{x}_i), f_\theta(\mathbf{x}_j))$  defines the dissimilarity between samples  $\mathbf{x}_i$  and  $\mathbf{x}_j$ , after being embedded.

### 2.3.0.1 Metric Learning

Thorstensen thesis, Raducanu S-LE

#### 2.3.1 Ranking Loss

##### 2.3.1.1 Pairwise Loss

##### 2.3.1.2 Contrastive Loss

Definition of Contrastive Loss:

### 2.3.1.3 Triplet Loss

Definition of Triplet Loss:

Triplet loss was extended in ([Sohn, 2016](#)) to simultaneously optimize against N negative classes.

### 2.3.1.4 Large-Margin K-Nearest Neighbors (LMNN)

### 2.3.1.5 FaceNet

FaceNet is a convolutional neural network which learns a mapping from face images to a compact Euclidean space where distances directly correspond to a measure of face similarity ([Schroff et al., 2015](#)).

$$\|f(x_i^a) - f(x_i^p)\|_2^2 + \alpha < \|f(x_i^a) - f(x_i^n)\|_2^2, \quad \forall (f(x_i^a), f(x_i^p), f(x_i^n)) \in \mathcal{T} \quad (2-51)$$

$$\mathcal{L} = \|f(x_i^a) - f(x_i^p)\|_2^2 - \|f(x_i^a) - f(x_i^n)\|_2^2 + \alpha \quad (2-52)$$

### 2.3.1.6 Siamese Neural Networks

## 2.3.2 Manifold Regularization

## 2.3.3 Multiple Instance Metric Learning

[Xu et al.](#)

## CHAPTER 3

### PROBLEM DESCRIPTION

## CHAPTER 4

### EXPERIMENTAL DESIGN

## CHAPTER 5

### PRELIMINARY WORK

The work by Wei et al. in [Wei and Zhou \(2016\)](#) suggested that for image classification tasks, certain formulations of MIL were better suited than others. Algorithms such as miGraph, MIBoosting and miFV which assume non-i.i.d samples or take advantage of aggregating properties of bags tend to work better than those which adopt the standard assumption. The authors of this work recommend miGraph with LBP bag generation or MIBoosting with Single Blob generation for image classification. Additionally, classification performance tended to increase as the number of instances increased.

## CHAPTER 6

### FUTURE TASKS

## CHAPTER 7

### CONCLUSIONS

## REFERENCES

- Alexander Hermans and Lucas Beyer and Bastian Leibe. In defense of the triplet loss for person re-identification. *CoRR*, abs/1703.07737, 2017. URL <http://arxiv.org/abs/1703.07737>.
- Boris Babenko, Nakul Verma, Piotr Dollr, and Serge Belongie. Multiple instance learning with manifold bags. pages 81–88, 01 2011.
- G. Baudat and F. Anouar. Generalized discriminant analysis using a kernel approach. *Neural Computation*, 12(10):2385–2404, 2000. doi: 10.1162/089976600300014980.
- M. Belkin and P. Niyogi. Semi-supervised learning on riemannian manifolds. *Machine Learning*, 56(1):209–239, Jul 2004. ISSN 1573-0565. doi: 10.1023/B:MACH.0000033120.25363.1e.
- M. Belkin, P. Niyogi, and V. Sindhwani. Manifold regularization: A geometric framework for learning from labeled and unlabeled examples. *J. Mach. Learn. Res.*, 7:2399–2434, December 2006. ISSN 1532-4435. URL <http://dl.acm.org/citation.cfm?id=1248547.1248632>.
- Y. Bengio, A. C. Courville, and P. Vincent. Unsupervised feature learning and deep learning: A review and new perspectives. *CoRR*, abs/1206.5538, 2012. URL <http://arxiv.org/abs/1206.5538>.
- E. Bengoetxea. *Inexact Graph Matching Using Estimation of Distribution Algorithms*. PhD thesis, Ecole Nationale Supérieure des Télécommunications, Paris, France, Dec. 2002.
- C. Bishop, M. Svensn, and C. K. I. Williams. Gtm: The generative topographic mapping. 10: 215–234, January 1998. URL <https://www.microsoft.com/en-us/research/publication/gtm-the-generative-topographic-mapping/>.
- J. Bocinsky. Learning multiple target concepts from uncertain, ambiguous data using the adaptive cosine estimator and spectral match filter. Master’s thesis, Univ. of Florida, Gainesville, FL, May 2019.
- M. Carbonneau, V. Cheplygina, E. Granger, and G. Gagnon. Multiple instance learning: A survey of problem characteristics and applications. *CoRR*, abs/1612.03365, 2016. URL <http://arxiv.org/abs/1612.03365>.



- Jing Chai, Xinghao Ding, Hongtao Chen, and Tingyu Li. Multiple-instance discriminant analysis. *Pattern Recognition*, 47(7):2517 – 2531, 2014. ISSN 0031-3203. doi: <https://doi.org/10.1016/j.patcog.2014.02.002>. URL <http://www.sciencedirect.com/science/article/pii/S0031320314000387>.
- G. Chao, Y. Luo, and W. Ding. Recent advances in supervised dimension reduction: A survey. *Machine Learning and Knowledge Extraction*, 1(1):341–358, 2019. ISSN 2504-4990. doi: 10.3390/make1010020.
- B. Chaudhuri and S. Parui. Target detection: Remote sensing techniques for defence applications. *Defence Science Journal*, 45:285–291, 04 1995. doi: 10.14429/dsj.45.4135.
- M. Chen, J. Wang, X. Li, and X. Sun. Robust semi-supervised manifold learning algorithm for classification. *Mathematical Problems in Engineering*, 2018:1–8, 02 2018. doi: 10.1155/2018/2382803.
- V. Cheplygina, M. Bruijne, and J. P. W. Pluim. Not-so-supervised: A survey of semi-supervised, multi-instance, and transfer learning in medical image analysis. *Medical Image Analysis*, 54:280 – 296, 2019. ISSN 1361-8415. doi: <https://doi.org/10.1016/j.media.2019.03.009>.
- Chun-Guang Li and Jun Guo. Supervised isomap with explicit mapping. In *First International Conference on Innovative Computing, Information and Control - Volume I (ICICIC'06)*, volume 3, pages 345–348, Aug 2006. doi: 10.1109/ICICIC.2006.530.
- M. Cook. Task driven extended functions of multiple instances (td-efumi). Master’s thesis, Univ. of Missouri, Columbia, MO, 2015.
- T. G. Dietterich, R. H. Lathrop, and T. Lozano-Prez. Solving the multiple instance problem with axis-parallel rectangles. *Artificial Intelligence*, 89(1):31 – 71, 1997. ISSN 0004-3702. doi: [https://doi.org/10.1016/S0004-3702\(96\)00034-3](https://doi.org/10.1016/S0004-3702(96)00034-3).
- Defense Systems Information Analysis Center DSIAC. DSIAC MS-003-DB Algorithm Development Database. <https://www.dsiac.org/resources/research-materials/cds-dvds-databases-digital-files/atr-algorithm-development-image>, 2014.

- X. Du. *Multiple Instance Choquet Integral For MultiResolution Sensor Fusion*. PhD thesis, Univ. of Missouri, Columbia, MO, Dec. 2017.
- X. Du and A. Zare. Technical report: Scene label ground truth map for muufl gulfport data set. Technical Report 417, University of Florida, Gainesville, FL, April 2017. URL <http://ufdc.ufl.edu/IR00009711/00001>.
- K. Fukunaga and J. M. Mantock. Nonparametric discriminant analysis. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, PAMI-5(6):671–678, Nov 1983. ISSN 1939-3539. doi: 10.1109/TPAMI.1983.4767461.
- P. Gader, A. Zare, R. Close, J. Aitken, and G. Tuell. Muufl gulfport hyperspectral and lidar airborne data set. Technical Report 570, University of Florida, Gainesville, FL, October 2013.
- U. Gaur and B. S. Manjunath. Weakly supervised manifold learning for dense semantic object correspondence. In *2017 IEEE International Conference on Computer Vision (ICCV)*, pages 1744–1752, Oct 2017. doi: 10.1109/ICCV.2017.192.
- Xiurui Geng, Luyan Ji, and Yongchao Zhao. The basic equation for target detection in remote sensing, 2017.
- Benyamin Ghogh, Fakhri Karray, and Mark Crowley. Fisher and kernel fisher discriminant analysis: Tutorial. *CoRR*, abs/1906.09436, 2019. URL <https://arxiv.org/abs/1906.09436>.
- T. Glenn, A. Zare, P. Gader, and D. Dranishnikov. Bullwinkle: Scoring code for sub-pixel targets. URL <https://github.com/GatorSense/MUUFLGulfport/>.
- D. Hong, N. Yokoya, N. Ge, J. Chanussot, and X. X. Zhu. Learnable manifold alignment (lema): A semi-supervised cross-modality learning framework for land cover and land use classification. *ISPRS Journal of Photogrammetry and Remote Sensing*, 147:193 – 205, 2019. ISSN 0924-2716.
- Gary B. Huang, Manu Ramesh, Tamara Berg, and Erik Learned-Miller. Labeled faces in the wild: A database for studying face recognition in unconstrained environments. Technical Report 07-49, University of Massachusetts, Amherst, October 2007.

- Balzs Kegl, Donald Wunsch, and Andrei Zinovyev. *Principal Manifolds for Data Visualisation and Dimension Reduction*, LNCSE 58. 01 2008. ISBN 978-3-540-73750-6.
- T. Kohonen. The self-organizing map. *Proceedings of the IEEE*, 78(9):1464–1480, Sep. 1990. ISSN 0018-9219. doi: 10.1109/5.58325.
- H. Li, D. Liu, and D. Wang. Approximate policy iteration with unsupervised feature learning based on manifold regularization. In *2015 International Joint Conference on Neural Networks (IJCNN)*, pages 1–6, July 2015.
- Weifeng Liu, Jose C. Principe, and Simon Haykin. *Kernel Adaptive Filtering: A Comprehensive Introduction*. Wiley Publishing, 1st edition, 2010. ISBN 0470447532.
- L. Livi and A. Rizzi. The graph matching problem. *Pattern Anal. Appl.*, 16(3):253–283, Aug 2013. ISSN 1433-7541. doi: 10.1007/s10044-012-0284-8.
- M. Meng and X. Zhan. Zero-shot learning via low-rank-representation based manifold regularization. *IEEE Signal Processing Letters*, 25(9):1379–1383, Sep. 2018. ISSN 1070-9908. doi: 10.1109/LSP.2018.2857201.
- K. P. Murphy. *Machine Learning: A Probabilistic Perspective*. The MIT Press, 2012. ISBN 0262018020, 9780262018029.
- R. Navaratnam, A. W. Fitzgibbon, and R. Cipolla. The joint manifold model for semi-supervised multi-valued regression. In *2007 IEEE 11th International Conference on Computer Vision*, pages 1–8, Oct 2007. doi: 10.1109/ICCV.2007.4408976.
- M. Nickel and D. Kiela. Poincaré embeddings for learning hierarchical representations. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems 30*, pages 6338–6347. Curran Associates, Inc., 2017.
- E. J. Palomo and E. Lopez-Rubio. The growing hierarchical neural gas self-organizing neural network. *IEEE Transactions on Neural Networks and Learning Systems*, 28(9):2000–2009, Sep. 2017. ISSN 2162-237X. doi: 10.1109/TNNLS.2016.2570124.

- Wei Ping, Ye Xu, Ren Kexin, Chi-Hung Chi, and Shen Fura. Non-i.i.d. multi-instance dimensionality reduction by learning a maximum bag margin subspace. volume 1, 01 2010.
- B. Raducanu and F. Dornaika. A supervised non-linear dimensionality reduction approach for manifold learning. *Pattern Recognition*, 45(6):2432 – 2444, 2012. ISSN 0031-3203.
- F. Ratle, G. Camps-Valls, and J. Weston. Semisupervised neural networks for efficient hyperspectral image classification. *IEEE Transactions on Geoscience and Remote Sensing*, 48(5):2271–2282, May 2010. ISSN 0196-2892. doi: 10.1109/TGRS.2009.2037898.
- Joseph Redmon and Ali Farhadi. YOLOv3: An incremental improvement. *CoRR*, abs/1804.02767, 2018. URL <http://arxiv.org/abs/1804.02767>.
- B. Ren, B. Hou, J. Zhao, and L. Jiao. Unsupervised classification of polarimetric SAR image via improved manifold regularized low-rank representation with multiple features. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 10(2):580–595, Feb 2017. ISSN 1939-1404. doi: 10.1109/JSTARS.2016.2573380.
- Bernardete Ribeiro, Armando Vieira, and João Carvalho das Neves. Supervised isomap with dissimilarity measures in embedding learning. In José Ruiz-Shulcloper and Walter G. Kropatsch, editors, *Progress in Pattern Recognition, Image Analysis and Applications*, pages 389–396, Berlin, Heidelberg, 2008. Springer Berlin Heidelberg.
- I. Rish, G. Grabarnik, G. A. Cecchi, F. Pereira, and G. J. Gordon. Closed-form supervised dimensionality reduction with generalized linear models. pages 832–839, 01 2008. doi: 10.1145/1390156.1390261.
- José Francisco Ruiz-Muñoz, Mauricio Orozco-Alzate, and Germán Castellanos-Domínguez. Multiple instance learning-based birdsong classification using unsupervised recording segmentation. In *IJCAI*, 2015.
- Saehoon Kim and Seungjin Choi. Local dimensionality reduction for multiple instance learning. In *2010 IEEE International Workshop on Machine Learning for Signal Processing*, pages 13–18, Aug 2010. doi: 10.1109/MLSP.2010.5589175.

- Bernhard Schölkopf, Alexander J. Smola, and Klaus-Robert Müller. *Kernel Principal Component Analysis*, page 327352. MIT Press, Cambridge, MA, USA, 1999. ISBN 0262194163.
- Florian Schroff, Dmitry Kalenichenko, and James Philbin. Facenet: A unified embedding for face recognition and clustering. *CoRR*, abs/1503.03832, 2015. URL <http://arxiv.org/abs/1503.03832>.
- D. I. Shuman, S. K. Narang, P. Frossard, A. Ortega, and P. Vandergheynst. The emerging field of signal processing on graphs: Extending high-dimensional data analysis to networks and other irregular domains. *IEEE Signal Processing Magazine*, 30(3):83–98, May 2013.
- Vin Silva and Joshua Tenenbaum. Unsupervised learning of curved manifolds. 01 2002. doi: 10.1007/978-0-387-21579-2\_31.
- Vin D. Silva and Joshua B. Tenenbaum. Global versus local methods in nonlinear dimensionality reduction. In S. Becker, S. Thrun, and K. Obermayer, editors, *Advances in Neural Information Processing Systems 15*, pages 721–728. MIT Press, 2003. URL <http://papers.nips.cc/paper/2141-global-versus-local-methods-in-nonlinear-dimensionality-reduction.pdf>.
- Kihyuk Sohn. Improved deep metric learning with multi-class n-pair loss objective. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems 29*, pages 1857–1865. Curran Associates, Inc., 2016.
- C. O. S. Sorzano, J. Vargas, and A. Pascual Montano. A survey of dimensionality reduction techniques, 2014.
- J. S. Stanley III, G. Wolf, and S. Krishnaswamy. Manifold alignment with feature correspondence. *CoRR*, abs/1810.00386, 2018. URL <http://arxiv.org/abs/1810.00386>.
- Yu-Yin Sun, Michael K. Ng, and Zhi-Hua Shou. Multi-instance dimensionality reduction. In *Proceedings of the Twenty-Fourth AAAI Conference on Artificial Intelligence, AAAI’10*, pages 587–592. AAAI Press, 2010. URL <http://dl.acm.org/citation.cfm?id=2898607.2898702>.
- R. Talmon, S. Mallat, H. Zaveri, and R. R. Coifman. Manifold learning for latent variable inference in dynamical systems. *IEEE Transactions on Signal Processing*, 63(15):3843–3856,

- Aug 2015. ISSN 1053-587X. doi: 10.1109/TSP.2015.2432731.
- J. B. Tenenbaum, V. Silva, and J. C. Langford. A global geometric framework for nonlinear dimensionality reduction. *Science*, 290(5500):2319–2323, 2000. ISSN 0036-8075. doi: 10.1126/science.290.5500.2319. URL <https://science.sciencemag.org/content/290/5500/2319>.
- S. Theodoridis and K. Koutroumbas. Kernel pca. In *Pattern Recognition, Fourth Edition*, chapter 6, pages 351–353. Academic Press, Inc., Orlando, FL, USA, 4th edition, 2008. ISBN 1597492728, 9781597492720.
- N. Thorstensen. *Manifold learning and applications to shape and image processing*. PhD thesis, Ecole Nationale des Ponts et Chaussees, Paris, France, Nov. 2009.
- I. W. Tsang and J. T. Kwok. Large-scale sparsified manifold regularization. In B. Schölkopf, J. C. Platt, and T. Hoffman, editors, *Advances in Neural Information Processing Systems 19*, pages 1401–1408. MIT Press, 2007. URL <http://papers.nips.cc/paper/3005-large-scale-sparsified-manifold-regularization.pdf>.
- D. Tuia and G. Camps-Valls. Kernel manifold alignment. 04 2015.
- L. van der Maaten, E. Postma, and H. Herik. Dimensionality reduction: A comparative review. *Journal of Machine Learning Research - JMLR*, 10, 01 2007.
- Michail Vlachos, Carlotta Domeniconi, Dimitrios Gunopulos, George Kollios, and Nick Koudas. Non-linear dimensionality reduction techniques for classification and visualization. In *Proceedings of the Eighth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD 02, page 645651, New York, NY, USA, 2002. Association for Computing Machinery. ISBN 158113567X. doi: 10.1145/775047.775143. URL <https://doi.org/10.1145/775047.775143>.
- E. Vural and C. Guillemot. A study of the classification of low-dimensional data with supervised manifold learning. *CoRR*, abs/1507.05880, 2018. URL <http://arxiv.org/abs/1507.05880>.
- C. Wang and S. Mahadevan. Multiscale manifold alignment. 09 2010.

- C. Wang and S. Mahadevan. Heterogeneous domain adaptation using manifold alignment. In *Proceedings of the Twenty-Second International Joint Conference on Artificial Intelligence - Volume Volume Two*, IJCAI'11, pages 1541–1546. AAAI Press, 2011. ISBN 978-1-57735-514-4. doi: 10.5591/978-1-57735-516-8/IJCAI11-259. URL <http://dx.doi.org/10.5591/978-1-57735-516-8/IJCAI11-259>.
- Quan Wang. Kernel principal component analysis and its applications in face recognition and active shape models. *CoRR*, abs/1207.3538, 2012. URL <http://arxiv.org/abs/1207.3538>.
- Yong Wang, Jian-Bin Xie, and Yi Wu. Orthogonal discriminant analysis revisited. *Pattern Recognition Letters*, 84:149 – 155, 2016. ISSN 0167-8655. doi: <https://doi.org/10.1016/j.patrec.2016.09.010>.
- Andrew Webb. A kernel approach to metric multidimensional scaling. pages 613–629, 02 2002.
- Andrew R Webb and David Lowe. The optimised internal representation of multilayer classifier networks performs nonlinear discriminant analysis. *Neural Networks*, 3(4):367 – 375, 1990. ISSN 0893-6080. doi: [https://doi.org/10.1016/0893-6080\(90\)90019-H](https://doi.org/10.1016/0893-6080(90)90019-H).
- Xiu-Shen Wei and Zhi-Hua Zhou. An empirical study on image bag generators for multi-instance learning. *Mach. Learn.*, 105(2):155198, November 2016. ISSN 0885-6125. doi: 10.1007/s10994-016-5560-1. URL <https://doi.org/10.1007/s10994-016-5560-1>.
- David Weinberger. Ai outside in: Machine learning’s triangle of error. URL <https://accelerate.withgoogle.com/stories/ai-outside>.
- Daniela M. Witten and Robert Tibshirani. Supervised multidimensional scaling for visualization, classification, and bipartite ranking. *Computational Statistics and Data Analysis*, 55(1):789 – 801, 2011. ISSN 0167-9473.
- Hui Wu. *Weakly supervised learning on image manifolds*. PhD thesis, University of North Carolina at Charlotte, Charlotte, NC, 2015.
- X. Geng, D. Zhan, and Z. Zhou. Supervised nonlinear dimensionality reduction for visualization and classification. *IEEE Transactions on Systems, Man, and Cybernetics, Part B (Cybernetics)*, 35(6):1098–1107, Dec 2005. ISSN 1083-4419.

- C. Xu, D. Tao, and Y. Rui. Large-margin weakly supervised dimensionality reduction. *31st International Conference on Machine Learning, ICML 2014*, 3:2472–2482, 01 2014.
- Y. Xu, W. Ping, and A. T. Campbell.
- S. Yan, D. Xu, B. Zhang, H. Zhang, Q. Yang, and S. Lin. Graph embedding and extensions: A general framework for dimensionality reduction. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 29(1):40–51, Jan 2007.
- Z. Zhang, H. Zha, and M. Zhang. Spectral methods for semi-supervised manifold learning. In *2008 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–6, June 2008. doi: 10.1109/CVPR.2008.4587381.
- A. Zare. *Hyperspectral Endmember Detection and Band Selection Using Bayesian Methods*. PhD thesis, Univ. of Florida, Gainesville, FL, 2008.
- Alina Zare, Changzhe Jiao, and Taylor Glenn. Discriminative multiple instance hyperspectral target characterization. *IEEE Trans. Pattern Anal. Mach. Inteli.*, 40(10):2342–2354, Oct. 2018. doi: 10.1109/TPAMI.2017.2756632.
- Y. Zhang, X. Zheng, G. Liu, X. Sun, H. Wang, and K. Fu. Semi-supervised manifold learning based multigraph fusion for high-resolution remote sensing image classification. *IEEE Geoscience and Remote Sensing Letters*, 11(2):464–468, Feb 2014. ISSN 1545-598X. doi: 10.1109/LGRS.2013.2267091.
- Yan Zhang, Zhao Zhang, Jie Qin, Li Zhang, Bing Li, and Fanzhang Li. Semi-supervised local multi-manifold isomap by linear embedding for feature extraction. *Pattern Recognition*, 76: 662 – 678, 2018. ISSN 0031-3203. doi: <https://doi.org/10.1016/j.patcog.2017.09.043>. URL <http://www.sciencedirect.com/science/article/pii/S0031320317303977>.
- Hong Zhu, Li-Zhi liao, and Michael K. Ng. Multi-instance dimensionality reduction via sparsity and orthogonality. *Neural Comput.*, 30(12):3281–3308, dec 2018. ISSN 0899-7667. doi: 10.1162/neco\_a\_01140. URL [https://doi.org/10.1162/neco\\_a\\_01140](https://doi.org/10.1162/neco_a_01140).