

tt()

D3 FTW!

Schedule

1. Why you're using D3
2. D3 Concepts
3. Let's get started



Schedule

1. Why you're using D3
2. D3 Concepts
3. Let's get started



D3

Data Driven Documents

D3 – the purpose

“D3.js is a JavaScript library for **manipulating documents based on data**.

D3 helps you bring data to life using HTML, SVG, and CSS.

(...)D3 is extremely fast, supporting large datasets and dynamic behaviours for interaction and animation.”



D3 vs Instant Mix

- [RawGraphs.io](https://rawgraphs.io)
- [LocalFocus.nl](https://localfocus.nl)
- [Flourish.studio](https://flourish.studio)



Just add water!


D3 vs Chart.js



```
<canvas id="myChart"></canvas>
```


```
<script>
```

```
new Chart("myChart", {  
  type: "bar",  
  data: {  
    labels: ["1980", "1990", "2000", "2010", "2020"],  
    datasets: [  
      {  
        label: "My data",  
        backgroundColor: "#af90ca",  
        data: [12, 15, 14, 16, 18],  
      },  
    ],  
  },  
});  
</script>
```



D3 vs Chart.css

```
1  <table class="charts-css bar">
2
3  <caption> 2016 Summer Olympics Medal Table </caption>
4
5  <thead>
6    <tr>
7      <th scope="col"> Country </th>
8      <th scope="col"> Gold </th>
9      <th scope="col"> Silver </th>
10     <th scope="col"> Bronze </th>
11   </tr>
12 </thead>
13
14 <tbody>
15   <tr>
16     <th scope="row"> USA </th>
17     <td> 46 </td>
18     <td> 37 </td>
19     <td> 38 </td>
20   </tr>
21   <tr>
22     <th scope="row"> GBR </th>
23     <td> 27 </td>
24     <td> 23 </td>
25     <td> 17 </td>
26   </tr>
27   <tr>
28     <th scope="row"> CHN </th>
29     <td> 26 </td>
30     <td> 18 </td>
31     <td> 26 </td>
32   </tr>
33 </tbody>
34
35 </table>
```



D3 Concepts

1. Why you're using D3

2. D3 Concepts

3. Let's get started



D3 Concepts

1. Selections


2. Joins

3. Accessor functions

4. Scales

5. Axes

6. Ticks



Selections – the purpose

We work with HTML elements, SVG ... and want to modify them

`d3.select()` is kinda like `document.querySelector()`

`d3.selectAll` is kinda like `document.querySelectorAll()`

```
d3.selectAll('circle')
```

```
d3.selectAll('circle').style('fill', 'red')
```

Selections

`d3.select()` is kinda like `document.querySelector()`

`d3.selectAll` is kinda like `document.querySelectorAll()`

Name	Behaviour	Example
<code>.style</code>	Update the style	<code>d3.selectAll('circle').style('fill', 'red')</code>
<code>.attr</code>	Update an attribute	<code>d3.selectAll('rect').attr('width', 10)</code>
<code>.classed</code>	Add/remove a class attribute	<code>d3.select('.item').classed('selected', true)</code>
<code>.property</code>	Update an element's property	<code>d3.selectAll('input[type=checkbox]').property('checked', true)</code>
<code>.text</code>	Update the text content	<code>d3.select('h1').text('Hello world')</code>
<code>.html</code>	Change the html content	<code>d3.select('form').html('<button>Turn off</button>')</code>

Joins – the purpose

We never know in advance how many SVG elements we will need.

It depends on our data

Joins

Data joins are kinda like doing a mail merge in Office to create address labels based on a list in Excel



```
<svg id="chart"></svg>
```

```
<script>
```

```
let myData = [40, 10, 20, 60, 30];
```

```
d3.select('#chart')
```

```
  .selectAll('rect')
```

```
  .data(myData)
```

```
  .join('rect');
```

```
</script>
```

Here we use `d3.join()` to create a `<rect>` element for each item in our `myData` array

Accessor functions – the purpose



```
<svg id="chart"></svg>
```

```
<script>
```

```
  const myData = [  
    { day: "Monday", cars: 40 },  
    { day: "Tuesday", cars: 10 },  
    { day: "Wednesday", cars: 20 },  
    { day: "Thursday", cars: 60 },  
    { day: "Friday", cars: 30 },  
  ];
```

```
  d3.select("#chart")
```

```
    .selectAll("rect")
```

```
    .data(myData)
```

```
    .join("rect")
```

```
    .attr('width', d => d.cars);
```

```
</script>
```

If you're using JSON (an array of objects) you'll need to tell D3 which property you want to use

← Accessor function

Schedule

1. Why you're using D3
2. D3 Concepts
- 3. Let's get started**



Exercise

1. Live demo!

2. Practice with selections, joins and accessor function:

1. https://codepen.io/Laura_B/pen/KKOBMgL

D3 Concepts

1. Why you're using D3

2. More D3 Concepts

3. Let's get started




Scales – the purpose


Scales allow to visualize data through:

size

position



(In a way they fit in your graphic view)



Scales – the math

Scales help you calculate


- how big elements of your graph should be
- where are they positioned

They are **functions**

domain = what you need to show

range = the options you have

We will cover this tomorrow



Scales

Scales allow to visualize data through:

size

position

and **color**



Huiswerk – voor morgen

- Werk in tweetallen
- Maak een **point scale** die er voor zorgt dat, hoeveel ritten er ook worden afgebeeld door een auto, ze altijd passen in een rij van 800px
- Maak een **kleurscale** die de user laat zien hoe rendabel de rit is, bijvoorbeeld:



- Zie: <https://www.d3indepth.com/scales/>

Wij zijn benieuwd!!!!



Uncaught SyntaxError
Unexpected end of input