

Chapter I

Data Communications: An Introduction

Nassau Community College
CMP 110: Data Communications & the Internet
Prof. Christopher R. Merlo
cmerlo@ncc.edu

What Is Data Communications?

- Simple answer: Getting data from Point A to Point B
- Better answer: Getting data from Point A to points B, C, D, ...
- Best answer: Transmission of **encoded** data and information in a **medium-specific** format between two or more **nodes**

Bits & Bytes

- Humans use natural language to communicate
- Computers only understand numbers
- We represent these numbers in **binary** with ones and zeroes
- Data must be **encoded** into a format that both sender and receiver understand

3

3

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and extend across the width of the page. There are no margins, text, or other markings on the paper.

Encoding Schemes

- **ASCII:** 7-bit encoding scheme
 - American Standard Code for Information Interchange
- **EBCDIC:** 8-bit encoding scheme
 - Extended Binary-coded Decimal Interchange Code
- **Unicode:** 16-bit encoding scheme
 - The first 128 entries are the same as ASCII

4

4

This image shows a full page of white paper with horizontal grey ruling lines. The lines are evenly spaced and run across the width of the page, providing a template for handwriting practice or general writing. There are no margins, text, or other markings on the page.

Analog vs. Digital

- **Analog Data:** *Continuously* variable level of light, sound, electricity, or other input
- **Digital Data:** *Discretely* variable level of input
- **Analog Transmission:** Utilizes *continuous* changes in voltage or light across a medium to convey data between two or more endpoints
- **Digital Transmission:** Utilizes *discrete* changes in voltage or light across a medium to convey data between two or more endpoints

Other Transmission Characteristics

- **Parallel Transmission** uses multiple parallel data paths to transmit multiple data bits *simultaneously*
- **Serial Transmission** uses one data path, which can only transmit one data bit at a time
- **Asynchronous Transmission** surrounds each data byte with a *start bit* and a *stop bit*, adding considerable overhead
- **Synchronous Transmission** uses occasional *sync bits* to synchronize sender & receiver

Other Transmission Characteristics

- **Simplex Transmission:** Data only travels in one direction; sender and receiver never switch roles
- **Duplex Transmission:** Nodes on the network can transmit data *and* receive data
 - **Half-Duplex Transmission:** A node must either send or receive data, but can not do both at the same time
 - **Full-Duplex Transmission:** Nodes can send and receive *simultaneously*
 - Full-duplex transmission requires more transmission media

Other Transmission Characteristics

- **Guided Media** consists of physical wiring or cabling
 - **Coaxial Cable:** Core conductor surrounded by insulation and grounding mesh
 - **Unshielded Twisted Pair (UTP):** One or more pairs of solid-core copper wire twisted together
 - **Fiber-Optic Cable:** Glass fiber core through which pulses of light pass

Other Transmission Characteristics

- **Unguided Media** uses radio or light waves to transmit data without wires or cabling
 - **Microwave Transmission** uses directionally-focused high-frequency radio waves
 - **Terrestrial Microwave Transmission** requires line-of-sight between sender and receiver
 - **Satellite Microwave Transmission** requires sender and receiver to each have line-of-sight with a satellite in *geosynchronous orbit*
 - **Infrared Transmission** uses light waves just outside the visible spectrum
 - **WiFi, Bluetooth**, etc. use lower-frequency radio waves

Data Transmission Security

- Transmissions must be secure against theft *and* data corruption
- Some transmission protocols employ **error detection** and retransmit corrupt packets
- Other protocols employ **error correction**, avoiding retransmissions
- Many **encryption** schemes exist to secure against data theft

Standards

- **Standards** provide a basic level of compatibility and interoperability among devices and services
- **De facto standards** arise from commonly-accepted practice
- **De jure or formal standards** are developed and published by a standards organization

Standards Organizations

- **ANSI:** Private, non-profit membership organization supported by private-sector and public-sector organizations, to coordinate and administer a *national standards system* in the US. ANSI is a member of ISO. <http://www.ansi.org/>
- **IEEE:** Develops standards in wired and wireless communications and in light & power systems. <http://www.ieee.org/>
- **ITU:** Part of the United Nations that coordinates international communications standards. <http://www.itu.int/>
- **ISO:** Coordinates international standards in a variety of areas (not just telecommunications). <http://www.iso.org/>

Standards Organizations

- **ISOC:** Assures the open development, evolution, and use of the Internet. Founded by **Vinton Cerf**.
- **IETF:** Publishes *RFCs*, written by engineers and computer scientists to invite peer review, or to share information or new ideas
 - **RFC 114:** FTP
 - **RFC 791:** Internet Protocol
 - **RFC 1157:** SNMP
 - **RFC 1945:** HTML
- **IAB:** Oversees technical and engineering development of the Internet; oversees many of ISOC's task forces, such as IETF

13

13

Development of the OSI Model

- **Problem #1:** Early hardware vendors each developed proprietary communication schemes
 - This led to *vendor lock-in* and *vendor lock-out*
 - A non-proprietary architecture was needed for inter-vendor communication

14

14

Development of the OSI Model

- **Problem #2:** Early hardware employed *time-sharing* software in a *mainframe/client* architecture
 - There was only one CPU, in the mainframe, which had to perform all processing and meta-processing
 - Adding users leads to increased processing demands
 - Adding users also leads to increased *meta-processing* demands, such as for communication
 - A *modular* solution was required to split communications processing off from the rest

15

15

Development of the OSI Model

- **ARPA** was experimenting with inter-vendor communications
- They required a *modular* solution so that separate communication processes could be handled separately
- They required a *layered* solution with internal modularity, so that separate protocols could be used on each layer

16

16

Development of the OSI Model

● Solution: The OSI Model

(or the *Open Systems Interconnection Reference Model*)

- Layer 7: **Application** Layer
- Layer 6: **Presentation** Layer
- Layer 5: **Session** Layer
- Layer 4: **Transport** Layer
- Layer 3: **Network** Layer
- Layer 2: **Data Link** Layer
- Layer 1: **Physical** Layer

This image shows a full page of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page, leaving small margins at the top and bottom. There are no vertical margin lines, text, or other markings on the page.

The OSI Model

● **Mnemonics:**

- **Please Do Not Throw Sausage Pizza Away**
(1-7)
- **All People Seem To Need Data Processing**
(7-1)

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There are approximately 20 lines visible. The paper has a slight shadow on its right side, suggesting it's resting on a surface.

The OSI Model

- **Layer 1: The Physical Layer** defines the characteristics of data bit transmission across *specific media*:
 - Type of signaling method -- analog or digital, simplex or duplex, serial or parallel, etc.
 - Electrical/optical characteristics of the transmission signal
 - **Bandwidth** or data rate
 - Network **topology** or layout

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There are approximately 20 lines visible. The paper has a slight shadow on the right side, suggesting it's resting on a surface.

The OSI Model

- **Layer 2: The Data Link Layer** prepares data for the Physical Layer, and provides services to the Network Layer:
 - Organizes data bits received from the Network Layer into **frames**
 - Provides hardware addressing information
 - **MAC** (Media Access Control) addresses uniquely identify each interface
 - Provides for error correction and retransmission

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

The OSI Model

- **Layer 3: The Network Layer** adds *network addressing and routing* information
 - Creates **packets** from information provided by the Transport Layer and provides packet sequencing
 - Performs **route discovery** and determines the best route for packets to travel from one network to another
 - Adds **network address** and **node address** data to each packet
 - **Establishes, maintains, and terminates** end-to-end connections between nodes on separate networks

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and extend across the width of the page. There are no margins, text, or other markings on the paper.

The OSI Model

- **Layer 4: The Transport Layer** provides end-to-end control of data flow
 - Creates **segments** from information provided by the Session Layer and provides segment sequencing
 - Identifies **port numbers** or **service addresses** at destination devices
 - Some layer 4 protocols are **connection-oriented**, meaning the receiving device provides acknowledgement to the sender when segments arrive; protocols which do not do this are **connectionless**

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There are approximately 20 lines visible. The paper has a slight shadow on its right side, suggesting it's resting on a surface.

The OSI Model

- **Layer 5: The Session Layer** establishes, maintains, and terminates communication sessions on a node-to-node level
- **Layer 6: The Presentation Layer** establishes what encoding will be used; it can also provide end-to-end encryption services
- **Layer 7: The Application Layer** provides underlying services that support user applications
 - File, print, & e-mail services
 - Remote access services (ftp, http, etc.)
 - Collaborative computing services (document management, conferencing, etc.)

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There are approximately 20 lines visible. The paper has a slightly textured appearance and is set against a dark background.

The TCP/IP Model

- Developed by:
 - **Vinton Cerf**, then an assistant professor at Stanford
 - **Robert Kahn**, then working for ARPA
- The goal: to have packets traverse multiple networks, without the sender or receiver knowing or even understanding the underlying network structure

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

The TCP/IP Model

- Cerf & Kahn published their work on **TCP** in 1974
- They developed **IP** first as part of TCP, and published it as its own standard in the late 1970s
- TCP/IP was adopted by the US military in 1980; the ARPANET was converted to TCP/IP in 1982

25

25

The TCP/IP Model

- Today, TCP/IP is a set of protocols that are accepted as *de facto* data communication standards
 - Also known as the **Internet Model** or the **DoD Model**
- Described in layers, similar to the OSI Model

26

26

The TCP/IP Model

The OSI Model	The TCP/IP Model
7: Application Layer	4: Process/Application Layer
6: Presentation Layer	
5: Session Layer	
4: Transport Layer	3: Host-to-Host Layer
3: Network Layer	2: Internet Layer
2: Data Link Layer	1: Network
1: Physical Layer	

27

27

Why Are There Two Models?

- Most development regarding data communications compatability follows the TCP/IP model
- However, most development is *described* using the OSI model
- Data *encapsulation* occurs at each layer, as data is sent down to the physical layer and then out to the network

28

28

Honors Received by Cerf & Kahn

- 1997: National Medal of Technology (awarded by Bill Clinton)
- 2004: ACM Turing Award
- 2005: Presidential Medal of Freedom (awarded by G.W. Bush)
- 2006: National Inventors Hall of Fame



29

29

Government Regulations

- **Wireless Ship Act of 1910**
 - *Required* certain seagoing vessels to carry radios for safety
 - One of the first laws passed by the US Congress governing data communications
 - Additional regulations quickly followed

30

30

Government Regulations

- Radio communications came to be regulated by the US Secretary of Commerce and Labor
 - Restricted airwave usage for ship-to-shore distress signals
 - Apportioned specific frequencies to connect coastline islands via wireless to AT&T's network
 - AT&T successfully lobbied to stifle the burgeoning wireless communications industry

31

31

Government Regulations

- **1982 Modified Final Judgment (MFJ)**
 - Settlement agreement from antitrust suit against AT&T
 - AT&T was required to split into separate companies (effective 1984)
 - One long-distance company
 - Several Regional Bell Operating Companies (RBOCs) or "Baby Bells"

32

32

Government Regulations

● 1982 Modified Final Judgment (MFJ)

- The “Baby Bells” included Ameritech, Bell Atlantic (which became Verizon), BellSouth (reacquired by AT&T in 2006), NYNEX, and Southwestern Bell (which became AT&T again in 2002)
- The telecommunications industry was **deregulated**, allowing RBOCs to compete in the telecommunications marketplace *and* in emerging markets like information systems and computing
- Fostered competition between long-distance companies

[illegible]

Government Regulations

● Telecommunications Act of 1996

- Complete *deregulation* of the telecommunications industry
- In theory, anyone who wanted to enter the market could do so (in practice, this required substantial capital)

[illegible]

Government Regulations

● Telecommunications Act of 1996: Good Points

- **Local Competition** required each carrier to interconnect with the others
- **Universal Service** required the FCC to enforce “...the availability of basic communications services to the public at just, reasonable, and affordable rates... taking into account advances in telecommunications technologies”

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There are approximately 20 lines visible. The paper has a slight shadow on the right side, suggesting it's resting on a surface.

Government Regulations

- **Telecommunications Act of 1996: Good Points**

- **E-Rate** required Universal Service, at subsidized rates, to schools, libraries, and rural health-care providers
- **Broadband Facilities** gave the FCC the power to induce deployment of high-speed Internet access, such as DSL and cable modems

[illegible]

Government Regulations

● Telecommunications Act of 1996: Bad Points

- Most media ownership regulations were eliminated
 - Number of major media companies in the US:
 - 1983: Around 50
 - 1996: 10
 - 2005: 6

37

37

This image shows a full page of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page, leaving small margins at the top and bottom. There are no vertical margin lines, text, or other markings on the page.

Government Regulations

- **Telecommunications Act of 1996: Bad Points**

- Most media ownership regulations were eliminated
 - 1996 to 2003: 5.9% increase in amount of commercial radio stations
 - Largest owner owned 60+ stations
 - 1996 to 2003: 35% decrease in amount of station owners
 - Largest owner owned 1200+ stations

38

38

[illegible]

Government Regulations

- **Telecommunications Act of 1996: Bad Points**

- Title V: **Communications Decency Act**

- First attempt by US Congress to regulate pornographic material on the Internet
- Imposed *criminal sanctions* on anyone who sends or makes available “...any comment, request, suggestion, proposal, image, or other communication that, in context, depicts or describes, in terms **patently offensive as measured by contemporary community standards**, sexual or excretory activities or organs” to minors

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and extend across the width of the page. There are no margins, text, or other markings on the paper.

Government Regulations

- **Telecommunications Act of 1996: Bad Points**

- Title V: **Communications Decency Act**

- Much of the Act was deemed unconstitutional in *Reno vs. ACLU*
- “Good Samaritan” provision protects ISPs from liability regarding information published by their clients
 - This is still in effect

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There are approximately 20 lines visible. The paper has a slight shadow on its right side, suggesting it's resting on a surface.