

Generate FOCUS-compliant cost report

Shows how to generate and download a cost report in FOCUS format using the Redis Cloud REST API.

Redis Cloud

This is a snapshot of the Redis Docs from July 13, 2026.

See <https://redis.io/docs/latest/operate/rc/api/examples/generate-cost-report/> for the current version.

You can use the Redis Cloud REST API to generate and download a cost report in a FinOps Open Cost and Usage Specification (FOCUS) compatible format. The report includes detailed information about your Redis Cloud subscription usage and associated charges.

To get the cost report using the REST API:

1. Use `POST /cost-report` to generate a cost report, with the request body containing the `startDate` and `endDate` for the report as well as any optional filters. Your account must have the **Owner**, **Viewer**, or **Billing admin** role to generate a cost report through this endpoint.
The response includes a `taskId` that you can use to track the status of the report generation.
2. Use `GET /tasks/{taskId}` to check report generation status. The report is ready when the status is `processing-completed` and the response field contains a `costReportId`.
3. Use `GET /cost-report/{costReportId}` to download the generated cost report.

The following sections provide examples for each step.

Generate a cost report

To generate a cost report, use `POST /cost-report`. Your account must have the **Owner**, **Billing admin**, or **Viewer** role to generate a cost report through this endpoint.

Include `startDate` and `endDate` in your request body using `YYYY-MM-DD` format. You can specify a date range up to 40 days.

```
{
  "startDate": "2025-01-01",
  "endDate": "2025-01-31"
}
```

More options and filters can be added to the request body to filter the report data.

Option name	Type	Description
format	Enum: csv, json	The format for the report file. Default is csv.
subscriptionIds	Array of integers	Filters the report to only include the specified subscriptions.
databaseIds	Array of integers	Filters the report to only include the specified databases.
subscriptionType	Enum: essentials, pro	Filters the report to only include subscriptions of the specified type.
regions	Array of strings	Filters the report to only include subscriptions in the specified regions.
tags	Array of key-value pairs	Filters the report to only include databases with the specified <u>tags</u> . Both key and value are required for each tag.

For example, the following request body generates a CSV report for all databases in the `us-east-1` region that have the `team:marketing` tag in January 2025:

```
{
  "startDate": "2025-01-01",
  "endDate": "2025-01-31",
  "format": "csv",
  "regions": ["us-east-1"],
}
```

```

"tags": [
  {
    "key": "team",
    "value": "marketing"
  }
]
}

```

The response body is a task object that contains the taskId for the task that generates the cost report:

```

{
  "taskId": "7ba51acc-cd1d-44c7-8453-281730d214ce",
  "commandType": "costReportCreateRequest",
  "status": "received",
  "description": "Task request received and is being queued for processing",
  "timestamp": "2025-11-07T15:44:29.811142433Z",
  "links": [
    {
      "href": "https://api.redislabs.com/v1/tasks/7ba51acc-cd1d-44c7-8453-281730d214ce",
      "type": "GET",
      "rel": "task"
    }
  ]
}

```

Get cost report status

To get the status of the cost report generation, use GET /tasks/{taskId} with the taskId from the previous step.

When the report is ready, the status is processing-completed and the response field contains a costReportId:

```

{

```

```
"taskId": "7ba51acc-cd1d-44c7-8453-281730d214ce",
"commandType": "costReportCreateRequest",
"status": "processing-completed",
"description": "Request processing completed successfully and its resource is ready for use.",
"timestamp": "2025-11-07T15:44:31.168900133Z",
"response": {
  "resource": {
    "costReportId": "a07524cf-6d4d-47ec-a1b7-810d1cbafcf7.json"
  }
},
"links": [
  {
    "href": "https://api.redislabs.com/v1/tasks/7ba51acc-cd1d-44c7-8453-281730d214ce",
    "type": "GET",
    "rel": "self"
  }
]
}
```

Download cost report

To get the cost report, use `GET /cost-report/{costReportId}` with the `costReportId` from the previous step.

You can use this cost report with any FOCUS-compatible cost reporting tool to analyze and visualize your costs.

Cost report fields

The cost report returned from the Redis Cloud REST API contains fields from the [FOCUS column library](#). The Redis Cloud-specific implementation is described in the following sections.

Billing account and publisher fields

Field	Type	Description
BillingAccountId	String	Redis Cloud account ID.
BillingAccountName	String	Display name of the Redis Cloud account.
BillingAccountType	String	Type of billing account structure. Always set to Redis Cloud.
PublisherName	String	Publisher/vendor of the service, which is Redis. Always redis.io.

Pricing fields

Field	Type	Description
PricingCategory	String	Pricing model category. Always Standard.
PricingCurrency	String	The currency used for pricing. Always USD.
PricingQuantity	BigDecimal	Quantity of units being priced. For hourly services like Redis Cloud Pro, this is the number of hours. For monthly services like Redis Cloud Essentials and network costs, this is typically one month.
PricingUnit	String	The unit of measure for pricing. Can be Hours (Pro), Months (Essentials), or Network.

Period fields

Field	Type	Description
BillingPeriodStart	Instant (ISO 8601 DateTime)	Start of the billing period (inclusive).
BillingPeriodEnd	Instant (ISO 8601 DateTime)	End of the billing period (exclusive).
ChargePeriodStart	Instant (ISO 8601 DateTime)	Start of the specific charge period (inclusive). May differ from billing period if the resource was created mid-period.
ChargePeriodEnd	Instant (ISO 8601 DateTime)	End of the specific charge period (exclusive). May differ from billing period if the resource was deleted mid-period.

Cost fields

Field	Type	Description
BilledCost	BigDecimal	Cost that Redis will invoice you for.
BillingCurrency	String (ISO 4217)	Currency code for all billing amounts. Always USD.
ConsumedQuantity	BigDecimal	Actual amount of resources used. May be null for fixed-price plans.
ConsumedUnit	String	Unit for ConsumedQuantity. Can be Hours or Network.
ContractedCost	BigDecimal	Cost after applying contractual discounts but before credits.
ContractedUnitPrice	BigDecimal	Per-unit price after applying your negotiated discounts.
EffectiveCost	BigDecimal	True cost after all discounts, credits, and adjustments.
ListCost	BigDecimal	Cost at Redis's published list prices before any discounts.
ListUnitPrice	BigDecimal	Redis's published price per unit at list rates.

Location, Resource, and SKU fields

Field	Type	Description
RegionId	String	Cloud vendor region identifier.
RegionName	String	Display name of the region.
ResourceId	String	Identifier of the resource being charged.
ResourceName	String	Display name you gave to the resource in the Redis Cloud console.
ResourceType	String	Whether the charge is for a specific database or a subscription-level service.

Tags	JSON Map<String, String>	User-defined tags on resources.
SkuPriceDetails	JSON Map<String, Object>	Redis-specific technical details about the database configuration, such as RBUs, memory limit, and throughput.

Charge fields

Field	Type	Description
ChargeCategory	String	Category of the charge: Usage, Purchase, Tax, or Adjustment.
ChargeDescription	String	A clear description of what you're being charged for, combining service type and resource details.
ChargeFrequency	String	How often the charge occurs - always Recurring.

Service fields

Field	Type	Description
ServiceCategory	String	The high-level category of service - always Databases.
ServiceName	String	The Redis Cloud service tier - Redis Cloud Pro or Redis Cloud Essentials.
ServiceSubcategory	String	The specific type of database service - always Caching.

RATE THIS PAGE



[Back to top](#) ↑