
SOCBYTE
ALL BYTES SECURED

INTEL REPORT



Report Details

Title	Prophet Spider | Threat Hunt
Sub Title	Financially motivated eCrime group active since at least 2017
Status	Closed
Type	Alert
Severity	High
Source	Multiple Sources
Created At	Sep 22, 2026, 08:35 PM

Prophet Spider | Threat Hunt

Financially motivated eCrime group active since at least 2017

Type: ALERT • Source: Multiple Sources • Created At: Sep 22, 2026, 08:35 PM

Analysis Summary

On September 22nd at 7:30 P.M., Cythority's vSOC conducted a threat hunt focused on Prophet Spider covering activity within the past 30 days.Prophet Spider is an opportunistic, financially motivated eCrime group active since at least 2017 that functions primarily as an Initial Access Broker (IAB) within the ransomware supply chain. Rather than executing full-chain ransomware deployment themselves, the threat actor specializes in gaining an initial foothold in corporate networks and subsequently selling or handing off that access to ransomware affiliates (such as Conti, Ryuk, or BlackCat/ALPHV) for monetization. Their tactics rely heavily on compromising vulnerable, internet-facing web servers and applications, frequently exploiting public-facing CVEs in platforms like Oracle WebLogic, Apache Tomcat, and Citrix ShareFile. Once inside, Prophet Spider deploys web shells for persistence, leverages native system utilities (LOLBins) like PowerShell (Invoke-WebRequest, DownloadString) and nslookup for quiet staging and C2 resolution, and uses tools such as Mimikatz or Cobalt Strike for credential dumping and lateral movement before turning the access over to secondary payload operators.

Because Prophet Spider operates primarily as a stealthy Initial Access Broker (IAB), public threat intelligence reports rarely attribute real-time Indicators of Compromise (IP addresses, domain hashes, file hashes) directly to the group within a strict 30-day window. Their infrastructure and staging IPs shift rapidly per targeted campaign to evade static blocklists.They are more known to use the latest CVEs to target companies and exploit those to gain initial access, then sell that access to other adversaries.

During this hunt, a total of 21 Indicators of Compromise (IOCs) were identified, including IP addresses, and file hash values. These indicators were aggregated from CrowdStrike, internal telemetry, and additional

intelligence sources referenced in this report. All identified IOCs were enriched using OSINT and threat intelligence platforms to validate their reputation. Analysis confirmed that the indicators are associated with malicious activity.

A CQL Advanced Event Search was conducted across the environment to identify any evidence of activity related to these indicators. No matches or suspicious activity were observed, confirming no current or historical presence within the environment. As a preventative measure, the validated malicious IOCs have been added to the IOC Management Block List to mitigate potential future exposure. This proactive control strengthens the security posture and reduces the attack surface. Based on the investigation and analysis performed, no impact to the environment has been identified and no further action is required at this time.

Affected Product

- Oracle WebLogic Server
- VMware Horizon
- Citrix ShareFile Storage Zones Controller
- Microsoft Internet Information Services (IIS)
- Apache Tomcat & Apache Log4j

Impact

- Initial network compromise / loss of confidentiality & integrity
- Credential theft and lateral movement
- Ransomware deployment (downstream/financial impact)
- Data exfiltration and reputational/legal impact

Indicators of Compromise (IOCs)

IP
194.5.82[.]11
138.199.21[.]243
194.114.136[.]95
149.28.193[.]216
149.28.207[.]120
195.123.240[.]183
64.190.113[.]185
195.123.240[.]233
67.43.234[.]96
213.252.232[.]237
98.159.108[.]69
190.211.254[.]95
109.176.229[.]89
169.150.198[.]91

MD5 Hashes

- c6c1c3d7e25327a6d46039aa837491e5
- 8addc16baeb0474d41ba2d3805665969

SHA256 Hashes

- a3d5ead160614336a013f5de4cff65a5198b1d73238a5b456f558e70b503f52e
- 2b03806939d1171f063ba8d14c3b10622edb5732e4f78dc4fe3eac98b56e5d46
- bb86dcfb6bca5fba8ab92d7a4ded9599baab400804c5fe5fb37aaef75f15e0ac
- D4bfaf3fd3d3b670f585114b4619aaf9b10173c5b1e92d42be0611b6a9b1eff2
- 52a72f899991506d2b1df958dd8736f7baa26592d664b771c3c3dbaef8d3114a

Remediation

• Patch internet-facing systems, especially Oracle WebLogic

• Reduce exposure, minimize/inventory public-facing web servers and apps

• Detect web shells and file integrity monitoring on web directories

• Monitor for anomalous activity, unusual Invoke-WebRequest/wget usage, Cobalt Strike beacon signatures, and lateral movement

• Deploy EDR on servers, not just endpoints

• If compromised: isolate the host, hunt for web shells network-wide, rotate credentials, and check for data staging (pre-ransomware indicator)