

DistAlgo is a high-level language for writing distributed algorithms, such that they serve as both clear specifications and runnable implementations of those algorithms. This document provides a brief, practical introduction to the major features of the language using several iterations of a familiar example.

DistAlgo is currently implemented as an extension of the Python language, and requires Python 3.4 or higher. This tutorial assumes some familiarity with Object-Oriented programming in general, and with Python, in particular.

Let's begin with the simplest possible version of "Hello World" written in DistAlgo.

```
1  def main():
2      print('Hello World.')
```

Listing 1: hello_world01.da - Main Function Definition

Every DistAlgo program must have a main function. In this case, the body of `main` merely contains a call to Python's `print` function, to output "Hello World" to standard output. As we will see in the next example, the intended use of the main function in a DistAlgo program is to create, prepare, and then begin the execution of the distinct processes that participate in the distributed algorithm.

In the second version of "Hello World" we can see how process definition and creation works in a DistAlgo program.

```
1  class P (process):
2      def setup(name):
3          pass
4
5      def run():
6          output('Hello World from:', self.name, ', AKA:', self.id)
7
8  def main():
9      ps = new(P)
10     setup(ps, ('bob',))
11     start(ps)
```

Listing 2: hello_world02.da - Process Definition

Distributed algorithms are constituted by the interaction of multiple, distinct processes. DistAlgo is intended for the implementation of distributed algorithms. To that end, DistAlgo makes it easy to define new process types that will execute the behavior required by the algorithm.

Every user defined process type in DistAlgo is an extension of the base class `process`. In the second version of "Hello World" we define a class called `P`, which extends `process`. In order to properly define a new type of DistAlgo process, the user must define two functions: `setup` and `run`.

The `setup` method is used to declare and initialize any instance variables of the user's new process class. Any parameters of the `setup` method are implicitly declared as instance variables and initialized with the value passed as the argument to the parameter. In the second example, `setup` has one parameter `name`, which is initialized with the value `'bob'`. In addition, every instance of a distalgo process has a unique identifier stored in an instance variable, `self.id`, which is the pair of the IP address and the port number upon which the process instance is listening.

The `run` method of a DistAlgo process contains the definition of the behavior of the process. For the example in listing 2, the process merely prints a "Hello World" message, identifying itself using both the name we supplied as an argument and its unique id.

In this second example we can also see a proper use of the `main` method of a DistAlgo program. Here we have calls to three Distalgo methods: `new`, `setup`, and `start`.

The `new` method is used to instantiate a set of DistAlgo process instances. We supply the classname of the process class we wish to instantiate, `P`, as an argument, and `new` returns a set of references to the new process instances. In this case we store the set in the variable `ps`. If the class name is the only argument, then `new` creates just one instance of that process class. However, even if `new` is used to create just once process instance, the returned value is still a set—in this case a singleton set—containing a reference to that process instance.

The `setup` method is used to initialize our new process instances. The first argument is a set of process instance references. The second argument is a tuple of arguments to be passed to the parameters of the `setup` method defined for the process class corresponding to the class of the process instances one is trying to initialize. Note, even if there is only one argument passed to the `setup` method of the process class, it must still be packaged within a singleton tuple.

Finally, we can begin the execution of the process instances by passing a set of references to those process instances to the `start` method. The call to `start` will cause the `run` method defined within the corresponding process class to begin executing at each process instance included in the call to `start`.

In the third example, we can see how multiple process instances are created.

```
1  class P (process):
2      def setup(name):
3          pass
4
5      def run():
6          output('Hello World from:', name, ', AKA:', self.id)
7
8  def main():
9      num_processes = 2
10     ps = new(P, num = num_processes)
11     setup(ps, ('bob', ))
12     start(ps)
```

Listing 3: hello_world03.da - Multiple Process Instances

You can run this program from the command line by entering: “python3 -m da hello_world3.da”.

This program is very similar to “hello_world2.da”. In fact, the definition of the process class, `P`, is identical to the one given in the previous example. There are just two changes in `main`. First, we add a new variable, `num_processes`, which is initialized to 2. Second, we pass this new variable as the argument to the `num` parameter of the `new` method, resulting in the instantiation of two process instances of the process class, `P`. These two instances are both initialized by the call to `setup`, and then set running by the call to `start`.

The instantiation and execution of the two process instances can be observed in the output when the program is run. There will be two “Hello World” outputs, each with a distinct value for `self.id`, though both will claim that their name is ‘bob’, since they are both initialized with the same parameter. You should think about how you might initialize the `name` fields of these two process instances with distinct values.

This latest version of hello_world features two DistAlgo process instances, but they do not interact with or even refer to each other. Distributed algorithms are intended to feature this sort of interplay between distinct processes, so let’s add some in the next example.

Here is the fourth example:

```
1 class P (process):
2     def setup(processes):
3         pass
4
5     def run():
6         for p in processes:
7             output(self.id, 'says Hello to: ', p)
8
9 def main():
10     num_processes = 2
11     ps = new(P, num = num_processes)
12     setup(ps, (ps,))
13     start(ps)
```

Listing 4: hello_world04.da - Multiple Processes Referring to Each Other

You can run this program from the command line by entering: “python3 -m da hello_world04.da”. There are several changes to the program. First, we have altered the definition of the **setup** method so that it accepts parameter, **processes**, which will hold a set of references to DistAlgo process instances. Next, we have altered the **run** method of **P** so that instead of greeting the entire world, it instead loops over all the process instances in **processes** and sends each of them an individualized greeting, `jprocess idj` says Hello to `jprocess idj`.

Within the main method we generate two distinct process instances of type **P**, and store the set of their references in `textttps`. We then initialize both instances passing that same set of references to **setup** to serve as the argument to `textttprocesses`. Finally, we start those process instances running as before.

If you run the program then you will see that in the output there are four “X say Hello to Y”. If we label the two process instances, *p1* and *p2*, then the four greetings have the following forms: i) “p1 says Hello to p1”; ii) “p1 says Hello to p2”; iii) “p2 says Hello to p1”; iv) “p2 says Hello to p2”, in some arbitrary order. But, we probably did not intend to have the processes greeting themselves. So what went wrong?

The problem occurs on line 12. We passed the entire set `ps` to the **processes** parameter of **P** for each process instance, but there is a reference to that process instance in the set `ps`. So, each ends up with a **processes** set that contains a reference to itself. How can we avoid this?

It turns out there is a common pattern present in many DistAlgo examples that allows one to initialize a process with a set of references to other process instances, but exclude a reference to the process instance one is attempting to initialize. It is illustrated in Example 6:

```
1 class P (process):
2     def setup(processes):
3         pass
4
5     def run():
6         for p in processes:
7             output(self.id, 'says Hello to: ', p)
8
9 def main():
10     num_processes = 2
11     ps = new(P, num = num_processes)
12     for p in ps:
```

```
13 |         setup(p, (ps - {p}, ))
14 |         start(ps)
```

Listing 5: hello_world06.da - Excluding Self-References, the Nice Way

The only difference between Example 6 and Example 4 occurs inside the call to the `setup` method within `main`. We initialize each of the process instances one at a time within a loop. For each process instance, instead of passing the entire set `ps` to the `processes` parameter of `P`, we instead pass the set produced taking the difference of `ps` with a singleton set that contains a reference to the process instance being initialized. Thus, each process instance is set up with a set of references to every other process instance in `ps`.

If you run Example 6 by entering “python3 -m da hello_world06.da”, then you will see that there now only two outputs. *p1* greets *p2*, and *p2* greets *p1*. All is once again right with the world. Each process instance greets the other