

Git

Git is a fast distributed revision control system.

<https://www.linux.com/learn/beginning-git-and-github-linux-users>

<http://rogerdudler.github.io/git-guide/>

Repositories and Branches

How to get a Git repository

```
# Git itself (approx. 40MB download):
$ git clone git://git.kernel.org/pub/scm/git/git.git
# the Linux kernel (approx. 640MB download):
$ git clone git://git.kernel.org/pub/scm/linux/kernel/git/torvalds/linux.git
```

The clone command creates a new directory named after the project (git or linux in the examples above). After you cd into this directory, you will see that it contains a copy of the project files, called the [working tree](#), together with a special top-level directory named `.git`, which contains all the information about the history of the project.

[Carla Schroder](#)

November 20, 2014

Beginning Git and Github for Linux Users

The screenshot shows a GitHub repository page for 'AlracWebmaven / playground'. The repository is described as 'test repo for learning git and github'. It has 1 commit, 1 branch, 0 releases, and 1 contributor. The 'master' branch is selected. The repository contains an 'Initial commit' by 'AlracWebmaven' 4 minutes ago, with the latest commit hash '4c1ac6d5ce'. The commit includes a 'LICENSE' and a 'README.md' file. The 'README.md' file content is visible, showing the title 'playground' and the description 'test repo for learning git and github'. On the right side, there are links for 'Code', 'Issues', 'Pull Requests', 'Wiki', 'Pulse', 'Graphs', and 'Settings'. The 'HTTPS clone URL' is 'https://github.com/AlracWebmaven/playground.git'. There are also buttons for 'Download ZIP' and 'Unwatch', 'Star', and 'Fork'.

The Git distributed revision control system is a sweet step up from Subversion, CVS, Mercurial, and all those others we've tried and made do with. It's great for distributed development, when you have multiple contributors working on the same project, and it is excellent for safely trying out all

kinds of crazy changes. We're going to use a free Github account for practice so we can jump right in and start doing stuff.

Conceptually Git is different from other revision control systems. Older RCS tracked changes to files, which you can see when you poke around in their configuration files. Git's approach is more like filesystem snapshots, where each commit or saved state is a complete snapshot rather than a file full of diffs. Git is space-efficient because it stores only changes in each snapshot, and links to unchanged files. All changes are checksummed, so you are assured of data integrity, and always being able to reverse changes.

Git is very fast, because your work is all done on your local PC and then pushed to a remote repository. This makes everything you do totally safe, because nothing affects the remote repo until you push changes to it. And even then you have one more failsafe: branches. Git's branching system is brilliant. Create a branch from your master branch, perform all manner of awful experiments, and then nuke it or push it upstream. When it's upstream other contributors can work on it, or you can create a pull request to have it reviewed, and then after it passes muster merge it into the master branch.

So what if, after all this caution, it still blows up the master branch? No worries, because you can revert your merge.

Practice on Github

The quickest way to get some good hands-on Git practice is by opening a free Github account. Figure 1 shows my Github testbed, named *playground*. New Github accounts come with a prefab repo populated by a README file, license, and buttons for quickly creating bug reports, pull requests, Wikis, and other useful features.

Free Github accounts only allow public repositories. This allows anyone to see and download your files. However, no one can make commits unless they have a Github account and you have approved them as a collaborator. If you want a private repo hidden from the world you need a [paid membership](#). Seven bucks a month gives you five private repos, and unlimited public repos with unlimited contributors.

Github kindly provides copy-and-paste URLs for cloning repositories. So you can create a directory on your computer for your repository, and then clone into it:

```
$ mkdir git-repos
$ cd git-repos
$ git clone https://github.com/AlracWebmaven/playground.git
Cloning into 'playground'...
remote: Counting objects: 4, done.
remote: Compressing objects: 100% (4/4), done.
remote: Total 4 (delta 0), reused 0 (delta 0)
Unpacking objects: 100% (4/4), done.
Checking connectivity... done.
$ ls playground/
LICENSE  README.md
```

All the files are copied to your computer, and you can read, edit, and delete them just like any other file. Let's improve README.md and learn the wonderfulness of Git branching.

Branching

Git branches are gloriously excellent for safely making and testing changes. You can create and destroy them all you want. Let's make one for editing README.md:

```
$ cd playground
$ git checkout -b test
Switched to a new branch 'test'
```

Run `git status` to see where you are:

```
$ git status
On branch test
nothing to commit, working directory clean
```

What branches have you created?

```
$ git branch
* test
  master
```

The asterisk indicates which branch you are on. `master` is your main branch, the one you never want to make any changes to until they have been tested in a branch. Now make some changes to README.md, and then check your status again:

```
$ git status
On branch test
Changes not staged for commit:
  (use "git add ..." to update what will be committed)
  (use "git checkout -- ..." to discard changes in working directory)
        modified:   README.md
no changes added to commit (use "git add" and/or "git commit -a")
```

Isn't that nice, Git tells you what is going on, and gives hints. To discard your changes, run

```
$ git checkout README.md
```

Or you can delete the whole branch:

```
$ git checkout master
$ git branch -D test
```

Or you can have Git track the file:

```
$ git add README.md
$ git status
On branch test
Changes to be committed:
  (use "git reset HEAD ..." to unstage)
        modified:   README.md
```

At this stage Git is tracking README.md, and it is available to all of your branches. Git gives you a helpful hint-- if you change your mind and don't want Git to track this file, run `git reset HEAD README.md`. This, and all Git activity, is tracked in the `.git` directory in your repository. Everything is in plain text files: files, checksums, which user did what, remote and local repos-- everything.

What if you have multiple files to add? You can list each one, for example `git add file1 file2 file2`, or add all files with `git add *`.

When there are deleted files, you can use `git rm filename`, which only un-stages them from Git and does not delete them from your system. If you have a lot of deleted files, use `git add -u`.

Committing Files

Now let's commit our changed file. This adds it to our branch and it is no longer available to other branches:

```
$ git commit README.md
[test 5badf67] changes to readme
1 file changed, 1 insertion(+)
```

You'll be asked to supply a commit message. It is a good practice to make your commit messages detailed and specific, but for now we're not going to be too fussy. Now your edited file has been committed to the branch `test`. It has not been merged with master or pushed upstream; it's just sitting there. This is a good stopping point if you need to go do something else.

What if you have multiple files to commit? You can commit specific files, or all available files:

```
$ git commit file1 file2
$ git commit -a
```

How do you know which commits have not yet been pushed upstream, but are still sitting in branches? `git status` won't tell you, so use this command:

```
$ git log --branches --not --remotes
commit 5badf677c55d0c53ca13d9753344a2a71de03199
Author: Carla Schroder
Date: Thu Nov 20 10:19:38 2014 -0800
    changes to readme
```

This lists un-merged commits, and when it returns nothing then all commits have been pushed upstream. Now let's push this commit upstream:

```
$ git push origin test
Counting objects: 7, done.
Delta compression using up to 8 threads.
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 324 bytes | 0 bytes/s, done.
Total 3 (delta 1), reused 0 (delta 0)
To https://github.com/AlracWebmaven/playground.git
 * [new branch]      test -> test
```

You may be asked for your Github login credentials. Git caches them for 15 minutes, and you can change this. This example sets the cache at two hours:

```
$ git config --global credential.helper 'cache --timeout=7200'
```

Now go to Github and look at your new branch. Github lists all of your branches, and you can preview your files in the different branches (figure 2).

