```
--
================================================================================
======
-- Meowdox Integrated Hub (ESP, Silent Aim, UI, Infinite Soru)
-- All Sources Are Public & Free - https://discord.gg/cSthtkp5dD
--
================================================================================
======

local Players = game:GetService("Players")
local RunService = game:GetService("RunService")
local UserInputService = game:GetService("UserInputService")
local TweenService = game:GetService("TweenService")
local ReplicatedStorage = game:GetService("ReplicatedStorage")
local LocalPlayer = Players.LocalPlayer
local Camera = workspace.CurrentCamera

-- ========================================
-- 1. ESP CONFIGURATION & MODULE
-- ========================================

_G.G_ESPEnabled        = false
_G.G_ESP_Name          = true
_G.G_ESP_Level         = true
_G.G_ESP_Bounty        = true
_G.G_ESP_Fruit         = true
_G.G_ESP_Distance      = true
_G.G_ESP_HP            = true
_G.G_ESP_TextSize      = 14
_G.G_ESP_Highlight     = false
_G.G_ESP_HighlightColor = "FF0000"

local ESPRunning = false
local espObjects = {}
local espUpdateConnection = nil
local lastESPUpdate = 0
local ESP_UPDATE_INTERVAL = 0.1
local playerCache = {}

local function getTeamInfo(player)
    if not player.Team then
        return "Unknown", Color3.fromRGB(255, 255, 255)
    end
    if player.Team.Name == "Marines" then
        return "Marines", Color3.fromRGB(0, 170, 255)
    else
        return "Pirates", Color3.fromRGB(255, 70, 70)
    end
```

```
end

local function hexToColor3(hex)
    local r = tonumber(hex:sub(1, 2), 16) / 255 or 0
    local g = tonumber(hex:sub(3, 4), 16) / 255 or 1
    local b = tonumber(hex:sub(5, 6), 16) / 255 or 0
    return Color3.new(r, g, b)
end

local function removeESP(player)
    if espObjects[player] then
        pcall(function()
            espObjects[player].gui:Destroy()
            if espObjects[player].highlight then
                espObjects[player].highlight:Destroy()
            end
        end)
        espObjects[player] = nil
    end
end

local function createESP(player)
    if player:GetAttribute("IsAuthor") or
       player.Name == "Mas_Yes" or
       player.Name == "sjqgduf" or
       player.Name == "huha123444" or
       player.Name == "ksxrcm111" or
       player.Name == "Dddyy5" then
        return
    end
    if player == LocalPlayer then return end
    local char = player.Character
    if not char then return end
    local head = char:FindFirstChild("Head")
    if not head then return end
    local team, color = getTeamInfo(player)
    local billboard = Instance.new("BillboardGui")
    billboard.Adornee = head
    billboard.Size = UDim2.new(0, 200, 0, 70)
    billboard.StudsOffset = Vector3.new(0, 3, 0)
    billboard.AlwaysOnTop = true

    local text = Instance.new("TextLabel")
    text.Size = UDim2.new(1, 0, 1, 0)
    text.BackgroundTransparency = 1
    text.TextScaled = false
    text.TextSize = _G.G_ESP_TextSize
    text.RichText = true
```

```
    text.Font = Enum.Font.SourceSansBold
    text.TextStrokeTransparency = 0
    text.TextColor3 = color
    text.Parent = billboard
    billboard.Parent = head

    local highlight = nil
    if _G.G_ESP_Highlight then
        local hlColor = hexToColor3(_G.G_ESP_HighlightColor)
        highlight = Instance.new("Highlight")
        highlight.Name = "ESP_PlayerHighlight"
        highlight.DepthMode = Enum.HighlightDepthMode.AlwaysOnTop
        highlight.FillColor = hlColor
        highlight.FillTransparency = 0.5
        highlight.OutlineColor = hlColor
        highlight.OutlineTransparency = 0
        highlight.Parent = char
    end

    espObjects[player] = {
        gui = billboard,
        label = text,
        char = char,
        highlight = highlight
    }
end

local function getPlayerData(player)
    if not playerCache[player] then
        playerCache[player] = {
            level = "?",
            fruit = "None",
            bounty = 0,
            team = "Unknown",
            color = Color3.fromRGB(255, 255, 255),
            lastUpdate = 0
        }
    end
    local data = playerCache[player]
    local now = tick()
    if now - data.lastUpdate > 5 then
        pcall(function() data.level = player.Data.Level.Value end)
        pcall(function() data.fruit = player.Data.DevilFruit.Value end)
        pcall(function() data.bounty = player.leaderstats["Bounty/Honor"].Value end)
        data.team, data.color = getTeamInfo(player)
        data.lastUpdate = now
    end
    return data
```

```
end

local function updateESP()
    local now = tick()
    if now - lastESPUpdate < ESP_UPDATE_INTERVAL then return end
    lastESPUpdate = now
    local myChar = LocalPlayer.Character
    local myRoot = myChar and myChar:FindFirstChild("HumanoidRootPart")
    if not myRoot then return end
    local myPos = myRoot.Position

    for _, player in ipairs(Players:GetPlayers()) do
        if player ~= LocalPlayer then
            if player:GetAttribute("IsAuthor") or
               player.Name == "Mas_Yes" or
               player.Name == "sjqgdu6" or
               player.Name == "huha124444" or
               player.Name == "ksxrcn111" or
               player.Name == "Dddyy5" then
                if espObjects[player] then
                    removeESP(player)
                end
                continue
            end
            local char = player.Character
            local head = char and char:FindFirstChild("Head")
            local data = espObjects[player]
            if char and head then
                if not data or data.char ~= char or not data.gui.Parent then
                    removeESP(player)
                    createESP(player)
                    data = espObjects[player]
                end
            else
                if data then
                    removeESP(player)
                end
                continue
            end
            if not data then continue end
            if char then
                local hum = char:FindFirstChild("Humanoid")
                local root = char:FindFirstChild("HumanoidRootPart")
                if hum and root then
                    local distance = math.floor((root.Position - myPos).Magnitude)
                    local hp = math.floor((hum.Health / hum.MaxHealth) * 100)
                    local pData = getPlayerData(player)
                    local level = pData.level
```

```
                local fruit = pData.fruit
                local bounty = pData.bounty
                local team = pData.team
                local color = pData.color
                local warnTag = bounty > 10000000 and "⚠ " or ""
                local pvpState = "PVP Enabled "
                local pvpIcon = "🔴 "
                local isPvpDisabled = false

                if player:GetAttribute("PvpDisabled") == true then
                    pvpState = "PvP Disabled "
                    pvpIcon = "🟢 "
                    isPvpDisabled = true
                end

                data.label.TextColor3 = color
                if data.label.TextSize ~= _G.G_ESP_TextSize then
                    data.label.TextSize = _G.G_ESP_TextSize
                end

                local parts = {}
                if _G.G_ESP_Name then parts[#parts + 1] = warnTag .. "[" .. team .. "] <font
color=\"rgb(255,255,0)\">" .. player.Name .. "</font>" end
                if _G.G_ESP_Level then parts[#parts + 1] = " [Lv." .. level .. "]" end
                if isPvpDisabled then
                    parts[#parts + 1] = "\n<font color=\"rgb(0,255,0)\">" .. pvpIcon .. pvpState ..
"</font>\n"
                else
                    parts[#parts + 1] = "\n" .. pvpIcon .. pvpState .. "\n"
                end
                if _G.G_ESP_Fruit then parts[#parts + 1] = "Fruit: " .. fruit .. "\n" end
                if _G.G_ESP_Bounty then parts[#parts + 1] = "Bounty: " .. math.floor(bounty /
1000000) .. "M\n" end
                if _G.G_ESP_Distance then parts[#parts + 1] = distance .. "m | " end
                if _G.G_ESP_HP then parts[#parts + 1] = "HP " .. hp .. "%" end
                data.label.Text = table.concat(parts)

                if _G.G_ESP_Highlight then
                    local hlColor = hexToColor3(_G.G_ESP_HighlightColor)
                    pcall(function()
                        for _, child in ipairs(char:GetChildren()) do
                            if child:IsA("Highlight") and child.Name ~= "ESP_PlayerHighlight" then
                                child.FillColor = hlColor
                                child.OutlineColor = hlColor
                                child.DepthMode = Enum.HighlightDepthMode.AlwaysOnTop
                            end
                        end
                    end)
```

```
                if not data.highlight or not data.highlight.Parent then
                    local hl = Instance.new("Highlight")
                    hl.Name = "ESP_PlayerHighlight"
                    hl.DepthMode = Enum.HighlightDepthMode.AlwaysOnTop
                    hl.FillColor = hlColor
                    hl.FillTransparency = 0.5
                    hl.OutlineColor = hlColor
                    hl.OutlineTransparency = 0
                    hl.Parent = char
                    data.highlight = hl
                else
                    data.highlight.FillColor = hlColor
                    data.highlight.OutlineColor = hlColor
                    data.highlight.DepthMode = Enum.HighlightDepthMode.AlwaysOnTop
                end
            else
                if data.highlight then
                    data.highlight:Destroy()
                    data.highlight = nil
                end
            end
        end
    end
end

local function EnableESP()
    if ESPRunning then return end
    ESPRunning = true
    for _, player in ipairs(Players:GetPlayers()) do
        createESP(player)
    end
    espUpdateConnection = task.spawn(function()
        while ESPRunning do
            pcall(updateESP)
            task.wait(ESP_UPDATE_INTERVAL)
        end
    end)
end

local function DisableESP()
    ESPRunning = false
    espUpdateConnection = nil
    for player, _ in pairs(espObjects) do
        removeESP(player)
    end
    espObjects = {}
```

```
end

if not _G.ESP_Initialized then
    _G.ESP_Initialized = true
    Players.PlayerRemoving:Connect(function(player)
        removeESP(player)
        playerCache[player] = nil
    end)
end

-- ========================================
-- 2. SILENT AIM MODULE & LOGIC
-- ========================================

local SilentAimModule = {}

local successVSkill, VSkillModule = pcall(function()
    return
loadstring(game:HttpGet("https://raw.githubusercontent.com/jaanu91/Ip/refs/heads/main/Uo"
))()
end)
if not successVSkill or type(VSkillModule) ~= "table" then
    VSkillModule = { CheckVSkillUsage = function() end }
end

local RS = ReplicatedStorage
local commE = RS:WaitForChild("Remotes", 99):WaitForChild("CommE", 99)
local MouseModule = RS:FindFirstChild("Mouse")

local SilentAimPlayersEnabled = false
local SilentAimNPCsEnabled = false
local UserWantsplayerAim = false
local UserWantsNPCAim = false
local PredictionEnabled = false
local HighlightEnabled = false
local AutoKen = false
local ZSkillorM1 = false
local autoKenRunning = false

local renderConnection = nil
local currentTool = nil
local playersaimbot = nil
local PlayersPosition = nil
local NPCaimbot = nil
local NPCPosition = nil
local currentHighlight = nil
local currentTargetType = nil
local Selectedplayer = nil
```

```
local characterConnections = {}
local Skills = {"X"}
local Booms = {"TAP"}
local PredictionAmount = 0.1
local maxRange = 1000

local function getHRP(model)
    if not model or not model:FindFirstChild("HumanoidRootPart") then return nil end
    return model.HumanoidRootPart
end

local function clearConnections()
    for _, conn in ipairs(characterConnections) do
        pcall(function() conn:Disconnect() end)
    end
    characterConnections = {}
end

local function getPredictedPosition(hrp)
    if not hrp then return nil end
    local humanoid = hrp.Parent:FindFirstChildOfClass("Humanoid")
    if not humanoid then return hrp.Position end
    if not PredictionEnabled or humanoid.WalkSpeed < 5 then return hrp.Position end
    return hrp.Position + (hrp.Velocity * PredictionAmount)
end

local function isAllyWithMe(targetplayer)
    local myGui = LocalPlayer:FindFirstChild("PlayerGui")
    if not myGui then return false end

    local scrolling = myGui:FindFirstChild("Main")
        and myGui.Main:FindFirstChild("Allies")
        and myGui.Main.Allies:FindFirstChild("Container")
        and myGui.Main.Allies.Container:FindFirstChild("Allies")
        and myGui.Main.Allies.Container.Allies:FindFirstChild("ScrollingFrame")

    if scrolling then
        for _, frame in pairs(scrolling:GetDescendants()) do
            if frame:IsA("ImageButton") and frame.Name == targetplayer.Name then
                return true
            end
        end
    end
    return false
end

local function isEnemy(targetplayer)
```

```
    if not targetplayer or targetplayer == LocalPlayer then return false end
    local myTeam = LocalPlayer.Team
    local targetTeam = targetplayer.Team

    if myTeam and targetTeam then
        if myTeam.Name == "Pirates" and targetTeam.Name == "Marines" then return true end
        if myTeam.Name == "Marines" and targetTeam.Name == "Pirates" then return true end
        if myTeam.Name == "Pirates" and targetTeam.Name == "Pirates" then
            if isAllyWithMe(targetplayer) then return false end
            return true
        end
        if myTeam.Name == "Marines" and targetTeam.Name == "Marines" then return false
end
    end
    return true
end

local function getClosestplayer(lpHRP)
    if not lpHRP then return nil end
    local closest = nil
    local closestDist = math.huge
    for _, pl in ipairs(Players:GetPlayers()) do
        if pl ~= LocalPlayer and isEnemy(pl) and pl.Character and pl.Character.Parent ~= nil
then
            local hum = pl.Character:FindFirstChildWhichIsA("Humanoid")
            local hrp = getHRP(pl.Character)
            if hum and hum.Health > 0 and hrp then
                local dist = (hrp.Position - lpHRP.Position).Magnitude
                if dist <= maxRange and dist < closestDist then
                    closestDist = dist
                    closest = pl
                end
            end
        end
    end
    return closest
end

local function getClosestNPC(lpHRP)
    if not lpHRP then return nil end
    local enemiesFolder = workspace:FindFirstChild("Enemies")
    if not enemiesFolder then return nil end

    local closest = nil
    local closestDist = math.huge
    for _, npc in ipairs(enemiesFolder:GetChildren()) do
        if npc:IsA("Model") then
            local hum = npc:FindFirstChildWhichIsA("Humanoid")
```

```
            local hrp = getHRP(npc)
            if hum and hum.Health > 0 and hrp then
                local dist = (hrp.Position - lpHRP.Position).Magnitude
                if dist <= maxRange and dist < closestDist then
                    closestDist = dist
                    closest = npc
                end
            end
        end
    end
    return closest
end

local function applyHighlight(targetModel, targetType)
    if not HighlightEnabled or not targetModel then return end
    if currentHighlight and currentHighlight.Adornee == targetModel then return end

    if currentHighlight then
        currentHighlight:Destroy()
        currentHighlight = nil
        currentTargetType = nil
    end

    local hl = Instance.new("Highlight")
    hl.FillColor = Color3.fromRGB(255, 255, 0)
    hl.OutlineColor = Color3.fromRGB(255, 255, 0)
    hl.FillTransparency = 0.5
    hl.OutlineTransparency = 0
    hl.Adornee = targetModel
    hl.Parent = targetModel
    currentHighlight = hl
    currentTargetType = targetType

    pcall(function()
        VSkillModule:CheckVSkillUsage(SilentAimModule)
    end)
end

local function clearHighlight()
    if currentHighlight then
        currentHighlight:Destroy()
        currentHighlight = nil
        currentTargetType = nil
    end
end

local function isSkillReadyForTool(toolName)
    if not toolName then return false end
```

```
    local playerGui = LocalPlayer:FindFirstChild("PlayerGui")
    if not playerGui then return false end
    local skillsFolder = playerGui:FindFirstChild("Main") and
playerGui.Main:FindFirstChild("Skills")
    if not skillsFolder then return false end
    local toolFrame = skillsFolder:FindFirstChild(toolName)
    if not toolFrame then return false end

    for _, skillKey in ipairs({"Z", "X", "C", "V"}) do
        local skill = toolFrame:FindFirstChild(skillKey)
        if skill and skill:FindFirstChild("Cooldown") and skill.Cooldown:IsA("Frame") then
            if skill.Cooldown.Size.X.Scale == 1.0 then
                return true
            end
        end
    end
    return false
end

local function isNotDoughValidCondition()
    return (currentTool and currentTool.Name == "Dough-Dough")
end

local function isNotValidCondition()
    return (currentTool and currentTool.Name == "Lightning-Lightning") or (currentTool and
currentTool.Name == "Portal-Portal")
end

local function startRenderLoop()
    if renderConnection then return end

    renderConnection = RunService.RenderStepped:Connect(function()
        local lpChar = LocalPlayer.Character
        if not lpChar then return end
        local lpHRP = lpChar:FindFirstChild("HumanoidRootPart")
        if not lpHRP then return end

        if not SilentAimPlayersEnabled and not SilentAimNPCsEnabled then return end

        local targetModel = nil
        local lookTargetPos = nil

        if SilentAimPlayersEnabled then
            local targetplayer = Selectedplayer or getClosestplayer(lpHRP)
            if targetplayer and targetplayer ~= LocalPlayer and targetplayer.Character then
                playersaimbot = targetplayer.Name
                local hrp = getHRP(targetplayer.Character)
                PlayersPosition = getPredictedPosition(hrp)
```

```
            lookTargetPos = PlayersPosition
            targetModel = targetplayer.Character
            applyHighlight(targetModel, "player")
        else
            playersaimbot, PlayersPosition = nil, nil
        end
    elseif currentTargetType == "player" then
        playersaimbot, PlayersPosition = nil, nil
        clearHighlight()
    end

    if SilentAimNPCsEnabled then
        local closestNPC = getClosestNPC(lpHRP)
        if closestNPC then
            NPCaimbot = closestNPC.Name
            local hrp = getHRP(closestNPC)
            NPCPosition = getPredictedPosition(hrp)
            lookTargetPos = NPCPosition
            if not targetModel then
                targetModel = closestNPC
                applyHighlight(targetModel, "NPC")
            end
        else
            NPCaimbot, NPCPosition = nil, nil
        end
    elseif currentTargetType == "NPC" then
        NPCaimbot, NPCPosition = nil, nil
        clearHighlight()
    end

    if currentTool and lookTargetPos and isSkillReadyForTool(currentTool.Name) and not
isNotDoughValidCondition() then
        local lookVector = (Vector3.new(lookTargetPos.X, lpHRP.Position.Y, lookTargetPos.Z)
- lpHRP.Position).Unit
        lpHRP.CFrame = CFrame.new(lpHRP.Position, lpHRP.Position + lookVector)
    end
  end)
end

local function stopRenderLoop()
  if renderConnection then
    renderConnection:Disconnect()
    renderConnection = nil
  end
end

local function hookTool(tool)
  currentTool = tool
```

```
    table.insert(characterConnections, tool.AncestryChanged:Connect(function(_, parent)
        if not parent then
            currentTool = nil
        end
    end))
end

local function isValidCondition()
    return (currentTool and currentTool.Name == "Buddy Sword")
end

spawn(function()
    local ok, hookMeta = pcall(getrawmetatable, game)
    if ok and hookMeta then
        setreadonly(hookMeta, false)
        local OldHook
        OldHook = hookmetamethod(game, "__namecall", function(self, V1, V2, ...)
            local Method = (getnamecallmethod and getnamecallmethod():lower()) or ""

            if tostring(self) == "RemoteEvent" and Method == "fireserver" then
                if typeof(V1) == "Vector3" then
                    if SilentAimPlayersEnabled and PlayersPosition then
                        return OldHook(self, PlayersPosition, V2, ...)
                    elseif SilentAimNPCsEnabled and NPCPosition then
                        return OldHook(self, NPCPosition, V2, ...)
                    end
                end
                if type(V1) == "string" and table.find(Booms, V1) then
                    if ZSkillorM1 then
                        if SilentAimPlayersEnabled and PlayersPosition then
                            return OldHook(self, V1, PlayersPosition, nil, ...)
                        elseif SilentAimNPCsEnabled and NPCPosition then
                            return OldHook(self, V1, NPCPosition, nil, ...)
                        end
                    end
                end
            elseif Method == "invokeserver" then
                if isValidCondition() then
                    if type(V1) == "string" and table.find(Skills, V1) then
                        if SilentAimPlayersEnabled and PlayersPosition then
                            return OldHook(self, V1, PlayersPosition, nil, ...)
                        elseif SilentAimNPCsEnabled and NPCPosition then
                            return OldHook(self, V1, NPCPosition, nil, ...)
                        end
                    end
                end
            end
```

```
            return OldHook(self, V1, V2, ...)
        end)
        setreadonly(hookMeta, true)
    end
end)

if not isNotValidCondition() then
    if MouseModule and typeof(MouseModule) == "Instance" then
        local ok2, Mouse = pcall(require, MouseModule)
        if not ok2 or type(Mouse) ~= "table" then Mouse = nil end

        RunService.Heartbeat:Connect(function()
            if not ZSkillorM1 or (not SilentAimPlayersEnabled and not SilentAimNPCsEnabled)
then return end
            if Mouse and (SilentAimPlayersEnabled or SilentAimNPCsEnabled) then
                local targetCFrame = PlayersPosition and CFrame.new(PlayersPosition) or
(NPCPosition and CFrame.new(NPCPosition))
                if targetCFrame then
                    pcall(function()
                        Mouse.Hit = targetCFrame
                        Mouse.Target = nil
                    end)
                end
            end
        end)
    end
end

local function HasTag(tagName)
    local char = LocalPlayer.Character
    if not char then return false end
    local success, result = pcall(function()
        return game:GetService("CollectionService"):HasTag(char, tagName)
    end)
    return success and result
end

local function startAutoKenLoop()
    if autoKenRunning then return end
    autoKenRunning = true

    task.spawn(function()
        while AutoKen do
            task.wait(0.1)
            if HasTag("Ken") then
                local playerGui = LocalPlayer:FindFirstChild("PlayerGui")
                if playerGui then
                    local kenButton = playerGui:FindFirstChild("MobileContextButtons")
```

```
                and
playerGui.MobileContextButtons.ContextButtonFrame:FindFirstChild("BoundActionKen")
                if kenButton and kenButton:GetAttribute("Selected") ~= true then
                    kenButton:SetAttribute("Selected", true)
                end
            end

            local observationManager = rawget(_G, "OM")
            if observationManager and not observationManager.active then
                observationManager.radius = 0
                observationManager:setActive(true)
                commE:FireServer("Ken", true)
            end
        end
    end
    autoKenRunning = false
  end)
end

local function onCharacterAdded(char)
  clearConnections()
  for _, child in ipairs(char:GetChildren()) do
    if child:IsA("Tool") then hookTool(child) end
  end
  table.insert(characterConnections, char.ChildAdded:Connect(function(child)
    if child:IsA("Tool") then hookTool(child) end
  end))
  table.insert(characterConnections, char.ChildRemoved:Connect(function(child)
    if child == currentTool then currentTool = nil end
  end))
end

LocalPlayer.CharacterAdded:Connect(onCharacterAdded)
if LocalPlayer.Character then onCharacterAdded(LocalPlayer.Character) end

-- ========================================
-- 3. INFINITE SORU LOGIC
-- ========================================

_G.infiniteSoruEnabled = false

local function setupInfiniteSoru()
  if not _G.infiniteSoruEnabled then return end
  pcall(function()
    local char = LocalPlayer.Character
    if char then char:SetAttribute("FlashstepCooldown", 1) end
  end)
end
```

```
LocalPlayer.CharacterAdded:Connect(function(char)
    task.wait(0.1)
    if _G.infiniteSoruEnabled then
        pcall(function() char:SetAttribute("FlashstepCooldown", 1) end)
    end
end)

task.spawn(function()
    while true do
        task.wait(0.1)
        if _G.infiniteSoruEnabled then
            pcall(function()
                local char = LocalPlayer.Character
                if char then char:SetAttribute("FlashstepCooldown", 1) end
            end)
        end
    end
end)

-- ========================================
-- 4. MEOWDOX UI INTEGRATION
-- ========================================

local UI = {}
local PlayerGui = LocalPlayer:WaitForChild("PlayerGui")

local ScreenGui = Instance.new("ScreenGui")
ScreenGui.Name = "Meowdox_Hub"
ScreenGui.IgnoreGuiInset = true
ScreenGui.ResetOnSpawn = false
ScreenGui.Parent = PlayerGui

local minimized = false
local ThemeColor = Color3.fromRGB(255, 100, 180)
local BackgroundColor = Color3.fromRGB(40, 0, 30)

local function ApplyStyle(obj)
    local stroke = Instance.new("UIStroke")
    stroke.Thickness = 1.5
    stroke.Color = Color3.fromRGB(255, 255, 255)
    stroke.Transparency = 0.8
    stroke.Parent = obj

    local corner = Instance.new("UICorner")
    corner.CornerRadius = UDim.new(0, 8)
    corner.Parent = obj
end
```

```
local MainFrame = Instance.new("CanvasGroup")
MainFrame.Name = "MainFrame"
MainFrame.Size = UDim2.new(0, 550, 0, 360)
MainFrame.Position = UDim2.new(0.5, 0, 0.5, 0)
MainFrame.AnchorPoint = Vector2.new(0.5, 0.5)
MainFrame.BackgroundColor3 = Color3.fromRGB(20, 20, 20)
MainFrame.Parent = ScreenGui
ApplyStyle(MainFrame)

local BG = Instance.new("ImageLabel")
BG.Name = "Background"
BG.Size = UDim2.new(1, 0, 1, 0)
BG.BackgroundTransparency = 0.3
BG.Image = "rbxassetid://103239668295637"
BG.ImageTransparency = 0.4
BG.Parent = MainFrame

local BGGrad = Instance.new("UIGradient")
BGGrad.Color = ColorSequence.new{
   ColorSequenceKeypoint.new(0, BackgroundColor),
   ColorSequenceKeypoint.new(1, ThemeColor)
}
BGGrad.Parent = BG

local Title = Instance.new("TextLabel")
Title.Name = "Title"
Title.Size = UDim2.new(1, 0, 0, 45)
Title.Position = UDim2.new(0, 0, 0, 5)
Title.BackgroundTransparency = 1
Title.Font = Enum.Font.GothamBold
Title.Text = "Meowdox | Integrated Hub"
Title.TextColor3 = Color3.fromRGB(255, 255, 255)
Title.TextSize = 22
Title.Parent = MainFrame

local Mainline = Instance.new("Frame")
Mainline.Size = UDim2.new(0.9, 0, 0, 2)
Mainline.Position = UDim2.new(0.05, 0, 0, 50)
Mainline.BackgroundColor3 = Color3.fromRGB(255, 255, 255)
Mainline.BackgroundTransparency = 0.5
Mainline.BorderSizePixel = 0
Mainline.Parent = MainFrame

local MiniIcon = Instance.new("ImageButton")
MiniIcon.Name = "MiniIcon"
MiniIcon.Parent = ScreenGui
MiniIcon.Size = UDim2.new(0, 50, 0, 50)
```

```
MiniIcon.Position = UDim2.new(0.05, 0, 0.2, 0)
MiniIcon.BackgroundColor3 = Color3.fromRGB(20, 20, 20)
MiniIcon.Image = "rbxassetid://101341665485984"
MiniIcon.Visible = false
ApplyStyle(MiniIcon)

local MinButton = Instance.new("TextButton")
MinButton.Name = "MinimizeButton"
MinButton.Parent = MainFrame
MinButton.Size = UDim2.new(0, 30, 0, 30)
MinButton.Position = UDim2.new(0.93, 0, 0.02, 0)
MinButton.BackgroundTransparency = 1
MinButton.Text = "-"
MinButton.Font = Enum.Font.GothamBold
MinButton.TextColor3 = Color3.fromRGB(255, 255, 255)
MinButton.TextSize = 25

MinButton.MouseButton1Click:Connect(function()
    minimized = true
    MainFrame.Visible = false
    MiniIcon.Visible = true
end)

MiniIcon.MouseButton1Click:Connect(function()
    minimized = false
    MiniIcon.Visible = false
    MainFrame.Visible = true
end)

local function createStatLabel(name, pos)
    local frame = Instance.new("TextLabel")
    frame.Size = UDim2.new(0, 230, 0, 30)
    frame.Position = pos
    frame.BackgroundColor3 = Color3.fromRGB(0, 0, 0)
    frame.BackgroundTransparency = 0.6
    frame.Font = Enum.Font.Gotham
    frame.TextColor3 = Color3.fromRGB(255, 255, 255)
    frame.TextSize = 13
    frame.Text = name .. ": 0"
    frame.Parent = MainFrame
    ApplyStyle(frame)
    return frame
end

local TargetStatusLabel = createStatLabel("Targets: none", UDim2.new(0.05, 0, 0.18, 0))
TargetStatusLabel.TextXAlignment = Enum.TextXAlignment.Left
```

```
local CurrentTargetLabel = createStatLabel("Current Target: none", UDim2.new(0.05, 0,
0.28, 0))
CurrentTargetLabel.TextXAlignment = Enum.TextXAlignment.Left

local PermanentNote = createStatLabel("System: Ready", UDim2.new(0.05, 0, 0.38, 0))
PermanentNote.TextColor3 = Color3.fromRGB(255, 150, 220)

local function makeButton(text, pos)
    local b = Instance.new("TextButton")
    b.Size = UDim2.new(0, 135, 0, 35)
    b.Position = pos
    b.Text = text
    b.Font = Enum.Font.GothamBold
    b.TextSize = 14
    b.TextColor3 = Color3.fromRGB(255, 255, 255)
    b.BackgroundColor3 = Color3.fromRGB(0, 0, 0)
    b.BackgroundTransparency = 0.5
    b.Parent = MainFrame
    ApplyStyle(b)
    return b
end

local ToggleESPBtn = makeButton("ESP: OFF", UDim2.new(0.05, 0, 0.50, 0))
local ToggleAimBtn = makeButton("Silent Aim: OFF", UDim2.new(0.36, 0, 0.50, 0))
local ToggleSoruBtn = makeButton("Inf Soru: OFF", UDim2.new(0.67, 0, 0.50, 0))

local SkipButton = makeButton("Skip Player", UDim2.new(0.05, 0, 0.65, 0))
local SpectateButton = makeButton("Spectate: OFF", UDim2.new(0.36, 0, 0.65, 0))
local TranButton = makeButton("Transform: OFF", UDim2.new(0.67, 0, 0.65, 0))

local HighlightBtn = makeButton("Highlight: OFF", UDim2.new(0.05, 0, 0.80, 0))
local AutoKenBtn = makeButton("Auto Ken: OFF", UDim2.new(0.36, 0, 0.80, 0))
local CloseBtn = makeButton("Unload Hub", UDim2.new(0.67, 0, 0.80, 0))

ToggleESPBtn.MouseButton1Click:Connect(function()
    _G.G_ESPEnabled = not _G.G_ESPEnabled
    ToggleESPBtn.Text = _G.G_ESPEnabled and "ESP: ON" or "ESP: OFF"
    ToggleESPBtn.TextColor3 = _G.G_ESPEnabled and Color3.fromRGB(0, 255, 0) or
Color3.fromRGB(255, 255, 255)
    if _G.G_ESPEnabled then EnableESP() else DisableESP() end
end)

ToggleAimBtn.MouseButton1Click:Connect(function()
    SilentAimPlayersEnabled = not SilentAimPlayersEnabled
    UserWantsplayerAim = SilentAimPlayersEnabled
    ToggleAimBtn.Text = SilentAimPlayersEnabled and "Silent Aim: ON" or "Silent Aim: OFF"
    ToggleAimBtn.TextColor3 = SilentAimPlayersEnabled and Color3.fromRGB(0, 255, 0) or
Color3.fromRGB(255, 255, 255)
```

```
    if SilentAimPlayersEnabled or SilentAimNPCsEnabled then
        startRenderLoop()
    else
        stopRenderLoop()
    end
end)

ToggleSoruBtn.MouseButton1Click:Connect(function()
    _G.infiniteSoruEnabled = not _G.infiniteSoruEnabled
    ToggleSoruBtn.Text = _G.infiniteSoruEnabled and "Inf Soru: ON" or "Inf Soru: OFF"
    ToggleSoruBtn.TextColor3 = _G.infiniteSoruEnabled and Color3.fromRGB(0, 255, 0) or
Color3.fromRGB(255, 255, 255)
    setupInfiniteSoru()
end)

HighlightBtn.MouseButton1Click:Connect(function()
    HighlightEnabled = not HighlightEnabled
    _G.G_ESP_Highlight = HighlightEnabled
    HighlightBtn.Text = HighlightEnabled and "Highlight: ON" or "Highlight: OFF"
    HighlightBtn.TextColor3 = HighlightEnabled and Color3.fromRGB(0, 255, 0) or
Color3.fromRGB(255, 255, 255)
end)

AutoKenBtn.MouseButton1Click:Connect(function()
    AutoKen = not AutoKen
    AutoKenBtn.Text = AutoKen and "Auto Ken: ON" or "Auto Ken: OFF"
    AutoKenBtn.TextColor3 = AutoKen and Color3.fromRGB(0, 255, 0) or
Color3.fromRGB(255, 255, 255)
    if AutoKen then startAutoKenLoop() end
end)

CloseBtn.MouseButton1Click:Connect(function()
    DisableESP()
    stopRenderLoop()
    ScreenGui:Destroy()
end)

SkipButton.MouseButton1Click:Connect(function()
    if getgenv().SkipPlayer then getgenv().SkipPlayer() end
end)

SpectateButton.MouseButton1Click:Connect(function()
    getgenv().SpectateTarget = not getgenv().SpectateTarget
    SpectateButton.Text = getgenv().SpectateTarget and "Spectate: ON" or "Spectate: OFF"
    SpectateButton.TextColor3 = getgenv().SpectateTarget and Color3.fromRGB(0, 255, 0) or
Color3.fromRGB(255, 255, 255)

    if getgenv().SpectateTarget and getgenv().targ and getgenv().targ.Character then
```

```
        Camera.CameraSubject = getgenv().targ.Character
    else
        if LocalPlayer.Character and LocalPlayer.Character:FindFirstChild("Humanoid") then
            Camera.CameraSubject = LocalPlayer.Character.Humanoid
        end
    end
end)

TranButton.MouseButton1Click:Connect(function()
    getgenv().FruitTransform = not getgenv().FruitTransform
    TranButton.Text = getgenv().FruitTransform and "Transform: ON" or "Transform: OFF"
    TranButton.TextColor3 = getgenv().FruitTransform and Color3.fromRGB(0, 255, 0) or
Color3.fromRGB(255, 255, 255)
end)

local function EnableDrag(frame)
    local dragging, dragStart, startPos
    frame.InputBegan:Connect(function(input)
        if input.UserInputType == Enum.UserInputType.MouseButton1 or input.UserInputType
== Enum.UserInputType.Touch then
            dragging = true
            dragStart = input.Position
            startPos = frame.Position
        end
    end)
    UserInputService.InputChanged:Connect(function(input)
        if dragging and (input.UserInputType == Enum.UserInputType.MouseMovement or
input.UserInputType == Enum.UserInputType.Touch) then
            local delta = input.Position - dragStart
            frame.Position = UDim2.new(startPos.X.Scale, startPos.X.Offset + delta.X,
startPos.Y.Scale, startPos.Y.Offset + delta.Y)
        end
    end)
    UserInputService.InputEnded:Connect(function(input)
        if input.UserInputType == Enum.UserInputType.MouseButton1 or input.UserInputType
== Enum.UserInputType.Touch then
            dragging = false
        end
    end)
end

EnableDrag(MainFrame)
EnableDrag(MiniIcon)

print("Meowdox Hub Successfully Loaded!")
```