

# Functional Testing

Zelin Cai, Patrick Silvestre

## 1 Input Domain

The input domain of the unit `nextDate` consists of dates formatted as follows:  $DD/MM/YYYY$ . For months,  $MM$ , the input condition specifies the range  $[1, 12]$ . If  $MM = 2$  and the year is not a leap year, then the input condition range for dates,  $DD$  is  $[1, 28]$  (a year is a leap year if divisible by 4 and not divisible by 100 (unless divisible by 400)). If  $MM = 2$  and the year is a leap year, then the input condition range for  $DD$  is  $[1, 29]$ . If  $MM = 4, 6, 9$ , or  $11$ , then the input condition range for  $DD$  is  $[1, 30]$ . If  $MM = 1, 3, 5, 7, 8, 10$ , or  $12$ , then the input condition range for  $DD$  is  $[1, 31]$ .

## 2 Equivalence Classes

In order to identify equivalence classes (ECs), the following strategy was used: input conditions typically specified a range  $[a, b]$ , thus one EC was identified for  $a \leq X \leq b$ , and two others were identified for  $X < a$  and  $b < X$ .

### 2.1 Months

- EC-01:  $01 \leq MM \leq 12$
- EC-02:  $MM < 01$
- EC-03:  $12 < MM$

### 2.2 Dates

#### 2.2.1 $MM = 2$ , $YY$ is not a leap year

- EC-04:  $01 \leq DD \leq 28$
- EC-05:  $DD < 01$
- EC-06:  $28 < DD$

### **2.2.2 MM = 2, YY is a leap year**

- EC-07:  $01 \leq DD \leq 29$
- EC-08:  $DD < 01$
- EC-09:  $29 < DD$

### **2.2.3 MM = 4, 6, 9, or 11**

- EC-10:  $01 \leq DD \leq 30$
- EC-11:  $DD < 01$
- EC-12:  $30 < DD$

### **2.2.4 MM = 1, 3, 5, 7, 8, 10, or 12**

- EC-13:  $01 \leq DD \leq 31$
- EC-14:  $DD < 01$
- EC-15:  $31 < DD$

## **2.3 Years**

- EC-13:  $1900 \leq YYYY \leq 2099$
- EC-14:  $YYYY < 1900$
- EC-15:  $2099 < YYYY$

## **3 Test Cases**

### **3.1 Test Cases from Equivalence Classes**

### **3.2 Test Cases for Boundary Value Analysis**

### **3.3 Test Cases for Random Testing**