

Super TUFF-R™

Insulation



WORLDWIDE PARTNER

Nominal Board Thickness 1'0" | 3'0" | 3'6" | 4'

R-VALUE 3.9 | 4.1 | 5.0 | 6.5

IT IS THE BUYER'S RESPONSIBILITY TO ENSURE PRODUCT USE IN ACCORDANCE WITH ALL APPLICABLE CODES AND REGULATIONS. CAUTION: This product is combustible and shall only be used as specified by the local building code with respect to flame spread classification and to the use of a suitable thermal barrier. SEE ICC-ES ESR-3089. Audited by INTERTEK TESTING SERVICES. For MSDS and more information, www.dowbuildingsolutions.com and/or call Dow 1-866-583-BLUE(2583), or contact your local building inspector. In an emergency call 1-989-636-4400.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.

DOW

