CMPS 312





Android Fundamentals

Dr. Abdelkarim Erradi CSE@QU

Outline

- 1. Introduction to Android
- 2. Android Programming Model

Introduction to Android



What is Android?

- Open source mobile operating system (OS) based on Linux kernel
 - originally purchased by Google from Android, Inc. in 2005
- Used on <u>over 80%</u> of all smartphones
- Powers devices such as watches, TVs, and cars
- The #1 OS worldwide
 - Over 2.5 billion active Android devices worldwide
 - Over 2 Million Android apps in Google Play store
- Highly customizable for devices by vendors

Android Software Stack

- **Applications** 3 Application Framework **Android Runtime** Libraries Linux Kernel
 - 1. Linux Kernel: interacts and manages hardware
 - 2. Expose native APIs; run apps
 - 3. Java API exposing Android OS features
 - 4. System and user apps

Android Software Stack


- Optimized Linux Kernel manages core services such as device hardware drivers, process and memory management, and power management
 - Acts as an abstraction layer between the hardware and the rest of the software stack
- 2. Android runtime (ART) = Virtual Machine to run Apps
 - Every App runs in its own process in its own instance of the Android Runtime
 - Expose native APIs and OS Core Libraries including 2D/3D graphics, SQLite database, encryption ...
- 3. Application Framework: Java APIs (Application Programming Interfaces) make Android OS features available to Apps

https://developer.android.com/guide/platform



Model-View-ViewModel (MVVM) Architecture





Advantages of MVVM



Separation of concerns

- View, ViewModel, and Model are separate components
 - Computation is not intermixed with Presentation. Consequently, code is cleaner, flexible and easier to understand and change.
 - Allow changing a component without significantly disturbing the others (e.g., UI can be completely changed without touching the model)
- => Easier maintenance




Android Programming Model



Android Programming Model





- App is composed of one or more screens (called Activity)
- An activity has:
- a <u>Layout</u> that define its appearance (how it **looks like**)
 - Layout acts as a container for UI Components (called <u>View</u>)
 - It decides the size and positions of views placed in it
 - Activity Kotlin class that provides the data to the UI and handles events
 - UI Components raise Events when the user interacts with them (such as a Clicked event is raised when a button is pressed).
 - In the activity class we define Event
 Handlers to respond to the UI events


Activity

- Activity is a screen that displays a UI to allow the user to do something such order groceries, send email ...
 - Has layout (.xml) file & Activity class
 - This allows a clear separation between the UI and the app logic
- Connecting activity with the layout is done in the onCreate method
- Can start other activities in the same or other apps
- Has a lifecycle: created, started, paused, resumed, stopped, and destroyed
- Listeners have code to handle events:
 - User interaction events such press a button or enters text in a text view
 - External events such as receiving a notification or screen rotation

Example

```
class MainActivity : AppCompatActivity() {
     override fun onCreate(savedInstanceState: Bundle?) {
           super.onCreate(savedInstanceState)
           setContentView(R.layout.activity_main)
 Connects
 activity
with layout
           changeColorBtn.setOnClickListener {
               greetingTv.setTextColor(getRandomColor())
```

Development Process



Project structure


арр manifests java qa.edu.cmps312.firstapp C LoginActivity **№** MainActivity 🕵 java (generated) res drawable layout activity_login.xml activity_main.xml mipmap values Gradle Scripts build.gradle (Project: FirstApp) www.build.gradle (Module: app) gradle-wrapper.properties (Gradle Version)

proguard-rules.pro (ProGuard Rules for app)

- AndroidManifest.xml
 - app config and settings (e.g., list app activities and required permissions)
- □ java/...
 - Kotlin source code
- res/... = resource files (many are XML)
 - o drawable/ = images
 - layout/ = GUI layouts
 - menu/ = app menu options
 - values/ = constant values
 - strings/ = localization data
 - styles/ = appearance styling
- Gradle
 - a build/compile management system
 - build.gradle = main build config file


App 1 - Color Changer


App that contains Text reading "YaHala!", an Image and a Button that randomly changes text's color with every click







App 2 – Guessing Game







App 3 – Tips Calculator






App 4 – Country Explorer





What Makes up Android UI?





UI components


- Set of pre-built UI components that can be composed to create a GUI
- e.g. button, TextView,
 Menu, List, etc.

Layout containers

 Control placement/ positioning of components in the Activity

UI Component

UI component is a class that has:




Steps to creating a GUI Interface

- Design it on paper (sketch)
 - Decide what information to present to user and what input they should supply
 - Decide the UI components and the layout on paper
- Create a layout and add UI components to it using the Layout Editor
 - Use the Layout Editor to group and arrange components
- Add event handlers to respond to the user actions
 - Do something when the user presses a button, selects an item from list, change text of input field, etc.

UI Sketch - Example Text = Button lmage You may design different ≥ Image layouts per screen size

Activity Lifecycle



An activity has essentially **four states**:

- If an activity in the foreground of the screen (at the top of the stack), it is *active*
 - If an activity has lost focus but is still visible (e.g., beneath a dialog box), it is *paused*. A paused activity is completely alive but can be killed by the system in case of low memory.
 - If an activity is completely obscured by another activity, it is **stopped**. It still retains all state and member information but can be **destroyed** by the system when memory is needed.
- If an activity is paused or stopped, it maybe killed. When it is displayed, it must be completely **restarted** and restored to its previous state.

Resources

- Android Kotlin Fundamentals Course
 - https://developer.android.com/courses/kotlinandroid-fundamentals/overview
 - https://codelabs.developers.google.com/androidkotlin-fundamentals/

- Android Dev Guide
 - https://developer.android.com/guide/