

CMPS 312

Firebase Cloud Services



Firestore Database



Authentication



Storage




Dr. Abdelkarim Erradi

CSE@QU

Outline


1. Firestore Data Model
2. Firestore CRUD Operations
3. Firebase Storage
4. Access Image Gallery and Camera
5. Firebase Authentication

Firebase Cloud Services

- Firebase is a **cloud platform** offering many **services** that work together as a backend server infrastructure for mobile/web apps
- We will focus on introducing:
 -  **Firestore:** store/query documents in collections
 -  **Storage:** store and retrieve files
 -  **Firebase Authentication:** secure user authentication using various identity providers (e.g., email/password, Google Auth)



Firestore Data Model






Firestore Database

- Cloud-hosted **scalable** database to manage app data
 - No need to set up or maintain backend servers
- Provides real-time updates and offline support
- Uses a **document-oriented** data model
 - Data is organized in **collections**
 - Each collection contains documents, which can further include subcollections
 - Allowing you to build flexible and hierarchical data structures
- **NoSQL** (does not use SQL as a query language)
- Access controlled with **security rules**
- Includes a [free tier](#) (1 GB data, 50K reads/day and 20K writes/day) then pay as you use


Data Model



- Firestore is **Document Oriented Database**
 - Stores data as **documents** that utilizes a flexible, JSON-like data model
 - instead of rows and columns as done in a relational database
 - Documents are grouped into **collections**
 - **API to query** and manage documents
- Better alternative data management solution for Mobile/Web applications (compared to using a Relational DB)
 - Real-time synchronization capabilities
 - Scalable data management

Document

```
{  
  "isbn" : 123,  
  "title": "Mr Bean and the Forty Thieves",  
  "category": "Fun",  
  "pages": 250  
  "authors": ["Mr Bean", "Juha Dahak"],  
  "publisher": {  
    "name": "MrBeanCo",  
    "country": "UK"  
  }  
}
```



property : value

property : array

property : map

- **Document = JSON-like object**
- **Document = set of key-value pairs**
- **Document = basic unit of data** in Firestore
 - You can only fetch a document not part of it
- Analogous to **row** in a relational database
- Size limit to **1 MB** per document
- A document can optionally point to subcollections
- A Document **cannot** point to another document

Data Types

- Cloud Firestore supports a variety of data types for values:
 - boolean, number, string,
 - geo point, binary blob, and timestamp
 - arrays, nested objects (called maps) to structure a complex object (e.g., address) within a document

Document


```
bird_type: "swallow"  
airspeed: 42.733  
coconut_capacity: 0.62  
isNative: false  
icon: <binary data>  
vector:  
  {x: 36.4255,  
   y: 25.1442,  
   z: 18.8816}  
distances_traveled:  
  [42, 39, 12, 42]
```


Collection



- **Collection = container** for documents
- Analogous to **table** in a relational database
- **Does not enforce** a schema
- Documents in a collection usually **have similar purpose** but they may have slightly different schema
- A collection cannot contain other collections


Example Collection & Documents



Firestore Root



Shopping List App



- Database with 2 **top-level** collections: **ShoppingItems** and **Categories**
- Each category document has a **Products** sub-collection


Document Identifiers


- Documents within a collection have **unique identifiers**
 - You can provide your own keys, such as using the **email** as a unique identifier for users
 - You can let Cloud Firestore assign a random IDs
- You do not need to "create" or "delete" collections
 - A collection gets created after you create the first document in a collection
 - A collection is deleted when you delete all the documents in a collection
- Access a document using its **collection** and its doc **Id**

```
final FirebaseFirestore db = FirebaseFirestore.instance;  
final u1DocRef = await db.collection("users").doc("u1@test.com").get();
```


Subcollections


- A subcollection is a collection associated with a specific document
 - E.g., A subcollection called messages for every room document in the rooms collection

 rooms

 roomA

name : "my chat room"

 messages


 message1

from : "alex"

msg : "Hello World!"

 message2

...


 roomB

...

- Get a reference to a message in the subcollection

```
final FirebaseFirestore db = FirebaseFirestore.instance;  
  
final message1DocRef =  
    db.collection("rooms").document("roomA")  
        .collection("messages").document("message1");
```


Example Restaurant Review App



Source: https://www.youtube.com/watch?v=v_hR4K4auoQ

Add Firebase to your Flutter project

- Login to <https://console.firebase.google.com/>
- Create a **project** (give it a meaningful name, see the steps at this [link](#))
 - to keep it simple disable Google Analytics for the project
- Create Firestore database (see the steps at this [link](#))
- Select the **Project settings** and add an Android app



- Download **google-services.json** and place it under **\android\app** subfolder

Dependencies

- Add to **pubspec.yaml**:

dependencies:

firebase_core: ^3.6.0

cloud_firestore: ^5.4.4

- Install [Firebase CLI](#)

npm install -g firebase-tools

- Install FlutterFire CLI

dart pub global activate flutterfire_cli

([add the folder](#) in the Warning message to Windows/MacOS System's environment path)

- Generate **firebase.json** and **firebase_options.dart** config files to connect to Firebase

firebase login

flutterfire configure

Easier way to Flutter app to use Firebase

- Add to `<project>/build.gradle`

```
plugins {  
    // Add the dependency for the Google services Gradle plugin  
    id 'com.google.gms.google-services' version '4.4.2' apply false  
}
```

- Add to `<project>/app/build.gradle`

```
plugins {  
    ...  
    // Add the Google services Gradle plugin  
    id 'com.google.gms.google-services'  
}
```

```
defaultConfig { ...
```

```
    minSdk = 23
```

Set the min SDK version to 23

Initialize Firebase in Your Flutter App

- Open the main function initialize Firebase before running the app

```
void main() async {  
  WidgetsFlutterBinding.ensureInitialized();  
  await Firebase.initializeApp();  
  runApp(  
    const ProviderScope(  
      child: MyApp(),  
    ),  
  );  
}
```



Firestore CRUD Operations



CREATE

C



READ

R



UPDATE

U



DELETE

D

Create Data Classes Mapped to Firestore Docs

- Normal **classes** having the same structure as Firebase docs
 - Map fields to/from Firestore using a fromJson and toJson method


```
class Category {
    String id;
    String name;
    // Default constructor
    Category({this.id = '', this.name = ''});
    factory Category.fromJson(Map<String, dynamic> data) {
        return Category(
            id: data['id'],
            name: data['name'] ?? '',
        );
    }
    Map<String, dynamic> toJson() {
        return {
            'name': name,
        };
    }
}
```

Query – return all documents

- Using **collection reference** use the **.get** method to return the collection documents
 - You can sort the results using **.orderBy**
 - Use the same technique to get documents from a subcollection associated with a particular document

```
Future<List<Product>> fun getProducts(categoryId: String) async {  
    final queryResult = await categoryCollectionRef.doc(categoryId).collection("products")  
        .orderBy("name", Query.Direction.DESENDING).get();  
    List<Product> products = queryResult.docs.map((doc) =>  
        Product.fromJson(doc.data() as Map<String, dynamic>  
        ).toList());  
    return products;  
}
```

Query – filter using .where

- Use **.where**  to filter the documents to return from a collection

```
final citiesRef = db.collection("cities");
final stateQuery = citiesRef.where("state", isEqualTo: "CA");
final populationQuery = citiesRef.where("population",
    isLessThan: 100000);
final nameQuery = citiesRef.where("name", isEqualTo: "Doha");
final notCapitals = citiesRef.where("capital", isNotEqualTo: true);
final cities = citiesRef.where("country", whereIn: ["USA", "Japan"]);
```

```
Future<Category?> getCategory(categoryName: String) async {
  final queryResult = await categoryRef.where("name", isEqualTo: categoryName).get();
  if (queryResult.docs.isNotEmpty) {
    return Category.fromJson(queryResult.docs.first.data());
  }
  return null;
}
```

and / or filter condition

- Filter condition connected with **and**

```
citiesRef.where("state", isEqualTo: "CA")  
           .where("population", isLessThan: 1000000);
```

- Filter condition connected with **or**







```
var query = db.collection("cities").where(  
    Filter.or(  
        Filter("capital", isEqualTo: true),  
        Filter("population", isGreaterThan: 100000),  
    ),  
);
```

Add a document to a Collection

- Get a collection reference

```
var collectionRef = db.collection("colName")
```

- Call **.add** method and pass the object to add the collection
 - Firebase adds the object to the collection and returns the auto-assigned **docId**






 cmp312-fall2020	 categories  	 9bbraJMpuCt7eFWpbvA6
categories >	9bbraJMpuCt7eFWpbvA6 >	name: "Fruits" 

```
final category = Category("Fruits");  
final categoryRef = db.collection("categories");  
final queryResult = await categoryRef.add(category.toJson());  
final categoryId = queryResult.id;
```


Add a document and set DocId

- First specify the desired **docId** to be assigned to the new doc
`collectionRef.doc(docId)`
- Call **.set** method and pass the object to add to the collection
 - Firebase adds the object to the collection and the id of the new doc is **docId** passed to **.doc** method

```
Future<void> addUser(User user) async {  
    var userCollectionRef = FirebaseFirestore.instance.collection("users");  
    await userCollectionRef.doc(user.email).set(user.toJson());  
}
```

 cmp312-fall2020	 users  	 erradi@live.com
users >	erradi@live.com >	email: "erradi@live.com"
categories		firstName: "Abdelkarim"
restaurants		lastName: "Erradi"
shoppingItems		role: "Admin"
		▼ address
		city: "Doha"
		houseNumber: "345"
		street: "Test St"

Update a document

- Use **.update** and pass the fields to update and their new values as a Map
 - Or use **.set** to replace the whole document

```
Future<void> updateQuantity(String itemId,
    int quantity) async {
    await shoppingItemRef.doc(itemId).update(
        {'quantity': quantity});
}
```

```
Future<void> updateItem(ShoppingItem item) async {
    await shoppingItemRef.doc(item.id).set(item.toJson());
}
```

Delete a document

- Use **.delete** method to delete a document

```
Future<void> deleteItem(ShoppingItem item) async {  
    await shoppingItemRef.doc(item.id).delete();  
}
```

Subscribing to collection/document Realtime Updates

- Use **.snapshots()** to observe the changes of a collection/document and get near **real-time updates**



```
Stream<List<ShoppingItem>> observeShoppingListItems() {  
    final uid = FirebaseAuth.instance.currentUser?.uid;  
    if (uid == null) return Stream.value([]);  
    return FirebaseFirestore.instance  
        .collection('shoppingItems')  
        .where('uid', isEqualTo: uid)  
        .snapshots()  
        .map((snapshot) => snapshot.docs  
            .map((doc) =>  
                ShoppingItem.fromJson(doc.data() as Map<String, dynamic>))  
            )  
        .toList());  
}
```

Securing Data

- Cloud Firestore **Security Rules** consist of:
 - **match statements**, which identify documents in the database, and
 - **allow expressions**, which control access to those documents

```
// Allow read/write access on all documents to any user signed in to the app
service cloud.firestore {
  match /databases/{database}/documents {
    match /{document=**} {
      allow read, write: if request.auth.uid != null;
    }
  }
}
```

Firebase Storage







Firebase Storage

- Firebase Cloud Storage
 - Store and serve files
 - Robust
 - Secure
 - Access controlled with security rules
- To access to the Firebase Storage service:
`final storageRef = FirebaseStorage.instance.ref()`;
`.ref()` creates a reference to the root path. You can append `.child()` to this reference to navigate to specific paths.



Firestore Storage File Operations



▼ Upload Operations



  `putBytes(byte[]): UploadTask`

  `putFile(Uri): UploadTask`



▼ Download Operations

  `getBytes(long): Task<byte[]>`



  `getFile(Uri): FileDownloadTask`



  `getFile(File): FileDownloadTask`



▼ Delete

  `delete(): Task<Void>`

▼ List

  `list(int): Task<ListResult>`

  `list(int, String): Task<ListResult>`

  `listAll(): Task<ListResult>`

List

- Get URLs of files in particular subfolder

```
Future<List<String>> getImageUrls() async {
  List<String> imageUrls = [];
  try {
    // Reference to the 'images/' directory in Firebase Storage
    final storageRef = FirebaseStorage.instance.ref().child("images/");

    // List all items in the 'images/' directory
    final result = await storageRef.listAll();

    // Loop through the items and get the download URL for each image
    for (var image in result.items) {
      String url = await image.getDownloadURL();
      imageUrls.add(url);
    }
  } catch (e) {
    print('Error fetching image URLs: $e');
  }
  return imageUrls;
}
```

Add file

```
final storageRef = FirebaseStorage.instance.ref();  
// Upload file  
await storageRef.child("images/$filename")  
    .putFile(filePath);  
final imageUrl = await storageRef.getDownloadURL();
```

Delete file

```
await storageRef.child("images/$filename").delete();
```



```
Future<void> downloadFile(String filename, String destinationPath) async {  
  try {  
    // Get reference to the file in Firebase Storage  
    final ref = FirebaseStorage.instance.ref('files/$filename');  
  
    // Download the file to the destination path  
    await ref.writeToFile(File(destinationPath));  
  
    print('File downloaded successfully to $destinationPath');  
  } catch (e) {  
    print('Error downloading file: $e');  
  }  
}
```

- Or you can simply get the download URL

```
final ref = FirebaseStorage.instance.ref('files/$filename');  
final imageUrl = await ref.getDownloadURL();
```

Firestore Authentication





Firebase Authentication

- **Authentication** = **Identity verification**:
 - Verify the identity of the user given the credentials received
 - Making sure the user is who he claims to be
- Every user gets a unique ID
- Restrict who can read and write what data



Multiple Identity Providers can be used for Authentication



Sign in

- Sign in using Firebase authentication

```
final authResult = await FirebaseAuth.instance.signInWithEmailAndPassword(  
    email: email,  
    password: password,  
);  
print(">> Debug: signIn.authResult : ${authResult.user?.uid}");
```

Sign up

- Sign up and the user details to Firebase authentication

```
Future<User?> signUp(User user) async {  
  try {  
    // Create a new user with email and password  
    User authResult = await FirebaseAuth.instance.createUserWithEmailAndPassword(  
      email: user.email,  
      password: user.password,  
    );  
  
    // If the user was created successfully, update their profile  
    if (authResult.user != null) {  
      await authResult.user!.updateDisplayName('${user.firstName} ${user.lastName}');  
      await authResult.user!.updatePhotoURL('http://test.com/spongebob.png');  
      // Refresh the user to apply changes  
      await authResult.user!.reload();  
    }  
  
    return authResult;  
  } catch (e) {  
    print('Error during sign up: $e');  
    return null;  
  }  
}
```


Sign out

- Sign out from Firebase auth
`await FirebaseAuth.instance.signOut();`
- Anywhere in the app you can access the details of current user

```
void getCurrentUser() {  
  User? user = FirebaseAuth.instance.currentUser;  
  if (user != null) {  
    print('User is signed in! Email: ${user.email}');  
  } else {  
    print('No user is signed in.');
```

Access Image Gallery and Camera



Access Image Gallery and Camera

- Using **image_picker** package for picking images from the image gallery or taking new pictures with the camera

```
Future<File?> pickImage(ImageSource source) async {  
    final imagePicker = ImagePicker();  
    final pickedImage = await imagePicker.pickImage(  
        source: source, // camera or gallery  
        maxWidth: double.infinity,  
    );  
  
    if (pickedImage == null) return null;  
    return File(pickedImage.path);  
}
```

image_picker methods

```
final ImagePicker picker = ImagePicker();  
// Pick an image  
final XFile? image = await picker.pickImage(source: ImageSource.gallery);  
// Capture a photo  
final XFile? photo = await picker.pickImage(source: ImageSource.camera);  
// Pick a video  
final XFile? galleryVideo =  
    await picker.pickVideo(source: ImageSource.gallery);  
// Capture a video  
final XFile? cameraVideo = await picker.pickVideo(source: ImageSource.camera);  
// Pick multiple images  
final List<XFile> images = await picker.pickMultiImage();  
// Pick single image or video  
final XFile? media = await picker.pickMedia();  
// Pick multiple images and videos  
final List<XFile> medias = await picker.pickMultipleMedia();
```

Summary

- **Cloud Firestore** database store/query app's data
 - Data model consists of collections to store documents that contain data as a key-value pair similar to JSON
- Firebase **Cloud Storage** is used to store and retrieve files
- **Firebase Authentication** provides built-in backend services to ease user authentication
 - email/password authentication allows users to register and log in to the app
 - Secure user's authentication using various identity providers (e.g., email/password, Google Auth)

Resources

- Cloud Firestore
 - <https://firebase.google.com/docs/firestore/>
- Get to know Cloud Firestore
 - <https://www.youtube.com/playlist?list=PLI-K7zZEsYLIuG5MCVEzXAQ7ACZBCuZgZ>
- Firestore codelab
 - <https://firebase.google.com/codelabs/firebase-get-to-know-flutter>
- Firebase Auth codelab
 - <https://firebase.google.com/codelabs/firebase-auth-in-flutter-apps>