

# CMPS 312



## Supabase Database



**Dr. Abdelkarim Erradi**  
**CSE@QU**

# Outline

1. Supabase Database
2. CRUD Operations
3. Row Level Security (RLS)
4. Realtime Updates







# Backend-as-Service (BaaS)

- **Purpose:** Provide ready-made backend for web & mobile apps
- **Benefits:**
  - No need to build/manage servers, databases, or APIs
  - Speeds up development and reduces infrastructure complexity & cost
  - Allows developers focus on frontend and core business logic
- **Common Features:** User authentication, Managed databases, File storage, Serverless functions,& Notifications
- **Examples:** **Supabase**, Firebase, AWS Amplify



# What is Supabase?


Supabase = Open-source **Backend-as-a-Service** (BaaS) built on PostgreSQL. Core Features:

-  **Database:** Managed PostgreSQL with Row-Level Security (RLS)
-  **Storage:** Scalable file storage with public/signed URLs
-  **Authentication:** Secure user sign-in via email/password & OAuth providers
-  **Realtime:** Broadcast database updates in real time
-  **Edge Functions:** Deploy serverless functions for custom logic
-  **Developer Tools:** SDKs for **Flutter/Dart**, JavaScript, and more


# Getting Started

- Add **supabase\_flutter** to `pubspec.yaml`
- Initialize Supabase in `main.dart`
  - This Enables database, authentication, and storage features in your Flutter app

```
await Supabase.initialize(  
  url: 'https://your-project.supabase.co',  
  anonKey: 'your-anon-key',  
);
```



# Supabase Database



PostgreSQL

# Supabase Database

- **Managed PostgreSQL:** Includes tables, views, triggers, and functions
- **Auto-Generated Web APIs** for every table, view and function
  - Use `.from('table')` to read/write from/to tables

## API Docs

### Read rows

#### TABLES AND VIEWS

Introduction

owners

pet\_owner\_view

pets

**todos**

To read rows in `todos`, use the `select` method.

[Learn more](#)

JavaScript Bash  Project API key: [Hide keys](#)

#### READ ALL ROWS


```
curl
'https://yjjocdq1flvamdmrhuyq.supabase.co/r
est/v1/todos?select=*' \
-H "apikey: SUPABASE_KEY" \
-H "Authorization: Bearer SUPABASE_KEY"
```

- **Schema First Design:** Create tables via SQL or Supabase dashboard
- **Row-Level Security (RLS)** with customizable policies



# Creating Database Table

- Design tables using **SQL scripts** or Supabase dashboard (visual editor)



*-- Example table: todos*

```
create table if not exists todos (  
  id uuid primary key default gen_random_uuid(),  
  description text not null,  
  -- Enforce data integrity with constraints  
  type text not null check (type in  
    ('personal', 'work', 'family')),  
  completed boolean not null default false,  
  -- Timestamp when todo was created  
  created_at timestamptz not null default now(),  
  -- Link todos to authenticated users  
  user_id uuid references auth.users(id)  
);
```



# PostgreSQL Common Data Types

- **Numeric**
  - INTEGER – General whole numbers
  - BIGINT – Large IDs or counters
  - NUMERIC(p,s) – Exact precision (money)
  - SERIAL – Auto-increment IDs
- **Character**
  - VARCHAR(n) – Variable-length text
  - TEXT – Large/unlimited text
- **Date/Time**
  - DATE – Calendar dates
  - TIMESTAMPTZ – Date/time with time zone
- **Boolean** – True/False flags
- **Other**
  - UUID – Unique identifiers
  - JSONB – Semi-structured data (queryable)

# Database Auto-Assigned IDs

Two common strategies for primary keys:

- Use PostgreSQL's **SERIAL** for efficient auto-incremented numeric ID

```
CREATE TABLE todos (  
  id SERIAL PRIMARY KEY,  
  ...);
```

- Use PostgreSQL's **gen\_random\_uuid()** for globally unique IDs

```
create table todos (  
  id uuid primary key default gen_random_uuid(),  
  ...);
```

# PostgreSQL: One-to-Many Relationships

- One parent row relates to many child rows (e.g., one author has many books)
  - Enforced via foreign key (FK) from child → parent primary key (PK)
  - Use ON DELETE CASCADE to remove child rows when parent is deleted

```
-- Parent table (one)
CREATE TABLE authors (
  author_id SERIAL PRIMARY KEY,
  name TEXT NOT NULL);
```

```
-- Performance: index FK to
speed-up joins & deletes
CREATE INDEX idx_books_author_id
ON books(author_id);
```

```
-- Child table (many)
CREATE TABLE books (
  book_id SERIAL PRIMARY KEY,
  author_id INT NOT NULL,
  title TEXT NOT NULL, ...
  CONSTRAINT fk_books_author
  FOREIGN KEY (author_id)
  REFERENCES authors(author_id)
  ON DELETE CASCADE
);
```



# CRUD Operations



CREATE



READ



UPDATE



DELETE

---

C

R

U

D

# CRUD

## CRUD

- Create: Add new records
- Read: Retrieve existing records
- Update: Modify existing records
- Delete: Remove records
- In Supabase perform CRUD via the auto-generated REST APIs

```
// Create
await Supabase.instance.client
  .from('tasks')
  .insert({'title': 'New Task'})
  .execute();

// Update
await Supabase.instance.client
  .from('tasks')
  .update({'done': true})
  .eq('id', 1)
  .execute();

// Delete
await Supabase.instance.client
  .from('tasks')
  .delete()
  .eq('id', 1)
  .execute();
```



# Database CRUD Operations

```
final client = Supabase.instance.client;
// CREATE
Future<void> addTodo(Todo todo) async {
  await client.from('todos').insert(todo.toJson());
}
// READ (List)
Future<List<Todo>> getTodos() async {
  final data = await client.from('todos').select().order('created_at', ascending: false);
  return (data as List).map((j) => Todo.fromJson(j)).toList();
}
// READ (single)
Future<Todo?> getTodoById(String id) async {
  final json = await client.from('todos').select().eq('id', id).maybeSingle();
  return json == null ? null : Todo.fromJson(json);
}
// UPDATE
Future<void> updateTodo(Todo todo) async {
  await client.from('todos').update(todo.toJson()).eq('id', todo.id);
}
// DELETE
Future<void> deleteTodo(String id) async {
  await client.from('todos').delete().eq('id', id);
}
// COUNT
Future<int> getTodosCount() async {
  final res = await client.from('todos').select().count(CountOption.exact);
  return res.count;
}
```

# Common Filter Methods and Examples

Method	Description	Example
<b>eq</b>	Exact match	<code>client.from('cities').select().eq('name', 'Doha');</code>
<b>neq</b>	Not equal	<code>client.from('cities').select().neq('country_id', 1);</code>
<b>lt / lte</b>	Less than / Less or equal	<code>client.from('cities').select().lt('population', 1000000);</code>
<b>gt / gte</b>	Greater than / Greater or equal	<code>client.from('cities').select().gte('population', 500000);</code>
<b>like</b>	Case-sensitive pattern matching used to find rows where a column contains specific text	<code>client.from('cities').select().like('name', '%Do%');</code>
<b>ilike</b>	Case-insensitive pattern matching	<code>client.from('cities').select().ilike('name', '%shire%');</code>
<b>in_</b>	Membership in a list	<code>client.from('cities').select().in_('country_id', [1, 2, 3]);</code>

# Combine Filters for Complex Queries

- This query combines multiple filters to return only students who meet all conditions

```
final students = await client
    .from('students')
    .select()
    .ilike('name', '%ali%')           // name contains "ali"
    .eq('status', 'active')           // only active students
    .gt('gpa', 3.0);                  // GPA > 3.0
```

- Find products that are out of stock or very cheap

```
final result = await supabase
    .from('products')
    .select()
    .or('quantity.eq.0,price.lt.10'); // out of stock OR cheap
```



# Best Practices

- Apply **Repository Pattern**: implement data read/write operations in repositories
- Use Providers to expose Supabase client and Repositories for easy access across the app
- **Optimize Queries**:
  - Use **projections**: `select('id, name')` instead of `select()` to reduce payload
  - Apply **server-side filtering** to retrieve only relevant data, improving application efficiency and responsiveness
  - Paginate large lists with `range(start, end)`
- **Error Handling**
  - Wrap calls in try/catch and show **user-friendly messages**
  - Log errors for debugging

## Providers to expose Supabase client and Repositories

- Use Riverpod providers to expose repositories

```
final supabaseClientProvider = Provider((ref) =>  
  Supabase.instance.client);
```

```
final todoRepositoryProvider = Provider((ref) {  
  final client = ref.watch(supabaseClientProvider);  
  return TodoRepository(client);  
});
```



# Row Level Security (RLS)



# Row Level Security (RLS)

- RLS: Ensures users can only access and modify the data they have access to
  - You can think of the RLS as automatically inserted WHERE clauses during query and mutation.

*-- Enable RLS on the table*

```
alter table todos enable row level security;
```

*-- Policy: Read own rows. The `user_id` is a built-in variable representing the current user*

```
create policy "read own" on todos
  for select using (auth.uid() = user_id);
```

*-- Policy: Modify own rows*

```
create policy "modify own" on todos
  for all using (auth.uid() = user_id);
```

# RSL Syntax

- USING filters **which existing rows** the user may see, modify or delete
- WITH CHECK restricts **which values a user may create or change to**
  - For SELECT: only USING runs
  - For INSERT: only WITH CHECK runs (no existing rows yet)
  - For UPDATE: both may apply (USING on the target row; WITH CHECK on the row after UPDATE)

-- Skeleton


```
CREATE POLICY policy_name
ON schema.table_name
TO { public | authenticated }    -- or other roles
FOR { SELECT | INSERT | UPDATE | DELETE }    -- (or: FOR ALL)
-- SELECT/UPDATE/DELETE gate: what rows the user is allowed to
select/update/delete
USING ( boolean_expression_for_existing_rows ) -- (true: FOR ALL)
-- INSERT/UPDATE gate: checks if the new/updated row complies with
the policy expression
WITH CHECK ( boolean_expression_for_new_or_updated_rows );
```

# RLS Examples



User

— create: only for herself →  
== update: only for herself →  
— read: her own posts and all published posts →



Post

-- 👁 Read Policy

-- allows anyone to read published posts

-- or the author to read their own (including drafts)

create policy "read published or own"

on posts

for select to authenticated, public

using (published = true OR author\_id = auth.uid());

-- ✎ Insert/Update/Delete Policy

-- Owner manage writes (INSERT/UPDATE/DELETE)

create policy "owner writes"

on posts

for all to authenticated

-- SELECT/UPDATE/DELETE gate: what rows the user is allowed to select/update/delete


using (author\_id = auth.uid())

-- Checks if the new/updated row complies with the policy expression (i.e., author\_id must be current user id. Users cannot change the author\_id or add for another author)

with check (author\_id = auth.uid());




# Real-Time Updates










# Real-Time Updates

- **What It Does:** Broadcasts database changes instantly to connected clients
  - Enables **instant updates** without manual refresh, improving user engagement
  - Once realtime has been enabled, the table will broadcast any changes to authorized subscribers (i.e., multiple users see updates in real-time)
- **Key Use Cases:** Live chat applications, Real-time dashboards, Multiplayer games
- **Best Practices:**
  - Subscribe only to relevant tables/rows to optimize performance
  - Integrate with state management (e.g., Riverpod providers) for better user experience (UX)






# Approach 1: Streams ( `.stream()` )

- **Purpose:** streams continuously push **all table data** to your app
  - Best for small (< 1,000 rows), frequently-changing dataset where you need the entire table in memory
- **Real-World Scenarios:**
  -  **Gaming leaderboards** (top 100 players)
  -  **Chat room participant list** (active users)
  -  **Live dashboard metrics** (system stats)
  -  **Online user presence** (who's online)
-  **Don't Use Streams When:**
  - Table has 1,000+ rows (memory issues)
  - You only need filtered subset
  - Performance/scalability critical

# Architecture Diagram - Streams



Events: INSERT → New row appears instantly  
UPDATE → Row updates instantly  
DELETE → Row disappears instantly



## Listen to Database Realtime Updates using Streams

### Postgres Stream:

```
.from('table').stream(primaryKey: ['id'])
```

### Stream for ToDo list

```
Stream<List<Todo>> observeTodos() {  
    final client = Supabase.instance.client;  
    return client  
        .from('todos')  
        .stream(primaryKey: ['id'])  
        .order('created_at', ascending: false)  
        .map((rows) =>  
            rows.map(Todo.fromJson).toList());  
}
```

# Implementation - Streams

*// 1. Repository - Stream method*

```
class MyRepository {  
    final SupabaseClient _client;  
    MyRepository(this._client);  
    // Stream all rows from table  
    Stream<List<MyModel>> observeItems() {  
        return _client.from('my_table')  
            .stream(primaryKey: ['id'])  
            .map((data) => data.map((json) => MyModel.fromJson(json)).toList());  
    }  
}
```






*// 2. Provider - StreamNotifier*

```
class MyItemsNotifier extends StreamNotifier<List<MyModel>> {  
    @override  
    Stream<List<MyModel>> build() {  
        final repository = ref.watch(myRepositoryProvider);  
        return repository.observeItems();  
    }  
}  
final myItemsProvider = StreamNotifierProvider<MyItemsNotifier, List<MyModel>>(() => MyItemsNotifier());
```


*// 3. UI - Consume the stream*

```
class MyScreen extends ConsumerWidget {  
    @override  
    Widget build(BuildContext context, WidgetRef ref) {  
        final itemsAsync = ref.watch(myItemsProvider);  
        return itemsAsync.when(  
            data: (items) => ListView.builder(  
                itemCount: items.length,  
                itemBuilder: (context, index) => ListTile(  
                    title: Text(items[index].name),  
                ),  
            ),  
            loading: () => CircularProgressIndicator(),  
            error: (error, stack) => Text('Error: $error'),  
        );  
    }  
}
```

# Approach 2: Channels ( `.channel()` )

- **Purpose:** Channels listen to **database change events** (INSERT/UPDATE/DELETE) and let you fetch only the data you need
  - Best for large datasets (**1,000+ rows**) with server-side filtering
  - Better performance and scalability
  - More control over what data is loaded
- **Real-World Scenarios:**
  -  **Todo/Task management** (millions of todos, show only user's)
  -  **E-commerce product catalog** (thousands of products, filtered view)
  -  **Email inbox** (show only unread, specific folder)
  -  **Analytics dashboard** (aggregated data)
  -  **User activity feeds** (show last 50)

# Architecture Diagram - Channels



Flow:

1. Initial load: Fetch with filters (e.g., 50 rows)
2. Setup: Subscribe to realtime channel
3. Event: INSERT/UPDATE/DELETE detected
4. Action: Re-fetch filtered data (still ~50 rows)
5. Result: UI updates with fresh data

# Implementation - Channels

```
// 1. Repository - Regular filtered query
class MyRepository { ...
    // Filtered fetch (server-side WHERE clause)
    Future<List<MyModel>> getFilteredItems({ String? searchQuery }) async {
        var query = _client.from('my_table').select( ... );
        return await query.map((json) => MyModel.fromJson(json)).toList();
    }
}


// 2. Provider - AsyncNotifier with Channel
class MyItemsNotifier extends AsyncNotifier<List<MyModel>> {
    RealtimeChannel? _channel;
    @override
    Future<List<MyModel>> build() async {
        final searchQuery = ref.watch(searchQueryProvider);
        ...
        _channel = supabase.channel('my_items_changes')
            .onPostgresChanges(
                event: PostgresChangeEvent.all,
                schema: 'public', table: 'my_table',
                callback: (payload) {
                    refresh(); // Refetch when changes detected
                },
            )
            .subscribe();
    }
    Future<void> refresh() async { ...
        state = await AsyncValue.guard(() => build());
    }
} ...

// 3. UI - Same as streams approach
```

# Which Approach to Choose?


## Quick Decision Tree

Do you have more than 1,000 rows?







# Scenario 1: Small Real-Time App


- **Requirements:** Gaming leaderboard, 100 active players, need instant updates
- **Choice:**  Streams
- **Reasoning:**
  - Small dataset, all data needed, low latency critical
- **Implementation:**

```
.stream(primaryKey: ['id'])
```

## Scenario 2: Chat Application

- **Messages:**  Channels (could be millions, paginated)
- **Participants:**  Streams (< 500 users, all displayed)
- **Reasoning:** Different requirements per feature

## Scenario 3: Social Media Feed

- **Requirements:** Millions of posts, show last 50, pagination
- **Choice:**  Channels
- **Reasoning:** Massive dataset, paginated, filtered by date
- **Implementation:** `channel() + LIMIT 50`

# Summary Recommendations

## 1. **Default Choice: Use Channels** for most production apps

- Better scalability
- More efficient
- Handles large datasets

## 2. **Use Streams Only When:**

- Dataset is small (< 1,000 rows)
- Need all data
- Simplicity is priority

## 3. **Always:**

- Add database indexes
- Enable RLS for security
- Clean up subscriptions



# References

- **Supabase Flutter Docs:**

<https://supabase.com/docs/guides/getting-started/quickstarts/flutter>

- **Supabase Database**

<https://supabase.com/docs/guides/database/overview>

- **RLS Policies:**

<https://supabase.com/docs/guides/auth/row-level-security>