

Disclaimer

- This training resource was developed to be used with the CZ ID platform
- In October, 2026, stewardship of CZ ID transitioned to UCSF and the platform was renamed to SeqtoID
- These training materials are not being actively maintained and may not reflect differences between CZ ID and SeqtoID, subsequent changes to the platform, or current methods and best practices in metagenomic sequencing and analysis




Bioinformatic Basics and mNGS Pipeline Information


Outline

- Review NGS workflow
 - Whole genome sequencing (WGS) vs metagenomic NGS (mNGS)
- Pipeline basics
- Walk through CZ ID mNGS pipeline steps

WGS vs mNGS Workflow Overview



WGS vs mNGS Workflow Overview



Raw sequencing reads: FASTQ format

READ 1 .FASTQ FILES

[illegible]

READ2 .FASTQ FILES

[illegible]

FASTQ format

Example Read1.fastq

```
@NB501961:14:HM7TLBGX2:1:11102:3233:17234 1:N:0:GATCACCA+GATCACCA
CATTCGGCTGGGTTTCGTCACCCTGCGGGAAGATGCGGGTCCAGGCGATAGAGGTGCGGAAGCATTGAAGCCCA
+
AAAAAEEEEEEEEEEEE/EEEEEEEEEEEEEEEEEEEE<EEEEEEEEEE//EAEEEEEEAA/EEE/EEAAEEEE<6/
```

1. A sequence identifier with information about the run.
2. The base calls: A, C, T, G and N.
3. A separator, which is simply a plus (+) sign.
4. The base call quality scores (coded in ASCII format)

Quality Score	Probability of Incorrect Base Call	Inferred Base Call Accuracy
10 (Q10)	1 in 10 = 10%	90%
20 (Q20)	1 in 100 = 1%	99%
30 (Q30)	1 in 1000 = 0.1%	99.9%

$$Q = -10\log_{10}(e)$$

How many reads are listed here?

File: Sample_R1.fastq

```
@NB501961:14:HM7TLBGX2:1:11102:3233:17234 1:N:0:GATCACCA+GATCACCA
CATTGGCTGGGTTTCGTCACCCTGCGGGAAGATGCGGGTCCAGGCGATAGAGGTGCGGAAGCATTGAAGCCATCTCGGCG
ATCAGTTTGATGTCTTCTTTGTAGCGACCGTAGAAGTCGACGGCTTCGTGTTTCGGGTAGTATTTN
+
AAAAEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEE<EEEEEEEE//EAEAAAAA/EEE/EEAAAAEE<6/<AEE<E<A//EEEEAAEE<EA/
<AA//EAAEAAE<E/EAEE///E<A/<AA//A<A<<A6<A//AA/E///6A#
@NB501961:14:HM7TLBGX2:1:11103:13923:13163 1:N:0:GATCACCA+GATCACCA
GAACTGGAGCTTTAGCCCGGTGATCCTGTGCCTCATTTGTATGGCTACCGCCATGGTGATGTACCTGCCATTTCTCAAAGCTTACG
AAAAACAGCTGCTGGCCAGGAGCGTGAAAACGCCGTCGGCCAGGCTGACAACGCGGCGCAGAN
+
AAAAEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEE/
EEEEEEAAAEAAEAAEAAEAAAAAAAAAAAAAAAAAAAAAEEEEEEEEEEEEEEEE<EEEEEEAE<AEAEAA<AAEAEAAE/6/A/EEEE/
EEE<AE/#
@NB501961:14:HM7TLBGX2:1:11104:15318:11334 1:N:0:GATCACCA+GATCACCA
GATAGTGCTGTTTCGCGAGCGATCGCCAGTACGCGCTCGCGCGTCTCCTGCGCCACGCGCAGCTCTTACCACGACCGTTGAGTA
CCAGGCTGGCGGTGCGCTTTGGAGACGCCCGCCAGTTCGGCGATATCTTTGATAGTTACGCGTTTGG
+
AAAAEEEEEEEEAAEEAEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEAAEEAEE<EAEE/EE/EEE<AAAAEE/
EEEEEEEEEEEE/EEE//AEE<E/EEEEAAE/A<<AEEEE/<66A///<</AA<//6AE<<6/<6
```

How do we get from here...

sample_R1.fastq

```
@NB501961:14:HM7TLBGX2:1:11102:3233:17234 1:N:0:GATCACCA+GATCACCA
CATTGGCTGGGTTTCGTCACCCTGCGGGAAGATGCGGGTCCAGGCGATAGAGGTGCGGAAGCATTGAAGCCATCTCGGCG
ATCAGTTTGATGTCTTCTTTGTAGCGACCGTAGAAGTCGACGGCTTCGTGTTGCGGTAGTATTTN
+
AAAAEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEE<EEEEEEEE//EAEAAAAA/EEE/EEAAAA<6/<AEE<E<A//EEEEAAEE<EA/
<AA//EAAEAAE<E/EAEE///E<A/<AA//A<A<<A6<A//AA/E///6A#
@NB501961:14:HM7TLBGX2:1:11103:13923:13163 1:N:0:GATCACCA+GATCACCA
GAACTGGAGCTTTAGCCCGGTGATCCTGTGCCTCATTTGTATGGCTACCGCCATGGTGATGTACCTGCCATTTCTCAAAGCTTACG
AAAAACAGCTGCTGGCCAGGAGCGTGAAAACGCCGTCGGCCAGGCTGACAACGCGGCGCAGAN
+
AAAAEEEEEEEEEEEEAAAAEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEE//
EEEEEEAAAEAAEAAEAAEAAAAEEEEEEEEEEEEEEEEAAAAEEEEEEEEEEEEEEA<EEEEEEAE<AEAEAA<AAEAAAAE/6/A/EEEE/
EEE<AE/#
@NB501961:14:HM7TLBGX2:1:11104:15318:11334 1:N:0:GATCACCA+GATCACCA
GATAGTGCTGTTTCGCGAGCGATCGCCAGTACGCGCTCGCGCTCTCCTGCGCCACGCGCAGCTCTTACCACGACCGTTGAGTA
CCAGGCTGGCGGTGCTTTGGAGACGCCCGCCAGTTCGGCGATATCTTTGATAGTTACGCGTTTGG
+
AAAAEEEEEEEEAAAAEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEEAAAAEE<EAAE/EE/EEE<AAAAE/
EEEEEEEEEEEE/EEE//AEE<E/EEEEAAE/A<<AAAAE/<66A///<</AA<//6AE<<6/<6
```

...to here?

< Medical Detectives

Patient 010 (CSF) ▾

Share

Download ▾

?

...

Metagenomic

Antimicrobial Resistance (Deprecated)

Consensus Genome

Taxon name

Q

Name Type: Scientific ▾

Background: MedicalDetectives_WaterCtrls ▾

Categories ▾

Threshold filters: 1 ▾

Read Specificity: Specific Only ▾

Annotation ▾

NT rPM >= 10 X

112 rows passing the above filters, out of 3100 total rows

CLEAR FILTERS

>

Taxon

Score ▾

Z ...

rPM

r

con...

con...

%...

L

E v...

NT NR

▾

▫ Alphavirus (1 viral species: ● 1)

72,976,252

100.0
100.0

3,650.9
3,646.7

19,344
19,322

1
1

19,139
19,139

100.0
99.9

11,671.6
2,450.2

10⁻³⁰⁵
10⁰

▫ Chikungunya virus

Known Pathogen

📍 72,976,252

100.0
100.0

3,650.9
3,646.7

19,344
19,322

1
1

19,139
19,139

100.0
99.9

11,671.6
2,450.2

10⁻³⁰⁵
10⁰

>

▫ Tetraparvovirus (1 viral species:)

46,706,236

100.0
100.0

2,366.2
2,304.6

12,537
12,211

2
1

12,102
11,987

99.1
99.6

4,677.3
896.3

10⁻²⁹⁶
10⁰

>

▫ Providencia (1 bacterial species: ● 1)

14,332,531

100.0
0.0

1,433.3
0.0

7,594
0

1
0

7,594
0

99.8
0.0

1,354.0
0.0

10⁻³⁰⁸
0

>

▫ Lactobacillus (1 bacterial species:)

2,502,625

100.0
100.0

28.9
293.5

153
1,555

7
9

79
1,475

98.6
78.8

209.0
157.7

10⁻¹⁰⁸
10⁻¹

>

▫ Rothia (1 bacterial species:)

2,364,849

100.0
100.0

238.4
5.5

1,263
29

6
0

1,127
0

96.5
97.3


2,086.8
45.7

10⁻²⁷²
10⁻¹⁶



Pipeline Overview

Raw reads



Medical Detectives

Patient 010 (CSF) ▾

Metagenomic

Antimicrobial Resistance (Deprecated)

Consensus Genome

Taxon name

Q

Name Type: Scientific ▾

Background: MedicalDetectives_WaterCtrls ▾

Categories ▾

Threshold filters: 1 ▾

Read Specificity: Specific Only ▾

Annotation ▾

NT rPM >= 10 X

112 rows passing the above filters, out of 3100 total rows

CLEAR FILTERS

>

Taxon

Score ▾

Z ...

rPM

r

con...

con...

%...

L

E v...

NT NR

▾

▾ Alphavirus (1 viral species: ● 1)

72,976,252

100.0

3,650.9

19,344

1

19,139

100.0

11,671.6

10⁻³⁰⁵

▾

▾ Chikungunya virus Known Pathogen

72,976,252

100.0

3,650.9

19,344

1

19,139

100.0

11,671.6

10⁻³⁰⁵

>

▾ Tetraparvovirus (1 viral species:)

46,706,236

100.0

2,366.2

12,537

2

12,102

99.1

4,677.3

10⁻²⁹⁶

>

▾ Providencia (1 bacterial species: ● 1)

14,332,531

100.0

1,433.3

7,594

1

7,594

99.8

1,354.0

10⁻³⁰⁸

>

▾ Lactobacillus (1 bacterial species:)

2,502,625

100.0

28.9

153

7

79

98.6

209.0

10⁻¹⁰⁸

>

▾ Rothia (1 bacterial species:)

2,364,849

100.0

238.4

1,263

6

1,127

96.5

2,086.8

10⁻²⁷²

Pipeline Goal


- Assign quality filtered reads to taxa by mapping or aligning against reference databases
- Assemble contigs and map reads to contigs to increase support for identified taxa (assembly-based alignment)

Pipeline Basics

- Assembly
- Sequence alignment against reference database(s)
- Reference database(s)

Sequence assembly into contigs

Assembly goal: Merge sequence reads into contigs to form longer DNA sequences and reconstruct the original sequence



Sequence assembly into contigs

Assembly goal: Merge sequence reads into contigs to form longer DNA sequences and reconstruct the original sequence

Microbial Genome Sequence



Sequencing Reads



Assembled Contigs



ATGGACTCATTTCGGTCG

TGATAGTTCCTAGATAC

TCGAATAGTAGCCTGAT

ATGGACTCATTTCGGTCGAATAGTAGCCTGATAGTTCCTAGATAC

Sequence alignment against database

Alignment goal: Query unknown sequences against a reference database of known sequences to identify the microbe of origin

Unknown sequence



Database of known sequences

```
> seq_1, unknown  
CTCATTCGGT
```

```
> species A  
GCCTCGATCTGTAGCCT
```

```
> species B  
ATGGACTCATTGGGTCG
```

```
> species C  
TGCTAAATCGCGCCCTA
```

```
> species D  
TGGCTAAGTCATATAGC
```

Sequence alignment against database

Alignment goal: Query unknown sequences against a database of known sequences to identify the microbe of origin

Unknown sequence



Database of known sequences

Sequence Alignment

```
> seq_1, unknown
CTCATTCGGT
```

```
> species A
GCCTCGATCTGTAGCCT
```

```
> species B
ATGGACTCATTCGGTCG
```

```
> species C
TGCTAAATCGCGCCCTA
```

```
> species D
TGGCTAAGTCATATAGC
```

```
> species A
GCCTCGATCTGTAGCCT
```

```
||| |||
CTCATTCGGT
```

```
> species B
ATGGACTCATTCGGTCG
```

```
|||||||
CTCATTCGGT
```

```
> species C
TGCTAAATCGCGCCCTA
```


```
||| |||
CTCATTCGGT
```

```
> species D
TGGCTAAGTCATATAGC
```

```
|||| |
CTCATTCGGT
```

Sequence alignment against database

Alignment goal: Query unknown sequences against a database of known sequences to identify the microbe of origin



CZ ID uses NCBI reference databases

NCBI houses a series of databases containing annotated collections of publicly available sequences

	NT Database	NR Database
What does NT/NR mean?	NT = nucleotide	NR = non-redundant protein

CZ ID uses NCBI reference databases

NCBI houses a series of databases containing annotated collections of publicly available sequences

	NT Database	NR Database
What does NT/NR mean?	NT = nucleotide	NR = non-redundant protein
What is in the database?	Contains all nucleotide sequences (RefSeq records plus all GenBank sequences except for those from the EST, GSS, STS and HTG divisions).	Contains non-redundant set of all CDS translations from GenBank along with all RefSeq, UniProtKB/Swiss-Prot, PDB and PRF proteins. Note: does not contain rRNA sequences given that these do not encode proteins

CZ ID uses NCBI reference databases

NCBI houses a series of databases containing annotated collections of all publicly available sequences (GenBank)

	NT Database	NR Database
What does NT/NR mean?	NT = nucleotide	NR = non-redundant protein
What is in the database?	Contains nucleotide sequences (RefSeq records plus all GenBank sequences except for those from the EST, GSS, STS and HTG divisions).	Contains non-redundant set of coding sequence translations from GenBank along with all RefSeq, UniProtKB/Swiss-Prot, PDB and PRF proteins. Note: does not contain rRNA sequences given that these do not encode proteins
How does it influence analysis?	NT hits tend to be more accurate for most organisms (bacteria, eukaryotes, viruses with close relatives in the DB)	NR alignments are especially good for detecting divergent viruses , since mutations in the NT sequence accumulate faster than the amino acid sequence

Where would you see the following *E. coli* matches?

E. coli polymerase

E. coli 16S rRNA

	NT Database	NR Database
Match (or hit) to <i>E. coli</i> based on...		

Where would you see the following *E. coli* matches?

E. coli polymerase

E. coli 16S rRNA

	NT Database	NR Database
Match (or hit) to <i>E. coli</i> based on...	16S rRNA Polymerase	Polymerase

CZ ID mNGS Pipeline Walkthrough

Raw reads



Raw reads




Step 1: QC and Host Filtering

- Truncate to 150 million reads (PE data) or 75 million reads (SE data)
- Filter out low quality reads, low complexity reads, and adapters ([fastp](#))
- Host read removal ([Bowtie](#) followed by [HISAT2](#))
- Human read removal ([Bowtie](#) followed by [HISAT2](#))
- Collapse duplicate reads ([CZID-dedup](#))
- Subsampling to 2 million PE reads or 1 million SE




Step 2: Read alignment against NCBI databases

- Reads are mapped against nucleotide (**NT**) and protein (**NR**) databases to obtain a preliminary accession for each read ([minimap2](#) and [DIAMOND](#)).
- Generate custom BLAST database containing all taxa identified as preliminary accessions.




Step 3: Assemble contigs and map reads to contigs

- Assemble reads into contigs using de novo assembly ([SPAdes](#)).
- Align reads to assembled contigs ([Bowtie2](#)).




Step 4: Align contigs against custom database

- Align contigs against database of preliminary accessions generated in the previous step (BLAST)



Step 5: Mapping to taxa

- Assign each read a final accession based on:
 1. Contig accession, or
 2. Initial read accession (if the read did not assemble into a contig)
- Assign each contig/unassembled read to a taxon using NCBI taxon IDs
- Compute statistics (e.g., reads per million for each taxon)



[Pipeline visualization](#)

CZ ID GitHub Repositories:

- [czid-web](#) - Frontend portal
- [czid-workflows](#) - Bioinformatics workflows
- [czid-cli](#) - Command line upload interface
- [czid-bench](#) - Pipeline benchmarking tools

Let's talk about QC next...