| BME 3400 | <b>Midterm</b> | Exam #3 | November | 24, 2009 |
|----------|----------------|---------|----------|----------|
|----------|----------------|---------|----------|----------|

Name: SOLUTION

This is a closed-book exam. 1 8.5x11" page of handwritten notes allowed. Calculators are allowed, but integrals should be solved before numbers are plugged in.

Show all your work! Free-body diagrams must be present and correct for full credit. Plug in numbers only at the end of a problem.

## HONOR CODE

The conditions of this examination are subject to the Georgia Institute of Technology Academic Honor Code.

I pledge that the work in this exam represents my own, original work. I have not communicated with anyone about the contents of this exam, nor participated in or observed any conduct prohibited by the Honor Code.

| Signature  |  |
|------------|--|
| arithornia |  |
| Signature  |  |
|            |  |

## Problem (50 points)

You are contracted by Burton to build a new snowboard. You build the board with 140 bald-cypress strips of 2 mm width and 6 mm height (Figure B). Bald-cypress has an elastic modulus of 9.7 GPa and a maximum allowable stress of 42 MPa.

- How much does the board deflect under the rider's feet in this maneuver where the rider is balanced on a rail midway between the feet. *Hint*: place x=0 at the rail.
- (Extra credit) How much does the board deflect at the end of the board?

Figure A: Snowboarder riding a rail





Figure B: Cross section of snowboard

V'(0)=0 =0 C1=0

V(0)=0 =0 C,=0



$$E = 9.7 \text{ Gpa}$$


$$I = \frac{6h^3}{12} = \frac{(6.280 \text{ m})(0.006 \text{ m})^3}{12} = 5.04 \times 10^{-7} \text{ m}^2$$

$$W = 80 \text{ kg} \times 9.8 \text{ m}/\text{s}^2 = 784 \text{ N}$$

$$\frac{\nabla(0.2m)}{4} = \left[ -\frac{(784 \text{ N})(0.2m)(0.2m)^2}{4} + \frac{(784 \text{ M})(0.2)^3}{12} \right] \\
-\frac{4}{9.7 \times 10^9} \quad \text{Pa} \times 5.04 \times 10^{-9} \text{ m} \times 4$$

- - 0.021 m

EXTRA CLEDIT



d < x < L M = 0  $EIV_1(x) = \int \int M dx$   $EIV_2(x) = C_3$   $EIV_3(x) = C_3 \times + C_4$ 

Board continues to deflect downward w/o any curvature since M=0
for dcxcL

compute a second curve  $V_2(L) = \frac{det}{end}$   $V_1(0.2) = V_2(0.2) = -0.021 m$  $V_1'(0.2) = V_2'(0.2) =$ 


Vi(0,2) = = [ (-wd x + w x2) = -0.16

EIV, (0.2) = EIV, (1.2) = C3 = EI(-0.16)

[I 7, (0.2)= EI V2 (0.2) = (3 X+ C4=EI fo, orl)

C4- E1(-0.021) - E1(-0.16)(0.20m) = 0.011

Veno: V1(0.8m) = (310.8) + C4 = -0.118m



J'(x=a)

$$y'(x=d) = \frac{Wd^{3}}{2EI} \left[ \frac{1}{2} - \frac{3}{6} \right] = -\frac{Wd^{3}}{6EI} \left[ \frac{1}{2} - \frac{3}{6} \right] = -\frac{784 \, \text{N} (0.2 \, \text{m})^{3}}{6(9.7 \, \text{e}^{9} \, \text{p}_{\text{n}})(5.04 \, \text{e}^{9} \, \text{m}^{3})}$$

$$y'(x=d) = \frac{Wd^{2}}{2EI} \left[ \frac{1}{2} - 1 \right] = -\frac{Wd^{2}}{4EI} \left[ \frac{1}{2} - \frac{3}{6} \right] = -\frac{3}{6(9.7 \, \text{e}^{9} \, \text{p}_{\text{n}})(5.04 \, \text{e}^{9} \, \text{m}^{3})}$$

$$y''(x=L) = y(x=d) + (L-d), y'(x=d)$$

$$y''(x=L) = -\frac{Wd^{2}}{EI} \left[ \frac{d}{6} + \frac{L-d}{4} \right] = -\frac{Wd^{2}}{EI} \left[ \frac{L}{4} - \frac{d}{12} \right] = -\frac{Wd^{2}}{12EI} (3L-d)$$

$$= -(784N(0.2m)^{2} (3.0.8m - 0.2m))$$

$$deflection$$

$$at end is = -0.118m$$

## Problem 1 (50 points)

When snowboarding on a flat run, the edge of the board can get caught on the snow, causing the rider to rapidly fall backwards. Concussions are likely if the velocity of the head exceeds 7 m/s on impact.

Speed

The rider is 1.8 m tall, 80 kg, and has a radius of gyration about the center of mass, G, of 0.2 m. He falls rigidly, and the edge of the board does not move relative to the ground.

Will he likely get a concussion if his initial angular velocity in the upright position is  $\omega = 2$  rad/s k?

FBD

mg of Fey

KIN Jay man

 $\sum M/\xi = mgh sin\theta = I_{G}d + mat.h$   $mghsin\theta = k^{2}md + m.hd.h$   $\alpha = mghsin\theta$   $K^{2}m + mh^{2}$   $\int d\theta = \int wdw$   $W_{A}$   $Sin \Phi d\theta = \frac{1}{2}w^{2}|_{W_{A}}$ 

$$\frac{gh}{k^2+h^2}\left(-\cos\theta\right)\Big|_{k^2+h^2}^{T/2} = \frac{1}{2}w_{\xi} - \frac{1}{2}w_{\lambda}$$

1.8 m Im

E

PLAN

ZM/E = IGX + P x māg

SDINE X(D), Integ. for Wf

STILL

STIL

h=1 m  $Ig=k^2m k=0.2m$  At=kX

$$\frac{1}{2}\omega_{f} = \frac{gh}{k^{2}+h^{2}} + \frac{1}{2}\omega_{J}^{2} = \frac{(9.8 \text{ m/s}^{2})(1\text{ m})}{(0.2\text{m})^{2}+(1\text{m})^{2}} + \frac{1}{2}(2\text{ rad/s})^{2}$$

$$\frac{1}{2}\omega_{f}^{2} = 11.42$$

$$\omega_{f} = \sqrt{2(11.42)} = 4.8 \text{ rad/s}$$

$$V_{H} = \omega_{f} \cdot l = (4.8 \text{ rad/s})(1.8\text{ m})$$