ETSI TS 129 571 V15.3.0 (2019-04)



5G; 5G System; Common Data Types for Service Based Interfaces; Stage 3 (3GPP TS 29.571 version 15.3.0 Release 15)





Reference RTS/TSGC-0429571vf30 Keywords 5G

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: <u>http://www.etsi.org/standards-search</u>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommitteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019. All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M[™] logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intelle	ctual Property Rights	2
Forew	ord	2
Modal	verbs terminology	2
	ord	
	Scope	
2	References	7
3	Definitions and abbreviations	8
3.1	Definitions	
3.2	Abbreviations	8
4	Overview	8
5	Common Data Types	8
5.1	Introduction	
5.2	Data Types for Generic Usage	
5.2.1	Introduction	
5.2.2	Simple Data Types	
5.2.3	Enumerations	
5.2.3.1	Enumeration: PatchOperation	
5.2.3.2	•	
5.2.3.3		
5.2.4	Structured Data Types	
5.2.4.1	Type: ProblemDetails	
5.2.4.2	• 1	
5.2.4.3		
5.2.4.4	· · · · · · · · · · · · · · · · · · ·	
5.2.4.5	V 1	
5.2.4.6		
5.2.4.7	V 1	
5.2.4.8	· · · · · · · · · · · · · · · · · · ·	
5.2.4.9		
5.2.4.1	· · · · · · · · · · · · · · · · · · ·	
5.2.4.1		
5.2.4.1	- Jr	
5.2.4.1	71	
5.2.4.1	· · · · · · · · · · · · · · · · · · ·	
5.2.4.1		
5.3	Data Types related to Subscription, Identification and Numbering	17
5.3.1	Introduction	
5.3.2	Simple Data Types	
5.3.3	Enumerations	
5.3.4	Structured Data Types	
5.3.4.1	Type: Guami	
5.3.4.2		
5.3.4.3	71	
5.4	Data Types related to 5G Network	
5.4.1	Introduction	
5.4.2	Simple Data Types	
5.4.3	Enumerations	
5.4.3.1	Enumeration: AccessType	
5.4.3.2	7.5	
5.4.3.3	Enumeration: PduSessionType	
5.4.3.4	**	
5.4.3.5		
5.4.3.6		
5.4.3.7		

5.4.3.8	Enumeration: RestrictionType	
5.4.3.9	Enumeration: CoreNetworkType	26
5.4.3.10	Enumeration: AccessTypeRm	26
5.4.3.11	Enumeration: RatTypeRm	26
5.4.3.12	Enumeration: PduSessionTypeRm	26
5.4.3.13	Enumeration: UpIntegrityRm	26
5.4.3.14	Enumeration: UpConfidentialityRm	26
5.4.3.15	Enumeration: SscModeRm	26
5.4.3.17	Enumeration: DnaiChangeTypeRm	
5.4.3.18	Enumeration: RestrictionTypeRm	
5.4.3.19	Enumeration: CoreNetworkType	
5.4.3.20	Enumeration: PresenceState	
5.4.4	Structured Data Types	
5.4.4.1	Type: SubscribedDefaultQos	
5.4.4.2	Type: Snssai	
5.4.4.3	Type: PlmnId	
5.4.4.4	Type: Tai	
5.4.4.5	Type: Ecgi	
5.4.4.6	Type: Ncgi	
5.4.4.7	Type: UserLocation	
	• •	
5.4.4.8	Type: EutraLocation	
5.4.4.9	Type: NrLocation	
5.4.4.10	Type: N3gaLocation	
5.4.4.11	Type: UpSecurity	
5.4.4.12	Type: NgApCause	
5.4.4.13	Type: BackupAmfInfo	
5.4.4.14	Type: RefToBinaryData	
5.4.4.15	Type RouteToLocation	
5.4.4.16	Type RouteInformation	
5.4.4.17	Type: Area	
5.4.4.18	Type: ServiceAreaRestriction	
5.4.4.19	Type: PlmnIdRm	
5.4.4.20	Type: TaiRm	33
5.4.4.21	Type: EcgiRm	33
5.4.4.22	Type: NcgiRm	33
5.4.4.23	Type: EutraLocationRm	33
5.4.4.24	Type: NrLocationRm	33
5.4.4.25	Type: UpSecurityRm	
5.4.4.26	Type: RefToBinaryDataRm	
5.4.4.27	Type: PresenceInfo	
5.4.4.28	Type: GlobalRanNodeId	
5.4.4.29	Type: GNbId	
5.4.4.30	Type: PresenceInfoRm	
5.5	Data Types related to 5G QoS	
5.5.1	Introduction	
5.5.2	Simple Data Types	
5.5.3	Enumerations	
5.5.3.1	Enumeration: PreemptionCapability	
5.5.3.2		
	Enumeration: PreemptionVulnerability	
5.5.3.3	Enumeration: ReflectiveQosAttribute	
5.5.3.4	Void	
5.5.3.5	Enumeration: NotificationControl	
5.5.3.6	Enumeration: QosResourceType	
5.5.3.7	Enumeration: PreemptionCapabilityRm	
5.5.3.8	Enumeration: PreemptionVulnerabilityRm	
5.5.3.9	Enumeration: ReflectiveQosAttributeRm	
5.5.3.10	Enumeration: NotificationControlRm	
5.5.3.11	Enumeration: QosResourceTypeRm	
5.5.3.12	Enumeration: AdditionalQosFlowInfo	38
5.5.4	Structured Data Types	39
5.5.4.1	Type: Arp	39
5.5.4.2	Type: Ambr	

5.5.4.3	Type: Dynamic5Qi	39	
5.5.4.4	Type: NonDynamic5Qi	40	
5.5.4.5	Type: ArpRm	40	
5.5.4.6	Type: AmbrRm	40	
5.6	Data Types related to 5G Trace		
5.6.1	Introduction		
5.6.2	Simple Data Types	40	
5.6.3	Enumerations	40	
5.6.3.1	Enumeration: TraceDepth	40	
5.6.3.2	Enumeration: TraceDepthRm	41	
5.6.4	Structured Data Types	42	
5.6.4.1	Type: TraceData	42	
5.7	Data Types related to 5G Operator Determined Barring	44	
5.7.1	Introduction	44	
5.7.2	Simple Data Types	44	
5.7.3	Enumerations	44	
5.7.3.1	Enumeration: RoamingOdb		
5.7.4.1	Enumeration: OdbPacketServices		
5.7.4	Structured Data Types	45	
5.7.4.1	Type: OdbData	45	
5.8	Data Types related to Charging		
5.8.1	Introduction		
5.8.2	Simple Data Types		
5.8.3	Enumerations		
5.8.4	Structured Data Types		
5.8.4.1	Type: SecondaryRatUsageReport		
5.8.4.2	Type: QoSFlowUsageReport	45	
Annex .	A (normative): OpenAPI specification	46	
A.1	General		
A.2	Data related to Common Data Types	46	
Annex :	B (informative): Change history	69	
History	· · · · · · · · · · · · · · · · · · ·	72	

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies the stage 3 protocol and data model for common data types that are used or may be expected to be used by multiple Service Based Interface APIs supported by the same or different Network Function(s).

The Principles and Guidelines for Services Definition are specified in 3GPP TS 29.501 [2].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1]	3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
[2]	3GPP TS 29.501: "5G System; Principles and Guidelines for Services Definition; Stage 3".
[3]	OpenAPI: "OpenAPI 3.0.0 Specification", https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.0.md .
[4]	IETF RFC 1166: "Internet Numbers".
[5]	IETF RFC 5952: "A recommendation for IPv6 address text representation".
[6]	IETF RFC 3986: "Uniform Resource Identifier (URI): Generic Syntax".
[7]	3GPP TS 23.003: "Numbering, addressing and identification".
[8]	3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
[9]	IETF RFC 7807: "Problem Details for HTTP APIs".
[10]	IETF RFC 3339: "Date and Time on the Internet: Timestamps".
[11]	3GPP TS 38.413: "NG-RAN; NG Application Protocol (NGAP) ".
[12]	IETF RFC 6901: "JavaScript Object Notation (JSON) Pointer".
[13]	3GPP TS 24.007: " Mobile radio interface signalling layer 3; General aspects".
[14]	IETF RFC 6902: "JavaScript Object Notation (JSON) Patch".
[15]	IETF RFC 4122: "A Universally Unique IDentifier (UUID) URN Namespace"
[16]	3GPP TS 36.413: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 Application Protocol (S1AP)".
[17]	IETF RFC 7042: "IANA Considerations and IETF Protocol and Documentation Usage for IEEE 802 Parameters".
[18]	IETF RFC 6733: "Diameter Base Protocol".
[19]	3GPP TS 32.422: "Telecommunication management; Subscriber and equipment trace; Trace control and configuration management".
[20]	3GPP TS 24.501: "Non-Access-Stratum (NAS) Protocol for 5G System (5GS); Stage 3".

[21]	3GPP TS 29.002: "Mobile Application Part (MAP) specification".
[22]	Void
[23]	3GPP TS 23.032: "Universal Geographical Area Description (GAD)".
[24]	ITU-T Recommendation Q.763 (1999): "Specifications of Signalling System No.7; Formats and codes".
[25]	3GPP TS 29.500: "5G System; Technical Realization of Service Based Architecture; Stage 3".
[26]	3GPP TS 23.015: "Technical Realization of Operator Determined Barring".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

5GC 5G Core Network	
DNAI Data Network Access Identifier	
GPSI Generic Public Subscription Identifi	er
GUAMI Globally Unique AMF Identifier	
PEI Permanent Equipment Identifier	
SBI Service Based Interface	
SUPI Subscription Permanent Identifier	

4 Overview

For the different 5GC SBI API, data types shall be defined. Data types identified as common data types shall be defined in this Technical specification and should be referenced from individual 5GC SBI API specifications.

Data types applicable or intended to be applicable to several 5GC SBI API specifications should be interpreted as common data types.

5 Common Data Types

5.1 Introduction

In the following subclauses, common data types for the following areas are defined:

- Data types for generic usage;
- Data types for Subscription, Identification and Numbering;
- Data types related to 5G Network;
- Data types related to 5G QoS;
- Data types related to 5G Trace;
- Data types related to 5G ODBs.

5.2 Data Types for Generic Usage

5.2.1 Introduction

This clause defines common data types for generic usage.

5.2.2 Simple Data Types

This subclause specifies common simple data types.

Table 5.2.2-1: Simple Data Types

Type Name	Type Definition	Description
Binary	string	String with format "binary" as defined in OpenAPI Specification [3]
BinaryRm	string	This data type is defined in the same way as the "Binary" data
		type, but with the OpenAPI "nullable: true" property.
Bytes	string	String with format "byte" as defined in OpenAPI Specification [3],
BytesRm	otring	i.e, base64-encoded characters, This data type is defined in the same way as the "Bytes" data
byteskiii	string	type, but with the OpenAPI "nullable: true" property.
Date	string	String with format "date" as defined in OpenAPI Specification [3]
DateRm	string	This data type is defined in the same way as the "Date" data type,
		but with the OpenAPI "nullable: true" property.
DateTime	string	String with format "date-time" as defined in
Data Tima - Day	-tois-s	OpenAPI Specification [3]
DateTimeRm	string	This data type is defined in the same way as the "DateTime" data type, but with the OpenAPI "nullable: true" property.
DiameterIdentity	string	String containing a Diameter Identity, according to clause 4.3 of
2.0		IETF RFC 6733 [18].
		Pattern: '^([A-Za-z0-9]+(-[A-Za-z0-9]+).)+[a-z]{2,}\$'
DiameterIdentityRm	string	This data type is defined in the same way as the
		"DiameterIdentity" data type, but with the OpenAPI "nullable: true"
Double	number	property. Number with format "double" as defined in
Double	Humber	OpenAPI Specification [3]
DoubleRm	number	This data type is defined in the same way as the "Double" data
		type, but with the OpenAPI "nullable: true" property.
DurationSec	integer	Unsigned integer identifying a period of time in units of seconds.
DurationSecRm	integer	This data type is defined in the same way as the "DurationSec"
Float	numbar	data type, but with the OpenAPI "nullable: true" property. Number with format "float" as defined in
Float	number	OpenAPI Specification [3]
FloatRm	number	This data type is defined in the same way as the "Float" data
		type, but with the OpenAPI "nullable: true" property.
Uint16	integer	Unsigned 16-bit integers, i.e. only value between 0 and 65535 are
		permissible.
Uint16Rm	integer	This data type is defined in the same way as the "Uint16" data
Int32	integer	type, but with the OpenAPI "nullable: true" property. Integer with format "int32" as defined in OpenAPI Specification [3]
Int32Rm	integer	This data type is defined in the same way as the "Int32" data
	oge.	type, but with the OpenAPI "nullable: true" property.
Int64	integer	Integer with format "int64" as defined in OpenAPI Specification [3]
Int64Rm	integer	This data type is defined in the same way as the "Int64" data
la d A A al ala	- tois -	type, but with the OpenAPI "nullable: true" property.
lpv4Addr	string	String identifying a IPv4 address formatted in the "dotted decimal" notation as defined in in IETF RFC 1166 [4].
		Pattern: '^(([0-9] [1-9][0-9] 1[0-9] 2[0-4][0-9] 25[0-5])\.){3}([0-
		9][1-9][0-9][1[0-9][0-9][2[0-4][0-9][25[0-5])\$'
lpv4AddrRm	string	This data type is defined in the same way as the "Ipv4Addr" data
		type, but with the OpenAPI "nullable: true" property.
lpv6Addr	string	String identifying an IPv6 address formatted according to clause 4
		of IETF RFC 5952 [5]. The mixed IPv4 IPv6 notation according to clause 5 of IETF RFC 5952 [5] shall not be used.
		Pattern: '^((: (0? ([1-9a-f][0-9a-f](0,3}))):)((0? ([1-9a-f][0-9a-
		f]{0,3})):){0,6}(: (0? ([1-9a-f][0-9a-f]{0,3})))\$'
		and
InveA ddrD	otring	Pattern: '^((([^:]+:){7}([^:]+)) ((([^:]+:)*[^:]+)?::(([^:]+:)*[^:]+)?))\$'
Ipv6AddrRm	string	This data type is defined in the same way as the "Ipv6Addr" data type, but with the OpenAPI "nullable: true" property.
Ipv6Prefix	string	String identifying an IPv6 address prefix formatted according to
	9	clause 4 of IETF RFC 5952 [5].
		Pattern: '^((: (0? ([1-9a-f][0-9a-f]{0,3}))):)((0? ([1-9a-f][0-9a-
		f[{0,3})):\{0,6}(: (0? ([1-9a-f][0-9a-f]{0,3})))(\(([0-9]) ([0-9]{2})) (1[0-
		1][0-9]) (12[0-8])))\$' and
		Pattern:
		'^((([^:]+:){7}([^:]+)) ((([^:]+:)*[^:]+)?::(([^:]+:)*[^:]+)?))(\/.+)\$'

Ipv6PrefixRm	string	This data type is defined in the same way as the "Ipv6Prefix" data type, but with the OpenAPI "nullable: true" property.
MacAddr48	string	String identifying a MAC address formatted in the hexadecimal notation according to subclause 1.1 and subclause 2.1 of
		IETF RFC 7042 [17]. Pattern: '^([0-9a-fA-F]{2})((-[0-9a-fA-F]{2}){5})\$'
MacAddr48Rm	string	This data type is defined in the same way as the "MacAddr48"
	J	data type, but with the OpenAPI "nullable: true" property.
SupportedFeatures	string	A string used to indicate the features supported by an API that is used as defined in subclause 6.6 in 3GPP TS 29.500 [1]. The string shall contain a bitmask indicating supported features in hexadecimal representation: Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent the support of 4 features as described in table 5.2.2-3. The most significant character representing the highest-numbered features shall appear first in the string, and the character representing features 1 to 4 shall appear last in the string. The list of features and their numbering (starting with 1) are defined separately for each API. If the string contains a lower number of characters than there are defined features for an API,
		all features that would be represented by characters that are not present in the string are not supported.
Uinteger	integer	Unsigned Integer, i.e. only value 0 and integers above 0 are permissible.
UintegerRm	integer	This data type is defined in the same way as the "Uinteger" data type, but with the OpenAPI "nullable: true" property.
Uint32	integer	Unsigned 32-bit integers, i.e. only value 0 and 32-bit integers above 0 are permissible.
Uint32Rm	integer	This data type is defined in the same way as the "UInt32" data type, but with the OpenAPI "nullable: true" property.
Uint64	integer	Unsigned 64-bit integers, i.e. only value 0 and 64-bit integers above 0 are permissible.
Uint64Rm	integer	This data type is defined in the same way as the "Uint64" data type, but with the OpenAPI "nullable: true" property.
Uri	string	String providing an URI formatted according to IETF RFC 3986 [6].
UriRm	string	This data type is defined in the same way as the "Uri" data type, but with the OpenAPI "nullable: true" property.
VarUeld	string	String represents the SUPI or GPSI. Pattern: "^(imsi-[0-9]{5,15} nai+ msisdn-[0-9]{5,15} extid- [^@]+@[^@]+ .+)\$".
VarUeldRm	string	This data type is defined in the same way as the "VarUeld" data type, but with the OpenAPI "nullable: true" property.
TimeZone	string	String with format " <time-numoffset>" optionally appended by "<daylightsavingtime>", where:</daylightsavingtime></time-numoffset>
		 - <time-numoffset> shall represent the time zone adjusted for daylight saving time and be encoded as time-numoffset as defined in subclause 5.6 of IETF RFC 3339 [10];</time-numoffset>
		 - <daylightsavingtime> shall represent the adjustment that has been made and shall be encoded as "+1" or "+2" for a +1 or +2 hours adjustment.</daylightsavingtime>
		Example: "-08:00+1" (for 8 hours behind UTC, +1 hour adjustment for Daylight Saving Time).
TimeZoneRm	string	This data type is defined in the same way as the "TimeZone" data type, but with the OpenAPI "nullable: true" property.

Table 5.2.2-2: Reused OpenAPI data types

Type Name		Description
boolean		As defined in OpenAPI Specification [3]
integer		As defined in OpenAPI Specification [3]
number		As defined in OpenAPI Specification [3]
string		As defined in OpenAPI Specification [3]
NOTE Data types defined in OpenAPI Specification [3] do not follow the		
UpperCamel convention for data types in 3GPP TS 29.501 [2]		

Table 5.2.2-3: Meaning of a Hexadecimal Character in SupportedFeatures Type

Character	Feature n+3 supported	Feature n+2 supported	Feature n+1 supported	Feature n supported
"0"	no	no	no	no
"1"	no	no	no	yes
"2"	no	no	yes	no
"3"	no	no	yes	yes
"4"	no	yes	no	no
"5"	no	yes	no	yes
"6"	no	yes	yes	no
"7"	no	yes	yes	yes
"8"	yes	no	no	no
"9"	yes	no	no	yes
"A"	yes	no	yes	no
"B"	yes	no	yes	yes
"C"	yes	yes	no	no
"D"	yes	yes	no	yes
"E"	yes	yes	yes	no
"F"	yes	yes	yes	yes
NOTE 1 "r	NOTE 1 "n" shall be i * 4 + 1, where "i" is zero or a natural number, i.e			
	permissible values of "n" are 1, 5, 9,			
NOTE 2 If	NOTE 2 If a feature is not defined, it shall be indicated with value "no".			

For example, if only the first feature defined in the feature list is set to 1, the corresponding SupportedFeatures attribute would have a value of "1", or "001" (any amount of 0's to the left of the 1 would result into an equivalent feature list). If we have 32 features defined, and only the last feature in a feature list is set to 1, the corresponding SupportedFeatures attribute would have a value of "80000000".

5.2.3 Enumerations

5.2.3.1 Enumeration: PatchOperation

Table 5.2.3.1-1: Enumeration PatchOperation

Enumeration value	Description
"add"	Add operation as defined in IETF RFC 6902 [14].
"copy"	Copy operation as defined in IETF RFC 6902 [14].
"move"	Move operation as defined in IETF RFC 6902 [14].
"remove"	Remove operation as defined in IETF RFC 6902 [14].
"replace"	Replace operation as defined in IETF RFC 6902 [14].
"test"	Test operation as defined in IETF RFC 6902 [14].

5.2.3.2 Enumeration: UriScheme

Table 5.2.3.2-1: Enumeration UriScheme

Enumeration value	Description
"http"	HTTP URI scheme
"https"	HTTPS URI scheme

5.2.3.3 Enumeration: ChangeType

Table 5.2.3.3-1: Enumeration ChangeType

Enumeration value	Description
"ADD"	This value indicates new attribute has been added to the resource
"MOVE"	This value indicates existing attribute has been moved to a different path in the resource.
"REMOVE"	This value indicates existing attribute has been deleted from the resource.
"REPLACE"	This value indicates existing attribute has been updated with new value.

5.2.4 Structured Data Types

5.2.4.1 Type: ProblemDetails

Table 5.2.4-1: Definition of type ProblemDetails

Attribute name	Data type	Р	Cardinality	Description
type	Uri	0	01	A URI reference according to IETF RFC 3986 [6] that identifies the problem type.
title	string	0	01	A short, human-readable summary of the problem type. It should not change from occurrence to occurrence of the problem.
status	integer	0	01	The HTTP status code for this occurrence of the problem.
detail	string	0	01	A human-readable explanation specific to this occurrence of the problem.
instance	Uri	0	01	A URI reference that identifies the specific occurrence of the problem.
cause	string	С	01	A machine-readable application error cause specific to this occurrence of the problem This IE should be present and provide application-related error information, if available.
invalidParams	array(InvalidPara m)	0	1N	Description of invalid parameters, for a request rejected due to invalid parameters.

NOTE 1: See IETF RFC 7807 [9] for detailed information and guidance for each attribute, and 3GPP TS 29.501 [2] for guidelines on error handling support by 5GC SBI APIs.

5.2.4.2 Type: Link

Table 5.2.4.2-1: Definition of type link

Attribute name	Data type	Р	Cardinality	Description
href	Uri	М	1	It contains the LIRI of the linked resource

NOTE 2: Additional attributes may be defined per API.

5.2.4.3 Type PatchItem

Table 5.2.4.3-1: Definition of type PatchItem

Attribute name	Data type	P	Cardinality	Description	Applicability
ор	PatchOperation	М	1	This IE indicates the patch operation as defined in IETF RFC 6902 [14] to be performed on resource.	
path	string	M	1	This IE contains a JSON pointer value (as defined in IETF RFC 6901 [12]) that references a location of a resource on which the patch operation shall be performed.	
from	string	С	01	This IE indicates the path of the source JSON element (according to JSON Pointer syntax) being moved or copied to the location indicated by the "path" attribute. It shall be present if the patch operation is "move" or "copy".	
value	Any type	С	01	This IE indicates a new value for the resource specified in the path attribute. It shall be present if the patch operation is "add", "replace" or "test". The data type of this attribute shall be the same as the type of the resource on which the patch operation shall be performed. The null value shall be allowed.	

5.2.4.4 Type: LinksValueSchema

Table 5.2.4.4-1: Definition of type LinksValueSchema as a list of mutually exclusive alternatives

Data type	Cardinality	Description
array(Link)	1N	Array of links
Link	1	link

5.2.4.5 Type: SelfLink

Table 5.2.4.5-1: Definition of type SelfLink

Attribute name	Data type	Р	Cardinality	Description
self	Link	М	1	It contains the URI of the linked resource.

5.2.4.6 Type: InvalidParam

Table 5.2.4.6-1: Definition of type InvalidParam

Attribute name	Data type	Р	Cardinality	Description
param	string	Μ	1	Attribute's name encoded as a JSON Pointer.
reason	string	0	01	A human-readable reason, e.g. "must be a positive integer".

5.2.4.7 Type: LinkRm

This data type is defined in the same way as the "Link" data type, but with the OpenAPI "nullable: true" property.

5.2.4.8 Type ChangeItem

Table 5.2.4.8-1: Definition of type ChangeItem

Attribute name	Data type	Р	Cardinality	Description	Applicability
ор	ChangeType	М	1	This IE indicates the change type which happens to the resource.	
path	string	M	1	This IE contains a JSON pointer value (as defined in IETF RFC 6901 [12]) that references a location of an attribute on which the change has been applied.	
from	string	С	01	This IE indicates the path of the source JSON element (according to JSON Pointer syntax) being moved or copied to the location indicated by the "path" attribute. It shall be present if the "op" attribute is of value "MOVE".	
origValue	Any type	0	01	This IE indicates the original value of the attribute specified in the path attribute. This attribute only applies when the "op" attribute is of value "REMOVE", "REPLACE" or "MOVE" Based on the use case, this attribute may be included.	
newValue	Any type	С	01	This IE indicates a new value of the attribute specified in the path attribute. It shall be present if the "op" attribute is of value "ADD", "REPLACE". The data type of this attribute shall be the same as the type of the resource on which the change has happened. The null value shall be allowed.	

5.2.4.9 Type NotifyItem

Table 5.2.4.9-1: Definition of type Notifyltem

Attribute name	Data type	Р	Cardinality	Description	Applicability
resourceld	Uri	М	1	This IE contains the URI of the	
				resource which has been changed.	
changes	array(Changelte	М	1N	This IE contains the changes which	
	m)			have been applied on the resource	
				identified by the resourceld attribute.	

5.2.4.10 Type: ComplexQuery

Table 5.2.4.10-1: Definition of type ComplexQuery as a list of mutually exclusive alternatives

Data type	Cardinality	Description
Cnf	1	A conjunctive normal form
Dnf	1	A disjunctive normal form

The ComplexQuery data type is either a conjunctive normal form or a disjunctive normal form. The attribute names "cnfUnits" and "dnfUnits" (see subclause 5.2.4.11 and subclause 5.2.4.12) serve as discriminator.

5.2.4.11 Type: Cnf

Table 5.2.4.11-1: Definition of type Cnf

Attribute name	Data type	Р	Cardinality	Description	Applicability
cnfUnits	array(CnfUnit)	М		During the processing of cnfUnits attribute, all the members in the array shall be interpreted as logically concatenated with logical "AND".	

5.2.4.12 Type: Dnf

Table 5.2.4.12-1: Definition of type Dnf

Attribute name	Data type	Р	Cardinality	Description	Applicability
dnfUnits	array(DnfUnit)	M	1N	During the processing of dnfUnits	
				attribute, all the members in the array	
				shall be interpreted as logically	
				concatenated with logical "OR".	

5.2.4.13 Type: CnfUnit

Table 5.2.4.13-1: Definition of type CnfUnit

Attribute name	Data type	Р	Cardinality	Description	Applicability
cnfUnit	array(Atom)	M		During the processing of cnfUnit attribute, all the members in the array shall be interpreted as logically concatenated with logical "OR".	

5.2.4.14 Type: DnfUnit

Table 5.2.4.14-1: Definition of type DnfUnit

Attribute name	Data type	Р	Cardinality	Description	Applicability
dnfUnit	array(Atom)	M	1N	During the processing of dnfUnit	
				attribute, all the members in the array	
				shall be interpreted as logically	
				concatenated with logical "AND".	

5.2.4.15 Type: Atom

Table 5.2.4.15-1: Definition of type Atom

Attribute name	Data type	P	Cardinality	Description	Applicability
attr	string	М	1	This attribute contains the name of a defined query parameter.	
value	any type	М	1	This attribute contains the value of the query parameter as indicated by attrattribute.	
negative	boolean	0	01	This attribute indicates whether the negative condition applies for the query condition.	

5.3 Data Types related to Subscription, Identification and Numbering

5.3.1 Introduction

This clause defines common data types related to subscription, identification and numbering information.

5.3.2 Simple Data Types

This subclause specifies common simple data types.

Table 5.3.2-1: Simple Data Types

Type Name	Type Definition	Description
Dnn	string	String representing a Data Network as defined in subclause 9A of
		3GPP TS 23.003 [7]. It shall be formatted as string in which the
		labels are separated by dots (e.g. "Label1.Label2.Label3").
DnnRm	string	This data type is defined in the same way as the "Dnn" data type, but with the OpenAPI "nullable: true" property.
Gpsi	string	String identifying a Gpsi shall contain either an External Id or an
		MSISDN. It shall be formatted as follows:
		-External Identifier: "extid- <extid>, where <extid> shall be</extid></extid>
		formatted according to subclause 19.7.2 of 3GPP TS 23.003 [7]
		that describes an External Identifier.
		-MSISDN: "msisdn- <msisdn>, where <msisdn> shall be formatted according to subclause 3.3 of 3GPP TS 23.003 [7] that describes</msisdn></msisdn>
		an MSISDN.
		Pattern: '^(msisdn-[0-9]{5,15} extid+@.+ .+)\$'
GpsiRm	string	This data type is defined in the same way as the "Gpsi" data type,
Opon	J9	but with the OpenAPI "nullable: true" property.
GroupId	string	String identifying a group of devices network internal globally
,		unique ID which identifies a set of IMSIs, as specified in
		subclause 19.9 of 3GPP TS 23.003 [7].
		Pattern: '^[A-Fa-f0-9]{8}-[0-9]{3}-[0-9]{2,3}-([A-Fa-f0-9][A-Fa-f0-
GroupIdRm	otring	9]){1,10}\$'. This data type is defined in the same way as the "GroupId" data
Groupiakiii	string	type, but with the OpenAPI "nullable: true" property.
Pei	string	String representing a Permanent Equipment Identifier, if it
	James Grand	contains an IMEI or IMEISV it is defined as specified in
		subclause 6.2 of 3GPP TS 23.003 [7].
		Pattern: '^(imei-[0-9]{15} imeisv-[0-9]{16} .+)\$'
PeiRm	string	This data type is defined in the same way as the "Pei" data type,
Cupi	otring	but with the OpenAPI "nullable: true" property. String identifying a Supi shall contain either an IMSI or an NAI. It
Supi	string	shall be formatted as follows for:
		- IMSI "imsi- <imsi>, <imsi> shall be formatted according to</imsi></imsi>
		subclause 2.2 of 3GPP TS 23.003 [7] that describes an IMSI.
		- NAI "nai- <nai>, <nai> shall be formatted according to</nai></nai>
		subclause 28.6.2 of 3GPP TS 23.003 [7] that describes an NAI.
		To enable that the value is used as part of an URI, the string shall
		only contain characters allowed according to the "lower-with-
		hyphen" naming convention defined in 3GPP TS 29.501 [2].
		Pattern: '^(imsi-[0-9]{5,15} nai+ .+)\$'
SupiRm	string	This data type is defined in the same way as the "Supi" data type,
		but with the OpenAPI "nullable: true" property.
NfInstanceId	string	String uniquely identifying a NF instance. The format of the NF
		Instance ID shall be a Universally Unique Identifier (UUID)
		version 4, as described in IETF RFC 4122 [15].
Amfld	string	String identifying the AMF ID composed of AMF Region ID (8
		bits), AMF Set ID (10 bits) and AMF Pointer (6 bits) as specified in subclause 2.10.1 of 3GPP TS 23.003 [7].
		It is encoded as a string of 6 hexadecimal characters (i.e., 24
		bits).
		Pattern: '^[A-Fa-f0-9]{6}\$'
AmfRegionId	string	String identifying the AMF Region ID (8 bits), as specified in
		subclause 2.10.1 of 3GPP TS 23.003 [7].
		It is encoded as a string of 2 hexadecimal characters (i.e. 8 bits). Pattern: '^[A-Fa-f0-9]{2}\$'
AmfSetId	string	String identifying the AMF Set ID (10 bits) as specified in
	James	subclause 2.10.1 of 3GPP TS 23.003 [7].
		It is encoded as a string of 3 hexadecimal characters where the
		first character is limited to values 0 to 3 (i.e. 10 bits).
		Pattern: '^[0-3][A-Fa-f0-9]{2}\$'
RfspIndex	integer	Unsigned integer representing the "Subscriber Profile ID for
		RAT/Frequency Priority" as specified in 3GPP TS 36.413 [16]. Minimum = 1. Maximum = 256.
	_1	

RfspIndexRm	integer	This data type is defined in the same way as the "RfspIndex" data type, but with the OpenAPI "nullable: true" property.
NfGroupId	string	Identifier of a group of NFs

5.3.3 Enumerations

For Data Types related to Subscription, Identification and Numbering, no Enumerations data types are defined in this version of the specification.

5.3.4 Structured Data Types

5.3.4.1 Type: Guami

Table 5.3.4.1-1: Definition of type Guami

Attribute name	Data type	Р	Cardinality	Description
plmnld	Plmnld	М	1	PLMN Identity
amfld	Amfld	М	1	AMF Identity

5.3.4.2 Type: Networkld

Table 5.3.4.2-1: Definition of type NetworkId

Attribute name	Data type	Р	Cardinality	Description
mcc	Mcc	С	01	Mobile Country Code
mnc	Mnc	С	01	Mobile Network Code
NOTE: At least one MNC or MCC shall be included.				

5.3.4.3 Type: GuamiRm

This data type is defined in the same way as the "Guami" data type, but with the OpenAPI "nullable: true" property.

5.4 Data Types related to 5G Network

5.4.1 Introduction

This clause defines common data types related to 5G Network (other than related to 5G QoS).

5.4.2 Simple Data Types

This subclause specifies common simple data types.

Table 5.4.2-1: Simple Data Types

Type Name	Type Definition	Description
ApplicationId	string	String providing an application identifier.
ApplicationIdRm	string	This data type is defined in the same way as the "ApplicationId" data type, but with the OpenAPI "nullable: true" property.
PduSessionId	integer	Unsigned integer identifying a PDU session, within the range 0 to
		255, as specified in subclause 11.2.3.1b, bits 1 to 8, of
Mcc	string	3GPP TS 24.007 [13]. Mobile Country Code part of the PLMN, comprising 3 digits, as
IVICC	Stillig	defined in subclause 9.3.3.5 of 3GPP TS 38.413 [11].
		Pattern: '^[0-9]{3}\$'
MccRm	string	This data type is defined in the same way as the "Mcc" data type, but with the OpenAPI "nullable: true" property.
Mnc	string	Mobile Network Code part of the PLMN, comprising 2 or 3 digits, as defined in subclause 9.3.3.5 of 3GPP TS 38.413 [11].
		Pattern: '^[0-9]{2,3}\$'
MncRm	string	This data type is defined in the same way as the "Mnc" data type, but with the OpenAPI "nullable: true" property.
Tac	string	2 or 3-octet string identifying a tracking area code as specified in subclause 9.3.3.10 of 3GPP TS 38.413 [11], in hexadecimal
		representation. Each character in the string shall take a value of
		"0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the
		TAC shall appear first in the string, and the character representing the 4 least significant bit of the TAC shall appear last
		in the string.
		Fuerrales.
		Examples: A legacy TAC 0x4305 shall be encoded as "4305".
		An extended TAC 0x63F84B shall be encoded as "63F84B"
TacRm	string	This data type is defined in the same way as the "Tac" data type,
Firting On III d	-	but with the OpenAPI "nullable: true" property.
EutraCellId	string	28-bit string identifying an E-UTRA Cell Id as specified in subclause 9.3.1.9 of 3GPP TS 38.413 [11], in hexadecimal
		representation. Each character in the string shall take a value of
		"0" to "9" or "A" to "F" and shall represent 4 bits. The most
		significant character representing the 4 most significant bits of the Cell Id shall appear first in the string, and the character
		representing the 4 least significant bit of the Cell Id shall appear
		last in the string.
		Pattern: '^[A-Fa-f0-9]{7}\$'
		Example:
E	<u> </u>	An E-UTRA Cell Id 0x5BD6007 shall be encoded as "5BD6007".
EutraCellIdRm	string	This data type is defined in the same way as the "EutraCellId" data type, but with the OpenAPI "nullable: true" property.
NrCellId	string	36-bit string identifying an NR Cell Id as specified in subclause
		9.3.1.7 of 3GPP TS 38.413 [11], in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A"
		to "F" and shall represent 4 bits. The most significant character
		representing the 4 most significant bits of the Cell Id shall appear
		first in the string, and the character representing the 4 least significant bit of the Cell Id shall appear last in the string.
		Pattern: '^[A-Fa-f0-9]{9}\$'
		Example:
		An NR Cell Id 0x225BD6007 shall be encoded as "225BD6007".
NrCellIdRm	string	This data type is defined in the same way as the "NrCellId" data type, but with the OpenAPI "nullable: true" property.
Dnai	string	DNAI (Data network access identifier), see subclause 5.6.7 of
DnaiRm	string	3GPP TS 23.501 [8]. This data type is defined in the same way as the "Dnai" data type,
Dianan	Samig	but with the OpenAPI "nullable: true" property.

5GMmCause	Uinteger	This represents the 5GMM cause code values as specified in 3GPP TS 24.501 [20].
AreaCodeRm	string	This data type is defined in the same way as the "AreaCode" data type, but with the OpenAPI "nullable: true" property.
AmfName	string	FQDN (Fully Qualified Domain Name) of the AMF as defined in subclause 28.3.2.5 of 3GPP TS 23.003 [7].
AreaCode	string	Values are operator specific.
N3lwfld	string	This represents the identifier of the N3IWF ID as specified in subclause 9.3.1.57 of 3GPP TS 38.413 [11]. Pattern: '^[A-Fa-f0-9]+\$'
NgeNbId	string	This represents the identifier of the ng-eNB ID as specified in subclause 9.3.1.8 of 3GPP TS 38.413 [11]
		The string shall be formatted with following pattern: Pattern: '^('MacroNGeNB-[A-Fa-f0-9]{5} LMacroNGeNB-[A-Fa-f0-9]{6} SMacroNGeNB-[A-Fa-f0-9]{5})\$'
		The value of the ng-eNB ID shall be encoded in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The padding 0 shall be added to make multiple nibbles, so the most significant character representing the padding 0 if required together with the 4 most significant bits of the ng-eNB ID shall appear first in the string, and the character representing the 4 least significant bit of the ng-eNB ID (to form a nibble) shall appear last in the string.
		Examples: " SMacroNGeNB-34B89" indicates a Short Macro NG-eNB ID with value 0x34B89.

5.4.3 Enumerations

5.4.3.1 Enumeration: AccessType

Table 5.4.3.1-1: Enumeration AccessType

Enumeration value	Description
"3GPP_ACCESS"	3GPP access
"NON_3GPP_ACCESS"	Non-3GPP access

5.4.3.2 Enumeration: RatType

Table 5.4.3.2-1: Enumeration RatType

Enumeration value	Description
"NR"	New Radio
"EUTRA"	(WB) Evolved Universal Terrestrial Radio Access
"WLAN"	Wireless LAN
"VIRTUAL"	Virtual (see NOTE)
NOTE: Virtual shall be used if the N3IWF does not know the access technology used for an untrusted no 3GPP access.	

5.4.3.3 Enumeration: PduSessionType

The enumeration PduSessionType indicates the type of a PDU session. It shall comply with the provisions defined in table 5.4.3.3-1.

Table 5.4.3.3-1: Enumeration PduSessionType

Enumeration value	Description
"IPV4"	IPv4
"IPV6"	IPv6
"IPV4V6"	IPv4v6 (see subclause 5.8.2.2.1 of 3GPP TS 23.501 [8])
"UNSTRUCTURED"	Unstructured
"ETHERNET"	Ethernet

5.4.3.4 Enumeration: UpIntegrity

The enumeration UpIntegrity indicates whether UP integrity protection is required, preferred or not needed for all the traffic on the PDU Session. It shall comply with the provisions defined in table 5.4.3.4-1.

Table 5.4.3.4-1: Enumeration UpIntegrity

Enumeration value	Description
"REQUIRED"	UP integrity protection shall apply for all the traffic on the PDU
	Session.
"PREFERRED"	UP integrity protection should apply for all the traffic on the PDU
	Session.
"NOT_NEEDED"	UP integrity protection shall not apply on the PDU Session.

5.4.3.5 Enumeration: UpConfidentiality

The enumeration UpConfidentiality indicates whether UP confidentiality protection is required, preferred or not needed for all the traffic on the PDU Session. It shall comply with the provisions defined in table 5.4.3.5-1.

Table 5.4.3.5-1: Enumeration UpConfidentiality

Enumeration value	Description
"REQUIRED"	UP confidentiality protection shall apply for all the traffic on the PDU Session.
"PREFERRED"	UP confidentiality protection should apply for all the traffic on the PDU Session.
"NOT_NEEDED"	UP confidentiality protection shall not apply on the PDU Session.

5.4.3.6 Enumeration: SscMode

The enumeration SscMode represents the service and session continuity mode.

Table 5.4.3.6-1: Enumeration SscMode

Enumeration value	Description
"SSC_MODE_1"	see 3GPP TS 23.501 [2]
"SSC_MODE_2"	see 3GPP TS 23.501 [2]
"SSC_MODE_3"	see 3GPP TS 23.501 [2]

5.4.3.7 Enumeration: DnaiChangeType

The enumeration DnaiChangeType represents the type of a DNAI change. A NF service consumer may subscribe to "EARLY", "LATE" or "EARLY_LATE" types of DNAI change. The types of observed DNAI change the SMF may notify are "EARLY" or "LATE". The DnaiChangeType data type shall comply with the provisions defined in table 5.4.3.7-1.

Table 5.4.3.7-1: Enumeration DnaiChangeType

Enumeration value	Description	Applicability
EARLY	Early notification of UP path reconfiguration.	
EARLY_LATE	Early and late notification of UP path reconfiguration. This value shall only be present in the subscription to the DNAI change event.	
LATE	Late notification of UP path reconfiguration.	

5.4.3.8 Enumeration: RestrictionType

Table 5.4.3.8-1: Enumeration RestrictionType

Enumeration value	Description
"ALLOWED_AREAS"	This value indicates that areas are allowed.
"NOT_ALLOWED_AREAS"	This value indicates that areas are not allowed.

5.4.3.9 Enumeration: CoreNetworkType

Table 5.4.3.9-1: Enumeration CoreNetworkType

Enumeration value	Description		
"5GC"	5G Core		
"EPC"	Evolved Packet Core		

5.4.3.10 Enumeration: AccessTypeRm

This enumeration is defined in the same way as the "AccessType" enumeration, but with the OpenAPI "nullable: true" property.

5.4.3.11 Enumeration: RatTypeRm

This enumeration is defined in the same way as the "RatType" enumeration, but with the OpenAPI "nullable: true" property.

5.4.3.12 Enumeration: PduSessionTypeRm

This enumeration is defined in the same way as the "PduSessionType" enumeration, but with the OpenAPI "nullable: true" property.

5.4.3.13 Enumeration: UpIntegrityRm

This enumeration is defined in the same way as the "UpIntegrity" enumeration, but with the OpenAPI "nullable: true" property.

5.4.3.14 Enumeration: UpConfidentialityRm

This enumeration is defined in the same way as the "UpConfidentiality" enumeration, but with the OpenAPI "nullable: true" property.

5.4.3.15 Enumeration: SscModeRm

This data type is defined in the same way as the "SscMode" enumeration, but with the OpenAPI "nullable: true" property.

5.4.3.17 Enumeration: DnaiChangeTypeRm

This data type is defined in the same way as the "DnaiChangeType" enumeration, but with the OpenAPI "nullable: true" property.

5.4.3.18 Enumeration: RestrictionTypeRm

This data type is defined in the same way as the "RestrictionType" enumeration, but with the OpenAPI "nullable: true" property.

5.4.3.19 Enumeration: CoreNetworkType

This data type is defined in the same way as the "CoreNetworkType" enumeration, but with the OpenAPI "nullable: true" property.

5.4.3.20 Enumeration: PresenceState

Table 5.4.3.20-1: Enumeration PresenceState

Enumeration value	Description
"IN_AREA"	Indicates that the UE is inside or enters the presence reporting
	area.
"OUT_OF_AREA"	Indicates that the UE is outside or leaves the presence
	reporting area.
"UNKNOWN"	Indicates it is unknown whether the UE is in the presence
	reporting area or not.
"INACTIVE"	Indicates that the presence reporting area is inactive in the
	serving node.

5.4.4 Structured Data Types

5.4.4.1 Type: SubscribedDefaultQos

Table 5.4.4.1-1: Definition of type SubscribedDefaultQos

Attribute name	Data type	Р	Cardinality	Description
5qi	5Qi	Μ	1	Default 5G QoS identifier
arp	Arp	М	1	Default Allocation and Retention Priority see
				3GPP TS 23.501 [8] subclause 5.7.2.7.
priorityLevel	5QiPriorityLevel	0	01	Defines the 5QI Priority Level.
				When present, it contains the 5QI Priority Level
				value that overrides the standardized or pre-
				configured value as described in
				3GPP TS 23.501 [8].

5.4.4.2 Type: Snssai

Table 5.4.4.2-1: Definition of type Snssai

Attribute name	Data type	Р	Cardinality	Description
sst	Uinteger	M	1	Unsigned integer, within the range 0 to 255, representing the Slice/Service Type. It indicates the expected Network Slice behaviour in terms of features and services. Values 0 to 127 correspond to the standardized SST range. Values 128 to 255 correspond to the Operator-specific range. See subclause 28.4.2 of 3GPP TS 23.003 [7]. Standardized values are defined in subclause 5.15.2.2 of 3GPP TS 23.501 [8].
sd	string	0	01	3-octet string, representing the Slice Differentiator, in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the SD shall appear first in the string, and the character representing the 4 least significant bit of the SD shall appear last in the string. This is an optional parameter that complements the Slice/Service type(s) to allow to differentiate amongst multiple Network Slices of the same Slice/Service type.
				Pattern: '^[A-Fa-f0-9]{6}\$'

When Snssai needs to be converted to string (e.g. when used in maps as key), the string shall be composed of one to three digits "sst" optionally followed by "-" and 6 hexadecimal digits "sd", and shall match the following pattern:

 $^{([0-9][1-9][0-9][1-9][0-9][2([0-4][0-9]|5[0-5]))(-[A-Fa-f0-9]\{6\})? \\$

Example 1: "255-19CDE0"

Example 2: "29"

5.4.4.3 Type: Plmnld

Table 5.4.4.3-1: Definition of type Plmnld

Attribute name	Data type	Р	Cardinality	Description
mcc	Мсс	М	1	Mobile Country Code
mnc	Mnc	М	1	Mobile Network Code

5.4.4.4 Type: Tai

Table 5.4.4.4-1: Definition of type Tai

Attribute name	Data type	Р	Cardinality	Description
plmnld	Plmnld	М	1	PLMN Identity
tac	Tac	М	1	Tracking Area Code

5.4.4.5 Type: Ecgi

Table 5.4.4.5-1: Definition of type Ecgi

Attribute name	Data type	Р	Cardinality	Description
plmnld	Plmnld	M	1	PLMN Identity
eutraCellId	EutraCellId	М	1	E-UTRA Cell Identity

5.4.4.6 Type: Ncgi

Table 5.4.4.6-1: Definition of type Ncgi

Attribute name	Data type	Р	Cardinality	Description
plmnld	Plmnld	М	1	PLMN Identity
nrCellId	NrCellId	М	1	NR Cell Identity

5.4.4.7 Type: UserLocation

Table 5.4.4.7-1: Definition of type UserLocation

Attribute name	Data type	Р	Cardinality	Description	
eutraLocation	EutraLocation	C	01	E-UTRA user location (see NOTE).	
nrLocation	NrLocation	С	01	NR user location (see NOTE).	
n3gaLocation	N3gaLocation	С	01	Non-3GPP access user location (see NOTE).	
NOTE: At least one of eutraLocation, nrLocation and n3gaLocation shall be present. Several of them may be present.					

5.4.4.8 Type: EutraLocation

Table 5.4.4.8-1: Definition of type EutraLocation

Attribute name	Data type	Р	Cardinality	Description
tai	Tai	М	1	Tracking Area Identity
ecgi	Ecgi	М	1	E-UTRA Cell Identity
ageOfLocationInform ation	integer	0	0 1	The value represents the elapsed time in minutes since the last network contact of the mobile station. Value "0" indicates that the location information was obtained after a successful paging procedure for Active Location Retrieval when the UE is in idle mode or after a successful NG-RAN location reporting procedure with the eNB when the UE is in connected mode. Any other value than "0" indicates that the location information is the last known one. See 3GPP TS 29.002 [21] subclause 17.7.8.
ueLocationTimestam p	DateTime	0	01	The value represents the UTC time when the UeLocation information was acquired.
geographicalInformat ion	string	0	01	Refer to geographical Information. See 3GPP TS 23.032 [23] subclause 7.3.2. Only the description of an ellipsoid point with uncertainty circle is allowed to be used. Allowed characters are 0-9 and A-F;
geodeticInformation	string	0	01	Refers to Calling Geodetic Location. See ITU-T Recommendation Q.763 (1999) [24] subclause 3.88.2. Only the description of an ellipsoid point with uncertainty circle is allowed to be used. Allowed characters are 0-9 and A-F.
globalNgenbId	GlobalRanNodel d	0	01	It indicates the global identity of the ng-eNodeB in which the UE is currently located. See 3GPP TS 38.413 [11] subclause 9.3.1.8.

5.4.4.9 Type: NrLocation

Table 5.4.4.9-1: Definition of type NrLocation

Attribute name	Data type	Р	Cardinality	Description
tai	Tai	М	1	Tracking Area Identity
ncgi	Ncgi	М	1	NR Cell Identity
ageOfLocationInformat ion	integer	0	0 1	The value represents the elapsed time in minutes since the last network contact of the mobile station. Value "0" indicates that the location information was obtained after a successful paging procedure for Active Location Retrieval when the UE is in idle mode or after a successful NG-RAN location reporting procedure with the gNB when the UE is in connected mode. Any other value than "0" indicates that the location information is the last known one. See 3GPP TS 29.002 [21] subclause 17.7.8.
ueLocationTimestamp	DateTime	0	01	The value represents the UTC time when the UELocation information was acquired.
geographicalInformatio n	string	0	01	Refer to geographical Information. See 3GPP TS 23.032 [23] subclause 7.3.2. Only the description of an ellipsoid point with uncertainty circle is allowed to be used. Allowed characters are 0-9 and A-F;
geodeticInformation	string	Ο	01	Refers to Calling Geodetic Location. See ITU-T Recommendation Q.763 (1999) [24] subclause 3.88.2. Only the description of an ellipsoid point with uncertainty circle is allowed to be used. Allowed characters are 0-9 and A-F.
globalGnbld	GlobalRanNodel d	0	01	It indicates the global identity of the gNodeB in which the UE is currently located. See 3GPP TS 38.413 [11] subclause 9.3.1.6.

5.4.4.10 Type: N3gaLocation

Table 5.4.4.10-1: Definition of type N3gaLocation

Attribute name	Data type	Р	Cardinality	Description
n3gppTai	Tai	С	01	The unique non 3GPP TAI used in the PLMN. It shall
				be present over the 3GPP PLMN internal interfaces,
				but shall not be present over the N5 interface.
n3lwfld	string	С	01	This IE shall contain the N3IWF identifier received
				over NGAP and shall be encoded as a string of
				hexadecimal characters.
				Pattern: '^[A-Fa-f0-9]+\$'
				It shall be present over the 3GPP PLMN internal
				interfaces, but shall not be present over the N5
				interface.
uelpv4Addr	Ipv4Addr	С	01	UE local IPv4 address (used to reach the N3IWF).
				The uelPv4Addr or the uelPv6Addr shall be present.
uelpv6Addr	Ipv6Addr	С	01	UE local IPv6 address (used to reach the N3IWF).
				The uelPv4Addr or the uelPv6Addr shall be present.
portNumber	Uinteger	C	01	UDP or TCP source port number. It shall be present
				if NAT is detected.

5.4.4.11 Type: UpSecurity

Table 5.4.4.11-1: Definition of type UpSecurity

Attribute name	Data type	Р	Cardinality	Description
upIntegr	UpIntegrity	M	1	This IE shall indicate whether UP integrity protection
				is required, preferred or not needed for all the traffic on the PDU Session.
				on the PDO Session.
upConfid	UpConfidentiality	M	1	This IE shall indicate whether UP confidentiality
				protection is required, preferred or not needed for all
				the traffic on the PDU Session.

5.4.4.12 Type: NgApCause

Table 5.4.4.12-1: Definition of type NgApCause

Attribute name	Data type	Р	Cardinality	Description
group	Uinteger	M	1	This IE shall indicate the group of the NGAP cause. The value of this IE shall equal to the ASN.1 value of the specified NGAP cause group. NGAP supports following cause groups defined as separate enumerations, as specified in subclause 9.4.5 of 3GPP TS 38.413 [11], with following values: 0 – radioNetwork 1 – transport 2 – nas 3 – protocol 4 – misc
value	Uinteger	М	1	This IE shall carry the NG AP cause value in specific cause group identified by the "group" attribute, as specified in subclause 9.4.5 of 3GPP TS 38.413 [11].

5.4.4.13 Type: BackupAmfInfo

Table 5.4.4.13-1: Definition of type BackupAmfInfo

Attribute name	Data type	Р	Cardinality	Description
backupAmf	AmfName	M		This IE shall contain the AMF name of the backup AMF related to the specific GUAMI(s) (see subclause 5.21.2.3 of 3GPP TS 23.501 [2]). If no GUAMI is included in BackupAmfinfo, the AMF name of the backup AMF is related to all the GUAMI(s) supported by the AMF.
guamiList	array(Guami)	С	1N	If present, this IE shall contain the GUAMI(s).

5.4.4.14 Type: RefToBinaryData

Table 5.4.4.14-1: Definition of type RefToBinaryData

Attribute name	Data type	P	Cardinality	Description
contentId	string	М	1	This IE shall contain the value of the Content-ID
				header of the referenced binary body part.

5.4.4.15 Type RouteToLocation

Table 5.4.4.15-1: Definition of type RouteToLocation

Attribute name	Data type	Р	Cardinality	Description		
dnai	Dnai	М	1	Identifies the location of the application.		
routeInfo	RouteInformation	C	01	Includes the traffic routing information.		
routeProfld	string	С	01	Identifies the routing profile Id.		
NOTE: Either the "routeInfo" attribute or the "routeProfId" attribute shall be included in the						
"RouteToLocation" data type.						

5.4.4.16 Type RouteInformation

Table 5.4.4.16-1: Definition of type RouteInformation

Attribute name	Data type	Р	Cardinality	Description		
ipv4Addr	lpv4Addr	С	01	Ipv4address of the tunnel end point in the data network.		
ipv6Addr	lpv6Addr	С	01	lpv6 address of the tunnel end point in the data network.		
portNumber	Uinteger	М	1	UDP port number of the tunnel end point in the data network.		
NOTE: At least one of the "ipv4Addr" attribute and the "ipv6Addr" attribute shall be included in the "RouteInformation" data type.						

5.4.4.17 Type: Area

Table 5.4.4.17-1: Definition of type Area

Attribute name	Data type	Р	Cardinality	Description
tacs	array(Tac)	С	1N	List of TACs; shall be present if and only if areaCode is absent.
areaCodes	AreaCode	С	01	Area Code; shall be present if and only if tacs is absent.

5.4.4.18 Type: ServiceAreaRestriction

Table 5.4.4.18-1: Definition of type ServiceAreaRestriction

Attribute name	Data type	Р	Cardinality	Description
restrictionType	RestrictionType	С	01	string "ALLOWED_AREAS" or "NOT_ALLOWED_AREAS" shall be present if and only if the areas attribute is present
areas	array(Area)	0	0N (NOTE)	A list of Areas. These areas are: - allowed areas if RestrictionType is "ALLOWED_AREAS" - not allowed areas if RestrictionType is "NOT_ALLOWED_AREAS"
maxNumOfTAs	Uinteger	С	01	Maximum number of allowed tracking areas. This attribute shall be absent when attribute "restrictionType" takes the value "NOT_ALLOWED_AREAS".

5.4.4.19 Type: PlmnldRm

This data type is defined in the same way as the "PlmnId" data type, but with the OpenAPI "nullable: true" property.

5.4.4.20 Type: TaiRm

This data type is defined in the same way as the "Tai" data type, but with the OpenAPI "nullable: true" property.

5.4.4.21 Type: EcgiRm

This data type is defined in the same way as the "Ecgi" data type, but with the OpenAPI "nullable: true" property.

5.4.4.22 Type: NcgiRm

This data type is defined in the same way as the "Ncgi" data type, but with the OpenAPI "nullable: true" property.

5.4.4.23 Type: EutraLocationRm

This data type is defined in the same way as the "EutraLocation" data type, but with the OpenAPI "nullable: true" property.

5.4.4.24 Type: NrLocationRm

This data type is defined in the same way as the "NrLocation" data type, but with the OpenAPI "nullable: true" property.

5.4.4.25 Type: UpSecurityRm

This data type is defined in the same way as the "UpSecurity" data type, but with the OpenAPI "nullable: true" property.

5.4.4.26 Type: RefToBinaryDataRm

This data type is defined in the same way as the "RefToBinaryData" data type, but with the OpenAPI "nullable: true" property.

5.4.4.27 Type: PresenceInfo

Table 5.4.4.27-1: Definition of type PresenceInfo

Attribute name	Data type	Р	Cardinality	Description
prald	String	С	01	Represents an identifier to the specified area. This IE shall be present if the Area of Interest subscribed or reported is a Presence Reporting Area.
presenceState	PresenceState	С	01	Indicates whether the UE is inside or outside of the area of interest (e.g presence reporting area or the LADN area), or if the presence reporting area is inactive in the serving node.
trackingAreaList	array(Tai)	С	1N	Represents the list of tracking areas that constitutes the area. This IE shall be present if the subscription or the event report is for tracking UE presence in the tracking areas. For non 3GPP access the TAI shall be the N3GPP TAI.
ecgiList	array(Ecgi)	С	1N	Represents the list of EUTRAN cell lds that constitutes the area. This IE shall be present if the Area of Interest subscribed is a list of EUTRAN cell lds.
ncgiList	array(Ncgi)	С	1N	Represents the list of NR cell Ids that constitutes the area. This IE shall be present if the Area of Interest subscribed is a list of NR cell Ids.
globalRanNodeIdList	array(GlobalRan Nodeld)	С	1N	Represents the list of NG RAN node identifiers that constitutes the area. This IE shall be present if the Area of Interest subscribed is a list of NG RAN node identifiers.

5.4.4.28 Type: GlobalRanNodeld

Table 5.4.4.28-1: Definition of type GlobalRanNodeld

Attribute name	Data type	Р	Cardinality	Description
plmnld	Plmnld	М	1	Indicates the identity of the PLMN that the RAN node
				belongs to.
n3lwfld	N3Iwfld	С	01	This IE shall be included if the RAN node belongs to
				non 3GPP access (i.e a N3IWF).
				(NOTE).
gNbld	GNbld	С	01	This IE shall be included if the RAN Node Id
				represents a gNB. When present, this IE shall
				contain the identifier of the gNB. (NOTE 1).
ngeNbId	NgeNbld	С	01	This IE shall be included if the RAN Node Id
				represents a NG-eNB. When present, this IE shall
				contain the identifier of an NG-eNB. (NOTE 1).
NOTE: At most one of the three attributes n3lwfld, gNbldm, ngeNbld shall be present.				

5.4.4.29 Type: GNbld

Table 5.4.4.29-1: Definition of type GNbld

Attribute name	Data type	Р	Cardinality	Description
bitLength	integer	M	1	Unsigned integer representing the bit length of the gNB ID as defined in subclause 9.3.1.6 of 3GPP TS 38.413 [11], within the range 22 to 32
gNbValue	string	M	1	This represents the identifier of the gNB. The string shall be formatted with following pattern: '^[A-Fa-f0-9]{6,8}\$' The value of the gNB ID shall be encoded in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The padding 0 shall be added to make multiple nibbles, the most significant character representing the padding 0 if required together with the 4 most significant bits of the gNB ID shall appear first in the string, and the character representing the 4 least significant bit of the gNB ID shall appear last in the string. Examples: A 30 bit value "382A3F47" indicates a gNB ID with value 0x382A3F47 A 22 bit value "2A3F47" indicates a gNB ID with value 0x2A3F47

5.4.4.30 Type: PresenceInfoRm

This data type is defined in the same way as the "PresenceInfo" data type, but with the OpenAPI "nullable: true" property.

5.5 Data Types related to 5G QoS

5.5.1 Introduction

This clause defines common data types related to 5G QoS.

5.5.2 Simple Data Types

This subclause specifies common simple data types.

Table 5.5.2-1: Simple Data Types

Type Name	Type Definition	Description
Qfi	integer	Unsigned integer identifying a QoS flow, within the range 0 to 63.
QfiRm	integer	This data type is defined in the same way as the "Qfi" data type, but with the OpenAPI "nullable: true" property.
5Qi	integer	Unsigned integer representing a 5G QoS Identifier (see
	-	subclause 5.7.2.1 of 3GPP TS 23.501 [8]), within the range 0 to
		255.
5QiRm	integer	This data type is defined in the same way as the "5Qi" data type,
DitData	a turina au	but with the OpenAPI "nullable: true" property.
BitRate	string	String representing a bit rate that shall be formatted as follows:
		Pattern: '^\d+(\.\d+)? (bps Kbps Mbps Gbps Tbps)\$'
		Examples: "125 Mbps", "0.125 Gbps", "125000 Kbps"
BitRateRm	string	This data type is defined in the same way as the "BitRate" data
Ditratorin	String	type, but with the OpenAPI "nullable: true" property.
ArpPriorityLevel	integer	Unsigned integer indicating the ARP Priority Level (see
, ,	3	subclause 5.7.2.2 of 3GPP TS 23.501 [8]), within the range 1 to
		15.
		Values are ordered in decreasing order of priority, i.e. with 1 as
A D : :: 1 ID	• •	the highest priority and 15 as the lowest priority.
ArpPriorityLevelRm	integer	This data type is defined in the same way as the
		"ArpPriorityLevel" data type, but with the OpenAPI "nullable: true"
5QiPriorityLevel	integer	property. Unsigned integer indicating the 5QI Priority Level (see
odii nonty Ecvoi	integer	subclauses 5.7.3.3 and 5.7.4 of 3GPP TS 23.501 [8]), within the
		range 1 to 127.
		Values are ordered in decreasing order of priority, i.e. with 1 as
		the highest priority and 127 as the lowest priority.
5QiPriorityLevelRm	integer	This data type is defined in the same way as the
		"5QiPriorityLevel" data type, but with the OpenAPI "nullable: true"
De electDe IDe elect	lata san	property.
PacketDelBudget	Integer	Unsigned integer indicating Packet Delay Budget (see subclauses 5.7.3.4 and 5.7.4 of 3GPP TS 23.501 [8])), expressed
		in milliseconds.
		Minimum = 1.
PacketDelBudgetR	integer	This data type is defined in the same way as the
m	3	"PacketDelBudget" data type, but with the OpenAPI "nullable:
		true" property.
PacketErrRate	string	String representing Packet Error Rate (see subclause 5.7.3.5 and
		5.7.4 of 3GPP TS 23.501 [8]), expressed as a "scalar x 10-k"
		where the scalar and the exponent k are each encoded as one
		decimal digit Pattern: '^([0-9]E-[0-9])\$'
		Pattern: '\[0-9]c-[0-9])φ
		Examples:
		Packer Error Rate 4x10 ⁻⁶ shall be encoded as "4E-6".
D 1 (E D) D		Packer Error Rate 10 ⁻² shall be encoded as "1E2".
PacketErrRateRm	string	This data type is defined in the same way as the "PacketErrRate"
PacketLossRate	Integer	data type, but with the OpenAPI "nullable: true" property. Unsigned integer indicating Packet Loss Rate (see
i auncilussitale	Integer	subclauses 5.7.2.8 and 5.7.4 of 3GPP TS 23.501 [8])), expressed
		in tenth of percent.
		Minimum = 0. Maximum = 1000.
PacketLossRateRm	Integer	This data type is defined in the same way as the
	-	"PacketLossRate" data type, but with the OpenAPI "nullable: true"
		property.
AverWindow	Integer	Unsigned integer indicating Averaging Window (see
		subclause 5.7.3.6 and 5.7.4 of 3GPP TS 23.501 [8]), expressed
		in milliseconds.
AverWindowRm	intogor	Minimum = 1. Maximum = 4095. Default = 2000 This data type is defined in the same way as the "AverWindow"
AVEIVVIIIUUWKIII	integer	data type, but with the OpenAPI "nullable: true" property.
		Judia type, but with the OpenAFT Hullable, true property.

MaxDataBurstVol		Unsigned integer indicating Maximum Data Burst Volume (see subclauses 5.7.3.7 and 5.7.4 of 3GPP TS 23.501 [8])), express in Bytes. Minimum = 1. Maximum = 4095.	
MaxDataBurstVoIR m	ŭ	This data type is defined in the same way as the "MaxDataBurstVol" data type, but with the OpenAPI "nullable: true" property.	

5.5.3 Enumerations

5.5.3.1 Enumeration: PreemptionCapability

The enumeration PreemptionCapability indicates the pre-emption capability of a request on other QoS flows. See subclause 5.7.2.2 of 3GPP TS 23.501 [8]. It shall comply with the provisions defined in table 5.5.3.1-1.

Table 5.5.3.1-1: Enumeration PreemptionCapability

Enumeration value	Description		
"NOT_PREEMPT"	Shall not trigger pre-emption.		
"MAY_PREEMPT"	May trigger pre-emption.		

5.5.3.2 Enumeration: PreemptionVulnerability

The enumeration Preemption Vulnerability indicates the pre-emption vulnerability of the QoS flow to pre-emption from other QoS flows. See subclause 5.7.2.2 of 3GPP TS 23.501 [8]. It shall comply with the provisions defined in table 5.5.3.2-1.

Table 5.5.3.2-1: Enumeration PreemptionVulnerability

Enumeration value	Description
"NOT_PREEMPTABLE"	Shall not be pre-empted.
"PREEMPTABLE"	May be pre-empted.

5.5.3.3 Enumeration: ReflectiveQosAttribute

The enumeration ReflectiveQosAttribute indicates whether certain traffic of the QoS flow may be subject to Reflective QoS (see subclause 5.7.2.3 of 3GPP TS 23.501 [2]). It shall comply with the provisions defined in table 5.5.3.3-1.

Table 5.5.3.3-1: Enumeration ReflectiveQosAttribute

Enumeration value	Description		
"RQOS"	Certain traffic of the Qos flow may be subject to Reflective QoS.		
"NO_RQOS"	Traffic of the Qos flow is not subject to Reflective QoS.		

5.5.3.4 Void

5.5.3.5 Enumeration: NotificationControl

The enumeration NotificationControl indicates whether notifications are requested from the RAN when the GFBR can no longer (or again) be fulfilled for a QoS Flow during the lifetime of the QoS Flow (see subclause 5.7.2.4 of 3GPP TS 23.501 [2]). It shall comply with the provisions defined in table 5.5.3.5-1.

Table 5.5.3.5-1: Enumeration NotificationControl

Enumeration value	Description
"REQUESTED"	Notifications are requested from the RAN.
"NOT_REQUESTED"	Notifications are not requested from the RAN.

5.5.3.6 Enumeration: QosResourceType

The enumeration QosResourceType indicates whether a QoS Flow is non-GBR, delay critical GBR, or non-delay critical GBR (see subclauses 5.7.3.4 and 5.7.3.5 of 3GPP TS 23.501 [2]). It shall comply with the provisions defined in table 5.5.3.6-1.

Table 5.5.3.6-1: Enumeration QosResourceType

Enumeration value	Description
"NON_GBR"	Non-GBR QoS Flow.
"NON_CRITICAL_GBR"	Non-delay critical GBR QoS flow.
"CRITICAL_GBR"	Delay critical GBR QoS flow.

5.5.3.7 Enumeration: PreemptionCapabilityRm

This enumeration is defined in the same way as the "PreemptionCapability" enumeration, but with the OpenAPI "nullable: true" property.

5.5.3.8 Enumeration: PreemptionVulnerabilityRm

This enumeration is defined in the same way as the "PreemptionVulnerability" enumeration, but with the OpenAPI "nullable: true" property.

5.5.3.9 Enumeration: ReflectiveQosAttributeRm

This enumeration is defined in the same way as the "ReflectiveQosAttribute" enumeration, but with the OpenAPI "nullable: true" property.

5.5.3.10 Enumeration: NotificationControlRm

This enumeration is defined in the same way as the "NotificationControl" enumeration, but with the OpenAPI "nullable: true" property.

5.5.3.11 Enumeration: QosResourceTypeRm

This enumeration is defined in the same way as the "QosResourceType" enumeration, but with the OpenAPI "nullable: true" property.

5.5.3.12 Enumeration: AdditionalQosFlowInfo

The enumeration AdditionalQosFlowInfo provides additional QoS flow information (see subclause 9.3.1.12 3GPP TS 38.413 [11]). It shall comply with the provisions defined in table 5.5.3.12-1.

Table 5.5.3.12-1: Enumeration AdditionalQosFlowInfo

Enumeration value	Description
"MORE_LIKELY"	Traffic for the QoS flow is likely to appear more often than traffic
	for other flows established for the PDU session.

5.5.4 Structured Data Types

5.5.4.1 Type: Arp

Table 5.5.4.1-1: Definition of type Arp

Attribute name	Data type	Р	Cardinality	Description	
priorityLevel	ArpPriorityLevel	М	1	Defines the relative importance of a resource request.	
preemptCap	PreemptionCapa bility	М	1	Defines whether a service data flow may get resources that were already assigned to another service data flow with a lower priority level.	
preemptVuln	PreemptionVulne rability	М	1	Defines whether a service data flow may lose the resources assigned to it in order to admit a servic data flow with higher priority level.	

5.5.4.2 Type: Ambr

Table 5.5.4.2-1: Definition of type Ambr

Attribute name	Data type	Р	Cardinality	Description
uplink	BitRate	М	1	AMBR for uplink
downlink	BitRate	М	1	AMBR for downlink

5.5.4.3 Type: Dynamic5Qi

Table 5.5.4.3-1: Definition of type Dynamic5Qi

Attribute name	Data type	Р	Cardinality	Description	Applicability
resourceType	QosResourceTy	M	1	Defines the 5QI resource type. See	
	ре			subclause 5.5.3.6.	
priorityLevel	5QiPriorityLevel	M	1	Defines the 5QI Priority Level. See	
				subclause 5.5.2.	
packetDelayBudget	PacketDelBudg	М	1	Defines the packet delay budget. See	
	et			subclause 5.5.2.	
packetErrRate	PacketErrRate	М	1	Defines the packet error rate. See	
•				subclause 5.5.2.	
averWindow	AverWindow	С	01	Defines the averaging window. See	
				subclause 5.5.2.	
				This IE shall be present only for a GBR	
				QoS flow or a Delay Critical GBR QoS	
				flow.	
maxDataBurstVol	MaxDataBurstV	С	01	Defines the maximum data burst volume.	
	ol			See subclause 5.5.2.	
				This IE shall be present for a Delay	
				Critical GBR QoS flow.	

5.5.4.4 Type: NonDynamic5Qi

Table 5.5.4.4-1: Definition of type NonDynamic5Qi

Attribute name	Data type	Р	Cardinality	Description	Applicability
priorityLevel	5QiPriorityLevel	0	01	Defines the 5Ql Priority Level. See subclause 5.5.2. When present, it contains the 5Ql	
				Priority Level value that overrides the standardized or pre-configured value.	
averWindow	AverWindow	0	01	Defines the averaging window. See subclause 5.5.2. This IE may be present for a GBR QoS flow or a Delay Critical GBR QoS flow. When present, it contains the Averaging Window that overrides the standardized or pre-configured value.	
maxDataBurstVol	MaxDataBurstV ol	0	01	Defines the maximum data burst volume. See subclause 5.5.2. This IE may be present for a Delay Critical GBR QoS flow. When present, it contains the Maximum Data Burst Volume value that overrides the standardized or pre-configured value.	

5.5.4.5 Type: ArpRm

This data type is defined in the same way as the "Arp" data type, but with the OpenAPI "nullable: true" property.

5.5.4.6 Type: AmbrRm

This data type is defined in the same way as the "Ambr" data type, but with the OpenAPI "nullable: true" property.

5.6 Data Types related to 5G Trace

5.6.1 Introduction

This clause defines common data types related to 5G Trace.

5.6.2 Simple Data Types

This subclause specifies common simple data types.

Table 5.6.2-1: Simple Data Types

Type Name	Type Definition	Description

5.6.3 Enumerations

5.6.3.1 Enumeration: TraceDepth

The enumeration TraceDepth defines how detailed information should be recorded in the trace. See 3GPP TS 32.422 [19] for further description of the values. It shall comply with the provisions defined in table 5.6.3.1-1.

Table 5.6.3.1-1: Enumeration TraceDepth

Enumeration value	Description
"MINIMUM"	Minimum
"MEDIUM"	Medium
"MAXIMUM"	Maximum
"MINIMUM_WO_VENDOR_EXTENSION"	Minimum without vendor specific extension
"MEDIUM_WO_VENDOR_EXTENSION"	Medium without vendor specific extension
"MAXIMUM_WO_VENDOR_EXTENSION"	Maximum without vendor specific extension

5.6.3.2 Enumeration: TraceDepthRm

This enumeration is defined in the same way as the "TraceDepth" enumeration, but with the OpenAPI "nullable: true" property.

5.6.4 Structured Data Types

5.6.4.1 Type: TraceData

Table 5.6.4.1-1: Definition of type TraceData

Attribute name	Data type	Р	Cardinality	Description
traceRef	string	М	1	Trace Reference (see 3GPP TS 32.422 [19]).
				It shall be encoded as the concatenation of MCC, MNC and Trace ID as follows: <mcc><mnc>-<trace id=""></trace></mnc></mcc>
				The Trace ID shall be encoded as a 3 octet string in hexadecimal representation. Each character in the Trace ID string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the Trace ID shall appear first in the string, and the character representing the 4 least significant bit of the Trace ID shall appear last in the string.
				Pattern: '^[0-9]{3}[0-9]{2,3}-[A-Fa-f0-9]{6}\$'
traceDepth	TraceDepth	М	1	Trace Depth (see 3GPP TS 32.422 [19]).
neTypeList	string	М	1	List of NE Types (see 3GPP TS 32.422 [19]).
				It shall be encoded as an octet string in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits shall appear first in the string, and the character representing the 4 least significant bit shall appear last in the string.
				Octets shall be coded according to 3GPP TS 32.422 [19].
				Pattern: '^[A-Fa-f0-9]+\$'
eventList	string	М	1	Triggering events (see 3GPP TS 32.422 [19]).
				It shall be encoded as an octet string in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits shall appear first in the string, and the character representing the 4 least significant bit shall appear last in the string.
				Octets shall be coded according to 3GPP TS 32.422 [19].
				Pattern: '^[A-Fa-f0-9]+\$'
collectionEntityIpv4A ddr	lpv4Addr	С	01	IPv4 Address of the Trace Collection Entity (see 3GPP TS 32.422 [x). At least one of the collectionEntitylpv4Addr or collectionEntitylpv6Addr attributes shall be present.
collectionEntityIpv6A ddr	lpv6Addr	С	01	IPv6 Address of the Trace Collection Entity (see 3GPP TS 32.422 [x). At least one of the collectionEntityIpv4Addr or collectionEntityIpv6Addr attributes shall be present.

interfaceList	string	0	01	List of Interfaces (see 3GPP TS 32.422 [19]).
				It shall be encoded as an octet string in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits shall appear first in the string, and the character representing the 4 least significant bit shall appear last in the string.
				Octets shall be coded according to 3GPP TS 32.422 [19].
				If this attribute is not present, all the interfaces applicable to the list of NE types indicated in the neTypeList attribute should be traced.
				Pattern: '^[A-Fa-f0-9]+\$'

5.7 Data Types related to 5G Operator Determined Barring

5.7.1 Introduction

This clause defines common data types related to 5G Operator Determined Barring.

5.7.2 Simple Data Types

This subclause specifies common simple data types.

Table 5.7.2-1: Simple Data Types

Type Name	Type Definition	Description

5.7.3 Enumerations

5.7.3.1 Enumeration: RoamingOdb

The enumeration RoamingOdb defines the Barring of Roaming as. See 3GPP TS 23.015 [26] for further description. It shall comply with the provisions defined in table 5.7.3.1-1.

Table 5.7.3.1-1: Enumeration RoamingOdb

Enumeration value	Description
"OUTSIDE_HOME_PLMN"	Barring of roaming outside the home PLMN
"OUTSIDE_HOME_PLMN_COUNTRY"	Barring of roaming outside the home PLMN country

5.7.4.1 Enumeration: OdbPacketServices

The enumeration OdbPacketServices defines the Barring of Packet Oriented Services. See 3GPP TS 23.015 [26] for further description. It shall comply with the provisions defined in table 5.7.4.1-1.

Table 5.7.4.1-1: Enumeration OdbPacketServices

Enumeration value	Description
"ALL_PACKET_SERVICES"	Barring of all Packet Oriented Services
"ROAMER_ACCESS_HPLMN_AP"	Barring of Packet Oriented Services from access points that are within the HPLMN whilst the subscriber is roaming in a VPLMN
"ROAMER_ACCESS_VPLMN_AP"	Barring of Packet Oriented Services from access points that are within the roamed to VPLMN.

5.7.4 Structured Data Types

5.7.4.1 Type: OdbData

Table 5.7.4.1-1: Definition of type OdbData

Attribute name	Data type	Р	Cardinality	Description
roamingOdb	RoamingOdb	0	01	Barring of Roaming (see 3GPP TS 23.015 [26]).

5.8 Data Types related to Charging

5.8.1 Introduction

This clause defines common data types related to Charging.

5.8.2 Simple Data Types

This subclause specifies common simple data types.

Table 5.8.2-1: Simple Data Types

Type Name Type Definition		Description
ChargingId	Uint32	Charging identifier allowing correlation of charging information
RatingGroup	Uint32	Identifier of a Rating Group
Serviceld	Uint32	Identifier of a Service

5.8.3 Enumerations

5.8.4 Structured Data Types

5.8.4.1 Type: SecondaryRatUsageReport

Table 5.8.4.1-1: Definition of type SecondaryRatUsageReport

Attribute name	Data type	Р	Cardinality	Description
secondaryRatType	RatType	М	1	Secondary RAT type
qosFlowsUsageData	array(QosFlowUs	М	1N	QoS flows usage data
	ageReport)			

5.8.4.2 Type: QoSFlowUsageReport

Table 5.8.4.2-1: Definition of type QoSFlowUsageReport

Attribute name	Data type	Р	Cardinality	Description
qfi	Qfi	М	1	QoS Flow Indicator
startTimeStamp	DateTime	М	1	UTC time indicating the start time of the collection period of the included usage data for DL and UL.
endTimeStamp	DateTime	М	1	UTC time indicating the end time of the collection period of the included usage data for DL and UL.
downlinkVolume	Int64	М	1	Data usage for DL, encoding a number of octets
uplinkVolume	Int64	М	1	Data usage for UL, encoding a number of octets

Annex A (normative): OpenAPI specification

A.1 General

This Annex specifies the formal definition of common data types. It consists of an OpenAPI 3.0.0 specification, in YAML format.

A.2 Data related to Common Data Types

```
openapi: 3.0.0
info:
  version: '1.0.1'
  title: 'Common Data Types'
 description: 'Common Data Types for Service Based Interfaces '
external Docs:
  description: 3GPP TS 29.571 Common Data Types for Service Based Interfaces, version 15.3.0
  url: 'http://www.3gpp.org/ftp/Specs/archive/29_series/29.571/'
paths: {}
components:
  schemas:
# Common Data Types for Generic usage definitiones as defined in subclause 5.2
#
# COMMON SIMPLE DATA TYPES
    Binary:
      format: binary
      type: string
    BinaryRm:
      format: binary
      type: string
     nullable: true
    Bytes:
      format: byte
      type: string
    BytesRm:
      format: byte
      type: string
      nullable: true
    Date:
      format: date
      type: string
    DateRm:
      format: date
      type: string
     nullable: true
    DateTime:
      format: date-time
     type: string
    DateTimeRm:
      format: date-time
      type: string
      nullable: true
    DiameterIdentity:
      type: string
      pattern: '^([A-Za-z0-9]+(-[A-Za-z0-9]+).)+[a-z]{2,}$'
    DiameterIdentityRm:
      type: string
      pattern: '^([A-Za-z0-9]+(-[A-Za-z0-9]+).)+[a-z]{2,}
     nullable: true
    Double:
      format: double
      type: number
    DoubleRm:
      format: double
      type: number
      nullable: true
    DurationSec:
```

```
type: integer
               DurationSecRm:
                        type: integer
                       nullable: true
                Float:
                       format: float
                        type: number
               FloatRm:
                       format: float
                        type: number
                      nullable: true
                Int.32:
                        format: int32
                        type: integer
                Int32Rm:
                       format: int32
                        type: integer
                       nullable: true
                       type: integer
                       format: int64
                Int64Rm:
                        format: int64
                        type: integer
                       nullable: true
                Ipv4Addr:
                       type: string
                        9][0-9]|2[0-4][0-9]|25[0-5])$'
                       example: '198.51.100.1'
                Ipv4AddrRm:
                       type: string
                        9][0-9]|2[0-4][0-9]|25[0-5])$'
                        example: '198.51.100.1'
                        nullable: true
                Ipv6Addr:
                        type: string
                        allOf:
                                 - pattern: '^{(:|(0?|([1-9a-f][0-9a-f]\{0,3\}))):)((0?|([1-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-
f]{0,3})):){0,6}(:|(0?|([1-9a-f][0-9a-f]{0,3})))$'
                               - pattern: '^((([^:]+:){7}([^:]+))|((([^:]+:)*[^:]+)?::(([^:]+:)*[^:]+)?))$'
                        example: '2001:db8:85a3::8a2e:370:7334'
                Ipv6AddrRm:
                        type: string
                        allOf:
                                 - pattern: '^((:|(0?|([1-9a-f][0-9a-f]{0,3}))):)((0?|([1-9a-f][0-9a-
f]\{0,3\})):\\ \{0,6\}(:|(0?|([1-9a-f][0-9a-f]\{0,3\})));\\ -pattern: '^((([^:]+:)\{7\}([^:]+))|((([^:]+:)*[^:]+)?::(([^:]+:)*[^:]+)?));\\ \}
                        example: '2001:db8:85a3::8a2e:370:7334'
                       nullable: true
                Ipv6Prefix:
                        type: string
                        allOf:
                                 - pattern: '^((:|(0?|([1-9a-f][0-9a-f]{0,3}))):)((0?|([1-9a-f][0-9a-
 f]\{0,3\})):\bar{)}\{0,6\}(:|(0?|([1-9a-f][0-9a-f]\{0,3\})))(\/(([0-9]]\{2\})|(1[0-1][0-9])|(12[0-8]))); \\ + ([0,3](0,3])):\bar{)}\{0,6\}(:|(0?|([1-9a-f][0-9a-f]\{0,3\}))); \\ + ([0,3](0,3](0,3])):\bar{)}\{0,6\}(:|(0?|([1-9a-f][0-9a-f]\{0,3\}))); \\ + ([0,3](0,3](0,3])):\bar{)}\{0,6\}(:|(0?|([1-9a-f][0-9a-f][0-9a-f]\{0,3\}))); \\ + ([0,3](0,3](0,3](0,3))) + ([0,3](0,3](0,3)) + ([0,3](0,3](0,3))) + ([0,3](0,3](0,3)) + ([0,3](0,3))) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3))) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3](0,3)) + ([0,3
                                - pattern: '^((([^:]+:){7}([^:]+))|((([^:]+:)*[^:]+)?::(([^:]+:)*[^:]+)?))(\/.+)$'
                        example: '2001:db8:abcd:12::0/64'
                Ipv6PrefixRm:
                        type: string
                        allOf:
                                - pattern: '^((:|(0?|([1-9a-f][0-9a-f]\{0,3\}))):)((0?|([1-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-f][0-9a-
nullable: true
               MacAddr48:
                       pattern: '^([0-9a-fA-F]{2})((-[0-9a-fA-F]{2}){5});
                MacAddr48Rm:
                        type: string
                       pattern: '^([0-9a-fA-F]{2})((-[0-9a-fA-F]{2}){5});
                       nullable: true
                SupportedFeatures:
                        type: string
                        pattern: '^[A-Fa-f0-9]*$'
                Uinteger:
                        type: integer
                        minimum: 0
```

#

```
UintegerRm:
  type: integer
  minimum: 0
 nullable: true
Uint16:
 type: integer
  minimum: 0
 maximum: 65535
Uint16Rm:
 type: integer
 minimum: 0
 maximum: 65535
 nullable: true
Uint32:
 format: int32
  type: integer
  minimum: 0
Uint32Rm:
  format: int32
  type: integer
 minimum: 0
  nullable: true
Uint64:
  format: int64
  type: integer
 minimum: 0
Uint64Rm:
  format: int64
  type: integer
  minimum: 0
 nullable: true
  type: string
UriRm:
  type: string
  nullable: true
VarUeId:
  type: string
  pattern: '^(imsi-[0-9]{5,15}|nai-.+|msisdn-[0-9]{5,15}|extid-[^@]+@[^@]+|.+)$'
VarUeIdRm:
  pattern: '^(imsi-[0-9]{5,15}|nai-.+|msisdn-[0-9]{5,15}|extid-[^@]+@[^@]+|.+)$'
  nullable: true
TimeZone:
  type: string
TimeZoneRm:
  type: string
  nullable: true
COMMON ENUMERATED DATA TYPES
PatchOperation:
  anyOf:
    - type: string
      enum:
        - add
- copy
        - move
        - remove
        - replace
        - test
    - type: string
UriScheme:
  anyOf:
    - type: string
      enum:
        - http
- https
    - type: string
ChangeType:
  anyOf:
    - type: string
      enum:
        - ADD
        - MOVE
        - REMOVE
```

```
- REPLACE
        - type: string
#
  COMMON STRUCTURED DATA TYPES
   ProblemDetails:
      type: object
      properties:
       type:
          $ref: '#/components/schemas/Uri'
        title:
         type: string
        status:
         type: integer
        detail:
         type: string
        instance:
         $ref: '#/components/schemas/Uri'
        cause:
          type: string
        invalidParams:
          type: array
          items:
           $ref: '#/components/schemas/InvalidParam'
         minItems: 1
   Link:
      type: object
      properties:
       href:
         $ref: '#/components/schemas/Uri'
    LinkRm:
      type: object
      properties:
       href:
         $ref: '#/components/schemas/Uri'
      nullable: true
    PatchItem:
      type: object
      properties:
       op:
         $ref: '#/components/schemas/PatchOperation'
       path:
         type: string
       from:
         type: string
       value:
         nullable: true
      required:
        - ор
        - path
    LinksValueSchema:
      oneOf:
       - type: array
         items:
           $ref: '#/components/schemas/Link'
         minItems: 1
        - $ref: '#/components/schemas/Link'
    SelfLink:
      type: object
      properties:
       self:
         $ref: '#/components/schemas/Link'
     required:
        - self
    InvalidParam:
      type: object
      properties:
       param:
         type: string
       reason:
         type: string
      required:
        - param
    ChangeItem:
      type: object
      properties:
```

```
$ref: '#/components/schemas/ChangeType'
    path:
      type: string
    from:
     type: string
    origValue: {}
newValue: {}
  required:
    - op
- path
NotifyItem:
  type: object
  properties:
    resourceId:
     $ref: '#/components/schemas/Uri'
    changes:
      type: array
      items:
        $ref: '#/components/schemas/ChangeItem'
      minItems: 1
ComplexQuery:
  oneOf:
    - $ref: '#/components/schemas/Cnf'
    - $ref: '#/components/schemas/Dnf'
Cnf:
  type: object
  required:
   - cnfUnits
  properties:
    cnfUnits:
      type: array
        $ref: '#/components/schemas/CnfUnit'
      minItems: 1
Dnf:
  type: object
  required:
    - dnfUnits
  properties:
    dnfUnits:
      type: array
      items:
        $ref: '#/components/schemas/DnfUnit'
      minItems: 1
CnfUnit:
  type: object
  required:
    - cnfUnit
  properties:
    cnfUnit:
      type: array
      items:
        $ref: '#/components/schemas/Atom'
      minItems: 1
DnfUnit:
  type: object
  required:
    - dnfUnit
  properties:
    dnfUnit:
      type: array
        $ref: '#/components/schemas/Atom'
      minItems: 1
Atom:
  type: object
  required:
    - attr
- value
  properties:
    attr:
     type: string
    value: {}
    negative:
      type: boolean
```

```
# Data Types related to Subscription, Identification and Numbering as defined in subclause 5.3
#
# SIMPLE DATA TYPES
    Dnn:
     type: string
    DnnRm:
      type: string
     nullable: true
    Gpsi:
     type: string
     pattern: '^(msisdn-[0-9]{5,15}|extid-[^@]+@[^@]+|.+)$'
    GpsiRm:
      type: string
      pattern: '^(msisdn-[0-9]{5,15}|extid-[^@]+@[^@]+|.+)$'
      nullable: true
    GroupId:
      type: string
      pattern: \ '^{[A-Fa-f0-9]\{8\}-[0-9]\{3\}-[0-9]\{2,3\}-([A-Fa-f0-9][A-Fa-f0-9])\{1,10\}$;}
    GroupIdRm:
      type: string
       pattern: \ '^[A-Fa-f0-9]\{8\}-[0-9]\{3\}-[0-9]\{2,3\}-([A-Fa-f0-9][A-Fa-f0-9])\{1,10\}\$' 
     nullable: true
      type: string
      pattern: '^(imei-[0-9]{15}|imeisv-[0-9]{16}|.+)$'
    PeiRm:
     type: string
      pattern: '^(imei-[0-9]{15}|imeisv-[0-9]{16}|.+)$'
     nullable: true
    Supi:
      type: string
      pattern: '^(imsi-[0-9]{5,15}|nai-.+|.+)$'
    SupiRm:
      type: string
      pattern: '^(imsi-[0-9]{5,15}|nai-.+|.+)$'
      nullable: true
    NfInstanceId:
      type: string
      format: uuid
    AmfId:
      type: string
      pattern: '^[A-Fa-f0-9]{6}$'
    AmfRegionId:
      type: string
     pattern: '^[A-Fa-f0-9]{2}$'
    AmfSetId:
     type: string
      pattern: '^[0-3][A-Fa-f0-9]{2}$'
    RfspIndex:
     type: integer
     minimum: 1
      maximum: 256
    RfspIndexRm:
      type: integer
     minimum: 1
     maximum: 256
     nullable: true
    NfGroupId:
      type: string
# STRUCTURED DATA TYPES
    Guami:
      type: object
      properties:
       plmnId:
         $ref: '#/components/schemas/PlmnId'
        amfId:
         $ref: '#/components/schemas/AmfId'
      required:
        plmnIdamfId
```

```
GuamiRm:
      type: object
     properties:
       plmnId:
         $ref: '#/components/schemas/PlmnId'
         $ref: '#/components/schemas/AmfId'
      required:
        - plmnId
        - amfId
     nullable: true
    NetworkId:
      type: object
      properties:
        mnc:
         $ref: '#/components/schemas/Mnc'
        mcc:
          $ref: '#/components/schemas/Mcc'
\mbox{\#} Data Types related to 5G Network as defined in subclause 5.4
#
# SIMPLE DATA TYPES
    ApplicationId:
     type: string
    ApplicationIdRm:
     type: string
     nullable: true
    PduSessionId:
     type: integer
     minimum: 0
     maximum: 255
      type: string
      pattern: '^d{3};
    MccRm:
     type: string
     pattern: '^\d{3}$'
     nullable: true
      type: string
     pattern: '^d{2,3};
    MncRm:
      type: string
      pattern: '^\d{2,3}$'
     nullable: true
    Tac:
     type: string
      pattern: '(^[A-Fa-f0-9]{4}$)|(^[A-Fa-f0-9]{6}$)'
     type: string
     pattern: '(^[A-Fa-f0-9]{4}$)|(^[A-Fa-f0-9]{6}$)'
     nullable: true
    EutraCellId:
     type: string
     pattern: '^[A-Fa-f0-9]{7}$'
    EutraCellIdRm:
     type: string
     pattern: '^[A-Fa-f0-9]{7}$'
     nullable: true
    NrCellId:
      type: string
     pattern: '^[A-Fa-f0-9]{9}$'
    NrCellIdRm:
     type: string
pattern: '^[A-Fa-f0-9]{9}$'
     nullable: true
    Dnai:
     type: string
    DnaiRm:
      type: string
     nullable: true
    5GMmCause:
      $ref: '#/components/schemas/Uinteger'
```

```
AmfName:
      type: string
   AreaCode:
     type: string
    AreaCodeRm:
      type: string
      nullable: true
   N3IwfId:
      type: string
      pattern: '^[A-Fa-f0-9]+$'
    NgeNbId:
      type: string
      pattern: '^(MacroNGeNB-[A-Fa-f0-9]{5}|LMacroNGeNB-[A-Fa-f0-9]{6}|SMacroNGeNB-[A-Fa-f0-9]{5})$'
# ENUMERATED DATA TYPES
#
   AccessType:
      type: string
      enum:
        - 3GPP_ACCESS
- NON_3GPP_ACCESS
    AccessTypeRm:
      type: string
      enum:
       - 3GPP_ACCESS
        - NON_3GPP_ACCESS
     nullable: true
    RatType:
     anyOf:
        - type: string
          enum:
            - NR
            - EUTRA
            - WLAN
            - VIRTUAL
        - type: string
    RatTypeRm:
      anyOf:
        - type: string
          enum:
            - NR
            - EUTRA
            - WLAN
            - VIRTUAL
        - type: string
      nullable: true
    PduSessionType:
      anyOf:
        - type: string
          enum:
            - IPV4
- IPV6
            - IPV4V6
            - UNSTRUCTURED
            - ETHERNET
        - type: string
    PduSessionTypeRm:
      anyOf:
        - type: string
          enum:
            - IPV4
            - IPV6
            - IPV4V6
            - UNSTRUCTURED
            - ETHERNET
        - type: string
      nullable: true
    UpIntegrity:
      anyOf:
        - type: string
          enum:
            - REQUIRED
            - PREFERRED
            - NOT_NEEDED
        - type: string
    UpIntegrityRm:
```

```
anyOf:
        - type: string
          enum:
           - REOUIRED
            - PREFERRED
            - NOT_NEEDED
        - type: string
     nullable: true
    UpConfidentiality:
      anyOf:
        - type: string
          enum:
            - REOUIRED
           - PREFERRED
           - NOT_NEEDED
       - type: string
    UpConfidentialityRm:
      anyOf:
        - type: string
          enum:
           - REQUIRED
            - PREFERRED
            - NOT_NEEDED
        - type: string
      nullable: true
    SscMode:
      anyOf:
        - type: string
          enum:
           - SSC_MODE_1
           - SSC_MODE_2
           - SSC_MODE_3
        - type: string
    SscModeRm:
      anyOf:
        - type: string
          enum:
           - SSC_MODE_1
           - SSC_MODE_2
           - SSC_MODE_3
        - type: string
      nullable: true
    DnaiChangeType:
      anyOf:
      - type: string
       enum:
          - EARLY
          - EARLY_LATE
          - LATE
      - type: string
       description: >
          This string provides forward-compatibility with future
          extensions to the enumeration but is not used to encode
          content defined in the present version of this API.
      description: >
        Possible values are
        - EARLY: Early notification of UP path reconfiguration.
        - EARLY_LATE: Early and late notification of UP path reconfiguration. This value shall only
be present in the subscription to the DNAI change event.
        - LATE: Late notification of UP path reconfiguration.
   DnaiChangeTypeRm:
      anyOf:
        - type: string
          enum:
           - EARLY
           - EARLY_LATE
           - LATE
        - type: string
      nullable: true
    RestrictionType:
      anyOf:
        - type: string
          enum:
           - ALLOWED_AREAS
           - NOT_ALLOWED_AREAS
        - type: string
   RestrictionTypeRm:
      anyOf:
```

```
- type: string
          enum:
           - ALLOWED_AREAS
           - NOT_ALLOWED_AREAS
        - type: string
     nullable: true
    CoreNetworkType:
      anyOf:
        - type: string
          enum:
           - 5GC
- EPC
        - type: string
    CoreNetworkTypeRm:
      anyOf:
       - type: string
         enum:

    5GC

         - EPC
        - type: string
     nullable: true
    PresenceState:
      anyOf:
        - type: string
          enum:
           - IN AREA
            - OUT_OF_AREA
            - UNKNOWN
            - INACTIVE
        - type: string
# STRUCTURED DATA TYPES
    Snssai:
     type: object
     properties:
       sst:
         type: integer
          minimum: 0
         maximum: 255
        sd:
         type: string
         pattern: '^[A-Fa-f0-9]{6}$'
      required:
       - sst
    PlmnId:
      type: object
      properties:
       mcc:
         $ref: '#/components/schemas/Mcc'
        mnc:
         $ref: '#/components/schemas/Mnc'
      required:
        - mcc
    PlmnIdRm:
      type: object
     properties:
        mcc:
         $ref: '#/components/schemas/Mcc'
        mnc:
         $ref: '#/components/schemas/Mnc'
      required:
        - mcc
        - mnc
     nullable: true
    Tai:
      type: object
      properties:
       plmnId:
         $ref: '#/components/schemas/PlmnId'
        tac:
         $ref: '#/components/schemas/Tac'
      required:
        plmnIdtac
```

```
TaiRm:
  type: object
 properties:
   plmnId:
     $ref: '#/components/schemas/PlmnId'
      $ref: '#/components/schemas/Tac'
  required:
    - plmnId
    - tac
 nullable: true
Ecqi:
  type: object
  properties:
   plmnId:
     $ref: '#/components/schemas/PlmnId'
      # PLMN Identity
    eutraCellId:
     $ref: '#/components/schemas/EutraCellId'
  required:
    - plmnId
    - eutraCellId
EcgiRm:
  type: object
 properties:
   plmnId:
      $ref: '#/components/schemas/PlmnId'
      # PLMN Identity
    eutraCellId:
     $ref: '#/components/schemas/EutraCellId'
  required:
    - plmnId
    - eutraCellId
  nullable: true
Ncgi:
  type: object
  properties:
   plmnId:
     $ref: '#/components/schemas/PlmnId'
    nrCellId:
     $ref: '#/components/schemas/NrCellId'
  required:
    - plmnId
- nrCellId
NcgiRm:
  type: object
  properties:
    plmnId:
     $ref: '#/components/schemas/PlmnId'
    nrCellId:
     $ref: '#/components/schemas/NrCellId'
  required:
    - plmnId
    - nrCellId
  nullable: true
UserLocation:
  type: object
  properties:
    eutraLocation:
     $ref: '#/components/schemas/EutraLocation'
    nrLocation:
      $ref: '#/components/schemas/NrLocation'
    n3gaLocation:
      $ref: '#/components/schemas/N3gaLocation'
EutraLocation:
  type: object
  properties:
    tai:
      $ref: '#/components/schemas/Tai'
    ecgi:
      $ref: '#/components/schemas/Ecgi'
    ageOfLocationInformation:
     type: integer
      minimum: 0
      maximum: 32767
    ueLocationTimestamp:
     $ref: '#/components/schemas/DateTime'
    geographicalInformation:
```

```
type: string
     pattern: '^[0-9A-F]{16}$'
    geodeticInformation:
     type: string
      pattern: '^[0-9A-F]{20}$'
    globalNgenbId:
     $ref: '#/components/schemas/GlobalRanNodeId'
 required:
    - tai
    - ecgi
EutraLocationRm:
  type: object
  properties:
    tai:
     $ref: '#/components/schemas/Tai'
    ecgi:
     $ref: '#/components/schemas/Ecgi'
    ageOfLocationInformation:
     type: integer
     minimum: 0
     maximum: 32767
    ueLocationTimestamp:
      $ref: '#/components/schemas/DateTime'
    geographicalInformation:
     type: string
     pattern: '^[0-9A-F]{16}$'
    geodeticInformation:
     type: string
     pattern: '^[0-9A-F]{20}$'
    globalNgenbId:
     $ref: '#/components/schemas/GlobalRanNodeId'
  required:
    - tai
- ecgi
  nullable: true
NrLocation:
  type: object
 properties:
    tai:
     $ref: '#/components/schemas/Tai'
    ncgi:
     $ref: '#/components/schemas/Ncgi'
    ageOfLocationInformation:
     type: integer
     minimum: 0
     maximum: 32767
    ueLocationTimestamp:
     $ref: '#/components/schemas/DateTime'
    geographicalInformation:
     type: string
     pattern: '^[0-9A-F]{16}$'
    geodeticInformation:
     type: string
     pattern: '^[0-9A-F]{20}$'
    globalGnbId:
     $ref: '#/components/schemas/GlobalRanNodeId'
  required:
    - tai
    - ncgi
NrLocationRm:
  type: object
  properties:
    tai:
     $ref: '#/components/schemas/Tai'
    ncai:
     $ref: '#/components/schemas/Ncgi'
    ageOfLocationInformation:
     type: integer
     minimum: 0
maximum: 32767
    ueLocationTimestamp:
     $ref: '#/components/schemas/DateTime'
    geographicalInformation:
     type: string
     pattern: '^[0-9A-F]{16}$'
    geodeticInformation:
     type: string
     pattern: '^[0-9A-F]{20}$'
```

```
globalGnbId:
     $ref: '#/components/schemas/GlobalRanNodeId'
 required:
    - tai
    - ncgi
 nullable: true
N3gaLocation:
 type: object
 properties:
   n3gppTai:
     $ref: '#/components/schemas/Tai'
   n3IwfId:
     type: string
     pattern: '^[A-Fa-f0-9]+$'
    ueIpv4Addr:
     $ref: '#/components/schemas/Ipv4Addr'
    ueIpv6Addr:
     $ref: '#/components/schemas/Ipv6Addr'
   portNumber:
     $ref: '#/components/schemas/Uinteger'
UpSecurity:
  type: object
 properties:
   upIntegr:
     $ref: '#/components/schemas/UpIntegrity'
    upConfid:
     $ref: '#/components/schemas/UpConfidentiality'
  required:
    - upIntegr
    - upConfid
UpSecurityRm:
 type: object
 properties:
    upIntegr:
     $ref: '#/components/schemas/UpIntegrity'
    upConfid:
     $ref: '#/components/schemas/UpConfidentiality'
 required:
    - upIntegr
    - upConfid
 nullable: true
NgApCause:
 type: object
 properties:
   group:
     $ref: '#/components/schemas/Uinteger'
    value:
     $ref: '#/components/schemas/Uinteger'
  required:
   - group
    - value
BackupAmfInfo:
  type: object
  properties:
   backupAmf:
     $ref: '#/components/schemas/AmfName'
    guamiList:
     type: array
      items:
        $ref: '#/components/schemas/Guami'
     minItems: 1
 required:
    - backupAmf
RefToBinaryData:
  type: object
 properties:
   contentId:
     type: string
 required:
    - contentId
RefToBinaryDataRm:
 type: object
 properties:
   contentId:
     type: string
  required:
     - contentId
 nullable: true
```

```
RouteToLocation:
 type: object
 properties:
   dnai:
     $ref: '#/components/schemas/Dnai'
    routeInfo:
     $ref: '#/components/schemas/RouteInformation'
   routeProfId:
     type: string
     nullable: true
 required:
    - dnai
  anyOf:
    - required: [ routeInfo ]
    - required: [ routeProfId ]
 nullable: true
RouteInformation:
  type: object
 properties:
   ipv4Addr:
     $ref: '#/components/schemas/Ipv4Addr'
    ipv6Addr:
      $ref: '#/components/schemas/Ipv6Addr'
   portNumber:
     $ref: '#/components/schemas/Uinteger'
  required:
    - portNumber
 nullable: true
SubscribedDefaultQos:
 type: object
 required:
   - 5qi
    - arp
 properties:
    5qi:
     $ref: '#/components/schemas/5Qi'
    arp:
     $ref: '#/components/schemas/Arp'
    priorityLevel:
     $ref: '#/components/schemas/5QiPriorityLevel'
 type: object
 oneOf:
    - required:
     - tacs
    - required:

    areaCode

  properties:
    tacs:
     type: array
     items:
       $ref: '#/components/schemas/Tac'
     minItems: 1
    areaCodes:
       $ref: '#/components/schemas/AreaCode'
ServiceAreaRestriction:
  type: object
 properties:
   restrictionType:
     $ref: '#/components/schemas/RestrictionType'
    areas:
      type: array
      items:
        $ref: '#/components/schemas/Area'
    maxNumOfTAs:
     $ref: '#/components/schemas/Uinteger'
  allOf:
    # 1st condition: restrictionType and areas attributes shall be either both absent
                     or both present
    - oneOf:
        - not:
            required: [ restrictionType ]
        - required: [ areas ]
    # 2nd condition: if restrictionType takes value NOT_ALLOWED_AREAS,
                     then maxNumOfTAs shall be absent
```

```
- anyOf:
        - not:
            required: [ restrictionType ]
            properties:
             restrictionType:
                type: string
                enum: [ NOT_ALLOWED_AREAS ]
        - not:
           required: [ maxNumOfTAs ]
PresenceInfo:
  type: object
 properties:
   praId:
     type: string
    presenceState:
     $ref: '#/components/schemas/PresenceState'
    trackingAreaList:
     type: array
      items:
       $ref: '#/components/schemas/Tai'
     minItems: 1
    ecgiList:
      type: array
      items:
        $ref: '#/components/schemas/Ecgi'
     minItems: 1
    ncgiList:
     type: array
      items:
        $ref: '#/components/schemas/Ncgi'
     minItems: 1
    globalRanNodeIdList:
      type: array
      items:
        $ref: '#/components/schemas/GlobalRanNodeId'
     minItems: 1
PresenceInfoRm:
  type: object
 properties:
   praId:
     type: string
    presenceState:
     $ref: '#/components/schemas/PresenceState'
    trackingAreaList:
     type: array
      items:
        $ref: '#/components/schemas/Tai'
     minItems: 0
    ecgiList:
     type: array
      items:
        $ref: '#/components/schemas/Ecgi'
     minItems: 0
   ncgiList:
     type: array
      items:
        $ref: '#/components/schemas/Ncgi'
     minItems: 0
    globalRanNodeIdList:
      type: array
      items:
        $ref: '#/components/schemas/GlobalRanNodeId'
  nullable: true
GlobalRanNodeId:
  type: object
 properties:
   plmnId:
      $ref: '#/components/schemas/PlmnId'
    n3IwfId:
      $ref: '#/components/schemas/N3IwfId'
    gNbId:
     $ref: '#/components/schemas/GNbId'
   ngeNbId:
     $ref: '#/components/schemas/NgeNbId'
  oneOf:
    - required: [ n3IwfId ]
    - required: [ qNbId ]
```

```
- required: [ ngeNbId ]
      required:
       - plmnId
    GNbId:
      type: object
      properties:
        bitLength:
         type: integer
         minimum: 22
         maximum: 32
        gNBValue:
         type: string
          pattern: '^[A-Fa-f0-9]{6,8}$'
      required:
        - bitLength
        - gNBValue
# Data Types related to 5G QoS as defined in subclause 5.5
#
 SIMPLE DATA TYPES
#
#
    Qfi:
     type: integer
     minimum: 0
     maximum: 63
    QfiRm:
     type: integer
     minimum: 0
     maximum: 63
     nullable: true
    5Qi:
     type: integer
     minimum: 0
     maximum: 255
    5QiRm:
     type: integer
     minimum: 0
     maximum: 255
     nullable: true
    BitRate:
      type: string
      pattern: \' \' d+(\.\d+) ? \ (bps | Kbps | Mbps | Gbps | Tbps) $'
    BitRateRm:
      type: string
     pattern: '^\d+(\.\d+)? (bps|Kbps|Mbps|Gbps|Tbps)$'
     nullable: true
    ArpPriorityLevelRm:
     type: integer
     minimum: 1
     maximum: 15
     nullable: true
    ArpPriorityLevel:
     type: integer
      minimum: 1
     maximum: 15
     nullable: true
      description: nullable true shall not be used for this attribute
    5QiPriorityLevel:
      type: integer
     minimum: 1
     maximum: 127
    5QiPriorityLevelRm:
     type: integer
     minimum: 1
     maximum: 127
     nullable: true
    PacketDelBudget:
     type: integer
      minimum: 1
    PacketDelBudgetRm:
      type: integer
      minimum: 1
     nullable: true
```

```
PacketErrRate:
     type: string
     pattern: '^([0-9]E-[0-9])$'
    PacketErrRateRm:
     type: string
     pattern: '^([0-9]E-[0-9])$'
     nullable: true
    PacketLossRate:
     type: integer
     minimum: 0
     maximum: 1000
    PacketLossRateRm:
     type: integer
     minimum: 0
     maximum: 1000
     nullable: true
    AverWindow:
     type: integer
     minimum: 1
     maximum: 4095
     default: 2000
    AverWindowRm:
     type: integer
     maximum: 4095
     default: 2000
     minimum: 1
     nullable: true
    MaxDataBurstVol:
     type: integer
     minimum: 1
     maximum: 4095
    MaxDataBurstVolRm:
      type: integer
     minimum: 1
     maximum: 4095
     nullable: true
# ENUMERATED DATA TYPES
    PreemptionCapability:
     anyOf:
       - type: string
         enum:
           - NOT_PREEMPT
           - MAY_PREEMPT
       - type: string
    PreemptionCapabilityRm:
     anyOf:
        - type: string
         enum:
           NOT_PREEMPTMAY_PREEMPT
        - type: string
     nullable: true
    {\tt Preemption Vulnerability:}
     anyOf:
        - type: string
         enum:
           - NOT_PREEMPTABLE
           - PREEMPTABLE
       - type: string
    PreemptionVulnerabilityRm:
      anyOf:
        - type: string
          enum:
           - NOT_PREEMPTABLE
            - PREEMPTABLE
       - type: string
      nullable: true
    ReflectiveQoSAttribute:
     anyOf:
        - type: string
         enum:
           - RQOS
            - NO_RQOS
        - type: string
```

```
ReflectiveQoSAttributeRm:
      anyOf:
        - type: string
          enum:
            - RQOS
            - NO_RQOS
        - type: string
     nullable: true
   NotificationControl:
     anyOf:
        - type: string
          enum:
            - REOUESTED
            - NOT_REQUESTED
        - type: string
   NotificationControlRm:
      anyOf:
        - type: string
          enum:
           - REQUESTED
            - NOT_REQUESTED
        - type: string
      nullable: true
    QosResourceType:
      anyOf:
        - type: string
          enum:
            - NON_GBR
            - NON_CRITICAL_GBR
           - CRITICAL_GBR
       - type: string
    QosResourceTypeRm:
      anyOf:
        - type: string
          enum:
            - NON_GBR
            - NON_CRITICAL_GBR
           - CRITICAL_GBR
        - type: string
      nullable: true
    AdditionalQosFlowInfo:
     anyOf:
       - type: string
         enum:
           - MORE_LIKELY
        - type: string
     nullable: true
#
# STRUCTURED DATA TYPES
    Arp:
     type: object
     properties:
       priorityLevel:
         $ref: '#/components/schemas/ArpPriorityLevel'
       preemptCap:
         $ref: '#/components/schemas/PreemptionCapability'
       preemptVuln:
         $ref: '#/components/schemas/PreemptionVulnerability'
      required:
        priorityLevelpreemptCap
        - preemptVuln
    ArpRm:
      type: object
      properties:
       \verb"priorityLevel":
          $ref: '#/components/schemas/ArpPriorityLevel'
       preemptCap:
         $ref: '#/components/schemas/PreemptionCapability'
       preemptVuln:
         $ref: '#/components/schemas/PreemptionVulnerability'
      required:
        priorityLevelpreemptCap
```

```
- preemptVuln
      nullable: true
    Ambr:
      type: object
      properties:
        uplink:
          $ref: '#/components/schemas/BitRate'
        downlink:
          $ref: '#/components/schemas/BitRate'
      required:
        - uplink
        - downlink
    AmbrRm:
      type: object
      properties:
        uplink:
          $ref: '#/components/schemas/BitRate'
        downlink:
          $ref: '#/components/schemas/BitRate'
      required:
        - uplink
        - downlink
      nullable: true
    Dynamic5Qi:
      type: object
      properties:
        resourceType:
          $ref: '#/components/schemas/QosResourceType'
        priorityLevel:
          $ref: '#/components/schemas/5QiPriorityLevel'
        packetDelayBudget:
         $ref: '#/components/schemas/PacketDelBudget'
        packetErrRate:
          $ref: '#/components/schemas/PacketErrRate'
        averWindow:
          $ref: '#/components/schemas/AverWindow'
        maxDataBurstVol:
          $ref: '#/components/schemas/MaxDataBurstVol'
      required:
        - resourceType
        - priorityLevel
        - packetDelayBudget
        - packetErrRate
    NonDynamic5Qi:
      type: object
      properties:
        \verb"priorityLevel":
          $ref: '#/components/schemas/5QiPriorityLevel'
        averWindow:
         $ref: '#/components/schemas/AverWindow'
        maxDataBurstVol:
          $ref: '#/components/schemas/MaxDataBurstVol'
      minProperties: 0
# Data Types related to 5G Trace as defined in subclause 5.6
#
#
# SIMPLE DATA TYPES
#
#
 Enumerations
#
    TraceDepth:
      anyOf:
        - type: string
          enum:
            - MINIMUM
            - MEDIUM
            - MAXIMUM
            - MINIMUM_WO_VENDOR_EXTENSION
            - MEDIUM_WO_VENDOR_EXTENSION
            - MAXIMUM_WO_VENDOR_EXTENSION
        - type: string
    TraceDepthRm:
      anyOf:
```

```
- type: string
          enum:
           - MINIMUM
            - MEDIUM
            - MAXIMUM
            - MINIMUM_WO_VENDOR_EXTENSION
            - MEDIUM_WO_VENDOR_EXTENSION
           - MAXIMUM_WO_VENDOR_EXTENSION
        - type: string
      nullable: true
# STRUCTURED DATA TYPES
    TraceData:
      type: object
     nullable: true
     properties:
        traceRef:
         type: string
         pattern: '^[0-9]{3}[0-9]{2,3}-[A-Fa-f0-9]{6}$'
        traceDepth:
         $ref: '#/components/schemas/TraceDepth'
        neTypeList:
         type: string
         pattern: '^[A-Fa-f0-9]+$'
        eventList:
         type: string
          pattern: '^[A-Fa-f0-9]+$'
       collectionEntityIpv4Addr:
          $ref: '#/components/schemas/Ipv4Addr'
        collectionEntityIpv6Addr:
         $ref: '#/components/schemas/Ipv6Addr'
        interfaceList:
          type: string
         pattern: '^[A-Fa-f0-9]+$'
      required:
        - traceRef
        - traceDepth
        - neTypeList
        - eventList
# Data Types related to 5G ODB as defined in subclause 5.7
# SIMPLE DATA TYPES
#
#
 Enumerations
   RoamingOdb:
      anyOf:
         type: string
          enum:
           - OUTSIDE_HOME_PLMN
            - OUTSIDE_HOME_PLMN_COUNTRY
        - type: string
   OdbPacketServices:
      anyOf:
        - type: string
          enum:
            - ALL_PACKET_SERVICES
            - ROAMER_ACCESS_HPLMN_AP
            - ROAMER_ACCESS_VPLMN_AP
        - type: string
      nullable: true
# STRUCTURED DATA TYPES
    OdbData:
      type: object
      properties:
       roamingOdb:
          $ref: '#/components/schemas/RoamingOdb'
```

```
# Data Types related to Charging as defined in subclause 5.8
# SIMPLE DATA TYPES
#
#
    ChargingId:
     $ref: '#/components/schemas/Uint32'
    RatingGroup:
      $ref: '#/components/schemas/Uint32'
    ServiceId:
      $ref: '#/components/schemas/Uint32'
# Enumerations
#
# STRUCTURED DATA TYPES
    SecondaryRatUsageReport:
      type: object
     properties:
        secondaryRatType:
         $ref: '#/components/schemas/RatType'
        qosFlowsUsageData:
          type: array
         items:
            $ref: '#/components/schemas/QosFlowUsageReport'
          minItems: 1
      required:
        - secondaryRatType
        - qosFlowsUsageData
    QosFlowUsageReport:
      type: object
      properties:
        qfi:
         $ref: '#/components/schemas/Qfi'
        startTimeStamp:
         $ref: '#/components/schemas/DateTime'
        endTimeStamp:
          $ref: '#/components/schemas/DateTime'
        downlinkVolume:
          $ref: '#/components/schemas/Int64'
        uplinkVolume:
         $ref: '#/components/schemas/Int64'
      required:
        - qfi
        - startTimeStamp
        - endTimeStamp
        - downlinkVolume
        - uplinkVolume
# HTTP responses
  responses:
    '400':
     description: Bad request
      content:
        application/problem+json:
         schema:
            $ref: '#/components/schemas/ProblemDetails'
    '401':
      description: Unauthorized
        application/problem+json:
          schema:
            $ref: '#/components/schemas/ProblemDetails'
```

```
'403':
 description: Forbidden
 content:
   application/problem+json:
     schema:
       $ref: '#/components/schemas/ProblemDetails'
'404':
 description: Not Found
 content:
   application/problem+json:
     schema:
       $ref: '#/components/schemas/ProblemDetails'
4051:
 description: Method Not Allowed
'408':
 description: Request Timeout
 content:
   application/problem+json:
     schema:
       $ref: '#/components/schemas/ProblemDetails'
'406':
 description: 406 Not Acceptable
'409':
 description: Conflict
 content:
   application/problem+json:
     schema:
       $ref: '#/components/schemas/ProblemDetails'
 description: Gone
 content:
   application/problem+json:
     schema:
        $ref: '#/components/schemas/ProblemDetails'
'411':
 description: Length Required
 content:
   application/problem+json:
     schema:
       $ref: '#/components/schemas/ProblemDetails'
'412':
 description: Precondition Failed
 content:
    application/problem+json:
       $ref: '#/components/schemas/ProblemDetails'
'413':
 description: Payload Too Large
 content:
   application/problem+json:
     schema:
       $ref: '#/components/schemas/ProblemDetails'
14141:
 description: URI Too Long
 content:
   application/problem+json:
     schema:
        $ref: '#/components/schemas/ProblemDetails'
 description: Unsupported Media Type
 content:
    application/problem+json:
     schema:
        $ref: '#/components/schemas/ProblemDetails'
'429':
 description: Too Many Requests
 content:
   application/problem+json:
     schema:
        $ref: '#/components/schemas/ProblemDetails'
500:
 description: Internal Server Error
 content:
   application/problem+json:
     schema:
       $ref: '#/components/schemas/ProblemDetails'
'501':
 description: Not Implemented
```

```
content:
   application/problem+json:
    schema:
$ref: '#/components/schemas/ProblemDetails'
'503':
 description: Service Unavailable
 content:
   application/problem+json:
     schema:
       $ref: '#/components/schemas/ProblemDetails'
'504':
 description: Gateway Timeout
 content:
   application/problem+json:
     schema:
      $ref: '#/components/schemas/ProblemDetails'
default:
  description: Generic Error
```

Annex B (informative): Change history

						Change history	
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New
0017.10	OT 4 # 0.0	04.475040				1.22.15.6	version
2017-10	CT4#80	C4-175048				Initial Draft.	0.1.0
2017-10 2017-12	CT4#80 CT4#81	C4-175400 C4-176442		-		Skeleton and scope After CT4#81	0.2.0
2017-12	CT4#81	C4-176442 C4-181395				After CT4#82	0.3.0
2018-03	CT4#83	C4-182440				After CT4#83	0.5.0
2018-04	CT4#84	C4-183521				After CT4#84	0.6.0
2018-05	CT4#85	C4-184635				After CT4#85	0.7.0
2018-06	CT#80	CP-181110				Presented for information and approval	1.0.0
2018-06	CT#80					Approved in CT#80	15.0.0
2018-09	CT#81	CP-182065	0001		F	ProblemDetails	15.1.0
2018-09	CT#81	CP-182065	0002		F	Structure of Amfld	15.1.0
2018-09	CT#81	CP-182065	0012		В	DNAI change notification type	15.1.0
2018-09	CT#81	CP-182065	0015		F	RatType	15.1.0
2018-09	CT#81	CP-182065	0017	1	ВВ	Definition of DNAI	15.1.0
2018-09 2018-09	CT#81 CT#81	CP-182068 CP-182065	0008	1	F	Add support for 5G Trace OpenAPI Corrections	15.1.0 15.1.0
2018-09	CT#81	CP-182065	0010	1	В	Structure of ECGI and NCGI	15.1.0
2018-09	CT#81	CP-182065	0007	1	F	Averaging Window	15.1.0
2018-09	CT#81	CP-182065	0020	1	_	sd pattern	15.1.0
2018-09	CT#81	CP-182065	0021	1		Correction of the title of clauses 5.2.4.4 _LinksValueSchema and 5.2.4.5 _ SelfLink	15.1.0
2018-09	CT#81	CP-182065	0023		F	NAI format in 5G System	15.1.0
2018-09	CT#81	CP-182065	0031		F	GroupId Definition	15.1.0
2018-09	CT#81	CP-182065	0009	1	F	Removal of systematic references to the "format" keyword in data type definitions	15.1.0
2018-09	CT#81	CP-182065	0033		F	Naming Conventions	15.1.0
2018-09	CT#81	CP-182065	0027	1	F	5GMMCause and NGAP Cause	15.1.0
2018-09	CT#81	CP-182173	0006	3		BackUp AMF Info	15.1.0
2018-09	CT#81	CP-182065	0035		F	URI Scheme	15.1.0
2018-09	CT#81	CP-182065	0024	2		Cleanup of the specification	15.1.0
2018-09	CT#81 CT#81	CP-182065	0025 0005	4	F	Correction to Regular Expression Pattern of GPSI	15.1.0
2018-09 2018-09	CT#81	CP-182065 CP-182065	0005	1		Common data types: NonDynamic5qi and Dynamic5qi Common data type used in both TS 29.505 and TS 29.519	15.1.0 15.1.0
2018-09	CT#81	CP-182065	0029	1	В	n6 Traffic Routing Information data type	15.1.0
2018-09	CT#81	CP-182065	0019	4		DefaultQosInformation	15.1.0
2018-09	CT#81	CP-182065	0034	1		Update of N3gaLocation data type	15.1.0
2018-09	CT#81	CP-182065	0016	3	F	Mobility Restriction	15.1.0
2018-09	CT#81	CP-182042	0030	3		Adding "nullable" property to OpenAPI definitions of data types	15.1.0
2018-09	CT#81	CP-182174	0026	3		Presence Reporting Area	15.1.0
2018-09	CT#81	CP-182011	0032	4		Adding age of location, geographic information and other missing ones in the UserLocation type	15.1.0
2018-09		CP-182183		1		Common data type for data change notification	15.1.0
2018-09	CT#81	CP-182065	0037		F	API version number update	15.1.0
2018-12 2018-12	CT#82	CP-183024	0040		F	Application ID Corrections to PDU Session Id, PDU Session Type and	15.2.0
	CT#82	CP-183024				SupportedFeatures	15.2.0
2018-12 2018-12	CT#82 CT#82	CP-183024 CP-183024	0038 0047	1	F	Area definition DNN	15.2.0 15.2.0
2018-12	CT#82	CP-183024 CP-183024	0047	1		Update of missing status code 429 in TS 29.571	15.2.0
2018-12	CT#82	CP-183024	0057	1	_	29571 CR cardinality	15.2.0
2018-12	CT#82	CP-183024	0037	2		The ARP in Default QoS	15.2.0
2018-12	CT#82	CP-183024	0058	1		Snssai pattern	15.2.0
2018-12	CT#82	CP-183024	0039	1		GroupId pattern	15.2.0
2018-12	CT#82	CP-183024	0059		F	Adding of HTTP status code "406 Not Acceptable"	15.2.0
2018-12	CT#82	CP-183024	0041	1		VarUeld definition	15.2.0
2018-12	CT#82	CP-183024	0061		F	ProblemDetails for 501	15.2.0
2018-12	CT#82	CP-183024	0063	1	F	ChangeItem alignment	15.2.0
2018-12	CT#82	CP-183024	0046	2		Regular Expression Patterns	15.2.0
2018-12	CT#82	CP-183024	0048	3		Alignments with NGAP	15.2.0
2018-12 2018-12	CT#82 CT#82	CP-183168 CP-183024	0065	1		Secondary RAT usage data reporting Data types associated with Subscribed and Authorized Default QoS for Default QoS Flow	15.2.0 15.2.0
2018-12	CT#82	CP-183024	0042	3	F	Alignment of pattern for data types with "nullable" property	15.2.0
2018-12	CT#82	CP-183024	0042	1	+	NF Group Id	15.2.0
2018-12	CT#82	CP-183024	0053	2		data type for complex query expression	15.2.0
2010-12	CT#82	CP-183161	0064	2		NgRanIdentifier and PresenceInfo	15.2.0
		1 00 101					
2018-12		CP-183024	0068		F	Addition of HTTP status code "412 Precondition Failed"	15.20
	CT#82 CT#82	CP-183024 CP-183024	0068 0051	3	F	Addition of HTTP status code "412 Precondition Failed" Introduction of Barring of Roaming in 5GC	15.2.0 15.2.0

2018-12	CT#82	CP-183024	0067	1	F	Charging related types	15.2.0
2018-12	CT#82	CP-183024	0070		F	Correction of the reference for the SupportedFeatures Data Type	15.2.0
2018-12	CT#82	CP-183024	0072	1	F	Update open API version	15.2.0
2018-12	CT#82	CP-183024	0073		F	ExternalDoc update	15.2.0
2019-03	CT#83	CP-190029	0075	3	F	Corrections on subscribed Priority	15.3.0
2019-03	CT#83	CP-190029	0076	1	F	AmfRegionId and AmfSetId	15.3.0
2019-03	CT#83	CP-190029	0077	2	F	Supported features	15.3.0
2019-03	CT#83	CP-190029	0078	2	F	Corrections on n3iwf Id	15.3.0
2019-03	CT#83	CP-190029	0079	2	F	Corrections on the encoding of bit string	15.3.0
2019-03	CT#83	CP-190029	0081	2	F	Corrections on Type RouteToLocation	15.3.0
2019-03	CT#83	CP-190029	0082	1	F	ODB correction	15.3.0
2019-03	CT#83	CP-190029	0083		F	3GPP TS 29.571 API version update	15.3.0

History

Document history						
V15.0.0	September 2018	Publication				
V15.1.0	October 2018	Publication				
V15.2.0	April 2019	Publication				
V15.3.0	April 2019	Publication				