

# Moro Game Console Specification

Version: 0.1.13

Last Modified: Sat, 01 Jun 2013 15:45:12 +0000

Authors: C Nelson

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in RFC 2119.

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 Unported License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>.

The spirit of this specification is to define a limited, retro, cartridge-based console. It defines a very limited set of parameters which should be adhered to by implementing parties to maintain the feeling and spirit of Moro. Moro is meant to be old-fashioned and nostalgic. Modern conveniences should be shunned.

Moro is the Amish of the game console world.

## Software

Implementations of this specification **MUST** use GNU/Linux.

It is **RECOMMENDED** to use a Debian-based distribution, but most distributions will work.

Implementations **MUST** also use X11. It is **RECOMMENDED** to use XOrg.

Implementations **SHOULD** have a very basic window manager, configured such that normal applications will be displayed fullscreen and with no window decorators.

The reference implementation uses lightdm (<http://www.freedesktop.org/wiki/Software/LightDM/>) as its display manager, and fluxbox (<http://fluxbox.org/>) as its window manager.

When started, the OS **SHOULD** automatically mount any mass storage drives that are connected.

The mass storage drives **SHOULD** be mounted according to their filesystem labels following the pattern “/media/”.

After mounting, the OS **MUST** attempt to execute “/media/app/launcher”.

The file **MUST** be executable.

Its current/working directory **SHOULD** be “~”.

## Hardware

### Cartridge

There MAY be only one mass storage drive in the cartridge. Any additional drives in the cartridge SHOULD be used by the application itself, and will not be automatically used by the operating system.

The filesystem containing the main executable MUST be labeled “app”. Additional mass storage drives SHOULD be labeled with meaningful names, but they will not be used directly.

The auxilliary drives MAY be used for cached data files, cartridge-local game saves, or other application data.

Digital Restrictions Management (<http://drm.info/>) MAY be implemented (though NOT RECOMMENDED) by requiring a device to always be connected to the GPIO connector and respond to challenges presented by the application. It is RECOMMENDED that if this is implemented in an application, only a warning is presented about the application’s authenticity.

Applications MUST NOT require a network connection to operate unless it is a vital part of the application.

### Console

**Slot** The Slot is the opening that receives game cartridges.

The Slot MUST be at least, 10cm long, 2cm wide, with a minimum depth of 2cm, and a maximum depth of 4cm.

The connectors between the console and the cartridge SHOULD be out of sight during normal usage.

**Cartridge Connectors** There are two connectors supported for connecting cartridges.

**USB** There MUST be two female USB connectors on either end of the area immediately below the slot.

They MUST be offset toward the center of the slot by 1cm from either side.

They MUST also be aligned vertically, with the long edge of the USB connector aligned with the short edge of the slot.

**GPIO** In the dead center of the area immediately below the slot, there SHOULD be a bank of 26 (2x13) female pin headers. If present, they MUST be 0.1"-spaced.

There MAY be more than 26 female pin headers, but they must be the same spacing and extend on either side as an addition to the primary bank of 26. If present, the additional banks MUST NOT have any space between it and the primary bank of headers.

**Gamepad Connectors** There MUST be at least two USB connectors (more are RECOMMENDED) on the front of the console. These connectors SHOULD be suggested to the end-user that they are for gamepads, keyboards, mice, and other user input devices.