

# Biostatistics 615 - Statistical Computing

## Lecture 13

### Random Numbers and Monte Carlo Methods

Jian Kang

Nov 5, 2015

# Random Numbers

## True random numbers

- Truly random, non-deterministic numbers
- Easy to imagine conceptually
- Very hard to generate one or test its randomness
- For example, <http://www.random.org> generates randomness via atmospheric noise

## Pseudo random numbers

- A deterministic sequence of random numbers (or bits) from a seed
- Good random numbers should be very hard to guess the next number just based on the observations.

# Usage of random numbers in statistical methods

- Resampling procedure
  - Permutation
  - Bootstrapping
- Simulation of data for evaluating a statistical method.
- Stochastic processes
  - Markov-Chain Monte-Carlo (MCMC) methods

# Usage of random numbers in other areas

- Hashing

- Good hash function uniformly distribute the keys to the hash space
- Good pseudo-random number generators can replace a good hash function

- Cryptography

- Generating pseudo-random numbers given a seed is equivalent to <sup>加密</sup>encrypting the seed to a sequence of random bits
- If the pattern of pseudo-random numbers can be predicted, the original seed can also be deciphered.

# True random numbers

**DILBERT** By SCOTT ADAMS



- Generate only through physical process
- Hard to generate automatically
- Very hard to provide true randomness

# Pseudo-random numbers : Example code

```
#include <iostream>
#include <cstdlib>
int main(int argc, char** argv) {
    int n = (argc > 1) ? atoi(argv[1]) : 1;
    int seed = (argc > 2) ? atoi(argv[2]) : 0;

    srand(seed); // set seed -- same seed, same pseudo-random numbers

    for(int i=0; i < n; ++i) {
        std::cout << (double)rand()/(RAND_MAX+1.) << std::endl;
        // generate value between 0 and 1
    }

    return 0;
}
```

# Pseudo-random numbers : Example run

```
user@host:~/ $ ./randExample 3 0
0.242578
0.0134696
0.383139
user@host:~/ $ ./randExample 3 0
0.242578
0.0134696
0.383139
user@host:~/ $ ./randExample 3 10
7.82637e-05
0.315378
0.556053
```

# Properties of pseudo-random numbers

## Deterministic given the seed

- Given a fixed random seed, the pseudo-random numbers should generate identical sequence of random numbers
- Deterministic feature is useful for debugging a code



## Irregularity and unpredictability without knowing the seed

- Without knowing the seed, the random numbers should be hard to guess
- If you can guess it better than random, it is possible to exploit the weakness to generate random numbers with a skewed distribution.

偏态分布



# Good vs. bad random numbers



- Images using true random numbers from random.org vs. rand() function in PHP
- Visible patterns suggest that rand() gives predictable sequence of pseudo-random numbers

# Generating uniform random numbers - example in R

```
> x <- runif(10)          # x is size 10 vector uniformly distributed from 0 to 1
> x <- runif(10,0,10)      # x ranges 0 to 10
> x <- as.integer(runif(10,0,10))
> x
[1] 6 0 7 4 4 8 1 4 3 4
> set.seed(3429248)        # set an arbitrary seed
> x <- as.integer(runif(10,0,10))
> x
[1] 7 6 3 4 6 7 4 9 2 1
> set.seed(3429248)        # setting the same seed
> x <- as.integer(runif(10,0,10)) # reproduce the same random variables
> x
[1] 7 6 3 4 6 7 4 9 2 1
```

# Generating uniform random numbers in C++

```
#include <iostream>
#include <boost/random/uniform_int.hpp>
#include <boost/random/uniform_real.hpp>
#include <boost/random/variante_generator.hpp>
#include <boost/random/mercenne_twister.hpp>
int main(int argc, char** argv) {
    typedef boost::mt19937 prgType; // Mersenne-twister : a widely used
    prgType rng; // lightweight pseudo-random-number-generator
    boost::uniform_int<> six(1,6); // uniform distribution from 1 to 6
    boost::variante_generator<prgType&, boost::uniform_int<> > die(rng,six);
    // die maps random numbers from rng to uniform distribution 1..6
    映射
    int x = die(); // generate a random integer between 1 and 6
    std::cout << "Rolled die : " << x << std::endl;

    boost::uniform_real<> uni_dist(0,1);
    boost::variante_generator<prgType&, boost::uniform_real<> > uni(rng,uni_dist);
    double y = uni(); // generate a random number between 0 and 1
    std::cout << "Uniform real : " << y << std::endl;
    return 0;
}
```

# Running Example

```
user@host:~/ $ ./randExample  
Rolled die : 5  
Uniform real : 0.135477
```

```
user@host:~/ $ ./randExample  
Rolled die : 5  
Uniform real : 0.135477
```

The random number does not vary (unlike R)

to get a different sequence , we need to set seed

# Specifying the seed

```
int main(int argc, char** argv) {  
    typedef boost::mt19937 prgType;  
    prgType rng;  
    if ( argc > 1 )  
        rng.seed(atoi(argv[1])); // set seed if argument is specified  
  
    boost::uniform_int<> six(1,6);  
    // ... same as before  
}
```

# Running Example

```
user@host:~/$ ./randExample  
Rolled die : 5  
Uniform real : 0.135477
```

```
user@host:~/$ ./randExample 1  
Rolled die : 3  
Uniform real : 0.997185
```

```
user@host:~/$ ./randExample 3  
Rolled die : 4  
Uniform real : 0.0707249
```

```
user@host:~/$ ./randExample 3  
Rolled die : 4  
Uniform real : 0.0707249
```

# If we don't want the reproducibility

```
// include other headers as before
#include <ctime>
int main(int argc, char** argv) {
    typedef boost::mt19937 prgType;
    prgType rng;
    if ( argc > 1 )
        rng.seed(atoi(argv[1])); // set seed if argument is specified
    else
        rng.seed(std::time(0));    // otherwise, use current time to pick
                                   // arbitrary seed to start

    boost::uniform_int<> six(1,6);
    // ... same as before
}
```

# Running Example

```
user@host:~/$ ./randExample  
Rolled die : 4  
Uniform real : 0.367588
```

```
user@host:~/$ ./randExample  
Rolled die : 5  
Uniform real : 0.0984682
```

```
user@host:~/$ ./randExample 3  
Rolled die : 4  
Uniform real : 0.0707249
```

```
user@host:~/$ ./randExample 3  
Rolled die : 4  
Uniform real : 0.0707249
```



# Generating random numbers from non-uniform distribution

## Sampling from known distribution using R

```
> x <- rnorm(1)      # x is a random number sampled from  $N(0,1)$   
> y <- rnorm(1,3,2)  # y is a random number sampled from  $N(3,2^2)$   
> z <- rbinom(1,1,0.3) # z is a Bernoulli random number with  $p=0.3$ 
```

# Generating random numbers from non-uniform distribution

## Sampling from known distribution using R

```
> x <- rnorm(1)      # x is a random number sampled from  $N(0,1)$   
> y <- rnorm(1,3,2)  # y is a random number sampled from  $N(3,2^2)$   
> z <- rbinom(1,1,0.3) # z is a Bernoulli random number with  $p=0.3$ 
```

What if `runif()` was the only random number generator we have?

# Generating random numbers from non-uniform distribution

## Sampling from known distribution using R

```
> x <- rnorm(1)      # x is a random number sampled from  $N(0,1)$ 
> y <- rnorm(1,3,2)   # y is a random number sampled from  $N(3,2^2)$ 
> z <- rbinom(1,1,0.3) # z is a Bernoulli random number with  $p=0.3$ 
```

## What if runif() was the only random number generator we have?

If we know the inverse CDF, it is easy to implement

```
> x <- qnorm(runif(1)) # x follows  $N(0,1)$ 
> y <- qnorm(runif(1),3,2) # equivalent to  $y <- qnorm(runif(1))*2+3$ 
> z <- qbinom(runif(1),1,0.3) # z is a Bernoulli random number with  $p=0.3$ 
```


# Inverse transform sampling

- Goal: Sample from a distribution with a known CDF function  $F$ .
- Theorem: Let  $U \sim \text{Uniform}(0, 1)$ , and  $X = F^{-1}(U)$ , then  $X \sim F$ .
- Example: Sample  $X \sim \text{Exp}(\lambda)$ .
  - Density:  $f(x) = \lambda e^{-\lambda x}$ .
  - CDF:  $F(x) = 1 - e^{-\lambda x}$ .
  - $\Rightarrow X = -\frac{1}{\lambda} \ln(1 - U)$ .
- Proof:

$$\begin{aligned} & P(X \leq x) \\ = & P(F^{-1}(U) \leq x) \\ = & P(U \leq F(x)) \\ = & F(x) \end{aligned}$$

([http://en.wikipedia.org/wiki/Inverse\\_transform\\_sampling](http://en.wikipedia.org/wiki/Inverse_transform_sampling))

# Inverse transform sampling



(<http://kennychowdhary.me/2012/10/>

francis-ford-copula-part-1-generating-samples-from-the-uniform-distribution/)

# Random number generation in C++

```
#include <iostream>
#include <ctime>
#include <boost/random/normal_distribution.hpp>
#include <boost/random/variante_generator.hpp>
#include <boost/random/mercenne_twister.hpp>
int main(int argc, char** argv) {
    typedef boost::mt19937 prgType;
    prgType rng;

    if ( argc > 1 )
        rng.seed(atoi(argv[1]));
    else
        rng.seed(std::time(0));

    boost::normal_distribution<> norm_dist(0,1); // standard normal distribution
    // PRG sampled from standard normal distribution
    boost::variante_generator<prgType&, boost::normal_distribution<> >
        norm(rng,norm_dist);

    double x = norm(); // Generate a random number from the PRG
    std::cout << "Sampled from standard normal distribution : " << x << std::endl;
    return 0;
}
```

# Sample from Gaussian distribution

- Inverse CDF  $\Rightarrow$  no closed form inverse CDF function
- Central Limit Theorem  $\Rightarrow$  needs multiple random samples
- The Box–Muller transformation

([http://en.wikipedia.org/wiki/Normal\\_distribution#Generating\\_values\\_from\\_normal\\_distribution](http://en.wikipedia.org/wiki/Normal_distribution#Generating_values_from_normal_distribution))

# Box-Muller Transformation (Box and Muller, 1958)

Let

$$\begin{aligned}U_1, U_2 &\sim \text{Uniform}(0, 1] \\ R &= \sqrt{-2 \ln U_1} \\ \Theta &= 2\pi U_2 \\ Z_0 &= R \cos(\Theta) \\ Z_1 &= R \sin(\Theta)\end{aligned}$$

Then

$$Z_0, Z_1 \sim N(0, 1), \text{ i.i.d.}$$

Where

$$R^2 \sim \chi_2^2 = \text{Exp}\left(\frac{1}{2}\right)$$

([http://en.wikipedia.org/wiki/Box%E2%80%93Muller\\_transform](http://en.wikipedia.org/wiki/Box%E2%80%93Muller_transform))



# Generating random numbers from complex distributions

## Problem

- When the distribution is complex, the inverse CDF may not be easily obtainable
- Need to implement your own function to generate the random numbers

## A simple example - mixture of two normal distributions

$$f(x; \mu_1, \sigma_1^2, \mu_2, \sigma_2^2, \alpha) = \alpha f_{\mathcal{N}}(x; \mu_1, \sigma_1^2) + (1 - \alpha) f_{\mathcal{N}}(x; \mu_2, \sigma_2^2)$$

How to generate random numbers from this distribution?

# Sample from Gaussian mixture

## Key idea

- Introduce a Bernoulli random variable  $w \sim \text{Bernoulli}(\alpha)$
- Sample  $y \sim \mathcal{N}(\mu_1, \sigma_1^2)$  and  $z \sim \mathcal{N}(\mu_2, \sigma_2^2)$
- Let  $x = wy + (1 - w)z$ .

# Sample from Gaussian mixture

## Key idea

- Introduce a Bernoulli random variable  $w \sim \text{Bernoulli}(\alpha)$
- Sample  $y \sim \mathcal{N}(\mu_1, \sigma_1^2)$  and  $z \sim \mathcal{N}(\mu_2, \sigma_2^2)$
- Let  $x = wy + (1 - w)z$ .

## An R implementation

```
w <- rbinom(1,1,alpha)
y <- rnorm(1,mu1,sigma1)
z <- rnorm(1,mu2,sigma2)
x <- w*y + (1-w)*z
```

# Sampling from bivariate normal distribution

Bivariate normal distribution

$$\begin{pmatrix} x \\ y \end{pmatrix} \sim \mathcal{N} \left( \begin{pmatrix} \mu_x \\ \mu_y \end{pmatrix}, \begin{bmatrix} \sigma_x^2 & \sigma_{xy} \\ \sigma_{xy} & \sigma_y^2 \end{bmatrix} \right)$$

# Sampling from bivariate normal distribution

## Bivariate normal distribution

$$\begin{pmatrix} x \\ y \end{pmatrix} \sim \mathcal{N} \left( \begin{pmatrix} \mu_x \\ \mu_y \end{pmatrix}, \begin{bmatrix} \sigma_x^2 & \sigma_{xy} \\ \sigma_{xy} & \sigma_y^2 \end{bmatrix} \right)$$

## Sampling from bivariate normal distribution

```
x <- rnorm(1,mu.x,sigma.x)
y <- rnorm(1,mu.y,sigma.y) # WRONG. Valid only when sigma.xy = 0
```

How can we sample from a joint distribution?

# Possible approaches

## Use known packages

- `mvtnorm` package provides `rmvnorm()` function for sampling from a multivariate-normal distribution
- Without using it, how to implement it?

# Possible approaches

## Use known packages

- `mvtnorm` package provides `rmvnorm()` function for sampling from a multivariate-normal distribution
- Without using it, how to implement it?

## Use conditional distribution

$$y|x \sim \mathcal{N}\left(\mu_y + \frac{\sigma_{xy}}{\sigma_x^2}(x - \mu_x), \sigma_y^2 \left(1 - \frac{\sigma_{xy}^2}{\sigma_x^2 \sigma_y^2}\right)\right)$$

```
x <- rnorm(1, mu.x, sigma.x)
y <- rnorm(1, mu.y + sigma.xy/sigma.x^2*(x-mu.x),
          sigma.y^2 - sigma.xy^2/sigma.x^2)
```

# Sampling from multivariate normal distribution

## Problem

- Randomly sample from  $\mathbf{x} \sim \mathcal{N}(\mathbf{m}, V)$
- The covariance matrix  $V$  is positive definite



# Sampling from multivariate normal distribution

## Problem

- Randomly sample from  $\mathbf{x} \sim \mathcal{N}(\mathbf{m}, V)$
- The covariance matrix  $V$  is positive definite

## Using conditional distribution

- Sample  $x_1 \sim \mathcal{N}(m_1, V_{11})$
- Sample  $x_2 \sim \mathcal{N}(m_2 + V_{12} V_{22}^{-1} (x_1 - m_1), V_{22} - V_{12}^T V_{11}^{-1} V_{12})$
- Repetitively sample  $x_i$  from subsequent conditional distributions.

This approach would require excessive amount of computational time

# Using Cholesky decomposition for sampling from MVN

## Key idea

- If  $\mathbf{x} \sim \mathcal{N}(\mathbf{m}, V)$ ,  $A\mathbf{x} \sim \mathcal{N}(A\mathbf{m}, A V A^T)$ .
- Sample  $\mathbf{z} \sim \mathcal{N}(0, I_n)$  from standard normal distribution
- Find  $A$  such that

$$\mathbf{x} = A\mathbf{z} + \mathbf{m} \sim \mathcal{N}(\mathbf{m}, A A^T) = \mathcal{N}(\mathbf{m}, V)$$

- Cholesky decomposition  $V = U^T U$  generates an example  $A = U^T$ .

## An example R code

```
z <- rnorm(length(m))
U <- chol(V)
x <- m + t(U) %*% z
```

# Summary - Random Number Generation

## Random Number Generator

- True Random Number Generator
- Pseudo-random Number Generator

## Generating Pseudo random Numbers in C++

- Use built-in `rand()` for toy examples
- Use boost library (e.g. Mersenne-twister) for more serious stuff
- Use inverse CDF for sampling from a known distribution
- For complex distributions, use generative procedure considering computational efficiency.

# Monte-Carlo Methods

## Informal definition

- Approximation by random sampling.
- Randomized algorithms to solve deterministic problems approximately.

## Goals

- Integration:  $E[f(x)]$
- Probability:  $P(X \in A) = E[1_{X \in A}]$
- Bayesian inference:  $P(\theta | \text{Data}) \propto P(\theta)P(\text{Data} | \theta)$
- Especially useful when analytic solution is not available or in high dimensional parameter space.

## An example problem

Calculating

$$\theta = \int_0^1 f(x) dx$$

where  $f(x)$  is a function with  $0 \leq f(x) \leq 1$

The problem is equivalent to computing  $E[f(u)]$  where  $u \sim U(0, 1)$ .

# The crude Monte-Carlo method

## Algorithm

- Generate  $u_1, u_2, \dots, u_B$  uniformly from  $U(0, 1)$ .
- Take their average to estimate  $\theta$

$$\hat{\theta} = \frac{1}{B} \sum_{i=1}^B f(u_i)$$

# The crude Monte-Carlo method

## Algorithm

- Generate  $u_1, u_2, \dots, u_B$  uniformly from  $U(0, 1)$ .
- Take their average to estimate  $\theta$

$$\hat{\theta} = \frac{1}{B} \sum_{i=1}^B f(u_i)$$

## Desirable properties of Monte-Carlo methods

- Consistency: estimates converges to true answer as  $B$  increases
- Unbiasedness:  $E[\hat{\theta}] = \theta$
- Minimal Variance

# Analysis of crude Monte-Carlo method

## Bias

$$E[\hat{\theta}] = \frac{1}{B} \sum_{i=1}^B E[f(u_i)] = \frac{1}{B} \sum_{i=1}^B \theta = \theta$$

# Analysis of crude Monte-Carlo method

## Bias

$$E[\hat{\theta}] = \frac{1}{B} \sum_{i=1}^B E[f(u_i)] = \frac{1}{B} \sum_{i=1}^B \theta = \theta$$

## Variance

$$\begin{aligned}\text{Var}[\hat{\theta}] &= \frac{1}{B} \int_0^1 (f(u) - \theta)^2 du \\ &= \frac{1}{B} E[f(u)^2] - \frac{\theta^2}{B}\end{aligned}$$



# Analysis of crude Monte-Carlo method

## Bias

$$E[\hat{\theta}] = \frac{1}{B} \sum_{i=1}^B E[f(u_i)] = \frac{1}{B} \sum_{i=1}^B \theta = \theta$$

## Variance

$$\begin{aligned}\text{Var}[\hat{\theta}] &= \frac{1}{B} \int_0^1 (f(u) - \theta)^2 du \\ &= \frac{1}{B} E[f(u)^2] - \frac{\theta^2}{B}\end{aligned}$$

## Consistency

$$\lim_{B \rightarrow \infty} \hat{\theta} = \theta$$

# Accept-reject (or hit-and-miss) Monte Carlo method

## Algorithm

- 1 Define a rectangle  $R$  between  $(0, 0)$  and  $(1, 1)$ 
  - Or more generally, between  $(x_m, x_M)$  and  $(y_m, y_M)$ .
- 2 Set  $h = 0$  (hit),  $m = 0$  (miss).
- 3 Sample a random point  $(x, y) \in R$ .
- 4 If  $y < f(x)$ , then increase  $h$ . Otherwise, increase  $m$
- 5 Repeat step 3 and 4 for  $B$  times
- 6  $\hat{\theta} = \frac{h}{h+m}$ .

# Analysis of accept-reject Monte Carlo method

## Bias

Let  $u_i, v_i$  follow  $U(0, 1)$ , then  $\Pr(v_i < f(u_i)) = \theta$

$$E[\hat{\theta}] = E\left[\frac{h}{h+m}\right] = \frac{\sum_{i=1}^B I(v_i < f(u_i))}{B} = \theta$$

# Analysis of accept-reject Monte Carlo method

## Bias

Let  $u_i, v_i$  follow  $U(0, 1)$ , then  $\Pr(v_i < f(u_i)) = \theta$

$$E[\hat{\theta}] = E\left[\frac{h}{h+m}\right] = \frac{\sum_{i=1}^B I(v_i < f(u_i))}{B} = \theta$$

## Variance

$h \sim \text{Binom}(B, \theta)$ .

$$\text{Var}[\hat{\theta}] = \frac{\theta(1-\theta)}{B}$$


# Which method is better?

$$\begin{aligned}\sigma_{AR}^2 - \sigma_{crude}^2 &= \frac{\theta(1-\theta)}{B} - \frac{1}{B}E[f(u)^2] + \frac{\theta^2}{B} \\ &= \frac{\theta - E[f(u)]^2}{B} \\ &= \frac{1}{B} \int_0^1 f(u)(1-f(u)) du \geq 0\end{aligned}$$

The crude Monte-Carlo method has less variance than accept-rejection method

# Example

- Let  $X, Y \sim \text{Uniform}(0, 1)$
- What is  $P(X^2 + Y^2 \geq 1)$ ?
- Accept-reject Monte Carlo in 1D is equivalent to crude Monte Carlo in 2D.



- Crude Monte Carlo method
  - Use uniform distribution (or other original generative model) to calculate the integration
  - Every random sample is equally weighted.
  - Straightforward to understand
- Rejection sampling
  - Estimation from discrete count of random variables
  - Larger variance than crude Monte-Carlo method
  - Typically easy to implement
  - Can be used to sample from any shape

# General rejection sampling (von Neumann, 1951)

- Goal: sample from a target distribution  $\pi(x)$  whose PDF function is known up to a constant  $f(x) = c\pi(x)$ .
- Rejection sampling:
  - ① Construct an envelope function  $g(x)$  with a constant  $M$  such that  $Mg(x) \geq f(x)$  for all  $x$ .
  - ② Sample  $x$  from  $g(\cdot)$  and  $u$  from  $Uniform(0, 1)$
  - ③ Compute the ratio  $r = \frac{f(x)}{Mg(x)}$ .
    - If  $u < r$ , accept  $x$ .
    - Otherwise, discard  $x$ .
  - ④ Go back to Step 2.
- Theorem: the accepted sample  $x$  follows the target distribution  $\pi$ .

([http://en.wikipedia.org/wiki/Rejection\\_sampling](http://en.wikipedia.org/wiki/Rejection_sampling))



# Proof of rejection sampling

$$\begin{aligned}P(x \text{ is accepted}) &= \int P(u < r | X = x) g(x) dx \\&= \int \frac{f(x)}{Mg(x)} g(x) dx \\&= \int \frac{c\pi(x)}{Mg(x)} g(x) dx \\&= \frac{c}{M} \int \pi(x) dx \\&= \frac{c}{M}\end{aligned}$$


Therefore

$$\begin{aligned}P(X = x | x \text{ is accepted}) &= \frac{P(X = x, x \text{ is accepted})}{P(x \text{ is accepted})} \\&= \frac{\frac{c\pi(x)}{Mg(x)} g(x)}{\frac{c}{M}} \\&= \pi(x)\end{aligned}$$







# Example

- Target: truncated Gaussian distribution  $\pi(x) \propto \phi(x)I_{x>c}$ , where  $\phi(x) = \frac{1}{\sqrt{2\pi}} e^{-\frac{x^2}{2}}$  is the standard Gaussian density function.
- Envelope 1:  $g(x) \sim N(0, 1)$ , i.e.,  $g(x) = \phi(x)$ .
  - $Mg(x) \geq \phi(x)I_{x>c} \Rightarrow M = 1$  is ok.
  - $r = \frac{\phi(x)I_{x>c}}{\phi(x)} = I_{x>c} \Rightarrow$  acceptance rate is  $1 - \Phi(c)$ .
- Envelope 2:  $g(z) = \lambda e^{-\lambda z}$  and  $x = z + c$ .
  - $Mg(z) \geq \phi(z+c)I_{z+c>c} \Rightarrow M\lambda e^{-\lambda z} \geq \frac{1}{\sqrt{2\pi}} e^{-\frac{(z+c)^2}{2}}$  for all  $z$ .
  - First let  $\lambda$  be fixed,
$$M \geq \max_z \frac{1}{\sqrt{2\pi\lambda}} e^{-\frac{(z+c)^2}{2} - \lambda z} = \frac{1}{\sqrt{2\pi\lambda}} e^{-\frac{\lambda^2}{2} - \lambda c}.$$
  - How to choose  $\lambda$  to maximize acceptance rate?

# Envelope 1: $N(0, 1)$



## Envelope 2: $Exp(\lambda)$



# Good envelope function

- Easy to construct.
- Easy to sample from.
- Close to the target function  $\Rightarrow$  low rejection rate.

