

# Little Book of Semaphores, Chapter 2

Geoffrey Matthews  
Western Washington University

January 12, 2015

# Semaphores

- A non-negative integer variable, initialized to any value.
- Only **increment** and **decrement** available.
- When a thread decrements, if the value is zero the thread blocks.
- When a thread increments, if there are threads waiting, one gets unblocked.

# Semaphores

- A non-negative integer variable, initialized to any value.
- Only **increment** and **decrement** available.
- When a thread decrements, if the value is zero the thread blocks.
- When a thread increments, if there are threads waiting, one gets unblocked.
- Increment and decrement are atomic.

# Semaphores

- A non-negative integer variable, initialized to any value.
- Only **increment** and **decrement** available.
- When a thread decrements, if the value is zero the thread blocks.
- When a thread increments, if there are threads waiting, one gets unblocked.
- Increment and decrement are atomic.
- No getter. Why?

# Notation for Semaphors

Decrement	Increment
P	V
Wait	Signal
Wait	Post
Acquire	Release
Get	Release

## Semaphore notation in cleaned up Python and Racket

```
fred = Semaphore(1)
fred.signal()
fred.wait()
```

```
(define fred (make-semaphore 1))
(semaphore-post fred)
(semaphore-wait fred)
```

# Why semaphores?

- Semaphores impose constraints that help programmers avoid errors.
- Solutions using semaphores are often clean and organized.
- Semaphores can be implemented easily in hardware, so solutions are portable.

# Why semaphores?

- Semaphores impose constraints that help programmers avoid errors.
- Solutions using semaphores are often clean and organized.
- Semaphores can be implemented easily in hardware, so solutions are portable.
- However, they can get complex quickly.