

# Mean-field Theory: Drift and the Mean Drift

Binan Gu

Department of Mathematical Sciences, New Jersey Institute of Technology

New Jersey Institute of Technology  
Optimization & Machine Learning Seminar Spring 2022



# Overview

Background

Mean-Field Approximation

Mathematical Procedures

## Wireless Sensor Networks

- ▶ Each sensor is a (random) vertex/node/agent.

## Wireless Sensor Networks

- ▶ Each sensor is a (random) vertex/node/agent.
- ▶ It collects and transmits data to the next node.

## Wireless Sensor Networks

- ▶ Each sensor is a (random) vertex/node/agent.
- ▶ It collects and transmits data to the next node.
- ▶ Large amount of nodes, so effective planning of transmission paths is important.

## Wireless Sensor Networks

- ▶ Each sensor is a (random) vertex/node/agent.
- ▶ It collects and transmits data to the next node.
- ▶ Large amount of nodes, so effective planning of transmission paths is important.

## Example (Routing Algorithm)

## Wireless Sensor Networks

- ▶ Each sensor is a (random) vertex/node/agent.
- ▶ It collects and transmits data to the next node.
- ▶ Large amount of nodes, so effective planning of transmission paths is important.

## Example (Routing Algorithm)

- ▶ Each node is associated with battery energy (and other constraints, e.g. storage, capacity, bandwidth, etc.).

## Wireless Sensor Networks

- ▶ Each sensor is a (random) vertex/node/agent.
- ▶ It collects and transmits data to the next node.
- ▶ Large amount of nodes, so effective planning of transmission paths is important.

## Example (Routing Algorithm)

- ▶ Each node is associated with battery energy (and other constraints, e.g. storage, capacity, bandwidth, etc.).
- ▶ The goal is to maximize the lifetime of the network, i.e. preserving connectivity and preventing energy burnouts.



## Wireless Sensor Networks

- ▶ Each sensor is a (random) vertex/node/agent.
- ▶ It collects and transmits data to the next node.
- ▶ Large amount of nodes, so effective planning of transmission paths is important.

## Example (Routing Algorithm)

- ▶ Each node is associated with battery energy (and other constraints, e.g. storage, capacity, bandwidth, etc.).
- ▶ The goal is to maximize the lifetime of the network, i.e. preserving connectivity and preventing energy burnouts.
- ▶ Data transmission between the nodes is like a queue, with random arrival and processing times.

# Mean-field Theory

## Mean-field Interaction Models

- ▶ Population processes in which individuals behave similarly.

# Mean-field Theory

## Mean-field Interaction Models

- ▶ Population processes in which individuals behave similarly.
- ▶ Care about “proportions of agents in a certain state” rather than the individual status of each agent.

# Mean-field Theory

## Mean-field Interaction Models

- ▶ Population processes in which individuals behave similarly.
- ▶ Care about “proportions of agents in a certain state” rather than the individual status of each agent.
- ▶ Symmetric reduction on the state space to gain efficiency in analysis.

## Mean-field Interaction Models

- ▶ Population processes in which individuals behave similarly.
- ▶ Care about “proportions of agents in a certain state” rather than the individual status of each agent.
- ▶ Symmetric reduction on the state space to gain efficiency in analysis.
- ▶ Continuous and deterministic approximation of population processes in their **first moment**.

## Mean-field Interaction Models

- ▶ Population processes in which individuals behave similarly.
- ▶ Care about “proportions of agents in a certain state” rather than the individual status of each agent.
- ▶ Symmetric reduction on the state space to gain efficiency in analysis.
- ▶ Continuous and deterministic approximation of population processes in their **first moment**.

Thomas G. Kurtz

## Mean-field Interaction Models

- ▶ Population processes in which individuals behave similarly.
- ▶ Care about “proportions of agents in a certain state” rather than the individual status of each agent.
- ▶ Symmetric reduction on the state space to gain efficiency in analysis.
- ▶ Continuous and deterministic approximation of population processes in their **first moment**.

Thomas G. Kurtz

- ▶ University of Wisconsin-Madison.

## Mean-field Interaction Models

- ▶ Population processes in which individuals behave similarly.
- ▶ Care about “proportions of agents in a certain state” rather than the individual status of each agent.
- ▶ Symmetric reduction on the state space to gain efficiency in analysis.
- ▶ Continuous and deterministic approximation of population processes in their **first moment**.

## Thomas G. Kurtz

- ▶ University of Wisconsin-Madison.
- ▶ Convergence, approximation and representation of several important classes of Markov processes.



# Mean-field Theory

## Mean-field Interaction Models

- ▶ Population processes in which individuals behave similarly.
- ▶ Care about “proportions of agents in a certain state” rather than the individual status of each agent.
- ▶ Symmetric reduction on the state space to gain efficiency in analysis.
- ▶ Continuous and deterministic approximation of population processes in their **first moment**.

## Thomas G. Kurtz

- ▶ University of Wisconsin-Madison.
- ▶ Convergence, approximation and representation of several important classes of Markov processes.
- ▶ Systems biology, population genetics, telecommunications networks and mathematical finance.

## Example: Radio transmission in a single channel

Saturated nodes: every node always has a message to send. Each transmission has success probability depending on the number of nodes using the channel,

$$p_s(n) = 2^{-n}.$$

Two states:

1. Waiting to send, with  $p_1$  to initiate.
2. Initiated but failed, and try to retransmit with  $p_2$ .

If transmission is successful in state 1, then the node stays in state 1 or otherwise goes to 2. Once retransmission is successful in state 2, it goes back to 1.




Fig. 1. The behaviour of a node in Example 1. The number of transmitting nodes is  $n$ .

# Mean-Field Approximation

## Agent Processes

Consider  $N$  agents with

- ▶ discrete time horizon  $T = \mathbb{N}$ .

# Mean-Field Approximation

## Agent Processes

Consider  $N$  agents with

- ▶ discrete time horizon  $T = \mathbb{N}$ .
- ▶ discrete state space  $\mathcal{S}$ .

## Agent Processes

Consider  $N$  agents with

- ▶ discrete time horizon  $T = \mathbb{N}$ .
- ▶ discrete state space  $\mathcal{S}$ .
- ▶  $\{X_i^{(N)}(t) : t \in T\}$ ,  $\mathcal{S}$ -valued discrete time Markov chains.

# Mean-Field Approximation

## Agent Processes

Consider  $N$  agents with

- ▶ discrete time horizon  $T = \mathbb{N}$ .
- ▶ discrete state space  $\mathcal{S}$ .
- ▶  $\{X_i^{(N)}(t) : t \in T\}$ ,  $\mathcal{S}$ -valued discrete time Markov chains.
- ▶ Each  $X_i^{(N)}(t)$  follows a transition map  $K_i : \mathcal{S}^N \times \mathcal{S} \rightarrow [0, 1]$ , namely, the probability  $K_i(\mathbf{v}, s)$  that agent  $i$  transitions from
  - ▶  $\mathbf{v} \in \mathcal{S}^N$ , state of the entire system (including agent  $i$ 's current state) to
  - ▶  $s \in \mathcal{S}$ , the next state.

# Paradigms about Time Slots

Transition Types

# Paradigms about Time Slots

## Transition Types

1. Fully synchronized (i.e. synchronous DTMCs).



# Paradigms about Time Slots

## Transition Types

1. Fully synchronized (i.e. synchronous DTMCs).
2. Independent time slots (occurring at the same rate over sufficiently long intervals of time).

# Paradigms about Time Slots

## Transition Types

1. Fully synchronized (i.e. synchronous DTMCs).
2. Independent time slots (occurring at the same rate over sufficiently long intervals of time).

We discuss type 2, known as the *clock independence assumption*. This implies no simultaneous transitions (think of a property of the Poisson process). This assumption is not free.

# Paradigms about Time Slots

## Transition Types

1. Fully synchronized (i.e. synchronous DTMCs).
2. Independent time slots (occurring at the same rate over sufficiently long intervals of time).

We discuss type 2, known as the *clock independence assumption*. This implies no simultaneous transitions (think of a property of the Poisson process). This assumption is not free.

Let  $D$  be the time resolution (number of subintervals for one unit of time), and define  $\epsilon = 1/D$  to form *global time*

$$T_G = \{0, \epsilon, 2\epsilon, \dots\}.$$

# Paradigms about Time Slots

## Transition Types

1. Fully synchronized (i.e. synchronous DTMCs).
2. Independent time slots (occurring at the same rate over sufficiently long intervals of time).

We discuss type 2, known as the *clock independence assumption*. This implies no simultaneous transitions (think of a property of the Poisson process). This assumption is not free.

Let  $D$  be the time resolution (number of subintervals for one unit of time), and define  $\epsilon = 1/D$  to form *global time*

$$T_G = \{0, \epsilon, 2\epsilon, \dots\}.$$

The transition  $K_i(\mathbf{v}, s)$  is then modified into:

$$\hat{K}_i(\mathbf{v}, s) = \begin{cases} \epsilon K_i(\mathbf{v}, s), & \text{if } s \neq \mathbf{v}_i \\ 1 - \epsilon (1 - K_i(\mathbf{v}, s)), & \text{if } s = \mathbf{v}_i \end{cases}$$

With the time-rescaled transition maps, we associate the collection of them with a new DTMC

$$Y^{(N)}(t) = \left( \hat{X}_1^{(N)}(t), \dots, \hat{X}_N^{(N)}(t) \right)$$

with transition map (via independence of transitions)

$$\mathcal{K}^{(N)}(\mathbf{v}, \mathbf{v}') = \prod_{i=1}^N \hat{K}_i(\mathbf{v}, \mathbf{v}_i')$$

# Mean Field Interaction Models and Population Processes

## Definition (Mean Field Interaction Models (MFIM))

$Y^{(N)}(t)$  is an MFIM if

$$\mathcal{K}^{(N)}(\mathbf{v}, \mathbf{v}') = \mathcal{K}^{(N)}(\pi(\mathbf{v}), \pi(\mathbf{v}'))$$

for any permutation  $\pi$  on the agents.

# Mean Field Interaction Models and Population Processes

## Definition (Mean Field Interaction Models (MFIM))

$Y^{(N)}(t)$  is an MFIM if

$$\mathcal{K}^{(N)}(\mathbf{v}, \mathbf{v}') = \mathcal{K}^{(N)}(\pi(\mathbf{v}), \pi(\mathbf{v}'))$$

for any permutation  $\pi$  on the agents.

Note: this transition map may depend on the number agents in each state, but not on the state of a certain agent.

# The Mean-Field Procedure

## Occupation Measures

Proportion of Agents in State  $s$

$$M_s^{(N)}(t) = \frac{1}{N} \sum_{1 \leq n \leq N} \mathbf{1} \left( \hat{X}_n^{(N)}(t) = s \right)$$

whose values form an alternative representation  $\Delta$  of the state space. The *agent model*  $\left( \hat{X}_1^{(N)}(t), M^{(N)}(t) \right) : t \in T_G$  is also Markov with (double) transition  $P_1^{(N)}$ .

## Infinitesimal Generator for Arbitrary Agent

$$Q_{s,s'}^{(N)}(\mathbf{m}) = \lim_{D \rightarrow \infty} DP_{s,s'}^{(N)}(\mathbf{m})$$

where  $P_{s,s'}^{(N)}(\mathbf{m})$  is the marginal transition probability of an arbitrary agent.



Right-continuation with left limit (càdlàg) of the process  $M^{(N)}(t)$  via

$$\overline{M}^{(N)}(t) = M^{(N)}(\epsilon \lfloor Dt \rfloor).$$

# Drift and ODEs

Right-continuation with left limit (càdlàg) of the process  $M^{(N)}(t)$  via

$$\overline{M}^{(N)}(t) = M^{(N)}(\epsilon \lfloor Dt \rfloor).$$

Know:  $Q_{s,s'}^{(N)}(\mathbf{m})$ , rate of any agent given current proportion  $\mathbf{m}$ .

# Drift and ODEs

Right-continuation with left limit (càdlàg) of the process  $M^{(N)}(t)$  via

$$\overline{M}^{(N)}(t) = M^{(N)}(\epsilon \lfloor Dt \rfloor).$$

Know:  $Q_{s,s'}^{(N)}(\mathbf{m})$ , rate of any agent given current proportion  $\mathbf{m}$ .

Want:  $\mathbb{E} \left[ \overline{M}^{(N)}(t) \right]$ , expected proportion of each state in time.

# Drift and ODEs

Right-continuation with left limit (càdlàg) of the process  $M^{(N)}(t)$  via

$$\overline{M}^{(N)}(t) = M^{(N)}(\epsilon \lfloor Dt \rfloor).$$

Know:  $Q_{s,s'}^{(N)}(\mathbf{m})$ , rate of any agent given current proportion  $\mathbf{m}$ .

Want:  $\mathbb{E} \left[ \overline{M}^{(N)}(t) \right]$ , expected proportion of each state in time.

Thus want: generator  $F^{(N)}$  of  $\overline{M}^{(N)}(t)$ .

# Drift and ODEs

Right-continuation with left limit (càdlàg) of the process  $M^{(N)}(t)$  via

$$\overline{M}^{(N)}(t) = M^{(N)}(\epsilon \lfloor Dt \rfloor).$$

Know:  $Q_{s,s'}^{(N)}(\mathbf{m})$ , rate of any agent given current proportion  $\mathbf{m}$ .

Want:  $\mathbb{E} \left[ \overline{M}^{(N)}(t) \right]$ , expected proportion of each state in time.

Thus want: generator  $F^{(N)}$  of  $\overline{M}^{(N)}(t)$ .

Procedure: prove a Dynkin-type formula

$$\begin{aligned} & \mathbb{E} \left[ \overline{M}^{(N)}(t) \mid \overline{M}^{(N)}(0) \right] \\ &= \overline{M}^{(N)}(0) + \int_0^t \mathbb{E} \left[ F^{(N)} \left( \overline{M}^{(N)}(s) \right) \mid \overline{M}^{(N)}(0) \right] ds \end{aligned}$$

where a lot of ODE theory will apply (Picard, Gronwall, etc.)

- ▶ Count number of transitions in  $[t, t + \epsilon)$ ,

$$W_{s,s'}^{(N)}(t) = \sum_{k=1}^N \mathbf{1} \left\{ \hat{X}_k^{(N)}(t) = s, \hat{X}_k^{(N)}(t + \epsilon) = s' \right\}$$

- ▶ Count number of transitions in  $[t, t + \epsilon)$ ,

$$W_{s,s'}^{(N)}(t) = \sum_{k=1}^N \mathbf{1} \left\{ \hat{X}_k^{(N)}(t) = s, \hat{X}_k^{(N)}(t + \epsilon) = s' \right\}$$

- ▶ Express instantaneous change of the proportions,

$$\Delta \bar{M} = \bar{M}^{(N)}(t + \epsilon) - \bar{M}^{(N)}(t) = \sum_{s \neq s'} \frac{W_{s,s'}^{(N)}(t)}{N} (e_{s'} - e_s)$$

- ▶ Count number of transitions in  $[t, t + \epsilon)$ ,

$$W_{s,s'}^{(N)}(t) = \sum_{k=1}^N \mathbf{1} \left\{ \hat{X}_k^{(N)}(t) = s, \hat{X}_k^{(N)}(t + \epsilon) = s' \right\}$$

- ▶ Express instantaneous change of the proportions,

$$\Delta \bar{M} = \bar{M}^{(N)}(t + \epsilon) - \bar{M}^{(N)}(t) = \sum_{s \neq s'} \frac{W_{s,s'}^{(N)}(t)}{N} (e_{s'} - e_s)$$

- ▶ Take an expectation, and then limit of rescale,

$$\hat{F}^{(N)}(\mathbf{m}) = \mathbb{E} \left[ \Delta \bar{M} \mid \bar{M}^{(N)}(t) = \mathbf{m} \right] = \sum_{s,s'} \mathbf{m}_s P_{s,s'}^{(N)}(\mathbf{m}) (e_{s'} - e_s)$$

$$F^{(N)}(\mathbf{m}) = \lim_{D \rightarrow \infty} D \hat{F}^{(N)}(\mathbf{m}) = \sum_{s,s'} \mathbf{m}_s Q_{s,s'}^{(N)}(\mathbf{m}) (e_{s'} - e_s)$$



# The Propagation of Chaos

## Definition ( $\rho$ -chaotic Sequence)

Let  $\rho \in \mathcal{M}(\mathcal{S})$  be a probability measure. For  $N \geq 1$ , the sequence  $\{\rho_N\}$  of measures, each in  $\mathcal{M}(\mathcal{S}^N)$ , is  $\rho$ -chaotic iff for any fixed natural number  $k$  and bounded functions  $\{f_i\}_{i=1}^k$ :

$$\lim_{N \rightarrow \infty} \int_{\mathcal{S}^N} f_1(\mathbf{v}_1) f_2(\mathbf{v}_2) \dots f_k(\mathbf{v}_k) \rho_N(d\mathbf{v}) = \prod_{i=1}^k \int_{\mathcal{S}} f_i(\mathbf{s}) \rho(d\mathbf{s})$$

i.e. a chaotic sequence mains a form of independence in the observations of separate agents in the limit. This is not utilized in the drift computation.

## Mean Drift ODEs

One can show that  $\bar{Y}^{(N)}(t)$ , the joint agent process in continuous time, is  $\mu$ -chaotic, where  $\mu(i) = \mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right]$  for  $i \in \mathcal{S}$ .

# Mean Drift ODEs

One can show that  $\bar{Y}^{(N)}(t)$ , the joint agent process in continuous time, is  $\mu$ -chaotic, where  $\mu(i) = \mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right]$  for  $i \in \mathcal{S}$ .

Asymptotic independence implies,

$$\begin{aligned} \mathbb{P} \left\{ \bar{M}_i^{(N)}(t) = \frac{k}{N} \right\} &= \binom{N}{k} \text{Binomial stuff} \\ &\approx \binom{N}{k} \left( \mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right] \right)^k \left( 1 - \mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right] \right)^{N-k} \\ &\approx e^{-N\mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right]} \frac{\left( \mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right] \right)^k}{k!} \end{aligned}$$

# Mean Drift ODEs

One can show that  $\bar{Y}^{(N)}(t)$ , the joint agent process in continuous time, is  $\mu$ -chaotic, where  $\mu(i) = \mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right]$  for  $i \in \mathcal{S}$ .

Asymptotic independence implies,

$$\begin{aligned} \mathbb{P} \left\{ \bar{M}_i^{(N)}(t) = \frac{k}{N} \right\} &= \binom{N}{k} \text{Binomial stuff} \\ &\approx \binom{N}{k} \left( \mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right] \right)^k \left( 1 - \mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right] \right)^{N-k} \\ &\approx e^{-N\mathbb{E}[\bar{M}_i^{(N)}(t)]} \frac{\left( \mathbb{E} \left[ \bar{M}_i^{(N)}(t) \right] \right)^k}{k!} \end{aligned}$$

Thus the generator can be computed using the asymptotically independent Poisson densities, extracting more information from the mere  $Q_{s,s'}^{(N)}(\mathbf{m})$ 's.

## Example: Radio transmission in a single channel

Saturated nodes: every node always has a message to send. Each transmission has success probability depending on the number of nodes using the channel,

$$p_s(n) = 2^{-n}.$$

Two states:

1. Waiting to send, with  $p_1$  to initiate.
2. Initiated but failed, and try to retransmit with  $p_2$ .

If transmission is successful in state 1, then the node stays in state 1 or otherwise goes to 2. Once retransmission is successful in state 2, it goes back to 1.





Fig. 1. The behaviour of a node in Example 1. The number of transmitting nodes is  $n$ .

# Approximation comparisons



**Fig. 2.** Comparison between the proportion of nodes in the back-off state at time  $t = 1000$  ( $\phi_2^{(N)}(1000)$ ) for different network sizes  $N$ , based on a transient analysis of the Markov models (the solutions of the Chapman-Kolmogorov equations) and a mean field analysis by the ODEs incorporating the mean-drift.

This shows that the mean drift approximation is good even when  $N$  is not that large.



Mahmoud Talebi and Jan Friso Groote and Jean-Paul M.G. Linnartz “The Mean Drift: Tailoring the Mean Field Theory of Markov Processes for Real-World Applications ”.  
*Analytical and Stochastic Modelling Techniques and Applications*. 2017.