Using beacr

```
starting_seed = beacr::get_seed()
```

```
## Welcome to ‘beacr‘! This message appears only once.
## Visit https://cnsodano.github.io/beacr-pre-alpha/ to learn more about how to use ‘beacr‘ and access
## A good place to get started is by executing ‘vignette('beacr')‘ in your R console.
## If you want to learn more, check out other vignettes with ‘browseVignettes(package='beacr')‘

## beacr: Debug logs are being written to: /workspaces/codespace_env/04_with_beacr/beacr

## beacr: Seed log default location is: /workspaces/codespace_env/04_with_beacr/beacr

## beacr fully loaded!

## i Did not detect a seed log file. Writing one to ‘/workspaces/codespace_env/04_with_beacr/beacr/seed

## x No preregistration identifier passed, using pulse without preregistration. See the 'Preregistratio
##   the Getting Started vignette for more details: ‘vignette('beacr')‘

## v Pulse successfully acquired. Details written to log at /workspaces/codespace_env/04_with_beacr/bea
```

```
set.seed(starting_seed)
data = read_data_transparently_published_on_osf("dw2rz")

predictions = coin_flip(nrow(data))
cat("Accuracy: ", mean(predictions == data$label), "\n")
```

```
## Accuracy:  0.4804805
```

```
for (i in 1:5){
    set.seed(as.integer(starting_seed)+i)
    predictions = coin_flip(nrow(data))
    cat("Accuracy: ", mean(predictions == data$label), "\n")
}
```

```
## Accuracy:  0.4654655
## Accuracy:  0.4804805
## Accuracy:  0.5165165
## Accuracy:  0.4564565
## Accuracy:  0.4954955
```