

Companion to Bird & de Moor, Algebra of Programming

§9. Dynamic Programming

§9.1. Theory

§9.1.1. Example: segmenting a list

- (9.1.1a)
- $\langle T \rangle = \text{concat}$
 $T=[\text{nil}, \text{cat}]$ takes a non-empty first list, so T° cuts a non-empty prefix off a list every way, and folding with T flattens a list of segments
 - $\langle h \rangle = \text{list}(\text{sum})$
 $h=[\text{nil}, \text{cons}(\text{sum}\times 1)]$ puts a segment's sum in front, so folding with h sums every segment
 - $H = \text{partition list}(\text{sum})$
 H segments a list every way, then sums each segment; with R comparing the largest entry, M cuts the list so that the largest segment sum is as small as possible

(9.1.1b)

	x	h(x)
1	$l(())$	$[\]$
2	$r([c], [])$	$[c]$
3	$r([a, b], [c])$	$[a + b, c]$
4	$r([a], [b + c])$	$[a, b + c]$

- (9.1.1c)
- $H([a, b, c], ys) \iff ys = [a + b + c] \vee ys = [a, b + c] \vee ys = [a + b, c] \vee ys = [a, b, c]$
 H sends $[a, b, c]$ to the sums of its four segmentations and nothing else
 - $T^\circ F(H) h = H$
cut once, solve the rest, put the pieces back together

(9.1.1d)

	name	type	definition	meaning
1	H	A→B	$H \triangleq \langle T \rangle^\circ \langle h \rangle$	take the input apart by the T -decompositions, and put it together by h
2	M	A→B	$M \triangleq \frac{H}{\exists} \text{ est}(R)$	the problem to be solved: an answer of H that is best under R

$\text{Map}(h) \wedge h \text{ Pres } R^\circ \wedge R^\circ R^\circ \sqsubseteq R^\circ \implies (\mu X : \frac{T^\circ}{\exists} P(F(X) h) \text{ est}(R)) \sqsubseteq \frac{H}{\exists} \text{ est}(R)$

Theorem 9.1

every answer the recursion returns is an optimal one

- $\frac{T^\circ}{\exists}$ takes the input apart one step every way; $F(X)$ solves each part by the recursion X ; h assembles each candidate; $\text{est}(R)$ keeps a best one
- $\sqsubseteq M$: that never misses the optimum, though all candidates are never listed as H would
- h monotonic on R : a better part never makes the whole worse
- $\sqsubseteq$, not $=$: some optima may not be returned; that the recursion returns anything at all needs T° to stop taking apart — dynamic programming theorem

$$\frac{T^\circ}{\exists} P(F(\frac{H}{\exists} \text{est}(R)) h) \text{est}(R) \sqsubseteq H \quad (9.2)$$

taking the input apart every way T allows ($\frac{T^\circ}{\exists}$), solving each part by M and keeping an optimum ($P(F(M)h) \text{est}(R)$)
returns only what H returns



1	$\frac{T^\circ}{\exists} P(F(\frac{H}{\exists} \text{est}(R)) h) \text{est}(R)$	$P(S) \text{est}(R) \sqsubseteq \exists S$
2	$\sqsubseteq \frac{T^\circ}{\exists} \exists F(\frac{H}{\exists} \text{est}(R)) h$	$\frac{R}{\exists} \exists = R$
3	$= T^\circ F(\frac{H}{\exists} \text{est}(R)) h$	$\frac{S}{\exists} \text{est}(R) \sqsubseteq S$
4	$\sqsubseteq T^\circ F(H) h$	$T^\circ F(H) h = H$
5	$= H$	

$$\text{Map}(h) \wedge h \text{ Pres } R^\circ \wedge R^\circ R^\circ \sqsubseteq R^\circ \implies H^\circ \frac{T^\circ}{\exists} P(F(\frac{H}{\exists} \text{est}(R)) h) \text{est}(R) \sqsubseteq R^\circ \quad (9.3)$$

for every b that H returns from an input, the step $\frac{T^\circ}{\exists} P(F(M)h) \text{est}(R)$ returns from that input only b' with R relating b' to b



1	$H^\circ \frac{T^\circ}{\exists} P(F(\frac{H}{\exists} \text{est}(R)) h) \text{est}(R)$	$P(S) \text{est}(R) \sqsubseteq \epsilon \setminus (S R^\circ)$
2	$\sqsubseteq H^\circ \frac{T^\circ}{\exists} (\epsilon \setminus (F(\frac{H}{\exists} \text{est}(R)) h R^\circ))$	$H^\circ = h^\circ F(H^\circ) T$
3	$= h^\circ F(H^\circ) T \frac{T^\circ}{\exists} (\epsilon \setminus (F(\frac{H}{\exists} \text{est}(R)) h R^\circ))$	$T \frac{T^\circ}{\exists} \sqsubseteq \epsilon$
4	$\sqsubseteq h^\circ F(H^\circ) \epsilon (\epsilon \setminus (F(\frac{H}{\exists} \text{est}(R)) h R^\circ))$	$S (S \setminus R) \sqsubseteq R$
5	$\sqsubseteq h^\circ F(H^\circ) F(\frac{H}{\exists} \text{est}(R)) h R^\circ$	




6	$= h^\circ F(H^\circ \frac{H}{\exists} \text{est}(R)) h R^\circ$	$S^\circ \frac{S}{\exists} \text{est}(R) \sqsubseteq R^\circ$
7	$\sqsubseteq h^\circ F(R^\circ) h R^\circ$	$\text{Map}(f)$
8	$\sqsubseteq R^\circ R^\circ$	$\implies f \text{ Pres } R \iff f^\circ F(R) f \sqsubseteq R$
9	$\sqsubseteq R^\circ$	$R^\circ R^\circ \sqsubseteq R^\circ$

Map(h) $\wedge$ h Pres $R^\circ \wedge R^\circ R^\circ \sqsubseteq R^\circ \wedge \text{ThinCondition}(T, h, R, Q) \Rightarrow (\mu X : \frac{T^\circ}{S} \text{thin}(Q) P(F(X) h) \text{est}(R)) \sqsubseteq \frac{H}{S} \text{est}(R)$ Theorem 9.2

an optimum over everything **H** returns is reached by taking the input apart every way **T** allows, dropping the parts that can never win, solving each of the rest and keeping one optimum


$$H \triangleq (T)^\circ (h) \text{ — } H \triangleq (T)^\circ (h)$$



$$1 \quad \frac{H}{S} \text{est}(R)$$

$$2 \quad \sqsubseteq \frac{T^\circ}{S} \text{thin}(Q) P(F(X) h) \text{est}(R)$$

$QF(H)h \sqsubseteq F(H)hR$, h monotonic on $R \text{ — } Q \sqsubseteq R \wedge 1 \sqsubseteq Q \wedge R$
 $R \sqsubseteq R$
 $\Rightarrow \text{est}(R) = \text{thin}(Q) \text{est}(R), X \sqsubseteq \text{est}(R) \Leftrightarrow X \sqsubseteq \exists$
 $\wedge \in X \sqsubseteq R^\circ$




$T^\circ F(H)h = H$: taking the input apart once by T° , solving the parts by $F(H)$ and assembling by h returns exactly what H returns

$QF(H)h \sqsubseteq F(H)hR$: every result of thinning by Q , solving the parts by $F(H)$ and assembling by h is reached by R from a result of solving by $F(H)$ and assembling by h without Q

$$\frac{T^\circ}{S} \text{thin}(Q) P(F(\frac{H}{S} \text{est}(R)) h) \text{est}(R) \sqsubseteq H$$

(9.1.1e)

taking the input apart every way **T** allows ($\frac{T^\circ}{S}$), dropping the parts **thin(Q)** rejects, solving each rest by **M** and keeping an optimum returns only what **H** returns



$$1 \quad \frac{T^\circ}{S} \text{thin}(Q) P(F(\frac{H}{S} \text{est}(R)) h) \text{est}(R)$$

$$2 \quad \sqsubseteq \frac{T^\circ}{S} \text{thin}(Q) \exists F(\frac{H}{S} \text{est}(R)) h$$

$$3 \quad \sqsubseteq \frac{T^\circ}{S} \exists F(\frac{H}{S} \text{est}(R)) h$$

$$4 \quad = T^\circ F(\frac{H}{S} \text{est}(R)) h$$

$$5 \quad \sqsubseteq T^\circ F(H) h$$

$$6 \quad = H$$

$$P(S) \text{est}(R) \sqsubseteq \exists S$$

$$\text{thin}(Q) \exists \sqsubseteq \exists$$

$$\frac{R}{S} \exists = R$$

$$\frac{S}{S} \text{est}(R) \sqsubseteq S$$


$$T^\circ F(H) h = H$$

$$\text{Map}(h) \wedge h \text{ Pres } R^\circ \wedge R^\circ R^\circ \sqsubseteq R^\circ \wedge \text{ThinCondition}(T, h, R, Q) \Rightarrow H^\circ \frac{T^\circ}{3} \text{thin}(Q) P(F(\frac{H}{3} \text{est}(R)) h) \text{est}(R) \sqsubseteq R^\circ \quad (9.1.1f)$$

H° followed by the body at M is $\mathbb{E}R^\circ$: an answer of the body is never worse than an answer of H to the same input



1	$H^\circ \frac{T^\circ}{3} \text{thin}(Q) P(F(\frac{H}{3} \text{est}(R)) h) \text{est}(R)$	$P(S) \text{est}(R) \sqsubseteq \mathbb{E} \setminus (S R^\circ)$
2	$\sqsubseteq H^\circ \frac{T^\circ}{3} \text{thin}(Q) (\mathbb{E} \setminus (F(\frac{H}{3} \text{est}(R)) h R^\circ))$	$H^\circ = h^\circ F(H^\circ) T$
3	$= h^\circ F(H^\circ) T \frac{T^\circ}{3} \text{thin}(Q) (\mathbb{E} \setminus (F(\frac{H}{3} \text{est}(R)) h R^\circ))$	$T \frac{T^\circ}{3} \sqsubseteq \mathbb{E}$
4	$\sqsubseteq h^\circ F(H^\circ) \mathbb{E} \text{thin}(Q) (\mathbb{E} \setminus (F(\frac{H}{3} \text{est}(R)) h R^\circ))$	$\mathbb{E} \text{thin}(Q) \sqsubseteq Q^\circ \mathbb{E}$



5	$\sqsubseteq h^\circ F(H^\circ) Q^\circ \mathbb{E} (\mathbb{E} \setminus (F(\frac{H}{3} \text{est}(R)) h R^\circ))$	$S (S \setminus R) \sqsubseteq R$
6	$\sqsubseteq h^\circ F(H^\circ) Q^\circ F(\frac{H}{3} \text{est}(R)) h R^\circ$	$\text{ThinCondition}(T, h, R, Q)$
7	$\sqsubseteq R^\circ h^\circ F(H^\circ) F(\frac{H}{3} \text{est}(R)) h R^\circ$	$\Rightarrow h^\circ F(H^\circ) Q^\circ \sqsubseteq R^\circ h^\circ F(H^\circ)$


8	$= R^\circ \quad h^\circ \quad F(H^\circ \quad \frac{H}{\exists} \quad \text{est}(R)) \quad h \quad R^\circ$	$S^\circ \quad \frac{S}{\exists} \quad \text{est}(R) \quad \subseteq R^\circ$
9	$\sqsubseteq R^\circ \quad h^\circ \quad F(R^\circ) \quad h \quad R^\circ$	$\text{Map}(f)$ $\implies f \text{ Pres } R \iff f^\circ F(R) \quad f \subseteq R$
10	$\sqsubseteq R^\circ \quad R^\circ \quad R^\circ$	$R^\circ \quad R^\circ \subseteq R^\circ$
11	$\sqsubseteq R^\circ \quad R^\circ$	$R^\circ \quad R^\circ \subseteq R^\circ$
12	$\sqsubseteq R^\circ$	

§9.1.2. Checking the conditions

Proposition 9.1

$$V_2 \ V_1^\circ = \emptyset \implies \frac{[V_1, V_2]^\circ}{3} \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R) = (\text{ran}(V_1) \ \frac{V_1^\circ}{3} \text{thin}(Q_1) \ P(U_1) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{V_2^\circ}{3} \text{thin}(Q_2) \ P(U_2) \ \text{est}(R))$$


when V_1 and V_2 have disjoint ranges, the body over $[V_1, V_2]$ runs the V_1 problem on inputs V_1 reaches and the V_2 problem on inputs V_2 reaches



1	$\frac{[V_1, V_2]^\circ}{3} \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R)$	$\frac{[V_1, V_2]^\circ}{3} \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R) = (\text{ran}(V_1) \ \frac{[V_1, V_2]^\circ}{3} \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{[V_1, V_2]^\circ}{3} \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R))$
2	$= (\text{ran}(V_1) \ \frac{[V_1, V_2]^\circ}{3} \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{[V_1, V_2]^\circ}{3} \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R))$	$V_2 \ V_1^\circ = \emptyset \implies \text{ran}(V_1) \ \frac{[V_1, V_2]^\circ}{3} = \text{ran}(V_1) \ \frac{V_1^\circ}{3} \ P(l)$
3	$= (\text{ran}(V_1) \ \frac{V_1^\circ}{3} \ P(l) \ \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{[V_1, V_2]^\circ}{3} \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R))$	$V_2 \ V_1^\circ = \emptyset \implies \text{ran}(V_2) \ \frac{[V_1, V_2]^\circ}{3} = \text{ran}(V_2) \ \frac{V_2^\circ}{3} \ P(r)$



4	$= (\text{ran}(V_1) \ \frac{V_1^\circ}{3} \ P(l) \ \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{V_2^\circ}{3} \ P(r) \ \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R))$	$P(l) \ \text{thin}(Q_1 + Q_2) = \text{thin}(Q_1) \ P(l)$
5	$= (\text{ran}(V_1) \ \frac{V_1^\circ}{3} \ \text{thin}(Q_1) \ P(l) \ P([U_1, U_2]) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{V_2^\circ}{3} \ P(r) \ \text{thin}(Q_1 + Q_2) \ P([U_1, U_2]) \ \text{est}(R))$	$P(r) \ \text{thin}(Q_1 + Q_2) = \text{thin}(Q_2) \ P(r)$
6	$= (\text{ran}(V_1) \ \frac{V_1^\circ}{3} \ \text{thin}(Q_1) \ P(l) \ P([U_1, U_2]) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{V_2^\circ}{3} \ \text{thin}(Q_2) \ P(r) \ P([U_1, U_2]) \ \text{est}(R))$	




7	$= (\text{ran}(V_1) \ \frac{V_1^\circ}{3} \ \text{thin}(Q_1) \ P(l) \ P([U_1, U_2]) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{V_2^\circ}{3} \ \text{thin}(Q_2) \ P(r) \ P([U_1, U_2]) \ \text{est}(R))$	$l \ [R, S] = R$
8	$= (\text{ran}(V_1) \ \frac{V_1^\circ}{3} \ \text{thin}(Q_1) \ P(U_1) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{V_2^\circ}{3} \ \text{thin}(Q_2) \ P(r) \ P([U_1, U_2]) \ \text{est}(R))$	$r \ [R, S] = S$
9	$= (\text{ran}(V_1) \ \frac{V_1^\circ}{3} \ \text{thin}(Q_1) \ P(U_1) \ \text{est}(R)) \cup (\text{ran}(V_2) \ \frac{V_2^\circ}{3} \ \text{thin}(Q_2) \ P(U_2) \ \text{est}(R))$	

Map(cost) $\wedge$ h cost = F(cost) k $\wedge$ F($\leq$) k $\sqsubseteq$ k $\leq \implies$ F(cost $\leq$ cost $^\circ$) h $\sqsubseteq$ h cost $\leq$ cost $^\circ$ Proposition 9.2

if h then **cost** equals **F(cost)** then a **k** monotonic on $\leq$, then **h** is monotonic on **cost $\leq$ cost $^\circ$** ,
which compares two values by comparing their **costs** under $\leq$

Map(cost) $\wedge$ h cost = F(cost) k $\wedge$ F($\leq$) k $\sqsubseteq$ k $\leq \implies$ F(cost $\leq$ cost $^\circ$) h cost $\sqsubseteq$ h cost $\leq$

by shunting at the map **cost**, **F(cost $\leq$ cost $^\circ$)h $\sqsubseteq$ h cost $\leq$ cost $^\circ$** is **F(cost $\leq$ cost $^\circ$)h cost $\sqsubseteq$ h cost $\leq$** , which the chain proves



1	$F(\text{cost} \leq \text{cost}^\circ) \text{ h cost}$	$\text{h cost} = F(\text{cost}) \text{ k}$
2	$= F(\text{cost} \leq \text{cost}^\circ) F(\text{cost}) \text{ k}$	$\text{Map}(f) \wedge R = f S f^\circ$
3	$\sqsubseteq F(\text{cost}) F(\leq) \text{ k}$	$\implies R f \sqsubseteq f S$
4	$\sqsubseteq F(\text{cost}) \text{ k} \leq$	$F(\leq) \text{ k} \sqsubseteq \text{ k} \leq$
5	$= \text{h cost} \leq$	$\text{h cost} = F(\text{cost}) \text{ k}$

(9.1.2a)


	the condition	how it is discharged
1	$F(R) \text{ h} \sqsubseteq \text{h} R$ Proposition 9.2, $R \triangleq \text{cost} \leq \text{cost}^\circ$, $\text{h cost} = F(\text{cost}) \text{ k}$, $F(\leq) \text{ k} \sqsubseteq \text{ k} \leq$	monotonicity when the cost is itself a fold with a step k monotonic on $\leq$
2	$F(R \text{ n } (H^\circ H)) \text{ h} \sqsubseteq \text{h} R$ Proposition 9.3, $R \triangleq \text{cost} \leq \text{cost}^\circ$, $\text{h cost} = F(\langle \text{cost}, H^\circ \rangle) \text{ k}$, $F(\leq \times 1) \text{ k} \sqsubseteq \text{ k} \leq$, H° simple;	monotonicity in context : k may also read the input the part was built from
3	$QF(H) \text{ h} \sqsubseteq F(H) \text{ h} R$ at $Q \triangleq F(U, V)$ Proposition 9.4, U, V preorders, $F(U, R) \text{ h} \sqsubseteq \text{h} R$, $V H \sqsubseteq H R$	both conditions at once, split along the two arguments of a bifunctor

Map(cost) $\wedge$ Simple(S) $\wedge$ h cost = F((cost,S)) k $\wedge$ F($\leq \times 1$) k $\sqsubseteq$ k $\leq \Rightarrow$


Proposition 9.3

F((cost $\leq$ cost $^\circ$) $\cap$ (S S $^\circ$)) h $\sqsubseteq$ h cost $\leq$ cost $^\circ$

improving each part by **R** within its **S**-context, then assembling by **h**, is below **hR**



1	F((cost $\leq$ cost $^\circ$) $\cap$ (S S $^\circ$)) h	
2	= F((cost $\leq$ cost $^\circ$) $\cap$ (S S $^\circ$)) h	Map(f)
3	$\sqsubseteq$ F((cost $\leq$ cost $^\circ$) $\cap$ (S S $^\circ$)) h cost cost $^\circ$	$\Rightarrow 1 \sqsubseteq f f^\circ$
4	= F((cost $\leq$, S) (cost, S) $^\circ$) h cost cost $^\circ$	$\langle X, Y \rangle (R, S)^\circ = (X R^\circ) \cap (Y S^\circ)$
5	= F((cost $\leq$, S) (cost, S) $^\circ$ (cost, S)) k cost $^\circ$	h cost = F((cost, S)) k




6	$\sqsubseteq$ F((cost $\leq$, S)) k cost $^\circ$	$\langle X, Y \rangle (R \times 1) = \langle X R, Y \rangle$
7	= F((cost, S)) F($\leq \times 1$) k cost $^\circ$	F($\leq \times 1$) k $\sqsubseteq$ k $\leq$
8	$\sqsubseteq$ F((cost, S)) k $\leq$ cost $^\circ$	h cost = F((cost, S)) k
9	= h cost $\leq$ cost $^\circ$	

G(U, R) h $\sqsubseteq$ h R $\wedge$ V H $\sqsubseteq$ H R $\Rightarrow$ G(U, V) G(1, H) h $\sqsubseteq$ G(1, H) h R

Proposition 9.4

thinning the parts by **U** in the first argument and by **V** in the second (G(U, V)), then solving by **H** and assembling by **h**, gives only what solving and assembling and then improving by **R** gives

(G(1, H) h R)



1	G(U, V) G(1, H) h	
2	= G(U, V H) h	V H $\sqsubseteq$ H R
3	$\sqsubseteq$ G(U, H R) h	
4	= G(1, H) G(U, R) h	G(U, R) h $\sqsubseteq$ h R
5	$\sqsubseteq$ G(1, H) h R	

§9.2. The string edit problem



(9.2a)

	name	type	definition	meaning
1	Op	Type	$(\exists a. o = \text{cpy}(a)) \vee (\exists a. o = \text{del}(a)) \vee (\exists a. o = \text{ins}(a))$	an edit operation copies, deletes or inserts one character
2			$\text{FX} = 1 + (\text{Op} \times \text{X})$	$\text{F}(\text{Op}, \text{X})$ is the empty sequence or one operation paired with an X
3	edit	$[\text{Op}] \rightarrow [\text{Char}] \times [\text{Char}]$	$\text{edit} = ([\text{base}, \text{step}])$, $\text{edit}([]) = ([], [])$, $\text{edit}([\text{op}] \# \text{es}) = \text{step}((\text{op}, \text{edit}(\text{es})))$	the two strings an edit sequence turns one into the other
4			$\text{length} = ([\text{zero}, \pi_2 \text{ succ}])$	the number of operations in a sequence
5	R	$[\text{Op}] \rightarrow [\text{Op}]$	$\text{R} = \text{length} \leq \text{length}^\circ$, $\text{R}(\text{es}, \text{fs}) \iff \text{length}(\text{es}) \leq \text{length}(\text{fs})$	es is no longer than fs
6	V	$[\text{Char}] \times [\text{Char}] \rightarrow [\text{Char}] \times [\text{Char}]$	$\text{V} = \text{suffix}^\circ \times \text{suffix}^\circ$, $\text{V}(\text{p}, \text{q}) \iff \text{suffix}(\pi_1(\text{p}), \pi_1(\text{q})) \wedge \text{suffix}(\pi_2(\text{p}), \pi_2(\text{q}))$	each string of the first pair is a suffix of the matching string of the second
7	Q	$\text{F}([\text{Char}] \times [\text{Char}]) \rightarrow \text{F}([\text{Char}] \times [\text{Char}])$	$\text{l}(\text{val}) \text{ Q } \text{l}(\text{val}') \iff \text{true}$, $\text{r}(\text{p}) \text{ Q } \text{r}(\text{q}) \iff \text{V}(\pi_2(\text{p}), \pi_2(\text{q}))$, $(\forall \text{val}. \forall \text{val}'. u = \text{l}(\text{val}) \implies v = \text{l}(\text{val}') \implies \text{false}) \wedge (\forall \text{p}. \forall \text{q}. u = \text{r}(\text{p}) \implies v = \text{r}(\text{q}) \implies \text{false}) \implies (u \text{ Q } v \iff \text{false})$, $\text{Q}(\text{l}(\text{u}), \text{l}(\text{u})), \text{Q}(\text{r}(\text{p}), \text{r}(\text{q})) \iff \text{V}(\pi_2(\text{p}), \pi_2(\text{q}))$	the identity on the base summand; on the step summand any two operations, and the two pairs of strings by V
8	empty	$[\text{Char}] \times [\text{Char}] \rightarrow [\text{Char}] \times [\text{Char}]$	$\text{empty}(\text{p}, \text{q}) \iff \text{p} = \text{q} \wedge \text{p} = ([], [])$	holds only at the pair of two empty strings
9	unstep	$[\text{Char}] \times [\text{Char}] \rightarrow [\text{Op}] \times [\text{Char}] \times [\text{Char}]$	$\text{q} \in \text{unstep}(\text{p}) \implies \text{step}(\text{q}) = \text{p}$, $\text{unstep}([[], []]) = []$, $\text{unstep}([[\text{a}] \# \text{xs}, []]) = [(\text{del}(\text{a}), (\text{xs}, []))]$, $\text{unstep}([[], [\text{b}] \# \text{ys}]) = [(\text{ins}(\text{b}), ([], \text{ys}))]$, $\text{unstep}([[\text{a}] \# \text{xs}, [\text{b}] \# \text{ys}]) = \text{if } \text{a} = \text{b} \text{ then } [(\text{cpy } \text{a}, \text{xs}, \text{ys})] \text{ else } [(\text{del } \text{a}, \text{xs}, [\text{b}] \# \text{ys}), (\text{ins } \text{b}, [\text{a}] \# \text{xs}, \text{ys})]$	every split of a pair of strings into one operation and a smaller pair; step puts it back
10	[nil, cons]	$\text{Unit} + \text{Op} \times [\text{Op}] \rightarrow [\text{Op}]$	$[\text{nil}, \text{cons}](\text{l}(\text{u})) = []$, $[\text{nil}, \text{cons}](\text{r}(\text{o}, \text{es})) = [\text{o}] \# \text{es}$	[nil, cons] : the empty edit sequence, or one operation in front of a sequence
11	[base, step]	$\text{Unit} + \text{Op} \times [\text{Char}] \times [\text{Char}] \rightarrow [\text{Char}] \times [\text{Char}]$	$\text{base} = ([[], []])$, $\text{step}((\text{cpy}(\text{a}), (\text{xs}, \text{ys}))) = ([\text{a}] \# \text{xs}, [\text{a}] \# \text{ys})$, $\text{step}((\text{del}(\text{a}), (\text{xs}, \text{ys}))) = ([\text{a}] \# \text{xs}, \text{ys})$, $\text{step}((\text{ins}(\text{a}), (\text{xs}, \text{ys}))) = (\text{xs}, [\text{a}] \# \text{ys})$	[base, step] : the two empty strings, or one operation added to the front of the pair

circuit	Hinze–Marsden
length is a map, so entire: $1 \sqsubseteq \text{length} \text{ length}^\circ$	
$\alpha \text{ length} = F(\text{length})[\text{zero}, \pi_2 \text{ succ}] : \text{length}^\Delta([\text{zero}, \pi_2 \text{ succ}]) - \text{es } R \text{ fs} \iff \text{length}(\text{es}) \leq \text{length}(\text{fs})$	
length is a map, so simple, and F is monotonic: $F(\text{length}^\circ)F(\text{length}) \sqsubseteq F(1) = 1$	
succ is monotonic on $\leq$: $F(\leq)[\text{zero}, \pi_2 \text{ succ}] \sqsubseteq [\text{zero}, \pi_2 \text{ succ}] \leq$	
$F(\text{length})[\text{zero}, \pi_2 \text{ succ}] = \alpha \text{ length}$ again	
$R \sqsubseteq \text{length} \leq \text{length}^\circ - \text{es } R \text{ fs} \iff \text{length}(\text{es}) \leq \text{length}(\text{fs})$	

$Q \vdash F(\text{edit}^\circ) [\text{nil}, \text{cons}] \sqsubseteq F(\text{edit}^\circ) [\text{nil}, \text{cons}] R$ (9.2d)	
every edit sequence built from a decomposition Q puts above a given one — any operation, each string lengthened at the front — is at least as long as one built from the given one	
circuit	Hinze–Marsden
$=$ $Q \triangleq 1 + (U \times V)$ is $F(U, V)$ at $U \triangleq T - l(\text{val}) \ Q \ l(\text{val}') \iff \text{true}$, $r(p) \ Q \ r(q) \iff V(\pi_2(p), \pi_2(q))$, $(\forall \text{val}. \forall \text{val}'. u = l(\text{val}) \implies v = l(\text{val}') \implies \text{false}) \wedge (\forall p. \forall q. u = r(p) \implies v = r(q) \implies \text{false})$ $\implies (u \ Q \ v \iff \text{false})$; and the bifunctor F preserves composition: $F(U, V)F(1, \text{edit}^\circ) = F(U, V \text{ edit}^\circ)$	
$\sqsubseteq$ Proposition 9.4's second condition $V \text{ edit}^\circ \sqsubseteq \text{edit}^\circ R - \text{edit } V^\circ \sqsubseteq R^\circ \text{ edit}$	
$=$ F preserves composition: $F(U, \text{edit}^\circ R) = F(1, \text{edit}^\circ)F(U, R)$	
$\sqsubseteq$ Proposition 9.4's first condition $F(T, R) \alpha \sqsubseteq \alpha R$, left as an exercise in the book: cons adds one to both lengths whatever the two operations are	

$\text{edit } V^\circ \sqsubseteq R^\circ \text{ edit}$ (9.2e) cutting a front off either string an edit sequence produces ($\text{edit } V^\circ$) leaves a pair that a sequence no longer produces ($R^\circ \text{ edit}$)	
circuit	Hinze–Marsden
$=$ $V \triangleq \text{suffix}^\circ \times \text{suffix}^\circ$, and $\times$ preserves composition	
$\sqsubseteq$ $\text{edit } (\text{suffix} \times 1) \sqsubseteq R^\circ \text{ edit}$: drop the operation that produced the head, or weaken its cpy to an ins . Proved by induction at suffix directly, not through $\text{suffix} = \text{tail}^*$ and $BA \sqsubseteq CB \implies BA^* \sqsubseteq C^*B$ as the book does	
$\sqsubseteq$ $\text{edit } (1 \times \text{suffix}) \sqsubseteq R^\circ \text{ edit}$, the mirror image: cpy weakens to a del	
$\sqsubseteq$ R° is transitive, $\leq$ being so	

$\text{step } \text{base}^\circ = \emptyset$ (9.2f) no pair of strings is both a result of step and the result $([], [])$ of base	
circuit	Hinze–Marsden
	
 base returns only $([], [])$, so $\text{base}^\circ = \text{empty } \text{base}^\circ$	
 $\text{step } \text{empty} = \emptyset$: cpy and del put a character on the left string, ins one on the right	
 $\emptyset$ composed with anything is $\emptyset$	

§9.2.1. Tabulation

(9.2.1a)

1	$\text{mle}(xs, ys) = \text{head}(\text{column}(xs, ys))$, $\text{column}(xs, ys) = [\text{mle}(u, ys) \mid u \leftarrow \text{tails}(xs)]$ $\text{column}(xs) = ([\text{fstcol}(xs), \text{nextcol}(xs)])$, $\text{fstcol} = \text{list}(\text{del}) \text{ tails}$ the tabulation: $\text{mle}(xs, ys)$ needs $\text{mle}(u, v)$ for every tail u of xs and v of ys , so the columns are built right to left
2	$\text{column}(xs, [b] \# ys) = \text{nextcol}(xs, (b, \text{column}(xs, ys)))$ $\text{nextcol}(xs)(b, us) = ([\text{base}(b, \text{last}(us)), \text{step}(b)] \triangleright (xus), xus = \text{zip}(xs, \text{zip}(\text{init}(us), \text{tail}(us)))$ each column is a fold built bottom to top, over xs zipped with the adjacent pairs of the column to its right
3	$\text{base}(b, u) = [[\text{ins}(b)] \# u]$ $\text{step}(b)((a, (u, v)), ws) = (a \rightarrow b \rightarrow [[\text{cpy}(a)] \# v] \# ws, [\text{bmin}(R)([\text{del}(a)] \# w, [\text{ins}(b)] \# u)] \# ws)$ $w = \text{head}(ws)$; these base , step are not edit 's. An entry depends on the one below it (a delete), the one to its right (an insert), and the one below that (a copy) — quadratic in the two lengths

§9.3. Optimal bracketing

(9.3a)

	name	type	definition	meaning
1	<code>tree(A)</code>	Type	$\text{tree}(A) \triangleq \text{tip}(A) \mid \text{bin}(\text{tree}(A), \text{tree}(A))$	a tree is a tip holding one value, or a node joining two trees; $\mathbf{h} \triangleq [\text{tip}, \text{bin}]$
2	<code>flatten</code>	$\text{tree}(A) \rightarrow \text{LA}$	$\langle [\text{wrap}, \text{cat}] \rangle = \text{flatten}, \text{flatten}(\text{tip}(a)) = [a],$ $\text{flatten}(\text{bin}(xs, ys)) = \text{cat}(\text{flatten}(xs), \text{flatten}(ys))$	the tips of a tree, left to right; $\mathbf{H} = \text{flatten}^\circ$ builds every tree over a list
3	<code>opb(p)</code>	$\text{Int} \times \text{S}$	$\text{opb}(p) \triangleq ((\text{cb}(\pi_2(\pi_1(p)), \pi_2(\pi_2(p))) + \pi_1(\pi_1(p))) + \pi_1(\pi_2(p)), \text{sb}(\pi_2(\pi_1(p)), \pi_2(\pi_2(p))))$	joining two subtrees costs cb of their sizes plus the cost of each
4	$\langle \text{cost}, \text{size} \rangle$	$\text{tree}(A) \rightarrow \text{Int} \times \text{S}$	$\langle \text{cost}, \text{size} \rangle(\text{tip}(a)) = (0, \text{st}(a)),$ $\langle \text{cost}, \text{size} \rangle(\text{bin}(xs, ys)) = \text{opb}(\langle \text{cost}, \text{size} \rangle(xs), \langle \text{cost}, \text{size} \rangle(ys))$	the cost of evaluating a bracketing, paired with the size of its result
5	<code>sz</code>	$\text{LA} \rightarrow \text{S}$	$\text{sz}([a]) = \text{st}(a), \text{sz}([a] \# xs) = \text{sb}(\text{st}(a), \text{sz}(xs)),$ $\text{Assoc}(\text{sb}) \implies \pi_2(\langle \text{cost}, \text{size} \rangle(xs)) = \text{sz}(\text{flatten}(xs))$	sb associative, so the size depends only on the flattened list
6	<code>R</code>	$\text{tree}(A) \rightarrow \text{tree}(A)$	$R = \text{cost} \leq \text{cost}^\circ, R(xs, ys) \iff \text{cost}(xs) \leq \text{cost}(ys)$	t costs no more than t'
7	<code>g</code>	$\text{F}(\text{Int} \times \text{LA}) \rightarrow \text{Int}$	$g \triangleq [\neg 0, (1 \times \text{sz})^2 \text{ opb } \pi_1], g(\text{l}(a)) = 0,$ $g(\text{r}((cx, xs), cy, ys)) = (\text{cb}(\text{sz}(xs), \text{sz}(ys)) + cx) + cy$	the cost of the top step alone: zero at a tip, cb of the two sizes at a node
8	<code>nonsingle</code>	$\text{LA} \rightarrow \text{LA}$	$xs \text{ nonsingle } ys \iff xs = ys \wedge (\exists a. \exists zs. xs = [a] \# zs)$	holds at the lists of two or more elements
9	<code>splits</code>	$\text{LA} \rightarrow [\text{L } A \times \text{L } A]$	$\text{splits} = (\text{inits}^+, \text{tails}^+) \text{ zip}, \text{splits}(xs) = \text{zip}(((\text{inits}^+)(xs), (\text{tails}^+)(xs)))$	every way to cut a list into two non-empty parts — an implementation of $\frac{\text{cat}^\circ}{\exists}$
10	<code>array</code>	$\text{LA} \rightarrow [\text{tree } A]$	$\text{array} \triangleq \text{inits list}(\text{row}), \text{array}(xs, xss) \iff xss = \text{list}(\text{row}, \text{inits}(xs))$	the best trees of every segment, held as rows
11	<code>row</code>	$\text{LA} \rightarrow [\text{tree } A]$	$\text{row} = \text{tails list}(\text{mct}), \text{row}(xs, xss) \iff xss = \text{list}(\text{mct}, \text{tails}(xs))$	the best tree of every non-empty suffix
12	<code>col</code>	$\text{LA} \rightarrow [\text{tree } A]$	$\text{col} = \text{inits list}(\text{mct}), \text{col}(xs, xss) \iff xss = \text{list}(\text{mct}, \text{inits}(xs))$	the best tree of every non-empty prefix
13	<code>mix</code>	$[\text{tree } A] \times [\text{tree } A] \rightarrow \text{tree}(A)$	$\text{mix} = \text{zip list}(\text{bin}) \text{ minlist}(R), \text{mix}(p, xs) \iff xs = \text{minlist}(R) (\text{list bin zip})$	join the matching prefix and suffix trees and keep a cheapest
14	<code>next</code>	$[\text{tree } A] \times [\text{tree } A] \rightarrow [\text{tree } A]$	$\text{next} = (\pi_1, \text{mix}) \text{ snoc}, \text{next}(p, xss) \iff xss = \text{snoc}((\pi_1(p), \text{minlist}(R) (\text{list bin zip})))$	add the next best tree to the end of the column

15

name	type	definition	meaning
process	$A \times [[\text{tree } A]] \rightarrow [\text{tree } A]$	$\text{process} \triangleq ((\text{tip wrap}) \times 1) \text{ loop}(\text{next}) ,$ $\text{process}((a, xsss), xss) \Leftrightarrow$ $\text{loop}(\text{next})(([\text{tip } a], xsss), xss)$	start the column at a tip and run next over the rows

Assoc(sb) $\Rightarrow$ F((cost, flatten)) g = [tip, bin] cost (9.5) pairing each subtree with its cost and its flattening and then applying g gives what building the tree by [tip, bin] and taking its cost gives	
circuit	Hinze–Marsden
$F(\text{tree}(A)) \rightarrow \boxed{F((\text{cost}, \text{flatten}))} \rightarrow F(\text{Int} \times \text{LA}) \rightarrow \boxed{g} \rightarrow \text{Int}$	
$A + \text{tree}(A)^2 \rightarrow \left\{ \begin{array}{l} \boxed{l} \rightarrow A \rightarrow \text{zero} \\ \boxed{r} \rightarrow \text{tree}(A) \rightarrow \left\{ \begin{array}{l} \text{cost} \\ \text{flatten} \rightarrow \text{LA} \rightarrow \text{sz} \end{array} \right\} \\ \text{tree}(A) \rightarrow \left\{ \begin{array}{l} \text{cost} \\ \text{flatten} \rightarrow \text{LA} \rightarrow \text{sz} \end{array} \right\} \end{array} \right\} \rightarrow \text{opb} \rightarrow \text{Int}$ definition of g; coproducts and products — $g \triangleq [\multimap 0, (1 \times \text{sz})^2 \text{ opb } \pi_1]$	
$A + \text{tree}(A)^2 \rightarrow \left\{ \begin{array}{l} \boxed{l} \rightarrow A \rightarrow \text{zero} \\ \boxed{r} \rightarrow \text{tree}(A) \rightarrow \left\{ \begin{array}{l} \text{cost} \\ \text{size} \end{array} \right\} \\ \text{tree}(A) \rightarrow \left\{ \begin{array}{l} \text{cost} \\ \text{size} \end{array} \right\} \end{array} \right\} \rightarrow \text{opb} \rightarrow \text{Int}$ flatten sz=size, since sb is associative — $\text{sz}([a]) = \text{st}(a)$, $\text{sz}([a] \# xs) = \text{sb}(\text{st}(a), \text{sz}(xs))$	
$A + \text{tree}(A)^2 \rightarrow \left\{ \begin{array}{l} \boxed{l} \rightarrow A \rightarrow \text{zero} \\ \boxed{r} \rightarrow \text{tree}(A) \rightarrow \boxed{\text{bin}} \rightarrow \text{tree}(A) \rightarrow \left\{ \begin{array}{l} \text{cost} \rightarrow \text{Int} \\ \text{size} \rightarrow S \end{array} \right\} \end{array} \right\} \rightarrow \text{opb} \rightarrow \text{Int}$ $(\text{cost}, \text{size}) \triangleq ([\text{opt}, \text{opb}])$, at a node $\text{bin}(\text{cost}, \text{size}) = (\text{cost}, \text{size})^2 \text{ opb}$	
$A + \text{tree}(A)^2 \rightarrow \left\{ \begin{array}{l} \boxed{l} \rightarrow A \rightarrow \boxed{\text{tip}} \rightarrow \text{tree}(A) \rightarrow \text{cost} \\ \boxed{r} \rightarrow \text{tree}(A) \rightarrow \boxed{\text{bin}} \rightarrow \text{tree}(A) \rightarrow \text{cost} \end{array} \right\} \rightarrow \text{Int}$ tip cost=zero; products, $(\text{cost}, \text{size}) \pi_1 = \text{cost}$	
$A + \text{tree}(A)^2 \rightarrow \left\{ \begin{array}{l} \boxed{l} \rightarrow A \rightarrow \boxed{\text{tip}} \\ \boxed{r} \rightarrow \text{tree}(A) \rightarrow \boxed{\text{bin}} \end{array} \right\} \rightarrow \text{tree}(A) \rightarrow \boxed{\text{cost}} \rightarrow \text{Int}$ coproducts, $[\text{tip cost}, \text{bin cost}] = [\text{tip}, \text{bin}] \text{ cost}$	


$F(\leq \times 1) \ g \sqsubseteq g \leq$ (9.6)	
raising the cost of either subtree ($\leq \times 1$ in both slots) and then applying g returns a value at least what g returns on the costs before raising ($g \leq$)	
circuit	Hinze–Marsden
$F(\text{Int} \times \text{LA}) \rightarrow \boxed{F(\leq \times 1)} \rightarrow \boxed{g} \rightarrow \text{Int}$	
$A + \text{Int} \times \text{LA} \times \text{Int} \times \text{LA} \rightarrow$ $\text{definition of } g \text{ — } g \triangleq [\neg 0, (1 \times \text{sz})^2 \text{ opb } \pi_1]$	
$A + \text{Int} \times \text{LA} \times \text{Int} \times \text{LA} \rightarrow$ $\text{definition of } \text{opb}, \text{ and } + \text{ monotonic}$	
$A + \text{Int} \times \text{LA} \times \text{Int} \times \text{LA} \rightarrow$ $\leq \text{ reflexive, so } \text{zero} \sqsubseteq \text{zero} \leq; \text{ coproducts}$	
$F(\text{Int} \times \text{LA}) \rightarrow \boxed{g} \rightarrow \boxed{\leq} \rightarrow \text{Int}$ $\text{definition of } g \text{ — } g \triangleq [\neg 0, (1 \times \text{sz})^2 \text{ opb } \pi_1]$	

21


nonsingle mct = nonsingle (init col,tail row) mix

(9.7)


on a list of two or more elements, **mct** gives what **mix** gives on the column of its **init** and the row of its **tail**




1	nonsingle mct	nonsingle splits list(graft) minlist(R)
2	= nonsingle splits list(graft) minlist(R)	splits = (inits ⁺ , tails ⁺) zip
3	= nonsingle (inits ⁺ , tails ⁺) zip list(graft) minlist(R)	graft $\triangleq$ (mct $\times$ mct) bin



4	= nonsingle (inits ⁺ , tails ⁺) zip list(mct $\times$ mct) list(bin) minlist(R)	zip list(f $\times$ g) M = (list(f) $\times$ list(g)) zip M
5	= nonsingle (inits ⁺ , tails ⁺) (list(mct) $\times$ list(mct)) zip list(bin) minlist(R)	$\langle R, S \rangle (U \times V) = \langle R U, S V \rangle$



6	= nonsingle (inits ⁺ list(mct), tails ⁺ list(mct)) zip list(bin) minlist(R)	mix = zip list(bin) minlist(R)
7	= nonsingle (inits ⁺ list(mct), tails ⁺ list(mct)) mix	nonsingle $\langle U, V \rangle = \langle \text{nonsingle } U, \text{nonsingle } V \rangle$
8	= (nonsingle inits ⁺ list(mct), nonsingle tails ⁺ list(mct)) mix	nonsingle inits ⁺ M = nonsingle init inits M



9	= (nonsingle init inits list(mct), nonsingle tails ⁺ list(mct)) mix	nonsingle tails ⁺ M = nonsingle tail tails M
10	= (nonsingle init inits list(mct), nonsingle tail tails list(mct)) mix	nonsingle $\langle U, V \rangle = \langle \text{nonsingle } U, \text{nonsingle } V \rangle$
11	= nonsingle (init inits list(mct), tail tails list(mct)) mix	col = inits list(mct)





12	= nonsingle (init col, tail tails list(mct)) mix	row = tails list(mct)
13	= nonsingle (init col, tail row) mix	




nonsingle col = nonsingle (init col,tail row) next

(9.8)




on a list of two or more elements, the column is what **next** makes of the column of its **init** and the row of its **tail**





1	nonsingle col	col $\triangleq$ inits list(mct)
2	$\triangleq$ nonsingle inits list(mct)	nonsingle inits M = nonsingle (init inits,1) snoc M
3	= nonsingle (init inits,1) snoc list(mct)	snoc list(f) = (list(f) $\times$ f) snoc









4	= nonsingle (init inits,1) (list(mct) $\times$ mct) snoc	$\langle R,S \rangle (U \times V) = \langle R U, S V \rangle$
5	= nonsingle (init inits list(mct),mct) snoc	col = inits list(mct)
6	= nonsingle (init col,mct) snoc	nonsingle $\langle U,V \rangle =$ nonsingle $\langle U,$ nonsingle $V \rangle$















7	= nonsingle (init col,nonsingle mct) snoc	(9.7) nonsingle mct = nonsingle (init col,tail row) mix
8	= nonsingle (init col,nonsingle (init col,tail row) mix) snoc	nonsingle $\langle U,V \rangle =$ nonsingle $\langle U,$ nonsingle $V \rangle$
9	= nonsingle (init col,(init col,tail row) mix) snoc	$\langle \text{init col}, V \rangle \langle \pi_1, M \rangle = \langle \text{init col}, (\text{init col}, V) M \rangle$







10	= nonsingle (init col,tail row) $\langle \pi_1, \text{mix} \rangle$ snoc	next = $\langle \pi_1, \text{mix} \rangle$ snoc
11	= nonsingle (init col,tail row) next	

nonsingle row = nonsingle (mct,tail row) cons (9.10) on a list of two or more elements, the row is mct of the whole list consed onto the row of its tail	
   (1) (2) (3)	
1 nonsingle row	row $\triangleq$ tails list(mct)
2 $\triangleq$ nonsingle tails list(mct)	nonsingle tails M = nonsingle (1,tail tails) cons M
3 = nonsingle (1,tail tails) cons list(mct)	cons list(f) = (f $\times$ list(f)) cons
   (4) (5) (6)	
4 = nonsingle (1,tail tails) (mct $\times$ list(mct)) cons	$\langle R,S \rangle (U \times V) = \langle R U, S V \rangle$
5 = nonsingle (mct,tail tails list(mct)) cons	row = tails list(mct)
6 = nonsingle (mct,tail row) cons	

cons col = (1 $\times$ array) process (9.9) the column of a consed onto x is what process makes of a and the array of x	
circuit	Hinze–Marsden
	 list tree A
 = Exercise 9.13 with $k \triangleq$ cons col, $g \triangleq$ tip wrap, $h \triangleq$ row, $f \triangleq$ next: its two equations are (9.8) — (9.8) nonsingle col = nonsingle (init col,tail row) next — at $a:[b]$ and at $a:(u++[b])$, with $[a]$ col=[tip(a)]	 list tree A
 products	 list tree A
 definition of process	 list tree A

tops = (1 × array) process tail (9.3c) the trees at the top of the new rows are what process makes of a and the array of x , less its first	
circuit	Hinze–Marsden
	 list tree A
$= \text{LA} \rightarrow \text{cons} \rightarrow \text{LA} \rightarrow \text{inits} \rightarrow \text{tail} \rightarrow \text{LA} \rightarrow \text{list(mct)} \rightarrow [\text{tree(A)}]$ definition of tops$\hat{=}$tic list(mct), our name	 list tree A
$= \text{LA} \rightarrow \text{cons} \rightarrow \text{LA} \rightarrow \text{col} \rightarrow \text{tail} \rightarrow [\text{tree(A)}]$ tail list(f)=list(f) tail; definition of col	 list tree A
$= \text{LA} \rightarrow \text{array} \rightarrow \text{process} \rightarrow \text{tail} \rightarrow [\text{tree(A)}]$ (9.9) — (9.9) cons col = (1 × array) process	 list tree A

rests = π_2 array (9.3d) the rest of each new row is the array of x	
circuit	Hinze–Marsden
	 list list tree A
$= \text{LA} \rightarrow \text{cons} \rightarrow \text{LA} \rightarrow \text{inits} \rightarrow \text{tail} \rightarrow \text{LA} \rightarrow \text{list(tail row)} \rightarrow [[\text{tree(A)}]]$ definition of rests$\hat{=}$tic list(tail row), our name	 list list tree A
$= \text{LA} \rightarrow \text{array} \rightarrow [[\text{tree(A)}]]$ tic list(tail)=π_2 inits; definition of array	 list list tree A





$\text{newrows} = (1 \times \text{array}) \text{ step}$ (9.3e)	
the rows of the array of $\mathbf{a}:\mathbf{x}$ below its first are what step makes of $\mathbf{a}$ and the array of $\mathbf{x}$	
circuit	Hinze–Marsden
$\begin{array}{c} A \\ LA \end{array} \text{newrows} \rightarrow [[\text{tree}(A)]]$	
$\begin{array}{c} A \\ LA \end{array} \text{cons} \rightarrow LA \rightarrow \text{inits} \rightarrow \text{tail} \rightarrow [LA] \rightarrow \text{list}(\text{row}) \rightarrow [[\text{tree}(A)]]$ definition of $\text{newrows} \triangleq \text{tic list}(\text{row})$, our name	
$\begin{array}{c} A \\ LA \end{array} \text{cons} \rightarrow LA \rightarrow \text{inits} \rightarrow \text{tail} \rightarrow [LA] \rightarrow \text{list}(\text{mct}, \text{tail row}) \rightarrow \text{cons} \rightarrow [[\text{tree}(A)]]$ (9.10) — (9.10) nonsingle row = nonsingle (mct, tail row) cons — on the non-singleton tic lists	
$\begin{array}{c} A \\ LA \end{array} \begin{array}{c} \text{tops} \\ \text{rests} \end{array} \rightarrow \begin{array}{c} [\text{tree}(A)] \\ [\text{tree}(A)] \end{array} \rightarrow \text{zip} \rightarrow [\text{tree}(A) \times [\text{tree}(A)]] \rightarrow \text{list}(\text{cons}) \rightarrow [[\text{tree}(A)]]$ $\text{list}(f,g) = (\text{list}(f), \text{list}(g))$ zip; products; definitions of tops and rests	
$\begin{array}{c} A \\ LA \end{array} \text{array} \rightarrow \text{step} \rightarrow [[\text{tree}(A)]]$ $\text{tops} = (1 \times \text{array})$ process tail and rests = π_2 array; products; definition of step	

$\text{cons array} = (1 \times \text{array}) \text{ addcol}$ (9.3f)	
the array of a consed onto x is what addcol makes of a and the array of x	
circuit	Hinze–Marsden
$=$ definition of array	
$=$ $\text{cons inits} = (\pi_1 \text{ wrap, tic}) \text{ cons}$, abbreviating cons inits tail by tic	
$=$ $\text{cons list}(f) = (f \times \text{list}(f)) \text{ cons}$; definition of newrows	
$=$ $\text{wrap row} = \text{tip wrap}$	
$=$ $\text{newrows} = (1 \times \text{array}) \text{ step}$; products; definition of addcol	

§9.4. Data compression







(9.4a)

	name	type	definition	meaning
1	String	Type	$\text{String} \triangleq [\text{Char}]$	a string is a snoc-list of characters
2	LA	Type	$\text{LA} \triangleq [\text{A}]$	a non-empty snoc-list: one value, then any number more appended
3	Code	Type	$\text{Code} \triangleq \text{sym}(\text{Char}) \mid \text{ptr}(\text{String}, \text{String})$	a code is one character, or a pointer back to a repeated piece
4	extend	$\text{String} \times \text{Code} \rightarrow [\text{Char}]$	$\text{extend} \triangleq \text{extend} \ , \ \text{extend}((\text{xs}, \text{sym}(\text{a})), \text{x}) = \text{x} = \text{snoc}(\text{xs}, \text{a}) \ , \ \text{extend}((\text{xs}, \text{ptr}(\text{ys}, \text{zs})), \text{x}) = \text{x} = \text{cat}(\text{xs}, \text{zs}) \wedge \text{zs} \neq [] \wedge (\text{init}^+)(\text{cat}(\text{ys}, \text{zs}), \text{cat}(\text{xs}, \text{zs}))$	a symbol appends its character; a pointer appends zs when $\text{ys} \# \text{zs}$ is a proper prefix of $\text{xs} \# \text{zs}$
5	decode	$[\text{Code}] \rightarrow [\text{Char}]$	$\text{decode} \triangleq ([\text{nil}, \text{extend}])$	rebuild the string from its codes, left to right; $\text{H} = \text{decode}^\circ$
6	bytes	$\text{Code} \rightarrow \mathbb{N}$	$\text{bytes}(\text{sym}(\text{a})) = \text{c} \ , \ \text{bytes}(\text{ptr}(\text{a}, \text{a}')) = \text{p}$	a symbol costs c , a pointer costs p
7	size	$[\text{Code}] \rightarrow \mathbb{N}$	$([\text{nil}, \text{distr} \ [1 \times \text{c}, 1 \times \text{p}] \text{ plus}]) = \text{size} \ , \ \text{size}(\text{wrap}(\text{a})) = 0 \ , \ \text{size}(\text{snoc}(\text{cs}, \text{e})) = \text{size}(\text{cs}) + \text{bytes}(\text{e})$	the total cost of a code sequence
8	R	$[\text{Code}] \rightarrow [\text{Code}]$	$\text{R} = \text{size} \leq \text{size}^\circ \ , \ \text{R}(\text{xs}, \text{ys}) \iff \text{size}(\text{xs}) \leq \text{size}(\text{ys})$	u costs no more than v
9	prefix	$[\text{Char}] \rightarrow [\text{Char}]$	$\text{xs prefix ys} \iff (\text{prefix}^\circ)(\text{ys}, \text{xs})$	ys is a prefix of x
10	$(\text{T} + \text{T})$	$\text{Code} \rightarrow \text{Code}$	$(\text{T} + \text{T}) = [\text{sym}, \text{ptr}]^\circ \ (\text{T} + \text{T}) \ [\text{sym}, \text{ptr}] \ , \ \text{sym}(\text{a}) \ (\text{T} + \text{T}) \ \text{sym}(\text{a}') \iff \text{true} \ , \ \text{ptr}(\text{a}, \text{a}') \ (\text{T} + \text{T}) \ \text{ptr}(\text{a}'', \text{a}''') \iff \text{true} \ , \ (\forall \text{a}. \forall \text{a}'. \text{e} = \text{sym}(\text{a}) \implies \text{f} = \text{sym}(\text{a}') \implies \text{false}) \wedge (\forall \text{a}. \forall \text{a}'. \forall \text{a}'' . \forall \text{a}''' . \text{e} = \text{ptr}(\text{a}, \text{a}') \implies \text{f} = \text{ptr}(\text{a}'', \text{a}''') \implies \text{false}) \implies (\text{e} \ (\text{T} + \text{T}) \ \text{f} \iff \text{false})$	any symbol to any symbol, any pointer to any pointer
11	Q	$\text{F}[\text{Char}] \rightarrow \text{F}[\text{Char}]$	$\text{Q} = \text{F}((\text{T} + \text{T}), \text{prefix}^\circ) \ , \ \text{l}(\text{val}) \ \text{Q} \ \text{l}(\text{val}') \iff \text{true} \ , \ \text{r}(\text{p}) \ \text{Q} \ \text{r}(\text{q}) \iff (\text{prefix}^\circ)(\pi_1(\text{p}), \pi_1(\text{q})) \wedge (\text{T} + \text{T})(\pi_2(\text{p}), \pi_2(\text{q})) \ , \ (\forall \text{val}. \forall \text{val}' . \text{u} = \text{l}(\text{val}) \implies \text{v} = \text{l}(\text{val}') \implies \text{false}) \wedge (\forall \text{p}. \forall \text{q}. \text{u} = \text{r}(\text{p}) \implies \text{v} = \text{r}(\text{q}) \implies \text{false}) \implies (\text{u} \ \text{Q} \ \text{v} \iff \text{false})$	compare two decompositions by the prefix order on the strings and U on the codes
12	reduce	$[\text{Char}] \rightarrow [\text{String} \times \text{Code}]$	$\text{reduce} \triangleq \text{reduce} \ , \ \text{q} \in \text{reduce}(\text{ws}) \iff \text{extend}(\text{q}, \text{ws})$	the last code of a string: one symbol, or a pointer to its longest repeated tail

$(\mu X : \frac{[nil, extend]^{\circ}}{\exists} \text{thin}(Q) P([nil, (X \times 1) snoc]) \text{est}(R)) \sqsubseteq \frac{decode^{\circ}}{\exists} \text{est}(R) , \quad (9.4b)$ $\text{encode} = (\text{null} \rightarrow nil, \text{reduce list}((\text{encode} \times 1) snoc) \text{minlist}(R))$ a smallest code sequence decoding to the given string is built from the right, each step emitting the last character as a symbol or ending with a pointer back into what has already been decoded	
circuit	Hinze–Marsden
$[Char] \xrightarrow{\frac{1}{\exists}} P[Char] \xrightarrow{E(decode^{\circ})} P[Code] \xrightarrow{\text{est}(R)} [Code]$ the specification — $decode \triangleq ([nil, extend])$	
$[Char] \xrightarrow{\frac{1}{\exists}} P[Char] \xrightarrow{E([nil, extend]^{\circ})} \text{thin}(Q) \xrightarrow{P([Char])} P([nil, (X \times 1) snoc]) \xrightarrow{P[Code]} \text{est}(R) \xrightarrow{[Code]}$ at $Q \triangleq F(T+T, prefix^{\circ}) = 1 + (prefix^{\circ} \times (T+T))$, the two T on symbols and on pointers. Monotonicity $F(R) \alpha \sqsubseteq \alpha R$ is routine, the two costs being constants: $(T+T)[c, p] = [c, p]$. $\sqsubseteq$ Proposition 9.4 splits the thinning condition in two — $F(T+T, R) \alpha \sqsubseteq \alpha R$, and $decode$ $prefix \sqsubseteq R^{\circ} decode$, for which $decode \text{init} \sqsubseteq R^{\circ} decode$ is enough: dropping the last character of the output shortens or removes the last code element and never raises the cost. So between a symbol and a pointer nothing can be decided in advance, and between two pointers the longer match wins	
$[Char] \xrightarrow{\frac{1}{\exists}} P[Char] \xrightarrow{E(extend^{\circ})} \text{thin}(prefix^{\circ} \times (T+T)) \xrightarrow{P([Char] \times Code)} P((X \times 1) snoc) \xrightarrow{P[Code]} \text{est}(R) \xrightarrow{[Code]}$ $\sqsubseteq$ Proposition 9.1: nil and $extend$ have disjoint ranges. The decompositions of one string are $\frac{extend^{\circ}}{\exists} (ws \# [a]) = \{(ws, \text{sym } a)\} \cup \{(xs, \text{ptr}(ys, zs)) \mid xs \# zs = ws \# [a], ys \# zs \text{ a proper prefix of } ws\}$ — take the last character as a symbol, or end with a pointer	
$[Char] \xrightarrow{\text{reduce}} [[Char] \times Code] \xrightarrow{\text{list}((\text{encode} \times 1) snoc)} [[Code]] \xrightarrow{\text{minlist}(R)} [Code]$ $\sqsubseteq$ reduce implements $\frac{extend^{\circ}}{\exists} \text{thin}(prefix^{\circ} \times (T+T))$: thinning leaves at most two, the symbol and the pointer of the longest repeated tail lrt. Again exponential; the book gives no tabulation for it	

§9.4.1. Derivation

$Q \vdash F(\text{decode}^\circ) [\text{nil}, \text{snoc}] \sqsubseteq F(\text{decode}^\circ) [\text{nil}, \text{snoc}] R$ (9.4.1a)	
every code sequence built from a decomposition Q puts above a given one — a code element of the same kind, a longer front string — costs at least as much as one built from the given one	
circuit	Hinze–Marsden
$=$ $Q \triangleq 1 + (\text{prefix}^\circ \times (T+T))$ is $F(T+T, \text{prefix}^\circ) - l(\text{val}) \ Q \ l(\text{val}') \iff \text{true}, r(p) \ Q \ r(q) \iff (\text{prefix}^\circ)(\pi_1(p), \pi_1(q)) \wedge (T+T)(\pi_2(p), \pi_2(q)), (\forall \text{val}. \forall \text{val}'. u = l(\text{val}) \implies v = l(\text{val}') \implies \text{false}) \wedge (\forall p. \forall q. u = r(p) \implies v = r(q) \implies \text{false})$ $\implies (u \ Q \ v \iff \text{false})$	
$=$ the bifunctor F preserves composition: $F(U, \text{prefix}^\circ) F(1, \text{decode}^\circ) = F(U, \text{prefix}^\circ \text{decode}^\circ)$	
$\sqsubseteq$ Proposition 9.4's second condition $\text{prefix}^\circ \text{decode}^\circ \sqsubseteq \text{decode}^\circ R$: dropping the last character drops the last sym, or shortens or drops the last pointer. Proved at prefix directly by induction, not through init	
$=$ F preserves composition: $F(U, \text{decode}^\circ R) = F(1, \text{decode}^\circ) F(U, R)$	
$\sqsubseteq$ Proposition 9.4's first condition $F(T+T, R) \alpha \sqsubseteq \alpha R$, left as an exercise in the book: snoc adds the cost of the last element to both sides, and $[c, p](T+T) = [c, p]$	

extend nil[°] = 0 (9.4.1b) no string is both a result of extend and the result [] of nil	
circuit	Hinze–Marsden
	
 nil returns only [], so nil[°]=null nil[°]	
 extend null=0: a symbol ends the string with a character, a pointer with its non-empty ZS	
 0 composed with anything is 0	