# Companion to Bird & de Moor, Algebra of Programming

# §5. Datatypes in Allegories

## §5.1. Relators

(5.1a)

A **relator** `F : 𝒞↛𝒟` is a 2-functor between allegories: it preserves `𝟙`, composition and `⊑`.

(5.1b)

| | the statement |
|---|---|
| 1 | `Map(f) ⇒ Map(F(f))` and `Map(f) ⇒ F(f°) = F(f)°` . Lemma 5.1 |
| 2 | Over a **tabular** allegory a functor is a relator `⇔` it preserves `°`. Theorem 5.1 the book's reverse direction (preserving `°` ⟹ relator) needs the source to be `Rel`: the counterexample over a tabular allegory that is not `Rel` shows it can fail |
| 3 | `F(R°) = F(R)°` for every `R`, so `F(R)°` needs no bracket. |
| 4 | Two relators agreeing on maps are equal. Corollary 5.1 |
| 5 | `Coreflexive(X); Coreflexive(Y) ⇒ F(X ∩ Y) = F(X) ∩ F(Y)` Ex 5.2 |
| 6 | `F(R ∩ S) ⊑ F(R) ∩ F(S)` , and strictly. Ex 5.2 |
| 7 | `F(dom(R)) = dom(F(R))` Ex 5.5 |

The **power relator** `P` — `xs P(R) ys⇔(∀a∈xs. ∃b∈ys. a R b)∧(∀b∈ys. ∃a∈xs. a R b)` — is where the fourth is strict: for `R={(a₁,b₁),(a₂,b₂)}` and `S={(a₁,b₂),(a₂,b₁)}` the pair `({a₁,a₂},{b₁,b₂})` is in `P(R)∩P(S)`, while `R∩S=∅`.

## §5.2. Relational products

(5.1)


⟨R,S⟩ ≜ (R π₁°) ∩ (S π₂°) — the **fork** of R : C→A and S : C→B, with (π₁,π₂) the tabulation of ⊤.

⟨R,S⟩≜Rπ₁°∩Sπ₂° c ⟨R,S⟩ (a,b)⇔c R a∧c S b.

(5.2a)

⟨R,S⟩ π₁ = dom(S) R (5.6)  ⟨R,S⟩ π₂ = dom(R) S (5.7)


(5.2b)




A domain is coreflexive, so ⟨R,S⟩π₁⊑R, with equality exactly when S is entire; for maps both triangles commute and ⟨f,g⟩ is unique. In Rel, c ⟨R,S⟩ (a,b) iff c R a and c S b — copy c, then R on one strand and S on the other, which is ◁(R⊗S) on the right.

No ° survives the translation. π₁=𝟙⊗⊸ discards the second component, so π₁°=𝟙⊗⊸ **creates** one out of nothing, and ∩ is copy, run both, merge. Draw that and the created strands — the two dots with no left end, and the crossing they force — are merged against real ones, which is the monoid's unit law:

(5.2c)





⊸▷=𝟙 on each half

### §5.2.1. Relational product R×S

(5.2)

R × S ≜ ⟨π₁ R,π₂ S⟩ — the relational product R×S≜⟨π₁R,π₂S⟩.

(5.2.1a)





Right-then-up is (R×S)π₁, up-then-right is π₁R, and (R×S)π₁⊑π₁R, equality when S is entire. In Rel, (c,d) (R×S) (a,b) iff c R a and d S b — two strands side by side, no copy dot: R×S=R⊗S.





### §5.2.2. Absorption

For X : E→C and Y : E→D, ⟨X,Y⟩(R×S)=⟨XR,YS⟩. Both sides are this picture:

(5.3)






(5.2.2a)




| | the law | picture |
|---|---|---|
| 1 | `⟨X,Y⟩ ⟨R,S⟩° = (X R°) ∩ (Y S°)` |  |
| 2 | `⟨R,S⟩° ⟨U,V⟩ ⊑ (R° U) × (S° V)` |  |
| 3 | `Map(f) ⇒ f ⟨R,S⟩ = ⟨f R,f S⟩` `f` a map; it fails for an arbitrary arrow; |  |
| 4 | `X ⟨R,S⟩ ⊑ ⟨X R,X S⟩` the half of the row above that holds for every `X` | |
| 5 | `F(R × S) unzip(F) ⊑ unzip(F) (F(R) × F(S))` `unzip(F)≜⟨F(π₁),F(π₂)⟩`; only `⊑` for an arbitrary `R`, `S` |  |
| 6 | `g=curry(f)⇔(g×𝟙)eval=f` reading `×` as the relational product, does `Rel` have exponentials? | |

## §5.3. Relational coproducts

(5.3a)

| | the statement<br>R : $a_1 \to c$, S : $a_2 \to c$ | picture |
|---|---|---|
| 1 | [R,S] ≜ (l° R) ∪ (r° S)<br>(5.9) The tape is the union — a particle entering at A+B takes exactly one branch — and the two mirrored boxes are what makes the branches disjoint. |  |
| 2 | [R,S] = [$\frac{R}{∋}$,$\frac{S}{∋}$] ∋ |  |
| 3 | l [R,S] = R , r [R,S] = S<br>l T = R; r T = S ⇛ T = [R,S] , | |
| 4 | U : $a_1 \to D$, V : $a_2 \to D$<br>[U,V]° [R,S] = (U° R) ∪ (V° S) (5.11) |  |
| 5 | Z : c→D<br>[R,S] Z = [R Z,S Z] | |


(5.3b)

| | the statement<br>R : $a_1 \to b_1$, S : $a_2 \to b_2$ | picture |
|---|---|---|
| 1 | R + S ≜ [R l,S r] (5.10) |  |
| 2 | l l° = 𝟙 , r r° = 𝟙 Ex 5.12 |  |
| 3 | l r° = 𝟘 , r l° = 𝟘 Ex 5.12 |  |
| 4 | (l° l) ∪ (r° r) = 𝟙 Ex 5.12 |  |


### §5.3.1. [R,S] = [$\frac{R}{∋}$,$\frac{S}{∋}$] ∋ — a case of relations is the case of their transposes, then ∋

The universal-property row is not free: l,r were only ever asked to be a coproduct of **maps**. They stay one once every arrow is allowed because $\frac{\cdot}{∋}$ sends an arrow A→C to a map A→PC reversibly, so the map coproduct can be applied underneath it. For any T : A+B→C,

(5.3.1a)




**(5.3.1b)**




Nothing here holds only up to ⊑: every triangle commutes on the nose, which is the difference from the fork above. The border spells `[R,S]=[`$\frac{R}{\ni}$`,` $\frac{S}{\ni}$`]∋`, and pushing ∋ into the union that `[·,·]` on maps already is turns that back into the definition, `(l°` $\frac{R}{\ni}$ `∪r°` $\frac{S}{\ni}$`)∋=l°R ∪ r°S`.

**(5.3.1c)**

| | **the law** | **picture** |
|---|---|---|
| 1 | prove (5.11), and say why duality does not carry it over from the product law | |
| 2 | `(R + S) ∩ ([P,Q] [U,V]°) = (R ∩ (P U°)) + (S ∩ (Q V°))` `[P,Q][U,V]°` is a full 2×2 of composites; `R+S` is diagonal, so the meet cuts the two off-diagonal branches |  |

## §5.4. The power relator P(R)

(5.4a)


P(R) ≜ (∈ \ (R ∈)) ∩ ((∋ R) / ∋) — the power relator P(R) : PA↛PB, R lifted to sets.

xs P(R) ys⇔(∀a∈xs. ∃b∈ys. a R b)∧(∀b∈ys. ∃a∈xs. a R b)

(5.4b)

| | | in Rel | in words | im(xs) | partner |
|---|---|---|---|---|---|
| 1 | (∋R)/∋ | ∀y∈ys. ∃x∈xs. x R y | ∀y. some xs R y | ys⊆im(xs) | every y has a partner |
| 2 | (∋/(∋R))° | ∀y. (∃x∈xs. x R y)→y∈ys | every y with some xs R y is in ys | ys⊇im(xs) | ys leaves out no partner |
| 3 | E(R) | ys={y\|∃x∈xs. x R y} | ys = every y with some xs R y | ys=im(xs) | every y has a partner, and none is left out |
| 4 | ((∋R°)/∋)° | ∀x∈xs. ∃y∈ys. x R y | ∀x. x R some ys | — | every x has a partner |
| 5 | P(R) | P(R)(xs,ys) ⇔ (∀y. y ∈ ys ⇒ (∃x. x ∈ xs ∧ R(x,y))) ∧ (∀x. x ∈ xs ⇒ (∃y. y ∈ ys ∧ R(x,y))) | ∀y. some xs R y and ∀x. x R some ys | — | every x and every y has a partner |

(5.4c)




| | xs | (∋R)/∋ | (∋/(∋R))° | E(R) | ((∋R°)/∋)° | P(R) |
|---|---|---|---|---|---|---|
| 1 | ∅ | ∅ | all 8 subsets of abc | ∅ | all 8 subsets of abc | ∅ |
| 2 | {1} | ∅, a, b, ab | ab, abc | ab | a, b, ab, ac, bc, abc | a, b, ab |
| 3 | {2} | ∅ | all 8 subsets of abc | ∅ | none | none |
| 4 | {3} | ∅, c | c, ac, bc, abc | c | c, ac, bc, abc | c |
| 5 | {1,2} | ∅, a, b, ab | ab, abc | ab | none | none |
| 6 | {1,3} | all 8 subsets of abc | abc | abc | ac, bc, abc | ac, bc, abc |
| 7 | {2,3} | ∅, c | c, ac, bc, abc | c | none | none |
| 8 | {1,2,3} | all 8 subsets of abc | abc | abc | none | none |

(5.4d)

| | law | the reading |
|---|---|---|
| 1 | X ⊑ P(R) ⇔ X ∋ ⊑ ∋ R ∧ X° ∋ ⊑ ∋ R° | One containment, and the same one at R° — which is the definition read off the two divisions. Hence P(R°)=P(R)°, and R⊑S⇒P(R)⊑P(S) . |
| 2 | P(𝟙) = 𝟙 | The straightness axiom verbatim: extensionality **is** P's unit law. |
| 3 | Map(f) ⇒ P(f) = E(f) | In Rel, xs P(f) ys⇔ys={f(a)\|a∈xs}. The half at f° says every a∈xs has its f(a) on ys; f has just the one image per a, so that already says ys contains everything xs reaches, which is the fraction's second half. For a map the two definitions coincide. |
| 4 | P(R S) = P(R) P(S) | ⊒ is the division cancellation laws. ⊑ is the one law in this section that is not a calculation: it needs a tabulation of P(RS). |

### §5.4.1. Type relators

(5.4.1a)

T(R) = ⟮F(R,𝟙) α⟯ — the type functor T acts on an arrow R : A→B by rebuilding with α, applying R to the parameter.

(5.4.1b)

| | name | law | what it says |
|---|---|---|---|
| 1 | the defining equation | T(R) = ⟮F(R,𝟙) α⟯ | Rebuild the structure with α, applying R to the parameter on the way. |
| 2 | type relator | T(R)° = T(R°) | A datatype acts on relations, not only on maps — the map of the converse is the converse of the map. |


## §5.5. Relational catamorphisms

(5.5a)

> The initial algebra `α : F(T)→T` among the maps is also initial in the allegory:

### §5.5.1. The defining equation

(5.5.1a)





An F-algebra is a **weakened** natural transformation. A transformation `F⇒𝟙` on $\mathcal{A}$ would need a component `FX→X` at every object and a commuting square at every arrow, but F-Algebra only need it works on T and A.

(5.5.1b)


| | `(\|[c,f]\|)=reduce(c,f)`<br>catamorphism: arrows of the form `(\|f\|)` are called catamorphisms, and these two examples reveal the notion to be a familiar idea in abstract clothing | |
|---|---|---|
| 1 | **part** | **Nat** | **[A]** |
| 2 | datatype | `Nat::=zero\|succ Nat` | `[A]::=nil\|cons(A,[A])` |
| 3 | base functor `F` | `F(X)=1+X` | `F(X)=1+A×X` |
| 4 | initial algebra `α` | `α=[zero,succ]`<br>`: 1+Nat→Nat` | `α=[nil,cons]`<br>`: 1+A×[A]→[A]` |
| 5 | the fold, pointwise | `(\|[c,f]\|)(zero)=c`<br>`(\|[c,f]\|)(succ(n))=f((\|[c,f]\|)(n))` | `(\|[c,f]\|)(nil)=c`<br>`(\|[c,f]\|)(cons(a,x))=f(a,(\|[c,f]\|)(x))` |

### §5.5.2. (|R|) = (|$\frac{F(\ni)\ R}{\ni}$|) ∋ — folding with R is a fold of maps into sets, then ∋

(5.5.2a)





(5.12)




the last two rows at `X:=(|R|)`:

$$\alpha\ X = F(X)\ R \Leftrightarrow \frac{X}{\ni} = (\!|\frac{F(\ni)\ R}{\ni}|\!) \qquad (5.5.2b)$$

in a tabular allegory, with $F$ a relator and $\alpha : F(T) \to T$ its initial algebra: a relation $X$ out of $T$ satisfies the fold equation $\alpha X = F(X) R$ of $R$ exactly when $\frac{X}{\ni}$ is the fold of the map $\frac{F(\ni) R}{\ni}$




| | | |
|---|---|---|
| 1 | $\frac{X}{\ni}$ | $\alpha$ iso; $\alpha X = F(X) R$ |
| 2 | $= \frac{\alpha^\circ\ F(X)\ R}{\ni}$ | $\alpha^\circ$ is a map because $\alpha$ is an iso, so it leaves $\Lambda$: $\frac{\alpha^\circ F(X) R}{\ni} = \alpha^\circ \frac{F(X) R}{\ni}$ — `Map(f)` $\Rightarrow \frac{f\ R}{\ni} = f\ \frac{R}{\ni}$ |
| 3 | $= \alpha^\circ\ \frac{F(X)\ R}{\ni}$ | $X = \frac{X}{\ni}\ni$ — $\frac{R}{\ni}\ \ni = R$ |
| 4 | $= \alpha^\circ\ \frac{F(\frac{X}{\ni})\ \ni)\ R}{\ni}$ | $F(\frac{X}{\ni})\ni) = F(\frac{X}{\ni}) F(\ni)$ as $F$ is a functor, and $F(\frac{X}{\ni})$ is a map (a relator sends maps to maps), so it leaves $\Lambda$ — $\triangleq$ relator, `Map(f)` $\Rightarrow \frac{f\ R}{\ni} = f\ \frac{R}{\ni}$ |
| 5 | $= \alpha^\circ\ F(\frac{X}{\ni})\ \frac{F(\ni)\ R}{\ni}$ | fold uniqueness, $\frac{F(\ni) R}{\ni}$ being a map — `(h : f → g) ≜ f h = F(h) g , Map(f)` $\Rightarrow$ `α (⦇f⦈) = F(⦇f⦈) f` |
| 6 | $= (\!\|\frac{F(\ni)\ R}{\ni}\|\!)$ | |

## §5.6. Combinatorial functions


(5.6a)

| | definition | type | note |
|---|---|---|---|
| 1 | `[A]::=nil\|cons(A,[A]) list(A) = [A]` | $\mathcal{A}\to\mathcal{A}$ | The list type, under the short name it keeps. |
| 2 | `R′ = (\|[[],(R × 𝟙) cons]\|)` | `[A]→[B]` | The relator's action on `R : A→B`: one `R` per element, the shape untouched. |
| 3 | `subseq = (\|[[],cons ∪ π₂]\|)` | `[A]→[A]` | `xs subseq ys`: `ys` is `xs` with elements dropped — `cons` keeps the head, `π₂` drops it. |
| 4 | `prefix = (\|[[],cons ∪ ⊸ nil]\|)`<br>`prefix = cat° π₁ =init*` | `[A]→[A]` | `ys` is an initial segment of `xs`; the first `nil` is where it stops early. `init≜snoc° π₁`. |
| 5 | `suffix = cat° π₂ =tail*` | `[A]→[A]` | The dual, `tail≜cons° π₂`; as a reduce it needs snoc-lists. |
| 6 | `partition = concat°` | `[A]→[[A]]` | This `cat` is restricted to `[A]⁺×[A]→[A]`, so `ys` is a list of non-empty segments of `xs`. |
| 7 | `concat = (\|[[],cat]\|)` | `[[A]]→[A]` | Joins the segments back up, which is why its converse splits a list. |
| 8 | `inits` | `[A]→[[A]]` | Implements $\frac{\texttt{prefix}}{\ni}$, listing the prefixes by increasing length. |
| 9 | `tails` | `[A]→[[A]]` | Implements $\frac{\texttt{suffix}}{\ni}$ by decreasing length — the opposite order. |
| 10 | `cpp`, `cpl`, `cpr` | `[A]×[B]→[A×B]`<br>`[A]×B→[A×B]`<br>`A×[B]→[A×B]` | Every pair `(a,b)` with `a` from the first list and `b` from the second; `cpl`, `cpr` keep one side a single element. |
| 11 | `cpp setify = (setify × setify)` $\frac{\ni\times\ni}{\ni}$<br>`cpl setify = (setify × 𝟙)` $\frac{\ni\times\mathbb{1}}{\ni}$<br>`cpr setify = (𝟙 × setify)` $\frac{\mathbb{1}\times\ni}{\ni}$ | `[A]×[B]→P(A×B)` | Forgetting the order with `setify`, `cpp` is the transpose of $\ni\times\ni$. |
| 12 | `cp(F)` $\triangleq \frac{\texttt{F}(\ni)}{\ni}$ | `F(PA)→PFA` | `cp(F)`, the transpose of a relator's action on $\ni$; `cpp` implements it at `F(A)=A×A`. |
| 13 | `cp(list) = (\|`$\frac{[[],(\ni\times\ni)\ \texttt{cons}]}{\ni}$`\|)`<br>$\frac{[[],(\ni\times\ni)\ \texttt{cons}]}{\ni}$ `= [[]` $\frac{\mathbb{1}}{\ni}$`,`$\frac{\ni\times\ni}{\ni}$<br>`E(cons)]` | `list(PA)→P(list(A))` | `cp(list)`: (5.12) `(\|R\|) = (\|`$\frac{\texttt{F}(\ni)\ \texttt{R}}{\ni}$`\|)` $\ni$ at $\ni'$=`(\|[nil,(∋×𝟙)cons]\|)`, then the algebra expanded. |
| 14 | `cplist = (\|[[] τ,cpp cons′]\|)` | `[[A]]→[[A]]` | `cp(list)` with every set a list: `cpp` in place of $\frac{\ni\times\ni}{\ni}$. |


**`glue concat ⊑ (𝟙 × concat) cons`** (5.6b)

putting **a** on the front of the first segment and flattening (**`glue concat`**) gives at most flattening the segments and putting **a** on the front of the result (**`(𝟙×concat) cons`**)

the starting composite




| | | |
|---|---|---|
| 1 | `glue concat` | definition of glue |
| 2 | `≜ (𝟙 × cons°) assocl cons × 𝟙 cons concat` | since `concat=⦇[nil,cat]⦈` |
| 3 | `= (𝟙 × cons°) assocl cons × 𝟙 (𝟙 × concat) cat` | naturality of `assocl` |
| 4 | `= (𝟙 × (cons° (𝟙 × concat))) assocl cons × 𝟙 cat` | since `concat=⦇[nil,cat]⦈` |




| | | |
|---|---|---|
| 5 | `⊑ (𝟙 × concat) (𝟙 × cat°) assocl cons × 𝟙 cat` | since `(cons×𝟙) cat=assocr (𝟙×cat) cons` |
| 6 | `= (𝟙 × concat) (𝟙 × cat°) assocl assocr (𝟙 × cat) cons` | since `assocl assocr=𝟙` and `cat° cat⊑𝟙` |
| 7 | `⊑ (𝟙 × concat) cons` | |

## §5.6.1. $\frac{\text{subseq}}{\ni}$ = ⦇[[] $\frac{𝟙}{\ni}$,⟨$\frac{𝟙 \times \ni}{\ni}$ E(cons),π₂⟩ cup]⦈ — the set of subsequences is a fold of maps into sets











(5.6.1a)

`cup` $\triangleq \frac{(\pi_1\ \ni) \cup (\pi_2\ \ni)}{\ni}$ — `cup` unions two sets.


`cup`$\triangleq \frac{\pi_1 \ni \cup \pi_2 \ni}{\ni}$ `: PA×PA→PA`

$$\frac{F(\ni)\ [[],cons \cup \pi_2]}{\ni} = [[]\ \frac{\mathbb{1}}{\ni}, \frac{(\mathbb{1} \times \ni)\ (cons \cup \pi_2)}{\ni}] \qquad (5.6.1b)$$

the set of lists the algebra builds is, from nothing, just **nil**, and from a head and a set of tails, every tail in the set with the head put on or left off — (5.12) $(\!|R|\!) = (\!|\frac{F(\ni)\ R}{\ni}|\!)\ \ni$ at **subseq=(\[nil,cons ∪ π₂\])**, **subseq = (\[\[\],cons ∪ π₂\])** .











| **circuit** — the fork is F([A])=1+A×[A]: nil above, the pair below | **Hinze–Marsden** |
|---|---|
|  $\frac{F(\ni)\ [[],cons \cup \pi_2]}{\ni}$ |  the $\pi_2$ operand of cons ∪ $\pi_2$ under the $\mathbb{1}$×∋ summand of F(∋), i.e. $(\mathbb{1}\times\ni)\pi_2$ |
| =  $\frac{(\mathbb{1} + (\mathbb{1} \times \ni))\ [[],cons \cup \pi_2]}{\ni}$<br>F(X)=1+A×X — list(A) = [A] |  the same operand under $\mathbb{1}$+$\mathbb{1}$×∋, whose $\mathbb{1}$×∋ summand it sits in |
| =  $\frac{[[],(\mathbb{1} \times \ni)\ (cons \cup \pi_2)]}{\ni}$<br>R+S≜[Rl,Sr], l[R,S]=R, r[R,S]=S — [R,S] ≜ (l° R) ∪ (r° S) , l [R,S] = R , r [R,S] = S , l T = R; r T = S<br>⇒ T = [R,S] |  the $\pi_2$ operand of the second arm $(\mathbb{1}\times\ni)(cons \cup \pi_2)$ |
| =  $[\frac{[]}{\ni}, \frac{(\mathbb{1} \times \ni)\ (cons \cup \pi_2)}{\ni}]$<br>[R,S] = $[\frac{R}{\ni}, \frac{S}{\ni}]$ ∋ at T:=[nil,(1×∋)(cons ∪ π₂)] |  the $\pi_2$ operand under its $\frac{\mathbb{1}}{\ni}$, the arm $(\mathbb{1} \times \ni)\ \pi_2 = \pi_2\ \ni$ rewrites |
| =  $[[]\ \frac{\mathbb{1}}{\ni}, \frac{(\mathbb{1} \times \ni)\ (cons \cup \pi_2)}{\ni}]$<br>Map(f); $\mathbb{1}\Box = \ni\Box$<br>⇒ $\frac{f}{\ni} = f\ \frac{\mathbb{1}}{\ni}$ , $\frac{f}{\ni} = f\ \frac{\mathbb{1}}{\ni}$ for f a map, at f:=nil |  the same operand; the two rows differ only in the nil arm |

(5.6.1c)




$\frac{(\mathbb{1} \times \ni)\ (\mathsf{cons} \cup \pi_2)}{\ni} = \langle \frac{\mathbb{1} \times \ni}{\ni}\ \mathsf{E(cons)}, \pi_2 \rangle\ \mathsf{cup}$ **(5.6.1d)**

power transpose of join: the power transpose of the join of two relations is $\langle \frac{R}{\ni}, \frac{S}{\ni} \rangle$ cup, where cup is the function that returns the union of two sets

| circuit | Hinze–Marsden |
|---|---|
|  $\frac{(\mathbb{1} \times \ni)\ (\mathsf{cons} \cup \pi_2)}{\ni}$ $\frac{\mathsf{F}(\ni)\ [[], \mathsf{cons} \cup \pi_2]}{\ni} = [[]\ \frac{\mathbb{1}}{\ni}, \frac{(\mathbb{1} \times \ni)\ (\mathsf{cons} \cup \pi_2)}{\ni}]$ 's second branch |  the cons operand of $\mathsf{cons} \cup \pi_2$ |
| =  $\frac{((\mathbb{1} \times \ni)\ \mathsf{cons}) \cup ((\mathbb{1} \times \ni)\ \pi_2)}{\ni}$ $\mathsf{T}(X_1 \cup X_2) = \mathsf{T}X_1 \cup \mathsf{T}X_2$ — $(S \cup T)\ R = (S\ R) \cup (T\ R)$, $R\ (S \cup T) = (R\ S) \cup (R\ T)$, $R \cap (S \cup T) = R \cap S \cup R \cap T$, $(R \cup S)^\circ = S^\circ \cup R^\circ$ |  the $\pi_2$ operand of $(\mathbb{1} \times \ni)\mathsf{cons} \cup (\mathbb{1} \times \ni)\pi_2$ |
| =  $\frac{((\mathbb{1} \times \ni)\ \mathsf{cons}) \cup (\pi_2\ \ni)}{\ni}$ $(\mathbb{1} \times \ni)\pi_2 = \pi_2 \ni$ — $(R \times S)\ \pi_1 \sqsubseteq \pi_1\ R \wedge (R \times S)\ \pi_2 \sqsubseteq \pi_2\ S$ at $\pi_2$, an equality because $\mathbb{1}$ is entire |  the $\pi_2$ operand of $(\mathbb{1} \times \ni)\mathsf{cons} \cup \pi_2 \ni$ |
| =  $\langle \frac{(\mathbb{1} \times \ni)\ \mathsf{cons}}{\ni}, \frac{\pi_2\ \ni}{\ni} \rangle$ cup $\frac{R \cup S}{\ni} = \langle \frac{R}{\ni}, \frac{S}{\ni} \rangle$ cup — $\triangleq$ cup |  the cons operand under its $\frac{\mathbb{1}}{\ni}$ |
| =  $\langle \frac{\mathbb{1} \times \ni}{\ni}\ \mathsf{E(cons)}, \pi_2 \rangle$ cup $\frac{S}{\ni}\ \mathsf{E}(R) = \frac{S\ R}{\ni}$, absorption $\frac{S}{\ni}\ \mathsf{E}(R) = \frac{SR}{\ni}$ at $S := \mathbb{1} \times \ni$, $R := \mathsf{cons}$; fusion and $\frac{\ni}{\ni} = \mathbb{1}$ on the $\pi_2$ operand |  the $\pi_2$ operand, bare $\pi_2$ |

**(5.6.1e)**




$[\frac{\mathsf{nil}}{\ni}, \langle \frac{\mathbb{1} \times \ni}{\ni}\ \mathsf{E(cons)}, \pi_2 \rangle\ \mathsf{cup}]$


which writes Pcons; cons is a map, and there $\mathsf{P(cons)} = \mathsf{E(cons)}$ — $\mathsf{Map(f)} \Rightarrow \mathsf{P(f)} = \mathsf{E(f)}$.

## §5.7. Lax natural transformations (LaT)











(5.7a)

φ : G⇒F is **lax at** R : A↛B when G(R)φ$_B$⊑φ$_A$F(R); it is a **lax natural transformation** (LaT) when lax at every R.

(5.7b)




(5.7c)

| | closed under | commutative diagram | string diagram |
|---|---|---|---|
| 1 | composition<br>ψφ |  H(R)ψB⊑ψAG(R) and G(R)φB⊑φAF(R) give H(R)(ψBφB)⊑(ψAφA)F(R) |  |
| 2 | horizontal composition<br>χ∘φ |  φ : G⇒F with G,F : 𝒞→𝒟 and χ : L⇒K with L,K : 𝒟→ℰ give χ∘φ : L∘G⇒K∘F, the family A ↦ χGAK(φA)<br>L(G(R))χGB⊑χGAK(G(R)) is χ lax at G(R); then K(G(R)φB)⊑K(φAF(R)) is K applied to φ's own inequation; χ:=𝟙K gives K(φ) : K∘G⇒K∘F, K composed on the outside; φ:=𝟙G gives χG : L∘G⇒K∘G, G composed on the inside<br>two candidates, χGAK(φA) and L(φA)χFA, ordered by ⊑; this row is the first |  |
| 3 | union<br>φ ∪ ψ |  G(R)φB⊑φAF(R) and G(R)ψB⊑ψAF(R) give G(R)(φB ∪ ψB)⊑(φA ∪ ψA)F(R) |  |
| 4 | a relator K<br>K(φ) |  G(R)φB⊑φAF(R) gives K(G(R))K(φB)⊑K(φA)K(F(R)) | |
| 5 | product<br>φ×ψ |  φ : G⇒F and ψ : G'⇒F' give φ×ψ : G×G'⇒F×F'<br>(R×S)(U×V)=(RU)×(SV) and monotonicity in both slots — the row above's K applied to the inequation, run on a bifunctor; the fork is the derived case ⟨φ,ψ⟩=◁(φ×ψ), and its ONE cost is the lax copy law R◁⊑◁(R×R) — R ◁ ≤ ◁ (R ⊗ R) , R ⊸ ≤ ⊸ |  |
| 6 | coproduct<br>φ+ψ |  φ : G⇒F and ψ : G'⇒F' give φ+ψ : G+G'⇒F+F'<br>(R+S)(U+V)=(RU)+(SV) and monotonicity in both slots; the co-fork is the derived case [φ,ψ]=(φ+ψ)▿, and ▿ costs nothing |  |
| 7 | meet — **fails**<br>φ∩ψ | the step it would need is (φAF(R))∩(ψAF(R))⊑(φ∩ψ)AF(R), the wrong direction of R (S ∩ T) ⊑ (R S) ∩ (R T)<br>a counterexample: aa = (0,1); bb = (0,0); (R × R)(aa,bb); b₁ = {0}; b₁ = E(π₁ ∩ π₂){bb}; a₁ = ∅; a₁ = E(π₁ ∩ π₂){aa}; b₂ = ∅; b₂ = E(R)(a₁)<br>⇒ ¬((R × R) (π₁ ∩ π₂) ⊑ (π₁ ∩ π₂) R) | |
| 8 | Each row is the general slide RAX⊑X'RB and RBY⊑Y'RC give RA(XY)⊑(X'Y')RC at RA,RB:=G(R),F(R) and X,X':=φB,φA, quantified over R; at X'=X with RA,RB endorelations it is the monotonicity reading instead — the ∀R sits outside the law, and is the only difference | | |

## §5.7.1. meet is not closed in LaT

(5.7.1a)

**counterexample — φ,ψ : G⇒F lax natural does NOT give φ∩ψ lax natural**




A=B≜{0,1}, R≜{(0,0),(1,0)}, φ≜π₁∩π₂ : Δ⇒Id


## §5.7.2. Two stacked towers

(5.7.2a)

| | | lower — inside ONE allegory | upper — between allegories |
|---|---|---|---|
| 1 | 0-cell | an object A | an allegory $\mathcal{C}$ — **a whole lower tower** |
| 2 | 1-cell | a relation R : A↛B | a relator F : $\mathcal{C}$↛$\mathcal{D}$ |
| 3 | 2-cell | R⊑S | a LaT φ : G⇒F ≙ lax |
| 4 | order | R⊑S | φ⊑ψ componentwise |
| 5 | union | R ∪ S | φ ∪ ψ, **survives** lax(φ); lax(ψ) ⇒ G(R) (φB ∪ ψB) ⊑ (φA ∪ ψA) F(R) |
| 6 | product | R×S ≙ × | φ×ψ, **survives**; a TENSOR, not a categorical product; SYMMETRIC ⟨R,S⟩ π₁ = dom(S) R , ⟨R,S⟩ π₂ = dom(R) S lax(φ); lax(ψ) ⇒ (G(R) × G'(R)) (φB × ψB) ⊑ (φA × ψA) (F(R) × F'(R)) |
| 7 | coproduct | R+S | φ+ψ, **survives**; a BIPRODUCT lax(φ); lax(ψ) ⇒ (G(R) + G'(R)) (φB + ψB) ⊑ (φA + ψA) (F(R) + F'(R)) |
| 8 | meet | R∩S | φ∩ψ componentwise, **fails** aa = (0,1); bb = (0,0); (R × R)(aa,bb); b₁ = {0}; b₁ = E(π₁ ∩ π₂){bb}; a₁ = ∅; a₁ = E(π₁ ∩ π₂){aa}; b₂ = ∅; b₂ = E(R)(a₁) ⇒ ¬((R × R) (π₁ ∩ π₂) ⊑ (π₁ ∩ π₂) R) |
| 9 | converse | R° | φ°, **fails**, oplax: φA°G(R)⊑F(R)φB° |
| 10 | zero object | z with 𝟙 z=𝟘 | the constant relator at such a z, initial and terminal |

## §5.7.3. R⊑S is a special case of LaT

(5.7.3a)




G≜const A, F≜const B — the relators X↦A and X↦B, each sending every arrow to 𝟙 ≙ lax

with $\mathcal{C}$ two objects and one non-identity arrow X→Y, a LaT const A⇒const B is the pair φX,φY : A↛B with φY⊑φX — the datum R⊑S

not every LaT is constant: ∋ : P⇒Id X ⊑ P(R) ⇔ X ∋ ⊑ ∋ R ∧ X° ∋ ⊑ ∋ R° π₂ : (A×−)⇒Id (𝟙 × ∋) π₂ = π₂ ∋ ◁ : Id⇒Δ R ◁ ≤ ◁ (R ⊗ R) , R ⊸ ≤ ⊸