# Companion to Bird & de Moor, Algebra of Programming

# §8. Thinning Algorithms

## §8.1. Thinning

(8.1)

`thin(Q) ≜ ⊇ ∩ (∈ \ (Q° ∈))` — `thin(Q)` takes a set `ys` to a subset `xs` that keeps a `Q`-lower bound of every `a∈ys`.


`thin(≤) ys thin(≤) xs⇔xs⊆ys∧(∀a∈ys. ∃b∈xs. b≤a).`

(8.1a)


| | the law | what it says |
|---|---|---|
| 1 | `X ⊑ S⫽∋ thin(Q) ⇔ X ∋ ⊑ S ∧ S° X ⊑ Q° ∈` | `S` is the whole algebra: it produces every candidate that `thin(Q)` thins. Everything kept is an `S`-value, and every `S`-value has a `Q`-lower bound among the kept ones |
| 2 | `thin(Q) ∋ ⊑ ∋` | everything a thinning keeps was in the set |
| 3 | `thin(Q)° ∋ ⊑ ∋ Q` | every element of the set has a `Q`-lower bound among the kept ones |
| 4 | `Q ⊑ R ⇒ thin(Q) ⊑ thin(R)` | the fewer pairs `Q` relates, the fewer subsets count as thinnings |
| 5 | `𝟙 ⊑ Q ⇒ 𝟙 ⊑ thin(Q)`<br>`Q² ⊑ Q ⇒ thin(Q)² ⊑ thin(Q)` | keeping everything is always a legal thinning |
| 6 | `Q ⊑ R ∧ 𝟙 ⊑ Q ∧ R² ⊑ R ⇒ est(R) = thin(Q) est(R) 𝟙 ⊑ Q`<br>`⇒ est(R) ⊑ thin(Q) est(R)` | **thin-introduction**: thinning first cannot lose an `R`-minimum |
| 7 | `thin(Q)⊒est(Q) 𝟙⫽∋` (8.2) — (8.2) `est(Q) 𝟙⫽∋ ⊑ thin(Q)` | **thin-elimination**: keeping one element is a thinning, but its domain is the sets `est(Q)` is defined on |
| 8 | `S⫽∋ thin(Q)⊒ S⫽∋ est(R) 𝟙⫽∋`<br>(8.3), `R∩(S°S)⊑Q` — thin-elimination variant | the usable variant: `R` need only refine `Q` between values `S` gives one argument |
| 9 | `P(thin(Q)) union ⊑ union thin(Q)` (8.4) — (8.4)<br>`P(thin(Q)) union ⊑ union thin(Q)` | thinning each member set is a thinning of the union |

### §8.1.1. `X ⊑ S⫽∋ thin(Q) ⇔ X ∋ ⊑ S ∧ S° X ⊑ Q° ∈` — the definition of `S⫽∋ thin(Q)`

(8.1.1a)




(8.1.1b)





`X ⊑ S⫽∋ thin(Q) ⇔ X ∋ ⊑ S ∧ S° X ⊑ Q° ∈` at `X≜thin(Q)`, `S≜∋`: the left side is `thin(Q)⊑thin(Q)`, since `∋⫽∋=Λ(∋)=𝟙`

## §8.1.2. $Q \sqsubseteq R \wedge \mathbb{1} \sqsubseteq Q \wedge R^2 \sqsubseteq R \Rightarrow \mathrm{est}(R) = \mathrm{thin}(Q)\ \mathrm{est}(R)$ — thinning first, then taking the smallest, is the same as taking the smallest

### $\mathbb{1} \sqsubseteq Q \Rightarrow \mathrm{est}(R) \sqsubseteq \mathrm{thin}(Q)\ \mathrm{est}(R)$ (8.1.2a)


the $\sqsubseteq$ half: keeping everything is a thinning — $\mathbb{1} \sqsubseteq Q$




| | | |
|---|---|---|
| 1 | $\mathrm{est}(R)$ | $\mathbb{1} \sqsubseteq \mathrm{thin}(Q)$ — $\mathbb{1} \sqsubseteq Q \Rightarrow \mathbb{1} \sqsubseteq \mathrm{thin}(Q)$, $Q^2 \sqsubseteq Q \Rightarrow \mathrm{thin}(Q)^2 \sqsubseteq \mathrm{thin}(Q)$ |
| 2 | $\sqsubseteq \mathrm{thin}(Q)\ \mathrm{est}(R)$ | |

### $\mathrm{thin}(Q)\ \mathrm{est}(R) \sqsubseteq \ni$ (8.1.2b)


the $\sqsupseteq$ half, first condition of the UP of $\mathrm{est}$ at $X \triangleq \mathrm{thin}(Q)\ \mathrm{est}(R)$ — $X \sqsubseteq \mathrm{est}(R) \Leftrightarrow X \sqsubseteq \ni \wedge \in X \sqsubseteq R^\circ$




| | | |
|---|---|---|
| 1 | $\mathrm{thin}(Q)\ \mathrm{est}(R)$ | $R \cap S \sqsubseteq R$ |
| 2 | $\sqsubseteq \mathrm{thin}(Q) \ni$ | $\mathrm{thin}(Q) \ni \sqsubseteq \ni$ |
| 3 | $\sqsubseteq \ni$ | |

### $Q \sqsubseteq R \wedge R^2 \sqsubseteq R \Rightarrow \in \mathrm{thin}(Q)\ \mathrm{est}(R) \sqsubseteq R^\circ$ (8.1.2c)

the $\sqsupseteq$ half, second condition




| | | |
|---|---|---|
| 1 | $\in \mathrm{thin}(Q)\ \mathrm{est}(R)$ | $\in \mathrm{thin}(Q) \sqsubseteq Q^\circ\ \in$ |
| 2 | $\sqsubseteq Q^\circ \in \mathrm{est}(R)$ | $\in \mathrm{est}(R) \sqsubseteq R^\circ$ |
| 3 | $\sqsubseteq Q^\circ\ R^\circ$ | $Q \sqsubseteq R$ |
| 4 | $\sqsubseteq R^{\circ 2}$ | $R^2 \sqsubseteq R \Rightarrow R^{\circ 2} \sqsubseteq R^\circ$ |
| 5 | $\sqsubseteq R^\circ$ | |


### §8.1.3. Properties of thinning

**est(Q) $\frac{1}{\ni}$ ⊑ thin(Q)** (8.2)

the singleton holding a Q-least member of a set is a thinning of that set

**est(Q) $\frac{1}{\ni}$ ∋ ⊑ ∋**


every member of the singleton is a member of the set — ≜ **thin**, ∋/∋ half




| | | |
|---|---|---|
| 1 | est(Q) $\frac{1}{\ni}$ ∋ | $\frac{1}{\ni}$ ∋ = 𝟙 |
| 2 | = est(Q) | R ∩ S ⊑ R |
| 3 | ⊑ ∋ | |

**∈ est(Q) $\frac{1}{\ni}$ ⊑ Q° ∈**

the singleton's member stands in Q to every member of the set — ≜ **thin**, ∈\(Q°∈) half





| | | |
|---|---|---|
| 1 | ∈ est(Q) $\frac{1}{\ni}$ | ∈ est(R) ⊑ R° |
| 2 | ⊑ Q° $\frac{1}{\ni}$ | $\frac{1}{\ni}$ ⊑ ∈ |
| 3 | ⊑ Q° ∈ | |

$$\mathtt{R} \cap (\mathtt{S}^\circ\ \mathtt{S}) \sqsubseteq \mathtt{Q} \Rightarrow \tfrac{\mathtt{S}}{\ni}\ \mathtt{est(R)}\ \tfrac{\mathbb{1}}{\ni} \sqsubseteq \tfrac{\mathtt{S}}{\ni}\ \mathtt{thin(Q)} \tag{8.3}$$

$$\tfrac{\mathtt{S}}{\ni}\ \mathtt{est(R)}\ \tfrac{\mathbb{1}}{\ni} \ni \sqsubseteq \mathtt{S}$$


every member of the singleton is a value S returns — $\mathtt{X} \sqsubseteq \tfrac{\mathtt{S}}{\ni}\ \mathtt{thin(Q)} \Leftrightarrow \mathtt{X} \ni \sqsubseteq \mathtt{S} \wedge \mathtt{S}^\circ\ \mathtt{X} \sqsubseteq \mathtt{Q}^\circ \in$, first condition




| | | |
|---|---|---|
| 1 | $\tfrac{\mathtt{S}}{\ni}\ \mathtt{est(R)}\ \tfrac{\mathbb{1}}{\ni} \ni$ | $\tfrac{\mathbb{1}}{\ni} \ni = \mathbb{1}$ |
| 2 | $= \tfrac{\mathtt{S}}{\ni}\ \mathtt{est(R)}$ | $\mathtt{R} \cap \mathtt{S} \sqsubseteq \mathtt{R}$ |
| 3 | $\sqsubseteq \tfrac{\mathtt{S}}{\ni} \ni$ | $\tfrac{\mathtt{R}}{\ni} \ni = \mathtt{R}$ |
| 4 | $= \mathtt{S}$ | |

$$\mathtt{R} \cap (\mathtt{S}^\circ\ \mathtt{S}) \sqsubseteq \mathtt{Q} \Rightarrow \mathtt{S}^\circ\ \tfrac{\mathtt{S}}{\ni}\ \mathtt{est(R)}\ \tfrac{\mathbb{1}}{\ni} \sqsubseteq \mathtt{Q}^\circ \in$$

the singleton's member stands in Q to every value S returns at the same argument — $\mathtt{X} \sqsubseteq \tfrac{\mathtt{S}}{\ni}\ \mathtt{thin(Q)} \Leftrightarrow \mathtt{X} \ni \sqsubseteq \mathtt{S} \wedge \mathtt{S}^\circ\ \mathtt{X} \sqsubseteq \mathtt{Q}^\circ \in$, second condition





| | | |
|---|---|---|
| 1 | $\mathtt{S}^\circ\ \tfrac{\mathtt{S}}{\ni}\ \mathtt{est(R)}\ \tfrac{\mathbb{1}}{\ni}$ | $\tfrac{\mathtt{S}}{\ni}\ \mathtt{est(R} \cap (\mathtt{S}^\circ\ \mathtt{S})) = \tfrac{\mathtt{S}}{\ni}\ \mathtt{est(R)}$ |
| 2 | $= \mathtt{S}^\circ\ \tfrac{\mathtt{S}}{\ni}\ \mathtt{est(R} \cap (\mathtt{S}^\circ\ \mathtt{S}))\ \tfrac{\mathbb{1}}{\ni}$ | $\mathtt{T}^\circ\ \tfrac{\mathtt{T}}{\ni} \sqsubseteq \in$ |
| 3 | $\sqsubseteq \in \mathtt{est(R} \cap (\mathtt{S}^\circ\ \mathtt{S}))\ \tfrac{\mathbb{1}}{\ni}$ | $\in \mathtt{est(R)} \sqsubseteq \mathtt{R}^\circ$ |
| 4 | $\sqsubseteq (\mathtt{R} \cap (\mathtt{S}^\circ\ \mathtt{S}))^\circ\ \tfrac{\mathbb{1}}{\ni}$ | $\mathtt{R} \cap (\mathtt{S}^\circ\ \mathtt{S}) \sqsubseteq \mathtt{Q}$ |
| 5 | $\sqsubseteq \mathtt{Q}^\circ\ \tfrac{\mathbb{1}}{\ni}$ | $\tfrac{\mathbb{1}}{\ni} \sqsubseteq \in$ |
| 6 | $\sqsubseteq \mathtt{Q}^\circ \in$ | |

**preorder(Q) ∧ S Pres Q ⇒ (|$\frac{F(∋)\ S}{∋}$ thin(Q)|) ⊑ $\frac{(|S|)}{∋}$ thin(Q)** Theorem 8.1

thinning at every step of the reduce is a thinning of the whole candidate set

**(|$\frac{F(∋)\ S}{∋}$ thin(Q)|) ∋ ⊑ (|S|)**


everything the thinning fold keeps is a value of the plain fold — **X ⊑ $\frac{S}{∋}$ thin(Q) ⇔ X ∋ ⊑ S ∧ S° X ⊑ Q° ∈** , first condition, by fusion from the chain below




| | | |
|---|---|---|
| 1 | $\frac{F(∋)\ S}{∋}$ thin(Q) ∋ | |
| 2 | = $\frac{F(∋)\ S}{∋}$ thin(Q) ∋ | thin(Q) ∋ ⊑ ∋ |
| 3 | ⊑ $\frac{F(∋)\ S}{∋}$ ∋ | $\frac{R}{∋}$ ∋ = R |
| 4 | = F(∋) S | |

**preorder(Q) ∧ S Pres Q ⇒ (|S|)° (|$\frac{F(∋)\ S}{∋}$ thin(Q)|) ⊑ Q° ∈**

every value of the plain fold is Q-above one the thinning fold keeps — **X ⊑ $\frac{S}{∋}$ thin(Q) ⇔ X ∋ ⊑ S ∧ S° X ⊑ Q° ∈** , second condition, by hylomorphism theorem from the chain below





| | | |
|---|---|---|
| 1 | S° F(Q° ∈) $\frac{F(∋)\ S}{∋}$ thin(Q) | |
| 2 | = S° F(Q°) F(∈) $\frac{F(∋)\ S}{∋}$ thin(Q) | S Pres Q<br>⇒ S° F(Q°) ⊑ Q° S° |
| 3 | ⊑ Q° S° F(∈) $\frac{F(∋)\ S}{∋}$ thin(Q) | S° F(∈) $\frac{F(∋)\ S}{∋}$ ⊑ ∈ |
| 4 | ⊑ Q° ∈ thin(Q) | ∈ thin(Q) ⊑ Q° ∈ |
| 5 | ⊑ Q°² ∈ | |
| 6 | ⊑ Q° ∈ | |

(8.1.3a)

| | step | type | example | what it does |
|---|---|---|---|---|
| 1 | S:F(A)→A is 8.1's algebra; example F(X)=V+V×X, S=[τ,cons], candidate a=cons(v,p) | | | |
| 2 | S° | A→FA | cons(v,p) ↦ r(v,p) | takes a apart into the input of its last step |
| 3 | F(Q°∈) | FA→F(PA) | r(v,p) ↦ r(v,ps), some p'∈ps with p' Q p | replaces each recursive component by a set holding a Q-no-worse one; v stays |
| 4 | $\frac{F(∋)S}{∋}$ | F(PA)→PA | r(v,ps) ↦ {cons(v,t) \| t∈ps} | picks one element from each set, combines by S, collects every result |
| 5 | thin(Q) | PA→PA | {cons(v,t) \| t∈ps} ↦ ys | keeps a subset; every dropped element is Q-beaten by a kept one |
| 6 | ⊑ Q°∈ | A→PA | ys holds y with y Q cons(v,p') Q cons(v,p) = a | the thinned set still holds an element Q-no-worse than a (S monotonic on Q, Q transitive) |

**Q ⊑ R ∧ preorder(Q) ∧ preorder(R) ∧ S Pres Q ⇒ (⦇F(∋) S / ∋ thin(Q)⦈ est(R) ⊑ ⦇S⦈ / ∋ est(R)** Corollary 8.1

the thinning fold refines the optimisation problem itself




(1) (2) (3)


| | | |
|---|---|---|
| 1 | ⦇F(∋) S / ∋ thin(Q)⦈ est(R) | Theorem 8.1 preorder(Q) ∧ S Pres Q ⇒ ⦇F(∋) S / ∋ thin(Q)⦈ ⊑ ⦇S⦈ / ∋ thin(Q) |
| 2 | ⊑ ⦇S⦈ / ∋ thin(Q) est(R) | |
| 3 | = ⦇S⦈ / ∋ est(R) | |

**P(thin(Q)) union ⊑ union thin(Q)** (8.4)

thinning each member set, then taking the union, is a thinning of the union

**P(thin(Q)) union ∋ ⊑ ∋ ∋**

every member of the result is a member of a member set — **X ⊑ S / ∋ thin(Q) ⇔ X ∋ ⊑ S ∧ S° X ⊑ Q° ∈** , first condition





(1) (2) (3) (4)

| | | |
|---|---|---|
| 1 | P(thin(Q)) union ∋ | union ∋ = ∋ ∋ |
| 2 | = P(thin(Q)) ∋ ∋ | P(R) ∋ ⊑ ∋ R |
| 3 | ⊑ ∋ thin(Q) ∋ | thin(Q) ∋ ⊑ ∋ |
| 4 | ⊑ ∋ ∋ | |

**(∋ ∋)° P(thin(Q)) union ⊑ Q° ∈**

every member of a member set has a **Q**-lower bound in the result — **X ⊑ S / ∋ thin(Q) ⇔ X ∋ ⊑ S ∧ S° X ⊑ Q° ∈** , second condition




(1) (2) (3) (4) (5) (6) (7) (8)

| | | |
|---|---|---|
| 1 | (∋ ∋)° P(thin(Q)) union | (R S)° = S° R° |
| 2 | = ∈ ∈ P(thin(Q)) union | ∈ P(R) ⊑ R ∈ |
| 3 | ⊑ ∈ thin(Q) ∈ union | ∈ thin(Q) ⊑ Q° ∈ |
| 4 | ⊑ Q° ∈ ∈ union | (R S)° = S° R° |
| 5 | = Q° (∋ ∋)° union | union ∋ = ∋ ∋ |
| 6 | = Q° (union ∋)° union | (R S)° = S° R° |
| 7 | = Q° ∈ union° union | union = E(∋) |
| 8 | ⊑ Q° ∈ | |

## §8.2. Paths in a layered network

(8.2a)

| | definition | type | meaning |
|---|---|---|---|
| 1 | `F(B,X) = B + (B × X)` | `𝐴×𝐴→𝐴` | a path is either one vertex a, or a vertex a followed by a path xs |
| 2 | `α = [τ,cons]` | `F(A,LA)→LA` | build a path: wrap one vertex as [a], or put a in front of xs |
| 3 | `wrapz ≜ ⟨τ,zero⟩` | `A→LA×ℕ` | a path of one vertex, no edge, cost 0 |
| 4 | `(a,(xs,n)) ↦ ([a]⧺xs,wt(a,head(xs)) + n)` | `A×(LA×ℕ)→LA×ℕ` | put a in front of the path; the cost adds the weight of the new edge a→head(xs) |
| 5 | `cost ≜ ⦇[wrapz,consw]⦈ π₂` | `LA→ℕ` | the cost of $[a_0,\ldots,a_n]$ is $wt(a_0,a_1)+\ldots+wt(a_{n-1},a_n)$ |
| 6 | `R ≜ cost ≤ cost°` | `LA→LA` | xs is cheaper than ys |
| 7 | `⦇F(∋,𝟙) α⦈ = L(∋)` | `LA→LB` | L(∋) relates a list of layers to every path that chooses one vertex from each layer |
| 8 | `minpath ⊑ L(∋)/∋ est(R)` | `L(PA)→LA` | the input $[x_0,\ldots,x_n]$ : L(PA) is a list of layers, each a set of vertices; a path chooses one vertex from each layer, and minpath returns a cheapest one |
| 9 | `Q ≜ R ∩ (head head°)` | `LA→LA` | like R, and the two paths also start at the same vertex: head(xs) = head(ys) |
| 10 | `a ↦ l(a)` | `B→B+C` | mark a value as the left alternative |
| 11 | `b ↦ r(b)` | `C→B+C` | mark a value as the right alternative |
| 12 | `cpl ≜ cp(𝟙 × A)` | `PB×A→P(B×A)` | pair every element of the set with the value beside it |
| 13 | `cpr ≜ cp(A × 𝟙)` | `A×PB→P(A×B)` | pair the value beside the set with every element of the set |
| 14 | `F(∋,𝟙)/∋ = [P(l),cpl P(r)]` | `F(PB,X)→PF(B,X)` | cpl transpose: from layer x and a set of paths ps, choose a vertex a ∈ x |
| 15 | `F(𝟙,∋)/∋ = [𝟙/∋ P(l),cpr P(r)]` | `F(B,PX)→PF(B,X)` | cpr transpose: from a vertex a and a set of paths ps, choose a tail xs ∈ ps |
| 16 | `step ≜ cpr P(cons) est(R)` | `A×P(LA)→LA` | put a in front of every path in ps and keep a cheapest one |

(8.2b)


| | the law | what it says |
|---|---|---|
| 1 | `F(∋,Q)α⊑F(∋,𝟙)αQ` | `F(∋,𝟙)α` is monotonic on `Q`; on `R` it is not, since the next edge can cost arbitrarily much |
| 2 | `S head⊑[𝟙,π₁]` `S≜F(𝟙,∋)α` | `S head` is simple, which gives `R∩(S°S)⊑Q`: between two paths `S` builds from one argument, equal cost and equal head already means `Q` |

## §8.2.1. Derivation

$$\left(\frac{F(\ni,1)}{\ni}\ P\left(\frac{F(1,\ni)\ \alpha}{\ni}\ \mathrm{est}(R)\right)\right)\ \mathrm{est}(R) \sqsubseteq \frac{\left(F(\ni,1)\ \alpha\right)}{\ni}\ \mathrm{est}(R) \tag{8.2.1a}$$

a least-cost path in a layered network, as a fold over the layers


- Why it is needed: `est(R)` keeps one cheapest `w` of the set `Λ(S)(x)`; `thin(Q)` needs every dropped `z` to be `Q`-beaten by a kept one. For `{w}` alone to be a thinning we need `w Q z` for every `z` in `Λ(S)(x)`.
- We have `w R z` (`w` is cheapest) and `w (S°S) z` (both are built by `S` from the same argument `x`); the hypothesis turns the two into `w Q z`: among candidates from one argument, cheaper already means `Q`-better.




| | | |
|---|---|---|
| 1 | $\left(\frac{F(\ni,1)}{\ni}\ P\left(\frac{F(1,\ni)\ \alpha}{\ni}\ \mathrm{est}(R)\right)\right)\ \mathrm{est}(R)$ | $\frac{F(\ni,1)}{\ni}\ P\left(\frac{F(1,\ni)\ \alpha}{\ni}\ \mathrm{est}(R)\right) \sqsubseteq \frac{F(\ni,\ni)\ \alpha}{\ni}\ \mathrm{thin}(Q)$ |
| 2 | $\sqsubseteq \left(\frac{F(\ni,\ni)\ \alpha}{\ni}\ \mathrm{thin}(Q)\right)\ \mathrm{est}(R)$ | $\left(\frac{F(\ni,\ni)\ \alpha}{\ni}\ \mathrm{thin}(Q)\right)\ \mathrm{est}(R) \sqsubseteq \frac{\left(F(\ni,1)\ \alpha\right)}{\ni}\ \mathrm{est}(R)$ |
| 3 | $\sqsubseteq \frac{\left(F(\ni,1)\ \alpha\right)}{\ni}\ \mathrm{est}(R)$ | |

$$\mathbf{S \triangleq F(\mathbb{1},\ni)\ \alpha\ ,\ R \cap (S^\circ\ S) \sqsubseteq Q \Rightarrow \frac{F(\ni,1)}{\ni}\ P\left(\frac{F(1,\ni)\ \alpha}{\ni}\ \mathrm{est}(R)\right) \sqsubseteq \frac{F(\ni,\ni)\ \alpha}{\ni}\ \mathrm{thin}(Q)} \tag{8.2.1b}$$

thinning the algebra of a layered network costs no more than taking the program's two cases




| | | |
|---|---|---|
| 1 | $\frac{F(\ni,1)}{\ni}\ P\left(\frac{F(1,\ni)\ \alpha}{\ni}\ \mathrm{est}(R)\right)$ | |
| 2 | $= \frac{F(\ni,1)}{\ni}\ P\left(\frac{F(1,\ni)\ \alpha}{\ni}\ \mathrm{est}(R)\right)$ | $P(\frac{\mathbb{1}}{\ni})\ E(\ni) = \mathbb{1}$ |
| 3 | $= \frac{F(\ni,1)}{\ni}\ P\left(\frac{F(1,\ni)\ \alpha}{\ni}\ \mathrm{est}(R)\ \frac{\mathbb{1}}{\ni}\right)\ E(\ni)$ | (8.3) $R \cap (S^\circ\ S) \sqsubseteq Q$ $\Rightarrow \frac{S}{\ni}\ \mathrm{est}(R)\ \frac{\mathbb{1}}{\ni} \sqsubseteq \frac{S}{\ni}\ \mathrm{thin}(Q)$ |
| 4 | $\sqsubseteq \frac{F(\ni,1)}{\ni}\ P\left(\frac{F(1,\ni)\ \alpha}{\ni}\right)\ P(\mathrm{thin}(Q))\ E(\ni)$ | (8.4) $P(\mathrm{thin}(Q))\ \mathrm{union} \sqsubseteq \mathrm{union}\ \mathrm{thin}(Q)$ |
| 5 | $\sqsubseteq \frac{F(\ni,1)}{\ni}\ P\left(\frac{F(1,\ni)\ \alpha}{\ni}\right)\ E(\ni)\ \mathrm{thin}(Q)$ | $\frac{\forall\ S}{\ni} = \frac{\forall}{\ni}\ P(\frac{S}{\ni})\ \mathrm{union}$ |
| 6 | $= \frac{F(\ni,1)\ F(1,\ni)\ \alpha}{\ni}\ \mathrm{thin}(Q)$ | $F(R,\mathbb{1})\ F(\mathbb{1},S) = F(R,S)$ |
| 7 | $= \frac{F(\ni,\ni)\ \alpha}{\ni}\ \mathrm{thin}(Q)$ | |

$= \mathrm{cp}(F)\ P(\alpha)\ \mathrm{est}(R) = [\tau,\mathrm{step}]$

at the layered network ($F(A,X)=A+A\times X$, $B$ the paths $V^+$, $\alpha=[\tau,\mathrm{cons}]$): $\frac{F(\mathbb{1},\ni)}{\ni}\ P(\alpha)\ \mathrm{est}(R)=[\tau,\mathrm{step}]$ — $\mathrm{step} \triangleq \mathrm{cpr}\ P(\mathrm{cons})\ \mathrm{est}(R)$

$= \frac{F(\ni,\mathbb{1})}{\ni}\ =\mathbb{1}+\mathrm{cpl}$ — $\frac{F(\ni,\mathbb{1})}{\ni}\ = [P(l),\mathrm{cpl}\ P(r)]$

(8.2.1c)

```
F(A,X)  =  A   +   A  ×  X
           |       |     |
           R       R     S
           ↓       ↓     ↓
F(A',X') =  A'  +   A' ×  X'
```

`u F(R,S) v` holds iff one of:

- `u`, `v` are both `inl` and `d R d'`: the leaf moves by `R`;

- `u`, `v` are both `inr` and `p₁ R q₁ ∧ p₂ S q₂`: the vertex moves by `R`, the rest by `S`.
- An `inl` never relates to an `inr`: `R+S≜[R inl, S inr]` returns to the summand it came from, and `F(𝟙)=𝟙` allows no crossing.
- `F(∃,∃)` relates `inr({a,b},{p,q})` to `inr(a,p)`, `inr(a,q)`, `inr(b,p)`, `inr(b,q)`, and `inl({a,b})` to `inl(a)`, `inl(b)`.

## §8.3. Implementing thin

(8.3a)

| | definition | type | meaning |
|---|---|---|---|
| 1 | (setify ∋)(xs,x) ⇔ x ∈ xs | [A]→PA | the set of a list's elements |
| 2 | cup ≜ $\frac{(\pi_1\ \ni)\ \cup\ (\pi_2\ \ni)}{\ni}$ | PA×PA→PA | the union of two sets |
| 3 | cp(F) ≜ $\frac{F(\ni)}{\ni}$ | F(PA)→PFA | every F-shaped value whose parts are chosen from the given sets |
| 4 | cpLFn(zer,x) = [], cpLFn(PolyC.one,u) = [u, ()], cpLFn(const(a),c) = [c], cpLFn(arg₁,a) = [a], cpLFn(arg₂,xs) = xs , cpLFn(l ⊕ a,l(u)) = inl′(cpLFn(l,u)), cpLFn(a ⊕ r,r(v)) = inr′(cpLFn(r,v)), cpLFn(l ⊗ r,(u,v)) = cppFn(cpLFn(l,u),cpLFn(r,v)) | relator(list(X))→ list(relator(X)) | by the shape of F: a constant or arg₁ is a one-element list, arg₂ the list itself, a sum lists its summand, a product pairs every element of one list with every element of the other |
| 5 | linear(zer) = true, linear(one) = true, linear(const(a)) = true, linear(arg₁) = true, linear(arg₂) = true, linear(l ⊕ r) = linear(l) ∧ linear(r), linear(l ⊗ r) = linear(l) ∧ linear(r) ∧ (¬ hasArg₂(l) ∨ ¬hasArg₂(r)) | P(PolyC(ι)) | no product in F has the argument on both sides |
| 6 | sort(⩽) ≜ setify° ordered(⩽) | PA→LA | read a set back as one of its ⩽-ordered listings |
| 7 | (a,[]) ↦ [a] , bump(Q)((a,[b]⧺xs),ys) ⇔ Q(a,b) ∧ ys = [a]⧺xs ∨ Q(b,a) ∧ ys = [b]⧺xs ∨ ¬Q(a,b) ∧ ¬Q(b,a) ∧ ys = [a]⧺[b]⧺xs | A×[A]→[A] | put a in front of a thinned list, dropping whichever of a and the old head the other beats |
| 8 | thinL(Q) ≜ (setify thin(Q) setify°) ∩ subseq | [A]→[A] | only drop elements, and on the set of the elements be a thinning by Q |
| 9 | T ⊑ thinL(Q) ⇔ T ⊑ subseq ∧ T setify ⊑ setify thin(Q) | | what a list implementation of thin(Q) must do: only drop elements, and thin the set |
| 10 | preorder(Q) ⇒ ⦏[nil,bump(Q)]⦐ ⊑ thinL(Q) | | an implementation: thin a list in one pass, bumping each element into the thinned rest |
| 11 | minL(Q) ≜ setify est(Q) | [A]→A | a Q-least element of the list |


### §8.3.1. Sorting sets

(8.3.1a)

| | the law | what it says |
|---|---|---|
| 1 | `preorder(Q) ∧ connected(Q) ⇒ bumpFold(Q)([a]⧺xs,ys) ⇔ (∃w. minL(Q)([a]⧺xs,w) ∧ ys = [w])` (8.5) | what thinning should come to when it can: one element |
| 2 | `sort(⩽) thinL(Q) ⊑ thin(Q) sort(⩽)` (8.6) — (8.6) `sort(⩽) thinL(Q) ⊑ thin(Q) sort(⩽)` | the thinning may run after the sort |
| 3 | `sort(⩽) minL(R) ⊑ est(R)` (8.7) | a minimum of the sorted list is a minimum of the set |
| 4 | `sort(f ⩽ f°) f′ ⊑ P(f) sort(⩽)` (8.8) | shunt a function through a sort |
| 5 | `Coreflexive(p) ⇒ sort(⩽) filter(p) ⊑ E(p) sort(⩽)` (8.9) `p : A → A` | filtering a sorted list sorts the restricted set |
| 6 | `preorder(⩽) ∧ connected(⩽) ⇒ (sort(⩽) × sort(⩽)) merge(⩽) ⊑ cup sort(⩽)` (8.10) | merging two sorted lists sorts their union |
| 7 | `F(sort(⩽)) cpL ⊑ cp(F) sort(F(⩽))` (8.11), `F(A,X)=1+A×X` | `cpL` is the list implementation of the cartesian product `cp(F)` |
| 8 | `linear(F) ⇒ relator(sort(⩽)) cpL(F,A,X) ⊑ cp(relator(F,A)) sort(relator(⩽))` (8.11), `F` polynomial and linear | the same for every linear polynomial `F` |

**`sort(⩽) thinL(Q) ⊑ thin(Q) sort(⩽)`** (8.6)


every list got by sorting the set and then thinning it by `Q` is also got by thinning the set by `Q` and then sorting.




| | | |
|---|---|---|
| 1 | `sort(⩽) thinL(Q)` | `sort(⩽) ≜ setify° ordered(⩽)` |
| 2 | `≜ setify° ordered thinL(Q)` | `ordered thinL(Q) ⊑ thinL(Q) ordered` |
| 3 | `⊑ setify° thinL(Q) ordered` | `setify° thinL(Q) ⊑ thin(Q) setify°` |
| 4 | `⊑ thin(Q) setify° ordered` | |
| 5 | `= thin(Q) sort(⩽)` | |

**Coreflexive(p) ∧ f Pres ⩽ ⇒ F(sort(⩽)) cpL f′ filter(p) ⊑ $\frac{\mathsf{F(∋)\ f\ p}}{\mathsf{∋}}$ sort(⩽)** Lemma 8.1

sorting each argument set (**F(sort(⩽))**), forming every combination of their elements (**cpL**), applying **f** to each (**f′**) and keeping those that pass **p** (**filter(p)**) gives one of the sorted lists of the set of all **f(u)** that pass **p**, with **u** drawn from the argument sets.




| | | |
|---|---|---|
| 1 | `F(sort(⩽)) cpL f′ filter(p)` | `F(sort(⩽)) cpL ⊑ cp(F) sort(F(⩽))` |
| 2 | `⊑ cp(F) sort(F(⩽)) f′ filter(p)` | `Map(f)` `⇒ f Pres R ⇔ F(R) ⊑ f R f°` |
| 3 | `⊑ cp(F) sort(f ⩽ f°) f′ filter(p)` | `sort(f ⩽ f°) f′ ⊑ P(f) sort(⩽)` |
| 4 | `⊑ cp(F) P(f) sort(⩽) filter(p)` | `Coreflexive(p)` `⇒ sort(⩽) filter(p) ⊑ E(p) sort(⩽)` |
| 5 | `⊑ cp(F) P(f) E(p) sort(⩽)` | `Map(f)` `⇒ P(f) = E(f)` |
| 6 | `=` $\frac{\mathsf{F(∋)\ f\ p}}{\mathsf{∋}}$ `sort(⩽)` | |

(8.3.1b)

At `F(A,X)=1+A×X`, `f(r(a,x))=a+x`, ⩽ is ≤, `p` passes the odd numbers, input `r(3,{4,1,2})`.

| | left side | what it does | result |
|---|---|---|---|
| 1 | input | an `r(a,xs)`, `xs` a set | `r(3,{4,1,2})` |
| 2 | `F(sort(⩽))` | sorts the set in the `X` place; `a` is untouched | `r(3,[1,2,4])` |
| 3 | `cpL` | pairs `a` with each element, in list order | `[r(3,1),r(3,2),r(3,4)]` |
| 4 | `f′` | `f` on each | `[4,5,7]` |
| 5 | `filter(p)` | keeps the odd ones, order kept | `[5,7]` |

| | right side | what it does | result |
|---|---|---|---|
| 1 | input | | `r(3,{4,1,2})` |
| 2 | `F(∋)` | relates `r(3,xs)` to each `r(3,x)` with `x∈xs` | `r(3,4)`, `r(3,1)`, `r(3,2)` |
| 3 | `f` | | 7, 4, 5 |
| 4 | `p` | only odd values pass | 7, 5 |
| 5 | `Λ(…)` | collects every result into one set | `{5,7}` |
| 6 | `sort(⩽)` | | `[5,7]` |

- ⊑: the left's `[5,7]` is one result of the right; with ties `sort(⩽)` has several orders.
- `f` preserving ⩽ is used at `f′`: `[1,2,4]` is sorted, so `[4,5,7]` is; `filter(p)` only drops elements. With `f(r(a,x))=a−x` the left gives `[1,−1]` after `p`, not sorted, so ⊑ fails.


### §8.3.2. Binary thinning

(8.3.2a)

**Binary thinning** data: `Q` a preorder with `Q⊑R` and both $f_1 p_1$, $f_2 p_2$ monotonic on `Q`; ⩽ a connected preorder with both $f_1$, $f_2$ monotonic on ⩽; `R` a preorder.

**Coreflexive(p₁) ∧ Coreflexive(p₂) ∧ Q ⊑ R ∧ preorder(Q) ∧ preorder(R) ∧ (f₁ p₁) Pres Q ∧ (f₂ p₂) Pres Q ∧ preorder(⩽) ∧ connected(⩽) ∧ f₁ Pres ⩽ ∧ f₂ Pres ⩽ ⇒ ⦇cpL ⟨f₁′ filter(p₁),f₂′ filter(p₂)⟩ merge(⩽) thinL(Q)⦈ minL(R) ⊑ $\frac{⦇(f_1\ p_1)\ ∪\ (f_2\ p_2)⦈}{∋}$ est(R)** Theorem 8.2

a fold on sorted lists of partial solutions, thinned at every step, refines the thinning specification — at binary thinning data.




(1) (2) (3) (4)

| | | |
|---|---|---|
| 1 | ⦇cpL ⟨f₁′ filter(p₁),f₂′ filter(p₂)⟩ merge(⩽) thinL(Q)⦈ minL(R) | (8.3.2c) Coreflexive(p₁) ∧ Coreflexive(p₂) ∧ preorder(⩽) ∧ connected(⩽) ∧ f₁ Pres ⩽ ∧ f₂ Pres ⩽ ⇒ F(sort(⩽)) cpL ⟨f₁′ filter(p₁),f₂′ filter(p₂)⟩ merge(⩽) thinL(Q) ⊑ $\frac{F(∋)\ ((f_1\ p_1)\ ∪\ (f_2\ p_2))}{∋}$ thin(Q) sort(⩽) |
| 2 | ⊑ ⦇$\frac{F(∋)\ ((f_1\ p_1)\ ∪\ (f_2\ p_2))}{∋}$ thin(Q)⦈ sort(⩽) minL(R) | sort(⩽) minL(R) ⊑ est(R) |
| 3 | ⊑ ⦇$\frac{F(∋)\ ((f_1\ p_1)\ ∪\ (f_2\ p_2))}{∋}$ thin(Q)⦈ est(R) | S₁ Pres Q ∧ S₂ Pres Q ⇒ F(Q) (S₁ ∪ S₂) ⊑ (S₁ ∪ S₂) Q |
| 4 | ⊑ $\frac{⦇(f_1\ p_1)\ ∪\ (f_2\ p_2)⦈}{∋}$ est(R) | |

(8.3.2b)


At F(A,X)=1+A×X, f₁(l())=f₂(l())=0, f₁(r(a,x))=x, f₂(r(a,x))=a+x, p₁ passes all, p₂ passes values ≤6, ⩽ is ≤, Q is =, R is ≥, input [3,3,1].

| | input | f₁′ filter(p₁) | f₂′ filter(p₂) | merge(⩽) | thinL(Q) |
|---|---|---|---|---|---|
| 1 | l() | [0] | [0] | [0,0] | [0] |
| 2 | r(1,[0]) | [0] | [1] | [0,1] | [0,1] |
| 3 | r(3,[0,1]) | [0,1] | [3,4] | [0,1,3,4] | [0,1,3,4] |
| 4 | r(3, [0,1,3,4]) | [0,1,3,4] | [3,4,6] | [0,1,3,3,4,4,6] | [0,1,3,4,6] |
| 5 | minL(R) | | | | 6 |

- merge(⩽) is one pass: both copies arrive ≤-sorted (fᵢ monotonic on ⩽, filter(pᵢ) only drops), so it only compares their two heads.
- thinL(Q) compares neighbours only; the list is ≤-sorted, so equal values are neighbours and one pass drops every repeat.


**Coreflexive(p₁) ∧ Coreflexive(p₂) ∧ preorder(⩽) ∧ connected(⩽) ∧ f₁ Pres ⩽ ∧ f₂ Pres ⩽ ⇒**
**F(sort(⩽)) cpL ⟨f₁′ filter(p₁),f₂′ filter(p₂)⟩ merge(⩽) thinL(Q) ⊑ $\frac{\mathsf{F(∋)\ ((f_1\ p_1)\ ∪\ (f_2\ p_2))}}{∋}$**
**thin(Q) sort(⩽)** (8.3.2c)

sorting the candidate set turns the thinning algebra into an algebra on sorted lists.





(1)

⊑




(2)


⊑




(3)


| | | |
|---|---|---|
| 1 | F(sort(⩽)) cpL ⟨f₁′ filter(p₁),f₂′ filter(p₂)⟩ merge(⩽) thinL(Q) | X ⟨R,S⟩ ⊑ ⟨X R,X S⟩ |
| 2 | ⊑ (F(sort(⩽)) cpL f₁′ filter(p₁),F(sort(⩽)) cpL f₂′ filter(p₂)) merge(⩽) thinL(Q) | Lemma 8.1 Coreflexive(p) ∧ f Pres ⩽ ⇒ F(sort(⩽)) cpL f′ filter(p) ⊑ $\frac{\mathsf{F(∋)\ f\ p}}{∋}$ sort(⩽) |
| 3 | ⊑ ⟨$\frac{F(∋)\ f_1\ p_1}{∋}$ sort(⩽),$\frac{F(∋)\ f_2\ p_2}{∋}$ sort(⩽)⟩ merge(⩽) thinL(Q) | ⟨X,Y⟩ (R × S) = ⟨X R,Y S⟩ |

=





(4)

⊑





(5)

=





(6)

=




(7)

⊑




(8)

| | | |
|---|---|---|
| 4 | = ⟨$\frac{F(∋)\ f_1\ p_1}{∋}$,$\frac{F(∋)\ f_2\ p_2}{∋}$⟩ (sort(⩽) × sort(⩽)) merge(⩽) thinL(Q) | preorder(⩽) ∧ connected(⩽) ⇒ (sort(⩽) × sort(⩽)) merge(⩽) ⊑ cup sort(⩽) |
| 5 | ⊑ ⟨$\frac{F(∋)\ f_1\ p_1}{∋}$,$\frac{F(∋)\ f_2\ p_2}{∋}$⟩ cup sort(⩽) thinL(Q) | $\frac{R\ ∪\ S}{∋}$ = ⟨$\frac{R}{∋}$,$\frac{S}{∋}$⟩ cup |
| 6 | = $\frac{(F(∋)\ f_1\ p_1)\ ∪\ (F(∋)\ f_2\ p_2)}{∋}$ sort(⩽) thinL(Q) | R (S ∪ T) = (R S) ∪ (R T) |
| 7 | = $\frac{F(∋)\ ((f_1\ p_1)\ ∪\ (f_2\ p_2))}{∋}$ sort(⩽) thinL(Q) | (8.6) sort(⩽) thinL(Q) ⊑ thin(Q) sort(⩽) |
| 8 | ⊑ $\frac{F(∋)\ ((f_1\ p_1)\ ∪\ (f_2\ p_2))}{∋}$ thin(Q) sort(⩽) | |

## §8.4. The knapsack problem

(8.4a)

| | definition | type | meaning |
|---|---|---|---|
| 1 | FX = L + E × X | 𝐴→𝐴 | here L ≜ 1 and E ≜ Item: the trivial base, or an item and what is built from the rest |
| 2 | total(f) ≜ f′ sum | Int | add up f over the items of the list |
| 3 | subseq ≜ ⦇[nil,cons ∪ π₂]⦈ | [A]→[A] | every subsequence of the list |
| 4 | value ≜ val′ sum | [Item]→ Int | the total value of a packing |
| 5 | weight ≜ wt′ sum | [Item]→ Int | the total weight of a packing |
| 6 | [nil,cons] = [nil,cons] | F[Item]→ [Item] | keep the item: the list constructor |
| 7 | within(w,xs) ⇔ weight(xs) ≤ w | [Item]→ [Item] | the packing weighs at most w |
| 8 | S ≜ ([nil,cons] within(w)) ∪ [nil,π₂] | F[Item]→ [Item] | at each item, keep it if the packing still fits, or drop it |
| 9 | R ≜ value ≥ value° | [Item]→ [Item] | x is worth at least as much as y |
| 10 | Q(val,wt) ≜ R ∩ (weight ≤ weight°) | [Item]→ [Item] | x is worth at least as much as y and weighs no more |









(8.4b)

| | the law | what it says |
|---|---|---|
| 1 | (𝟙×R) (cons (within w))⊑cons (within w)R<br>FALSE | not monotonic on R: a selection of greater value need not still fit once one more item goes in |
| 2 | F(Q(val,wt)) [nil,cons] within(w) ⊑ [nil,cons] within(w) Q(val,wt)<br>F(Q(val,wt)) [nil,π₂] ⊑ [nil,π₂] Q(val,wt) , | both halves are monotonic on Q once ties in value are broken by weight |
| 3 | F(R) [nil,cons] ⊑ [nil,cons] R<br>F(R) [nil,π₂] ⊑ [nil,π₂] R | both algebras are monotonic on R itself, so R is the sort order P |

## §8.4.1. Derivation

**0 ≤ w ∧ (∀i. 0 ≤ wt(i)) ⇒ ⦇cpL (g₁,g₂) merge(R) thinL(Q(val,wt))⦈ minL(R) ⊑ $\frac{\text{subseq within(w)}}{\ni}$ est(R)** (8.4.1a)


the knapsack problem, as a fold that thins the packings kept at each item

| circuit | Hinze–Marsden |
|---|---|
|  $\frac{\text{subseq within(w)}}{\ni}$ est(R) |  |
| =  $\frac{\text{⦇[nil,cons] within(w)) ∪ [nil,π₂]⦈}}{\ni}$ est(R) fusion, weights non-negative. |  |
| ⊒  ⦇cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt))⦈ minL(R) binary thinning theorem, at P≜R, F linear, Q from F(Q(val,wt)) [nil,cons] within(w) ⊑ [nil,cons] within(w) Q(val,wt) , F(Q(val,wt)) [nil,π₂] ⊑ [nil,π₂] Q(val,wt) |  |
| ⊒  ⦇[nil τ,cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))]⦈ minL(R) 0 ≤ w ⇒ [nil τ,cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] ⊑ cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt)) under the fold; minL(R) is head, packings coming out in descending value |  |

## §8.4.2. Splitting the fold's body


**0 ≤ w ⇒ [nil τ,cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] ⊑ cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt))** (8.4.2a)


the fold's body splits into a base case **nil τ** and a step that extends each kept packing by the item or leaves it out





| | | |
|---|---|---|
| 1 | [nil τ,cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | 1 ⊑ Q(val,wt) |
| 2 | ⊑ [nil ⟨τ,τ⟩ cat thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | 1 ⊑ R |


| | | |
|---|---|---|
| 3 | ⊑ [nil ⟨τ,τ⟩ merge(R) thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | Map(f)<br>⇒ f ⟨R,S⟩ = ⟨f R,f S⟩ |
| 4 | = [(nil τ,nil τ) merge(R) thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | 0 ≤ w<br>⇒ nil within(w) = nil |

= 


+ 


(5)

⊑ 

+ 


(6)


= 

+ 


(7)


| | | |
|---|---|---|
| 5 | = [(nil within(w) τ,nil τ) merge(R) thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | Coreflexive(within(w)) |
| 6 | ⊑ [(nil τ filter(within(w)),nil τ) merge(R) thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | inl [nil,cons] = nil |
| 7 | = [(inl [nil,cons] τ filter(within(w)),nil τ) merge(R) thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | inl [nil,π₂] = nil |

= 


+ 


(8)

= 

+ 


(9)

= 


+ 

(10)

| | | |
|---|---|---|
| 8 | = [(inl [nil,cons] τ filter(within(w)),inl [nil,π₂] τ) merge(R) thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | τ R′ = R τ |
| 9 | = [(inl τ g₁,inl τ g₂) merge(R) thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | l cpL = inl τ |
| 10 | = [(l cpL g₁,l cpL g₂) merge(R) thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | Map(f)<br>⇒ f ⟨R,S⟩ = ⟨f R,f S⟩ |




| | | |
|---|---|---|
| 11 | = [l cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt)),cpr ⟨h₁,h₂⟩ merge(R) thinL(Q(val,wt))] | Map(f)<br>⇒ f ⟨R,S⟩ = ⟨f R,f S⟩ |
| 12 | = [l cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt)),⟨cpr h₁,cpr h₂⟩ merge(R) thinL(Q(val,wt))] | inr′ [nil,π₂]′ = π₂′ |
| 13 | = [l cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt)),⟨cpr h₁,cpr inr′ g₂⟩ merge(R) thinL(Q(val,wt))] | inr′ [nil,cons]′ = cons′ |




| | | |
|---|---|---|
| 14 | = [l cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt)),⟨cpr inr′ g₁,cpr inr′ g₂⟩ merge(R) thinL(Q(val,wt))] | Map(f)<br>⇒ f ⟨R,S⟩ = ⟨f R,f S⟩ |
| 15 | = [l cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt)),cpr inr′ ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt))] | r cpL = cpr inr′ |
| 16 | = [l cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt)),r cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt))] | l T = R ∧ r T = S<br>⇒ T = [R,S] |
| 17 | = cpL ⟨g₁,g₂⟩ merge(R) thinL(Q(val,wt)) | |

## §8.5. The paragraph problem

(8.5a)

| | definition | type | meaning |
|---|---|---|---|
| 1 | FX = L + E × X | 𝐴→𝐴 | here L ≜ Word and E ≜ Word: one word, or a word and what is built from the rest |
| 2 | Line ≜ L(Word) | Type | a line is a non-empty list of words |
| 3 | Para ≜ L(Line) | Type | a paragraph is a non-empty list of lines |
| 4 | μF ≜ wrap(L) \| cons(E,μF) | L→μF | the one-element non-empty list holding a |
| 5 | new(a,xss) ≜ [[a]]⧺xss | Para | start a new first line holding only the word a |
| 6 | glue(a,[xs]) = [[a]⧺xs], glue(a,[xs]⧺a') = [[a]⧺xs]⧺a' | Para→ Para | put the word a at the front of the first line |
| 7 | partition ≜ ⦇[τ²,new] ∪ [τ²,glue]⦈ | L(Word)→ Para | every way of breaking the words into lines |
| 8 | width[a] = len(a), width([a]⧺xs) = (len(a) + width(xs)) + 1 | Line→Int | the lengths of the words plus one space between neighbours |
| 9 | head[xs] = xs, head([xs]⧺a) = xs | Para→ Line | the first line of the paragraph |
| 10 | fits(w,[xs]) = width(xs) ≤ w, fits(w,[xs]⧺a) = width(xs) ≤ w ∧ fits(w,a) | Para→ Para | every line is at most w wide |
| 11 | ok(w,xss) ≜ width(head(xss)) ≤ w | Para→ Para | the paragraphs whose first line is at most w wide |
| 12 | sqr(n) ≜ nn | Int | n squared |
| 13 | waste(w,[xs]) = 0, waste(w,[xs]⧺a) = sqr(w−width(xs)) + waste(w,a) | Para→Int | the squared white space left on every line but the last, added up |
| 14 | R ≜ waste(w) ≤ waste(w)° | Para→ Para | p wastes no more than q |
| 15 | Q(len)(w) ≜ R ∩ (head head°) | Para→ Para | p wastes no more than q and has the same first line |
| 16 | start(a) ≜ [[[a]]] | [Para] | the one candidate for a single word: the paragraph of one line holding that word |








(8.5b)

| | the law | what it says |
|---|---|---|
| 1 | (𝟙×R) glue⊑glue R FALSE | glue is not monotonic on R: the waste of a paragraph depends on its whole first line, so no greedy algorithm solves this |
| 2 | F(Q(len)(w)) [τ²,new] ⊑ [τ²,new] Q(len)(w)<br>(∀a. 0 ≤ len(a)) ⇒ F(Q(len)(w)) [τ²,glue] ok(w) ⊑ [τ²,glue] ok(w) Q(len)(w)<br>cons monotonic on collect≤collect°. , | both halves are monotonic on Q once ties in waste are broken by the first line |
| 3 | merge(T) = cat | T needs no sorting at all |
| 4 | F(T) [τ²,new] ⊑ [τ²,new] T<br>F(T) [τ²,glue] ⊑ [τ²,glue] T | both algebras are monotonic on T, so T is the sort order P |

## §8.5.1. Derivation

**(∀a. 0 ≤ len(a)) ∧ (∀a. len(a) ≤ w) ⇒ ⦇cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w))⦈ minL(R) ⊑ $\frac{\text{partition fits(w)}}{\ni}$ est(R)** (8.5.1a)


a paragraph laid out as a fold that thins the layouts kept at each word

| circuit | Hinze–Marsden |
|---|---|
|  $\frac{\text{partition fits(w)}}{\ni}$ est(R) |  |
| =  $\frac{\text{⦇[τ²,new] ∪ ([τ²,glue] ok(w))⦈}}{\ni}$ est(R)<br>fusion, every word fits on a line by itself. |  |
| =  $\frac{\text{⦇[τ²,new] ∪ ([τ²,glue] ok(w))⦈}}{\ni}$ est(R)<br>the algebra as (f₁p₁) ∪ (f₂p₂), p₁≜𝟙 — binary thinning theorem. | |
|  ⦇cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w))⦈ minL(R)<br>⊒ binary thinning theorem, at P≜T with merge T=cat ( merge(T) = cat ), Q from F(Q(len)(w)) [τ²,new] ⊑ [τ²,new] Q(len)(w) , (∀a. 0 ≤ len(a))<br>⇒ F(Q(len)(w)) [τ²,glue] ok(w) ⊑ [τ²,glue] ok(w) Q(len)(w) |  |
| = ⦇[start,cpr ⟨h₁,h₂⟩ cat thinL(Q)]⦈ minL(R)<br>cpL=τ+cpr, gᵢ along the coproduct — start(a) ≜ [[[a]]] , new(a,xss) ≜ [[a]]#xss , glue(a,[xs]) = [[a]#xs], glue(a,[xs]#a') = [[a]#xs]#a' | |

## §8.5.2. Splitting the fold's body


**(∀a. len(a) ≤ w) ⇒ [τ² τ,cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] ⊑ cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w))** (8.5.2a)

the fold's body splits into a base case **start** for a single word and a step that extends each kept layout by **new** and by **glue**





| | | |
|---|---|---|
| 1 | [τ² τ,cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | τ² = τ² |
| 2 | = [τ² τ,cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | 𝟙 ⊑ Q(len)(w) |
| 3 | ⊑ [τ² ⟨τ,τ⟩ cat thinL(Q(len)(w)),cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | merge(T) = cat |


| | | |
|---|---|---|
| 4 | = [τ² ⟨τ,τ⟩ merge(T) thinL(Q(len)(w)),cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | Map(f)<br>⇒ f ⟨R,S⟩ = ⟨f R,f S⟩ |




| | | |
|---|---|---|
| 5 | = [⟨τ² τ,τ² τ⟩ merge(T) thinL(Q(len)(w)),cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | (∀a. len(a) ≤ w)<br>⇒ τ² ok(w) = τ² |
| 6 | = [⟨τ² τ,τ² ok(w) τ⟩ merge(T) thinL(Q(len)(w)),cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | Coreflexive(ok(w)) |
| 7 | ⊑ [⟨τ² τ,τ² τ filter(ok(w))⟩ merge(T) thinL(Q(len)(w)),cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | inl [g,h] = g |
| 8 | = [⟨inl [τ²,new] τ,inl [τ²,glue] τ filter(ok(w))⟩ merge(T) thinL(Q(len)(w)),cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | τ R′ = R τ |




| | | |
|---|---|---|
| 9 | = [⟨inl τ g₁,inl τ g₂⟩ merge(T) thinL(Q(len)(w)),cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | l cpL = inl τ |
| 10 | = [⟨l cpL g₁,l cpL g₂⟩ merge(T) thinL(Q(len)(w)),cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | Map(f)<br>⇒ f ⟨R,S⟩ = ⟨f R,f S⟩ |
| 11 | = [l cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w)),cpr ⟨h₁,h₂⟩ merge(T) thinL(Q(len)(w))] | Map(f)<br>⇒ f ⟨R,S⟩ = ⟨f R,f S⟩ |
| 12 | = [l cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w)),⟨cpr h₁,cpr h₂⟩ merge(T) thinL(Q(len)(w))] | inr′ [g,h]′ = h′ |



| (13) | (14) | (15) | (16) |
|---|---|---|---|
| 13 | = [l cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w)),⟨cpr inr′ g₁,cpr inr′ g₂⟩ merge(T) thinL(Q(len)(w))] | Map(f)<br>⇒ f ⟨R,S⟩ = ⟨f R,f S⟩ | |
| 14 | = [l cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w)),cpr inr′ ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w))] | r cpL = cpr inr′ | |
| 15 | = [l cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w)),r cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w))] | l T = R ∧ r T = S<br>⇒ T = [R,S] | |
| 16 | = cpL ⟨g₁,g₂⟩ merge(T) thinL(Q(len)(w)) | | |

## §8.6. Bitonic tours

(8.6a)

| | definition | type | meaning |
|---|---|---|---|
| 1 | FX = L + E × X | 𝒜→𝒜 | here L ≜ City×City and E ≜ City: the last two cities, or a city and what is built from the rest |
| 2 | Journey(City) ≜ μF | Type | a list of at least two cities, the last two held as a pair |
| 3 | Tour(City) ≜ Journey(City) × Journey(City) | Type | the outward journey and the return journey |
| 4 | head[a, b] = a, head([a]⁜a') = a | Journey(City)→ City | the first city of the journey |
| 5 | next[a, b] = b, next([a]⁜a') = head(a') | Journey(City)→ City | the second city of the journey |
| 6 | tail([a, b]) = [b], tail([a]⁜a') = a' | Journey(City)→ L(City) | the journey without its first city, a non-empty list |
| 7 | [a]⁜[c] = [a, c], [a]⁜[b]⁜xs = [a]⁜[b]⁜xs | L(City)→ Journey(City) | a put in front of a non-empty list, a journey |
| 8 | replaceHead = (𝟙 × tail) ⁜ | Journey(City)→ Journey(City) | replace the first city of the journey by a |
| 9 | outcost[a, b] = tc(a,b), outcost([a]⁜a') = tc(a,head(a')) + outcost(a') | Journey(City)→ Int | the cost of travelling the journey forwards |
| 10 | incost[a, b] = tc(b,a), incost([a]⁜a') = tc(head(a'),a) + incost(a') | Journey(City)→ Int | the cost of travelling the journey backwards |
| 11 | cost(t) ≜ outcost(π₁(t)) + incost(π₂(t)) | Int | the outward journey forwards plus the return journey backwards |
| 12 | start(a,b) = ([a, b],[a, b]) | City×City→ Tour(City) | the tour of the last two cities, both journeys being that one edge |
| 13 | dropl(a,t) ≜ (replaceHead(a,π₁(t)),[a]⁜π₂(t)) | Tour(City) | a replaces the first city of the outward journey and is put in front of the return |
| 14 | dropr(a,t) ≜ ([a]⁜π₁(t),replaceHead(a,π₂(t))) | Tour(City) | a is put in front of the outward journey and replaces the first city of the return |
| 15 | [start,dropl](l(p)) = start(p), [start,dropl](r(q)) = dropl(π₁(q),π₂(q)) | F(Tour(City))→ Tour(City) | start at the last two cities, then add each city by dropl |
| 16 | [start,dropr](l(p)) = start(p), [start,dropr](r(q)) = dropr(π₁(q),π₂(q)) | F(Tour(City))→ Tour(City) | start at the last two cities, then add each city by dropr |
| 17 | tour ≜ ⦇[start,dropl] ∪ [start,dropr]⦈ | μF→Tour(City) | every bitonic tour of the cities |
| 18 | R ≜ cost ≤ cost° | Tour(City)→ Tour(City) | t costs no more than t′ |
| 19 | next₂(t) ≜ (next(π₁(t)),next(π₂(t))) | City×City | the second cities of both journeys |
| 20 | head₂(t) ≜ (head(π₁(t)),head(π₂(t))) | City×City | the first cities of both journeys |

| definition | type | meaning |
|---|---|---|
| `Q ≜ R ∩ (next₂ next₂°) ∩ (head₂ head₂°)` | `Tour(City)→ Tour(City)` | t costs no more than t′, and both journeys of t and t′ share their first two cities |






(8.6b)

| | the law | what it says |
|---|---|---|
| 1 | `(𝟙×R) dropl⊑dropl R` FALSE<br>`(𝟙×R) dropr⊑dropr R` FALSE | neither drop is monotonic on `R`: the two edges it adds and removes depend on `head` and `next` of both lists |
| 2 | `F(Q) [start,dropl] ⊑ [start,dropl] Q`<br>`F(Q) [start,dropr] ⊑ [start,dropr] Q` , | both are, once ties in cost are broken by the two second cities — the heads already agree among tours of one input |
| 3 | `F(T) [start,dropl] ⊑ [start,dropl] T`<br>`F(T) [start,dropr] ⊑ [start,dropr] T` | both algebras are monotonic on `T`, so `T` is the sort order `P` |

## §8.6.1. Derivation

`⦇cpL ⟨g₁,g₂⟩ cat thinL(Q)⦈ minL(R) ⊑ ⦇[start,dropl] ∪ [start,dropr]⦈/∋ est(R)` (8.6.1a)

a least-cost bitonic tour, as a fold that thins the tours kept at each city

| circuit | Hinze–Marsden |
|---|---|
|  |  |
| =  `tour ≜ ⦇[start,dropl] ∪ [start,dropr]⦈` | |
| ⊒  `⦇cpL ⟨g₁,g₂⟩ cat thinL(Q)⦈ minL(R)` binary thinning theorem, at `P≜T` with `merge T=cat`, `Q` from `F(Q) [start,dropl] ⊑ [start,dropl] Q` , `F(Q) [start,dropr] ⊑ [start,dropr] Q` |  |
| = `⦇[start τ,cpr ⟨dropl′,dropr′⟩ cat thinL(Q)]⦈ minL(R)` `cpL=τ+cpr`, `gᵢ=[start′,dropᵢ′]` — `start(a,b) = ([a, b],[a, b])` , `dropl(a,t) ≜ (replaceHead(a,π₁(t)),[a]⧺π₂(t))` ; quadratic, two tours added per step | |