

# Companion to Bird & de Moor, Algebra of Programming


## §7. Optimisation Problems

### §7.1. Minimum and maximum

(7.1a)

For  $R : A \rightarrow A$ ,  $\text{est}(R) \triangleq \exists n (\epsilon \setminus R^\circ) : PA \rightarrow A \quad X \in \epsilon \setminus R^\circ \iff EX \in R^\circ$ , and  $EX$  runs  $y \rightarrow XS \rightarrow X$ , member first, so its pair  $(y, x)$  is in  $R^\circ$  exactly when  $x R y$ ; at  $R \triangleq \leq$  that is  $x \leq y$  for every  $y \in XS$ , the least —  $\epsilon \setminus \leq$  would give  $y \leq x$ , the greatest.

$\text{est}(R) = \exists n (\subseteq (\frac{R}{\exists})^\circ)$   $x$  is the  $\text{est}(R)$  of  $XS$  when  $x \in XS$  and  $XS \subseteq \Lambda(R)(x)$ , the set of every  $y$  with  $x R y$  — mem-ldiv at  $Z \triangleq R^\circ$



$XS (\text{est}(R)) x \iff x \in XS \wedge (\forall y \in XS. x R y)$  the same predicate under the same letter,  $\min R$ , so  $\text{est}(R) = \min(R^\circ)$  once  $R$  is an arrow;

$XS (\text{est}(R)) x \iff (x \text{ in } XS) \text{ and all } x R \setminus : XS \text{ in } q$

$\text{est}(R) = \exists n \text{ all } R^\circ$  all  $R \triangleq \epsilon \setminus R$ ,  $q$ 's all; the chains below keep it written  $\epsilon \setminus$

$E(R) \triangleq \frac{\exists R}{\exists} : PA \rightarrow PB$ ,  $XS E(R) yS \iff yS = \{y \mid \exists x \in XS. x R y\}$  the image of  $XS$ , pow-laws


$P(R) : PA \rightarrow PB$ ,  $XS P(R) yS \iff (\forall x \in XS. \exists y \in yS. x R y) \wedge (\forall y \in yS. \exists x \in XS. x R y)$  every  $x$  and every  $y$  has a partner, powrel-readings

(7.1b)

| the law                                                                                                             | what it says                                                                                   |
|---------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| $X \in \text{est}(R) \iff X \in \exists$ and $X^\circ \exists \in R$                                                | in the set, and below every element of it                                                      |
| $\frac{1}{\exists} (\epsilon \setminus R) = R$                                                                      | bounding a singleton is bounding its element                                                   |
| $\frac{S}{\exists} (\epsilon \setminus R) = S^\circ \setminus R$                                                    | bound $S$ 's image without building the set                                                    |
| $\text{union} \triangleq \frac{\exists \exists}{\exists} : PPA \rightarrow PA$                                      | flattens a set of sets                                                                         |
| $\text{union} (\epsilon \setminus R) = \epsilon \setminus (\epsilon \setminus R)$                                   | bound a union by bounding each member set                                                      |
| $\frac{1}{\exists} \text{est}(R) = 1 \cap R^\circ$ (7.4)                                                            | a singleton's minimum is its element, where $R$ is reflexive                                   |
| $\frac{S}{\exists} \text{est}(R) = S \cap (S^\circ \setminus R^\circ)$                                              | $\frac{S}{\exists} \text{est}(R)$ at $S := 1$<br>an $S$ -value that points to every $S$ -value |
| $\frac{S}{\exists} \text{est}(R \cap (S^\circ S)) = \frac{S}{\exists} \text{est}(R)$                                | only $R$ between values $S$ gives one argument counts — context                                |
| $E(S) \text{est}(R) = (\exists S) \cap ((\exists S)^\circ \setminus R^\circ)$ (7.7)                                 | the same for the image of a set<br>$\frac{S}{\exists} \text{est}(R)$ at $S := \exists S$       |
| $\text{Map}(f) \implies P(f) \text{est}(R) = \text{est}(f R f^\circ) f$                                             | shunt a function through a minimum                                                             |
| $P(S) \text{est}(R) = (\exists S) \cap (\epsilon \setminus (SR^\circ))$ (7.9)<br>$R$ reflexive                      | fusion with the power relator<br>$\exists$ is the only proof here that tabulates               |
| $P(S) \text{est}(R) \subseteq (\exists S) \cap (\epsilon \setminus (SR^\circ))$                                     | the half of the row above that costs nothing                                                   |
| $P(\text{est}(R)) \text{est}(R) \subseteq \text{union est}(R)$<br>$R$ transitive                                    | a minimum in each set, then a minimum of those                                                 |
| $R R \subseteq R \implies P(\text{est}(R)) \text{est}(R) = P(\text{dom}(\text{est}(R))) \text{union est}(R)$ (7.12) | the same as an equality, once empty sets are dropped                                           |

#### §7.1.1. $X \in \text{est}(R) \iff X \in \exists$ and $X^\circ \exists \in R$

(7.1.1a)



#### §7.1.2. $\frac{1}{\exists} (\epsilon \setminus R) = R$

$$\begin{array}{c} X \\ \hline \frac{1}{\exists} (\epsilon \backslash R) \end{array} \xleftrightarrow{f^\circ \cdot \neg f^\circ} \begin{array}{c} \frac{1}{\exists}^\circ X \\ \hline \epsilon \backslash R \end{array} \xleftrightarrow{T^\circ \cdot \neg T^\circ} \begin{array}{c} \epsilon \frac{1}{\exists}^\circ X \\ \hline R \end{array} \xleftrightarrow{\circ} \begin{array}{c} (\frac{1}{\exists} \exists)^\circ X \\ \hline R \end{array} \xleftrightarrow{i \dashv E} \begin{array}{c} X \\ \hline R \end{array} \quad (7.1)$$

### §7.1.3. $\frac{S}{\exists} (\epsilon \backslash R) = S^\circ \backslash R$

$\frac{S}{\exists}$  gathers the  $S$ -image of a point into one set and  $\epsilon \backslash R$  asks that every member of that set be  $R$ -related to the target, so the set cancels and  $S^\circ \backslash R$  asks it of the  $S$ -image directly.

$$\begin{array}{c} X \\ \hline \frac{S}{\exists} (\epsilon \backslash R) \end{array} \xleftrightarrow{f^\circ \cdot \neg f^\circ} \begin{array}{c} \frac{S}{\exists}^\circ X \\ \hline \epsilon \backslash R \end{array} \xleftrightarrow{T^\circ \cdot \neg T^\circ} \begin{array}{c} \epsilon \frac{S}{\exists}^\circ X \\ \hline R \end{array} \xleftrightarrow{\circ} \begin{array}{c} (\frac{S}{\exists} \exists)^\circ X \\ \hline R \end{array} \xleftrightarrow{\cdot \exists \dashv \frac{S}{\exists}} \begin{array}{c} S^\circ X \\ \hline R \end{array} \xleftrightarrow{T^\circ \cdot \neg T^\circ} \begin{array}{c} X \\ \hline S^\circ \backslash R \end{array} \quad (7.2)$$

### §7.1.4. **union** $(\epsilon \backslash R) = \epsilon \backslash (\epsilon \backslash R)$

$$\begin{array}{c} X \\ \hline \text{union} (\epsilon \backslash R) \end{array} \xleftrightarrow{f^\circ \cdot \neg f^\circ} \begin{array}{c} \text{union}^\circ X \\ \hline \epsilon \backslash R \end{array} \xleftrightarrow{T^\circ \cdot \neg T^\circ} \begin{array}{c} \epsilon \text{union}^\circ X \\ \hline R \end{array} \xleftrightarrow{\circ} \begin{array}{c} (\text{union} \exists)^\circ X \\ \hline R \end{array} \xleftrightarrow{\cdot \exists \dashv \frac{S}{\exists}} \begin{array}{c} (\exists \exists)^\circ X \\ \hline R \end{array} \xleftrightarrow{\circ, T^\circ \cdot \neg T^\circ} \begin{array}{c} X \\ \hline \epsilon \backslash (\epsilon \backslash R) \end{array} \quad (7.3)$$

### §7.1.5. $\frac{S}{\exists} \text{ est}(R) = S \cap (S^\circ \backslash R^\circ)$

$$\begin{array}{c} X \\ \hline \frac{S}{\exists} \text{ est}(R) \end{array} \xleftrightarrow{f^\circ \cdot \neg f^\circ} \begin{array}{c} \frac{S}{\exists}^\circ X \\ \hline \text{est}(R) \end{array} \xleftrightarrow{\Delta \dashv \cap} \begin{array}{c} \frac{S}{\exists}^\circ X \\ \hline \exists \\ \hline \frac{S}{\exists}^\circ X \\ \hline \epsilon \backslash R^\circ \end{array} \xleftrightarrow{f^\circ \cdot \neg f^\circ} \begin{array}{c} X \\ \hline \frac{S}{\exists} \exists \\ \hline X \\ \hline \frac{S}{\exists} (\epsilon \backslash R^\circ) \end{array} \xleftrightarrow{\cdot \exists \dashv \frac{S}{\exists}, (7.2)} \begin{array}{c} X \\ \hline S \\ \hline X \\ \hline S^\circ \backslash R^\circ \end{array} \xleftrightarrow{\Delta \dashv \cap} \begin{array}{c} X \\ \hline S \cap (S^\circ \backslash R^\circ) \end{array} \quad (7.5)$$

### §7.1.6. $\frac{S}{\exists} \text{ est}(R) = \frac{S}{\exists} \text{ est}(R \cap S^\circ S)$

$$\begin{array}{c} X \\ \hline \frac{S}{\exists} \text{ est}(R \cap S^\circ S) \end{array} \xleftrightarrow{(7.5), \circ} \begin{array}{c} X \\ \hline S \cap (S^\circ \backslash (R^\circ \cap S^\circ S)) \end{array} \xleftrightarrow{\Delta \dashv \cap, T^\circ \cdot \neg T^\circ} \begin{array}{c} X \\ \hline S \\ \hline S^\circ X \\ \hline R^\circ \cap S^\circ S \end{array} \xleftrightarrow{\Delta \dashv \cap, S^\circ \cdot \text{monotone}} \begin{array}{c} X \\ \hline S \\ \hline S^\circ X \\ \hline R^\circ \end{array} \xleftrightarrow{T^\circ \cdot \neg T^\circ, \Delta \dashv \cap} \begin{array}{c} X \\ \hline S \cap (S^\circ \backslash R^\circ) \end{array} \xleftrightarrow{(7.5)} \begin{array}{c} X \\ \hline \frac{S}{\exists} \text{ est}(R) \end{array} \quad (7.6)$$


### §7.1.7. **P(f)** $\text{est}(R) = \text{est}(f R f^\circ)$ **f**

$$\begin{array}{c} \text{P(f)} \text{ est}(R) \\ \hline f \text{ a map} \end{array} \xrightarrow[\text{modular law, } f \text{ simple}]{\text{P=E on maps, (7.5)}} \begin{array}{c} (\exists f) \cap ((\exists f)^\circ \backslash R^\circ) \\ \hline \end{array} \xrightarrow[\cdot f \dashv \cdot f^\circ, \circ, \text{est}]{\circ, T^\circ \cdot \neg T^\circ, f^\circ \cdot \neg f^\circ} \begin{array}{c} (\exists f) \cap (\epsilon \backslash (f R^\circ)) \\ \hline \end{array} \xrightarrow[\cdot f \dashv \cdot f^\circ, \circ, \text{est}]{\text{modular law, } f \text{ simple}} \begin{array}{c} (\exists \cap ((\epsilon \backslash (f R^\circ)) f^\circ)) f \\ \hline \end{array} \xrightarrow[\cdot f \dashv \cdot f^\circ, \circ, \text{est}]{\text{modular law, } f \text{ simple}} \begin{array}{c} \text{est}(f R f^\circ) \text{ f} \\ \hline \end{array} \quad (7.8)$$

### §7.1.8. **P(S)** $\text{est}(R) \sqsubseteq (\exists S) \cap (\epsilon \backslash (S R^\circ))$

$$\begin{array}{c} \text{P(S)} \text{ est}(R) \\ \hline (\exists S) \cap (\epsilon \backslash (S R^\circ)) \end{array} \xleftrightarrow{\Delta \dashv \cap, T^\circ \cdot \neg T^\circ} \begin{array}{c} \text{P(S)} \text{ est}(R) \\ \hline \exists S \\ \hline \text{EP(S)} \text{ est}(R) \\ \hline S R^\circ \end{array} \xleftrightarrow{\text{UP of est}} \begin{array}{c} \text{P(S)} \exists \\ \hline \exists S \\ \hline \text{EP(S)} \\ \hline S \epsilon \end{array} \quad (7.10)$$

### §7.1.9. **P(est(R))** $\text{est}(R) \sqsubseteq \text{union est}(R)$




## §7.2. Monotonic algebras

(7.2a)

An  $F$ -algebra  $\varphi : FA \rightarrow A$  is **monotonic on**  $R : A \rightarrow A$  when it is lax at  $R$  at  $G := F$ ,  $F := \text{Id}$ :  $F(R)\varphi \sqsubseteq \varphi R$ .  $R$  is an **endorelation**, so  $B=A$  and the two components  $\varphi_A, \varphi_B$  are the one arrow  $\varphi$  — an algebra, not a family.

For a map  $f : FA \rightarrow A$  that is  $f \circ F(R)f \in R$  adj-all's  $f^\circ \cdot \dashv f^\circ$  at  $X := F(R)f, Y := R$ , equivalently  $F(R) \sqsubseteq f R f^\circ \cdot f \dashv f^\circ$  then  $f^\circ \cdot \dashv f^\circ, .$   
 $(\leq \times \leq) + \sqsubseteq + \leq$  — addition on  $\text{Nat}$  is monotonic on  $\leq$ , which at the point level reads  $c = a + b \wedge a \leq a' \wedge b \leq b' \implies c \leq a' + b'$ .

(7.2b)




### §7.2.1. Function $f$ is monotonic on $R$ iff it distributes over $R$

(7.2.1a)

$f : FA \rightarrow A$  **distributes over**  $R$  if  $F(\text{est}(R))f \sqsubseteq \frac{F(\exists)f}{\exists} \text{est}(R)$ .

$+$  distributes over  $\leq$ , at the point level  $\min(xs) + \min(ys)$  is a least element of  $\{x+y \mid x \in xs \wedge y \in ys\}$  for  $xs, ys$  non-empty and  $\min \triangleq \text{est}(\leq)$ .


(7.2.1b)




$$f^\circ F(R) f \sqsubseteq R \iff F(\text{est}(R)) f \sqsubseteq \frac{F(\exists) f}{\exists} \text{est}(R)$$

Theorem 7.1


function  $f$  is monotonic over  $R$  if and only if it distributes over  $R$ ;  $f$  a map,  $R$  reflexive



$f$  distributes over  $R \iff \frac{F(\exists) f}{\exists} \text{est}(R) \text{ distributes} \iff \text{the fraction bent as adj-E-bend}$



(7.5) splits the bound in two, div-laws moving  $(F(\exists) f)^\circ$  across









$\text{est}(R) \sqsubseteq \exists \iff \text{est}$  — so the first conjunct drops

$(F(\exists) f)^\circ = f^\circ F(\epsilon) \iff \text{est}(R) = R^\circ \iff \text{est}, R \text{ reflexive}$

both sides conversed —  $F(R^\circ)^\circ = F(R)$ , relator-laws

### §7.2.2. Greedy Theorem: $(\lfloor \frac{S}{\circ} \rfloor \text{est}(R)) \sqsubseteq (\lfloor \frac{S \circ}{\circ} \rfloor \text{est}(R))$ , given $S$ monotonic on $R$ , $F$ preserving $\circ$ , and $R$ transitive

Theorem 7.2

| circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Hinze–Marsden                                                                         |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| $(\lfloor \frac{S}{\circ} \rfloor \text{est}(R)) \sqsubseteq (\lfloor \frac{S \circ}{\circ} \rfloor \text{est}(R))$<br>the conclusion: one minimum kept at each step is below every result collected and one minimum taken at the end                                                                                                                                                                                                                                    |                                                                                       |
| $(\lfloor \frac{S}{\circ} \rfloor \text{est}(R)) \sqsubseteq (S)$<br>$\Leftrightarrow (S) \circ (\lfloor \frac{S}{\circ} \rfloor \text{est}(R)) \sqsubseteq R^\circ$<br>(7.5) at $(S)$ ; $(\lfloor \frac{S}{\circ} \rfloor \text{est}(R)) \sqsubseteq (S) \circ R^\circ \Leftrightarrow (S) \circ (\lfloor \frac{S}{\circ} \rfloor \text{est}(R)) \sqsubseteq R^\circ$ — div-laws                                                                                        |                                                                                       |
| $\Rightarrow \lfloor \frac{S}{\circ} \rfloor \text{est}(R) \sqsubseteq S$<br>the left conjunct; (7.5), and $(\lfloor - \rfloor)$ is monotone                                                                                                                                                                                                                                                                                                                             |                                                                                       |
|  <p><math>\Rightarrow</math> the right conjunct; <math>(S) \circ (\lfloor \frac{S}{\circ} \rfloor \text{est}(R))</math> is the least <math>X</math> with <math>X = S^\circ F(X) (\lfloor \frac{S}{\circ} \rfloor \text{est}(R))</math> hylomorphism theorem — so Knaster–Tarski leaves this one inequation</p> <p><math>\frac{S}{\circ} = \frac{1}{\circ} E(S)</math> — adj-E-bend</p> |    |
|  <p><math>\sqsubseteq S^\circ F(R^\circ) \sqsubseteq R^\circ S^\circ</math> — <math>\triangleq</math> monotonic at <math>S</math>, conversed; <math>F(R)^\circ = F(R^\circ)</math> — relator-laws</p>                                                                                                                                                                                |   |
|  <p><math>\sqsubseteq S^\circ (\frac{S}{\circ} \text{est}(R)) \sqsubseteq S^\circ (S^\circ \setminus R^\circ) \sqsubseteq R^\circ</math> — (7.5), div-laws</p>                                                                                                                                                                                                                        |  |
|  <p><math>\sqsubseteq R</math> transitive</p>                                                                                                                                                                                                                                                                                                                                         |  |

§7.2.3.  $\text{takewhile}(p) = ([\text{nil}, (\pi_1 p \rightarrow \text{cons}, \rightarrow \text{nil})])$ 

(7.2.3a)

| name                     | definition                                                                         | type                                                   | example                                                                                    | in words                                                                                        |
|--------------------------|------------------------------------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| F                        | $FX = 1 + A \times X$                                                              | $\mathcal{A} \rightarrow \mathcal{A}$                  |                                                                                            | nothing, or a head and a tail                                                                   |
| nil, cons                | $[A] ::= \text{nil} \mid \text{cons}(A, [A])$<br>$\triangleq \text{subseq}$        | $1 \rightarrow [A],$<br>$A \times [A] \rightarrow [A]$ | $\text{cons}(3, [1, 2]) = [3, 1, 2]$                                                       | the empty list; a head onto a tail                                                              |
| $\alpha$                 | $[\text{nil}, \text{cons}]$                                                        | $F[A] \rightarrow [A]$                                 |                                                                                            | both constructors as one map                                                                    |
| p                        | a coreflexive                                                                      | $A \rightarrow A$                                      | $p \triangleq \text{even} \text{ — } 2 \mid p \mid 2, \text{ and } 3 \notin \text{dom}(p)$ | $\{(a, a) \mid a \text{ passes the test}\}$                                                     |
| R                        | $\text{length} \leq \text{length}^\circ$ , a preorder                              | $[A] \rightarrow [A]$                                  | $[1] \text{ R } [1, 2]$                                                                    | $xs \text{ R } ys \iff \text{length}(xs) \leq \text{length}(ys)$                                |
| $\rightarrow \text{nil}$ | the constant nil — the second nil of prefix                                        | $A \times [A] \rightarrow [A]$                         | $(\rightarrow \text{nil})(3, [1, 2]) = \text{nil}$                                         | drop the pair, return nil                                                                       |
| prefix                   | $([\text{nil}, \rightarrow \text{nil} \cup \text{cons}]) \triangleq \text{subseq}$ | $[A] \rightarrow [A]$                                  | $[3, 1, 2] \text{ prefix } [3, 1]$                                                         | $xs \text{ prefix } ys \iff \exists zs. xs = ys \# zs$<br>— at each cons, stop or keep the head |
| S                        | $[\text{nil}, \rightarrow \text{nil} \cup (p \times 1) \text{ cons}]$              | $F[A] \rightarrow [A]$                                 | $(4, [2]) \text{ S } [4, 2]$ , and $(3, [2]) \text{ S } \text{nil}$ only                   | prefix's algebra with one extra p<br>— stop, or keep a head that passes p                       |
| $(g \rightarrow X, Y)$   | X where g is defined and Y where it is not                                         | $A \rightarrow B$                                      |                                                                                            | the test picks the branch                                                                       |


$\text{nil} \text{ R } \top$ ,  $\text{nil} \text{ R}^\circ = \text{nil}$  nil is the shortest list — below every list, and above only itself, so it loses every  $\text{est}(\text{R}^\circ)$

**prefix =  $([\text{nil}, \rightarrow \text{nil} \cup \text{cons}])$**


(7.2.3b)

the fold whose algebra, at each **cons**, stops with **nil** or keeps the head:  $xs \text{ prefix } ys \iff \exists zs. xs = ys \# zs$

**the defining square**  $\alpha \text{ prefix} = F(\text{prefix})[\text{nil}, \rightarrow \text{nil} \cup \text{cons}]$  — build the list and then take a prefix, or take a prefix of the tail and then rebuild with the algebra




$F = 1 + A \times -$ , so  $F(\text{prefix}) = 1 + 1 \times \text{prefix}$ : the head passes, the fold recurses on the tail alone



the algebra  $[\text{nil}, \rightarrow \text{nil} \cup \text{cons}] : F([A]) \rightarrow [A]$  as a circuit: **nil** on the 1 branch; on a pair  $(a, ys')$  two outputs, **nil** and  $\text{cons}(a, ys')$

**Hinze–Marsden**



the **cons** operand of  $\rightarrow \text{nil} \cup \text{cons}$ ;  $\rightarrow \text{nil}$  makes a constant and draws nothing

$\text{nil} \text{ prefix } ys \iff ys = \text{nil}$   
 $\text{cons}(a, xs') \text{ prefix } ys \iff ys = \text{nil} \vee \exists ys'. xs' \text{ prefix } ys' \wedge ys = \text{cons}(a, ys')$

a right fold:  $\alpha^\circ$  peels,  $F(\text{prefix})$  recurses, the algebra runs on the way back;  $\text{init}^*$  ( $\triangleq \text{subseq}$ ) is the tail-recursive form  
lax natural only,  $\text{list}(\text{R}) \text{ prefix} \sqsubseteq \text{prefix}$   
 $\text{list}(\text{R})$ :  $\text{list}(\text{R})$  first needs an  $\text{R}$ -image of every element, **prefix** first may have dropped the ones without

| $\alpha \text{ prefix list}(p) = F(\text{prefix list}(p)) S$ <span style="float: right;">(7.2.3c)</span><br>building the list and then keeping a $p$ -passing prefix of it is keeping one of the tail first, and then building with $S$<br>this same diagram is <b>subseq</b> 's: algebra $[\text{nil}, \pi_2 \cup \text{cons}]$ , type $[A] \rightarrow [A]$ |                                                                                                                                                                        |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>circuit</b> — the fork is $F([A]) = 1 + A \times [A]$ : nil above, the pair below<br><p><math>\alpha \text{ prefix list}(p)</math></p>                                                                                                                                                                                                                     | <b>Hinze–Marsden</b><br><p>the <b>cons</b> branch alone, without<br/> <math>1 +</math> or <math>\multimap \text{nil}</math></p>                                        |
| <p><math>F(\text{prefix}) [\text{nil}, \multimap \text{nil} \cup \text{cons}] \text{list}(p)</math><br/>         defining equation</p>                                                                                                                                                                                                                        | <p>the <b>cons</b> operand of <math>\multimap \text{nil} \cup</math><br/> <b>cons</b></p>                                                                              |
| <p><math>F(\text{prefix}) [\text{nil}, \multimap \text{nil} \cup (p \times \text{list}(p)) \text{cons}] \text{list}(p)</math><br/>         list(p) through cons</p>                                                                                                                                                                                           | <p>the <math>(p \times \text{list}(p))</math> cons<br/>         operand of <math>\multimap \text{nil} \cup</math><br/> <math>(p \times \text{list}(p))</math> cons</p> |
| <p><math>[\text{nil}, \multimap \text{nil} \cup (p \times (\text{prefix list}(p))) \text{cons}]</math><br/>         relator, <b>prefix</b> entire</p>                                                                                                                                                                                                         |                                                                                                                                                                        |
| <p><math>F(\text{prefix list}(p)) S</math><br/> <b>prefix list(p)</b> entire</p>                                                                                                                                                                                                                                                                              |                                                                                                                                                                        |

$\triangleq$  **reduce** reads that off as  $\text{prefix list}(p) = (S)$ . fusion cannot:  $\text{list}(p)$  is not entire,  $(1 \times \text{list}(p)) \multimap \text{nil} \sqsubseteq \multimap \text{nil}$ , and no algebra meets the side condition. ,

| $(1 \times R^\circ) (\multimap \text{nil} \cup ((p \times 1) \text{cons})) \sqsubseteq (\multimap \text{nil} \cup ((p \times 1) \text{cons})) R^\circ$ (7.2.3d) |                                                                                                                                                      |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| shortening the tail and then taking the step lands inside taking the step and then shortening the result                                                        |                                                                                                                                                      |
| circuit — the cons branch of $F(R^\circ)S \in SR^\circ$                                                                                                         | reason                                                                                                                                               |
| <p style="text-align: center;"><math>(1 \times R^\circ) (\multimap \text{nil} \cup ((p \times 1) \text{cons}))</math></p>                                       |                                                                                                                                                      |
| $=$ <p style="text-align: center;"><math>((1 \times R^\circ) \multimap \text{nil}) \cup ((p \times R^\circ) \text{cons})</math></p>                             | each operand is reached on its own $\text{adj-all}$ — and $(1 \times R^\circ)$ $(p \times 1)$ is $p$ and $R^\circ$ on the pair's two strands at once |
| $\sqsubseteq$ <p style="text-align: center;"><math>\multimap \text{nil} \cup ((p \times R^\circ) \text{cons})</math></p>                                        | $\multimap$ is the greatest arrow into $1$ , so $(1 \times R^\circ) \multimap \sqsubseteq \multimap$                                                 |
| $\sqsubseteq$ <p style="text-align: center;"><math>\multimap \text{nil} \cup ((p \times 1) \text{cons} R^\circ)</math></p>                                      | $\text{cons length} = (1 \times \text{length}) \pi_2$<br>succ with succ monotone —<br>a shorter tail makes a shorter list                            |
| $=$ <p style="text-align: center;"><math>(\multimap \text{nil} R^\circ) \cup ((p \times 1) \text{cons} R^\circ)</math></p>                                      | $\text{nil } R^\circ = \text{nil} \triangleq \text{takewhile}$ —<br>so the constant branch may<br>carry the $R^\circ$ the other one<br>already has   |
| $=$ <p style="text-align: center;"><math>(\multimap \text{nil} \cup ((p \times 1) \text{cons})) R^\circ</math></p>                                              | one $R^\circ$ past the join is the<br>two inside it $\text{adj-all}$                                                                                 |

the  $\text{nil}$  branch, which no row above draws, is  $\text{nil} \sqsubseteq \text{nil } R^\circ$ .

| $\frac{S}{\exists} \text{est}(R^\circ) = [\text{nil}, (\pi_1 p \rightarrow \text{cons}, \neg \text{nil})]$ <span style="float: right;">(7.2.3e)</span>                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|
| the longest of the lists the algebra allows is the <b>cons</b> where the head passes <b>p</b> , and <b>nil</b> where it does not                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                |
| formula                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | reason                         |
| $\begin{array}{c} A \\ [A] \end{array} \left[ \frac{1}{\exists} \right] \text{PF}[A] \text{---} E(S) \text{---} P[A] \text{---} \text{est}(R^\circ) \text{---} [A]$                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                |
| $= F[A] \left\{ \begin{array}{l} \begin{array}{c} l \\ [A] \end{array} \left[ \frac{1}{\exists} \right] p1 \text{---} E(\text{nil}) \text{---} P[A] \text{---} \text{est}(R^\circ) \text{---} [A] \\ \begin{array}{c} r \\ [A] \end{array} \begin{array}{c} A \\ [A] \end{array} \left[ \frac{1}{\exists} \right] P(A \times [A]) \text{---} E(\neg \text{nil} \cup ((p \times 1) \text{cons})) \text{---} P[A] \text{---} \text{est}(R^\circ) \end{array} \right\}$ $[\frac{\text{nil}}{\exists} \text{est}(R^\circ), \frac{\neg \text{nil} \cup ((p \times 1) \text{cons})}{\exists} \text{est}(R^\circ)]$ | coproduct of maps              |
| $= F[A] \left\{ \begin{array}{l} \begin{array}{c} l \\ [A] \end{array} \text{nil} \text{---} [A] \\ \begin{array}{c} r \\ [A] \end{array} \begin{array}{c} A \\ [A] \end{array} \left[ \frac{1}{\exists} \right] P(A \times [A]) \text{---} E(\neg \text{nil} \cup ((p \times 1) \text{cons})) \text{---} P[A] \text{---} \text{est}(R^\circ) \end{array} \right\}$ $[\text{nil}, \frac{\neg \text{nil} \cup ((p \times 1) \text{cons})}{\exists} \text{est}(R^\circ)]$                                                                                                                                      | singleton, $R^\circ$ reflexive |
| $= F[A] \left\{ \begin{array}{l} \text{nil} \text{---} [A] \\ \begin{array}{c} A \\ [A] \end{array} (\pi_1 p \rightarrow \text{cons}, \neg \text{nil}) \text{---} [A] \end{array} \right\}$                                                                                                                                                                                                                                                                                                                                                                                                                  | $\text{nil } R = T$            |

the set is  $\{\text{nil}\}$  where  $p$  fails on the head and  $\{\text{nil}, \text{cons}(a, xs)\}$  where it holds, and  $\text{nil}$  loses the second —  $\triangleq \text{est}$  at a two-element set.

(7.2.3f)


| name | definition                                                                                | type                   | example                                                          | in words                                                                   |
|------|-------------------------------------------------------------------------------------------|------------------------|------------------------------------------------------------------|----------------------------------------------------------------------------|
| S    | $[\text{nil}, \neg \text{nil} \cup (p \times 1) \text{cons}] \triangleq \text{takewhile}$ | $F[A] \rightarrow [A]$ | $(4, [2]) \text{ S } [4, 2]$ , and $(3, [2]) \text{ S nil only}$ | prefix's algebra with one extra $p$ — stop, or keep a head that passes $p$ |

$$\text{takewhile} \triangleq \frac{\text{prefix list}(p)}{\exists} \text{est}(R^\circ)$$

Exercise 7.39

$$\text{takewhile} = ([\text{nil}, (\pi_1 p \rightarrow \text{cons}, \neg \text{nil})])$$

**takewhile:**  $\text{takewhile}(p)(x)$  returns the longest prefix of  $x$  with the property that all its elements satisfy  $p$ ; the catamorphism is the standard implementation.

 $\triangleq \text{est}$ 

|     |                                                                        |                                        |
|-----|------------------------------------------------------------------------|----------------------------------------|
| (a) | $\frac{\text{prefix list}(p)}{\exists} \text{est}(R^\circ)$            | (7.2.3c)                               |
| (b) | $= \frac{([S])}{\exists} \text{est}(R^\circ)$                          | greedy theorem at $R^\circ$ — (7.2.3d) |
| (c) | $\sqsubseteq \frac{([S])}{\exists} \text{est}(R^\circ)$                | (7.2.3e)                               |
| (d) | $= ([\text{nil}, (\pi_1 p \rightarrow \text{cons}, \neg \text{nil})])$ |                                        |

$\text{takewhile}(p)^\circ \text{takewhile}(p) \sqsubseteq \text{prefix}^\circ \text{prefix} \cap R \cap R^\circ \sqsubseteq 1$   
 $\text{takewhile}(p) \sqsubseteq \text{prefix list}(p)$  and  $(\text{prefix list}(p))^\circ \text{takewhile}(p) \sqsubseteq R$  — (7.5) at  $\text{est}(R^\circ)$  — and two prefixes of one list of equal length are equal, so  $\text{takewhile}(p)$  is simple: the longest, not a longest.

$\frac{\text{prefix list}(p)}{\exists} \text{est}(R^\circ)$  entire  
 $\text{nil}$  is always a  $p$ -prefix and  $R$  is connected on the prefixes of one list, so the longest exists.

$$X \sqsubseteq Y, X \text{ entire}, Y \text{ simple} \implies X = Y$$

$([\text{nil}, (\pi_1 p \rightarrow \text{cons}, \neg \text{nil})])$  is a reduce of maps, hence entire — what turns the  $\sqsubseteq$  above into the heading's  $=$ .

**§7.2.4.  $\text{mss} = ([\text{zero}(1, \frac{1}{2}), ((1 \times \pi_1) \oplus, ((1 \times \pi_1) \oplus \frac{1}{2}, \pi_2 \pi_2) \text{cup})]) \pi_2 \text{est}(\geq)$**

(7.2.4a)





$\text{FX} = 1 + A \times X$ ,  $\alpha \triangleq [\text{nil}, \text{cons}]$ ,  $\text{sum} = ([\text{zero}, \text{plus}])$  and  $\text{segment} = \text{suffix prefix}$  from cata-examples and (7.2.5e).

$\text{head} \triangleq \text{cons}^\circ \pi_1$ ,  $\text{wrap} \triangleq (1, \neg \text{nil}) \text{cons}$  the head of a list and the one-element list, beside  $\triangleq \text{subseq's tail} \triangleq \text{cons}^\circ \pi_2$

$\oplus \triangleq \frac{\neg \text{zero} \cup \text{plus}}{\exists} \text{est}(\geq)$  the set at  $(a, b)$  is  $\{0, a+b\}$ , so  $\oplus$  is the larger of the two,

| $\text{mss} = \frac{\text{suffix}}{\exists} E\left(\frac{\text{prefix sum}}{\exists} \text{est}(\geq)\right) \text{est}(\geq) \quad (7.2.4b)$                                                         |                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| maximum segment sum problem: using <b>segment=suffix prefix</b> , the specification is expressed in this form                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                       |
| formula — one wire from [A] to A, its type written along it                                                                                                                                           | reason                                                                                                                                                                                                                                                                                                                                                                                |
| $[A] \xrightarrow{\frac{1}{\exists}} P[A] \xrightarrow{E(\text{segment sum})} PA \xrightarrow{\text{est}(\geq)} A$                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                       |
| $= [A] \xrightarrow{\frac{1}{\exists}} P[A] \xrightarrow{E(\text{suffix prefix sum})} PA \xrightarrow{\text{est}(\geq)} A$                                                                            | <b>segment=suffix prefix</b><br>(7.2.5e), $\triangleq \text{mss}$                                                                                                                                                                                                                                                                                                                     |
| $= [A] \xrightarrow{\frac{1}{\exists}} E(\text{suffix}) P[A] \xrightarrow{E(\text{prefix sum})} PA \xrightarrow{\text{est}(\geq)} A$                                                                  | <b>absorption</b><br>pow-laws — $\text{frac}(S, \exists)$<br>$E(R) = \text{frac}(SR, \exists)$ at<br>$S := \text{suffix}, R := \text{prefix sum}$                                                                                                                                                                                                                                     |
| $= [A] \xrightarrow{\frac{1}{\exists}} E(\text{suffix}) P[A] \xrightarrow{E\left(\frac{\text{prefix sum}}{\exists}\right)} PPA \xrightarrow{\text{union}} PA \xrightarrow{\text{est}(\geq)} A$        | $\frac{R}{\exists} \exists = R, \text{union} = E(\exists)$<br>pow-laws's<br>$\text{frac}(R, \exists) \exists = R$ at<br>$R := \text{prefix sum}$ and<br>$E(R) \triangleq \text{frac}(\exists R, \exists)$ ;<br>(7.1b)'s<br>$\text{union} \triangleq \text{frac}(\exists \exists, \exists)$ ; the<br>middle equality is $\triangleq$<br>relator's<br>$F(RS) = F(R)F(S)$ at<br>$F := E$ |
| $= [A] \xrightarrow{\frac{1}{\exists}} E(\text{suffix}) P[A] \xrightarrow{E\left(\frac{\text{prefix sum}}{\exists}\right)} PPA \xrightarrow{E(\text{est}(\geq))} PA \xrightarrow{\text{est}(\geq)} A$ | (7.1b), the sets non-<br>empty                                                                                                                                                                                                                                                                                                                                                        |
| $= [A] \xrightarrow{\frac{1}{\exists}} E(\text{suffix}) P[A] \xrightarrow{E\left(\frac{\text{prefix sum}}{\exists} \text{est}(\geq)\right)} PA \xrightarrow{\text{est}(\geq)} A$                      | <b>relator</b><br>$\triangleq \text{relator}$ —<br>$F(RS) = F(R)F(S)$ at<br>$F := E$                                                                                                                                                                                                                                                                                                  |

The **union** step is (7.1b)'s  $P(\text{est}(R)) \text{est}(R) = P(\text{dom}(\text{est}(R))) \text{union} \text{est}(R)$  — every suffix has the empty prefix, so **Dom** is **1** here — and  $P(f) = E(f)$  at the map it is applied to (powrel-laws).

| $[nil, \multimap nil \cup cons] \text{ sum} = F(\text{sum}) \text{ S}$ <span style="float: right;">(7.2.4c)</span>                                                                                   |                                                                                                                                                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fusion: <b>prefix</b> expressed as a catamorphism on cons-lists, $([nil, \multimap nil \cup cons])$ , and this is the fusion condition that expresses <b>prefix sum</b> as a catamorphism            |                                                                                                                                                                                       |
| <b>circuit</b> — the fork is the bracket's case split $F([A])=1+A \times [A]$ : nil above, the pair and its $u$ below                                                                                | <b>Hinze–Marsden</b>                                                                                                                                                                  |
| <br>$[nil, \multimap nil \cup cons] \text{ sum}$                                                                    | <br>the <b>cons</b> operand of $\multimap nil \cup cons$                                           |
| <br>$[nil \text{ sum}, \multimap nil \text{ sum} \cup cons \text{ sum}]$<br>coproduct of maps, composition over $u$ |                                                                                                                                                                                       |
| <br>$[zero, \multimap zero \cup (1 \times sum) \text{ plus}]$<br>sum's defining equation                          | <br>the $(1 \times sum)$ <b>plus</b> operand of $\multimap zero \cup (1 \times sum)$ <b>plus</b> |
| <br>$[zero, (1 \times sum) (\multimap zero \cup plus)]$<br>$(1 \times sum) \multimap = \multimap$ , sum entire    |                                                                                                                                                                                       |
| <br>$F(\text{sum}) [zero, \multimap zero \cup plus]$<br>relator                                                   |                                                                                                                                                                                       |

fusion at  $R := [nil, \multimap nil \cup cons]$ ,  $S := \text{sum}$ : the side condition, so **prefix sum**  $= ([zero, \multimap zero \cup plus])$ . **prefix** is the reduce, **sum** the map fused into it — the intermediate list is gone.


$$(1 \times \geq)(\neg \text{zero} \cup \text{plus})E(\neg \text{zero} \cup \text{plus})\geq$$

(7.2.4d)

monotonic algebra: an **F**-algebra **S** is monotonic on a relation **R** if  $F(R)SESR$  — the **plus** branch of  $F(\geq)SE\geq$ ; the **zero** branch is  $\text{zero}E\text{zero}\geq$

**circuit** — the head above, the running sum below; the tape is the  $u$

$$(1 \times \geq)(\neg \text{zero} \cup \text{plus}) \quad ((1 \times \geq) \neg \text{zero}) \cup ((1 \times \neg \text{zero} \cup (\text{plus} \geq) \geq) \text{plus}) \quad (\neg \text{zero} \cup \text{plus}) \geq$$



dom-slide,  $(\geq \times \geq)$   
 $\text{plus} \sqsubseteq \text{plus} \geq$ ;  $(\leq \times \leq)$   
 $\text{plus} \sqsubseteq \text{plus} \leq$  is  $\triangleq$  monotonic,  
 written  $+$  there, and **plus** is  
 a map, so it is monotonic on  
 an order and on its opposite  
 together, which carries it to  $\geq$ .



$$\frac{S}{\geq} \text{est}(\geq) = [\text{zero}, \oplus]$$

(7.2.4e)

the largest sum the algebra offers is zero from nothing and, from a head and a running sum, the larger of zero and the head added to it


**circuit** — the tape is the coproduct:  
 zero's branch above, plus's below

Hinze–Marsden



the **zero** arm of the bracket


$$\begin{aligned} & \begin{array}{c} A \\ A \end{array} \begin{array}{c} \boxed{\frac{1}{3}} \\ \boxed{\frac{1}{3}} \end{array} \begin{array}{c} \text{PFA}^2 \\ \text{PA}^2 \end{array} \begin{array}{c} \boxed{E(\text{plus})} \\ \boxed{E(\neg \text{zero} \cup \text{plus})} \end{array} \begin{array}{c} \text{PA} \\ \text{PA} \end{array} \begin{array}{c} \boxed{\text{est}(\geq)} \\ \boxed{\text{est}(\geq)} \end{array} \begin{array}{c} A \\ A \end{array} \\ & \frac{[\text{zero} \ni \text{est}(\geq), \neg \text{zero} \cup \text{plus} \ni \text{est}(\geq)]}{\ni} \\ & = \text{coproduct of maps — coprod-calc at} \\ & \text{T} := [\text{zero}, \neg \text{zero} \cup \text{plus}], \text{ then} \\ & [U, V]Z = [UZ, VZ] \text{ — coprod-laws,} \\ & \text{composition over } U \end{aligned}$$



the **plus** operand of the lower arm's  $\neg \text{zero} \cup \text{plus}$ , under its  $1 \ni E(\dots)$  and  $\text{est}(\geq)$

$$\begin{array}{c} \text{FA} \\ \text{FA} \end{array} \begin{array}{c} \boxed{l} \text{ zero} \\ \boxed{r} \end{array} \begin{array}{c} \boxed{\frac{1}{3}} \\ \boxed{\frac{1}{3}} \end{array} \begin{array}{c} \text{PA}^2 \\ \text{PA}^2 \end{array} \begin{array}{c} \boxed{E(\neg \text{zero} \cup \text{plus})} \\ \boxed{E(\neg \text{zero} \cup \text{plus})} \end{array} \begin{array}{c} \text{PA} \\ \text{PA} \end{array} \begin{array}{c} \boxed{\text{est}(R)} \\ \boxed{\text{est}(R)} \end{array} \begin{array}{c} A \\ A \end{array}$$

= singleton,  $\geq$  reflexive — (7.1b)'s  $\frac{1}{3}$   
 $\text{est}(R) = 1 \cap R$  at  $R := \geq$ , **zero** a map; the  
 lower branch is  $\oplus$ 's definition,  $\triangleq$  **mss**, and no  
 law



with (7.2.4d) the greedy theorem gives  $([\text{zero}, \oplus]) \sqsubseteq \frac{\text{prefix sum}}{\ni} \text{est}(\geq)$  — and Exercise 7.40 makes it an equality.

$$[\text{nil}, \text{cons}] \left( \langle \langle [\text{zero}, \emptyset] \rangle, \frac{\text{suffix}}{\exists} E(\langle \langle [\text{zero}, \emptyset] \rangle \rangle) \rangle = F(\langle \langle [\text{zero}, \emptyset] \rangle, \frac{\text{suffix}}{\exists} E(\langle \langle [\text{zero}, \emptyset] \rangle \rangle) \rangle) k \quad (7.2.4f)$$

$k \triangleq [\text{zero} \langle 1, \frac{1}{\exists} \rangle, \langle w, \langle w \frac{1}{\exists}, \pi_2 \pi_2 \rangle \text{cup} \rangle], w \triangleq (1 \times \pi_1) \oplus$ : the value at the whole list, paired with the set of the values at its suffixes, runs  $k$ 's recursion.

the equation at that branch

$$\text{nil}(g, \frac{\text{suffix}}{\exists} E(g)) = \text{zero} \langle 1, \frac{1}{\exists} \rangle$$

$$\text{cons}(g, \frac{\text{suffix}}{\exists} E(g)) = (1 \times \langle g, \frac{\text{suffix}}{\exists} E(g) \rangle) \langle w, \langle w \frac{1}{\exists}, \pi_2 \pi_2 \rangle \text{cup} \rangle$$

why


$\text{nil}$  has one suffix, itself, and  $g(\text{nil}) = \text{zero}$ , so the set is the singleton  $\{\text{zero}\}$

$g(\text{cons}(a, x)) = a \oplus (g(x))$ , which is  $w$  reading  $g(x)$  off  $\pi_1$ ; and the suffixes of  $\text{cons}(a, x)$  are  $\text{cons}(a, x)$  itself, whose value is that same  $w$ , together with those of  $x$ , which  $\pi_2 \pi_2$  carries — so the two sets meet at  $\text{cup}$

$$\text{mss} = \langle k \rangle \pi_2 \text{est}(\geq)$$

Exercise 7.40

maximum segment sum problem:  $\frac{\text{suffix}}{\exists} E(\langle \langle [\text{zero}, \emptyset] \rangle \rangle)$  expressed as the catamorphism  $\langle k \rangle$ , hence  $\text{mss}$  implemented by a linear-time algorithm,  $\oplus \triangleq \frac{\text{zero} \cup \text{plus}}{\exists} \text{est}(\geq) \triangleq \text{mss}; k \text{ and } w \text{ — (7.2.4f).}$



|     |                                                                                                          |                                                                                                                     |
|-----|----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| (a) | $\text{mss}$                                                                                             | $\text{mss} = \frac{\text{suffix}}{\exists} E(\frac{\text{prefix sum}}{\exists} \text{est}(\geq)) \text{est}(\geq)$ |
| (b) | $= \frac{\text{suffix}}{\exists} E(\frac{\text{prefix sum}}{\exists} \text{est}(\geq)) \text{est}(\geq)$ | $\frac{\text{prefix sum}}{\exists} \text{est}(\geq) = \langle [\text{zero}, \emptyset] \rangle$                     |
| (c) | $= \frac{\text{suffix}}{\exists} E(\langle [\text{zero}, \emptyset] \rangle) \text{est}(\geq)$           | $\langle k \rangle \pi_2 = \frac{\text{suffix}}{\exists} E(\langle [\text{zero}, \emptyset] \rangle)$               |
| (d) | $= \langle k \rangle \pi_2 \text{est}(\geq)$                                                             |                                                                                                                     |

one fold builds the  $n+1$  running maxima and the final  $\text{est}(\geq)$  reads them in one more pass, so  $\text{mss}$  is linear.

§7.2.5.  $\text{filter}(p) = ([\text{nil}, (\pi_1 p \rightarrow \text{cons}, \pi_2)])$ 


(7.2.5a)

| name                                       | definition                                                             | type                           | example                                                              | in words                                                                                                                                                              |
|--------------------------------------------|------------------------------------------------------------------------|--------------------------------|----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| $F, \alpha, p, R$                          | as in $\trianglelefteq$ takewhile                                      |                                |                                                                      |                                                                                                                                                                       |
| $\pi_2$                                    | $\pi_2$ where $\trianglelefteq$ takewhile has $\rightarrow \text{nil}$ | $A \times [A] \rightarrow [A]$ | $\pi_2(3, [1, 2]) = [1, 2]$                                          | drop the head, keep the tail                                                                                                                                          |
| subseq                                     | $([\text{nil}, \pi_2 \cup \text{cons}]) \trianglelefteq \text{subseq}$ | $[A] \rightarrow [A]$          | $[3, 1, 2] \text{ subseq } [3, 2]$                                   | $xs \text{ subseq } ys \iff ys \text{ is } xs \text{ with elements dropped}$ — at each $\text{cons}$ , drop the head or keep it                                       |
| $S$                                        | $[\text{nil}, \pi_2 \cup (p \times 1) \text{ cons}]$                   | $F[A] \rightarrow [A]$         | $(4, [2]) S [2]$ and $(4, [2]) S [4, 2]$ , but $(3, [2]) S [2]$ only | subseq's algebra with one extra $p$ — drop the head, or keep a head that passes $p$                                                                                   |
| $1 \sqsubseteq \pi_2 R \text{ cons}^\circ$ |                                                                        |                                |                                                                      | the tail is one shorter than the $\text{cons}$ , so $\pi_2$ loses the $\text{est}(R^\circ)$ at every step — where $\trianglelefteq$ takewhile's loser is $\text{nil}$ |

$$(1 \times R^\circ)(\pi_2 \cup (p \times 1) \text{ cons}) \sqsubseteq (\pi_2 \cup (p \times 1) \text{ cons}) R^\circ$$

(7.2.5b)

shortening the tail and then taking the step lands inside taking the step and then shortening the result

**formula** — the  $\text{cons}$  branch of  $F(R^\circ) S \sqsubseteq SR^\circ$ ; **reason** under each circuitthe  $\text{nil}$  branch:  $\text{nil} \sqsubseteq \text{nil } R^\circ$ .

| $\frac{S}{\text{est}(R^\circ) = [\text{nil}, (\pi_1 p \rightarrow \text{cons}, \pi_2)]}$ <div>the longest of the lists the algebra allows is the <b>cons</b> where the head passes <b>p</b>, and the tail where it does not</div> |                                                                                                                                                                                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| formula                                                                                                                                                                                                                           | reason                                                                                                                                                                                                                                                                      |
|                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                             |
|                                                                                                                                                                                                                                   | $S = [\text{nil}, \pi_2 \cup (p \times 1) \text{ cons}] \triangleq \text{filter} \text{ — and the } \% \exists \text{ of a coproduct of maps is the coproduct of their } \% \exists \text{ coprod-calc}$                                                                    |
|                                                                                                                                                                                                                                   | $\text{nil} \% \exists \text{ is the singleton } \{\text{nil}\}, \text{ and } \text{est}(R^\circ) \text{ of a singleton is its element because } R^\circ \text{ is reflexive } \triangleq \text{est}$                                                                       |
|                                                                                                                                                                                                                                   | $\frac{\pi_2 \cup (p \times 1) \text{ cons}}{\% \exists} = \left( \frac{\pi_2}{\% \exists}, \frac{(p \times 1) \text{ cons}}{\% \exists} \right) \text{ cup } \triangleq \text{cup}$                                                                                        |
|                                                                                                                                                                                                                                   | $1 \sqsubseteq \pi_2 R \text{ cons}^\circ \triangleq \text{filter} \text{ — } xs \ R \ \text{cons}(a, xs), \text{ so } \text{est}(R^\circ) \text{ returns the cons where } p \ a \text{ puts it in the set and } xs \text{ where the set is } \{xs\} \triangleq \text{est}$ |

the head is dropped, not the whole tail: that is the one place  $\pi_2$  shows against (7.2.3e)'s  $\rightarrow \text{nil}$ .

(7.2.5d)


| name | definition                                                                         | type                   | example                                                                                | in words                                                                                                 |
|------|------------------------------------------------------------------------------------|------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| S    | $[\text{nil}, \pi_2 \cup (p \times 1) \text{ cons}]$<br>$\triangleq \text{filter}$ | $F[A] \rightarrow [A]$ | $(4, [2]) \ S \ [2]$ and<br>$(4, [2]) \ S \ [4, 2]$ , but<br>$(3, [2]) \ S \ [2]$ only | <b>subseq's algebra with one extra <math>p</math></b><br>— drop the head, or keep a head that passes $p$ |

$$\text{filter} = ([\text{nil}, (\pi_1 p \rightarrow \text{cons}, \pi_2)])$$

Exercise 7.41

**filter: filter(p) x** returns the longest subsequence of **x** with the property that all its elements satisfy **p**; the catamorphism is the standard program; **R** a preorder.

(7.2.5e)



|     |                                                              |                                                  |
|-----|--------------------------------------------------------------|--------------------------------------------------|
| (a) | $\frac{\text{subseq list}(p)}{\supset} \text{est}(R^\circ)$  | $\text{subseq list}(p) = (S) \text{ — (7.2.3c)}$ |
| (b) | $= \frac{(S)}{\supset} \text{est}(R^\circ)$                  | greedy theorem at $R^\circ$ — (7.2.5b)           |
| (c) | $\equiv \frac{(S)}{\supset} \text{est}(R^\circ)$             | (7.2.5c)                                         |
| (d) | $= ([\text{nil}, (\pi_1 p \rightarrow \text{cons}, \pi_2)])$ |                                                  |

the catamorphism is entire and **filter(p)** simple, so  $\supset$  is  $=$ .

$(\text{subseq list}(p))^\circ (\text{subseq list}(p)) \cap R \cap R^\circ \subseteq 1$  fails — two **p**-subsequences of one list can be of equal length and different — so §Section 7.2.3's uniqueness argument does not transfer. What survives **est**( $R^\circ$ ) is the one keeping **exactly** the passing elements: a subsequence that drops a passing element is beaten by the one that keeps it.

(7.2.5e)

| definition                                                                                 | type                  | note                                                                                                                                  |
|--------------------------------------------------------------------------------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| <b>segment</b> = suffix prefix                                                             | $[A] \rightarrow [A]$ | A contiguous stretch of <b>xs</b> : a suffix, then a prefix of that.                                                                  |
| $\text{filter}(p) \triangleq \frac{\text{subseq list}(p)}{\supset} \text{est}(R^\circ)$    | $[A] \rightarrow [A]$ | The longest subsequence of <b>xs</b> whose every element passes <b>p</b> . $\text{est}(R^\circ)$ is $\triangleq \text{est}$           |
| $R \triangleq \text{length} \leq \text{length}^\circ$                                      | $[A] \rightarrow [A]$ | The preorder <b>filter</b> and <b>takewhile</b> maximise over: the longer list wins. $\geq \triangleq \leq^\circ$                     |
| $\text{takewhile}(p) \triangleq \frac{\text{prefix list}(p)}{\supset} \text{est}(R^\circ)$ | $[A] \rightarrow [A]$ | The same with <b>prefix</b> for <b>subseq</b> : the longest prefix whose every element passes <b>p</b> .                              |
| $\text{mss} \triangleq \frac{\text{segment sum}}{\supset} \text{est}(\geq)$                | $[A] \rightarrow A$   | Maximum segment sum. <b>segment=suffix prefix</b> splits it into $\frac{\text{prefix sum}}{\supset} \text{est}(\geq)$ on each suffix. |


## §7.3. Planning a company party

(7.3a)

| definition                                                                      | type                                              | note                                                                                           |
|---------------------------------------------------------------------------------|---------------------------------------------------|------------------------------------------------------------------------------------------------|
| $\text{tree } A ::= \text{node } (A, [\text{tree } A])$                         | $\mathcal{A} \rightarrow \mathcal{A}$             | The company hierarchy: an employee, and the list of subtrees under them.                       |
| $F(A, B) = A \times [B]$                                                        | $\mathcal{A} \rightarrow \mathcal{A}$             | The base functor <b>tree</b> folds: an employee beside the recursive position, one layer deep. |
| rating                                                                          | $A \rightarrow \text{Int}$                        | What one employee is worth as a guest.                                                         |
| $\text{cost} = \text{list}(\text{rating}) \text{ sum}$                          | $[A] \rightarrow \text{Int}$                      | What a guest list is worth.                                                                    |
| $R = \text{cost} \leq \text{cost}^\circ$                                        | $[A] \rightarrow [A]$                             | The preorder the guest list is maximised over.                                                 |
| $\text{choose} \triangleq \pi_1 \cup \pi_2$                                     | $[A] \times [A] \rightarrow [A]$                  | Takes one of the two parties a subtree returns.                                                |
| $\text{include} = (1 \times (\text{list}(\pi_2) \text{ concat})) \text{ cons}$  | $F(A, [A] \times [A]) \rightarrow [A]$            | The party that invites the root, which puts every immediate subtree's root out. A map.         |
| $\text{exclude} = (1 \times (\text{list}(\text{choose}) \text{ concat})) \pi_2$ | $F(A, [A] \times [A]) \rightarrow [A]$            | The party that leaves the root out, so each subtree is free to choose. Not a map.              |
| $S \triangleq (\text{include}, \text{exclude})$                                 | $F(A, [A] \times [A]) \rightarrow [A] \times [A]$ | The algebra: one step returns both parties of a subtree at once.                               |
| $\text{party} = \langle S \rangle \text{ choose}$                               | $\text{tree}(A) \rightarrow [A]$                  | Every guest list the president's ruling allows.                                                |
| the specification<br>$\frac{\text{party}}{\exists} \text{ est}(R^\circ)$        | $\text{tree}(A) \rightarrow [A]$                  | A guest list of greatest total conviviality.                                                   |

## §7.3.1. include and exclude

(7.3.1a)




the small grey number is the employee's rating

(7.3.1b)

| node    | the algebra's input<br>$A \times [[A] \times [A]]$ | include                                         | exclude                                |
|---------|----------------------------------------------------|-------------------------------------------------|----------------------------------------|
| d, e, f | $(d, [])$                                          | $[d]$                                           | $[]$                                   |
| b       | $(b, ([d], []), ([e], []))$                        | $[b]$                                           | $[d, e], [d], [e], []$                 |
| c       | $(c, ([f], []))$                                   | $[c]$                                           | $[f], []$                              |
| a       | $(a, ([b], \dots), ([c], \dots))$                  | $[a] \# \text{exclude}(b) \# \text{exclude}(c)$ | $\text{choose}(b) \# \text{choose}(c)$ |

with those ratings,  $\text{est}(R^\circ)$  keeps  $([b]=7, [d, e]=6)$  at **b**, where **include** wins, and  $([c]=2, [f]=8)$  at **c**, where **exclude** wins, so at the root  $\text{include}=[a, d, e, f]=17$  beats  $\text{exclude}=[b, f]=15$ , and **choose** takes 17.

(7.3.1c)



$$\begin{array}{c} A \\ \hline [A]^2 \xrightarrow{\text{list(choose)}} [A] \xrightarrow{\text{concat}} [A] \end{array}$$

(7.3.1d)

list(choose) [([d],[ ]), ([e],[ ])]  
 1st item ([d],[ ]) choose  $\rightarrow$  [d] or [ ]  
 2nd item ([e],[ ]) choose  $\rightarrow$  [e] or [ ]  
 2x2=4 combinations: [ [d],[e] ] [ [d],[ ] ] [ [ ],[e] ] [ [ ],[ ] ]  
 concat flattens: [d,e] [d] [e] [ ]

(7.3.1e)

### §7.3.2. $\text{list}((R \times R)^\circ)$

$$\begin{array}{c} [ ([b],[d,e]) , ([c],[f]) ] \\ \downarrow \quad \downarrow \\ [ ([b],[d]) , ([c],[ ]) ] \end{array} \quad \text{list}((R \times R)^\circ), \text{elementwise}$$

(7.3.2a)

$([b],[d,e])$   
 | — exclude: the best party in b's subtree when b does not come  
 | — include: the best party in b's subtree when b comes

(7.3.2b)

| element            | 1st component<br>include                      | 2nd component<br>exclude                                                                           |
|--------------------|-----------------------------------------------|----------------------------------------------------------------------------------------------------|
| 1st, $([b],[d,e])$ | $[b] R^\circ [b]$<br>$7 \geq 7$ , reflexivity | $[d,e] R^\circ [d]$<br>$6 \geq 5$ , and $([b],[d,e])$ is the pair $\text{est}(R^\circ)$ keeps at b |
| 2nd, $([c],[f])$   | $[c] R^\circ [c]$<br>$2 \geq 2$ , reflexivity | $[f] R^\circ [ ]$<br>$8 \geq 0$ , and $([c],[f])$ is the pair $\text{est}(R^\circ)$ keeps at c     |

the first component of  $1 \times \text{list}((R \times R)^\circ)$  is the root employee.

$R \triangleq \text{cost} \leq \text{cost}^\circ$  is a preorder, so the components that do not move are related by reflexivity —  $(R \times R)^\circ$  demands a relation in **both** components, it cannot skip one.

$R$  compares cost only, not contents:  $[f] R^\circ [ ]$  is legal though  $[f]$  has an element  $[ ]$  does not. That is why the three leaves of §Section 7.3.3's proof all reduce to “**cost** is a sum”.

### §7.3.3. $(1 \times \text{list}((R \times R)^\circ)) S \sqsubseteq S(R \times R)^\circ$ — $S : F([A] \times [A]) \rightarrow [A] \times [A]$ monotonic on $(R \times R)^\circ$

(7.3.3a)



(7.3.3b)

$$\begin{array}{ccc} \text{tree}(A) & \xrightarrow{\frac{(S) \text{choose}}{\exists}} P[A] & \text{tree}(A) \xrightarrow{\frac{(S)}{\exists}} P([A] \times [A]) \xrightarrow{E(\text{choose})} P[A] \\ \frac{(S) \text{choose}}{\exists} & = & \frac{(S)}{\exists} E(\text{choose}) \quad \text{pow-laws, absorption,} \end{array}$$

$$\begin{aligned}
S &\triangleq \{\text{include}, \text{exclude}\} \\
(1 \times \text{list}((R \times R)^\circ)) S &\sqsubseteq S (R \times R)^\circ \\
(1 \times \text{list}((R \times R)^\circ)) \text{include} &\sqsubseteq \text{include } R^\circ \\
(1 \times \text{list}((R \times R)^\circ)) \text{exclude} &\sqsubseteq \text{exclude } R^\circ
\end{aligned}
\tag{7.3.3c}$$

bettering both parties of every subtree before the node's algebra runs gets no further than running it first and bettering the two parties it returns,



|     |                                                                                           |  |
|-----|-------------------------------------------------------------------------------------------|--|
| (a) | $(1 \times \text{list}((R \times R)^\circ)) (1 \times (\text{list}(g) \text{ concat})) h$ |  |
| (b) | $\sqsubseteq (1 \times (\text{list}(g R^\circ) \text{ concat})) h$                        |  |
| (c) | $\sqsubseteq (1 \times (\text{list}(g) \text{ concat } R^\circ)) h$                       |  |
| (d) | $\sqsubseteq (1 \times (\text{list}(g) \text{ concat})) h R^\circ$                        |  |

$g \quad (R \times R)^\circ g \sqsubseteq g R^\circ$   
 $g := \pi_2$  is  $(R \times R)^\circ \pi_2 = (\text{dom}(\pi_1 R^\circ)) \pi_2 R^\circ \sqsubseteq \pi_2 R^\circ$ ,  $g := \pi_1$  its mirror  $(\text{dom}(\pi_2 R^\circ)) \pi_1 R^\circ \sqsubseteq \pi_1 R^\circ$  — 1 and 4 of bdm-prod-laws, then  $\text{dom} \sqsubseteq 1$ ;  $g := \text{choose} \triangleq \pi_1 \cup \pi_2$  is the union of the two lax-closure. **list** monotonic,  $\triangleq$  relator  
**concat**  $\text{list}(R^\circ) \text{ concat} \sqsubseteq \text{concat } R^\circ$   
a LEAF: no law above it. **cost** is a sum, so  $\text{cost}(\text{concat}(xss)) = \text{sum}(\text{list}(\text{cost})(xss))$  and a cheaper part makes a cheaper whole.  
 $h \quad (1 \times R^\circ) h \sqsubseteq h R^\circ$   
a LEAF:  $\text{cost}(\text{cons}(a, xs)) = \text{rating}(a) + \text{cost}(xs)$ , so a cheaper tail makes a cheaper list. For  $h := \pi_2$  it is an EQUALITY  $(1 \times R^\circ) \pi_2 = (\text{dom}(\pi_1)) \pi_2 R^\circ = \pi_2 R^\circ$  :  $\pi_1$  is a map, hence entire, so  $\text{dom}(\pi_1) = 1$  — dom-laws

|                                                |               |             |
|------------------------------------------------|---------------|-------------|
| $(1 \times (\text{list}(g) \text{ concat})) h$ | $g$           | $h$         |
| <b>include</b>                                 | $\pi_2$       | <b>cons</b> |
| <b>exclude</b>                                 | <b>choose</b> | $\pi_2$     |

(7.3.3d)


|                                                                           |                                                                                                                                     |
|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| $R \triangleq \{(\emptyset, \emptyset)\} : \{0, 1\} \rightarrow \{0, 1\}$ | not entire — undefined at 1                                                                                                         |
| $(R \times R) \text{ choose}$ at $(\emptyset, 1)$                         | nothing — $R \times R$ needs BOTH components related, and $R$ is undefined at 1                                                     |
| $\text{choose } R$ at $(\emptyset, 1)$                                    | $\emptyset$ — <b>choose</b> picks the first component $\emptyset$ , and $R \emptyset \emptyset$ holds                               |
| $((\emptyset, 1), \emptyset)$                                             | in <b>choose</b> $R$ , not in $(R \times R) \text{ choose}$                                                                         |
| $(R \times R) \text{ choose} = \text{choose } R$                          | iff $R$ is entire — $\text{dom} \sqsubseteq 1$ is the $g$ row's only inequality step, and it is an equality iff $\text{dom}(R) = 1$ |

#### §7.3.4. The derivation

$$(\langle \text{include}, \pi_2 \text{ list}(\frac{\text{choose}}{\exists} \text{ est}(R^\circ)) \text{ concat} \rangle) \frac{\text{choose}}{\exists} \text{ est}(R^\circ) \sqsubseteq \frac{\text{party}}{\exists} \text{ est}(R^\circ) \quad (7.3.4a)$$


the best of every guest list the president allows is one pass up the tree, each subtree handing up its best party with its boss in and its best with the boss out, and **choose** taking the better of the two at the root

$\triangleq \text{party}$



|     |                                                                                                                      |                                                                                                                                            |
|-----|----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| (a) | $\frac{\text{party}}{\exists} \text{ est}(R^\circ)$                                                                  | $\text{party} \triangleq (S) \text{ choose}, \frac{(S)}{\exists} \text{ choose} = \frac{(S)}{\exists} E(\text{choose}) \text{ — (7.3.3b)}$ |
| (b) | $= \frac{(S)}{\exists} E(\text{choose}) \text{ est}(R^\circ)$                                                        | $(R \times R)^\circ \text{ choose} \sqsubseteq \text{choose } R^\circ \text{ — (7.3.3c)}$                                                  |
| (c) | $\sqsubseteq \frac{(S)}{\exists} \text{ est}((R \times R)^\circ) \frac{\text{choose}}{\exists} \text{ est}(R^\circ)$ |                                                                                                                                            |

(7.3.4b)



|     |                                                                                                                                                                                                           |                                                                                                                                                                              |
|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (a) | $\sqsubseteq \frac{(S)}{\exists} \text{ est}((R \times R)^\circ) \frac{\text{choose}}{\exists} \text{ est}(R^\circ)$                                                                                      | $(\frac{\text{include}}{\exists} \text{ est}(R^\circ), \frac{\text{exclude}}{\exists} \text{ est}(R^\circ)) \sqsubseteq \frac{(S)}{\exists} \text{ est}((R \times R)^\circ)$ |
| (b) | $\sqsubseteq \langle \langle \frac{\text{include}}{\exists} \text{ est}(R^\circ), \frac{\text{exclude}}{\exists} \text{ est}(R^\circ) \rangle \rangle \frac{\text{choose}}{\exists} \text{ est}(R^\circ)$ | include a map                                                                                                                                                                |
| (c) | $\sqsubseteq \langle \langle \text{include}, \frac{\text{exclude}}{\exists} \text{ est}(R^\circ) \rangle \rangle \frac{\text{choose}}{\exists} \text{ est}(R^\circ)$                                      | $\pi_2 \text{ list}(\frac{\text{choose}}{\exists} \text{ est}(R^\circ)) \text{ concat} \sqsubseteq \frac{\text{exclude}}{\exists} \text{ est}(R^\circ)$                      |
| (d) | $\sqsubseteq \langle \langle \text{include}, \pi_2 \text{ list}(\frac{\text{choose}}{\exists} \text{ est}(R^\circ)) \text{ concat} \rangle \rangle \frac{\text{choose}}{\exists} \text{ est}(R^\circ)$    |                                                                                                                                                                              |

## §7.4. Shortest paths on a cylinder

(7.4a)

|                                                                     | on $L = \text{list}^+$ , sec-cyl-gen                                                                                                | on $\text{Vec}$                                                                                                                                                                    | note                                                                                                                                           |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| $F$                                                                 | $F(A, X) = A + A \times X$                                                                                                          | $F(A, A[m]) = A[1] + A[m+1]$                                                                                                                                                       | A square alone, or in front of the path so far.                                                                                                |
| the input                                                           | $L(N\ A)$                                                                                                                           | $A[m][n] \triangleq (A[n])[m]$                                                                                                                                                     | $m$ columns of $n$ squares, outermost index first — the matrix itself.                                                                         |
| a path                                                              | $L\ A$ , a non-empty list                                                                                                           | $A[1] \triangleq A, A[m+1] \triangleq A \times A[m]$                                                                                                                               | Through $m$ columns, $m$ squares: the count is in the type. A one-square path is the square; $\text{Vec}(m)$ is the functor $X \mapsto X[m]$ . |
| the paths into a row                                                | $P(L\ A)$                                                                                                                           | $A[p][m], p = 3^{m-1}$                                                                                                                                                             | Three moves per column crossed, so this count is in the type too; a set forgets it.                                                            |
| $\alpha$                                                            | $[\text{wrap}, \text{cons}]$<br>$F(A, LA) \rightarrow LA$                                                                           | $\text{wrap} = 1 : A \rightarrow A[1]$<br>$\text{cons} : A \times A[m] \rightarrow A[m+1]$                                                                                         | $\text{wrap}$ is an identity; $\text{cons}$ is only an iso, so it stays a bead.                                                                |
| moves                                                               | $NA \rightarrow PNA$                                                                                                                | $X[n] \rightarrow X[3][n]$                                                                                                                                                         | $\text{moves}(x) = (\text{up}(x), x, \text{down}(x))$ , a $3 \times n$ matrix.                                                                 |
| trans                                                               | $PNX \rightarrow NPX$                                                                                                               | $X[3][n] \rightarrow X[n][3]$                                                                                                                                                      | The transpose.                                                                                                                                 |
| union                                                               | $PPX \rightarrow PX$                                                                                                                | $\text{concat} : X[j][k] \rightarrow X[jk]$                                                                                                                                        | The $j$ rows laid end to end; $j$ is 3 inside <b>gen</b> and $n$ inside <b>paths</b> .                                                         |
| zip                                                                 | $F(NA, NB) \rightarrow NF(A, B)$                                                                                                    | $F(A[n], B[n]) \rightarrow F(A, B)[n]$                                                                                                                                             | Unchanged.                                                                                                                                     |
| cp                                                                  | $F(A, PB) \rightarrow P(F(A, B))$                                                                                                   | $A \times B[p] \rightarrow (A \times B)[p]$                                                                                                                                        | The square paired with each of the $p$ candidates.                                                                                             |
| $\text{est}(R) \triangleq \exists n (\in \text{PPX} \rightarrow X)$ |                                                                                                                                     | $X[k] \rightarrow X, \exists : X[k] \rightarrow X$                                                                                                                                 | A component that is $R$ -below every component; $\exists$ is “is some component” and $\in$ its converse.                                       |
| $R \triangleq \text{sum} \leq \text{sum}^\circ$                     | $L\ \text{Nat} \rightarrow L\ \text{Nat}$                                                                                           | $\text{Nat}[m] \rightarrow \text{Nat}[m]$                                                                                                                                          | The cost of a path, which the cheapest minimises — one order per length $m$ .                                                                  |
| gen                                                                 | $F(1, \text{moves trans } N(\text{union}))$<br>$\text{zip } N(\text{cp } P(\alpha))$<br>$F(NA, N(P(LA)))$<br>$\rightarrow N(P(LA))$ | $F(1, \text{moves trans } \text{Vec}(n)(\text{concat}))$<br>$\text{zip } \text{Vec}(n)(\text{cp } \text{Vec}(3p)(\text{cons}))$<br>$F(A[n], A[n][p][m]) \rightarrow A[n][3p][m+1]$ | The same composite without $\alpha$ ; the type shown is the $\text{cons}$ side, the $\text{wrap}$ side is $1 : A[n] \rightarrow A[n]$ .        |
| $(\text{gen})$                                                      | $L(N\ A) \rightarrow N(P(L\ A))$                                                                                                    | $A[m][n] \rightarrow A[n][p][m]$                                                                                                                                                   | Columns in, rows out.                                                                                                                          |
| $\text{paths} \triangleq (\text{gen})$<br>concat                    | $(\text{gen})$ setify union<br>$L\ N\ \text{Nat} \rightarrow P(L\ \text{Nat})$                                                      | $A[m][n] \rightarrow A[np][m]$                                                                                                                                                     | The $n$ rows of $p$ paths laid end to end: every path of the cylinder, in one row.                                                             |
| $Q$ ,<br>Section 7.4.3                                              | $F(1, \text{moves trans } N(\text{est}(R)))$<br>$\text{zip } N(\alpha)$                                                             | $F(1, \text{moves trans } \text{Vec}(n)(\text{est}(R)))$<br>$\text{zip}, F(A[n], A[n][m]) \rightarrow A[n][m+1]$                                                                   | The cheapest of three; no $p$ anywhere. $(Q) : A[m][n] \rightarrow A[n][m]$ has the type of a transpose.                                       |
| the<br>specification<br>paths<br>$\text{est}(R)$                    | $L\ N\ \text{Nat} \rightarrow L\ \text{Nat}$                                                                                        | $A[m][n] \rightarrow A[m], \text{est}(R) : X[np] \rightarrow X$                                                                                                                    | A cheapest path from the entry side to the exit side.                                                                                          |

§7.4.1.  $\text{gen} \triangleq (1 \times (\text{moves trans } \text{Vec}(n)(\text{concat}))) \text{ zip } \text{Vec}(n)(\text{cp } \text{Vec}(3p)(\text{cons}))$

(7.4.1a)



(7.4.1b)

a row is the outer index, a cell one path

$u = ((1,2,3,4), C)$

$C = 5$

6

7

8

$(1 \times (\text{moves trans Vec}(n)(\text{concat})))$

$\text{moves}(C)$

$= 6 \ 7 \ 8 \ 5$

5 6 7 8

8 5 6 7

$\text{trans}(\text{that})$

$= 6 \ 5 \ 8$

7 6 5

8 7 6

5 8 7

$\text{Vec}(n)(\text{concat})(\text{that}) = \text{that}$

$\text{zip}(\text{that})$

$= (1, 6 \ 5 \ 8)$

(2, 7 6 5)

(3, 8 7 6)

(4, 5 8 7)

$\text{Vec}(n)(\text{cp})(\text{that})$

$= 1 \ 6 \ 2 \ 7 \ 3 \ 8 \ 4 \ 5$

1 5 2 6 3 7 4 8

1 8 2 5 3 6 4 7

:  $A[n] \times A[n]$

one candidate per row, one square long:

a column of squares

1 keeps the column, the candidates move down, unmoved, up: a  $3 \times n$  matrix

:  $A[3][n]$

the transpose: row  $k$  gets rows  $k-1, k, k+1$

:  $A[n][3]$

$\text{concat}: X[3][1] \rightarrow X[3]$  is 1

each row: its square, and its candidates

:  $(A \times A[3])[n]$

$\text{cp}$  pairs the square with each candidate:

row  $k$  of that is the  $k$ -th  $3 \times 2$  block, left to right; each line a two-square path

:  $A[n][3][2]$

#### §7.4.2. $\text{gen}$ is an F-algebra; $(\text{gen}): \text{cons } (\text{gen}) = (1 \times (\text{gen})) \text{gen}$

(7.4.2a)



the  $[m+1]$  bracket puts the column back on the matrix, then the fold reads all of it

the fold reads the rest under  $F$ , then one  $\text{gen}$  puts the column in front

(7.4.2b)

$xs = 1 \ 2 \ 3 \ 4$

5 6 7 8

:  $A[m][n], m=2$

$(\text{gen})(xs) = \text{gen}((1,2,3,4), (\text{gen})(5,6,7,8))$

$(\text{gen})(5,6,7,8)$

$= 5$

6

7

8

one column: each square its own one-square path

:  $A[n][1][1]$

both halves are in (7.4.1b): the tail folds to the column 5 6 7 8, one path per row and each of them one square long, and  $\text{gen}$  on it is that walk.

#### §7.4.3. $Q \triangleq (1 \times (\text{moves trans Vec}(n)(\text{est}(R)))) \text{ zip}, A[n] \times A[n][m] \rightarrow A[n][m+1]$

(7.4.3a)



$u = ((1,2,3,4),C)$

$C = 5$

6

7

8

$(1 \times (\text{moves trans Vec}(n)(\text{est}(R))))$

$\text{moves}(C)$

$= 6 \ 7 \ 8 \ 5$

$5 \ 6 \ 7 \ 8$

$8 \ 5 \ 6 \ 7$

$\text{trans}(\text{that})$

$= 6 \ 5 \ 8$

$7 \ 6 \ 5$

$8 \ 7 \ 6$

$5 \ 8 \ 7$

$\text{Vec}(n)(\text{est}(R))(\text{that})$

$= 5 \ 5 \ 6 \ 5$

$\text{zip}(\text{that})$

$= 1 \ 5$

$2 \ 5$

$3 \ 6$

$4 \ 5$

$: A[n] \times A[n][m]$

one path per row, one square long

1 keeps the column, the paths move down, unmoved, up: a  $3 \times n$  matrix

$: A[3][n][m]$

the transpose: row  $k$  gets rows  $k-1, k, k+1$

$: A[n][3][m]$

the cheapest into each row – chosen BEFORE


$: A[n][m]$  the new square is put in front each row: its square, and the one predecessor that survived; the  $[m+1]$  bracket is cons

$: A[n][m+1]$

#### §7.4.4. paths $\text{est}(R) \sqsubseteq (\text{Q}) \text{ est}(R)$

$(\forall i. 1 \sqsubseteq R) \wedge (\forall i. R \ R \sqsubseteq R) \wedge (\forall i. (1 \times R) \text{ cons} \sqsubseteq \text{cons } R) \Rightarrow (\text{Q}) \text{ est}(R) \sqsubseteq \text{paths est}(R)$  (7.4.4a)

a cheapest of all  $\text{np}$  paths of the cylinder is beaten by the greedy fold's one path per row and then a cheapest of those  $n$ , which costs  $O(n \times m)$ .



|     |                                                                       |                                                                                                                                                                                                                             |
|-----|-----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (a) | $(\text{Q}) \text{ est}(R)$                                           | $(\forall i. 1 \sqsubseteq R) \wedge (\forall i. R \ R \sqsubseteq R) \wedge (\forall i. (1 \times R) \text{ cons} \sqsubseteq \text{cons } R) \Rightarrow (\text{Q}) \sqsubseteq (\text{Q}) \text{ Vec}(n)(\text{est}(R))$ |
| (b) | $\sqsubseteq (\text{Q}) \text{ Vec}(n)(\text{est}(R)) \text{ est}(R)$ | $S \ S \sqsubseteq S \Rightarrow \text{Vec}(j)(\text{est}(S)) \text{ est}(S) \sqsubseteq \text{concat est}(S)$                                                                                                              |
| (c) | $\sqsubseteq (\text{Q}) \text{ concat est}(R)$                        | $f \ g = f \ g$                                                                                                                                                                                                             |
| (d) | $= \text{paths est}(R)$                                               |                                                                                                                                                                                                                             |

$S \ S \sqsubseteq S \Rightarrow \text{Vec}(j)(\text{est}(S)) \text{ est}(S) \sqsubseteq \text{concat est}(S)$ ,  $R$  transitive


a cheapest of each of the  $j$  rows and then a cheapest of those  $j$  is a cheapest of all  $jk$  entries laid end to end.

$(\forall i. 1 \sqsubseteq R) \wedge (\forall i. R \ R \sqsubseteq R) \wedge (\forall i. (1 \times R) \text{ cons} \sqsubseteq \text{cons } R) \Rightarrow (\text{Q}) \sqsubseteq (\text{Q}) \text{ Vec}(n)(\text{est}(R))$ ,  $R$  reflexive, transitive and monotonic

the one path per row the greedy fold keeps is one of the  $p$  that  $(\text{Q})$  generates for that row, and a cheapest of them.

$$R \sqsubseteq R \wedge (1 \times R) \text{ cons } \sqsubseteq \text{ cons } R \Rightarrow (1 \times \text{Vec}(n)(\text{est}(R))) Q \sqsubseteq \text{gen Vec}(n)(\text{est}(R)) \quad (7.13)$$

choosing a cheapest of each square's  $\mathbf{p}$  paths before the column is extended is no better than extending first and choosing among the  $3\mathbf{p}$ .



|     |                                                         |                                       |
|-----|---------------------------------------------------------|---------------------------------------|
| (a) | $\text{gen Vec}(n)(\text{est}(R))$                      | (7.13); zip, trans, moves lax natural |
| (b) | $\sqsubseteq (1 \times \text{Vec}(n)(\text{est}(R))) Q$ |                                       |

$$(7.13) \text{ on Vec: } (1 \times R) \text{ cons } \sqsubseteq \text{ cons } R \Rightarrow (1 \times \text{est}(R)) \text{ cons } \sqsubseteq \text{cp Vec}(k)(\text{cons}) \text{ est}(R), R \text{ monotonic}$$

putting the new square in front of every one of the  $\mathbf{p}$  candidates and then choosing a cheapest is beaten by choosing a cheapest first and putting the square in front of that one.

## §7.5. The security van problem

(7.5a)

| definition                                                                                                                                                                                                                                                                                                                   | type                                        | example                                                                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| $R \triangleq \text{length} \leq \text{length}^\circ$                                                                                                                                                                                                                                                                        | $[[A]] \rightarrow [[A]]$                   | $[[a,b,c]]$ to $[[a],[b,c]]$ , and not back: $1 \leq 2$ .                                                     |
| $\text{ceiling} \triangleq \frac{\text{prefix sum}}{\ni} \text{est}(\geq)$                                                                                                                                                                                                                                                   | $[A] \rightarrow \text{Int}$                | $\text{ceiling}[a,b]$ is the largest of $0, a, a+b$ .                                                         |
| $\text{floor} \triangleq \frac{\text{prefix sum}}{\ni} \text{est}(\leq)$                                                                                                                                                                                                                                                     | $[A] \rightarrow \text{Int}$                | $\text{floor}[a,b]$ is the smallest of $0, a, a+b$ , so $[a,b]$ carries $\text{ceiling} - \text{floor}$ cash. |
| <b>secure</b><br>the coreflexive on $x$ with<br>$\text{bmax}(\text{ceiling } x, \text{ceiling } x - \text{floor } x) \leq N$                                                                                                                                                                                                 | $[A] \rightarrow [A]$                       | <b>secure</b> keeps $[a]$ exactly when $-N \leq a \leq N$ .                                                   |
| <b>ok</b><br>the coreflexive on $(a, xs)$ with $xs$ non-empty and $[a] \# \text{head}(xs)$ <b>secure</b>                                                                                                                                                                                                                     | $A \times [[A]] \rightarrow A \times [[A]]$ | <b>ok</b> keeps $(a, [[b],[c]])$ exactly when $[a,b]$ is <b>secure</b> .                                      |
| $\text{new} \triangleq (\text{wrap} \times 1) \text{ cons}$                                                                                                                                                                                                                                                                  | $A \times [[A]] \rightarrow [[A]]$          | $\text{new}(a, [[b],[c]]) = [[a],[b],[c]]$ .                                                                  |
| $\text{glue} \triangleq (1 \times \text{cons}^\circ) \text{ assocl } (\text{cons} \times 1) \text{ cons}$                                                                                                                                                                                                                    | $A \times [[A]] \rightarrow [[A]]$          | $\text{glue}(a, [[b],[c]]) = [[a,b],[c]]$ .                                                                   |
| $\text{old} \triangleq (1 \times \text{cons}^\circ) \text{ assocl } ((\text{cons } \text{secure}) \times 1) \text{ cons}$                                                                                                                                                                                                    | $A \times [[A]] \rightarrow [[A]]$          | $\text{old}(a, [[b],[c]]) = [[a,b],[c]]$ when $[a,b]$ is <b>secure</b> , and nothing otherwise.               |
| <b>partition</b> = $([\text{nil}, \text{new } u \text{ glue}])$<br>cutting the transactions into non-empty segments<br>is one pass along them that either opens a segment<br>for the transaction in hand or puts it on the front<br>of the segment already open                                                              | $[A] \rightarrow [[A]]$                     | <b>partition</b> $[a,b]$ gives $[[a],[b]]$ and $[[a,b]]$ .                                                    |
| $S \triangleq [\text{nil}, \text{new } u \text{ old}]$                                                                                                                                                                                                                                                                       | $F[[A]] \rightarrow [[A]]$                  | $S(a, [[b],[c]])$ gives $[[a],[b],[c]]$ , and $[[a,b],[c]]$ when $[a,b]$ is <b>secure</b> .                   |
| $(\forall a. \text{secureP}(\text{amount})(N, [a])) \Rightarrow$<br>$\text{partition list}(\text{secure}) = (S)$<br>cutting the transactions into non-empty segments<br>every way and keeping the cuts whose every<br>segment is <b>secure</b> is the one fold whose algebra is<br>$[\text{nil}, \text{new } u \text{ old}]$ | $[A] \rightarrow [[A]]$                     | Both take $[a,b]$ to $[[a],[b]]$ — each $[a]$ is <b>secure</b> — and to $[[a,b]]$ when $[a,b]$ is.            |
| $H \triangleq (\text{head prefix}^\circ \text{ head}^\circ) u (\text{nil}^\circ \text{ nil})$                                                                                                                                                                                                                                | $[[A]] \rightarrow [[A]]$                   | $[[a],[b,c]]$ to $[[a,b],[c]]$ : $[a]$ is a prefix of $[a,b]$ .                                               |
| $R; H \triangleq R n (R^\circ \Rightarrow H)$                                                                                                                                                                                                                                                                                | $[[A]] \rightarrow [[A]]$                   | $[[a,b,c]]$ to $[[a],[b,c]]$ by $ R $ , and $[[a],[b,c]]$ to $[[a,b],[c]]$ by $R n H$ .                       |
| $ R  \triangleq R n \neg R^\circ$                                                                                                                                                                                                                                                                                            | $[[A]] \rightarrow [[A]]$                   | $[[a,b,c]]$ to $[[a],[b,c]]$ : $1 < 2$ . The strict part $R$ splits into: $R; H =  R  u (R n H)$ .            |
| the specification<br>$\frac{\text{partition list}(\text{secure})}{\ni} \text{est}(R)$                                                                                                                                                                                                                                        | $[A] \rightarrow [[A]]$                     | $[a,b]$ gives $[[a,b]]$ when $[a,b]$ is <b>secure</b> , and $[[a],[b]]$ otherwise.                            |

§7.5.1. **secure prefix**  $\ni$  **prefix secure**

(7.5a)

(7.5.1a)



$$\text{secure } \langle \text{ceiling}, \text{ceiling-floor} \rangle \text{ bmax} = \langle \text{ceiling}, \text{ceiling-floor} \rangle \text{ bmax } (\leq N)$$

a stretch passes **secure** before the test exactly where the test's own value passes  $\leq N$  after it, which is  $\triangleq$  **secure**'s  $\text{bmax}(\text{ceiling } x, \text{ceiling } x - \text{floor } x) \leq N$

Exercise 7.49



$$\text{secure prefix} \sqsubseteq \text{prefix secure}$$


every pair **secure** then **prefix** gives, **prefix** then **secure** gives too — a prefix of a secure stretch is itself secure, which is the prefix-closure  
B&dM p.185 names

### §7.5.2. partition $\text{list}(\text{secure}) = ([\text{nil}, \text{new } u \text{ old}])$

(7.5.2a)

| definition                                                                                                                                                                                                                                                                                               | Hinze–Marsden |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| <b>new</b> $\triangleq (\text{wrap} \times 1) \text{ cons}$<br><b>wrap</b> makes the transaction a segment on its own, and <b>cons</b> puts that segment at the front of the schedule:<br>the van is called                                                                                              |               |
| <b>glue</b> $\triangleq (1 \times \text{cons}^\circ) \text{ assocl } (\text{cons} \times 1) \text{ cons}$<br><b>cons</b> $^\circ$ splits the schedule into its first segment and the rest, the first <b>cons</b> puts the transaction at the front of that segment, and the second puts the segment back |               |
| <b>old</b> $\triangleq (1 \times \text{cons}^\circ) \text{ assocl } ((\text{cons } \text{secure}) \times 1) \text{ cons}$<br><b>glue</b> with <b>secure</b> on the segment the transaction has just joined: the van stays away only where the longer segment still passes                                |               |

(7.5.2b)



$$(\forall a. \text{secureP}(\text{amount})(N, [a])) \Rightarrow [\text{nil}, \text{new } u \text{ glue}] \text{ list}(\text{secure}) = F(\text{list}(\text{secure})) S$$

testing every segment for security after the algebra has run is testing it before it ran: a segment **glue** has extended is secure exactly where **old** would have let it be, and the one transaction **new** sets out on its own is secure whatever it is

(7.5.1a)

| $(\forall a. \text{secureP}(\text{amount})(N, [a])) \Rightarrow \text{partition list}(\text{secure}) = \langle S \rangle$ <span style="float: right;">Exercise 7.51</span>                                                           |               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| cutting the transactions into non-empty segments every way and keeping the cuts whose every segment<br>is secure is the one fold whose algebra is $[\text{nil}, \text{new} \cup \text{old}]$                                         |               |
| step                                                                                                                                                                                                                                 | Hinze–Marsden |
| <b>partition list(secure)</b><br>the specification: cut the transactions every way, then keep the cuts whose every segment is secure                                                                                                 |               |
| $= \langle [\text{nil}, \text{new} \cup \text{glue}] \rangle \text{list}(\text{secure})$<br><b>partition</b> is the fold that either opens a segment for the transaction in hand or puts it on the front of the segment already open |               |
| $= \langle [\text{nil}, \text{new} \cup \text{old}] \rangle$<br>fusion: the condition above moves <b>list(secure)</b> inside that fold, which is what turns <b>glue</b> into <b>old</b>                                              |               |

(7.5.2c)



$$(\forall a. \text{secureP}(\text{amount})(N, [a])) \Rightarrow \text{partition list}(\text{secure}) = \langle S \rangle$$

cutting the transactions every way and then keeping the cuts whose every segment is secure is one pass along them that either calls the van or extends the open segment while it stays secure

### §7.5.3. $(1 \times R) \text{new} \sqsubseteq (\text{new} \cup \text{old}) R$

| $(1 \times R) \text{new} \sqsubseteq (\text{new} \cup \text{old}) R$ <span style="float: right;">(7.14)</span>                                                                                                                         |               |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| calling the van for the transaction on a no-longer schedule gets no further than calling it on this one and shortening<br>the schedule afterwards                                                                                      |               |
| step                                                                                                                                                                                                                                   | Hinze–Marsden |
| <b><math>(1 \times R) \text{new}</math></b><br>the left side of (7.14) $\triangleq \text{secure}$                                                                                                                                      |               |
| $= (\text{wrap} \times R) \text{cons}$<br>$\text{new} \triangleq (\text{wrap} \times 1) \text{cons}$ — (7.5.2a) — and $(\text{wrap} \times 1) (1 \times R) = (\text{wrap} \times R)$                                                   |               |
| $\sqsubseteq \text{new} R$<br><b>cons</b> is monotonic on $R$ — $(1 \times R) \text{cons} \sqsubseteq \text{cons} R$ , consing onto a no-longer schedule leaves it no longer — and $\text{new} \sqsubseteq \text{new} \cup \text{old}$ |               |

### §7.5.4. $H \triangleq (\text{head prefix}^\circ \text{head}^\circ) \cup (\text{nil}^\circ \text{nil})$

(7.5.4a)



### §7.5.5. $(1 \times (R;H)) \text{new} \sqsubseteq (\text{new } u \text{ old})(R;H)$

(7.18)



whatever schedule the van is called on, the result's first segment is the one transaction  $[a]$ , so any two results of **new** on that transaction stand in  $H$


$$(1 \times (R;H)) \text{new} \sqsubseteq (\text{new } u \text{ old})(R;H) \quad (7.16)$$

calling the van for the transaction on a  $R;H$ -better schedule gets no further than calling it on this one and bettering the whole schedule afterwards

| step                                                                                                                   | Hinze–Marsden |
|------------------------------------------------------------------------------------------------------------------------|---------------|
| $(1 \times (R;H)) \text{new}$<br>the left side of (7.16)                                                               |               |
| $\sqsubseteq (1 \times R) \text{new}$<br>$R;H \sqsubseteq R \text{ — } \triangleq \text{secure}$                       |               |
| $\sqsubseteq \text{new } R \cap \text{new } H$<br>(7.14) as far as its <b>new</b> $R$ line — (7.14) — and (7.18)       |               |
| $= \text{new } (R \cap H)$<br>$\text{new}$ is a map, and a map distributes over $\cap$                                 |               |
| $\sqsubseteq \text{new } (R;H)$<br>$X \cap Y \sqsubseteq X;Y$ , and $\text{new} \sqsubseteq \text{new } u \text{ old}$ |               |


### §7.5.6. $(1 \times (R;H)) \text{old} \sqsubseteq (\text{new } u \text{ old})(R;H)$

(7.19)




**old** leaves the transaction **[a]** at the front of the first segment, and **[a]** is what **new** makes that segment, so the two first segments are **prefix-related** whatever the schedules were

(7.20)



**old** keeps the schedule's length, so a strictly shorter one still comes out no longer than the one the van's own segment lengthens

(7.21)





on a tie the one first segment is a prefix of the other, so prefix-closure of **secure** — Exercise 7.49 — lets **old** fire on this side too, and it keeps both the length and the prefix

$$(1 \times (R;H)) \text{ old} \sqsubseteq (\text{new} \cup \text{old}) (R;H) \quad (7.17)$$


gluing the transaction onto a better schedule for the rest gets no further than gluing it on, or calling the van, and bettering the whole schedule after,

**circuit** — the old branch of each union

**Hinze–Marsden**





the **old** operand of **new**  $\cup$  **old**, in every row





$$(1 \times |R|) \text{ old} \cup (1 \times (RnH)) \text{ old}$$

$R;H = |R| \cup (RnH) \triangleq \text{secure}$ ,  $\cup$  distributes,




$$\text{new} (RnH) \cup \text{old} (RnH)$$

(7.19) and (7.20) on  $|R|$  — (7.19), (7.20) — and (7.21) on  $RnH$  — (7.21)



$$(\text{new} \cup \text{old})(R;H)$$

$XnY \sqsubseteq X;Y$ , converses




### §7.5.7. The derivation

$$(\forall a. \text{secureP}(\text{amount})(N, [a])) \Rightarrow ([\text{nil}, (\text{ok} \rightarrow \text{glue}, \text{new})]) \sqsubseteq \frac{\text{partition list}(\text{secure})}{\exists} \text{est}(R) \quad (7.5.7a)$$

the fewest secure segments the transactions can be cut into are one pass along them, the next transaction glued onto the open segment wherever that segment stays secure and the van called where it does not

$\triangleq \text{secure}$



|     |                                                                                 |                                                                                              |
|-----|---------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| (a) | $\frac{\text{partition list}(\text{secure})}{\exists} \text{est}(R)$            | $\text{partition list}(\text{secure}) = \langle S \rangle \triangleq \text{secure}$ , fusion |
| (b) | $= \frac{\langle S \rangle}{\exists} \text{est}(R)$                             | $R;H \sqsubseteq R \triangleq \text{secure}$                                                 |
| (c) | $\sqsubseteq \frac{\langle S \rangle}{\exists} \text{est}(R;H)$                 | greedy theorem at $R;H$ — (7.17), (7.16), (7.18)                                             |
| (d) | $\sqsubseteq \langle \frac{\langle S \rangle}{\exists} \text{est}(R;H) \rangle$ | $\text{old} \sqsubseteq \text{new} (R;H)^\circ$                                              |
| (e) | $\sqsubseteq ([\text{nil}, (\text{ok} \rightarrow \text{glue}, \text{new})])$   |                                                                                              |