

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jun 26, 2021

21 00 [1761]

PRODUCT NUMBER

DV5380000

PRODUCT NAME

Catalyst DV5380

MANUFACTURER'S NAME

ACROMAPRO WOOD FINISHES

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

DV5380000 = | Acute | Chronic | Fire |

Product Weight

8.09 lb/gal

Specific Gravity

0.97

FLASH POINT

46 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethanol 64-17-5	N	N	N	N	55	68
Methyl Isobutyl Ketone 108-10-1	N	Y	Y	Y	2	3
Water 7732-18-5	N	N	N	N	5	4
Sulfuric Acid 7664-93-9	Y	Y	Y	N	0.1	< 1

Volatile Organic Compounds - U.S. EPA / Canada

	DV5380000	
	LB/Gal	g/L
Coating Density	8.09	968
	By wt	By vol
Total Volatiles	62.3%	75.0%
Federally exempt solvents		
Water	4.7%	3.8%
Non-Organic Volatiles		
Sulfuric Acid	0.1%	0.1%
Organic Volatiles	57.5%	71.1%
Percent Non-Volatile	37.7%	25.0%
VOC Content	LB/Gal	g/L
Total	4.65	557
Less exempt solvents	4.83	579
Of solids	18.64	2233
Of solids	1.52 lb/lb	1.52 kg/kg
	By wt	
By wt LVP-VOC	57.5%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **1.02**

Volatile Organic Compounds - California

	DV5380000	
	LB/Gal	g/L
Coating Density	8.09	968
	By wt	By vol
Total Volatiles	62.3%	75.0%
Exempt solvents		
Water	4.7%	3.8%
Non-Organic Volatiles		
Sulfuric Acid	0.1%	0.1%
Organic Volatiles	57.5%	71.1%
Percent Non-Volatile	37.7%	25.0%
VOC Content	LB/Gal	g/L
Total	4.65	557
Less exempt solvents	4.83	579
Of solids	18.64	2233
Of solids	1.52 lb/lb	1.52 kg/kg
	By wt	
By wt LVP-VOC	57.5%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.93**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	DV5380000	
	LB/Gal	g/L
Coating Density	8.09	968
	By wt	By vol
Total Volatiles	62.3%	75.0%
Exempt solvents		
Water	4.7%	3.8%
Non-Organic Volatiles		
Sulfuric Acid	0.1%	0.1%
Organic Volatiles	57.5%	71.1%
Percent Non-Volatile	37.7%	25.0%
VOC Content	LB/Gal	g/L
Total	4.65	557
Less exempt solvents	4.83	579
Of solids	18.64	2233
Of solids	1.52 lb/lb	1.52 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	DV5380000	
	By wt	By vol
Total Volatiles	62.2%	75.0%
VOC Content	LB/Gal	g/L
Total	4.65	557

Volatile Organic Compounds - EU Directive 2010/75/EU

	DV5380000	
	By wt	By vol
Total Volatiles	62.3%	75.0%
VOC Content	LB/Gal	g/L
Total	4.66	558

Volatile Organic Compounds - Mexico

	DV5380000	
	LB/Gal	g/L
Coating Density	8.09	968
	By wt	By vol
Total Volatiles	62.3%	75.0%
Exempt solvents		
Water	4.7%	3.8%
Organic Volatiles	57.7%	71.2%
Percent Non-Volatile	37.7%	25.0%
VOC Content	LB/Gal	g/L
Total	4.66	558
Less exempt solvents	4.84	581
Of solids	18.68	2238
Of solids	1.53 lb/lb	1.53 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	DV5380000	
	LB/Gal	kg/L
Volatile HAPS	0.17	0.021
Of solids	0.70	0.084
Of solids	0.05 lb/lb	0.05 kg/kg

Air Quality Data

Density of Organic Solvent Blend

6.55 lb/gal

Photochemically Reactive

No

Additional Regulatory Information

US EPA TSCA:

Not Applicable

Relevant identified uses of the substance or mixture and uses advised against:

Not Applicable

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

