

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

May 13, 2020

06 00 [3308]

PRODUCT NUMBER

HS5103G00

PRODUCT NAME

Glazing Stain Neutral New

MANUFACTURER'S NAME

ACROMAPRO WOOD FINISHES

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

HS5103G00 = | Acute | Chronic | Fire |

Product Weight

6.77 lb/gal

Specific Gravity

0.81

FLASH POINT

84 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Light Aliphatic Hydrocarbon 64742-47-8	N	N	N	N	64	68
Heavy Aromatic Naphtha 64742-94-5	N	N	N	N	9	8
Naphthalene 91-20-3	N	Y	Y	Y	1	< 1
1-Butanol 71-36-3	N	Y	Y	N	10	10
1-(2-Butoxymethylethoxy)-propanol 29911-28-2	N	N	N	N	5	4

Volatile Organic Compounds - U.S. EPA / Canada

	HS5103G00	
	LB/Gal	g/L
Coating Density	6.77	810
	By wt	By vol
Total Volatiles	90.5%	92.5%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	90.5%	92.5%
Percent Non-Volatile	9.5%	7.5%
VOC Content	LB/Gal	g/L
Total	6.12	734
Less exempt solvents	6.12	734
Of solids	82.03	9829
Of solids	9.57 lb/lb	9.57 kg/kg
	By wt	
By wt LVP-VOC	75.4%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **1.30**

Volatile Organic Compounds - California

	HS5103G00	
	LB/Gal	g/L
Coating Density	6.77	810
	By wt	By vol
Total Volatiles	90.5%	92.5%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	90.5%	92.5%
Percent Non-Volatile	9.5%	7.5%
VOC Content	LB/Gal	g/L
Total	6.12	734
Less exempt solvents	6.12	734
Of solids	82.03	9829
Of solids	9.57 lb/lb	9.57 kg/kg
	By wt	
By wt LVP-VOC	75.4%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **1.25**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	HS5103G00	
	LB/Gal	g/L
Coating Density	6.77	810
	By wt	By vol
Total Volatiles	90.5%	92.5%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	90.5%	92.5%
Percent Non-Volatile	9.5%	7.5%
VOC Content	LB/Gal	g/L
Total	6.12	734
Less exempt solvents	6.12	734
Of solids	82.03	9829
Of solids	9.57 lb/lb	9.57 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	HS5103G00	
	By wt	By vol
Total Volatiles	90.5%	92.5%
VOC Content	LB/Gal	g/L
Total	6.12	734

Volatile Organic Compounds - EU Directive 2010/75/EU

	HS5103G00	
	By wt	By vol
Total Volatiles	85.5%	88.1%
VOC Content	LB/Gal	g/L
Total	5.78	693

Volatile Organic Compounds - Mexico

	HS5103G00	
	LB/Gal	g/L
Coating Density	6.77	810
	By wt	By vol
Total Volatiles	90.5%	92.5%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	90.5%	92.5%
Percent Non-Volatile	9.5%	7.5%
VOC Content	LB/Gal	g/L
Total	6.12	734
Less exempt solvents	6.12	734
Of solids	82.03	9829
Of solids	9.57 lb/lb	9.57 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	HS5103G00	
	LB/Gal	kg/L
Volatile HAPS	0.09	0.010
Of solids	1.22	0.146
Of solids	0.14 lb/lb	0.14 kg/kg

Air Quality Data

Density of Organic Solvent Blend

6.62 lb/gal

Photochemically Reactive

Yes

Additional Regulatory Information

US EPA TSCA:

Not Applicable

Relevant identified uses of the substance or mixture and uses advised against:

Not Applicable

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.