

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation
Apr 10, 2021

06 00 [1510]

PRODUCT NUMBER

HS5170000

PRODUCT NAME

AccuStain™ Wiping Base

MANUFACTURER'S NAME

ACROMAPRO WOOD FINISHES

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

HS5170000 = | Acute | Chronic | Fire |

Product Weight

6.66 lb/gal

Specific Gravity

0.80

FLASH POINT

100 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	4	4
Light Aliphatic Hydrocarbon 64742-47-8	N	N	N	N	79	82
Ethylbenzene 100-41-4	N	Y	Y	Y	0.1	< 1
Light Aromatic Hydrocarbons 64742-95-6	N	N	N	N	2	2
Cumene 98-82-8	N	Y	Y	Y	0.1	< 1
Trimethylbenzene 25551-13-7	N	N	N	N	1	< 1

Volatile Organic Compounds - U.S. EPA / Canada

	HS5170000	
	LB/Gal	g/L
Coating Density	6.66	798
	By wt	By vol
Total Volatiles	88.0%	90.9%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	87.9%	90.9%
Percent Non-Volatile	12.0%	9.1%
VOC Content	LB/Gal	g/L
Total	5.86	702
Less exempt solvents	5.86	702
Of solids	64.20	7693
Of solids	7.30 lb/lb	7.30 kg/kg
	By wt	
By wt LVP-VOC	87.9%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.99**

Volatile Organic Compounds - California

	HS5170000	
	LB/Gal	g/L
Coating Density	6.66	798
	By wt	By vol
Total Volatiles	88.0%	90.9%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	87.9%	90.9%
Percent Non-Volatile	12.0%	9.1%
VOC Content	LB/Gal	g/L
Total	5.86	702
Less exempt solvents	5.86	702
Of solids	64.20	7693
Of solids	7.30 lb/lb	7.30 kg/kg
	By wt	
By wt LVP-VOC	87.9%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.97**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	HS5170000	
	LB/Gal	g/L
Coating Density	6.66	798
	By wt	By vol
Total Volatiles	88.0%	90.9%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	87.9%	90.9%
Percent Non-Volatile	12.0%	9.1%
VOC Content	LB/Gal	g/L
Total	5.86	702
Less exempt solvents	5.86	702
Of solids	64.20	7693
Of solids	7.30 lb/lb	7.30 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	HS5170000	
	By wt	By vol
Total Volatiles	88.0%	90.9%
VOC Content	LB/Gal	g/L
Total	5.86	702

Volatile Organic Compounds - EU Directive 2010/75/EU

	HS5170000	
	By wt	By vol
Total Volatiles	88.0%	90.9%
VOC Content	LB/Gal	g/L
Total	5.86	702

Volatile Organic Compounds - Mexico

	HS5170000	
	LB/Gal	g/L
Coating Density	6.66	798
	By wt	By vol
Total Volatiles	88.0%	90.9%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	87.9%	90.9%
Percent Non-Volatile	12.0%	9.1%
VOC Content	LB/Gal	g/L
Total	5.86	702
Less exempt solvents	5.86	702
Of solids	64.20	7693
Of solids	7.30 lb/lb	7.30 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	HS5170000	
	LB/Gal	kg/L
Volatile HAPS	0.01	0.001
Of solids	0.17	0.020
Of solids	0.01 lb/lb	0.01 kg/kg

Air Quality Data**Density of Organic Solvent Blend**

6.45 lb/gal

Photochemically Reactive

No

Additional Regulatory Information**US EPA TSCA:**

Not Applicable

Relevant identified uses of the substance or mixture and uses advised against:

Not Applicable

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.