

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Oct 12, 2020

03 00 [3468]

PRODUCT NUMBER

TT5907000

PRODUCT NAME

Retarder 0987 HAPS Free

MANUFACTURER'S NAME

ACROMAPRO WOOD FINISHES

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

TT5907000 = | Acute | Chronic | Fire |

Product Weight

7.90 lb/gal

Specific Gravity

0.95

FLASH POINT

77 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethyl 3-Ethoxypropionate 763-69-9	N	N	N	N	98	98
n-Butyl Acetate 123-86-4	N	Y	N	N	2	2

Volatile Organic Compounds - U.S. EPA / Canada

	TT5907000	
	LB/Gal	g/L
Coating Density	7.90	946
	By wt	By vol
Total Volatiles	100.0%	100.0%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	100.0%	100.0%
Percent Non-Volatile	0.0%	0.0%
VOC Content	LB/Gal	g/L
Total	7.89	946
Less exempt solvents	7.89	946
Of solids	0.00	0
Of solids	0.00 lb/lb	0.00 kg/kg
	By wt	
By wt LVP-VOC	100.0%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 3.55

Volatile Organic Compounds - California

	TT5907000	
	LB/Gal	g/L
Coating Density	7.90	946
	By wt	By vol
Total Volatiles	100.0%	100.0%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	100.0%	100.0%
Percent Non-Volatile	0.0%	0.0%
VOC Content	LB/Gal	g/L
Total	7.89	946
Less exempt solvents	7.89	946
Of solids	0.00	0
Of solids	0.00 lb/lb	0.00 kg/kg
	By wt	
By wt LVP-VOC	100.0%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **3.52**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	TT5907000	
	LB/Gal	g/L
Coating Density	7.90	946
	By wt	By vol
Total Volatiles	100.0%	100.0%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	100.0%	100.0%
Percent Non-Volatile	0.0%	0.0%
VOC Content	LB/Gal	g/L
Total	7.89	946
Less exempt solvents	7.89	946
Of solids	0.00	0
Of solids	0.00 lb/lb	0.00 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	TT5907000	
	By wt	By vol
Total Volatiles	100.0%	100.0%
VOC Content	LB/Gal	g/L
Total	7.89	946

Volatile Organic Compounds - EU Directive 2010/75/EU

	TT5907000	
	By wt	By vol
Total Volatiles	100.0%	100.0%
VOC Content	LB/Gal	g/L
Total	7.89	946

Volatile Organic Compounds - Mexico

	TT5907000	
	LB/Gal	g/L
Coating Density	7.90	946
	By wt	By vol
Total Volatiles	100.0%	100.0%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	100.0%	100.0%
Percent Non-Volatile	0.0%	0.0%
VOC Content	LB/Gal	g/L
Total	7.89	946
Less exempt solvents	7.89	946
Of solids	0.00	0
Of solids	0.00 lb/lb	0.00 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	TT5907000		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	0.00 % by wt
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

7.90 lb/gal

Photochemically Reactive

No

Additional Regulatory Information

US EPA TSCA:

Not Applicable

Relevant identified uses of the substance or mixture and uses advised against:

Not Applicable

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.