

## 1. Identification

**Product identifier** 866-0333 CHROMA-CHEM® LITHOL RUBINE

**Other means of identification**

**SAP Specification** 000000139022

**Recommended use** Non-aqueous colorant

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Company** Chromaflo Technologies Corporation  
2600 Michigan Avenue  
Ashtabula, OH, USA 44005-0816

**Canadian facility** Chromaflo Technologies Canada  
235 Orenda Road  
Brampton, Ontario, Canada L6T-1E6

**US telephone** 440-997-5137

**Canadian telephone** 905-451-3810

**NA: EMERGENCY # (3E)** 866-519-4752

**GLOBAL: EMERG. # (3E)** (+1) 760-476-3962

**3E CONTRACT #** 12154

**3E ACCESS CODE** 334294

**CANADA: CANUTEC** 613-996-6666

**EMERGENCY NUMBER**

**Product Regulatory Services** ehs\_americas@chromaflo.com

**Supplier** Not available.

## 2. Hazard(s) identification

|                         |                                                   |                                     |
|-------------------------|---------------------------------------------------|-------------------------------------|
| <b>Physical hazards</b> | Flammable liquids                                 | Category 3                          |
| <b>Health hazards</b>   | Skin corrosion/irritation                         | Category 2                          |
|                         | Serious eye damage/eye irritation                 | Category 2A                         |
|                         | Sensitization, skin                               | Category 1                          |
|                         | Carcinogenicity                                   | Category 2                          |
|                         | Reproductive toxicity                             | Category 2                          |
|                         | Specific target organ toxicity, single exposure   | Category 3 narcotic effects         |
|                         | Specific target organ toxicity, repeated exposure | Category 1 (central nervous system) |

**Label elements**



**Signal word** Danger

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Hazard statement</b>         | Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (central nervous system) through prolonged or repeated exposure.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Precautionary statement</b>  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Prevention</b>               | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. |
| <b>Response</b>                 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.                                                                                               |
| <b>Storage</b>                  | Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Disposal</b>                 | Dispose of contents/container in accordance with local/regional/national/international regulations.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Other hazards</b>            | None known.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Supplemental information</b> | If product is in liquid or paste form, hazards related to dust are not considered significant. But product may contain substances that could be potential hazards if caused to become airborne due to abrasive processes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

### 3. Composition/information on ingredients

#### Mixtures

| Chemical name                                                        | Common name and synonyms | CAS number | %        |
|----------------------------------------------------------------------|--------------------------|------------|----------|
| Manganese Compounds                                                  |                          | 12238-31-2 | 10 - 20  |
| Stoddard Solvent                                                     |                          | 8052-41-3  | 10 - 20  |
| Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha |                          | 64742-89-8 | 2.5 - 10 |
| Solvent Naphtha (petroleum), medium aliphatic                        |                          | 64742-88-7 | 2.5 - 10 |
| Xylene                                                               |                          | 1330-20-7  | 2.5 - 10 |
| 1,2,4-Trimethylbenzene                                               |                          | 95-63-6    | 1 - 2.5  |
| Isobutanol                                                           |                          | 78-83-1    | 1 - 2.5  |
| Iso-butyl Acetate                                                    |                          | 110-19-0   | 1 - 2.5  |
| N-butyl Acetate                                                      |                          | 123-86-4   | 1 - 2.5  |
| N-butyl Alcohol                                                      |                          | 71-36-3    | 1 - 2.5  |
| Polyoxyethylene nonylphenol branched ether phosphate sodium salt     |                          | 68954-84-7 | 1 - 2.5  |
| 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime   |                          | 96-29-7    | 0.1 - 1  |
| Ethylbenzene                                                         |                          | 100-41-4   | 0.1 - 1  |
| Other components below reportable levels                             |                          |            | 40 - 60  |

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

|                     |                                                                                                                                                                                                                           |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation</b>   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.                                                                         |
| <b>Skin contact</b> | Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse. |
| <b>Eye contact</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.                       |

|                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Ingestion</b>                                                              | Rinse mouth. Get medical attention if symptoms occur.                                                                                                                                                                                                                                                                                                                                              |
| <b>Most important symptoms/effects, acute and delayed</b>                     | May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.                 |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.                                                                                        |
| <b>General information</b>                                                    | Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. |

## 5. Fire-fighting measures

|                                                                      |                                                                                                                                                                                    |
|----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Suitable extinguishing media</b>                                  | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).                                                                                                                        |
| <b>Unsuitable extinguishing media</b>                                | Do not use water jet as an extinguisher, as this will spread the fire.                                                                                                             |
| <b>Specific hazards arising from the chemical</b>                    | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. |
| <b>Special protective equipment and precautions for firefighters</b> | Self-contained breathing apparatus and full protective clothing must be worn in case of fire.                                                                                      |
| <b>Fire fighting equipment/instructions</b>                          | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.                                                               |
| <b>Specific methods</b>                                              | Use standard firefighting procedures and consider the hazards of other involved materials.                                                                                         |
| <b>General fire hazards</b>                                          | Flammable liquid and vapor.                                                                                                                                                        |

## 6. Accidental release measures

|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Methods and materials for containment and cleaning up</b>               | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.<br><br>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.<br><br>Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.<br><br>Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. |
| <b>Environmental precautions</b>                                           | Avoid discharge into drains, water courses or onto the ground.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## 7. Handling and storage

|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Precautions for safe handling</b> | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Conditions for safe storage,  
including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. ACGIH Threshold Limit Values**

| Components                                                     | Type | Value      | Form                 |
|----------------------------------------------------------------|------|------------|----------------------|
| 1,2,4-Trimethylbenzene (CAS 95-63-6)                           | TWA  | 25 ppm     |                      |
| Ethylbenzene (CAS 100-41-4)                                    | TWA  | 20 ppm     |                      |
| Isobutanol (CAS 78-83-1)                                       | TWA  | 50 ppm     |                      |
| Iso-butyl Acetate (CAS 110-19-0)                               | STEL | 150 ppm    |                      |
|                                                                | TWA  | 50 ppm     |                      |
| Manganese Compounds (CAS 12238-31-2)                           | TWA  | 0.1 mg/m3  | Inhalable fraction.  |
|                                                                |      | 0.02 mg/m3 | Respirable fraction. |
| N-butyl Acetate (CAS 123-86-4)                                 | STEL | 150 ppm    |                      |
|                                                                | TWA  | 50 ppm     |                      |
| N-butyl Alcohol (CAS 71-36-3)                                  | TWA  | 20 ppm     |                      |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3  | Non-aerosol.         |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 100 ppm    |                      |
| Xylene (CAS 1330-20-7)                                         | STEL | 150 ppm    |                      |
|                                                                | TWA  | 100 ppm    |                      |

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

| Components                                                                            | Type | Value      |
|---------------------------------------------------------------------------------------|------|------------|
| 1,2,4-Trimethylbenzene (CAS 95-63-6)                                                  | TWA  | 123 mg/m3  |
|                                                                                       |      | 25 ppm     |
| Ethylbenzene (CAS 100-41-4)                                                           | STEL | 543 mg/m3  |
|                                                                                       |      | 125 ppm    |
|                                                                                       | TWA  | 434 mg/m3  |
|                                                                                       |      | 100 ppm    |
| Isobutanol (CAS 78-83-1)                                                              | TWA  | 152 mg/m3  |
|                                                                                       |      | 50 ppm     |
| Iso-butyl Acetate (CAS 110-19-0)                                                      | TWA  | 713 mg/m3  |
|                                                                                       |      | 150 ppm    |
| Manganese Compounds (CAS 12238-31-2)                                                  | TWA  | 0.2 mg/m3  |
| N-butyl Acetate (CAS 123-86-4)                                                        | STEL | 950 mg/m3  |
|                                                                                       |      | 200 ppm    |
|                                                                                       | TWA  | 713 mg/m3  |
|                                                                                       |      | 150 ppm    |
| N-butyl Alcohol (CAS 71-36-3)                                                         | TWA  | 60 mg/m3   |
|                                                                                       |      | 20 ppm     |
| Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8) | TWA  | 1590 mg/m3 |
|                                                                                       |      | 400 ppm    |

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

| Components                       | Type | Value                |
|----------------------------------|------|----------------------|
| Stoddard Solvent (CAS 8052-41-3) | TWA  | 572 mg/m3<br>100 ppm |
| Xylene (CAS 1330-20-7)           | STEL | 651 mg/m3<br>150 ppm |
|                                  | TWA  | 434 mg/m3<br>100 ppm |

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

| Components                                                     | Type    | Value     | Form         |
|----------------------------------------------------------------|---------|-----------|--------------|
| 1,2,4-Trimethylbenzene (CAS 95-63-6)                           | TWA     | 25 ppm    |              |
| Ethylbenzene (CAS 100-41-4)                                    | TWA     | 20 ppm    |              |
| Isobutanol (CAS 78-83-1)                                       | TWA     | 50 ppm    |              |
| Iso-butyl Acetate (CAS 110-19-0)                               | TWA     | 150 ppm   |              |
| Manganese Compounds (CAS 12238-31-2)                           | TWA     | 0.2 mg/m3 |              |
| N-butyl Acetate (CAS 123-86-4)                                 | TWA     | 20 ppm    |              |
| N-butyl Alcohol (CAS 71-36-3)                                  | Ceiling | 30 ppm    |              |
|                                                                | TWA     | 15 ppm    |              |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA     | 200 mg/m3 | Non-aerosol. |
| Stoddard Solvent (CAS 8052-41-3)                               | STEL    | 580 mg/m3 |              |
|                                                                | TWA     | 290 mg/m3 |              |
| Xylene (CAS 1330-20-7)                                         | STEL    | 150 ppm   |              |
|                                                                | TWA     | 100 ppm   |              |

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

| Components                                                     | Type | Value      | Form                 |
|----------------------------------------------------------------|------|------------|----------------------|
| 1,2,4-Trimethylbenzene (CAS 95-63-6)                           | TWA  | 25 ppm     |                      |
| Ethylbenzene (CAS 100-41-4)                                    | TWA  | 20 ppm     |                      |
| Isobutanol (CAS 78-83-1)                                       | TWA  | 50 ppm     |                      |
| Iso-butyl Acetate (CAS 110-19-0)                               | STEL | 150 ppm    |                      |
|                                                                | TWA  | 50 ppm     |                      |
| Manganese Compounds (CAS 12238-31-2)                           | TWA  | 0.1 mg/m3  | Inhalable fraction.  |
|                                                                |      | 0.02 mg/m3 | Respirable fraction. |
| N-butyl Acetate (CAS 123-86-4)                                 | STEL | 150 ppm    |                      |
|                                                                | TWA  | 50 ppm     |                      |
| N-butyl Alcohol (CAS 71-36-3)                                  | TWA  | 20 ppm     |                      |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3  | Non-aerosol.         |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 100 ppm    |                      |
| Xylene (CAS 1330-20-7)                                         | STEL | 150 ppm    |                      |
|                                                                | TWA  | 100 ppm    |                      |

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

| Components                                                     | Type | Value     | Form         |
|----------------------------------------------------------------|------|-----------|--------------|
| 1,2,4-Trimethylbenzene (CAS 95-63-6)                           | TWA  | 25 ppm    |              |
| Ethylbenzene (CAS 100-41-4)                                    | TWA  | 20 ppm    |              |
| Isobutanol (CAS 78-83-1)                                       | TWA  | 50 ppm    |              |
| Iso-butyl Acetate (CAS 110-19-0)                               | STEL | 187 ppm   |              |
|                                                                | TWA  | 150 ppm   |              |
| Manganese Compounds (CAS 12238-31-2)                           | TWA  | 0.2 mg/m3 |              |
| N-butyl Acetate (CAS 123-86-4)                                 | STEL | 200 ppm   |              |
|                                                                | TWA  | 150 ppm   |              |
| N-butyl Alcohol (CAS 71-36-3)                                  | TWA  | 20 ppm    |              |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3 | Non-aerosol. |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 100 ppm   |              |
| Xylene (CAS 1330-20-7)                                         | STEL | 150 ppm   |              |
|                                                                | TWA  | 100 ppm   |              |

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

| Components                                                                            | Type    | Value      | Form  |
|---------------------------------------------------------------------------------------|---------|------------|-------|
| 1,2,4-Trimethylbenzene (CAS 95-63-6)                                                  | TWA     | 123 mg/m3  |       |
|                                                                                       |         | 25 ppm     |       |
| Ethylbenzene (CAS 100-41-4)                                                           | STEL    | 543 mg/m3  |       |
|                                                                                       |         | 125 ppm    |       |
|                                                                                       | TWA     | 434 mg/m3  |       |
|                                                                                       |         | 100 ppm    |       |
| Isobutanol (CAS 78-83-1)                                                              | TWA     | 152 mg/m3  |       |
|                                                                                       |         | 50 ppm     |       |
| Iso-butyl Acetate (CAS 110-19-0)                                                      | TWA     | 713 mg/m3  |       |
|                                                                                       |         | 150 ppm    |       |
| Manganese Compounds (CAS 12238-31-2)                                                  | TWA     | 5 mg/m3    | Dust. |
| N-butyl Acetate (CAS 123-86-4)                                                        | STEL    | 950 mg/m3  |       |
|                                                                                       |         | 200 ppm    |       |
|                                                                                       | TWA     | 713 mg/m3  |       |
|                                                                                       |         | 150 ppm    |       |
| N-butyl Alcohol (CAS 71-36-3)                                                         | Ceiling | 152 mg/m3  |       |
|                                                                                       |         | 50 ppm     |       |
| Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8) | TWA     | 1590 mg/m3 |       |
|                                                                                       |         | 400 ppm    |       |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)                        | TWA     | 1590 mg/m3 |       |
|                                                                                       |         | 400 ppm    |       |
| Stoddard Solvent (CAS 8052-41-3)                                                      | TWA     | 525 mg/m3  |       |
|                                                                                       |         | 100 ppm    |       |
| Xylene (CAS 1330-20-7)                                                                | STEL    | 651 mg/m3  |       |
|                                                                                       |         | 150 ppm    |       |

## Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

| Components | Type | Value                            | Form |
|------------|------|----------------------------------|------|
|            | TWA  | 434 mg/m <sup>3</sup><br>100 ppm |      |

### Biological limit values

#### ACGIH Biological Exposure Indices

| Components                  | Value    | Determinant                                   | Specimen            | Sampling Time |
|-----------------------------|----------|-----------------------------------------------|---------------------|---------------|
| Ethylbenzene (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | *             |
| Xylene (CAS 1330-20-7)      | 1.5 g/g  | Methylhippuric acids                          | Creatinine in urine | *             |

\* - For sampling details, please see the source document.

**Exposure guidelines** Occupational Exposure Limits are not relevant to the current physical form of the product.

#### Canada - Alberta OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

#### Canada - British Columbia OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

#### Canada - Manitoba OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

#### Canada - Ontario OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

#### Canada - Quebec OELs: Skin designation

N-butyl Alcohol (CAS 71-36-3) Can be absorbed through the skin.

#### Canada - Saskatchewan OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

#### US ACGIH Threshold Limit Values: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

#### Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

#### Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to vapor/mist at levels exceeding the exposure limits.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

### Appearance

|                                                     |                                |
|-----------------------------------------------------|--------------------------------|
| <b>Physical state</b>                               | Liquid.                        |
| <b>Form</b>                                         | Liquid. Paste.                 |
| <b>Color</b>                                        | Red                            |
| <b>Odor</b>                                         | Petroleum distillate odor.     |
| <b>Odor threshold</b>                               | Not available.                 |
| <b>pH</b>                                           | Not available.                 |
| <b>Melting point/freezing point</b>                 | Not available.                 |
| <b>Initial boiling point and boiling range</b>      | Not available.                 |
| <b>Flash point</b>                                  | 82.00 °F (27.78 °C) Closed Cup |
| <b>Evaporation rate</b>                             | Not available.                 |
| <b>Flammability (solid, gas)</b>                    | Not applicable.                |
| <b>Upper/lower flammability or explosive limits</b> |                                |
| <b>Explosive limit - lower (%)</b>                  | Not available.                 |
| <b>Explosive limit - upper (%)</b>                  | Not available.                 |
| <b>Vapor pressure</b>                               | Not available.                 |
| <b>Vapor density</b>                                | Not available.                 |
| <b>Relative density</b>                             | 1                              |
| <b>Solubility(ies)</b>                              |                                |
| <b>Solubility (water)</b>                           | Not available.                 |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.                 |
| <b>Auto-ignition temperature</b>                    | Not available.                 |
| <b>Decomposition temperature</b>                    | Not available.                 |
| <b>Viscosity</b>                                    | Not available.                 |
| <b>Other information</b>                            |                                |
| <b>Explosive properties</b>                         | Not explosive.                 |
| <b>Oxidizing properties</b>                         | Not oxidizing.                 |

## 10. Stability and reactivity

|                                           |                                                                                                                                                |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport.                                                  |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.                                                                                                    |
| <b>Possibility of hazardous reactions</b> | Hazardous polymerization does not occur.                                                                                                       |
| <b>Conditions to avoid</b>                | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| <b>Incompatible materials</b>             | Strong acids. Strong oxidizing agents. Halogens.                                                                                               |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.                                                                                                 |

## 11. Toxicological information

### Information on likely routes of exposure

|                                                                                     |                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation</b>                                                                   | May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.                                                                                                                                                                                     |
| <b>Skin contact</b>                                                                 | Causes skin irritation. May cause an allergic skin reaction.                                                                                                                                                                                                                                                                         |
| <b>Eye contact</b>                                                                  | Causes serious eye irritation.                                                                                                                                                                                                                                                                                                       |
| <b>Ingestion</b>                                                                    | Expected to be a low ingestion hazard.                                                                                                                                                                                                                                                                                               |
| <b>Symptoms related to the physical, chemical and toxicological characteristics</b> | May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. |

### Information on toxicological effects

|                       |            |
|-----------------------|------------|
| <b>Acute toxicity</b> | Not known. |
|-----------------------|------------|



| Components                           | Species | Test Results      |
|--------------------------------------|---------|-------------------|
| 1,2,4-Trimethylbenzene (CAS 95-63-6) |         |                   |
| <u>Acute</u>                         |         |                   |
| <b>Dermal</b>                        |         |                   |
| LD50                                 | Rabbit  | > 3160 mg/kg      |
| Ethylbenzene (CAS 100-41-4)          |         |                   |
| <u>Acute</u>                         |         |                   |
| <b>Oral</b>                          |         |                   |
| LD50                                 | Rat     | 3500 mg/kg        |
| Isobutanol (CAS 78-83-1)             |         |                   |
| <u>Acute</u>                         |         |                   |
| <b>Dermal</b>                        |         |                   |
| LD50                                 | Rabbit  | 3392 mg/kg        |
| <b>Oral</b>                          |         |                   |
| LD50                                 | Rat     | 2.46 g/kg         |
| N-butyl Alcohol (CAS 71-36-3)        |         |                   |
| <u>Acute</u>                         |         |                   |
| <b>Dermal</b>                        |         |                   |
| LD50                                 | Rabbit  | 3400 mg/kg        |
| <b>Oral</b>                          |         |                   |
| LD50                                 | Rat     | 790 mg/kg         |
| Xylene (CAS 1330-20-7)               |         |                   |
| <u>Acute</u>                         |         |                   |
| <b>Oral</b>                          |         |                   |
| LD50                                 | Rat     | 3523 - 8600 mg/kg |

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

#### Respiratory or skin sensitization

##### Canada - Alberta OELs: Irritant

|                                  |          |
|----------------------------------|----------|
| Isobutanol (CAS 78-83-1)         | Irritant |
| Iso-butyl Acetate (CAS 110-19-0) | Irritant |
| N-butyl Acetate (CAS 123-86-4)   | Irritant |
| N-butyl Alcohol (CAS 71-36-3)    | Irritant |

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

##### ACGIH Carcinogens

|                                                                |                                                                  |
|----------------------------------------------------------------|------------------------------------------------------------------|
| Ethylbenzene (CAS 100-41-4)                                    | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| Manganese Compounds (CAS 12238-31-2)                           | A4 Not classifiable as a human carcinogen.                       |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| Xylene (CAS 1330-20-7)                                         | A4 Not classifiable as a human carcinogen.                       |

##### Canada - Manitoba OELs: carcinogenicity

|                                                                |                                                               |
|----------------------------------------------------------------|---------------------------------------------------------------|
| Ethylbenzene (CAS 100-41-4)                                    | Confirmed animal carcinogen with unknown relevance to humans. |
| Manganese Compounds (CAS 12238-31-2)                           | Not classifiable as a human carcinogen.                       |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | Confirmed animal carcinogen with unknown relevance to humans. |
| Xylene (CAS 1330-20-7)                                         | Not classifiable as a human carcinogen.                       |

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Ethylbenzene (CAS 100-41-4)  
 Stoddard Solvent (CAS 8052-41-3)  
 Xylene (CAS 1330-20-7)

2B Possibly carcinogenic to humans.  
 3 Not classifiable as to carcinogenicity to humans.  
 3 Not classifiable as to carcinogenicity to humans.

|                                                           |                                                                                                                                                                          |
|-----------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Reproductive toxicity</b>                              | Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child. |
| <b>Specific target organ toxicity - single exposure</b>   | May cause drowsiness and dizziness.                                                                                                                                      |
| <b>Specific target organ toxicity - repeated exposure</b> | Causes damage to organs (central nervous system) through prolonged or repeated exposure.                                                                                 |
| <b>Aspiration hazard</b>                                  | Not an aspiration hazard.                                                                                                                                                |
| <b>Chronic effects</b>                                    | Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.                                                            |

**12. Ecological information**

|                    |                                                                                                                                                                                                    |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Ecotoxicity</b> | The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| Product                                                                               | Species |                                                     | Test Results                     |
|---------------------------------------------------------------------------------------|---------|-----------------------------------------------------|----------------------------------|
| 866-0333 CHROMA-CHEM® LITHOL RUBINE                                                   |         |                                                     |                                  |
| Aquatic                                                                               |         |                                                     |                                  |
| Crustacea                                                                             | EC50    | Daphnia                                             | 33.0881 mg/l, 48 hours estimated |
| Fish                                                                                  | LC50    | Fish                                                | 67.0812 mg/l, 96 hours estimated |
| Components                                                                            | Species |                                                     | Test Results                     |
| 1,2,4-Trimethylbenzene (CAS 95-63-6)                                                  |         |                                                     |                                  |
| Aquatic                                                                               |         |                                                     |                                  |
| Fish                                                                                  | LC50    | Fathead minnow (Pimephales promelas)                | 7.19 - 8.28 mg/l, 96 hours       |
| 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (CAS 96-29-7)      |         |                                                     |                                  |
| Aquatic                                                                               |         |                                                     |                                  |
| Fish                                                                                  | LC50    | Fathead minnow (Pimephales promelas)                | 777 - 914 mg/l, 96 hours         |
| Ethylbenzene (CAS 100-41-4)                                                           |         |                                                     |                                  |
| Aquatic                                                                               |         |                                                     |                                  |
| Crustacea                                                                             | EC50    | Water flea (Daphnia magna)                          | 1.37 - 4.4 mg/l, 48 hours        |
| Fish                                                                                  | LC50    | Fathead minnow (Pimephales promelas)                | 7.5 - 11 mg/l, 96 hours          |
| Isobutanol (CAS 78-83-1)                                                              |         |                                                     |                                  |
| Aquatic                                                                               |         |                                                     |                                  |
| Crustacea                                                                             | EC50    | Water flea (Daphnia pulex)                          | 950 - 1200 mg/l, 48 hours        |
| Fish                                                                                  | LC50    | Bleak (Alburnus alburnus)                           | 1000 - 3000 mg/l, 96 hours       |
| N-butyl Acetate (CAS 123-86-4)                                                        |         |                                                     |                                  |
| Aquatic                                                                               |         |                                                     |                                  |
| Fish                                                                                  | LC50    | Fathead minnow (Pimephales promelas)                | 17 - 19 mg/l, 96 hours           |
| N-butyl Alcohol (CAS 71-36-3)                                                         |         |                                                     |                                  |
| Aquatic                                                                               |         |                                                     |                                  |
| Crustacea                                                                             | EC50    | Water flea (Daphnia magna)                          | 1897 - 2072 mg/l, 48 hours       |
| Fish                                                                                  | LC50    | Bluegill (Lepomis macrochirus)                      | 100 - 500 mg/l, 96 hours         |
| Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8) |         |                                                     |                                  |
| Aquatic                                                                               |         |                                                     |                                  |
| Crustacea                                                                             | EC50    | Water flea (Daphnia pulex)                          | 2.7 - 5.1 mg/l, 48 hours         |
| Fish                                                                                  | LC50    | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 8.8 mg/l, 96 hours               |
|                                                                                       |         |                                                     | 8.8 mg/l, 96 hours               |

| Components                                                     | Species |                                                     | Test Results                 |
|----------------------------------------------------------------|---------|-----------------------------------------------------|------------------------------|
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) |         |                                                     |                              |
| Aquatic                                                        |         |                                                     |                              |
| Crustacea                                                      | EC50    | Water flea (Daphnia pulex)                          | 2.7 - 5.1 mg/l, 48 hours     |
| Fish                                                           | LC50    | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 8.8 mg/l, 96 hours           |
|                                                                |         |                                                     | 8.8 mg/l, 96 hours           |
| Xylene (CAS 1330-20-7)                                         |         |                                                     |                              |
| Aquatic                                                        |         |                                                     |                              |
| Fish                                                           | LC50    | Bluegill (Lepomis macrochirus)                      | 7.711 - 9.591 mg/l, 96 hours |

\* Estimates for product may be based on additional component data not shown.

#### Persistence and degradability

#### Bioaccumulative potential

##### Partition coefficient n-octanol / water (log Kow)

|                   |             |
|-------------------|-------------|
| Ethylbenzene      | 3.15        |
| Isobutanol        | 0.76        |
| Iso-butyl Acetate | 1.78        |
| N-butyl Acetate   | 1.78        |
| N-butyl Alcohol   | 0.88        |
| Stoddard Solvent  | 3.16 - 7.15 |
| Xylene            | 3.12 - 3.2  |

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

#### TDG

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| UN number                    | UN1263                                                                  |
| UN proper shipping name      | PAINT RELATED MATERIAL                                                  |
| Transport hazard class(es)   |                                                                         |
| Class                        | 3                                                                       |
| Subsidiary risk              | -                                                                       |
| Packing group                | III                                                                     |
| Environmental hazards        | Not available.                                                          |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

#### IATA

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| UN number                    | UN1263                                                                  |
| UN proper shipping name      | Paint related material                                                  |
| Transport hazard class(es)   |                                                                         |
| Class                        | 3                                                                       |
| Subsidiary risk              | -                                                                       |
| Packing group                | III                                                                     |
| Environmental hazards        | No.                                                                     |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

**IMDG**

|                                                                          |                                                                         |
|--------------------------------------------------------------------------|-------------------------------------------------------------------------|
| UN number                                                                | UN1263                                                                  |
| UN proper shipping name                                                  | PAINT RELATED MATERIAL                                                  |
| Transport hazard class(es)                                               |                                                                         |
| Class                                                                    | 3                                                                       |
| Subsidiary risk                                                          | -                                                                       |
| Packing group                                                            | III                                                                     |
| Environmental hazards                                                    |                                                                         |
| Marine pollutant                                                         | No.                                                                     |
| EmS                                                                      | Not available.                                                          |
| Special precautions for user                                             | Read safety instructions, SDS and emergency procedures before handling. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not established.                                                        |

IATA; IMDG; TDG

**15. Regulatory information**

**Canadian regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Controlled Drugs and Substances Act**

Not regulated.

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)**

Ethylbenzene (CAS 100-41-4)

Manganese Compounds (CAS 12238-31-2)

Xylene (CAS 1330-20-7)

**Precursor Control Regulations**

Not regulated.

**International regulations** Additional information is given in the Safety Data Sheet.

**Stockholm Convention**

Not applicable.

**Rotterdam Convention**

Not applicable.

**Kyoto protocol**

Not applicable.

**Montreal Protocol**

Not applicable.

**Basel Convention**

Not applicable.

**International Inventories**

| Country(s) or region | Inventory name                                     | On inventory (yes/no)* |
|----------------------|----------------------------------------------------|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS) | Yes                    |
| Canada               | Domestic Substances List (DSL)                     | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                | No                     |

| Country(s) or region        | Inventory name                                                         | On inventory (yes/no)* |
|-----------------------------|------------------------------------------------------------------------|------------------------|
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes                    |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)                                          | No                     |
| New Zealand                 | New Zealand Inventory                                                  | Yes                    |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |
| Taiwan                      | Taiwan Toxic Chemicals Substances Control Act                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

**Issue date** 01-29-2018

**Revision date** 08-01-2018

**Version #** 03

**Disclaimer** The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.