

1. Identification

Product identifier 866-1045 CHROMA-CHEM® RED IRON OXIDE V

Other means of identification

SAP Specification 000000139040

Recommended use Non-aqueous colorant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Chromaflo Technologies Corporation
2600 Michigan Avenue
Ashtabula, OH, USA 44005-0816

Canadian facility Chromaflo Technologies Canada
235 Orenda Road
Brampton, Ontario, Canada L6T-1E6

US telephone 440-997-5137

Canadian telephone 905-451-3810

NA: EMERGENCY # (3E) 866-519-4752

GLOBAL: EMERG. # (3E) (+1) 760-476-3962

3E CONTRACT # 12154

3E ACCESS CODE 334294

CANADA: CANUTEC 613-996-6666

EMERGENCY NUMBER

Product Regulatory Services ehs_americas@chromaflo.com

Supplier Not available.

2. Hazard identification

Physical hazards Flammable liquids Category 3

Health hazards Germ cell mutagenicity Category 1B

Carcinogenicity Category 1B

Reproductive toxicity Category 2

Specific target organ toxicity, repeated exposure Category 1 (central nervous system)

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (central nervous system) through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

None known.

Supplemental information

If product is in liquid or paste form, hazards related to dust are not considered significant. But product may contain substances that could be potential hazards if caused to become airborne due to abrasive processes.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ferric Oxide		1309-37-1	40 - 70
Stoddard Solvent		8052-41-3	3 - 7
Ferric Oxide		1309-37-1	1 - 5
Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha		64742-89-8	1 - 5
Nonylphenoxypoly(ethyleneoxy)ethanol, branched		68412-54-4	0.5 - 1.5
Polyoxyethylene nonylphenol branched ether phosphate sodium salt		68954-84-7	0.5 - 1.5
Solvent Naphtha (petroleum), medium aliphatic		64742-88-7	0.5 - 1.5
Xylene		1330-20-7	0.5 - 1.5
Ethylbenzene		100-41-4	0.1 - 1
Other components below reportable levels			15 - 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Narcosis. Behavioral changes. Decrease in motor functions. Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values Components

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Ferric Oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	5 mg/m3	Respirable fraction.
Stoddard Solvent (CAS 8052-41-3)	TWA	200 mg/m3	Non-aerosol.
Xylene (CAS 1330-20-7)	STEL	100 ppm	
		150 ppm	

**US. ACGIH Threshold Limit Values
Components**

Type

Value

Form

TWA

100 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components

Type

Value

Form

Ethylbenzene (CAS
100-41-4)

STEL

543 mg/m3

125 ppm

TWA

434 mg/m3

100 ppm

Ferric Oxide (CAS
1309-37-1)

TWA

5 mg/m3

Respirable.

5 mg/m3

Respirable.

Solvent naphtha
(petroleum), light aliph.;
Low boiling point naphtha
(CAS 64742-89-8)

TWA

1590 mg/m3

400 ppm

Stoddard Solvent (CAS
8052-41-3)

TWA

572 mg/m3

100 ppm

Xylene (CAS 1330-20-7)

STEL

651 mg/m3

150 ppm

TWA

434 mg/m3

100 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components

Type

Value

Form

Ethylbenzene (CAS
100-41-4)

TWA

20 ppm

Ferric Oxide (CAS
1309-37-1)

STEL

10 mg/m3

Fume.

10 mg/m3

Fume.

TWA

5 mg/m3

Fume.

5 mg/m3

Fume.

5 mg/m3

Dust.

5 mg/m3

Dust.

3 mg/m3

Respirable fraction.

3 mg/m3

Respirable fraction.

10 mg/m3

Total dust.

10 mg/m3

Total dust.

Solvent Naphtha
(petroleum), medium
aliphatic (CAS 64742-88-7)

TWA

200 mg/m3

Non-aerosol.

Stoddard Solvent (CAS
8052-41-3)

STEL

580 mg/m3

TWA

290 mg/m3

Xylene (CAS 1330-20-7)

STEL

150 ppm

TWA

100 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Ferric Oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
		5 mg/m3	Respirable fraction.
Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Ferric Oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
		5 mg/m3	Respirable fraction.
Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	
	TWA	434 mg/m3	
		100 ppm	
Ferric Oxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
		5 mg/m3	Dust and fume.
		10 mg/m3	Total dust.
		10 mg/m3	Total dust.
Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8)	TWA	1590 mg/m3	
		400 ppm	
Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	1590 mg/m3	
		400 ppm	
Stoddard Solvent (CAS 8052-41-3)	TWA	525 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
		100 ppm	
Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)			
Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	15 minute	125 ppm	
	8 hour	100 ppm	
Ferric Oxide (CAS 1309-37-1)	15 minute	20 mg/m3	
		20 mg/m3	
		10 mg/m3	Dust and fume.
		10 mg/m3	Dust and fume.
	8 hour	5 mg/m3	Dust and fume.
		5 mg/m3	Dust and fume.
		10 mg/m3	
		10 mg/m3	
Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8)	15 minute	500 ppm	
	8 hour	400 ppm	
Stoddard Solvent (CAS 8052-41-3)	15 minute	125 ppm	
	8 hour	100 ppm	
Xylene (CAS 1330-20-7)	15 minute	150 ppm	
	8 hour	100 ppm	

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines Occupational Exposure Limits are not relevant to the current physical form of the product.

Canada - Alberta OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Solvent Naphtha (petroleum), medium aliphatic (CAS
64742-88-7)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to vapor/mist at levels exceeding the exposure limits.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid. Paste.

Color

Red.

Odor

Petroleum distillate odor.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

Not available.

Flash point

82.00 °F (27.78 °C) Closed Cup

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

Not available.

Vapor density

Not available.

Relative density

1.75

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Explosive properties

Not explosive.

Oxidizing properties

Not oxidizing.

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Narcosis. Behavioral changes. Decrease in motor functions.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
------------	---------	--------------

Ethylbenzene (CAS 100-41-4)

Acute

Dermal

LD50	Rabbit	17800 mg/kg
------	--------	-------------

Oral

LD50	Rat	3500 mg/kg
------	-----	------------

Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8)

Acute

Inhalation

LC50	Rat	61 mg/l, 4 Hours
------	-----	------------------

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Acute

Inhalation

LC50	Rat	61 mg/l, 4 Hours
------	-----	------------------

Xylene (CAS 1330-20-7)

Acute

Oral

LD50	Rat	3523 - 8600 mg/kg
------	-----	-------------------

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye irritation Due to partial or complete lack of data the classification is not possible.

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization Due to partial or complete lack of data the classification is not possible.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

ACGIH Carcinogens

Ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Ferric Oxide (CAS 1309-37-1)	A4 Not classifiable as a human carcinogen.
Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	A4 Not classifiable as a human carcinogen.
	A3 Confirmed animal carcinogen with unknown relevance to humans.

Xylene (CAS 1330-20-7)
Canada - Manitoba OELs: carcinogenicity

Ethylbenzene (CAS 100-41-4)
 Ferric Oxide (CAS 1309-37-1)

A4 Not classifiable as a human carcinogen.

Confirmed animal carcinogen with unknown relevance to humans.
 Not classifiable as a human carcinogen.
 Not classifiable as a human carcinogen.
 Confirmed animal carcinogen with unknown relevance to humans.

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Xylene (CAS 1330-20-7)

Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4)
 Ferric Oxide (CAS 1309-37-1)

2B Possibly carcinogenic to humans.
 3 Not classifiable as to carcinogenicity to humans.
 3 Not classifiable as to carcinogenicity to humans.
 3 Not classifiable as to carcinogenicity to humans.

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Stoddard Solvent (CAS 8052-41-3)

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.
 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure

Causes damage to organs (central nervous system) through prolonged or repeated exposure.

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

Chronic effects

Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species	Test Results
866-1045 CHROMA-CHEM® RED IRON OXIDE	V	

Aquatic

Crustacea	EC50	Daphnia	78.029 mg/l, 48 hours estimated
Fish	LC50	Fish	157.2629 mg/l, 96 hours estimated

Components	Species	Test Results
------------	---------	--------------

Ethylbenzene (CAS 100-41-4)

Aquatic

Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours

Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8)

Aquatic

Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Aquatic

Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours

Xylene (CAS 1330-20-7)

Aquatic

Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours
------	------	--------------------------------	------------------------------

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log K_{ow})

Ethylbenzene	3.15
Stoddard Solvent	3.16 - 7.15
Xylene	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

UN number	UN1263
UN proper shipping name	PAINT RELATED MATERIAL
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	UN1263
UN proper shipping name	Paint related material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1263
UN proper shipping name	PAINT RELATED MATERIAL
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, <u>S</u> -E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
Taiwan	Taiwan Toxic Chemicals Substances Control Act	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 05-10-2017

Revision date 08-14-2019

Version # 05

Disclaimer The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses. Chromaflo Technologies Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information Product and Company Identification: Product and Company Identification
Transport Information: Proper Shipping Name/Packing Group