

## 1. Identification

**Product identifier** 866-1309 CHROMA-CHEM® RAW UMBER

**Other means of identification**

**SAP Specification** 000000139042

**Recommended use** Non-aqueous colorant

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Company** Chromaflo Technologies Corporation  
2600 Michigan Avenue  
Ashtabula, OH, USA 44005-0816

**Canadian facility** Chromaflo Technologies Canada  
235 Orenda Road  
Brampton, Ontario, Canada L6T-1E6

**US telephone** 440-997-5137

**Canadian telephone** 905-451-3810

**NA: EMERGENCY # (3E)** 866-519-4752

**GLOBAL: EMERG. # (3E)** (+1) 760-476-3962

**3E CONTRACT #** 12154

**3E ACCESS CODE** 334294

**CANADA: CANUTEC** 613-996-6666

**EMERGENCY NUMBER**

**Product Regulatory Services** ehs\_americas@chromaflo.com

**Supplier** Not available.

## 2. Hazard identification

|                         |                                                   |                                     |
|-------------------------|---------------------------------------------------|-------------------------------------|
| <b>Physical hazards</b> | Flammable liquids                                 | Category 3                          |
| <b>Health hazards</b>   | Serious eye damage/eye irritation                 | Category 2                          |
|                         | Germ cell mutagenicity                            | Category 1B                         |
|                         | Carcinogenicity                                   | Category 1B                         |
|                         | Reproductive toxicity                             | Category 2                          |
|                         | Specific target organ toxicity, repeated exposure | Category 1 (central nervous system) |

**Label elements**



**Signal word** Danger

**Hazard statement** Flammable liquid and vapor. Causes serious eye irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (central nervous system) through prolonged or repeated exposure.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

### Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

### Storage

Store in a well-ventilated place. Keep cool. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Other hazards

None known.

### Supplemental information

If product is in liquid or paste form, hazards related to dust are not considered significant. But product may contain substances that could be potential hazards if caused to become airborne due to abrasive processes.

## 3. Composition/information on ingredients

### Mixtures

| Chemical name                                                        | Common name and synonyms | CAS number | %         |
|----------------------------------------------------------------------|--------------------------|------------|-----------|
| Ferric Oxide                                                         |                          | 1309-37-1  | 10 - 30   |
| Stoddard Solvent                                                     |                          | 8052-41-3  | 5 - 10    |
| Carbon Black                                                         |                          | 1333-86-4  | 3 - 7     |
| Chromium (Iii) Oxide                                                 |                          | 1308-38-9  | 3 - 7     |
| Manganese Compounds                                                  |                          | 1317-34-6  | 3 - 7     |
| Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha |                          | 64742-89-8 | 3 - 7     |
| Calcium Carbonate                                                    |                          | 1317-65-3  | 1 - 5     |
| Silica, Crystalline, Quartz                                          |                          | 14808-60-7 | 1 - 5     |
| Solvent Naphtha (petroleum), medium aliphatic                        |                          | 64742-88-7 | 1 - 5     |
| Xylene                                                               |                          | 1330-20-7  | 1 - 5     |
| N-butyl Acetate                                                      |                          | 123-86-4   | 0.5 - 1.5 |
| Ethylbenzene                                                         |                          | 100-41-4   | 0.1 - 1   |
| Nonylphenoxypoly(ethyleneoxy)ethanol, branched                       |                          | 68412-54-4 | 0.1 - 1   |
| Other components below reportable levels                             |                          |            | 30 - 60   |

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

### Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Rinse mouth. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

Narcosis. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

|                            |                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General information</b> | Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## 5. Fire-fighting measures

|                                                                      |                                                                                                                                                                                    |
|----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Suitable extinguishing media</b>                                  | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).                                                                                                                        |
| <b>Unsuitable extinguishing media</b>                                | Do not use water jet as an extinguisher, as this will spread the fire.                                                                                                             |
| <b>Specific hazards arising from the chemical</b>                    | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. |
| <b>Special protective equipment and precautions for firefighters</b> | Self-contained breathing apparatus and full protective clothing must be worn in case of fire.                                                                                      |
| <b>Fire fighting equipment/instructions</b>                          | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.                                                               |
| <b>Specific methods</b>                                              | Use standard firefighting procedures and consider the hazards of other involved materials.                                                                                         |
| <b>General fire hazards</b>                                          | Flammable liquid and vapor.                                                                                                                                                        |

## 6. Accidental release measures

|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Methods and materials for containment and cleaning up</b>               | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.<br><br>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.<br><br>Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.<br><br>Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. |
| <b>Environmental precautions</b>                                           | Avoid discharge into drains, water courses or onto the ground.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## 7. Handling and storage

|                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Precautions for safe handling</b>                                | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. |
| <b>Conditions for safe storage, including any incompatibilities</b> | Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).                                                                                                                                                                                                                                                                                                                                                                                                             |

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

| Components                   | Type | Value   | Form                |
|------------------------------|------|---------|---------------------|
| Carbon Black (CAS 1333-86-4) | TWA  | 3 mg/m3 | Inhalable fraction. |

**US. ACGIH Threshold Limit Values  
Components**

| Components                                                     | Type | Value       | Form                 |
|----------------------------------------------------------------|------|-------------|----------------------|
| Chromium (Iii) Oxide (CAS 1308-38-9)                           | TWA  | 0.5 mg/m3   |                      |
| Ethylbenzene (CAS 100-41-4)                                    | TWA  | 20 ppm      |                      |
| Ferric Oxide (CAS 1309-37-1)                                   | TWA  | 5 mg/m3     | Respirable fraction. |
| Manganese Compounds (CAS 1317-34-6)                            | TWA  | 0.1 mg/m3   | Inhalable fraction.  |
|                                                                |      | 0.02 mg/m3  | Respirable fraction. |
| N-butyl Acetate (CAS 123-86-4)                                 | STEL | 150 ppm     |                      |
|                                                                | TWA  | 50 ppm      |                      |
| Silica, Crystalline, Quartz (CAS 14808-60-7)                   | TWA  | 0.025 mg/m3 | Respirable fraction. |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3   | Non-aerosol.         |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 100 ppm     |                      |
| Xylene (CAS 1330-20-7)                                         | STEL | 150 ppm     |                      |
|                                                                | TWA  | 100 ppm     |                      |

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

| Components                                                                            | Type | Value       | Form                  |
|---------------------------------------------------------------------------------------|------|-------------|-----------------------|
| Calcium Carbonate (CAS 1317-65-3)                                                     | TWA  | 10 mg/m3    |                       |
| Carbon Black (CAS 1333-86-4)                                                          | TWA  | 3.5 mg/m3   |                       |
| Chromium (Iii) Oxide (CAS 1308-38-9)                                                  | TWA  | 0.5 mg/m3   |                       |
| Ethylbenzene (CAS 100-41-4)                                                           | STEL | 543 mg/m3   |                       |
|                                                                                       |      | 125 ppm     |                       |
|                                                                                       | TWA  | 434 mg/m3   |                       |
|                                                                                       |      | 100 ppm     |                       |
| Ferric Oxide (CAS 1309-37-1)                                                          | TWA  | 5 mg/m3     | Respirable.           |
| Manganese Compounds (CAS 1317-34-6)                                                   | TWA  | 0.2 mg/m3   |                       |
| N-butyl Acetate (CAS 123-86-4)                                                        | STEL | 950 mg/m3   |                       |
|                                                                                       |      | 200 ppm     |                       |
|                                                                                       | TWA  | 713 mg/m3   |                       |
|                                                                                       |      | 150 ppm     |                       |
| Silica, Crystalline, Quartz (CAS 14808-60-7)                                          | TWA  | 0.025 mg/m3 | Respirable particles. |
| Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8) | TWA  | 1590 mg/m3  |                       |
|                                                                                       |      | 400 ppm     |                       |
| Stoddard Solvent (CAS 8052-41-3)                                                      | TWA  | 572 mg/m3   |                       |

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

| Components             | Type | Value     | Form |
|------------------------|------|-----------|------|
| Xylene (CAS 1330-20-7) | STEL | 100 ppm   |      |
|                        |      | 651 mg/m3 |      |
|                        | TWA  | 150 ppm   |      |
|                        |      | 434 mg/m3 |      |
|                        |      | 100 ppm   |      |

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

| Components                                                     | Type | Value       | Form                 |
|----------------------------------------------------------------|------|-------------|----------------------|
| Calcium Carbonate (CAS 1317-65-3)                              | STEL | 20 mg/m3    | Total dust.          |
|                                                                | TWA  | 3 mg/m3     | Respirable fraction. |
|                                                                |      | 10 mg/m3    | Total dust.          |
| Carbon Black (CAS 1333-86-4)                                   | TWA  | 3 mg/m3     | Inhalable            |
| Chromium (lii) Oxide (CAS 1308-38-9)                           | TWA  | 0.5 mg/m3   |                      |
| Ethylbenzene (CAS 100-41-4)                                    | TWA  | 20 ppm      |                      |
| Ferric Oxide (CAS 1309-37-1)                                   | STEL | 10 mg/m3    | Fume.                |
|                                                                | TWA  | 5 mg/m3     | Fume.                |
|                                                                |      | 5 mg/m3     | Dust.                |
|                                                                |      | 3 mg/m3     | Respirable fraction. |
|                                                                |      | 10 mg/m3    | Total dust.          |
| Manganese Compounds (CAS 1317-34-6)                            | TWA  | 0.2 mg/m3   |                      |
| N-butyl Acetate (CAS 123-86-4)                                 | TWA  | 20 ppm      |                      |
| Silica, Crystalline, Quartz (CAS 14808-60-7)                   | TWA  | 0.025 mg/m3 | Respirable fraction. |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3   | Non-aerosol.         |
| Stoddard Solvent (CAS 8052-41-3)                               | STEL | 580 mg/m3   |                      |
|                                                                | TWA  | 290 mg/m3   |                      |
|                                                                |      |             |                      |
| Xylene (CAS 1330-20-7)                                         | STEL | 150 ppm     |                      |
|                                                                | TWA  | 100 ppm     |                      |

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

| Components                           | Type | Value      | Form                 |
|--------------------------------------|------|------------|----------------------|
| Carbon Black (CAS 1333-86-4)         | TWA  | 3 mg/m3    | Inhalable fraction.  |
| Chromium (lii) Oxide (CAS 1308-38-9) | TWA  | 0.5 mg/m3  |                      |
| Ethylbenzene (CAS 100-41-4)          | TWA  | 20 ppm     |                      |
| Ferric Oxide (CAS 1309-37-1)         | TWA  | 5 mg/m3    | Respirable fraction. |
| Manganese Compounds (CAS 1317-34-6)  | TWA  | 0.1 mg/m3  | Inhalable fraction.  |
|                                      |      | 0.02 mg/m3 | Respirable fraction. |
| N-butyl Acetate (CAS 123-86-4)       | STEL | 150 ppm    |                      |

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

| Components                                                     | Type | Value       | Form                 |
|----------------------------------------------------------------|------|-------------|----------------------|
|                                                                | TWA  | 50 ppm      |                      |
| Silica, Crystalline, Quartz (CAS 14808-60-7)                   | TWA  | 0.025 mg/m3 | Respirable fraction. |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3   | Non-aerosol.         |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 100 ppm     |                      |
| Xylene (CAS 1330-20-7)                                         | STEL | 150 ppm     |                      |
|                                                                | TWA  | 100 ppm     |                      |

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

| Components                                                     | Type | Value     | Form                 |
|----------------------------------------------------------------|------|-----------|----------------------|
| Carbon Black (CAS 1333-86-4)                                   | TWA  | 3 mg/m3   | Inhalable fraction.  |
| Chromium (Iii) Oxide (CAS 1308-38-9)                           | TWA  | 0.5 mg/m3 |                      |
| Ethylbenzene (CAS 100-41-4)                                    | TWA  | 20 ppm    |                      |
| Ferric Oxide (CAS 1309-37-1)                                   | TWA  | 5 mg/m3   | Respirable fraction. |
| Manganese Compounds (CAS 1317-34-6)                            | TWA  | 0.2 mg/m3 |                      |
| N-butyl Acetate (CAS 123-86-4)                                 | STEL | 200 ppm   |                      |
|                                                                | TWA  | 150 ppm   |                      |
| Silica, Crystalline, Quartz (CAS 14808-60-7)                   | TWA  | 0.1 mg/m3 | Respirable fraction. |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3 | Non-aerosol.         |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 100 ppm   |                      |
| Xylene (CAS 1330-20-7)                                         | STEL | 150 ppm   |                      |
|                                                                | TWA  | 100 ppm   |                      |

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

| Components                          | Type | Value     | Form           |
|-------------------------------------|------|-----------|----------------|
| Calcium Carbonate (CAS 1317-65-3)   | TWA  | 10 mg/m3  | Total dust.    |
| Carbon Black (CAS 1333-86-4)        | TWA  | 3.5 mg/m3 |                |
| Ethylbenzene (CAS 100-41-4)         | STEL | 543 mg/m3 |                |
|                                     |      | 125 ppm   |                |
|                                     | TWA  | 434 mg/m3 |                |
|                                     |      | 100 ppm   |                |
| Ferric Oxide (CAS 1309-37-1)        | TWA  | 5 mg/m3   | Dust and fume. |
|                                     |      | 10 mg/m3  | Total dust.    |
| Manganese Compounds (CAS 1317-34-6) | TWA  | 5 mg/m3   | Dust.          |
| N-butyl Acetate (CAS 123-86-4)      | STEL | 950 mg/m3 |                |
|                                     |      | 200 ppm   |                |
|                                     | TWA  | 713 mg/m3 |                |

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

| Components                                                                            | Type | Value      | Form             |
|---------------------------------------------------------------------------------------|------|------------|------------------|
|                                                                                       |      | 150 ppm    |                  |
| Silica, Crystalline, Quartz (CAS 14808-60-7)                                          | TWA  | 0.1 mg/m3  | Respirable dust. |
| Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8) | TWA  | 1590 mg/m3 |                  |
|                                                                                       |      | 400 ppm    |                  |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)                        | TWA  | 1590 mg/m3 |                  |
|                                                                                       |      | 400 ppm    |                  |
| Stoddard Solvent (CAS 8052-41-3)                                                      | TWA  | 525 mg/m3  |                  |
|                                                                                       |      | 100 ppm    |                  |
| Xylene (CAS 1330-20-7)                                                                | STEL | 651 mg/m3  |                  |
|                                                                                       |      | 150 ppm    |                  |
|                                                                                       | TWA  | 434 mg/m3  |                  |
|                                                                                       |      | 100 ppm    |                  |

**Biological limit values**
**ACGIH Biological Exposure Indices**

| Components                  | Value    | Determinant                                   | Specimen            | Sampling Time |
|-----------------------------|----------|-----------------------------------------------|---------------------|---------------|
| Ethylbenzene (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | *             |
| Xylene (CAS 1330-20-7)      | 1.5 g/g  | Methylhippuric acids                          | Creatinine in urine | *             |

\* - For sampling details, please see the source document.

**Exposure guidelines** Occupational Exposure Limits are not relevant to the current physical form of the product.

**Canada - Alberta OELs: Skin designation**

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

**Canada - Manitoba OELs: Skin designation**

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

**Canada - Ontario OELs: Skin designation**

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

|                                       |                                                                                                                                                                                                                                                                                               |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Skin protection</b>                |                                                                                                                                                                                                                                                                                               |
| <b>Hand protection</b>                | Wear appropriate chemical resistant gloves.                                                                                                                                                                                                                                                   |
| <b>Other</b>                          | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.                                                                                                                                                                                                      |
| <b>Respiratory protection</b>         | Use a NIOSH/MSHA approved respirator if there is a risk of exposure to vapor/mist at levels exceeding the exposure limits.                                                                                                                                                                    |
| <b>Thermal hazards</b>                | Wear appropriate thermal protective clothing, when necessary.                                                                                                                                                                                                                                 |
| <b>General hygiene considerations</b> | Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

## 9. Physical and chemical properties

### Appearance

|                                                     |                                |
|-----------------------------------------------------|--------------------------------|
| <b>Physical state</b>                               | Liquid.                        |
| <b>Form</b>                                         | Liquid. Paste.                 |
| <b>Color</b>                                        | Reddish-brown                  |
| <b>Odor</b>                                         | Petroleum distillate odor.     |
| <b>Odor threshold</b>                               | Not available.                 |
| <b>pH</b>                                           | Not available.                 |
| <b>Melting point/freezing point</b>                 | Not available.                 |
| <b>Initial boiling point and boiling range</b>      | Not available.                 |
| <b>Flash point</b>                                  | 82.00 °F (27.78 °C) Closed Cup |
| <b>Evaporation rate</b>                             | Not available.                 |
| <b>Flammability (solid, gas)</b>                    | Not applicable.                |
| <b>Upper/lower flammability or explosive limits</b> |                                |
| <b>Explosive limit - lower (%)</b>                  | Not available.                 |
| <b>Explosive limit - upper (%)</b>                  | Not available.                 |
| <b>Vapor pressure</b>                               | Not available.                 |
| <b>Vapor density</b>                                | Not available.                 |
| <b>Relative density</b>                             | 1.36                           |
| <b>Solubility(ies)</b>                              |                                |
| <b>Solubility (water)</b>                           | Not available.                 |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.                 |
| <b>Auto-ignition temperature</b>                    | Not available.                 |
| <b>Decomposition temperature</b>                    | Not available.                 |
| <b>Viscosity</b>                                    | Not available.                 |
| <b>Other information</b>                            |                                |
| <b>Explosive properties</b>                         | Not explosive.                 |
| <b>Oxidizing properties</b>                         | Not oxidizing.                 |

## 10. Stability and reactivity

|                                           |                                                                                                                                                                       |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport.                                                                         |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.                                                                                                                           |
| <b>Possibility of hazardous reactions</b> | Hazardous polymerization does not occur.                                                                                                                              |
| <b>Conditions to avoid</b>                | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| <b>Incompatible materials</b>             | Strong acids. Strong oxidizing agents. Halogens.                                                                                                                      |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.                                                                                                                        |

## 11. Toxicological information

### Information on likely routes of exposure

|              |                                                      |
|--------------|------------------------------------------------------|
| Inhalation   | No adverse effects due to inhalation are expected.   |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact  | Causes serious eye irritation.                       |
| Ingestion    | Expected to be a low ingestion hazard.               |

|                                                                              |                                                                                                                                                                  |
|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms related to the physical, chemical and toxicological characteristics | Narcosis. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. |
|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Information on toxicological effects

|                |            |
|----------------|------------|
| Acute toxicity | Not known. |
|----------------|------------|

| Components                  | Species | Test Results      |
|-----------------------------|---------|-------------------|
| Ethylbenzene (CAS 100-41-4) |         |                   |
| <b>Acute</b>                |         |                   |
| <b>Dermal</b>               |         |                   |
| LD50                        | Rabbit  | 17800 mg/kg       |
| <b>Oral</b>                 |         |                   |
| LD50                        | Rat     | 3500 mg/kg        |
| Xylene (CAS 1330-20-7)      |         |                   |
| <b>Acute</b>                |         |                   |
| <b>Oral</b>                 |         |                   |
| LD50                        | Rat     | 3523 - 8600 mg/kg |

|                           |                                                                             |
|---------------------------|-----------------------------------------------------------------------------|
| Skin corrosion/irritation | Due to partial or complete lack of data the classification is not possible. |
|---------------------------|-----------------------------------------------------------------------------|

|                                   |                                |
|-----------------------------------|--------------------------------|
| Serious eye damage/eye irritation | Causes serious eye irritation. |
|-----------------------------------|--------------------------------|

### Respiratory or skin sensitization

#### Canada - Alberta OELs: Irritant

|                                      |          |
|--------------------------------------|----------|
| Calcium Carbonate (CAS 1317-65-3)    | Irritant |
| Chromium (Iii) Oxide (CAS 1308-38-9) | Irritant |
| N-butyl Acetate (CAS 123-86-4)       | Irritant |

|                           |                                                                             |
|---------------------------|-----------------------------------------------------------------------------|
| Respiratory sensitization | Due to partial or complete lack of data the classification is not possible. |
|---------------------------|-----------------------------------------------------------------------------|

|                    |                                                                             |
|--------------------|-----------------------------------------------------------------------------|
| Skin sensitization | Due to partial or complete lack of data the classification is not possible. |
|--------------------|-----------------------------------------------------------------------------|

|                        |                            |
|------------------------|----------------------------|
| Germ cell mutagenicity | May cause genetic defects. |
|------------------------|----------------------------|

|                 |                   |
|-----------------|-------------------|
| Carcinogenicity | May cause cancer. |
|-----------------|-------------------|

#### ACGIH Carcinogens

|                                                                |                                                                  |
|----------------------------------------------------------------|------------------------------------------------------------------|
| Carbon Black (CAS 1333-86-4)                                   | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| Chromium (Iii) Oxide (CAS 1308-38-9)                           | A4 Not classifiable as a human carcinogen.                       |
| Ethylbenzene (CAS 100-41-4)                                    | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| Ferric Oxide (CAS 1309-37-1)                                   | A4 Not classifiable as a human carcinogen.                       |
| Manganese Compounds (CAS 1317-34-6)                            | A4 Not classifiable as a human carcinogen.                       |
| Silica, Crystalline, Quartz (CAS 14808-60-7)                   | A2 Suspected human carcinogen.                                   |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| Xylene (CAS 1330-20-7)                                         | A4 Not classifiable as a human carcinogen.                       |

#### Canada - Alberta OELs: Carcinogen category

|                                              |                             |
|----------------------------------------------|-----------------------------|
| Silica, Crystalline, Quartz (CAS 14808-60-7) | Suspected human carcinogen. |
|----------------------------------------------|-----------------------------|

#### Canada - Manitoba OELs: carcinogenicity

|                                              |                                                               |
|----------------------------------------------|---------------------------------------------------------------|
| Carbon Black (CAS 1333-86-4)                 | Confirmed animal carcinogen with unknown relevance to humans. |
| Chromium (Iii) Oxide (CAS 1308-38-9)         | Not classifiable as a human carcinogen.                       |
| Ethylbenzene (CAS 100-41-4)                  | Confirmed animal carcinogen with unknown relevance to humans. |
| Ferric Oxide (CAS 1309-37-1)                 | Not classifiable as a human carcinogen.                       |
| Manganese Compounds (CAS 1317-34-6)          | Not classifiable as a human carcinogen.                       |
| Silica, Crystalline, Quartz (CAS 14808-60-7) | Suspected human carcinogen.                                   |

Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Xylene (CAS 1330-20-7)

**Canada - Quebec OELs: Carcinogen category**

Silica, Crystalline, Quartz (CAS 14808-60-7)

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Carbon Black (CAS 1333-86-4)

Chromium (Iii) Oxide (CAS 1308-38-9)

Ethylbenzene (CAS 100-41-4)

Ferric Oxide (CAS 1309-37-1)

Silica, Crystalline, Quartz (CAS 14808-60-7)

Stoddard Solvent (CAS 8052-41-3)

Xylene (CAS 1330-20-7)

**US. National Toxicology Program (NTP) Report on Carcinogens**

Silica, Crystalline, Quartz (CAS 14808-60-7)

Confirmed animal carcinogen with unknown relevance to humans.

Not classifiable as a human carcinogen.

Suspected carcinogenic effect in humans.

2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

1 Carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

3 Not classifiable as to carcinogenicity to humans.

Known To Be Human Carcinogen.

**Reproductive toxicity** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.

**Specific target organ toxicity - single exposure** Due to partial or complete lack of data the classification is not possible.

**Specific target organ toxicity - repeated exposure** Causes damage to organs (central nervous system) through prolonged or repeated exposure.

**Aspiration hazard** Due to partial or complete lack of data the classification is not possible.

**Chronic effects** Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Product                                                                               | Species |                                                     | Test Results                      |
|---------------------------------------------------------------------------------------|---------|-----------------------------------------------------|-----------------------------------|
| 866-1309 CHROMA-CHEM® RAW UMBER                                                       |         |                                                     |                                   |
| Aquatic                                                                               |         |                                                     |                                   |
| Crustacea                                                                             | EC50    | Daphnia                                             | 50.0866 mg/l, 48 hours estimated  |
| Fish                                                                                  | LC50    | Fish                                                | 100.9321 mg/l, 96 hours estimated |
| Components                                                                            | Species |                                                     | Test Results                      |
| Ethylbenzene (CAS 100-41-4)                                                           |         |                                                     |                                   |
| Aquatic                                                                               |         |                                                     |                                   |
| Crustacea                                                                             | EC50    | Water flea (Daphnia magna)                          | 1.37 - 4.4 mg/l, 48 hours         |
| Fish                                                                                  | LC50    | Fathead minnow (Pimephales promelas)                | 7.5 - 11 mg/l, 96 hours           |
| N-butyl Acetate (CAS 123-86-4)                                                        |         |                                                     |                                   |
| Aquatic                                                                               |         |                                                     |                                   |
| Fish                                                                                  | LC50    | Fathead minnow (Pimephales promelas)                | 17 - 19 mg/l, 96 hours            |
| Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8) |         |                                                     |                                   |
| Aquatic                                                                               |         |                                                     |                                   |
| Crustacea                                                                             | EC50    | Water flea (Daphnia pulex)                          | 2.7 - 5.1 mg/l, 48 hours          |
| Fish                                                                                  | LC50    | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 8.8 mg/l, 96 hours                |
|                                                                                       |         |                                                     | 8.8 mg/l, 96 hours                |
| Solvent Naphtha (petroleum), medium aliphatic (CAS 64742-88-7)                        |         |                                                     |                                   |
| Aquatic                                                                               |         |                                                     |                                   |
| Crustacea                                                                             | EC50    | Water flea (Daphnia pulex)                          | 2.7 - 5.1 mg/l, 48 hours          |
| Fish                                                                                  | LC50    | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 8.8 mg/l, 96 hours                |
|                                                                                       |         |                                                     | 8.8 mg/l, 96 hours                |

| Components                                        | Species                                                                                                                                                                                 | Test Results                                                |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|
| Xylene (CAS 1330-20-7)                            |                                                                                                                                                                                         |                                                             |
| Aquatic                                           |                                                                                                                                                                                         |                                                             |
| Fish                                              | LC50                                                                                                                                                                                    | Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours |
| Persistence and degradability                     | No data is available on the degradability of any ingredients in the mixture.                                                                                                            |                                                             |
| Bioaccumulative potential                         |                                                                                                                                                                                         |                                                             |
| Partition coefficient n-octanol / water (log Kow) |                                                                                                                                                                                         |                                                             |
| Ethylbenzene                                      |                                                                                                                                                                                         | 3.15                                                        |
| N-butyl Acetate                                   |                                                                                                                                                                                         | 1.78                                                        |
| Stoddard Solvent                                  |                                                                                                                                                                                         | 3.16 - 7.15                                                 |
| Xylene                                            |                                                                                                                                                                                         | 3.12 - 3.2                                                  |
| Mobility in soil                                  | No data available.                                                                                                                                                                      |                                                             |
| Other adverse effects                             | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |                                                             |

### 13. Disposal considerations

|                                              |                                                                                                                                                                                                                  |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Disposal instructions</b>                 | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.                         |
| <b>Local disposal regulations</b>            | Dispose in accordance with all applicable regulations.                                                                                                                                                           |
| <b>Hazardous waste code</b>                  | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.                                                                                                   |
| <b>Waste from residues / unused products</b> | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| <b>Contaminated packaging</b>                | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.       |

### 14. Transport information

#### TDG

|                                     |                                                                         |
|-------------------------------------|-------------------------------------------------------------------------|
| <b>UN number</b>                    | UN1263                                                                  |
| <b>UN proper shipping name</b>      | PAINT RELATED MATERIAL                                                  |
| <b>Transport hazard class(es)</b>   |                                                                         |
| Class                               | 3                                                                       |
| Subsidiary risk                     | -                                                                       |
| <b>Packing group</b>                | III                                                                     |
| <b>Environmental hazards</b>        | No                                                                      |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |

#### IATA

|                                     |                                                                         |
|-------------------------------------|-------------------------------------------------------------------------|
| <b>UN number</b>                    | UN1263                                                                  |
| <b>UN proper shipping name</b>      | Paint related material                                                  |
| <b>Transport hazard class(es)</b>   |                                                                         |
| Class                               | 3                                                                       |
| Subsidiary risk                     | -                                                                       |
| <b>Packing group</b>                | III                                                                     |
| <b>Environmental hazards</b>        | No.                                                                     |
| <b>ERG Code</b>                     | 3L                                                                      |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Other information</b>            |                                                                         |
| <b>Passenger and cargo aircraft</b> | Allowed with restrictions.                                              |
| <b>Cargo aircraft only</b>          | Allowed with restrictions.                                              |

#### IMDG

|                                   |                        |
|-----------------------------------|------------------------|
| <b>UN number</b>                  | UN1263                 |
| <b>UN proper shipping name</b>    | PAINT RELATED MATERIAL |
| <b>Transport hazard class(es)</b> |                        |
| Class                             | 3                      |
| Subsidiary risk                   | -                      |
| <b>Packing group</b>              | III                    |

**Environmental hazards****Marine pollutant**

No

**EmS**

F-E, S-E

**Special precautions for user**

Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not established.

**IATA; IMDG; TDG****15. Regulatory information****Canadian regulations**

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Controlled Drugs and Substances Act**

Not regulated.

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)**

Chromium (Iii) Oxide (CAS 1308-38-9)

Ethylbenzene (CAS 100-41-4)

Manganese Compounds (CAS 1317-34-6)

Xylene (CAS 1330-20-7)

**Precursor Control Regulations**

Not regulated.

**International regulations****Stockholm Convention**

Not applicable.

**Rotterdam Convention**

Not applicable.

**Kyoto protocol**

Not applicable.

**Montreal Protocol**

Not applicable.

**Basel Convention**

Not applicable.

**International Inventories****Country(s) or region****Inventory name****On inventory (yes/no)\***

Australia

Australian Inventory of Chemical Substances (AICS)

Yes

Canada

Domestic Substances List (DSL)

Yes

Canada

Non-Domestic Substances List (NDSL)

No

China

Inventory of Existing Chemical Substances in China (IECSC)

No

Europe

European Inventory of Existing Commercial Chemical Substances (EINECS)

No

Europe

European List of Notified Chemical Substances (ELINCS)

No

Japan

Inventory of Existing and New Chemical Substances (ENCS)

No

| Country(s) or region        | Inventory name                                                    | On inventory (yes/no)* |
|-----------------------------|-------------------------------------------------------------------|------------------------|
| Korea                       | Existing Chemicals List (ECL)                                     | No                     |
| New Zealand                 | New Zealand Inventory                                             | Yes                    |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                     | Yes                    |
| Taiwan                      | Taiwan Toxic Chemicals Substances Control Act                     | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

**Issue date** 05-09-2017

**Revision date** 12-04-2018

**Version #** 04

**Disclaimer** The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses. Chromaflo Technologies Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.