



ARTI™ DYE CONCENTRATES

ZZ00QB00X

DESCRIPTION:

Arti™ Dye Concentrates are dyes formulated to use in a variety of AcromaPro Solventborne Stains, Solventborne Sealers and Toners. Please refer to the Recommended Tinting Systems Chart on the next page for tinting specifics.

COLORS:

ZZ00QB001 Arti 1983 Dye Conc. Green	ZZ00QB004 Arti 402014 Dye Conc. Orange
ZZ00QB002 Arti 1984 Dye Conc. Black	ZZ00QB005 Arti 2015 Dye Conc. Red
ZZ00QB003 Arti 402013 Dye Conc. Yellow	ZZ00QB008 Arti Dye Conc. Brown

PRODUCT DATA:

Color:	See noted colors above	VOC:	790-860 g/l or 6.6-7.2 lbs/gal
Solids % by Vol.:	3-13 % (Theoretical)	Lbs. VOC / Lbs. Solids:	4.0 - 9.0
Solids % by Wt.:	5-20 % (Theoretical)	Lbs. VHAPs / Lbs. Solids:	0
Weight / Gal.:	8.10 lb	Flash Point (PMCC):	34° C / 93° F
Spec. Gravity:	0.98	Frost Sensitivity	No
Viscosity 25°C / 77°F:	#4 Ford: N/A	Photo chemically Reactive:	No
Viscosity 25°C / 77°F:	DIN 4: N/A	Shelf Life:	1 year (at 15-25° C / 59°-77° F)
Viscosity 23°C / 73°F:	Zahn #2 sig.: N/A	Theo. Coverage@1mil dry	N/A

MIXING / APPLICATION:

Working Temp: >18° C, 65° F substrate, coating and air

Catalyst: N/A

Catalyzation: N/A

Pot Life: 1 year (at 15-25° C / 59-77° F)

Mixing: Mix well before use

Sealer: N/A

Reducer: N/A

Application: N/A

Surface Prep: N/A

Use Directions: For interior use only. Mix thoroughly use. To be used in products specifying for Arti Dye Concentrates. Prior to application, test a sample piece to assure proper color match.

App. Equip.: N/A

Tinting: Please refer to the Recommended Tinting Chart on the next page for specifics.

DRYING TIMES TO SAND / STACK:

Method	Drying Temp.	Drying Time (@ 60 % RH and thickness @ 1 mil dry)
Air Drying	20° C / 68° F	N/A
*Forced Drying	70° C / 158° F	N/A



ARTI™ DYE CONCENTRATES

ZZ00QB00X

Recommended Tinting Systems						
Type	Code	Pigments	Max	Dyes	Max	Notes
A - Solventborne Stains						
SOLVENT BASED STAIN SYSTEM	HS5111	Arti's, 844X / 844	10%	Arti Dyes	10%	Excellent pore definition/oak
WIPING STAIN NEUTRAL	HS510W	Huls 824, 866	10%	No	-	Excellent pore definition/oak
BAC SPRAY STAIN NEUTRAL	HS5162	Huls 844X / 844	7%	Arti Dyes	7%	Lighter colors, idiot proof
STAIN BASE CONCENTRATE	HS5100W	Huls 824, 866	10%	No	-	Excellent pore definition/oak
ARTI CLEAR BASE 402000	NS5500	Arti Pigments	5%	Arti Dyes	2.5%	Part of Olesol Stain System
OLESOL STAIN	Part of a System	Arti Pigments	5%	Arti Dyes	See TDS	Haps free, good for machine spray
PROSTAIN	XS5161	Arti Pigments	5%	Arti Dyes	5%	Excellent pore definition/oak
TONER N.G.R. STAINS	XS516	No	-	Arti Dyes	7%	
ANTI-K TINKTUR	XS510T	Arti Pigments	2%	No	-	Spray, dry, remove with scotch brite
OLD GLAZE	HS510G	Huls 824	10%	No	-	Good wipability, watch adhesion
NEW GLAZE	HS5103G	Arti's, 824, 866	20%	Arti Dyes	20%	Good wipability, excellent adhesion
GLAZE GP	HS5105GF	Huls 844X / 844's	20%	No	-	Good wipability, watch adhesion
B - Solventborne Solid Colors						
POST CAT PRIMERS - SURFACER, UNISURFACER	DF5350-xx, DF5354-xx	Huls 866	5%	No	-	
POST CAT TOPCOAT - MATADOR	DH5360-xxxx	Huls 844X / 844	10%	No	-	
SATIN WHITE PRECAT LAC.(30)	NG52002-90013	Huls 866	5%	No	-	
WHITE PRECAT LAC. SEMI-GLOSS (60)	NG52002-90016	Huls 866	5%	No	-	
ULTRA HIDE PRECAT LAC. (35)	NG52003-9001X	Huls 866	5%	No	-	
URETHANES	VARIOUS	Huls 844X / 844	10%	No	-	
C - Solventborne Sealers/Toners/etc						
BLONDET	FL5100	Arti Pigments	5%	Arti Dyes	TBD	
PRECATS - INTRO, FACETT LV	NM52XX-XXXX	Arti Pigments	5%	Arti Dyes	TBD	
CARE SEAL PRECAT	FL5312	Huls 844, 866's	5%	Arti Dyes	TBD	
D - Waterborne Stains						
AQUA CHROMA SPRAY BASE	ES5110	H's, M's, 896's	7%	Aqualux	4%	Good grain definition, HAPs free
AQUA CHROMA WIPE BASE	ES5120	H's, 896's	20%	Aqualux	4%	Good grain definition, HAPs free

TESTING: Due to the wide variety of substrates, surface preparation methods, application methods, and environments, the customer should test the complete system for adhesion, compatibility and performance prior to full scale application.

FOR INDUSTRIAL SHOP APPLICATION: Thoroughly review Safety Data Sheet (SDS) for safety information and cautions prior to using this product. For Regulatory compliance data (i.e. VOC, HAPS, etc.), obtain an Environmental Data Sheet (EDS) prior to using the product. Regulatory documents are available from your local distributor or representative. Please direct any questions or comments to 1-800-524-5979.

NOTE: Product Data Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, AcromaPro cannot make any warranties as to the end result.