

ADDITIVE P111

ZZ5970000

DESCRIPTION:

Additive P111 is a solvent based additive for Acid Catalyzed products, Precats, Postcats and NC systems. Always add to the product while mixing. Do not exceed 5% by weight addition. Overdosing may result in fisheyes. This product is effective against bubbles and increases slip. Additive P111 will also improve adhesion to the substrate but compromises intercoat adhesion.

PRODUCT DATA:

Color:	Wet: Clear Dry: N/A	VOC:	780 g/l or 6.6 lbs/gal
Solids % by Vol.:	9 % (Theoretical)	Lbs. VOC / Lbs. Solids:	9.0
Solids % by Wt.:	10 % (Theoretical)	Lbs. VHAPs / Lbs. Solids:	9.0
Weight / Gal.:	7.32 lb	Flash Point (PMCC):	28° C / 82° F
Spec. Gravity:	0.88	Frost Sensitivity	No
Viscosity 23°C / 73°F:	#4 Ford: Low Viscosity	Photo chemically Reactive:	Yes
Viscosity 23°C / 73°F:	DIN 4: Low Viscosity	Shelf Life:	2 years (at 15-25° C / 59°-77° F)
Theoretical Coverage: N/A			

MIXING / APPLICATION:

Working Temp: >18° C, 65° F substrate, coating and air
Hardener: N/A
Catalyzation: N/A
Pot Life: Add to product while mixing. Do not exceed 5% by weight addition.
Sealer: N/A
Reducer: N/A
Application: N/A
Surface Prep: N/A
Use Directions: Overdosing may result in fisheyes. Effective against bubbles and increases slip. Improves adhesion to the substrate but compromises intercoat adhesion.
App. Equip.: N/A
Tinting: N/A

DRYING TIMES TO SAND / STACK / CURE:

Method	Drying Temp.	Drying Time (@ 60 % RH and thickness @ 1 mil dry)
Air Drying	N/A	N/A
*Forced Drying	N/A	N/A

TESTING: Due to the wide variety of substrates, surface preparation methods, application methods, and environments, the customer should test the complete system for adhesion, compatibility and performance prior to full scale application.

FOR INDUSTRIAL SHOP APPLICATION: Thoroughly review Safety Data Sheet (SDS) for safety information and cautions prior to using this product. For Regulatory compliance data (i.e. VOC, HAPS, etc.), obtain an Environmental Data Sheet (EDS) prior to using the product. Regulatory documents are available from your local distributor or representative. Please direct any questions or comments to 1-800-524-5979.

NOTE: Product Data Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, AcromaPro cannot make any warranties as to the end result.