Replace scalar values using .replace()

WRITING EFFICIENT CODE WITH PANDAS



Leonidas SouliotisPhD Candidate



The popular name dataset

Year of Birth	Gender	Ethnicity	Child's First Name	Count	Rank
2011	FEMALE	ASIAN AND PACIFIC ISLANDER	SOPHIA	119	1
2011	FEMALE	ASIAN AND PACIFIC ISLANDER	CHLOE	106	2



Replace values in pandas

```
start_time = time.time()
names['Gender'].loc[names.Gender=='MALE'] = 'BOY'
print("Replace values using .loc[]: {} sec".format(time.time() - start_time))
```

Results from the first method calculated in 0.0311849 seconds



Replace values using .replace()

```
start_time = time.time()
names['Gender'].replace('MALE', 'BOY', inplace=True)
print("Time using .replace(): {} sec".fomrat(time.time() - start_time))
```

```
Time using .replace(): 0.0016758441925 sec
```

```
Differerence in speed: 1,704.52411439%
```



Let's do it

WRITING EFFICIENT CODE WITH PANDAS



Replace values using lists

WRITING EFFICIENT CODE WITH PANDAS



Leonidas SouliotisPhD Candidate



Replace multiple values with one value

Year of Birth	Gender	Ethnicity	Child's First Name	Count	Rank
2011	FEMALE	WHITE NON HISP	HELENA	97	4

```
start_time = time.time()
names['Ethnicity'].loc[(names["Ethnicity"] == 'WHITE NON HISPANIC') |
(names["Ethnicity"] == 'WHITE NON HISP')] = 'WNH'
print("Results from the above operation calculated in %s seconds" %
  (time.time() - start_time))
```

Results from the second method calculated in 0.0276169776917 seconds



Replace multiple values using .replace() I

```
start_time = time.time()
names['Ethnicity'].replace(['WHITE NON HISPANIC','WHITE NON HISP'],
'WNH', inplace=True)
print("Time using .replace(): {} sec".format(time.time() - start_time))
```

```
Time using .replace(): 0.00144791603088 sec
```

```
Difference in speed: 2160.68681809%
```



```
names['Ethnicity'].replace(['WHITE NON HISP'], 'WHITE NON HISPANIC', inplace=True)
names['Ethnicity'].replace(['BLACK NON HISP'], 'BLACK NON HISPANIC', inplace=True)

names['Ethnicity'].replace(['BLACK NON HISP','WHITE NON HISP'], ['BLACK NON HISPANIC',
'WHITE NON HISPANIC'], inplace=True)
```



Let's do it

WRITING EFFICIENT CODE WITH PANDAS



Replace values using dictionaries

WRITING EFFICIENT CODE WITH PANDAS



Leonidas SouliotisPhD Candidate



Replace single values with dictionaries

```
start_time = time.time()
names['Gender'].replace({'MALE':'BOY', 'FEMALE':'GIRL'},
inplace=True)
print("Time using .replace() with dictionary: {} sec".format(time.time() - start_time))
```

```
Time using .replace() with dictionary: 0.00197792053223 sec
```

```
start_time = time.time()
names['Gender'].replace('MALE', 'BOY', inplace=True)
names['Gender'].replace('FEMALE', 'GIRL', inplace=True)
print("Time using multiple .replace(): {} sec".format(time.time() - start_time))
```

```
Time using multiple .replace(): 0.00307083129883 sec
```

Difference in speed: 55.2555448407%



Replace multiple values using dictionaries

```
Time using .replace() with dictionary: 0.0028018 sec
```



Let's do it!

WRITING EFFICIENT CODE WITH PANDAS

