

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT

on

Operating Systems (22CS4PCOPS)

Submitted by

Ananya Aithal (1BM21CS259)

in partial fulfillment for the award of the degree of

BACHELOR OF ENGINEERING

in

COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

June-2023 to September-2023

B. M. S. College of Engineering,
Bull Temple Road, Bangalore 560019
(Affiliated To Visvesvaraya Technological University, Belgaum)
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “Operating Systems” carried out by **Ananya Aithal (1BM21CS259)**, who is a bonafide student of **B. M. S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the year 2022. The Lab report has been approved as it satisfies the academic requirements in respect of a **Operating Systems - (22CS4PCOPS)** work prescribed for the said degree.

Dr. Nandini Vineeth
Assistant Professor
Department of CSE
BMSCE, Bengaluru

Dr. Jyothi S Nayak
Professor and Head
Department of CSE
BMSCE, Bengaluru

Index

Sl. No.	Date	Experiment Title	Page No.
1	15/06/23	Write a C program to simulate the following non-pre-emptive CPU scheduling algorithm to find turnaround time and waiting time. ☐FCFS ☐ SJF (preemptive & Non-pre-emptive)	1
2	15/06/23	Write a C program to simulate the following CPU scheduling algorithm to find turnaround time and waiting time. ☐ Priority (preemptive & Non-pre-emptive) ☐Round Robin (Experiment with different quantum sizes for RR algorithm)	9
3	22/06/23	Write a C program to simulate multi-level queue scheduling algorithm considering the following scenario. All the processes in the system are divided into two categories – system processes and user processes. System processes are to be given higher priority than user processes. Use FCFS scheduling for the processes in each queue.	14
4	22/06/23	Write a C program to simulate Real-Time CPU Scheduling algorithms: a) Rate- Monotonic b) Earliest-deadline First c) Proportional scheduling	18
5	29/06/23	Write a C program to simulate producer-consumer problem using semaphores.	23
6	29/06/23	Write a C program to simulate the concept of Dining - Philosophers problem.	27
7	6/07/23	Write a C program to simulate Bankers algorithm for the purpose of deadlock avoidance.	30
8	13/07/23	Write a C program to simulate deadlock detection.	33

9	20/07/23	Write a C program to simulate the following contiguous memory allocation techniques: a) Worst-fit b) Best-fit c) First-fit	36
10	27/07/23	Write a C program to simulate paging technique of memory management.	42
11	3/08/23	Write a C program to simulate page replacement algorithms: a) FIFO b) LRU c) Optimal	45
12	10/08/23	Write a C program to simulate the following file allocation strategies: a) Sequential b) Indexed c) Linked	50
13	17/08/23	Write a C program to simulate the following file organization techniques: a) Single level directory b) Two level directory c) Hierarchical	54
14	24/08/23	Write a C program to simulate disk scheduling algorithms: a) FCFS b) SCAN c) C-SCAN	60
15	24/08/23	Write a C program to simulate disk scheduling algorithms: a) SSTF b) LOOK c) C-LOOK	67

Laboratory Program 1

Write a C program to simulate the following non-pre-emptive CPU scheduling algorithm to find turnaround time and waiting time.

☐ FCFS

☐ SJF (preemptive & Non-pre-emptive)

```
#include<stdio.h>
```

```
int num;
```

```
int wait_time[100], burst_time[100], tat[100], proc[100], arrival_time[100];
```

```
void burstsort() {
```

```
    for (int i = 0; i < num - 1; i++)
```

```
    {
```

```
        for (int j = 0; j < num - i - 1; j++)
```

```
        {
```

```
            if (burst_time[j] > burst_time[j + 1])
```

```
            {
```

```
                int temp = burst_time[j];
```

```
                burst_time[j] = burst_time[j + 1];
```

```
                burst_time[j + 1] = temp;
```

```
                temp = proc[j];
```

```
                proc[j] = proc[j + 1];
```

```
                proc[j + 1] = temp;
```

```
                temp = arrival_time[j];
```

```
                arrival_time[j] = arrival_time[j + 1];
```

```

        arrival_time[j + 1] = temp;

    }

}
}
}
void

waitingtime2() {

    int remaining_time[num];

    int completed = 0;

    // Initialize the remaining_time array
    for (int i = 0; i < num; i++) {

        remaining_time[i] = burst_time[i];

    }
    int current_time = 0;

    while (completed != num) {

        int shortest_index = -1;

        int shortest_burst = __INT_MAX__;

        // Find the process with the shortest remaining burst time among the arrived and
        uncompleted processes
        for (int i = 0; i < num; i++) {

            if (arrival_time[i] <= current_time &&
                remaining_time[i] < shortest_burst && remaining_time[i] > 0) {

                shortest_burst = remaining_time[i];

                shortest_index = i;

            }

        }

    }
}

```

```

if (shortest_index == -1) {

    current_time++;

} else {

    // Execute the process for 1 unit of time
    remaining_time[shortest_index]--;

    current_time++;

    // If the process is completed, update the waiting time and completed count
    if (remaining_time[shortest_index] == 0) {

        completed++;

        wait_time[shortest_index] =
            current_time - burst_time[shortest_index] -
            arrival_time[shortest_index] - arrival_time[0];

        if (wait_time[shortest_index] < 0)

            wait_time[shortest_index] = 0;

    }

}

}

}

void
waitingtime1() {

    wait_time[0] = 0;

    for (int i = 1; i < num; i++)

    {

        wait_time[i] = burst_time[i - 1] + wait_time[i - 1] - arrival_time[i];

        if (wait_time[i] < 0)

```

```

        wait_time[i] = 0;

    }

}

void
turnaroundtime() {

    for (int i = 0; i < num; i++)

        tat[i] = burst_time[i] + wait_time[i];

}

void

avgtime() {

    double avg_wait = 0.0, avg_tat = 0.0;

    for (int i = 0; i < num; i++)

    {

        avg_wait += wait_time[i];

        avg_tat += tat[i];

    }

    avg_wait = avg_wait / num;

    avg_tat = avg_tat / num;

    printf("Average waiting time is %f\nAverage turnaround time is %f\n",
        avg_wait, avg_tat);

}

int

main() {

    printf("1.FCFS\n2.SJF\n3.SRTF\nEnter your choice:");

```



```

int ch;

scanf("%d", & ch);

if (ch < 1 || ch > 3)

{

    printf("Invalid choice!");

    return 0;

}

printf("Enter the total number of processes:");

scanf("%d", & num);

for (int i = 0; i < num; i++)

{

    printf("Process %d\n", i + 1);

    printf("Burst Time:");

    scanf("%d", & burst_time[i]);

    proc[i] = i + 1;

    printf("Arrival Time:");

    scanf("%d", & arrival_time[i]);

    printf("\n");

}

switch (ch)

{

case 1:

    waitingtime1();

```

```

turnaroundtime();

printf
("Process\tArrival Time\tBurst Time\tWaiting Time\tTurnaround Time\n");

for (int i = 0; i < num; i++)

    printf("%d\t%d\t\t%d\t\t%d\t\t%d\n", proc[i], arrival_time[i],
        burst_time[i], wait_time[i], tat[i]);

avgtime();

break;

case 2:
    burstsort();

    waitingtime1();

    turnaroundtime();

    printf
    ("Process\tArrival Time\tBurst Time\tWaiting Time\tTurnaround Time\n");

    for (int i = 0; i < num; i++)

        printf("%d\t%d\t\t%d\t\t%d\t\t%d\n", proc[i], arrival_time[i],
            burst_time[i], wait_time[i], tat[i]);

    avgtime();
    break;

case 3:

    waitingtime2();

    turnaroundtime();

    printf
    ("Process\tArrival Time\tBurst Time\tWaiting Time\tTurnaround Time\n");

    for (int i = 0; i < num; i++)

```

```

    printf("%d\t%d\t%d\t%d\t%d\n", proc[i], arrival_time[i],
        burst_time[i], wait_time[i], tat[i]);

    avgtime();

    break;

}

return 0;

}

```

Output

```

C:\Users\admin\CS4SEM>a
1.FCFS
2.SJF
3.SRTF
Enter your choice:1
Enter the total number of processes:4
Process 1
Burst Time:12
Arrival Time:1

Process 2
Burst Time:4
Arrival Time:0

Process 3
Burst Time:3
Arrival Time:2

Process 4
Burst Time:5
Arrival Time:4

Process Arrival Time    Burst Time    Waiting Time    Turnaround Time
1         1             12            0              12
2         0             4             12             16
3         2             3             14             17
4         4             5             13             18
Average waiting time is 9.750000
Average turnaround time is 15.750000

```

```

C:\Users\admin\CS4SEM>a
1.FCFS
2.SJF
3.SRTF
Enter your choice:2
Enter the total number of processes:4
Process 1
Burst Time:12
Arrival Time:1

Process 2
Burst Time:4
Arrival Time:0

Process 3
Burst Time:3
Arrival Time:2

Process 4
Burst Time:5
Arrival Time:4

Process Arrival Time    Burst Time    Waiting Time    Turnaround Time
3      2      3      0      3
2      0      4      3      7
4      4      5      3      8
1      1     12      7     19
Average waiting time is 3.250000
Average turnaround time is 9.250000

```

```

C:\Users\admin\CS4SEM>a
1.FCFS
2.SJF
3.SRTF
Enter your choice:3
Enter the total number of processes:4
Process 1
Burst Time:12
Arrival Time:1

Process 2
Burst Time:4
Arrival Time:0

Process 3
Burst Time:3
Arrival Time:2

Process 4
Burst Time:5
Arrival Time:4

Process Arrival Time    Burst Time    Waiting Time    Turnaround Time
1      1     12     10     22
2      0      4      0      4
3      2      3      1      4
4      4      5      2      7
Average waiting time is 3.250000
Average turnaround time is 9.250000

```

Laboratory Program 2

Write a C program to simulate the following CPU scheduling algorithm to find turnaround time and waiting time.

☐ Priority (preemptive & Non-pre-emptive)

☐ Round Robin (Experiment with different quantum sizes for RR algorithm)

```
#include <stdio.h>
```

```
#define MAX_PROCESSES 10
```

```
void roundRobin(int burst_time[], int arrival_time[], int n, int time_quantum) {  
    int remaining_time[MAX_PROCESSES];  
    int waiting_time[MAX_PROCESSES] = {0};  
    int turnaround_time[MAX_PROCESSES] = {0};
```

```
    // Initialize the remaining time array with burst times  
    for (int i = 0; i < n; i++) {  
        remaining_time[i] = burst_time[i];  
    }
```

```
    int current_time = 0;  
    int completed = 0;  
    int front = 0, rear = 0;  
    int queue[MAX_PROCESSES];
```

```
    while (completed < n) {  
        for (int i = 0; i < n; i++) {  
            if (arrival_time[i] <= current_time && remaining_time[i] > 0) {  
                queue[rear++] = i;  
            }  
        }  
    }
```

```
    if (front == rear) {  
        current_time++;  
        continue;  
    }
```

```
    int process_index = queue[front];  
    front = (front + 1) % MAX_PROCESSES;
```

```
    if (remaining_time[process_index] <= time_quantum) {  
        current_time += remaining_time[process_index];
```

```

        turnaround_time[process_index] = current_time - arrival_time[process_index];
        waiting_time[process_index] = turnaround_time[process_index] -
burst_time[process_index];
        remaining_time[process_index] = 0;
        completed++;
    } else {
        current_time += time_quantum;
        remaining_time[process_index] -= time_quantum;
    }
}

// Calculate average waiting time and turnaround time
double avg_waiting_time = 0.0;
double avg_turnaround_time = 0.0;

for (int i = 0; i < n; i++) {
    avg_waiting_time += waiting_time[i];
    avg_turnaround_time += turnaround_time[i];
}

avg_waiting_time /= n;
avg_turnaround_time /= n;

// Print the results
printf("Round Robin Scheduling with Arrival Time\n");
printf("Process\tBurst Time\tArrival Time\tWaiting Time\tTurnaround Time\n");

for (int i = 0; i < n; i++) {
    printf("%d\t%d\t%d\t%d\t%d\n", i + 1, burst_time[i], arrival_time[i], waiting_time[i],
turnaround_time[i]);
}

printf("\nAverage Waiting Time: %.2f\n", avg_waiting_time);
printf("Average Turnaround Time: %.2f\n", avg_turnaround_time);
}

void preemptivePriority(int burst_time[], int arrival_time[], int priority[], int n) {
    int remaining_time[MAX_PROCESSES];
    int waiting_time[MAX_PROCESSES] = {0};
    int turnaround_time[MAX_PROCESSES] = {0};

    // Initialize the remaining time array with burst times
    for (int i = 0; i < n; i++) {
        remaining_time[i] = burst_time[i];

```

```

}

int current_time = 0;
int completed = 0;

while (completed < n) {
    int highest_priority = 9999; // Higher value means lower priority
    int selected_process = -1;

    for (int i = 0; i < n; i++) {
        if (arrival_time[i] <= current_time && remaining_time[i] > 0 && priority[i] <
highest_priority) {
            highest_priority = priority[i];
            selected_process = i;
        }
    }

    if (selected_process == -1) {
        current_time++;
        continue;
    }

    remaining_time[selected_process]--;
    current_time++;

    if (remaining_time[selected_process] == 0) {
        turnaround_time[selected_process] = current_time - arrival_time[selected_process];
        waiting_time[selected_process] = turnaround_time[selected_process] -
burst_time[selected_process];
        completed++;
    }
}

// Calculate average waiting time and turnaround time
double avg_waiting_time = 0.0;
double avg_turnaround_time = 0.0;

for (int i = 0; i < n; i++) {
    avg_waiting_time += waiting_time[i];
    avg_turnaround_time += turnaround_time[i];
}

avg_waiting_time /= n;
avg_turnaround_time /= n;

```

```

// Print the results
printf("\nPreemptive Priority Scheduling with Arrival Time\n");
printf("Process\tBurst Time\tArrival Time\tPriority\tWaiting Time\tTurnaround Time\n");

for (int i = 0; i < n; i++) {
    printf("%d\t%d\t%d\t%d\t%d\t%d\t%d\n", i + 1, burst_time[i], arrival_time[i], priority[i],
waiting_time[i], turnaround_time[i]);
}

printf("\nAverage Waiting Time: %.2f\n", avg_waiting_time);
printf("Average Turnaround Time: %.2f\n", avg_turnaround_time);
}

int main() {
    int n;
    printf("Enter the total number of processes (up to %d): ", MAX_PROCESSES);
    scanf("%d", &n);

    int burst_time[MAX_PROCESSES], arrival_time[MAX_PROCESSES], priority[MAX_PROCESSES];

    printf("Enter the burst time, arrival time, and priority for each process:\n");
    for (int i = 0; i < n; i++) {
        printf("Process %d\n", i + 1);
        printf("Burst Time: ");
        scanf("%d", &burst_time[i]);
        printf("Arrival Time: ");
        scanf("%d", &arrival_time[i]);
        printf("Priority: ");
        scanf("%d", &priority[i]);
    }

    int time_quantum;
    printf("Enter the time quantum for Round Robin: ");
    scanf("%d", &time_quantum);

    roundRobin(burst_time, arrival_time, n, time_quantum);
    preemptivePriority(burst_time, arrival_time, priority, n);

    return 0;
}

```


Output

```
C:\Users\admin\CS4SEM>gcc os.c

C:\Users\admin\CS4SEM>a
Enter the total number of processes (up to 10): 3
Enter the burst time, arrival time, and priority for each process:
Process 1
Burst Time: 12
Arrival Time: 1
Priority: 1
Process 2
Burst Time: 4
Arrival Time: 0
Priority: 2
Process 3
Burst Time: 3
Arrival Time: 2
Priority: 3
Enter the time quantum for Round Robin: 2
Round Robin Scheduling with Arrival Time
Process Burst Time      Arrival Time      Waiting Time      Turnaround Time
1         12             1                 0                 2
2          4             0                 6                 0
3          3             2                 6                 9

Average Waiting Time: 4.00
Average Turnaround Time: 3.67
```

```
Preemptive Priority Scheduling with Arrival Time
Process Burst Time      Arrival Time      Priority      Waiting Time      Turnaround Time
1         12             1                 1              0                 12
2          4             0                 2             12                 16
3          3             2                 3             14                 17

Average Waiting Time: 8.67
Average Turnaround Time: 15.00
```

Laboratory Program 3

Write a C program to simulate a multi-level queue scheduling algorithm considering the following scenario. All the processes in the system are divided into two categories – system processes and user processes. System processes are to be given higher priority than user processes. Use FCFS scheduling for the processes in each queue.

```
#include<stdio.h>
#include<stdbool.h>

#define MAX_QUEUE_SIZE 100

// Structure to represent a process
struct process {
    int pid;
    int priority;
    int burst_time;
};

// Function to implement FCFS scheduling algorithm
void fcfs_scheduling(struct process queue[], int size) {
    int total_time = 0;
    float average_wait_time = 0;
    float average_turnaround_time = 0;

    printf("\nProcess\tPriority\tBurst Time\tWaiting Time\tTurnaround Time\n");

    for (int i = 0; i < size; i++) {
        int waiting_time = total_time;
        int turnaround_time = waiting_time + queue[i].burst_time;

        printf("%d\t%d\t%d\t%d\t%d\n", queue[i].pid, queue[i].priority, queue[i].burst_time,
            waiting_time, turnaround_time);

        total_time += queue[i].burst_time;
        average_wait_time += waiting_time;
        average_turnaround_time += turnaround_time;
    }

    average_wait_time /= size;
    average_turnaround_time /= size;

    printf("\nAverage Waiting Time: %.2f\n", average_wait_time);
    printf("Average Turnaround Time: %.2f\n", average_turnaround_time);
}
```

```

}

int main() {
    int num_system_processes, num_user_processes;

    printf("Enter the number of system processes: ");
    scanf("%d", &num_system_processes);

    printf("Enter the number of user processes: ");
    scanf("%d", &num_user_processes);

    // Create queues for system processes and user processes
    struct process system_queue[MAX_QUEUE_SIZE];
    struct process user_queue[MAX_QUEUE_SIZE];

    // Accept details for system processes
    printf("\nEnter details for system processes:\n");
    for (int i = 0; i < num_system_processes; i++) {
        printf("\nProcess %d:\n", i + 1);
        system_queue[i].pid = i + 1;
        system_queue[i].priority = 1; // Higher priority for system processes
        printf("Enter burst time: ");
        scanf("%d", &system_queue[i].burst_time);
    }

    // Accept details for user processes
    printf("\nEnter details for user processes:\n");
    for (int i = 0; i < num_user_processes; i++) {
        printf("\nProcess %d:\n", i + 1);
        user_queue[i].pid = i + 1;
        user_queue[i].priority = 2; // Lower priority for user processes
        printf("Enter burst time: ");
        scanf("%d", &user_queue[i].burst_time);
    }

    printf("\n--- System Processes ---\n");
    fcfs_scheduling(system_queue, num_system_processes);

    printf("\n--- User Processes ---\n");
    fcfs_scheduling(user_queue, num_user_processes);

    // Preemptive execution of system processes
    int system_queue_index = 0;
    int user_queue_index = 0;

```

```

printf("\n--- Execution Order ---\n");
printf("Process\tPriority\tBurst Time\n");

while (system_queue_index < num_system_processes || user_queue_index <
num_user_processes) {
    if (system_queue_index < num_system_processes && user_queue_index <
num_user_processes) {
        // Compare the burst times of the current processes in both queues
        if (system_queue[system_queue_index].burst_time <=
user_queue[user_queue_index].burst_time) {
            printf("%d\t%d\t\t%d\n", system_queue[system_queue_index].pid,
system_queue[system_queue_index].priority,
system_queue[system_queue_index].burst_time);
            system_queue_index++;
        } else {
            printf("%d\t%d\t\t%d\n", user_queue[user_queue_index].pid,
user_queue[user_queue_index].priority, user_queue[user_queue_index].burst_time);
            user_queue_index++;
        }
    } else if (system_queue_index < num_system_processes) {
        printf("%d\t%d\t\t%d\n", system_queue[system_queue_index].pid,
system_queue[system_queue_index].priority,
system_queue[system_queue_index].burst_time);
        system_queue_index++;
    } else if (user_queue_index < num_user_processes) {
        printf("%d\t%d\t\t%d\n", user_queue[user_queue_index].pid,
user_queue[user_queue_index].priority, user_queue[user_queue_index].burst_time);
        user_queue_index++;
    }
}

return 0;
}

```

Output

```
C:\Users\admin\CS4SEM>gcc os.c

C:\Users\admin\CS4SEM>a
Enter the number of system processes: 3
Enter the number of user processes: 3

Enter details for system processes:

Process 1:
Enter burst time: 12

Process 2:
Enter burst time: 25

Process 3:
Enter burst time: 3

Enter details for user processes:

Process 1:
Enter burst time: 20

Process 2:
Enter burst time: 6

Process 3:
Enter burst time: 9
```

```
--- System Processes ---

Process Priority      Burst Time      Waiting Time      Turnaround Time
1         1           12              0                12
2         1           25              12               37
3         1            3              37               40

Average Waiting Time: 16.33
Average Turnaround Time: 29.67

--- User Processes ---

Process Priority      Burst Time      Waiting Time      Turnaround Time
1         2           20              0                20
2         2            6              20               26
3         2            9              26               35

Average Waiting Time: 15.33
Average Turnaround Time: 27.00
```

Laboratory Program 4

Write a C program to simulate Real-Time CPU Scheduling algorithms:

- a) Rate- Monotonic
- b) Earliest-deadline First
- c) Proportional scheduling

```
#include <stdio.h>
```

```
#define MAX_TASKS 100
```

```
// Structure to represent a task
```

```
struct task {  
    int id;  
    int period;  
    int execution_time;  
    int deadline;  
    int priority;  
    int response_time;  
    int start_time;  
    int finish_time;  
};
```

```
// Function to simulate Rate-Monotonic scheduling algorithm
```

```
void rate_monotonic(struct task tasks[], int num_tasks) {  
    printf("Rate-Monotonic Scheduling:\n");  
  
    int current_time = 0;  
    int total_response_time = 0;  
    int total_turnaround_time = 0;  
  
    for (int i = 0; i < num_tasks; i++) {  
        struct task current_task = tasks[i];  
  
        if (current_task.start_time > current_time)  
            current_time = current_task.start_time;  
  
        current_task.start_time = current_time;  
        current_task.finish_time = current_time + current_task.execution_time;  
        current_task.response_time = current_task.start_time;  
        total_response_time += current_task.response_time;  
        total_turnaround_time += current_task.finish_time;  
    }
```

```

    current_time += current_task.period;

    printf("Task %d: Start Time = %d, Finish Time = %d\n", current_task.id,
current_task.start_time, current_task.finish_time);
}

float average_response_time = (float)total_response_time / num_tasks;
float average_turnaround_time = (float)total_turnaround_time / num_tasks;

printf("Average Response Time: %.2f\n", average_response_time);
printf("Average Turnaround Time: %.2f\n", average_turnaround_time);
printf("\n");
}

// Function to simulate Earliest-Deadline First scheduling algorithm
void earliest_deadline_first(struct task tasks[], int num_tasks) {
    printf("Earliest-Deadline First Scheduling:\n");

    int current_time = 0;
    int total_response_time = 0;
    int total_turnaround_time = 0;

    for (int i = 0; i < num_tasks; i++) {
        struct task current_task = tasks[i];

        if (current_task.start_time > current_time)
            current_time = current_task.start_time;

        current_task.start_time = current_time;
        current_task.finish_time = current_time + current_task.execution_time;
        current_task.response_time = current_task.start_time;
        total_response_time += current_task.response_time;
        total_turnaround_time += current_task.finish_time;

        current_time += current_task.period;

        printf("Task %d: Start Time = %d, Finish Time = %d\n", current_task.id,
current_task.start_time, current_task.finish_time);
    }

    float average_response_time = (float)total_response_time / num_tasks;
    float average_turnaround_time = (float)total_turnaround_time / num_tasks;

    printf("Average Response Time: %.2f\n", average_response_time);

```

```

    printf("Average Turnaround Time: %.2f\n", average_turnaround_time);
    printf("\n");
}

// Function to simulate Proportional Scheduling algorithm
void proportional_scheduling(struct task tasks[], int num_tasks) {
    printf("Proportional Scheduling:\n");

    int current_time = 0;
    int total_response_time = 0;
    int total_turnaround_time = 0;

    int total_execution_time = 0;
    for (int i = 0; i < num_tasks; i++) {
        total_execution_time += tasks[i].execution_time;
    }

    for (int i = 0; i < num_tasks; i++) {
        struct task current_task = tasks[i];

        if (current_task.start_time > current_time)
            current_time = current_task.start_time;

        current_task.start_time = current_time;
        current_task.finish_time = current_time + (int)((float)current_task.execution_time /
total_execution_time * 100);
        current_task.response_time = current_task.start_time;
        total_response_time += current_task.response_time;
        total_turnaround_time += current_task.finish_time;

        current_time += (int)((float)current_task.execution_time / total_execution_time * 100);

        printf("Task %d: Start Time = %d, Finish Time = %d\n", current_task.id,
current_task.start_time, current_task.finish_time);
    }

    float average_response_time = (float)total_response_time / num_tasks;
    float average_turnaround_time = (float)total_turnaround_time / num_tasks;

    printf("Average Response Time: %.2f\n", average_response_time);
    printf("Average Turnaround Time: %.2f\n", average_turnaround_time);
    printf("\n");
}

```



```

int main() {
    int num_tasks;

    printf("Enter the number of tasks: ");
    scanf("%d", &num_tasks);

    struct task tasks[MAX_TASKS];

    // Accept task details from the user
    for (int i = 0; i < num_tasks; i++) {
        printf("\nTask %d:\n", i + 1);
        tasks[i].id = i + 1;

        printf("Enter the period: ");
        scanf("%d", &tasks[i].period);

        printf("Enter the execution time: ");
        scanf("%d", &tasks[i].execution_time);

        printf("Enter the deadline: ");
        scanf("%d", &tasks[i].deadline);

        printf("Enter the priority: ");
        scanf("%d", &tasks[i].priority);

        printf("Enter the start time: ");
        scanf("%d", &tasks[i].start_time);
    }

    rate_monotonic(tasks, num_tasks);
    earliest_deadline_first(tasks, num_tasks);
    proportional_scheduling(tasks, num_tasks);

    return 0;
}

```

Output

```
C:\Users\admin\CS4SEM>a
Enter the number of tasks: 3
```

```
Task 1:
Enter the period: 100
Enter the execution time: 25
Enter the deadline: 50
Enter the priority: 1
Enter the start time: 0
```

```
Task 2:
Enter the period: 50
Enter the execution time: 10
Enter the deadline: 30
Enter the priority: 2
Enter the start time: 10
```

```
Task 3:
Enter the period: 150
Enter the execution time: 50
Enter the deadline: 100
Enter the priority: 3
Enter the start time: 0
```

```
Rate-Monotonic Scheduling:
Task 1: Start Time = 0, Finish Time = 25
Task 2: Start Time = 100, Finish Time = 110
Task 3: Start Time = 150, Finish Time = 200
Average Response Time: 83.33
Average Turnaround Time: 111.67
```

```
Earliest-Deadline First Scheduling:
Task 1: Start Time = 0, Finish Time = 25
Task 2: Start Time = 100, Finish Time = 110
Task 3: Start Time = 150, Finish Time = 200
Average Response Time: 83.33
Average Turnaround Time: 111.67
```

```
Proportional Scheduling:
Task 1: Start Time = 0, Finish Time = 29
Task 2: Start Time = 29, Finish Time = 40
Task 3: Start Time = 40, Finish Time = 98
Average Response Time: 23.00
Average Turnaround Time: 55.67
```

Laboratory Program 5

Write a C program to simulate producer-consumer problem using semaphores.

```
#include<stdio.h>
#include<stdlib.h>
int mutex=1,full=0,empty,x=0;

int wait(int s)
{
    return (--s);
}

int signal(int s)
{
    return(++s);
}

void producer()
{
    mutex=wait(mutex);
    full=signal(full);
    empty=wait(empty);
    x++;
    printf("\nProducer produces Item %d",x);
    mutex=signal(mutex);
}

void consumer()
```

```

{
    mutex=wait(mutex);
    full=wait(full);
    empty=signal(empty);
    printf("\nConsumer consumes Item %d",x);
    x--;
    mutex=signal(mutex);
}

```

```

void printbuffer()

```

```

{
    if(full==0)
    {
        printf("Buffer is empty!\n");
        return;
    }
    printf("The contents of the buffer are:");
    for(int i=1;i<=full;i++)
        printf("%d\t",i);
}

```

```

int main()

```

```

{
    int n,ch;
    printf("Enter the buffer size:");
    scanf("%d",&n);
    empty=n;
    printf("\n1.Producer\n2.Consumer\n3.Print Buffer Contents\n4.Exit");
}

```

```
while(1)
{
    printf("\nEnter your choice:");
    scanf("%d",&ch);
    switch(ch)
    {
        case 1: if((mutex==1)&&(empty!=0))
            producer();
        else
            printf("Buffer is full!!");
            break;
        case 2: if((mutex==1)&&(full!=0))
            consumer();
        else
            printf("Buffer is empty!!");
            break;
        case 3:
            printbuffer();
            break;
        case 4: return 0;
    }
}
}
```

Output

```
C:\Users\admin\CS4SEM>a
Enter the buffer size:3

1.Producer
2.Consumer
3.Print Buffer Contents
4.Exit
Enter your choice:1

Producer produces Item 1
Enter your choice:1

Producer produces Item 2
Enter your choice:1

Producer produces Item 3
Enter your choice:1
Buffer is full!!
Enter your choice:3
The contents of the buffer are:1      2      3
Enter your choice:2

Consumer consumes Item 3
Enter your choice:3
The contents of the buffer are:1      2
Enter your choice:2

Consumer consumes Item 2
Enter your choice:2

Consumer consumes Item 1
Enter your choice:3
Buffer is empty!
```

Laboratory Program 6

Write a C program to simulate the concept of Dining - Philosophers problem.

```
#include <pthread.h>
#include <semaphore.h>
#include <stdio.h>
#include <unistd.h>
#include <stdlib.h>

#define N 5
#define THINKING 2
#define HUNGRY 1
#define EATING 0
#define LEFT (phnum + 4) % N
#define RIGHT (phnum + 1) % N

int eat=0;

int state[N];
int phil[N] = { 0, 1, 2, 3, 4 };

sem_t mutex;
sem_t S[N];

void test(int phnum)
{
    if (state[phnum] == HUNGRY && state[LEFT] != EATING && state[RIGHT] != EATING)
    {
        // state that eating
        state[phnum] = EATING;
        eat++;
        sleep(2);
        printf("Philosopher %d takes fork %d and %d\n", phnum + 1, LEFT + 1, phnum + 1);
        printf("Philosopher %d is Eating\n", phnum + 1);
        sem_post(&S[phnum]);
    }
}

// Take up chopsticks
void take_fork(int phnum)
{
    sem_wait(&mutex);
```

```

// Set state of thread to hungry
state[phnum] = HUNGRY;
printf("Philosopher %d is Hungry\n", phnum + 1);
// Start eating only if neighbours are not eating
test(phnum);
sem_post(&mutex);
// If neighbour is eating, wait to be signalled
sem_wait(&S[phnum]);
sleep(1);
}

// Put down chopsticks
void put_fork(int phnum)
{
    sem_wait(&mutex);
    // Set state of thread to thinking
    state[phnum] = THINKING;
    printf("Philosopher %d putting fork %d and %d down\n", phnum + 1, LEFT + 1, phnum + 1);
    printf("Philosopher %d is thinking\n", phnum + 1);
    test(LEFT);
    test(RIGHT);
    sem_post(&mutex);
}

void* philosopher(void* num)
{
    while (1)
    {
        int* i = num;
        sleep(1);
        take_fork(*i);
        eat=eat+1;
        sleep(0);
        put_fork(*i);
    }
}

int main()
{
    int i;
    pthread_t thread_id[N];
    // Initializing Semaphores
    sem_init(&mutex, 0, 1);
    for (i = 0; i < N; i++)

```



```

sem_init(&S[i], 0, 0);
for (i = 0; i < N; i++)
{
    pthread_create(&thread_id[i], NULL, philosopher, &phil[i]);
    printf("Philosopher %d is thinking\n", i + 1);
}
for (i = 0; i < N; i++)
pthread_join(thread_id[i], NULL);
return 0;
}

```

Output

```

C:\Users\admin\CS4SEM>a
Philosopher 1 is thinking
Philosopher 2 is thinking
Philosopher 3 is thinking
Philosopher 4 is thinking
Philosopher 5 is thinking
Philosopher 5 is Hungry
Philosopher 4 is Hungry
Philosopher 2 is Hungry
Philosopher 1 is Hungry
Philosopher 1 takes fork 5 and 1
Philosopher 1 is Eating
Philosopher 3 is Hungry
Philosopher 3 takes fork 2 and 3
Philosopher 3 is Eating
Philosopher 1 putting fork 5 and 1 down
Philosopher 1 is thinking
Philosopher 5 takes fork 4 and 5
Philosopher 5 is Eating
Philosopher 3 putting fork 2 and 3 down
Philosopher 3 is thinking
Philosopher 2 takes fork 1 and 2
Philosopher 2 is Eating
Philosopher 1 is Hungry
Philosopher 5 putting fork 4 and 5 down
Philosopher 5 is thinking
Philosopher 4 takes fork 3 and 4
Philosopher 4 is Eating
Philosopher 3 is Hungry
Philosopher 2 putting fork 1 and 2 down
Philosopher 2 is thinking
Philosopher 1 takes fork 5 and 1
Philosopher 1 is Eating
Philosopher 4 putting fork 3 and 4 down
Philosopher 4 is thinking

```

Laboratory Program 7

Write a C program to simulate Bankers algorithm for the purpose of deadlock avoidance.

```
#include<stdio.h>
#include<stdlib.h>
int allocation[25][25],available[25],max[25][25],need[25][25],work[25][25],safe[25];
int main()
{
    int n,m,i,j;
    printf("Enter the number of processes:");
    scanf("%d",&n);
    printf("Enter the number of resources:");
    scanf("%d",&m);
    printf("Enter the allocation matrix:\n");
    for(i=0;i<n;i++)
    {
        for(j=0;j<m;j++)
            scanf("%d",&allocation[i][j]);
    }
    printf("Enter the maximum resources matrix:\n");
    for(i=0;i<n;i++)
    {
        for(j=0;j<m;j++)
            scanf("%d",&max[i][j]);
    }
    for(i=0;i<n;i++)
    {
        for(j=0;j<m;j++)
            need[i][j]=max[i][j]-allocation[i][j];
    }
    printf("Enter the available resources vector:\n");
    for(i=0;i<m;i++)
        scanf("%d",&available[i]);
    printf("Need Matrix :\n");
    for(i=0;i<n;i++)
    {
        for(j=0;j<m;j++)
            printf("%d ",need[i][j]);
        printf("\n");
    }
    int f[n], ans[n], ind = 0;
    for (i = 0; i < n; i++)
```

```

{
    f[i] = 0;
}
int y = 0,k;
for (k = 0; k < 5; k++) {
    for (i = 0; i < n; i++) {
        if (f[i] == 0) {

            int flag = 0;
            for (j = 0; j < m; j++) {
                if (need[i][j] > available[j]){
                    flag = 1;
                    break;
                }
            }

            if (flag == 0) {
                ans[ind++] = i;
                for (y = 0; y < m; y++)
                    available[y] += allocation[i][y];
                f[i] = 1;
            }
        }
    }
}

```

```

int flag = 1;

```

```

// To check if sequence is safe or not
for(int i = 0;i<n;i++)
{
    if(f[i]==0)
    {
        flag = 0;
        printf("The system is not in safe state.");
        break;
    }
}

```

```

if(flag==1)
{
    printf( "The safe sequence for the system is:\n");
    for (i = 0; i < n - 1; i++)
        printf( " P%d->",ans[i]);
}

```

```
        printf(" P%d\n",ans[n - 1]);  
    }  
  
    return 0;  
}
```

Output

```
C:\Users\admin\CS4SEM>a  
Enter the number of processes:5  
Enter the number of resources:3  
Enter the allocation matrix:  
0 1 0  
2 0 0  
3 0 2  
2 1 1  
0 0 2  
Enter the maximum resources matrix:  
7 5 3  
3 2 2  
9 0 2  
2 2 2  
4 3 3  
Enter the available resources vector:  
3 3 2  
Need Matrix :  
7 4 3  
1 2 2  
6 0 0  
0 1 1  
4 3 1  
The safe sequence for the system is:  
P1-> P3-> P4-> P0-> P2
```

Laboratory Program 8

Write a C program to simulate deadlock detection.

```
#include<stdio.h>
#include<stdlib.h>
int allocation[25][25],available[25],req[25][25];
int main()
{
    int n,m,i,j;
    printf("Enter the number of processes:");
    scanf("%d",&n);
    printf("Enter the number of resources:");
    scanf("%d",&m);
    printf("Enter the allocation matrix:\n");
    for(i=0;i<n;i++)
    {
        for(j=0;j<m;j++)
            scanf("%d",&allocation[i][j]);
    }
    printf("Enter the request matrix:\n");
    for(i=0;i<n;i++)
    {
        for(j=0;j<m;j++)
            scanf("%d",&req[i][j]);
    }
    printf("Enter the available resources vector:\n");
    for(i=0;i<m;i++)
        scanf("%d",&available[i]);
    int f[n], ans[n], ind = 0;
    for (i = 0; i < n; i++)
    {
        f[i] = 0;
    }
    int y = 0,k;
    for (k = 0; k < 5; k++) {
        for (i = 0; i < n; i++) {
            if (f[i] == 0) {

                int flag = 0;
                for (j = 0; j < m; j++) {
                    if (req[i][j] > available[j]){
                        flag = 1;
                        break;
                    }
                }
            }
        }
    }
}
```

```

    }
    }

    if (flag == 0) {
        ans[ind++] = i;
        for (y = 0; y < m; y++)
            available[y] += allocation[i][y];
        f[i] = 1;
    }
    }
    }
}

int flag = 1;

// To check if sequence is safe or not
for(int i = 0; i < n; i++)
{
    if(f[i]==0)
    {
        flag = 0;
        printf("Deadlock is encountered.");
        break;
    }
}

if(flag==1)
{
    printf("Deadlock is not encountered.The safe sequence for the system is:\n");
    for (i = 0; i < n - 1; i++)
        printf(" P%d->", ans[i]);
    printf(" P%d\n", ans[n - 1]);
}

return 0;
}

```

Output

```
C:\Users\admin\CS4SEM>a
Enter the number of processes:5
Enter the number of resources:3
Enter the allocation matrix:
1 1 1
2 0 2
0 2 0
7 0 1
0 0 1
Enter the request matrix:
0 1 0
1 2 2
3 3 0
1 1 1
5 0 1
Enter the available resources vector:
0 2 0
Deadlock is not encountered.The safe sequence for the system is:
P0-> P3-> P4-> P1-> P2
```

Laboratory Program 9

Write a C program to simulate the following contiguous memory allocation techniques:

- a) Worst-fit
- b) Best-fit
- c) First-fit

```
#include<stdio.h>
#include<stdlib.h>
int frag[100],block[100],files[100],nf,nb;
int maximum()
{
    int max=block[0];
    for(int i=1;i<nb;i++)
    {
        if(block[i]>max)
            max=block[i];
    }

    return max;
}
int minimum(int filesize)
{
    int min=block[0]-filesize;
    int temp=block[0];
    for(int i=1;i<nb;i++)
    {
        int diff=block[i]-filesize;
        if(diff<min&&diff>0)
        {
            min=diff;
            temp=block[i];
        }
    }

    return temp;
}
void worstfit()
{
    int i,j,blockpos;
    printf("Worst Fit Memory Allocation\nFile Number\tFile Size\tBlock Number\tBlock
Size\tFragment\n");
    for(i=0;i<nf;i++)
```



```

{
    int tempmax=maximum();
    blockpos=-2;
    if(files[i]<=tempmax)
    {
        for(j=0;j<nb;j++)
        {
            if(block[j]==tempmax)
            {
                blockpos=j;
                break;
            }
        }
        frag[blockpos]=block[blockpos]-files[i];
        block[blockpos]=-1;

printf("%d\t\t%d\t\t%d\t\t%d\t\t%d\n",i+1,files[i],blockpos+1,tempmax,frag[blockpos]);
    }
    else
    {
        printf("%d\t\t%d\t\t-----Not Allocated-----\n",i+1,files[i]);
    }
}

}

void firstfit()
{
    int i,j,alloc=0;
    printf("First Fit Memory Allocation\nFile Number\tFile Size\tBlock Number\tBlock
Size\tFragment\n");
    for(i=0;i<nf;i++)
    {
        alloc=0;
        for(j=0;j<nb;j++)
        {
            if(files[i]<=block[j])
            {
                alloc=1;
                break;
            }
        }
        if(alloc==1)
        {
            frag[i]=block[j]-files[i];

```

```

        printf("%d\t%d\t%d\t%d\t%d\n",i+1,files[i],j+1,block[j],frag[i]);
        block[j]=frag[i];
    }
    else
        printf("%d\t%d\t-----Not Allocated-----\n",i+1,files[i]);
}
}
void bestfit()
{
    int i,j,blockpos;
    printf("Best Fit Memory Allocation\nFile Number\tFile Size\tBlock Number\tBlock
Size\tFragment\n");
    for(i=0;i<nf;i++)
    {
        int tempbest=minimum(files[i]);
        //printf("%d",tempbest);
        blockpos=-2;
        if(files[i]<=tempbest)
        {
            for(j=0;j<nb;j++)
            {
                if(block[j]==tempbest)
                {
                    blockpos=j;
                    break;
                }
            }
            frag[blockpos]=block[blockpos]-files[i];
            block[blockpos]=frag[blockpos];

printf("%d\t%d\t%d\t%d\t%d\n",i+1,files[i],blockpos+1,tempbest,frag[blockpos]);
        }
        else
        {
            printf("%d\t%d\t-----Not Allocated-----\n",i+1,files[i]);
        }
    }
}
int main(int argc,char *argv[])
{
    int i,j;
    printf("Enter the number of blocks:");
    scanf("%d",&nb);

```

```

printf("Enter the size of each block:\n");
for(i=0;i<nb;i++)
{
    printf("Block %d:",i+1);
    scanf("%d",&block[i]);
}
printf("\nEnter the number of files:");
scanf("%d",&nf);
printf("\nEnter the size of each file:\n");
for(i=0;i<nf;i++)
{
    printf("File %d:",i+1);
    scanf("%d",&files[i]);
}
int ch;
printf("\n1.Worst Fit\n2.First Fit\n3.Best Fit\nEnter your choice:");
scanf("%d",&ch);
switch(ch)
{
    case 1:worstfit();
    break;
    case 2:firstfit();
    break;
    case 3:bestfit();
    break;
    default:return 0;
}
}

```

Output

```
C:\Users\admin\CS4SEM>gcc os.c

C:\Users\admin\CS4SEM>a
Enter the number of blocks:3
Enter the size of each block:
Block 1:5
Block 2:2
Block 3:7

Enter the number of files:2

Enter the size of each file:
File 1:1
File 2:4

1.Worst Fit
2.First Fit
3.Best Fit
Enter your choice:1
Worst Fit Memory Allocation


| File Number | File Size | Block Number | Block Size | Fragment |
|-------------|-----------|--------------|------------|----------|
| 1           | 1         | 3            | 7          | 6        |
| 2           | 4         | 1            | 5          | 1        |


```

```
C:\Users\admin\CS4SEM>a
Enter the number of blocks:3
Enter the size of each block:
Block 1:5
Block 2:2
Block 3:7

Enter the number of files:2

Enter the size of each file:
File 1:1
File 2:4

1.Worst Fit
2.First Fit
3.Best Fit
Enter your choice:2
First Fit Memory Allocation


| File Number | File Size | Block Number | Block Size | Fragment |
|-------------|-----------|--------------|------------|----------|
| 1           | 1         | 1            | 5          | 4        |
| 2           | 4         | 1            | 4          | 0        |


```

C:\Users\admin\CS4SEM>a

Enter the number of blocks:3

Enter the size of each block:

Block 1:5

Block 2:2

Block 3:7

Enter the number of files:2

Enter the size of each file:

File 1:1

File 2:4

1.Worst Fit

2.First Fit

3.Best Fit

Enter your choice:3

Best Fit Memory Allocation

File Number	File Size	Block Number	Block Size	Fragment
1	1	2	2	1
2	4	1	5	1

Laboratory Program 10

Write a C program to simulate paging technique of memory management.

```
#include<stdio.h>
int main()
{
    int memsize,pagesize,i,j,procpages=4,nproc;
    printf("Enter the memory size:");
    scanf("%d",&memsize);
    printf("\nEnter the page size of main memory:");
    scanf("%d",&pagesize);
    int npages=memsize/pagesize;
    printf("\nEnter the number of processes:");
    scanf("%d",&nproc);
    int processes[nproc][procpages];
    int frame[nproc];
    int phymem[50][50];
    printf("Enter the page frame:\n");
    for(i=0;i<nproc;i++)
    {
        printf("Process %d:",i+1);
        scanf("%d",&frame[i]);
    }
    for(i=0;i<nproc;i++)
    {
        /*printf("Enter the number of pages required for Process %d:",i+1);
        scanf("%d",&procpages);*/
        printf("\nEnter the page table for Process %d:\n",i+1);
        for(j=0;j<procpages;j++)
        {
            scanf("%d",&processes[i][j]);
        }
    }
    char logi,a;
    while(1)
    {
        printf("\nEnter the logical address:");
        scanf("%c",&a);
        scanf("%c",&logi);
        int logicaladd=(int)logi-97;

        if(logicaladd<=-1 || logicaladd>=40)
        {
```

```

printf("Invalid Logical address!\n");

printf("Page number\tData\n");
for(int x=0;x<npages;x++)
{
printf("%d\t\t",x);
for(int y=0;y<4;y++)
{
printf("%c\n",(char)phymem[x][y]);
}
}

return 0;
}
int offset=logicaladd%procpages;
for(i=0;i<nproc;i++)
{
for(j=0;j<4;j++)
{
if(processes[i][j]==logicaladd)
{
int phy=(procpages*frame[i])+offset;
//phyadd[frame[i]][phy]=logicaladd+97;
printf("Physical address is %d",phy);
}
}
}
}
}

```

Output

```
C:\Users\admin\CS4SEM>a
Enter the memory size:100

Enter the page size of main memory:4

Enter the number of processes:3
Enter the page frame:
Process 1:6
Process 2:5
Process 3:1

Enter the page table for Process 1:
0 1 2 3

Enter the page table for Process 2:
4 5 6 7

Enter the page table for Process 3:
8 9 10 11

Enter the logical address:a
Physical address is 24
Enter the logical address:d
Physical address is 27
Enter the logical address:e
Physical address is 20
Enter the logical address:f
Physical address is 21
Enter the logical address:j
Physical address is 5
Enter the logical address:k
Physical address is 6
Enter the logical address:
```


Laboratory Program 11

Write a C program to simulate page replacement algorithms:

- a) FIFO
- b) LRU
- c) Optimal

```
#include <stdio.h>
```

```
#define MAX_FRAMES 10
```

```
#define MAX_PAGES 100
```

```
int frames[MAX_FRAMES];
```

```
int pageQueue[MAX_FRAMES];
```

```
int pageQueueSize = 0;
```

```
int pageQueueFront = 0;
```

```
int findInFrames(int page, int numFrames) {
```

```
    for (int i = 0; i < numFrames; i++) {
```

```
        if (frames[i] == page) {
```

```
            return i;
```

```
        }
```

```
    }
```

```
    return -1;
```

```
}
```

```
void displayFrames(int numFrames) {
```

```
    printf("Current frames: ");
```

```
    for (int i = 0; i < numFrames; i++) {
```

```
        if (frames[i] != -1) {
```

```
            printf("%d ", frames[i]);
```

```
        }
```

```
    }
```

```
    printf("\n");
```

```
}
```

```
int findLRUIndex(int numFrames) {
```

```
    int index = 0;
```

```
    int min = pageQueueSize + 1;
```

```
    for (int i = 0; i < numFrames; i++) {
```

```
        int currentPage = frames[i];
```

```
        int j;
```

```
        for (j = pageQueueFront; j < pageQueueSize; j++) {
```

```

        if (pageQueue[j] == currentPage) {
            break;
        }
    }

    if (j < min) {
        min = j;
        index = i;
    }
}

return index;
}

int main() {
    int numFrames, numPages;

    printf("Enter the number of frames: ");
    scanf("%d", &numFrames);

    printf("Enter the number of pages: ");
    scanf("%d", &numPages);

    printf("Enter the page reference string:\n");
    for (int i = 0; i < numPages; i++) {
        scanf("%d", &pageQueue[i]);
        pageQueueSize++;
    }

    for (int i = 0; i < numFrames; i++) {
        frames[i] = -1;
    }

    int faultsFIFO = 0, faultsLRU = 0, faultsOptimal = 0;

    printf("\nFIFO Page Replacement Algorithm:\n");
    pageQueueFront = 0;
    for (int i = 0; i < numPages; i++) {
        int currentPage = pageQueue[i];
        if (findInFrames(currentPage, numFrames) == -1) {
            frames[pageQueueFront] = currentPage;
            pageQueueFront = (pageQueueFront + 1) % numFrames;
            displayFrames(numFrames);
            faultsFIFO++;
        }
    }
}

```

```
}  
}
```

```
printf("\nLRU Page Replacement Algorithm:\n");  
pageQueueFront = 0;  
for (int i = 0; i < numPages; i++) {  
    int currentPage = pageQueue[i];  
    if (findInFrames(currentPage, numFrames) == -1) {  
        int index = findLRUIndex(numFrames);  
        frames[index] = currentPage;  
        pageQueue[pageQueueSize] = currentPage;  
        pageQueueSize++;  
        displayFrames(numFrames);  
        faultsLRU++;  
    }  
}
```

```
printf("\nOptimal Page Replacement Algorithm:\n");  
for (int i = 0; i < numFrames; i++) {  
    frames[i] = -1;  
}
```

```
for (int i = 0; i < numPages; i++) {  
    int currentPage = pageQueue[i];  
    if (findInFrames(currentPage, numFrames) == -1) {  
        int optimalIndex = -1;  
        int maxDistance = -1;  
  
        for (int j = 0; j < numFrames; j++) {  
            int nextPage = frames[j];  
            int distance = -1;  
  
            for (int k = i + 1; k < numPages; k++) {  
                if (pageQueue[k] == nextPage) {  
                    distance = k - i;  
                    break;  
                }  
            }  
  
            if (distance == -1) {  
                optimalIndex = j;  
                break;  
            }  
        }  
    }  
}
```

```
        if (distance > maxDistance) {
            maxDistance = distance;
            optimalIndex = j;
        }
    }

    frames[optimalIndex] = currentPage;
    displayFrames(numFrames);
    faultsOptimal++;
}

printf("\nTotal Page Faults:\n");
printf("FIFO: %d\n", faultsFIFO);
printf("LRU: %d\n", faultsLRU);
printf("Optimal: %d\n", faultsOptimal);

return 0;
}
```

Output

```
C:\Users\admin\CS4SEM>gcc os.c

C:\Users\admin\CS4SEM>a
Enter the number of frames: 4
Enter the number of pages: 10
Enter the page reference string:
7 0 1 2 3 4 3 4 0 2

FIFO Page Replacement Algorithm:
Current frames: 7
Current frames: 7 0
Current frames: 7 0 1
Current frames: 7 0 1 2
Current frames: 3 0 1 2
Current frames: 3 4 1 2
Current frames: 3 4 0 2

LRU Page Replacement Algorithm:
Current frames: 3 4 7 2
Current frames: 3 4 0 2
Current frames: 3 4 1 2
Current frames: 3 4 0 2
Current frames: 1 4 0 2
```

```
LRU Page Replacement Algorithm:
Current frames: 3 4 7 2
Current frames: 3 4 0 2
Current frames: 3 4 1 2
Current frames: 3 4 0 2
Current frames: 1 4 0 2

Optimal Page Replacement Algorithm:
Current frames: 7
Current frames: 1
Current frames: 1 2
Current frames: 1 3
Current frames: 1 3 4
Current frames: 1 0 4

Total Page Faults:
FIFO: 7
LRU: 5
Optimal: 6
```

Laboratory Program 12

Write a C program to simulate the following file allocation strategies:

- a) Sequential
- b) Indexed
- c) Linked

```
#include <stdio.h>
#include <stdlib.h>

#define MAX_BLOCKS 100
#define MAX_FILES 10

// Data structures
struct File {
    int size;
    int blocks[MAX_BLOCKS];
};

struct IndexedFile {
    int size;
    int index_block;
};

struct LinkedBlock {
    int data;
    int next_block;
};

// Functions for Sequential File Allocation
void allocateSequential(struct File files[], int num_files, int total_blocks) {
    int current_block = 0;

    printf("\nSequential File Allocation:\n");
    for (int i = 0; i < num_files; i++) {
        if (current_block + files[i].size <= total_blocks) {
            for (int j = current_block; j < current_block + files[i].size; j++) {
                files[i].blocks[j - current_block] = j;
            }
            current_block += files[i].size;
            printf("File %d allocated blocks: ", i + 1);
            for (int j = 0; j < files[i].size; j++) {
                printf("%d ", files[i].blocks[j]);
            }
        }
    }
}
```

```

        printf("\n");
    } else {
        printf("File %d cannot be allocated due to insufficient space.\n", i + 1);
    }
}
}

```

// Functions for Indexed File Allocation

```

void allocateIndexed(struct IndexedFile files[], int num_files, int total_blocks, int index_blocks) {
    int current_block = index_blocks;

```

```

    printf("\nIndexed File Allocation:\n");
    for (int i = 0; i < num_files; i++) {
        if (current_block < total_blocks) {
            files[i].index_block = current_block;
            current_block++;
            printf("File %d index block: %d\n", i + 1, files[i].index_block);
        } else {
            printf("File %d cannot be allocated due to insufficient index space.\n", i + 1);
        }
    }
}

```

// Functions for Linked File Allocation

```

void allocateLinked(struct LinkedBlock blocks[], int num_blocks, struct File files[], int num_files)
{

```

```

    int current_block = 0;

    printf("\nLinked File Allocation:\n");
    for (int i = 0; i < num_files; i++) {
        if (current_block + files[i].size <= num_blocks) {
            for (int j = 0; j < files[i].size; j++) {
                blocks[current_block + j].data = i + 1;
                blocks[current_block + j].next_block = (j == files[i].size - 1) ? -1 : current_block + j + 1;
            }
            current_block += files[i].size;
            printf("File %d allocated blocks:\n", i + 1);
            for (int j = 0; j < files[i].size; j++) {
                printf("Block %d: Data %d, Next Block %d\n", current_block - files[i].size + j + 1,
                    blocks[current_block - files[i].size + j].data, blocks[current_block - files[i].size + j].next_block);
            }
        } else {
            printf("File %d cannot be allocated due to insufficient space.\n", i + 1);
        }
    }
}

```

```

    }
}

int main() {
    int total_blocks, index_blocks;

    printf("Enter the total number of blocks: ");
    scanf("%d", &total_blocks);

    printf("Enter the number of index blocks for indexed allocation: ");
    scanf("%d", &index_blocks);

    int num_files;
    printf("Enter the number of files (up to %d): ", MAX_FILES);
    scanf("%d", &num_files);

    struct File files[MAX_FILES];
    struct IndexedFile indexedFiles[MAX_FILES];
    struct LinkedBlock blocks[MAX_BLOCKS];

    printf("Enter the size of each file:\n");
    for (int i = 0; i < num_files; i++) {
        printf("File %d: ", i + 1);
        scanf("%d", &files[i].size);
        for (int j = 0; j < MAX_BLOCKS; j++) {
            files[i].blocks[j] = -1;
        }
    }

    allocateSequential(files, num_files, total_blocks);
    allocateIndexed(indexedFiles, num_files, total_blocks, index_blocks);
    allocateLinked(blocks, total_blocks, files, num_files);

    return 0;
}

```


Output

```
C:\Users\admin\CS4SEM>gcc os.c

C:\Users\admin\CS4SEM>a
Enter the total number of blocks: 4
Enter the number of index blocks for indexed allocation: 1
Enter the number of files (up to 10): 3
Enter the size of each file:
File 1: 12
File 2: 4
File 3: 6

Sequential File Allocation:
File 1 cannot be allocated due to insufficient space.
File 2 allocated blocks: 0 1 2 3
File 3 cannot be allocated due to insufficient space.

Indexed File Allocation:
File 1 index block: 1
File 2 index block: 2
File 3 index block: 3
```

```
Linked File Allocation:
File 1 cannot be allocated due to insufficient space.
File 2 allocated blocks:
Block 1: Data 2, Next Block 1
Block 2: Data 2, Next Block 2
Block 3: Data 2, Next Block 3
Block 4: Data 2, Next Block -1
File 3 cannot be allocated due to insufficient space.
```

Laboratory Program 13

Write a C program to simulate the following file organization techniques:

- a) Single level directory
- b) Two level directory
- c) Hierarchical

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#define MAX_FILES 100
```

```
struct File {  
    char name[20];  
    int size;  
};
```

```
struct SingleLevelDirectory {  
    struct File files[MAX_FILES];  
    int num_files;  
};
```

```
struct TwoLevelDirectory {  
    struct File files[MAX_FILES];  
    int num_files;  
    struct Directory1 {  
        char name[20];  
        int num_files;  
    } directories[MAX_FILES];  
    int num_directories;  
};
```

```
struct HierarchicalDirectory {  
    struct File files[MAX_FILES];  
    int num_files;  
    struct Directory2 {  
        char name[20];  
        int num_files;  
        struct SubDirectory {  
            char name[20];  
            int num_files;  
        } subdirectories[MAX_FILES];  
        int num_subdirectories;  
    };  
};
```

```

    } directories[MAX_FILES];
    int num_directories;
};

int main() {
    int choice;

    printf("Select file organization technique:\n");
    printf("1. Single level directory\n");
    printf("2. Two level directory\n");
    printf("3. Hierarchical directory\n");
    printf("Enter your choice: ");
    scanf("%d", &choice);

    switch (choice) {
        case 1: {
            struct SingleLevelDirectory dir;
            dir.num_files = 0;

            int num_files;
            printf("Enter the number of files: ");
            scanf("%d", &num_files);

            printf("Enter file details:\n");
            for (int i = 0; i < num_files; i++) {
                printf("File %d name: ", i + 1);
                scanf("%s", dir.files[i].name);
                printf("File %d size: ", i + 1);
                scanf("%d", &dir.files[i].size);
                dir.num_files++;
            }

            printf("\nSingle Level Directory:\n");
            for (int i = 0; i < dir.num_files; i++) {
                printf("File name: %s, Size: %d\n", dir.files[i].name, dir.files[i].size);
            }

            break;
        }
        case 2: {
            struct TwoLevelDirectory dir;
            dir.num_files = 0;
            dir.num_directories = 0;

```

```

int num_files, num_directories;
printf("Enter the number of directories: ");
scanf("%d", &num_directories);
dir.num_directories = num_directories;

for (int i = 0; i < num_directories; i++) {
    printf("Enter directory %d name: ", i + 1);
    scanf("%s", dir.directories[i].name);
    dir.directories[i].num_files = 0;

    printf("Enter the number of files in directory %s: ", dir.directories[i].name);
    scanf("%d", &num_files);

    printf("Enter file details:\n");
    for (int j = 0; j < num_files; j++) {
        printf("File %d name: ", j + 1);
        scanf("%s", dir.files[dir.num_files].name);
        printf("File %d size: ", j + 1);
        scanf("%d", &dir.files[dir.num_files].size);
        dir.directories[i].num_files++;
        dir.num_files++;
    }
}

printf("\nTwo Level Directory:\n");
for (int i = 0; i < num_directories; i++) {
    printf("Directory name: %s\n", dir.directories[i].name);
    for (int j = 0; j < dir.directories[i].num_files; j++) {
        printf("File name: %s, Size: %d\n", dir.files[j].name, dir.files[j].size);
    }
}

break;
}
case 3: {
    struct HierarchicalDirectory dir;
    dir.num_files = 0;
    dir.num_directories = 0;

    int num_files, num_directories;
    printf("Enter the number of directories: ");
    scanf("%d", &num_directories);
    dir.num_directories = num_directories;

```

```

for (int i = 0; i < num_directories; i++) {
    printf("Enter directory %d name: ", i + 1);
    scanf("%s", dir.directories[i].name);
    dir.directories[i].num_files = 0;
    dir.directories[i].num_subdirectories = 0;

    printf("Enter the number of subdirectories in directory %s: ", dir.directories[i].name);
    scanf("%d", &dir.directories[i].num_subdirectories);

    for (int j = 0; j < dir.directories[i].num_subdirectories; j++) {
        printf("Enter subdirectory %d name: ", j + 1);
        scanf("%s", dir.directories[i].subdirectories[j].name);
        dir.directories[i].subdirectories[j].num_files = 0;

        printf("Enter the number of files in subdirectory %s: ",
dir.directories[i].subdirectories[j].name);
        scanf("%d", &num_files);

        printf("Enter file details:\n");
        for (int k = 0; k < num_files; k++) {
            printf("File %d name: ", k + 1);
            scanf("%s", dir.files[dir.num_files].name);
            printf("File %d size: ", k + 1);
            scanf("%d", &dir.files[dir.num_files].size);
            dir.directories[i].subdirectories[j].num_files++;
            dir.directories[i].num_files++;
            dir.num_files++;
        }
    }
}

printf("\nHierarchical Directory:\n");
for (int i = 0; i < num_directories; i++) {
    printf("Directory name: %s\n", dir.directories[i].name);
    for (int j = 0; j < dir.directories[i].num_subdirectories; j++) {
        printf("Subdirectory name: %s\n", dir.directories[i].subdirectories[j].name);
        for (int k = 0; k < dir.directories[i].subdirectories[j].num_files; k++) {
            printf("File name: %s, Size: %d\n", dir.files[k].name, dir.files[k].size);
        }
    }
}


break;
}

```

```
        default:
            printf("Invalid choice.\n");
            break;
    }

    return 0;
}
```

Output



```
C:\Users\admin\CS4SEM>a
Select file organization technique:
1. Single level directory
2. Two level directory
3. Hierarchical directory
Enter your choice: 1
Enter the number of files: 4
Enter file details:
File 1 name: file1
File 1 size: 12
File 2 name: file2
File 2 size: 36
File 3 name: file3
File 3 size: 25
File 4 name: file4
File 4 size: 20

Single Level Directory:
File name: file1, Size: 12
File name: file2, Size: 36
File name: file3, Size: 25
File name: file4, Size: 20
```

```

C:\Users\admin\CS4SEM>a
Select file organization technique:
1. Single level directory
2. Two level directory
3. Hierarchical directory
Enter your choice: 2
Enter the number of directories: 2
Enter directory 1 name: direc1
Enter the number of files in directory direc1: 2
Enter file details:
File 1 name: file1direc1
File 1 size: 12
File 2 name: file2direc1
File 2 size: 25
Enter directory 2 name: direc2
Enter the number of files in directory direc2: 1
Enter file details:
File 1 name: file1direc2
File 1 size: 30

```

```

Two Level Directory:
Directory name: direc1
File name: file1direc1, Size: 12
File name: file2direc1, Size: 25
Directory name: direc2
File name: file1direc1, Size: 12

```

```

C:\Users\admin\CS4SEM>a
Select file organization technique:
1. Single level directory
2. Two level directory
3. Hierarchical directory
Enter your choice: 3
Enter the number of directories: 3
Enter directory 1 name: user1
Enter the number of subdirectories in directory user1: 2
Enter subdirectory 1 name: user1child1
Enter the number of files in subdirectory user1child1: 0
Enter file details:
Enter subdirectory 2 name: user1child2
Enter the number of files in subdirectory user1child2: 1
Enter file details:
File 1 name: file1_user1child2
File 1 size: 12
Enter directory 2 name: user2
Enter the number of subdirectories in directory user2: 0
Enter directory 3 name: user3
Enter the number of subdirectories in directory user3: 0

```

```

Hierarchical Directory:
Directory name: user1
Subdirectory name: user1child1
Subdirectory name: user1child2
File name: file1_user1child2, Size: 12
Directory name: user2
Directory name: user3

```

Laboratory Program 14

Write a C program to simulate disk scheduling algorithms:

- a) FCFS
- b) SCAN
- c) C-SCAN

```
#include<stdio.h>
#include<stdlib.h>
void fcfs()
{
    int RQ[100],i,n,TotalHeadMoment=0,initial;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);

    // logic for FCFS disk scheduling

    for(i=0;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    printf("Total head moment is %d",TotalHeadMoment);
}
void scan()
{
    int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);
    printf("Enter total disk size\n");
    scanf("%d",&size);
    printf("Enter the head movement direction for high 1 and for low 0\n");
    scanf("%d",&move);
```



```
// logic for Scan disk scheduling
```

```
    /*logic for sort the request array */  
    for(i=0;i<n;i++)  
    {  
        for(j=0;j<n-i-1;j++)  
        {  
            if(RQ[j]>RQ[j+1])  
            {  
                int temp;  
                temp=RQ[j];  
                RQ[j]=RQ[j+1];  
                RQ[j+1]=temp;  
            }  
        }  
    }  
}
```

```
int index;  
for(i=0;i<n;i++)  
{  
    if(initial<RQ[i])  
    {  
        index=i;  
        break;  
    }  
}
```

```
// if movement is towards high value  
if(move==1)  
{  
    for(i=index;i<n;i++)  
    {  
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);  
        initial=RQ[i];  
    }  
    // last movement for max size  
    TotalHeadMoment=TotalHeadMoment+abs(size-RQ[i-1]-1);  
    initial = size-1;  
    for(i=index-1;i>=0;i--)  
    {
```

```

        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}
// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
    // last movement for min size
    TotalHeadMoment=TotalHeadMoment+abs(RQ[i+1]-0);
    initial =0;
    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

printf("Total head movement is %d",TotalHeadMoment);
}

```

```

void cscan()
{
    int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);
    printf("Enter total disk size\n");
    scanf("%d",&size);
    printf("Enter the head movement direction for high 1 and for low 0\n");
    scanf("%d",&move);

    // logic for C-Scan disk scheduling

```

```

    /*logic for sort the request array */
    for(i=0;i<n;i++)
    {
        for( j=0;j<n-i-1;j++)
        {
            if(RQ[j]>RQ[j+1])
            {
                int temp;
                temp=RQ[j];
                RQ[j]=RQ[j+1];

                RQ[j+1]=temp;
            }
        }
    }

    int index;
    for(i=0;i<n;i++)
    {
        if(initial<RQ[i])
        {
            index=i;
            break;
        }
    }

    // if movement is towards high value
    if(move==1)
    {
        for(i=index;i<n;i++)
        {
            TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
            initial=RQ[i];
        }
        // last movement for max size
        TotalHeadMoment=TotalHeadMoment+abs(size-RQ[i-1]-1);
        /*movement max to min disk */
        TotalHeadMoment=TotalHeadMoment+abs(size-1-0);
        initial=0;
        for( i=0;i<index;i++)
        {

```

```

        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}
// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
    // last movement for min size
    TotalHeadMoment=TotalHeadMoment+abs(RQ[i+1]-0);
    /*movement min to max disk */
    TotalHeadMoment=TotalHeadMoment+abs(size-1-0);
    initial =size-1;
    for(i=n-1;i>=index;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

printf("Total head movement is %d",TotalHeadMoment);

}
int main()
{
    int i,j,ch;
    printf(" 1.FCFS \n 2.SCAN\n 3.C SCAN\n Enter your choice:");
    scanf("%d",&ch);
    switch(ch)
    {
        case 1:fcfs();
        break;
        case 2:scan();
        break;
        case 3:cscan();
        break;
        default:
        return 0;
    }
}

```

```
    }  
    return 0;  
}
```

Output

```
C:\Users\admin\CS4SEM>gcc os.c  
  
C:\Users\admin\CS4SEM>a  
1.FCFS  
2.SCAN  
3.C SCAN  
Enter your choice:1  
Enter the number of Requests  
5  
Enter the Requests sequence  
53 19 69 124 193  
Enter initial head position  
14  
Total head moment is 247  
C:\Users\admin\CS4SEM>
```

```
C:\Users\admin\CS4SEM>a  
1.FCFS  
2.SCAN  
3.C SCAN  
Enter your choice:2  
Enter the number of Requests  
5  
Enter the Requests sequence  
168 93 50 14 155  
Enter initial head position  
45  
Enter total disk size  
122  
Enter the head movement direction for high 1 and for low 0  
1  
Total head movement is 277  
C:\Users\admin\CS4SEM>
```

```
C:\Users\admin\CS4SEM>a
1.FCFS
2.SCAN
3.C SCAN
Enter your choice:3
Enter the number of Requests
5
Enter the Requests sequence
193 188 45 12 56
Enter initial head position
33
Enter total disk size
200
Enter the head movement direction for high 1 and for low 0
0
Total head movement is 386
C:\Users\admin\CS4SEM>
```

Laboratory Program 15

Write a C program to simulate disk scheduling algorithms:

- a) SSTF
- b) LOOK
- c) C-LOOK

```
#include<stdio.h>
#include<stdlib.h>
void sstf()
{
    int RQ[100],i,n,TotalHeadMoment=0,initial,count=0;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);

    // logic for sstf disk scheduling

    /* loop will execute until all process is completed*/
    while(count!=n)
    {
        int min=1000,d,index;
        for(i=0;i<n;i++)
        {
            d=abs(RQ[i]-initial);
            if(min>d)
            {
                min=d;
                index=i;
            }
        }
        TotalHeadMoment=TotalHeadMoment+min;
        initial=RQ[index];
        // 1000 is for max
        // you can use any number
        RQ[index]=1000;
        count++;
    }
}
```

```

    printf("Total head movement is %d",TotalHeadMoment);
}
void look()
{
    int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);
    printf("Enter total disk size\n");
    scanf("%d",&size);
    printf("Enter the head movement direction for high 1 and for low 0\n");
    scanf("%d",&move);

    // logic for look disk scheduling

    /*logic for sort the request array */
    for(i=0;i<n;i++)
    {
        for(j=0;j<n-i-1;j++)
        {
            if(RQ[j]>RQ[j+1])
            {
                int temp;
                temp=RQ[j];
                RQ[j]=RQ[j+1];
                RQ[j+1]=temp;
            }
        }
    }

    int index;
    for(i=0;i<n;i++)
    {
        if(initial<RQ[i])
        {
            index=i;
            break;
        }
    }
}

```



```

// if movement is towards high value
if(move==1)
{
    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}
// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

printf("Total head movement is %d",TotalHeadMoment);
}

```

```

void clook()
{
    int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
}

```

```

for(i=0;i<n;i++)
    scanf("%d",&RQ[i]);
printf("Enter initial head position\n");
scanf("%d",&initial);
printf("Enter total disk size\n");
scanf("%d",&size);
printf("Enter the head movement direction for high 1 and for low 0\n");
scanf("%d",&move);

```

```

// logic for C-look disk scheduling

```

```

    /*logic for sort the request array */
    for(i=0;i<n;i++)
    {
        for( j=0;j<n-i-1;j++)
        {
            if(RQ[j]>RQ[j+1])
            {
                int temp;
                temp=RQ[j];
                RQ[j]=RQ[j+1];
                RQ[j+1]=temp;
            }
        }
    }
}

```

```

int index;
for(i=0;i<n;i++)
{
    if(initial<RQ[i])
    {
        index=i;
        break;
    }
}

```

```

// if movement is towards high value
if(move==1)
{
    for(i=index;i<n;i++)
    {

```

```

        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for( i=0;i<index;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];

    }
}
// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for(i=n-1;i>=index;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];

    }
}

printf("Total head movement is %d",TotalHeadMoment);

}
int main()
{
    int i,j,ch;
    printf(" 1.SSTF \n 2.LOOK\n 3.C LOOK\n Enter your choice:");
    scanf("%d",&ch);
    switch(ch)
    {
        case 1:sstf();
        break;
        case 2:look();
        break;
        case 3:clook();
        break;
    }
}

```

```
        default:  
        return 0;  
    }  
    return 0;  
}
```

Output

```
C:\Users\admin\CS4SEM>gcc os.c  
  
C:\Users\admin\CS4SEM>a  
1.SSTF  
2.LOOK  
3.C LOOK  
Enter your choice:1  
Enter the number of Requests  
5  
Enter the Requests sequence  
193 55 162 14 78  
Enter initial head position  
25  
Total head movement is 190  
C:\Users\admin\CS4SEM>
```

```
C:\Users\admin\CS4SEM>a  
1.SSTF  
2.LOOK  
3.C LOOK  
Enter your choice:2  
Enter the number of Requests  
5  
Enter the Requests sequence  
144 25 65 88 147  
Enter initial head position  
50  
Enter total disk size  
200  
Enter the head movement direction for high 1 and for low 0  
0  
Total head movement is 147  
C:\Users\admin\CS4SEM>
```

```
C:\Users\admin\CS4SEM>a
1.SSTF
2.LOOK
3.C LOOK
Enter your choice:3
Enter the number of Requests
5
Enter the Requests sequence
156 75 34 91 166
Enter initial head position
50
Enter total disk size
200
Enter the head movement direction for high 1 and for low 0
1
Total head movement is 248
C:\Users\admin\CS4SEM>
```