Section 43_00_00_75A_dat(11575) Equipment Installation Specialties

Data Sheet

Rev#	Description of Change	Author	WP#	Date
43_00_00_75				
1.0	Copy fab version 43_00_00_75H_dat(11575) Rev 8.0 as baseline to create Assembly Test document.	L. Orosco		06/08/06
2.0	Published	L. Orosco		06/08/06
2.1	Remove non AT components and add AT Tool Install components	C. Young		09/22/06
3.0	Published	C. Bustos		09/26/06
3.1	Add 3/4" & 1" to SSP-530.X, add SSP-534.X & SSP-535.X per ATIS review ARs	C. Young		11/09/06
4.0	Published	C. Bustos		12/11/06
4.1	Add 1 1/4" & 1 1/2" to ADP-506.X, add ADP-511.X, HS-502.X, SSP-536.X & SSP-540.X per ATIS review ARs	C. Young		02/28/07
5.0	Published	C. Bustos		03/12/07
5.1	Add ADP-501.02, ADP-510.12, HS-502.06, 07 & 08, HSC-501.06, 07, & 08, SSP-536.03, SSP-537.X, SSP-538.X, SSP-539.X, SSP-541.X, SSP-542.X, SSP-543.X, SSP-544.X, SSP-545.X, SSP-546.X, SSP-547.X, SSP-548.X, SSP-549.X. Remove hose color code from HS-501.X, Delete PTU-501.X, SSP-530.X per ATIS review ARs	C. Young		05/02/07
6.0	Published	L. Orosco		05/07/07
6.1	Add HSC-503.X, SSP-541.02, SSP-542.02, SSP-550.X, SSP-551.X, SSP-552.X, SSP-553.X. Add Note to HS-502.X & revise Note in SSP-540.X per ATIS review ARs	C. Young		05/21/07
7.0	Published	L. Orosco		05/25/07
7.1	Add Dixon part to HSC-501.05, Ryan Herco part to HSC-503.06, Dixon & Ryan Herco parts to HSC-503.05, 07, 08. Add SSP-537.04 per ATIS review ARs	C. Young		07/12/07
8.0	Published	L. Orosco		07/13/07
8.1	Add Notes for HS-502.X & SSP-543.X, add ADP-509.15, delete SPP-3, STR-4 & STR-5 per ATIS review ARs	C. Young		10/23/07
9.0	Published	C. Bustos		10/31/07
9.1	Add SSP-527.X per ATIS review ARs	C. Young		11/06/07
10.0	Published	M. Smith		11/15/07
10.1	Add SSP-554.X & SSP-555.X per WP	C. Young		05/02/08
11.0	Published	C. Bustos		05/05/08

Rev #	Description of Change	Author	WP#	Date
11.1	Removed 2" Herco Braid tubing from HS-502.x table as the operating pressure does not meet SCEP pressure requirements	S. Garcia		7/15/11
12.0	Published	C. Bustos		09/09/11
12.1	Add high Temp Flex Duct	S. Garcia		06/20/12
13.0	Published	C. Bustos		06/21/12

NOTE: Equipment-installation-specific components are designated as XX-5XX.X. General facility components not requiring a single vendor/single part number are designated XX-XX.

Equipment Installation Components

Tag Number	Included	Description
ADP-501.X	X	Brass, gauge adapter
ADP-502.X	X	PVC X brass adapter
ADP-503.X	X	PVC X brass adapter tee
ADP-504.X	X	Stainless steel reinforced adapter FNPT
ADP-505.X	X	Stainless steel reinforced adapter FNPT
ADP-506.X	X	Stainless steel reinforced adapter MNPT
ADP-508.X	X	Stainless steel reinforced tee
ADP-509.X	X	Stainless steel reinforced reducing tee
ADP-510.X	X	Stainless steel reinforced union
ADP-511.X	X	PFA union adapter male
CS-501.X	X	Circuit setter
FC-502.X	X	Plastic flex duct
HS-501.X	X	Flexible hose (6EEP)
HS-502.X	X	Clear PVC tubing (SCEP)
HSC-501.X	X	Hose barb adapter MNPT - brass

Tag Number	Included	Description
HSC-502.X	X	Hose barb adapter FNPT - brass
HSC-503.X	X	Hose barb adapter MNPT – stainless steel
SSP-502.X	X	Gas filter
SSP-525.X	X	Strainer (Clear PVC)
SSP-526.X	X	Strainer (Bronze)
SSP-527.X	X	Strainer (Stainless steel)
SSP-532.X	X	Gas quick connect – brass
SSP-533.X	X	Water quick connect – brass
SSP-534.X	X	Union (to connect gas stick) – brass
SSP-535.X	X	Male connector – brass
SSP-536.X	X	Bulkhead union – stainless steel
SSP-537.X	X	Reducing union – brass
SSP-538.X	X	Male tube adapter – brass
SSP-539.X	X	Female branch tee – brass
SSP-540.X	X	Lift station
SSP-541.X	X	Union tee – brass
SSP-542.X	X	Union elbow – brass
SSP-543.X	X	Port connector – brass
SSP-544.X	X	Female tube adapter – stainless steel
SSP-545.X	X	Bulkhead male connector -stainless steel
SSP-546.X	X	Female branch tee – stainless steel
SSP-547.X	X	Reducing union – stainless steel
SSP-548.X	X	Male tube adapter – stainless steel
SSP-549.X	X	Union – stainless steel
SSP-550.X	X	Male connector – stainless steel
SSP-551.X	X	Reducing union tee - brass
SSP-552.X	X	Reducing port connector - brass
SSP-553.X	X	Female tube socket weld connector – stainless steel
SSP-554.X	X	Water stick – Ball valve, PRV & Bi-dicator
SSP-555.X	X	Water stick – Globe valve, Flowmeter & Bi-dicator

Component tag ADP-501.X

Function Brass adapter, gauge

Design pressure

Body Brass, lengthened shoulder

End connection As indicated below x same size Swagelok

Tag Number	Manufacturer	Figure Number	Size	Dim
ADP-501.01	Swagelok	B-8-RB-4	1/2" MNPT X 1/4" FNPT	1.08"
ADP-501.02	Swagelok	B-12-RB-4	3/4" MNPT X 1/4" FNPT	1.08"

Component tag ADP-502.X

Function PVC by brass adapter

Design pressure

Body Schedule 80 PVC Seals Buna-N o-ring

End connection PVC socket X brass FNPT

Tag Number	Manufacturer	Figure Number	Size
ADP-502.05	Spears	835-005BR	1/2"s X 1/2" FNPT
ADP-502.07	Spears	835-007BR	3/4"s X 3/4" FNPT
ADP-502.08	Spears	835-101BR	3/4"s X 1/2" FNPT
ADP-502.10	Spears	835-010BR	1"s X 1" FNPT
ADP-502.15	Spears	835-015BR	1 1/2" X 1 1/2" FNPT

Component tag ADP-503.X

Function PVC by brass adapter tee

Design pressure

Body Schedule 80 PVC
Seals Buna-N o-ring

End connection PVC socket X PVC socket X brass FNPT

Tag Number	Manufacturer	Figure Number	Size
ADP-503.05	Spears	802-005BR	1/2"s X 1/2"s X 1/2" FNPT
ADP-503.07	Spears	802-101BR	3./4"s X 3/4"s X 3/4" FNPT

Component tag ADP-504.X

Function Stainless steel reinforced adapter

Design Pressure

Body Schedule 80 PVC

End Connection PVC spigot X stainless steel reinforced FNPT

Tag Number	Manufacturer	Figure Number	Size
ADP-504.05	Spears	878-005SR	1/2" X 1/2" FNPT
ADP-504.06	Spears	878-072SR	1/2" X 1/4" FNPT
ADP-504.07	Spears	878-007SR	3/4" X 3/4" FNPT
ADP-504.08	Spears	878-098SR	3/4" X 1/4" FNPT
ADP-504.10	Spears	878-010SR	1" X 1" FNPT
ADP-504.11	Spears	878-128SR	1" X 1/4" FNPT

Component tag ADP-505.X

Function Stainless steel reinforced adapter

Design Pressure

Body Schedule 80 PVC

End Connection PVC socket X stainless steel reinforced FNPT

Tag Number	Manufacturer	Figure Number	Size
ADP-505.03	Spears	835-003SR	3/8"s X 3/8" FNPT
ADP-505.05	Spears	835-005SR	1/2"s X 1/2" FNPT
ADP-505.07	Spears	835-007SR	3/4"s X 3/4" FNPT
ADP-505.08	Spears	835-101SR	3/4"s X 1/2" FNPT
ADP-505.10	Spears	835-010SR	1"s X 1" FNPT
ADP-505.11	Spears	835-130SR	1"s X 1/2" FNPT
ADP-505.12	Spears	835-131SR	1"s X 3/4" FNPT
ADP-505.13	Spears	835-012SR	1 1/4"s X 1 1/4" FNPT
ADP-505.15	Spears	835-015SR	1 1/2"s X 1 1/2" FNPT
ADP-505.20	Spears	835-020SR	2"s X 2" FNPT
ADP-505.25	Spears	835-025SR	2 1/2"s X 2 1/2" FNPT
ADP-505.30	Spears	835-030SR	3"s X 3" FNPT

Component tag ADP-506.X

Function Stainless steel reinforced adapter

Design Pressure

Body Schedule 80 PVC

End Connection PVC socket X stainless steel reinforced MNPT

Tag Number	Manufacturer	Figure Number	Size
ADP-506.05	Spears	836-005R	1/2"s X 1/2" MNPT
ADP-506.07	Spears	836-007R	3/4"s X 3/4" MNPT
ADP-506.10	Spears	836-010R	1"s X 1" MNPT
ADP-506.12	Spears	836-012	1 1/4"s X 1 1/4" MNPT
ADP-506.15	Spears	836-015	1 1/2"s X 1 1/2" MNPT

Note:.12 & .15 are not stainless steel reinforced

Component tag ADP-508.X

Function Stainless steel reinforced tee

Design Pressure

Body Schedule 80 PVC

End Connection PVC socket X PVC socket X stainless steel reinforced

FNPT

Tag Number	Manufacturer	Figure Number	Size
ADP-508.05	Spears	802-005SR	1/2"s X 1/2"s X 1/2" FNPT
ADP-508.07	Spears	802-007SR	3/4"s X 3/4"s X3/4" FNPT

Component tag ADP-509.X

Function Stainless steel reinforced reducing tee

Design Pressure

Body Schedule 80 PVC

End Connection PVC socket X PVC socket X stainless steel reinforced

FNPT

Tag Number	Manufacturer	Figure Number	Size
ADP-509.05	Spears	802-072SR	1/2"s X 1/2"s X 1/4" FNPT
ADP-509.07	Spears	802-098SR	3/4"s X 3/4"s X 1/4" FNPT
ADP-509.08	Spears	802-101SR	3/4"s X 3/4"s X 1/2" FNPT
ADP-509.10	Spears	802-128SR	1"s X 1"s X 1/4" FNPT
ADP-509.15	Spears	802-207SR	1 1/2" s X 1 1/2" s X 1/4" FNPT

Component tag ADP-510.X

Function Stainless steel reinforced union

Design Pressure

Body Schedule 80 PVC

End Connection PVC socket X stainless steel reinforced FNPT

Tag Number	Manufacturer	Figure Number	Size
ADP-510.02	Spears	859-002SR	1/4"s X 1/4" FNPT
ADP-510.05	Spears	859-005SR	1/2"s X 1/2" FNPT
ADP-510.07	Spears	859-007SR	3/4"s X 3/4" FNPT
ADP-510.10	Spears	859-010SR	1"s X 1" FNPT
ADP-510.12	Spears	859-012SR	1 1/4"s X 1 1/4" FNPT
ADP-510.15	Spears	859-015SR	1 1/2"s X 1 1/2" FNPT
ADP-510.20	Spears	859-020SR	2"s X 2" FNPT

Component tag ADP-511.X

Function PFA union adapter male

Design pressure

Body PFA

End connection Flare & Nut X MNPT

Tag Number	Manufacturer	Figure Number	Size
ADP-511.05	Saint-Gobain (Furon)	FMF88UAMN-3	1/2"
ADP-511.07	Saint-Gobain (Furon)	FMF1212UAMN-3	3/4"
ADP-511.10	Saint-Gobain (Furon)	FMF1616UAMN-3	1"

Component tag CS-501.X

Function Circuit setter, calibrated balance valve

Design pressure 200 psig for Solder, 300 psig for FNPT & 175 psig for

flanged connection at 250 degrees F

Body Bronze
Ball Brass

Seats Glass & carbon filled TFE for 3" or less

Bronze (replaceable bronze disc with EPDM seal insert and

stainless steel stem)

End connection As indicated below

Tag No.	Mfr.	Figure Number	Size	Conn. Type
CS-501.01	Bell & Gossett	CB-1S – 117401	1"	Sweat
CS-501.02	Bell & Gossett	CB-1 1/2S – 117403	1 1/2"	Sweat
CS-501.03	Bell & Gossett	CB-2S - 117404	2"	Sweat
CS-501.11	Bell & Gossett	CB-1 – 117416	1"	FNPT
CS-501.12	Bell & Gossett	CB-1 1/2 – 117104	1 1/2"	FNPT
CS-501.13	Bell & Gossett	CB-2 – 117105	2"	FNPT
CS-501.21	Bell & Gossett	CB-4 – 117035	4"	Flanged

Component tag FC-502.X

Function Flexible plastic ducting, wire reinforced

Design 20°F to 160°F Body Medium Wall PVC

Reinforcing Steel wire
Color Blue/gray

Special features Flame retardant – UL94V-O

Tag Number	Manufacturer	Size
FC-502.00	Flexhaust (Flexadux R-2)	1 1/2"
FC-502.01	Flexhaust (Flexadux R-2)	2"
FC-502.02	Flexhaust (Flexadux R-2)	2 1/2"
FC-502.03	Flexhaust (Flexadux R-2)	3"
FC-502.04	Flexhaust (Flexadux R-2)	4"
FC-502.05	Flexhaust (Flexadux R-2)	5"
FC-502.06	Flexhaust (Flexadux R-2)	6"
FC-502.07	Flexhaust (Flexadux R-2)	7"
FC-502.08	Flexhaust (Flexadux R-2)	8"
FC-502.10	Flexhaust (Flexdux R2)	10"
FC-502.12	Flexhaust (Flexdux R2)	12"

Component Data Sheet

Component tag FC-506.X

Function High Temp Flexible plastic ducting, wire reinforced

Design -65°F to 225°F

Body Medium Wall Static Dissipative Polyurethane

Reinforcing Steel wire
Color Black

Special features Flame retardant – UL94V-O

Tag Number	Manufacturer	Size
FC-506.01	Flexhaust (Flexadux PU Flx Thane SD)	2"
FC-502.02	Flexhaust (Flexadux PU Flx Thane SD)	2 1/2"
FC-502.03	Flexhaust (Flexadux PU Flx Thane SD)	3"
FC-502.04	Flexhaust (Flexadux PU Flx Thane SD)	4"
FC-502.05	Flexhaust (Flexadux PU Flx Thane SD)	5"
FC-502.06	Flexhaust (Flexadux PU Flx Thane SD)	6"
FC-502.07	Flexhaust (Flexadux PU Flx Thane SD)	7"
FC-502.08	Flexhaust (Flexadux PU Flx Thane SD)	8"
FC-502.10	Flexhaust (Flexadux PU Flx Thane SD)	10"
FC-502.12	Flexhaust (Flexadux PU Flx Thane SD)	12"

Component tag HS-501.X (6EEP)

Function Flexible hose, general service

Design pressure Minus 40 degrees F to 180 degrees F

Construction Synthetic rubber liner, one fiber braid reinforcement,

synthetic rubber cover

End connection N/A

Tag No.	Mfr.	Figure Number – Color	Size	Max Psig
HS-501.01	Parker	801-6	3/8" ID	250
HS-501.02	Parker	801-8	1/2" ID	250
HS-501.03	Parker	801-10	5/8" ID	200
HS-501.04	Parker	801-12	3/4" ID	200
HS-501.05	Parker	801-16	1" ID	175

Component tag HS-502.X (SCEP)
Function Clear PVC tubing

Design pressure

Construction PVC liner, polyester braid reinforcement, heavy duty

End connection N/A

Tag No.	Mfr.	Figure Number	Size	Working psig
HS-502.05	Ryan Herco	0512-111	1" ID	150
HS-502.06	Ryan Herco	0512-121	1 1/4" ID	125
HS-502.07	Ryan Herco	0512-131	1 1/2" ID	100

Note: 1) Requires 2 SS band type hose clamps for this hose

Component Data Sheet

²⁾ Use Dixon parts from HSC-501.X or Dixon or Ryan Herco parts from HSC-503.X are both acceptable for this hose

Component tag HSC-501.X

Function Hose barb adapter, general service

Design pressure

Body Brass
Trim Brass
Seats N/A
Seals N/A
Packing N/A

End connection MNPT x Pushlok Barb (except Dixon parts)

Tag No.	Mfr.	Figure Number	MNPT Size	Hose (ID) Size
HSC-501.01	Parker	30182-6-6B	3/8"	3/8"
HSC-501.02	Parker	30182-8-8B	1/2"	1/2"
HSC-501.04	Parker	30182-12-12B	3/4"	3/4"
HSC-501.05	Parker	30182-16-16B	1"	1"
	Dixon	BST10	1"	1"
HSC-501.06	Dixon	BST20	1 1/2"	1 1/2"
HSC-501.07	Dixon	BST15	1 1/4"	1 1/4"
HSC-501.08	Dixon	BST25	2"	2"
HSC-501.11	Parker	30182-6-8B	3/8"	1/2"
HSC-501.12	Parker	30182-8-6B	1/2"	3/8"
HSC-501.13	Parker	30182-8-10B	1/2"	5/8"
HSC-501.14	Parker	30182-12-8B	3/4"	1/2"
HSC-501.15	Parker	30182-16-8B	1"	1/2"

Note: 1) Requires 2 SS band type hose clamps at end fitting for Dixon parts

Component tag HSC-502.X

Function Hose barb adapter, general service

Design pressure

Body Brass
Trim Brass
Seats N/A
Seals N/A
Packing N/A

Enc connection FNPT x Pushlok Barb

Tag No.	Mfr.	Figure Number	MNPT Size	Hose (ID) Size
HSC-502.01	Parker	30282-6-6B	3/8"	3/8"
HSC-502.04	Parker	30282-8-8B	1/2"	1/2"

Component tag HSC-503.X

Function Hose barb adapter, general service

Design pressure

Body Stainless steel

Trim N/A
Seats N/A
Seals N/A
Packing N/A

End connection MNPT x Pushlok Barb (except Dixon & Ryan Herco parts)

Tag No.	Mfr.	Figure Number	MNPT Size	Hose (ID) Size
HSC-503.01	Parker	30182-6-6C	3/8"	3/8"
HSC-503.02	Parker	30182-8-8C	1/2"	1/2"
HSC-503.04	Parker	30182-12-12C	3/4"	3/4"
HSC-503.05	Parker	30182-16-16C	1"	1"
	Dixon	RST10	1"	1"
	Ryan Herco	0704-010	1"	1"
HSC-503.06	Dixon	RST20	1 1/2"	1 1/2"
	Ryan Herco	0704-015	1 1/2"	1 1/2"
HSC-503.07	Dixon	RST15	1 1/4"	1 1/4"
	Ryan Herco	0704-012	1 1/4"	1 1/4"
HSC-503.08	Dixon	RST20	2"	2"
	Ryan Herco	0704-020	2"	2"
HSC-503.12	Parker	30182-8-6C	1/2"	3/8"

Note: 1) Requires 2 SS band type hose clamps at end fitting for Dixon & Ryan Herco parts

²⁾ Use Dixon or Ryan Herco parts for HS-502.X (SCEP) hoses

Component tag SSP-502.X

Function Gas filter, low-purity
Design pressure 250 psig, 750 psig
Body 316L stainless steel
Trim 316l stainless steel

Seats None
Seals Teflon
Packing None

End connection Compression, Male
Body construction 316L stainless steel
Trim construction 316L stainless steel

Tag No.	Manu- facturer	Figure Number	Range	Size	End Flow	Conn.	Dim	PSI Inlet
SSP-502.10	Mykrolis	WG2F02PS1	N/A	1/4"	High	MSWG x MSWG	5.00"	600
	Pall	SGLF6101SM4S	N/A	1/4"	High	MSWG x MSWG	4.19"	600
SSP-502.20	Mykrolis	WGMXMBSS4	N/A	3/8"	High	MSWG x MSWG	5.00"	600
	Pall	SGLF6101SM6S	N/A	3/8"	High	MSWG x MSWG	5.0"	600
SSP-502.30	Mykrolis	WGMXMBSS4	N/A	1/2"	High	MVCR x MVCR	8.86"	250
	Pall	GLF8101SM8	N/A	1/2"	High	MSWG x MSWG	7.75"	600

Notes:

1. Filters have 25 Ra max. internal finish.

Component tag SSP-525.X Function Strainer

Design pressure 150 psig at 68 degrees F

Body Clear PVC
Trim Clear PVC
Seats Viton
Seals Viton

Screen PVC, 20 mesh

End connection Spigot
Body construction One piece

Tag No.	Manufacturer	Figure Number	Size
SSP-525.01	George Fischer, Type 306	192.306.349	1/2"
SSP-525.02	George Fischer, Type 306	192.306.399	3/4"
SSP-525.03	George Fischer, Type 306	192.306.449	1"
SSP-525.04	George Fischer, Type 306	192.306.499	1 1/4"
SSP-525.05	George Fischer, Type 306	192.306.549	1 1/2"
SSP-525.06	George Fischer, Type 306	192.306.599	2"

Component tag SSP-526.X Function Strainer

Design pressure 400 psig at 150 degrees F

Body Bronze
Cover Bronze
Seals PTFE 0-ring

Gasket PTFE

Screen Stainless steel type 304, 20 mesh

End connection As indicated below

Body construction One piece

Tag No.	Mfr.	Figure Number	Size	Conn. Type
SSP-526.01	Conbraco	59 - 003 - 01	1/2"	FNPT
SSP-526.02	Conbraco	59 - 004 - 01	3/4"	FNPT
SSP-526.03	Conbraco	59 – 005 – 01	1"	FNPT
SSP-526.04	Conbraco	59 – 006 – 01	1 1/4"	FNPT
SSP-526.05	Conbraco	59 – 007 – 01	1 1/2"	FNPT
SSP-526.06	Conbraco	59 – 008 – 01	2"	FNPT
SSP-526.11	Conbraco	59 – 303 – 01	1/2"	Sweat
SSP-526.12	Conbraco	59 – 304 – 01	3/4"	Sweat
SSP-526.13	Conbraco	59 – 305 – 01	1"	Sweat
SSP-526.14	Conbraco	59 – 306 – 01	1 1/4"	Sweat
SSP-526.15	Conbraco	59 – 307 – 01	1 1/2"	Sweat
SSP-526.16	Conbraco	59 – 308 – 01	2"	Sweat

Component tag SSP-527.X Function Strainer

Design pressure 600 psig at 1124 degrees F

Body Stainless steel
Cover Stainless steel
Plug Stainless steel

Gasket Stainless steel type 304

Screen Stainless steel type 304, 20 mesh

End connection As indicated below

Body construction One piece

Tag No.	Mfr.	Figure Number	Size	Conn. Type
SSP-527.01	Conbraco	61 – 203 – 3A1	1/2"	FNPT
SSP-527.02	Conbraco	61 – 203 – 4A1	3/4"	FNPT
SSP-527.03	Conbraco	61 – 203 – 5A1	1"	FNPT
SSP-527.04	Conbraco	61 – 203 – 6A1	1 1/4"	FNPT
SSP-527.05	Conbraco	61 – 203 – 7A1	1 1/2"	FNPT
SSP-527.06	Conbraco	61 – 203 – 8A1	2"	FNPT
SSP-527.11	Conbraco	61 – 213 – 3A1	1/2"	Socket Weld
SSP-527.12	Conbraco	61 – 213 – 4A1	3/4"	Socket Weld
SSP-527.13	Conbraco	61 – 213 – 5A1	1"	Socket Weld
SSP-527.14	Conbraco	61 – 213 – 6A1	1 1/4"	Socket Weld
SSP-527.15	Conbraco	61 – 213 – 7A1	1 1/2"	Socket Weld
SSP-527.16	Conbraco	61 – 213 – 8A1	2"	Socket Weld

Component tag SSP-532.X

Function Gas quick connect
Design pressure 250 psig max.

Body Brass
Seats Brass

Seals Buna N o-ring

Packing None

End connection As indicated below x same size Swagelok

Body construction Two piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	CV	Dim.
Quick connect bulkhead body					
SSP-532.01	Swagelok	B-QC4-B1-400	1/4"	0.4	2.67"
SSP-532.02	Swagelok	B-QC6-B1-600	3/8"	1.5	2.98
SSP-532.03	Swagelok	B-QC8-B1-810	1/2"	3.3	3.56"
Quick connect stem (double-end shutoff)					
SSP-532.11	Swagelok	B-QC4-D-400	1/4"	0.4	2.42"
SSP-532.12	Swagelok	B-QC6-D-600	3/8"	1.5	2.64"
SSP-532.13	Swagelok	B-QC8-D-810	1/2"	3.3	3.16"

Component tag SSP-533.X

Function Water quick connect

Design pressure 1000 psig max.

Body Brass
Seats Brass

Seals Buna N o-ring

Packing None

End connection As indicated below x FNPT

Body construction Two piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
Quick connect coupler				
SSP-533.01	Parker	BH4-60	1/2"	2.87"
SSP-533.02	Parker	BH6-60	3/4"	3.56"
Quick connect nipple (double shutoff)				
SSP-533.11	Parker	BH4-61	1/2"	1.75"
SSP-533.12	Parker	BH6-61	3/4"	2.16"

Component tag SSP-534.X

Function Union (to connect gas stick)

Design pressure 250 psig max.

Body Brass
Seats Brass
Seals Brass
Packing None

End connection As indicated below x same size Swagelok

Body construction One piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-534.01	Swagelok	B-810-6	1/2"	2.02"
SSP-534.02	Swagelok	B-1210-6	3/4"	2.11"

Component tag SSP-535.X

Function Male connector
Design pressure 250 psig max.

Body Brass
Seats Brass
Seals Brass
Packing None

End connection As indicated below x MNPT

Body construction One piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-535.01	Swagelok	B-810-1-8	1/2"	1.93"
SSP-535.02	Swagelok	B-1210-1-12	3/4"	1.99"

Component tag SSP-536.X
Function Bulkhead union
Design pressure 250 psig max.
Body 316 stainless steel

Body 316 stainless steel
Seats 316 stainless steel
Seals 316 stainless steel

Packing None

End connection As indicated below x MNPT

Body construction Eight piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-536.01	Swagelok	SS-810-61	1/2"	2.80"
SSP-536.02	Swagelok	SS-1210-61	3/4"	3.11"
SSP-536.03	Swagelok	SS-1610-61	1"	3.77"

Component tag SSP-537.X Function Reducing union

Design pressure 250 psig max.

Body Brass
Seats Brass
Seals Brass
Packing None

End connection As indicated below x same size Swagelok

Body construction One piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-537.01	Swagelok	B-1010-6-8	5/8" X 1/2"	2.05"
SSP-537.02	Swagelok	B-1210-6-10	3/4" X 5/8"	2.11"
SSP-537.03	Swagelok	B-1410-6-12	7/8" X 3/4"	2.18"
SSP-537.04	Swagelok	B-1210-6-8	3/4" X 1/2"	2.11"

Component tag SSP-538.X

Function Male tube adapter
Design pressure 250 psig max.

BodyBrassSeatsBrassSealsBrassPackingNoneBody constructionOne pieceTrim constructionNone

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-538.01	Swagelok	B-8-TA-1-8	1/2"	2.00"
SSP-538.02	Swagelok	B-12-TA-1-12	3/4"	2.06"

Component tag SSP-539.X

Function Female branch tee
Design pressure 250 psig max.

Body Brass
Seats Brass
Seals Brass
Packing None

End connection As indicated below x FNPT

Body construction One piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-539.01	Swagelok	B-810-3-4TTF	1/2" X 1/2" X 1/4" FNPT	2.84"
SSP-539.02	Swagelok	B-1210-3TTF	3/4" X 3/4" X 3/4" FNPT	3.52"

Component tag SSP-540.X Function Lift station

Pump - duplex Dual voltage 50 Hz (2850 RPM) or 60 Hz (3450 RPM)

single phase TEFC motor

Pump body CPVC

Accessories Alternating float level control with relay and on/off switch

Electrical 115-208/230V @ 60 Hz, 115-220/240V @ 50 Hz

Tank capacity 37 gallons for .01 thru .04 and 56 gallons for .05 thru .08

Tank body HDPE
Tank inlet end connection 3" MNPT

Pump outlet end connection 1 1/4" MNPT for .01 thru .04 and 1 1/2" MNPT for .05 thru

.08

Tag No.	Manufacturer	Figure Number	Motor HP	Hz	Flow GPM	TDH Feet	Tank Size LxWxH
SSP-540.01	Serfilco	CPS37-EO1-AF	1/3	50	20	18.7	18" x 24" x 18"
SSP-540.02	Serfilco	w/3" MNPT Inlet	1/3	60	20	28	18" x 24" x 18"
SSP-540.03	Serfilco	CPS37-EO3-AF	3/4	50	20	23.6	18" x 24" x 18"
SSP-540.04	Serfilco	w/3" MNPT Inlet	3/4	60	20	37	18" x 24" x 18"
SSP-540.05	Serfilco	CPS56-EO4-AF	1	50	20	37.4	24" x 30" x18"
SSP-540.06	Serfilco	w/3" MNPT Inlet	1	60	20	55	24" x 30" x18"
SSP-540.07	Serfilco	CPS56-EO5-AF	1.5	50	20	44.9	24" x 30" x18"
SSP-540.08	Serfilco	w/3" MNPT Inlet	1.5	60	20	65	24" x 30" x18"

Note:

^{1.} Same Figure Number w/3" MNPT Inlet for both 50 Hz & 60 Hz.

^{2.} The flow and TDH shown in the above table are based on 1.0 specific gravity liquid at ambient temperature. Higher flow rates are possible at reduced heads. Consult manufacturer's pump curves for further information. To locate manufacturer's pump curves, go to http://www.serfilco.com, then choose Product Bulletins P-312 and go to page 2.

Component tag SSP-541.X
Function Union tee
Design pressure 250 psig max.

Body Brass
Seats Brass
Seals Brass
Packing None

End connection As indicated below x same size Swagelok

Body construction One piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-541.01	Swagelok	B-810-3	1/2" X 1/2" X 1/2"	2.84"
SSP-541.02	Swagelok	B-1210-3	3/4" X 3/4" X 3/4"	3.14"

Component tag SSP-542.X
Function Union elbow
Design pressure 250 psig max.

Body Brass
Seats Brass
Seals Brass
Packing None

End connection As indicated below x same size Swagelok

Body construction One piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-542.01	Swagelok	B-810-9	1/2"	1.42"
SSP-542.02	Swagelok	B-1210-9	3/4"	1.57"

Component tag SSP-543.X
Function Port connector
Design pressure 250 psig max.

BodyBrassSeatsBrassSealsBrassPackingNoneBody constructionOne pieceTrim constructionNone

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-543.01	Swagelok	B-811-PC	1/2"	1.43"
SSP-543.02	Swagelok	B-1211-PC	3/4"	1.49"

Note: 5EE tubing can be substituted for SSP-543.X

Component tag SSP-544.X

Function Female tube adapter

Design pressure 250 psig max.

Body 316 stainless steel
Seats 316 stainless steel
Seals 316 stainless steel

Packing None
Body construction One piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-544.01	Swagelok	SS-8-TA-7-8	1/2"	2.05"
SSP-544.02	Swagelok	SS-12-TA-7-12	3/4"	2.16"
SSP-544.03	Swagelok	SS-16-TA-7-16	1"	2.53"

Component tag SSP-545.X

Function Bulkhead male connector

Design pressure 250 psig max.

Body 316 stainless steel

Seats 316 stainless steel

Seals 316 stainless steel

PackingNoneBody constructionOne pieceTrim constructionNone

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-545.01	Swagelok	SS-810-11-8	1/2"	2.71"
SSP-545.02	Swagelok	SS-1210-11-12	3/4"	3.00"
SSP-545.03	Swagelok	SS-1610-11-16	1"	3.67"

Component tag SSP-546.X

Function Female branch tee
Design pressure 250 psig max.
Body Stainless steel
Seats Stainless steel
Seals Stainless steel

Packing None

End connection As indicated below x FNPT

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-546.01	Swagelok	SS-810-3-4TTF	1/2" X 1/2" X 1/4" FNPT	2.84"
SSP-546.02	Swagelok	SS-1210-3TTF	3/4" X 3/4" X 3/4" FNPT	3.52"

Component tag SSP-547.X

Function Reducing union

Design pressure 250 psig max.

Body Stainless steel

Seats Stainless steel
Seals Stainless steel

Packing None

End connection As indicated below x same size Swagelok

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-547.01	Swagelok	SS-1010-6-8	5/8" X 1/2"	2.05"
SSP-547.02	Swagelok	SS-1210-6-10	3/4" X 5/8"	2.11"
SSP-547.03	Swagelok	SS-1410-6-12	7/8" X 3/4"	2.18"

Component tag SSP-548.X

Function Male tube adapter
Design pressure 250 psig max.
Body Stainless steel
Seats Stainless steel
Seals Stainless steel

Packing None
Body construction One piece
Trim construction None

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-548.01	Swagelok	SS-8-TA-1-8	1/2"	2.00"
SSP-548.02	Swagelok	SS-12-TA-1-12	3/4"	2.06"

Component tag SSP-549.X Function Union

Design pressure 250 psig max.
Body Stainless steel
Seats Stainless steel
Seals Stainless steel

Packing None

End connection As indicated below x same size Swagelok

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-549.01	Swagelok	SS-810-6	1/2"	2.02"
SSP-549.02	Swagelok	SS-1210-6	3/4"	2.11"

Component tag SSP-550.X

Function Male connector
Design pressure 250 psig max.
Body Stainless steel
Seats Stainless steel
Seals Stainless steel

Packing None

End connection As indicated below x MNPT

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-550.01	Swagelok	SS-810-1-8	1/2"	1.93"
SSP-550.02	Swagelok	SS-1210-1-12	3/4"	1.99"

Component tag SSP-551.X

Function Reducing union tee

Design pressure 250 psig max.

Body Brass
Seats Brass
Seals Brass
Packing None

End connection As indicated below x same size Swagelok

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-551.01	Swagelok	B-1210-3-12-8	3/4" X 3/4" X 1/2"	3.14"

Component tag SSP-552.X

Function Reducing port connector

Design pressure 250 psig max.

BodyBrassSeatsBrassSealsBrassPackingNoneBody constructionOne pieceTrim constructionNone

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-552.01	Swagelok	B-1211-PC-8	3/4" X 1/2"	1.43"

Component tag SSP-553.X

Function Female tube socket weld connector

Design pressure 250 psig max.

Body Stainless steel

Seats Stainless steel

Seals Stainless steel

Packing None

End connection As indicated below x FNPT

Tag No.	Manufacturer	Figure Number	Size	Dim.
SSP-553.01	Swagelok	SS-8-TSW-7-8	1/2"	1.59"
SSP-553.02	Swagelok	SS-12-TSW-7-12	3/4"	1.73"

Component tag SSP-554.X

Function Water stick - Ball valve, Pressure reducing valve

(PRV) and Bi-dicator

Design pressure 150 psig
Body 304L SS
Packing PTFE

Seals Buna N o-ring

End connection Inlet: PVC Sch 80 Pipe Socket

Outlet: PVC Sch 80 Pipe Socket for w/o PRV,

MNPT for w/ PRV

Body construction Two piece

Tag No.	Manufacturer	Figure Number	Size	PRV
SSP-554.01	Evans Components	PW-08-STRPS-PT	1/2"	No
SSP-554.02	Evans Components	PW-12-STRPS-PT	3/4"	No
SSP-554.03	Evans Components	PW-16-STRPS-PT	1"	No
SSP-554.04	Evans Components	PW-24-STRPS-PT	1 1/2"	No
SSP-554.05	Evans Components	PW-32-STRPS-PT	2"	No
SSP-554.11	Evans Components	PW-08-STRPS-VEPM-G100-PT	1/2"	Yes
SSP-554.12	Evans Components	PW-12-STRPS-VEPM-G100-PT	3/4"	Yes
SSP-554.13	Evans Components	PW-16-STRPS-VEPM-G100-PT	1"	Yes
SSP-554.14	Evans Components	PW-24-STRPS-VEPM-G100-PT	1 1/2"	Yes
SSP-554.15	Evans Components	PW-32-STRPS-VEPM-G100-PT	2"	Yes

Component tag SSP-555.X

Function Water stick - Globe valve, Hedland flow meter

and Bi-dicator

Design pressure 150 psig
Body 304L SS
Packing PTFE

Seals Buna N o-ring
End connection Inlet: FNPT

Outlet: PVC Sch 80 Pipe Socket

Body construction Two Piece

Tag No.	Manufacturer	Figure Number	Size
SSP-555.01	Evans Components	PW-08-EZMF-GPVS-*-PT	1/2"
SSP-555.02	Evans Components	PW-12-EZMF-GPVS-*-PT	3/4"
SSP-555.03	Evans Components	PW-16-EZMF-GPVS-*-PT	1"
SSP-555.04	Evans Components	PW-24-EZMF-GPVS-*-PT	1 1/2"
SSP-555.55	Evans Components	PW-32-EZMF-GPVS-*-PT	2"

* P1: 1/2" (0.5 - 4 GPM)	* P9: 3/4" (4 - 28 GPM)	* P20: 1 1/2" (7 - 75 GPM)
* P2: 1/2" (1 - 7 GPM)	* P13: 1" (1 – 10 GPM)	* P21: 1 1/2" (10 - 100 GPM)
* P3: 1/2" (1 - 10 GPM)	* P14: 1" (3 -18 GPM)	* P22: 2" (2 – 25 GPM)
* P4: 1/2" (1 – 16 GPM)	* P15: 1" (4– 28 GPM)	* P23: 2" (5 – 50 GPM)
* P7: 3/4" (1 – 7 GPM)	* P18: 1-1/2" (2 – 25 GPM)	* P24: 2" (7 – 75 GPM)
* P8: 3/4" (3 – 18 GPM)	* P19: 1-1/2" (5 – 50 GPM)	* P25: 2" (10 – 100 GPM)

End of Section