

# Contents

An introduction to the custom preprocessing pipeline built for surfaced-based analysis

1. Motivation – Why surface?
2. Overall scheme – Covering multiple softwares (e.g., FSL, AFNI, ANTs, Freesurfer)
3. Pipeline details – Comparison with existing preprocessing pipelines
4. Practical applications – Not limited to surface analysis



## 2. Overall scheme

### Overall scheme of this pipeline

---

A) Make directories for preprocessed data (r1)

B) Convert DICOM images to NIFTI format (using `dicm2nii.m`, which was adapted from <https://github.com/xiangruili/dicm2nii>) (r2-r4)

C) Basic environmental setup for preprocessing (s1)

D) Preprocessing structural data

For surface-based preprocessing:

1. Use recon-all (Freesurfer) to correct bias-field, extract brain tissue, reconstruct structural images to cortical surface, and do anatomical segmentation (s2)
2. Use ciftify\_recon\_all (CIFTIFY, Dickie et al., 2019) to normalize structural images to MNI space, and resample native surface images onto Conte69 164k and 32k CIFTI surface (Van Essen et al., 2012) using MNI normalization parameters (s3)

For Volume-based preprocessing:

1. Use antsBrainExtraction (ANTs) to correct bias-field and extract brain tissue (s4)
2. Use antsRegistrationSyN (ANTs) to normalize structural images to MNI space (s4)
3. Use FAST (FSL) to do anatomical segmentation (s4)

[https://github.com/cocoanlab/surface\\_preprocessing](https://github.com/cocoanlab/surface_preprocessing)



## 2. Overall scheme

### E) Preprocessing functional data

1. Use 3dTshift (AFNI) to do slice-timing correction (s5, if needed)
2. Use 3dvolreg (AFNI) to do motion-correction (s6)
3. Use topup/applytopup (FSL) to do distortion-correction (s7)
4. Use flirt (FSL) with BBR cost function to co-register functional images to structural images (s8)
5. For surface-based preprocessing, additionally use bbregister (Freesurfer) to refine co-registration (s8)
6. Use ICA-AROMA (Pruim et al., 2015) to remove motion-related signals (s9)
7. Use 3dTproject (AFNI) to remove nuisance signals (s10)
8. Use applywarp (FSL, for surface-based preprocessing) or antsApplyTransforms (ANTs, for volume-based preprocessing) to normalize functional images to MNI space
9. For volume-based preprocessing, use susan (FSL) to spatially smooth functional images
10. For surface-based preprocessing, use ciftify\_subject\_fmri (CIFTIFY, Dickie et al., 2019) to transform functional images to Conte69 32k CIFTI surface, and spatially smooth (based on both surface-based and volume-based smoothing) functional images

Note: 8 can precede 6 and 7. depending on your purpose.


[https://github.com/cocoanlab/surface\\_preprocessing](https://github.com/cocoanlab/surface_preprocessing)




## 2. Overall scheme



Super useful!!!



Provide nice functions  
for some steps of preprocessing




Specialized tool for analysis  
based on CIFTI space




# FreeSurfer

Best tool for automatic cortical segmentation  
and surface-based analysis



Very good at MNI normalization



A savior for legacy MRI data – CIFTI-fy!



Computational Cognitive Affective Neuroscience Lab (Cocoon Lab) <https://cocoonlab.github.io>



## 2. Overall scheme

<https://docs.google.com/document/d/1wjh2fWaBKGc2XKo2aIKkbHGLzOIGgxyBlmCeL7VLI0o/edit>

# Surface Preprocessing Pipeline Software Installation Manual

April 2019, COCOAN Lab

## Introduction

This manual is written to guide those who wish to use the 'surface preprocessing' pipeline of Cocoon Lab. To use this new preprocessing pipeline, many softwares such as AFNI, ANTs, freesurfer, Connectome Workbench, ICA-AROMA, and CIFTIFY are needed to be installed in your workstation. Installing these softwares is not easy and takes many steps and efforts. Therefore, this manual aims to help the installation of the softwares, plus further information about running the code and minor issues to save your time and energy from troubleshooting!

[https://github.com/cocoonlab/surface\\_preprocessing](https://github.com/cocoonlab/surface_preprocessing)



Computational Cognitive Affective Neuroscience Lab (Cocoon Lab) <https://cocoonlab.github.io>



## 2. Overall scheme

You can also use either 1) fMRIPrep only or 2) fMRIPrep + ciftify!



### fMRIPrep: a robust preprocessing pipeline for functional MRI

Oscar Esteban<sup>1\*</sup>, Christopher J. Markiewicz<sup>2</sup>, Ross W. Blair<sup>1</sup>, Craig A. Moodie<sup>2</sup>, A. Ilkay Isik<sup>3</sup>, Asier Erramuzpe<sup>3</sup>, James D. Kent<sup>4</sup>, Mathias Goncalves<sup>5</sup>, Elizabeth DuPre<sup>6</sup>, Madeleine Snyder<sup>7</sup>, Hiroyuki Oya<sup>8</sup>, Satrajit S. Ghosh<sup>5,9</sup>, Jesse Wright<sup>1</sup>, Joke Durnez<sup>1</sup>, Russell A. Poldrack<sup>1,10</sup> and Krzysztof J. Gorgolewski<sup>1,10\*</sup>



Ciftify: A framework for surface-based analysis of legacy MR acquisitions

Erin W. Dickie<sup>a,\*</sup>, Alan Anticevic<sup>b,c,d,e</sup>, Dawn E. Smith<sup>a</sup>, Timothy S. Coalson<sup>f</sup>, Mathuvanthi Manogaran<sup>a</sup>, Navona Calarco<sup>a</sup>, Joseph D. Viviano<sup>a</sup>, Matthew F. Glasser<sup>f,g</sup>, David C. Van Essen<sup>h</sup>, Aristotle N. Voineskos<sup>a,h</sup>

<sup>a</sup> Kimel Family Translational Imaging-Genetics Laboratory, Campbell Family Mental Health Research Institute, Centre of Addiction and Mental Health, Toronto, Canada  
<sup>b</sup> Department of Psychiatry, Yale University School of Medicine, New Haven, CT, USA  
<sup>c</sup> Division of Neurocognition, Neurocomputation, & Neurogenetics (NCN), Yale University School of Medicine, New Haven, CT, USA  
<sup>d</sup> Interdepartmental Neuroscience Program, Yale University, New Haven, CT, USA  
<sup>e</sup> Department of Psychology, Yale University, New Haven, CT, USA  
<sup>f</sup> Departments of Radiology and Neuroscience, Washington University School of Medicine, St. Louis, USA  
<sup>g</sup> St. Luke's Hospital, Chesterfield, MO, USA  
<sup>h</sup> Department of Psychiatry, University of Toronto, Toronto, Canada

### HCP Grayordinates

If **CIFTI** output is enabled, the motion-corrected functional timeseries (in T1w space) is first sampled to the high resolution 164k vertex (per hemisphere) **fsaverage**. Following that, the resampled timeseries is sampled to *HCP Pipelines*'s **fsLR** mesh (with the left and right hemisphere aligned) using *Connectome Workbench*'s **-metric-resample** to generate a surface timeseries for each hemisphere. These surfaces are then combined with corresponding volumetric timeseries to create a **CIFTI2** file.

<https://fmripiprep.org/en/stable/index.html>

### fmripiprep\_ciftify\_BIDS-app

Runs a combination of fmripiprep and ciftify pipelines from BIDS specification

### Usage

```
run.py <bids_dir> <output_dir> <analysis_level> [options]
```

[https://edickie.github.io/ciftify/#/02\\_bids-app](https://edickie.github.io/ciftify/#/02_bids-app)



Computational Cognitive Affective Neuroscience Lab (Cocoon Lab) <https://cocoonlab.github.io>

