

Dynamic Programming

Heejin Park

Division of Computer Science and Engineering


Hanyang University

Contents


- **Introduction**
- **Assembly-line scheduling**
- **Rod cutting**
- **Matrix-chain multiplication**
- **Elements of dynamic programming**

Dynamic Programming

- **Dynamic programming** solves a problem by partitioning the problem into subproblems.
 - The subproblems are **independent**: divide-and-conquer method.
 - The subproblems are **not independent**: dynamic programming.



divide-and-conquer



Dynamic Programming

- A dynamic programming algorithm solves every subproblem just once and **saves its answer in a table** and then reuse it.

Dynamic Programming

- Dynamic programming is typically to solve **optimization problems**.
- **Optimization problems**
 - There can be many possible solutions.
 - Each solution has a value.
 - We find a solution with ***the*** optimal (minimum or maximum) value.
 - Such a solution is called ***an*** optimal solution to the problem.
 - Shortest path example

Dynamic Programming


- The development of a dynamic-programming algorithm can be broken into a sequence of four steps.
 1. Characterize the structure of an optimal solution.
 2. Recursively define the value of an optimal solution.
 3. Compute the value of an optimal solution in a bottom-up fashion.
 4. Construct an optimal solution from computed information.

Contents

- *Introduction*
- **Assembly-line scheduling**
- **Rod cutting**
- **Matrix-chain multiplication**
- **Elements of dynamic programming**

Assembly-line scheduling


assembly line



● **The problem:** Determine the fastest assembly time

Assembly-line scheduling


line 1



line 2

Assembly-line scheduling


line 1



line 2

Assembly-line scheduling

line 1



line 2

■ Transfer time: $t_{i,j}$


Assembly-line scheduling

- **Brute-force approach**

- Enumerate all possible ways and find a fastest way.
- There are 2^n possible ways: Too many.


Assembly-line scheduling

- **Step 1: The structure of the fastest way through the factory**
 - **Optimal substructure**
 - An optimal solution to a problem contains within it an optimal solution to subproblems.
 - For example, shortest path problem in a graph.



Assembly-line scheduling

- In this case, the fastest way to $S_{1,4}$ contains the fastest way through either $S_{1,3}$ or $S_{2,3}$.
- Generally, the fastest way through station $S_{i,j}$ contains the fastest way through either $S_{1,j-1}$ or $S_{2,j-1}$.



Assembly-line scheduling

• Step 2: A recursive solution

- $f_i[j]$ denotes the fastest time to finish station $S_{i,j}$.
 - $f_1[4]$ is the fastest time to finish the 4th station in line 1.
 - $f_2[3]$ is the fastest time to finish the 3th station in line 2.
- f^* denotes the fastest time to finish all stations.

Assembly-line scheduling

- **$f_i[j]$ for $j = 1$**

- $f_1[1] = e_1 + a_{1,1}$

- $f_2[1] = e_2 + a_{2,1}$

- **$f_i[j]$ for $j > 1$**

- $f_1[j] = \min(f_1[j-1] + a_{1,j}, f_2[j-1] + t_{2,j-1} + a_{1,j})$

- $f_2[j] = \min(f_2[j-1] + a_{2,j}, f_1[j-1] + t_{1,j-1} + a_{2,j})$

$$f^* = \min(f_1[n] + x_1, f_2[n] + x_2)$$

Assembly-line scheduling

- **Step 3: Computing the fastest times**

- *Simple recursive solution*

- The running time is $\Theta(2^n)$.

- Let $r_i(j)$ be the number of references made to $f_i[j]$.

- $r_i(j)$ for $j = n$

$$r_1(n) = r_2(n) = 1$$

- $r_i(j)$ for $j < n$


- $r_i(j) = 2^{n-j}$

$$r_1(j) = r_2(j) = r_1(j+1) + r_2(j+1)$$

- $f_1[1]$ and $f_2[1]$ are referred 2^{n-1} times, respectively.

Assembly-line scheduling

- *Dynamic programming*



Assembly-line scheduling


- **Running time**
 - We can compute the fastest time in $\Theta(n)$ time.

Assembly-line scheduling

Step 4: Constructing the fastest way through the factory

- The $l_i[j]$ values help us trace a fastest way.

line 1



line 2

$$l^* = 1$$

	2	3	4	5	6
$l_1[j]$	1	2	1	1	2
$l_2[j]$	1	2	1	2	2

Assembly-line scheduling

• Space consumption

- Table f : $2n$
- Table l : $2n-2$

• Space reduction

- Table f
 - $2n \rightarrow 4$
- Table l
 - $2n-2 \rightarrow 0$
 - If table f table is preserved.


Contents

- *Introduction*
- *Assembly-line scheduling*
- **Rod cutting**
- **Matrix-chain multiplication**
- **Elements of dynamic programming**








Rod cutting

- The **rod-cutting problem**: Given a rod of length n inches and a table of prices p_i for $i = 1, 2, \dots, n$, determine the maximum revenue r_n obtainable by cutting up the rod and selling the pieces.

length i	1	2	3	4	5	6	7	8	9	10
price p_i	1	5	8	9	10	17	17	20	24	30



Rod cutting



length i	1	2	3	4	5	6	7	8	9	10
price p_i	1	5	8	9	10	17	17	20	24	30

Rod cutting

$$r_n = \max(p_n, r_1 + r_{n-1}, r_2 + r_{n-2}, \dots, r_{n-1} + r_1)$$


$$r_n = \max_{1 \leq i \leq n} (p_i + r_{n-i})$$

Rod cutting

CUT-ROD (p, n)

```
1  if  $n == 0$   
2    return 0  
3   $q = -\infty$   
4  for  $i = 1$  to  $n$   
5     $q = \max(q, p[i] + \text{CUT-ROD}(p, n - i))$   
6  return  $q$ 
```

Rod cutting



Rod cutting

$$T(n) = 1 + \sum_{j=0}^{n-1} T(j)$$

$$T(n) = 2^n$$

Rod cutting

MEMOIZED-CUT-ROD (p, n)

- 1 let $r[0 .. n]$ be a new array
- 2 **for** $i = 0$ **to** n
- 3 $r[i] = -\infty$
- 4 **return** MEMOIZE-CUT-ROD-AUX (p, n, r)

Rod cutting

MEMOIZED-CUT-ROD-AUX (p, n, r)

```
1  if  $r[n] \geq 0$ 
2    return  $r[n]$ 
3  if  $n == 0$ 
4     $q = 0$ 
5  else  $q = -\infty$ 
6    for  $i = 1$  to  $n$ 
7       $q = \max(q, p[i] + \text{MEMOIZED-CUT-ROD-AUX}(p, n - i, r))$ 
8   $r[n] = q$ 
9  return  $q$ 
```


Rod cutting

BOTTOM-UP-CUT-ROD (p, n)

```
1  let  $r[0 .. n]$  be a new array
2   $r[0] = 0$ 
3  for  $j = 1$  to  $n$ 
4       $q = -\infty$ 
5      for  $i = 1$  to  $j$ 
6           $q = \max(q, p[i] + r[j - i])$ 
7       $r[j] = q$ 
8  return  $r[n]$ 
```

Rod cutting

- Subproblem graphs



Rod cutting

EXTENDED-BOTTOM-UP-CUT-ROD (p, n)

```
1  let  $r[0 .. n]$  and  $s[0 .. n]$  be new arrays
2   $r[0] = 0$ 
3  for  $j = 1$  to  $n$ 
4       $q = -\infty$ 
5      for  $i = 1$  to  $j$ 
6          if  $q < p[i] + r[j - i]$ 
7               $q = p[i] + r[j - i]$ 
8               $s[j] = i$ 
9       $r[j] = q$ 
10 return  $r$  and  $s$ 
```


Rod cutting

PRINT-CUT-ROD-SOLUTION(p, n)

```
1  ( $r, s$ ) = EXTENDED-BOTTOM-UP-CUT-ROD ( $p, n$ )  
2  while  $n > 0$   
3    print  $s[n]$   
4     $n = n - s[n]$ 
```

Rod cutting

i	0	1	2	3	4	5	6	7	8	9	10
$r[i]$	0	1	5	8	10	13	17	18	22	25	30
$s[i]$	0	1	2	3	2	2	6	1	2	3	10

Contents

- *Introduction*
- *Assembly-line scheduling*
- *Rod cutting*
- **Matrix-chain multiplication**
- **Elements of dynamic programming**

Matrix-chain multiplication

● Multiplying two matrices A and B

- We can multiply them if they are compatible: the number of columns of A must equal the number of rows of B .
- If A is a $p \times q$ matrix and B is a $q \times r$ matrix, the resulting matrix is a $p \times r$ matrix.

$$\begin{array}{c} \left[\begin{array}{ccc} \bullet & \bullet & \bullet \\ \circ & \circ & \circ \end{array} \right] \\ (A \text{ } 2 \times 3) \end{array} \times \begin{array}{c} \left[\begin{array}{c} \bullet \\ \bullet \\ \bullet \\ \circ \\ \circ \\ \circ \end{array} \right] \\ (B \text{ } 3 \times 2) \end{array} = \begin{array}{c} \left[\begin{array}{cc} \bullet & \bullet \\ \bullet & \bullet \end{array} \right] \\ (C \text{ } 2 \times 2) \end{array}$$

Matrix-chain multiplication

- The number of scalar multiplications to multiply A and B .
 - It is pqr because we compute pr elements and computing each element needs q scalar multiplications.

Matrix-chain multiplication

• The order of multiplications

- The order of multiplications does not change *the value of the product* because matrix multiplication is associative.
- For example, whether the left multiplication is done first or the right multiplication is done first does not matter.

$$(A_1 \cdot A_2) \cdot A_3 = A_1 \cdot (A_2 \cdot A_3)$$

- However, the order of multiplication affects *the number of scalar multiplications* needed to compute the product.

Matrix-chain multiplication

- The order of multiplications affects the number of scalar multiplications.
 - Computing $A_1 A_2 A_3$ where $A_1: 10 \times 100$ $A_2: 100 \times 5$ $A_3: 5 \times 50$
 - $(A_1 A_2) A_3$
 - $(A_1 A_2) = 10 * 100 * 5 = 5000$, $(10 \times 5) A_3 = 10 * 5 * 50 = 2500$
 $\Rightarrow 5000 + 2500 = \mathbf{7,500}$
 - $A_1 (A_2 A_3)$
 - $(A_2 A_3) = 100 * 5 * 50 = 25000$, $A_1(100 \times 50) = 10 * 100 * 50 = 50000$
 $\Rightarrow 25000 + 50000 = \mathbf{75,000}$
- Computing $(A_1 A_2) A_3$ is **10** times faster.

Matrix-chain multiplication

Matrix-chain multiplication problem

- Given a chain A_1, A_2, \dots, A_n of n matrices, where matrix A_i has dimension $p_{i-1} \times p_i$, find the order of matrix multiplications minimizing the scalar multiplications to compute the product.
- That is, to fully parenthesize the product of matrices minimizing scalar multiplications.

Matrix-chain multiplication

- The product $A_1 A_2 A_3 A_4$ can be fully parenthesized in five distinct ways.

$$A_1(A_2(A_3 A_4)), \quad A_1((A_2 A_3) A_4),$$

$$(A_1 A_2)(A_3 A_4),$$

$$(A_1(A_2 A_3))A_4, \quad ((A_1 A_2) A_3) A_4.$$

Matrix-chain multiplication

- **Solutions of the matrix-chain multiplication problem**
 - **Brute-force approach**
 - Enumerate all possible parenthesizations.
 - Compute the number of scalar multiplications of each parenthesization.
 - Select the parenthesization needing the least number of scalar multiplications.

Matrix-chain multiplication

- **The Brute-force approach is inefficient.**
 - The number of parenthesizations of a product of n matrices, denoted by $P(n)$, is as follows.

$$P(n) = \begin{cases} 1 & \text{if } n=1 \\ \sum_{k=1}^{n-1} P(k)P(n-k) & \text{if } n \geq 2 \end{cases}$$

- The number of enumerated parenthesizations is $\Omega(4^n/n^{3/2})$.

Matrix-chain multiplication

- Dynamic programming
- Optimal substructure

- $m[i, j]$: The minimum number of scalar multiplications for computing $A_i A_{i+1} \dots A_j$.

$$m[i, j] = \begin{cases} 0 & \text{if } i=j \\ \min_{i \leq k < j} \{m[i, k] + m[k+1, j] + p_{i-1} p_k p_j\} & \text{if } i < j \end{cases}$$

- matrix $A_i : p_{i-1} \times p_i$
- computing $A_{i \dots k} A_{k+1 \dots j}$ takes $p_{i-1} p_k p_j$ scalar multiplications.
- $s[i, j]$ stores the optimal k for tracing the optimal solution.

Matrix-chain multiplication

$i \backslash j$	1	2	3	4	5	6
1	0	15750	7875	9375	11875	15125
2		0	2625	4375	7125	10500
3			0	750	2500	5375
4				0	1000	3500
5					0	5000
6						0

m

$i \backslash j$	2	3	4	5	6
1	1	1	3	3	3
2		2	3	3	3
3			3	3	3
4				4	5
5					5

s

$$m[2,5] = \min \begin{cases} m[2,2] + m[3,5] + p_1 p_2 p_5 = 0 + 2500 + 35 \cdot 15 \cdot 20 = 13000, \\ m[2,3] + m[4,5] + p_2 p_3 p_5 = 2625 + 1000 + 35 \cdot 5 \cdot 20 = 7125, \\ m[2,4] + m[5,5] + p_1 p_4 p_5 = 4375 + 0 + 35 \cdot 10 \cdot 20 = 11375 \end{cases}$$

$$i=2, j=5, i \leq k < j$$

matrix dimension

A_1	30×35
A_2	35×15
A_3	15×5
A_4	5×10
A_5	10×20
A_6	20×25

Matrix-chain multiplication

- **Running time**

- $O(n^3)$ time in total
 - $\Theta(n^2)$ subproblems
 - $O(n)$ time for each subproblem

- **Space consumption**

- $\Theta(n^2)$ space to store the m and s tables.

Contents

- *Introduction*
- *Assembly-line scheduling*
- *Rod cutting*
- *Matrix-chain multiplication*
- **Elements of dynamic programming**


Elements of dynamic programming

- **Elements of dynamic programming**
 - *Optimal substructure*
 - *Overlapping subproblems*


Element of dynamic programming

• Subtleties

- Unweighted longest simple path problem
 - Does it have optimal substructure?



Elements of dynamic programming




$$q \rightarrow r \rightarrow t$$

Elements of dynamic programming

● Overlapping subproblems

- When a recursive algorithm revisits the same problem over and over again, the optimization problem has *overlapping subproblems*.

Elements of dynamic programming



Matrix chain multiplication: top-down vs. bottom-up

Elements of dynamic programming

● Memoization

- Recursive solution but solve each subproblem only once.
- Fills the table in recursive way.
- In most cases, it is slower than dynamic programming.
- It is useful when only a part of subproblems are solved.

Elements of dynamic programming

- **The running time** of a dynamic-programming algorithm depends on the product of two factors.
 - *The number of subproblems overall.*
 - *How many choices each subproblem has.*
- Assembly line scheduling
 - $\Theta(n)$ subproblems \cdot 2 choices = $\Theta(n)$
- Matrix chain multiplication
 - $\Theta(n^2)$ subproblems \cdot $(n-1)$ choices = $O(n^3)$

Programming assignment

- **Matrix-chain multiplication (optimal solution)**
 - Dynamic programming (#1)
 - Memoization (#2)
- **Longest Common Subsequence (#3)**
 - Optimal value (Space reduction)
- **Due on May 27**