Advanced Transformer Architectures for LLMs

Wei Xu

(some slides from Greg Durrett, Daniel Khashabi, Tatsunori Hashimoto)

Transformer Variants




Fig. 3. Taxonomy of Transformers

Positional Embeddings

LayerNorm

3 main types: encoder, decoder, enc-dec

Lin et al. (2021)

What is being used in LLMs?

- There are many architectural variations.
- Major differences? Norm, position embeddings, activations, tokenization
- This is an evolving field; a lot of empirical analysis is going into identifying best practices.

Name	Has pa...	Link	Year	Tokenizer type	Vocab count	Norm	Parallel Layer	Pre-norm	Position embedding	Activations	MoE	MLP factor	num_layers	model_dim
Original transformer	Yes	arxiv.org/abs....03762	2017	BPE	37000	LayerNorm	Serial	☐	Sine	ReLU	☐	4	6	
GPT	Yes	cdn.openai.com/res...er.pdf	2018	BPE	40257	LayerNorm	Serial	☐	Absolute	GeLU	☐	4	12	
GPT2	Yes	cdn.openai.com/bet...rs.pdf	2019	BPE	50257	LayerNorm	Serial	☑	Sine	GeLU	☐	4	48	
T5 (11B)	Yes	arxiv.org/abs....10683	2019	SentencePiece	32128	RMSNorm	Serial	☑	Relative	ReLU	☐	64	24	
GPT3 (175B)	Yes	arxiv.org/abs....14165	2020	BPE	50257	LayerNorm	Serial	☑	Sine	GeLU	☐	4	96	
mT5	Yes	arxiv.org/abs....11934	2020	SentencePiece	250000	RMSNorm	Serial	☑	Relative	GeGLU	☐	2.5	24	
T5 (XXL 11B) v1.1	Kind of	github.com/goo...d#t511	2020	SentencePiece	32128	RMSNorm	Serial	☑	Relative	GeGLU	☐	2.5	24	
Gopher (280B)	Yes	arxiv.org/abs....11446	2021	SentencePiece	32000	RMSNorm	Serial	☑	Relative	ReLU	☐	4	80	
Anthropic LM (not claude)	Yes	arxiv.org/abs....00861	2021	BPE	65536			☑			☐	4	64	
LaMDA	Yes	arxiv.org/abs....08239	2021	BPE	32000			☑	Relative	GeGLU	☐	8	64	
GPTJ	Kind of	huggingface.co/Ele...t-j-6b	2021	BPE	50257	LayerNorm	Parallel	☑	RoPE	GeLU	☐		28	
Chinchilla	Yes	arxiv.org/abs....15556	2022	SentencePiece	32000	RMSNorm	Serial	☑	Relative	ReLU	☐	4	80	
PaLM (540B)	Yes	arxiv.org/abs....02311	2022	SentencePiece	256000	RMSNorm	Parallel	☑	RoPE	SwiGLU	☐	4	118	
OPT (175B)	Yes	arxiv.org/abs....01068	2022	BPE	50272	LayerNorm	Serial	☑	Absolute	ReLU	☐	4	96	
BLOOM (175B)	Yes	arxiv.org/abs....05100	2022	BPE	250680	LayerNorm	Serial	☑	AliBi	GeLU	☐	4	70	
GPT-NeoX	Yes	arxiv.org/pdf...45.pdf	2022	BPE	50257	LayerNorm	Parallel	☑	RoPE	GeLU	☐	4	44	
GPT4 OPEN	Ad	arxiv.org/abs....08774	2023	BPE	100000			☐			☐			
LLaMA (65B)	Yes	arxiv.org/abs....13971	2023	BPE	32000	RMSNorm	Serial	☑	RoPE	SwiGLU	☐	2.6875	80	
LLaMA2 (70B)	Yes	arxiv.org/abs....09288	2023	BPE	32000	RMSNorm	Serial	☑	RoPE	SwiGLU	☐	3.5	80	
Mistral (7B)	Yes	arxiv.org/abs....06825	2023	BPE	32000	RMSNorm	Serial	☑	RoPE	SwiGLU	☐	3.5	32	

Image Credit: Tatsu Hashimoto

What is being used in LLMs?

- There are many architectural variations.
- Major differences? Norm, position embeddings, activations, tokenization
- This is an evolving field; a lot of empirical analysis is going into identifying best practices.

Name	Has pa...	Link	Year	Tokenizer type	Vocab count	Norm	Parallel Layer	Pre-norm	Position embedding	Activations	MoE	MLP factor	num_layers	model_dim
Original transformer	Yes	arxiv.org/abs....03762	2017	BPE	37000	LayerNorm	Serial	☐	Sine	ReLU	☐	4	6	
GPT	Yes	cdn.openai.com/res...er.pdf	2018	BPE	40257	LayerNorm	Serial	☐	Absolute	GeLU	☐	4	12	
GPT2	Yes	cdn.openai.com/bet...rs.pdf	2019	BPE	50257	LayerNorm	Serial	☑	Sine	GeLU	☐	4	48	
T5 (11B)	Yes	arxiv.org/abs....10683	2019	SentencePiece	32128	RMSNorm	Serial	☑	Relative	ReLU	☐	64	24	
GPT3 (175B)	Yes	arxiv.org/abs....14165	2020	BPE	50257	LayerNorm	Serial	☑	Sine	GeLU	☐	4	96	
mT5	Yes	arxiv.org/abs....11934	2020	SentencePiece	250000	RMSNorm	Serial	☑	Relative	GeGLU	☐	2.5	24	
T5 (XXL 11B) v1.1	Kind of	github.com/goo...d#t511	2020	SentencePiece	32128	RMSNorm	Serial	☑	Relative	GeGLU	☐	2.5	24	
Gopher (280B)	Yes	arxiv.org/abs....11446	2021	SentencePiece	32000	RMSNorm	Serial	☑	Relative	ReLU	☐	4	80	
Anthropic LM (not claude)	Yes	arxiv.org/abs....00861	2021	BPE	65536			☑			☐	4	64	
LaMDA	Yes	arxiv.org/abs....08239	2021	BPE	32000			☑	Relative	GeGLU	☐	8	64	
GPTJ	Kind of	huggingface.co/Ele...t-j-6b	2021	BPE	50257	LayerNorm	Parallel	☑	RoPE	GeLU	☐		28	
Chinchilla	Yes	arxiv.org/abs....15556	2022	SentencePiece	32000	RMSNorm	Serial	☑	Relative	ReLU	☐	4	80	
PaLM (540B)	Yes	arxiv.org/abs....02311	2022	SentencePiece	256000	RMSNorm	Parallel	☑	RoPE	SwiGLU	☐	4	118	
OPT (175B)	Yes	arxiv.org/abs....01068	2022	BPE	50272	LayerNorm	Serial	☑	Absolute	ReLU	☐	4	96	
BLOOM (175B)	Yes	arxiv.org/abs....05100	2022	BPE	250680	LayerNorm	Serial	☑	AliBi	GeLU	☐	4	70	
GPT-NeoX	Yes	arxiv.org/pdf...45.pdf	2022	BPE	50257	LayerNorm	Parallel	☑	RoPE	GeLU	☐	4	44	
GPT4 OPEN	Ad	arxiv.org/abs....08774	2023	BPE	100000			☐			☐			
LLaMA (65B)	Yes	arxiv.org/abs....13971	2023	BPE	32000	RMSNorm	Serial	☑	RoPE	SwiGLU	☐	2.6875	80	
LLaMA2 (70B)	Yes	arxiv.org/abs....09288	2023	BPE	32000	RMSNorm	Serial	☑	RoPE	SwiGLU	☐	3.5	80	
Mistral (7B)	Yes	arxiv.org/abs....06825	2023	BPE	32000	RMSNorm	Serial	☑	RoPE	SwiGLU	☐	3.5	32	

Image Credit: Tatsu Hashimoto

What is being used in LLMs?

- Mostly follow previous successful choices.

Name	Year	Norm	Parallel Layer	Pre-norm	Position embedding	Activations
Original transformer	2017	LayerNorm	Serial	☐	Sine	ReLU
GPT	2018	LayerNorm	Serial	☐	Absolute	GeLU
T5 (11B)	2019	RMSNorm	Serial	☑	Relative	ReLU
GPT2	2019	LayerNorm	Serial	☑	Sine	GeLU
T5 (XXL 11B) v1.1	2020	RMSNorm	Serial	☑	Relative	GeGLU
mT5	2020	RMSNorm	Serial	☑	Relative	GeGLU
GPT3 (175B)	2020	LayerNorm	Serial	☑	Sine	GeLU
GPTJ	2021	LayerNorm	Parallel	☑	RoPE	GeLU
LaMDA	2021			☑	Relative	GeGLU
Gopher (280B)	2021	RMSNorm	Serial	☑	Relative	ReLU
GPT-NeoX	2022	LayerNorm	Parallel	☑	RoPE	GeLU
BLOOM (175B)	2022	LayerNorm	Serial	☑	AliBi	GeLU
OPT (175B)	2022	LayerNorm	Serial	☑	Absolute	ReLU
PaLM (540B)	2022	RMSNorm	Parallel	☑	RoPE	SwiGLU
Chinchilla	2022	RMSNorm	Serial	☑	Relative	ReLU
Mistral (7B)	2023	RMSNorm	Serial	☑	RoPE	SwiGLU
LLaMA2 (70B)	2023	RMSNorm	Serial	☑	RoPE	SwiGLU
LLaMA (65B)	2023	RMSNorm	Serial	☑	RoPE	SwiGLU
Qwen (14B)	2024	RMSNorm	Serial	☑	RoPE	SwiGLU
DeepSeek (67B)	2024	RMSNorm	Serial	☑	RoPE	SwiGLU
Yi (34B)	2024	RMSNorm	Serial	☑	RoPE	SwiGLU

Image Credit: Tatsu Hashimoto

Open-source Efforts

OPT: Open Pre-trained Transformer LMs

- GPT-3 models only released via API access.
- PALM not generally available outside Google
  - Doesn't support reproducible experiments.




Figure 3: **Zero-shot NLP Evaluation Averages**. Across a variety of tasks and model sizes, OPT largely matches the reported averages of GPT-3. However, performance varies greatly per task: see Appendix A.

- OPT (125M-66B-175B; June 2022 by Meta), to roughly matches GPT-3, with parameters are shared with the research community

Zhang et al. (2022)

OPT: Open Pre-trained Transformer LMs

- Includes 114 page logbook for training 175B model, interesting read

2021-11-16 11pm [Myle]: Run 12.08

- Previous run failed with mysterious error: “p2p_plugin.c:141 NCCL WARN NET/IB : Got async event : port error”
- New log file: /shared/home/namangoyal/checkpoints/175B/175B_run12.08.me_fp16.fsdp.gpf32.0.relu.transformer_lm_megatron.nlay96.emb12288.lrnpos.0emb_scale.bm_none.tps2048.gpt2.adam.b2_0.95.eps1e-08.cl1.0.lr0.00012.endlr6e-06.wu2000.dr0.1.atdr0.1.0emb_dr.wd0.1.ms8.uf1.mu143052.s1.ngpu992/train.log

```
CKPT_DIR=/data/users/myleott/175B_run12.07.me_fp16.fsdp.gpf32.0.relu.transformer_lm_megatron.nlay96.emb12288.lrnpos.0emb_scale.bm_none.tps2048.gpt2.adam.b2_0.95.eps1e-08.cl1.0.lr0.00012.endlr6e-06.wu2000.dr0.1.atdr0.1.0emb_dr.wd0.1.ms8.uf1.mu143052.s1.ngpu992

BLOB_URL="<<<SCRUBBED FOR RELEASE>>>"

cd $CKPT_DIR
cp --recursive --include-pattern "checkpoint_5_13250*.pt" "$BLOB_URL" checkpoint_5_13250

export RESTORE_FILE=$CKPT_DIR/checkpoint_5_13250/checkpoint_5_13250.pt

export RUN_ID=175B_run12.08

INCLUDED_HOSTS=node-[1-38,40-89,91-94,96-119,121-128] \
    python -m fb_sweep.opt.sweep_opt_en_lm_175b \
    -n 124 -g 8 -t 1 \
    -p $RUN_ID \
    --checkpoints-dir /shared/home/namangoyal/checkpoints/175B/ \
    --restore-file $RESTORE_FILE

After launch:
sudo scontrol update job=1394 TimeLimit=UNLIMITED
sudo scontrol update job=1394 MailUser=<scrubbed> MailType=ALL
```

6 Considerations for Release


Following the recommendations for individual researchers generated by the Partnership for AI,[7] along with the governance guidance outlined by NIST,[8] we are disclosing all of the details involved in training OPT-175B through our logbook,[9] our code, and providing researchers access to model weights for OPT-175B, along with a suite of smaller baselines mirroring the setup for OPT-175B. We aim to be fully accountable for the development lifecycle of OPT-175B, and only through increasing transparency around LLM development can we start understanding the limitations and risks of LLMs before broader deployment occurs.

By sharing a detailed account of our day-to-day training process, we disclose not only how much compute was used to train the current version of OPT-175B, but also the human overhead required when underlying infrastructure or the training process itself becomes unstable at scale. These details

Zhang et al. (2022)

Bloom

- A BigScience initiative, open-access, 176B parameter (GPT-2 architecture)
- 59 languages (46 natural language + 13 programming language)
- 1.6TB of pre-processed text



https://huggingface.co/bigscience/bloom

LLaMA

- Released by Meta AI on **Feb 27, 2023**
- Weights of all models are publicly available (non-commercial license)

params	dimension	n heads	n layers	learning rate	batch size	n tokens
6.7B	4096	32	32	$3.0e^{-4}$	4M	1.0T
13.0B	5120	40	40	$3.0e^{-4}$	4M	1.0T
32.5B	6656	52	60	$1.5e^{-4}$	4M	1.4T
65.2B	8192	64	80	$1.5e^{-4}$	4M	1.4T

Table 2: **Model sizes, architectures, and optimization hyper-parameters.**




Figure 1: **Training loss over train tokens for the 7B, 13B, 33B, and 65 models.** LLaMA-33B and LLaMA-65B were trained on 1.4T tokens. The smaller models were trained on 1.0T tokens. All models are trained with a batch size of 4M tokens.

LLaMA

- Trained only on publicly available data:
  - English CommonCrawl
  - C4 (another CommonCrawl dataset)
  - GitHub (from Google BigQuery)
  - Wikipedia of 20 languages,
  - Gutenberg and Books3 (from ThePile)
  - ArXiv (latex files)
  - StackExchange.

Dataset	Sampling prop.	Epochs	Disk size
CommonCrawl	67.0%	1.10	3.3 TB
C4	15.0%	1.06	783 GB
Github	4.5%	0.64	328 GB
Wikipedia	4.5%	2.45	83 GB
Books	4.5%	2.23	85 GB
ArXiv	2.5%	1.06	92 GB
StackExchange	2.0%	1.03	78 GB

Table 1: **Pre-training data.** Data mixtures used for pre-training, for each subset we list the sampling proportion, number of epochs performed on the subset when training on 1.4T tokens, and disk size. The pre-training runs on 1T tokens have the same sampling proportion.

- Split all numbers into individual digits, and fall back to bytes for unknown UTF-8 characters

LLaMA

- LLaMA-13B matches and outperforms OPT and (old) GPT-3 for zero-shot and few-shot performance

		BoolQ	PIQA	SIQA	HellaSwag	WinoGrande	ARC-e	ARC-c	OBQA
GPT-3	175B	60.5	81.0	-	78.9	70.2	68.8	51.4	57.6
Gopher	280B	79.3	81.8	50.6	79.2	70.1	-	-	-
Chinchilla	70B	83.7	81.8	51.3	80.8	74.9	-	-	-
PaLM	62B	84.8	80.5	-	79.7	77.0	75.2	52.5	50.4
PaLM-cont	62B	83.9	81.4	-	80.6	77.0	-	-	-
PaLM	540B	**88.0**	82.3	-	83.4	**81.1**	76.6	53.0	53.4
LLaMA	7B	76.5	79.8	48.9	76.1	70.1	72.8	47.6	57.2
	13B	78.1	80.1	50.4	79.2	73.0	74.8	52.7	56.4
	33B	83.1	82.3	50.4	82.8	76.0	**80.0**	**57.8**	58.6
	65B	85.3	**82.8**	**52.3**	**84.2**	77.0	78.9	56.0	**60.2**

Table 3: **Zero-shot performance on Common Sense Reasoning tasks.**

		0-shot	1-shot	5-shot	64-shot
GPT-3	175B	14.6	23.0	-	29.9
Gopher	280B	10.1	-	24.5	28.2
Chinchilla	70B	16.6	-	31.5	35.5
PaLM	8B	8.4	10.6	-	14.6
	62B	18.1	26.5	-	27.6
	540B	21.2	29.3	-	39.6
LLaMA	7B	16.8	18.7	22.0	26.1
	13B	20.1	23.4	28.1	31.9
	33B	**24.9**	28.3	32.9	36.0
	65B	23.8	**31.0**	**35.0**	**39.9**

Table 4: **NaturalQuestions.** Exact match performance.

LLaMA

- Transformer variations that have been used in different LLMs




Image Credit: Rajesh Kavadiki

LLaMA

- Transformer variations that have been used in different LLMs
- Pre-normalization layer using RMSNorm
- SwiGLU activation function — combines Swish and Gated Linear Unit (GLU), also used in Google's PaLM model
- Rotary positional embeddings (RoPE)
- AdamW Optimizer

Normalization


Pre-norm vs. Post-norm

- Original Transformer — “Add” before “Norm”, or “Norm” before “Add”?

$$LayerNorm\big(x + SubLayer(x)\big)$$

or


$$x + SubLayer\big(LayerNorm(x)\big)$$



(Baevski & Auli, 2018; Child et al., 2019; Wang et al., 2019)

Pre-norm vs. Post-norm


- Pre-normalization Transformer (b) to have better-behaved gradients at initialization than in the original Transformer (a)




Xiong et al. (2020)

Pre-norm vs. Post-norm

- Pre-normalization Transformer (b) to have better-behaved gradients at initialization than in the original Transformer (a)
- In (b), LayerNorm does not disrupt residual






Xiong et al. (2020)

Pre-norm vs. Post-norm


- Post-norm produces noisy gradients with many tall spikes, needs warm up
- Pre-norm has fewer noisy gradients with smaller sizes, even without warmup



Nguyen & Salazar (2019)

Pre-norm vs. Post-norm

- Today, almost all LLMs use pre-norm for stability and larger learning rates for training large networks.
- Double Norm: Google's Gemma 2/3 used both pre-norm and post-norm.



(Recap) LayerNorm

- LayerNorm re-centers and re-scales input **a** = (a_1, a_2, …, a_n)
  - Re-center: enable the model to be insensitive to shift noises on both inputs and weights,
  - Re-scale: keep the output representations intact when both inputs and weights are randomly scaled.
- **g :** "gain"parameter of LayerNorm, a learnable vector, which helps to adaptively determine the optimal scale

mean

$$\bar{a}_i = \frac{a_i - \mu}{\sigma} g_i$$

variance

$$\mu = \frac{1}{n}\sum_{i=1}^{n} a_i, \quad \sigma = \sqrt{\frac{1}{n}\sum_{i=1}^{n}(a_i - \mu)^2}.$$

Ba et al. (2016)

RMSNorm

- RMSNorm (a) instead of standard LayerNorm (b)

root mean square

$$\bar{a}_i = \frac{a_i}{\mathbf{RMS}(\mathbf{a})} g_i, \quad \text{where } \mathbf{RMS}(\mathbf{a}) = \sqrt{\frac{1}{n}\sum_{i=1}^{n} a_i^2}.$$

(a)

(used in LLaMA1/2/3, PaLM, T5 …)

mean

variance

$$\bar{a}_i = \frac{a_i - \mu}{\sigma} g_i$$

(b)

$$\mu = \frac{1}{n}\sum_{i=1}^{n} a_i, \quad \sigma = \sqrt{\frac{1}{n}\sum_{i=1}^{n}(a_i - \mu)^2}.$$

(used in GPT1/2/3, OPT …)

Zhang and Sennrich (2019)

RMSNorm

- RMSNorm (a) instead of standard LayerNorm (b)

root mean square

$$\bar{a}_i = \frac{a_i}{\mathrm{RMS}(\mathbf{a})} g_i, \quad \text{where } \mathrm{RMS}(\mathbf{a}) = \sqrt{\frac{1}{n}\sum_{i=1}^{n} a_i^2}.$$

(a)

mean

variance

$$\bar{a}_i = \frac{a_i - \mu}{\sigma} g_i$$

(b)

$$\mu = \frac{1}{n}\sum_{i=1}^{n} a_i, \quad \sigma = \sqrt{\frac{1}{n}\sum_{i=1}^{n}(a_i - \mu)^2}.$$

only re-scaling invariance, skip re-centering

more computationally efficient

Zhang and Sennrich (2019)

RMSNorm

- RMSNorm (a) instead of standard LayerNorm (b)

root mean square

$$\bar{a}_i = \frac{a_i}{\mathrm{RMS}(\mathbf{a})} g_i, \quad \text{where } \mathrm{RMS}(\mathbf{a}) = \sqrt{\frac{1}{n}\sum_{i=1}^{n} a_i^2}.$$

(a)

mean

variance

$$\bar{a}_i = \frac{a_i - \mu}{\sigma} g_i$$

(b)

$$\mu = \frac{1}{n}\sum_{i=1}^{n} a_i, \quad \sigma = \sqrt{\frac{1}{n}\sum_{i=1}^{n}(a_i - \mu)^2}.$$

only re-scaling invariance, skip re-centering

more computationally efficient ??

Zhang and Sennrich (2019)

RMSNorm

- Matrix multiplications make up the majority of GPU FLOPs (and memory)
- Below is runtime analysis of the encoder layer of (Transformer-based) BERT

Matrix-matrix multiplication

softmax & layer normalization

Table 1. Proportions for operator classes in PyTorch.

Operator class	% flop	% Runtime
△ Tensor contraction	99.80	61.0
□ Stat. normalization	0.17	25.5
○ Element-wise	0.03	13.5

biases, dropout, activations, and residual connections

more computationally efficient ??

Ivanov et al. (2021)

RMSNorm

- Yet, RMSNorm runtime gains have been observed in papers

Model	Params	Ops	Step/s	Early loss	Final loss	SGLUE	XSum	WebQ	WMT EnDe
Vanilla Transformer	$223M$	$11.1T$	3.50	2.182 ± 0.005	1.838	71.66	17.78	23.02	26.62
RMS Norm	$223M$	$11.1T$	3.68	2.167 ± 0.008	**1.821**	**75.45**	**17.94**	**24.07**	**27.14**

- FLOPs alone are not a reliable measure of GPU runtime. Memory bandwidth, data reuse, overhead also matters

more computationally efficient ??

Narang et al. (2021)

Model	Params	Ops	Step/s	Early loss	Final loss	SGLUE	XSum	WebQ	WMT EnDe
Vanilla Transformer	$223M$	$11.1T$	3.50	2.182 ± 0.005	1.838	71.66	17.78	23.02	26.62
GeLU	$223M$	$11.1T$	3.58	2.179 ± 0.003	1.838	**75.79**	**17.86**	**25.13**	26.47
Swish	$223M$	$11.1T$	3.62	2.186 ± 0.003	1.847	**73.77**	17.74	**24.34**	**26.75**
ELU	$223M$	$11.1T$	3.56	2.270 ± 0.007	1.932	67.83	16.73	23.02	26.08
GLU	$223M$	$11.1T$	3.59	2.174 ± 0.003	**1.814**	**74.20**	**17.42**	24.34	**27.12**
GeGLU	$223M$	$11.1T$	3.55	2.130 ± 0.006	**1.792**	**75.96**	**18.27**	**24.87**	**26.87**
ReGLU	$223M$	$11.1T$	3.57	2.145 ± 0.004	**1.803**	**76.17**	**18.36**	**24.87**	**27.02**
SeLU	$223M$	$11.1T$	3.55	2.315 ± 0.004	1.948	68.76	16.76	22.75	25.99
SwiGLU	$223M$	$11.1T$	3.53	2.127 ± 0.003	**1.789**	**76.00**	**18.20**	**24.34**	**27.02**
LiGLU	$223M$	$11.1T$	3.59	2.149 ± 0.005	**1.798**	**75.34**	**17.97**	**24.34**	26.53
Sigmoid	$223M$	$11.1T$	3.63	2.291 ± 0.019	1.867	**74.31**	17.51	23.02	26.30
Softplus	$223M$	$11.1T$	3.47	2.207 ± 0.011	1.850	**72.45**	17.65	**24.34**	**26.89**
RMS Norm	$223M$	$11.1T$	3.68	2.167 ± 0.008	**1.821**	**75.45**	**17.94**	**24.07**	**27.14**
Rezero	$223M$	$11.1T$	3.51	2.262 ± 0.003	1.939	61.69	15.64	20.90	26.37
Rezero + LayerNorm	$223M$	$11.1T$	3.26	2.223 ± 0.006	1.858	70.42	17.58	23.02	26.29
Rezero + RMS Norm	$223M$	$11.1T$	3.34	2.221 ± 0.009	1.875	70.33	17.32	23.02	26.19
Fixup	$223M$	$11.1T$	2.95	2.382 ± 0.012	2.067	58.56	14.42	23.02	26.31
24 layers, $d_{\text{ff}} = 1536$, $H = 6$	$224M$	$11.1T$	3.33	2.200 ± 0.007	1.843	**74.89**	17.75	**25.13**	**26.89**
18 layers, $d_{\text{ff}} = 2048$, $H = 8$	$223M$	$11.1T$	3.38	2.185 ± 0.005	**1.831**	**76.45**	16.83	**24.34**	**27.10**
8 layers, $d_{\text{ff}} = 4608$, $H = 18$	$223M$	$11.1T$	3.69	2.190 ± 0.005	1.847	**74.58**	17.69	**23.28**	**26.85**
6 layers, $d_{\text{ff}} = 6144$, $H = 24$	$223M$	$11.1T$	3.70	2.201 ± 0.010	1.857	**73.55**	17.59	**24.60**	**26.66**
Block sharing	$65M$	$11.1T$	3.91	2.497 ± 0.037	2.164	64.50	14.53	21.96	25.48
+ Factorized embeddings	$45M$	$9.4T$	4.21	2.631 ± 0.305	2.183	60.84	14.00	19.84	25.27
+ Factorized & shared embeddings	$20M$	$9.1T$	4.37	2.907 ± 0.313	2.385	53.95	11.37	19.84	25.19
Encoder only block sharing	$170M$	$11.1T$	3.68	2.298 ± 0.023	1.929	69.60	16.23	23.02	26.23
Decoder only block sharing	$144M$	$11.1T$	3.70	2.352 ± 0.029	2.082	67.93	16.13	**23.81**	26.08
Factorized Embedding	$227M$	$9.4T$	3.80	2.208 ± 0.006	1.855	70.41	15.92	22.75	26.50
Factorized & shared embeddings	$202M$	$9.1T$	3.92	2.320 ± 0.010	1.952	68.69	16.33	22.22	26.44
Tied encoder/decoder input embeddings	$248M$	$11.1T$	3.55	2.192 ± 0.002	1.840	**71.70**	17.72	**24.34**	26.49
Tied decoder input and output embeddings	$248M$	$11.1T$	3.57	2.187 ± 0.007	**1.827**	**74.86**	17.74	**24.87**	**26.67**
Untied embeddings	$273M$	$11.1T$	3.53	2.195 ± 0.005	**1.834**	**72.99**	17.58	**23.28**	26.48
Adaptive input embeddings	$204M$	$9.2T$	3.55	2.250 ± 0.002	1.899	66.57	16.21	**24.07**	**26.66**
Adaptive softmax	$204M$	$9.2T$	3.60	2.364 ± 0.005	1.982	**72.91**	16.67	21.16	25.56
Adaptive softmax without projection	$223M$	$10.8T$	3.43	2.229 ± 0.009	1.914	**71.82**	17.10	23.02	25.72
Mixture of softmaxes	$232M$	$16.3T$	2.24	2.227 ± 0.017	**1.821**	**76.77**	17.62	22.75	**26.82**
Transparent attention	$223M$	$11.1T$	3.33	2.181 ± 0.014	1.874	54.31	10.40	21.16	**26.80**
Dynamic convolution	$257M$	$11.8T$	2.65	2.403 ± 0.009	2.047	58.30	12.67	21.16	17.03
Lightweight convolution	$224M$	$10.4T$	4.07	2.370 ± 0.010	1.989	63.07	14.86	23.02	24.73
Evolved Transformer	$217M$	$9.9T$	3.09	2.220 ± 0.003	1.863	**73.67**	10.76	**24.07**	26.58
Synthesizer (dense)	$224M$	$11.4T$	3.47	2.334 ± 0.021	1.962	61.03	14.27	16.14	**26.63**
Synthesizer (dense plus)	$243M$	$12.6T$	3.22	2.191 ± 0.010	1.840	**73.98**	16.96	**23.81**	**26.71**
Synthesizer (dense plus alpha)	$243M$	$12.6T$	3.01	2.180 ± 0.007	**1.828**	**74.25**	17.02	**23.28**	26.61
Synthesizer (factorized)	$207M$	$10.1T$	3.94	2.341 ± 0.017	1.968	62.78	15.39	**23.55**	26.42
Synthesizer (random)	$254M$	$10.1T$	4.08	2.326 ± 0.012	2.009	54.27	10.35	19.56	26.44
Synthesizer (random plus)	$292M$	$12.0T$	3.63	2.189 ± 0.004	1.842	**73.32**	17.04	**24.87**	26.43
Synthesizer (random plus alpha)	$292M$	$12.0T$	3.42	2.186 ± 0.007	**1.828**	**75.24**	17.08	**24.08**	26.39
Universal Transformer	$84M$	$40.0T$	0.88	2.406 ± 0.036	2.053	70.13	14.09	19.05	23.91
Mixture of experts	$648M$	$11.7T$	3.20	2.148 ± 0.006	**1.785**	**74.55**	**18.13**	**24.08**	**26.94**
Switch Transformer	$1100M$	$11.7T$	3.18	2.135 ± 0.007	**1.758**	**75.38**	**18.02**	**26.19**	**26.81**
Funnel Transformer	$223M$	$1.9T$	4.30	2.288 ± 0.008	1.918	67.34	16.26	22.75	23.20
Weighted Transformer	$280M$	$71.0T$	0.59	2.378 ± 0.021	1.989	69.04	16.98	23.02	26.30
Product key memory	$421M$	$386.6T$	0.25	2.155 ± 0.003	**1.798**	**75.16**	17.04	**23.55**	**26.73**

Table 1: Results for all architecture variants. The baseline model is the vanilla Transformer with relative attention. The early loss represents the mean and standard deviation of perplexity at $65,536$ steps. The final perplexity is reported at the end of pre-training ($524,288$ steps). SGLUE refers to SuperGLUE and WebQ refers to WebQuestions dataset. We report average, ROUGE-2, accuracy, and BLEU score for SuperGLUE, XSum, WebQuestions, and WMT EnDe, respectively, on the validation sets. **Note:** Results on WMT English to German are reported **without any pre-training**. The scores which outperform the vanilla Transformer are highlighted in **boldface**.

Do Transformer Modifications Transfer Across Implementations and Applications?

Sharan Narang* **Hyung Won Chung** **Yi Tay** **William Fedus**

Thibault Fevry† **Michael Matena†** **Karishma Malkan†** **Noah Fiedel**

Noam Shazeer **Zhenzhong Lan†** **Yanqi Zhou** **Wei Li**

Nan Ding **Jake Marcus** **Adam Roberts** **Colin Raffel†**

Narang et al. (2021)

Bias Term

- Standard feedforward network layer:

$$\mathrm{FFN}(x, W_1, W_2, b_1, b_2) = f(xW_1 + b_1)W_2 + b_2$$

- Original Transformer uses ReLU as activation function

$$\mathrm{FFN}(x, W_1, W_2, b_1, b_2) = \max(0, xW_1 + b_1)W_2 + b_2$$

- Many implementations (if they are not gated), e.g. T5, PaLM, DALL-E-mini …

$$\mathrm{FFN}_{\mathrm{ReLU}}(x, W_1, W_2) = \max(xW_1, 0)W_2$$

Geiping & Goldstein (2022)


Recap so far …

- Basically everyone does pre-norm
  - Intuition: keep the good parts of residual connections
  - Observations: nicer gradient propagation, fewer spike
- Most people do RMSnorm
  - In practice, works as well as LayerNorm
  - But, has fewer parameters to move around, saves on wallclock time
- People more generally drop bias terms
  - since the compute/param tradeoffs are not great.
  - without compromising performance

Activation Function

(Recap) ReLU

- Rectified Linear Unit (ReLU) function



$$f(x) = \max(0, x)$$

Activation Functions

- A lot different ones used in training LLMs:

  ReLU, GeLU, Swish, ELU, GLU, GeGLU, ReGLU, SeLU, SwiGLU, LiGLU, …

- Not much consensus …




Image Credit: ml-explained.com

SwiGLU in LLaMA

- SwiGLU activation function — combines Swish and Gated Linear Unit (GLU), also used in Google's PaLM model

- Feedforward layer in the Transformer using ReLU (with no bias shown here):

$$\mathrm{FFN}_{\mathrm{ReLU}}(x, W_1, W_2) = \max(xW_1, 0)W_2$$

- Replace ReLU by Swish:


$$\mathrm{FFN}_{\mathrm{Swish}}(x, W_1, W_2) = \mathrm{Swish}_1(xW_1)W_2$$

Shazeer (2020)

https://medium.com/@tariqanwarph/activation-function-and-glu-variants-for-transformer-models-a4fcbe85323f

Swish Activation

- Swish can be loosely viewed as a smooth function which nonlinearly interpolates between the linear function and ReLU




$$Swish_\beta(x) = x * sigmoid(\beta x)$$
$$= \frac{x}{1+e^{-\beta x}}$$

Ramachandran et al. (2017)

Gated Linear Unit (GLU)

- Similar to the gating mechanism in LSTM.
- Element-wise product of two linear transformations of the input, one is sigmoid-activated.



$$\mathrm{GLU}(x, W, V, b, c) = \sigma(xW + b) \otimes (xV + c)$$

Dauphin et al. (2017)

Sigmoid of a Vector





Image Credit: Gabriel Furnieles

SwiGLU

- SwiGLU activation function — combines Swish and Gated Linear Unit (GLU), also used in Google's PaLM model



$$\mathrm{GLU}(x, W, V, b, c) = \sigma(xW + b) \otimes (xV + c)$$

$$\mathrm{SwiGLU}(x, W, V, b, c, \beta) = \mathrm{Swish}_\beta(xW + b) \otimes (xV + c)$$

Dauphin et al. (2017)

SwiGLU in LLaMA

- SwiGLU activation function — combines Swish and Gated Linear Unit (GLU), also used in Google's PaLM model

- Feedforward layer in the Transformer using ReLU (with no bias shown here):

$$\mathrm{FFN}_{\mathrm{ReLU}}(x, W_1, W_2) = \max(xW_1, 0)W_2$$

- Replace ReLU by Swish or SwiGLU:

$$\mathrm{FFN}_{\mathrm{Swish}}(x, W_1, W_2) = \mathrm{Swish}_1(xW_1)W_2$$

$$\mathrm{FFN}_{\mathrm{SwiGLU}}(x, W, V, W_2) = (\mathrm{Swish}_1(xW) \otimes xV)W_2$$

Shazeer (2020)

https://medium.com/@tariqanwarph/activation-function-and-glu-variants-for-transformer-models-a4fcbe85323f

LLaMA

- SwiGLU activation function — combines Swish and Gated Linear Unit (GLU), also used in Google's PaLM model

Training Steps	65,536	524,288
$\mathrm{FFN}_{\mathrm{ReLU}}(baseline)$	1.997 (0.005)	1.677
$\mathrm{FFN}_{\mathrm{GELU}}$	1.983 (0.005)	1.679
$\mathrm{FFN}_{\mathrm{Swish}}$	1.994 (0.003)	1.683
$\mathrm{FFN}_{\mathrm{GLU}}$	1.982 (0.006)	1.663
$\mathrm{FFN}_{\mathrm{Bilinear}}$	1.960 (0.005)	1.648
$\mathrm{FFN}_{\mathrm{GEGLU}}$	**1.942** (0.004)	**1.633**
$\mathrm{FFN}_{\mathrm{SwiGLU}}$	**1.944** (0.010)	**1.636**
$\mathrm{FFN}_{\mathrm{ReGLU}}$	1.953 (0.003)	1.645

← Held-out log-perplexity on C4 corpus (used in T5 model)

Shazeer (2020)

https://medium.com/@tariqanwarph/activation-function-and-glu-variants-for-transformer-models-a4fcbe85323f

Gated Linear Unit (GLU)

- GLU variants generally works pretty well


Model	Params	Ops	Step/s	Early loss	Final loss	SGLUE	XSum	WebQ
Vanilla Transformer	$223M$	$11.1T$	3.50	2.182 ± 0.005	1.838	71.66	17.78	23.02
GeLU	$223M$	$11.1T$	3.58	2.179 ± 0.003	1.838	**75.79**	**17.86**	**25.13**
Swish	$223M$	$11.1T$	3.62	2.186 ± 0.003	1.847	**73.77**	17.74	**24.34**
ELU	$223M$	$11.1T$	3.56	2.270 ± 0.007	1.932	67.83	16.73	23.02
GLU	$223M$	$11.1T$	3.59	2.174 ± 0.003	**1.814**	**74.20**	**17.42**	24.34
GeGLU	$223M$	$11.1T$	3.55	2.130 ± 0.006	**1.792**	**75.96**	**18.27**	**24.87**
ReGLU	$223M$	$11.1T$	3.57	2.145 ± 0.004	**1.803**	**76.17**	**18.36**	**24.87**
SeLU	$223M$	$11.1T$	3.55	2.315 ± 0.004	1.948	68.76	16.76	22.75
SwiGLU	$223M$	$11.1T$	3.53	2.127 ± 0.003	**1.789**	**76.00**	**18.20**	**24.34**
LiGLU	$223M$	$11.1T$	3.59	2.149 ± 0.005	**1.798**	**75.34**	**17.97**	**24.34**
Sigmoid	$223M$	$11.1T$	3.63	2.291 ± 0.019	1.867	**74.31**	17.51	23.02
Softplus	$223M$	$11.1T$	3.47	2.207 ± 0.011	1.850	**72.45**	17.65	**24.34**

Narang et al. (2021)

Optimization

AdamW

- AdamW (Adam w/ weight decay) optimizer



Loshchilov and Hutter (2017)

AdamW Optimizer

- AdamW (Adam w/ weight decay)

$$x_t \leftarrow x_{t-1} - \alpha \frac{\beta_1 m_{t-1} + (1-\beta_1)(\nabla f_t + \boxed{w x_{t-1}})}{\sqrt{v_t} + \epsilon}$$

weight is regularized less when v is large

(insert line 6,7,8 into line 12; ignore 9,10)

Algorithm 2 Adam with L_2 regularization and

1: **given** $\alpha = 0.001, \beta_1 = 0.9, \beta_2 = 0.999, \epsilon = 10^{-8}, w \in \mathbb{R}$
2: **initialize** time step $t \leftarrow 0$, parameter vector $\boldsymbol{x}_{t=0} \in \mathbb{R}^n$, first moment vector $\boldsymbol{m}_{t=0} \leftarrow \boldsymbol{0}$, second moment vector $\boldsymbol{v}_{t=0} \leftarrow \boldsymbol{0}$, schedule multiplier $\eta_{t=0} \in \mathbb{R}$
3: **repeat**
4: $t \leftarrow t + 1$
5: $\nabla f_t(\boldsymbol{x}_{t-1}) \leftarrow \text{SelectBatch}(\boldsymbol{x}_{t-1})$ ▷ select batch and return the corresponding gradient
6: $\boldsymbol{g}_t \leftarrow \nabla f_t(\boldsymbol{x}_{t-1}) + w\boldsymbol{x}_{t-1}$
7: $\boldsymbol{m}_t \leftarrow \beta_1 \boldsymbol{m}_{t-1} + (1-\beta_1)\boldsymbol{g}_t$ ▷ here and below all operations are element-wise
8: $\boldsymbol{v}_t \leftarrow \beta_2 \boldsymbol{v}_{t-1} + (1-\beta_2)\boldsymbol{g}_t^2$
9: $\hat{\boldsymbol{m}}_t \leftarrow \boldsymbol{m}_t / (1-\beta_1^t)$ ▷ β_1 is taken to the power of t
10: $\hat{\boldsymbol{v}}_t \leftarrow \boldsymbol{v}_t / (1-\beta_2^t)$ ▷ β_2 is taken to the power of t
11: $\eta_t \leftarrow \text{SetScheduleMultiplier}(t)$ ▷ can be fixed, decay, or also be used for warm restarts
12: $\boldsymbol{x}_t \leftarrow \boldsymbol{x}_{t-1} - \eta_t \left(\alpha \hat{\boldsymbol{m}}_t / (\sqrt{\hat{\boldsymbol{v}}_t} + \epsilon) \right)$
13: **until** *stopping criterion is met*
14: **return** optimized parameters $\boldsymbol{x}_t$

Loshchilov and Hutter (2017)

https://towardsdatascience.com/why-adamw-matters-736223f31b5d

AdamW Optimizer

- AdamW (Adam w/ weight decay) optimizer

weight decay after (first and second moments of) gradient calculation for parameter-wise adaptive learning rate

Algorithm 2 ~~Adam with L_2 regularization and~~ Adam with weight decay (AdamW)

given $\alpha = 0.001, \beta_1 = 0.9, \beta_2 = 0.999, \epsilon = 10^{-8}, w \in \mathbb{R}$
initialize time step $t \leftarrow 0$, parameter vector $\boldsymbol{x}_{t=0} \in \mathbb{R}^n$, first moment vector $\boldsymbol{m}_{t=0} \leftarrow \boldsymbol{0}$, second moment vector $\boldsymbol{v}_{t=0} \leftarrow \boldsymbol{0}$, schedule multiplier $\eta_{t=0} \in \mathbb{R}$
repeat
  $t \leftarrow t + 1$
  $\nabla f_t(\boldsymbol{x}_{t-1}) \leftarrow \text{SelectBatch}(\boldsymbol{x}_{t-1})$ ▷ select batch and return the corresponding gradient
  $\boldsymbol{g}_t \leftarrow \nabla f_t(\boldsymbol{x}_{t-1})$ ~~$+ w\boldsymbol{x}_{t-1}$~~
  $\boldsymbol{m}_t \leftarrow \beta_1 \boldsymbol{m}_{t-1} + (1 - \beta_1)\boldsymbol{g}_t$ ▷ here and below all operations are element-wise
  $\boldsymbol{v}_t \leftarrow \beta_2 \boldsymbol{v}_{t-1} + (1 - \beta_2)\boldsymbol{g}_t^2$
  $\hat{\boldsymbol{m}}_t \leftarrow \boldsymbol{m}_t / (1 - \beta_1^t)$ ▷ β_1 is taken to the power of t
  $\hat{\boldsymbol{v}}_t \leftarrow \boldsymbol{v}_t / (1 - \beta_2^t)$ ▷ β_2 is taken to the power of t
  $\eta_t \leftarrow \text{SetScheduleMultiplier}(t)$ ▷ can be fixed, decay, or also be used for warm restarts
  $\boldsymbol{x}_t \leftarrow \boldsymbol{x}_{t-1} - \eta_t \left(\alpha \hat{\boldsymbol{m}}_t / (\sqrt{\hat{\boldsymbol{v}}_t} + \epsilon) + w\boldsymbol{x}_{t-1} \right)$
until *stopping criterion is met*
return optimized parameters $\boldsymbol{x}_t$


Loshchilov and Hutter (2017)


https://towardsdatascience.com/why-adamw-matters-736223f31b5d


Positional Embeddings

Positional Embeddings

- Sine embeddings in the original Transformer:








- Augment word embedding with position embeddings, each dim is a sine/cosine wave of a different frequency. Closer points = higher dot products
- Works essentially as well as just encoding position as a one-hot vector

Vaswani et al. (2017)

Positional Embeddings

- Sine embeddings in the original Transformer:

```
1 P = getPositionEncoding(seq_len=100, d=512, n=10000)
2 cax = plt.matshow(P)
3 plt.gcf().colorbar(cax)
```




The positional encoding matrix for n=10,000, d=512, sequence length=100

Image Credit: Mehreen Saeed

Positional Embeddings

- Absolute positional embeddings are added to input token embeddings
  - fixed encoding for each position (e.g., sine embeddings)
  - or learned encoding for each position



- Limitations:
  - embedding for each position (e.g., 1, 2, 3, …, 1000, … 5000)
  - can't generalize well to arbitrary long sequences
  - can't capture relative distance between two tokens

Positional Embeddings

- Relative positional embedding encodes the distance between tokens

0	1	2	3	4
-1	0	1	2	3
-2	-1	0	1	2
-3	-2	-1	0	1
-4	-3	-2	-1	0

Relative Positions Pattern
in 5 token Attention matrix


Shaw et al. (2018)

Positional Embeddings

- Relative positional embedding encodes the distance between tokens
- added directly to the self-attention matrix

0	1	2	3	4
-1	0	1	2	3
-2	-1	0	1	2
-3	-2	-1	0	1
-4	-3	-2	-1	0


Relative Positions Pattern in 5 token Attention matrix



Shaw et al. (2018)

Positional Embeddings


- Relative positional embedding encodes the distance between tokens
- added directly to the self-attention matrix
- Limitations: slow



Press et al. (2020)

Positional Embeddings


- Relative positional embedding encodes the distance between tokens
- added directly to the self-attention matrix
- Limitations: slow (why?)



Press et al. (2020)

Positional Embeddings

- Relative positional embedding encodes the distance between tokens
- added directly to the self-attention matrix
- Limitations: slow (why? changes KV values all the time, can't do KV caching)



Press et al. (2020)

KV Caching

- Accelerate LLM inference by reducing redundant computations
- Have the key and value projections cached





Image Credit: Cameron R. Wolfe

Rotary Positional Embeddings

- Rotary Positional Embeddings (RoPE)






Figure 3: Evaluation of RoPE in language modeling pre-training. **Left**: training loss for BERT and RoFormer.

Su et al. (2021)

Rotary Position Embeddings (RoPE)

04.09864v1 [cs.CL] 20 Apr 2021

RoFormer: Enhanced Transformer with Rotary Position Embedding

Jianlin Su
Zhuiyi Technology Co., Ltd.
Shenzhen
bojonesu@wezhuiyi.com

Yu Lu
Zhuiyi Technology Co., Ltd.
Shenzhen
julianlu@wezhuiyi.com

Shengfeng Pan
Zhuiyi Technology Co., Ltd.
Shenzhen
nickpan@wezhuiyi.com

Bo Wen
Zhuiyi Technology Co., Ltd.
Shenzhen
brucewen@wezhuiyi.com

Yunfeng Liu
Zhuiyi Technology Co., Ltd.
Shenzhen
glenliu@wezhuiyi.com

April 21, 2021

Abstract

Position encoding in transformer architecture provides supervision for dependency modeling between elements at different positions in the sequence. We investigate various methods to encode positional information in transformer-based language models and propose a novel implementation named Rotary Position Embedding(RoPE). The proposed RoPE encodes absolute positional information with rotation matrix and naturally incorporates explicit relative position dependency in self-attention formulation. Notably, RoPE comes with valuable properties such as flexibility of being expand to any sequence lengths, decaying inter-token dependency with increasing relative distances, and capability of equipping the linear self-attention with relative position encoding. As a result, the enhanced transformer with rotary position embedding, or RoFormer, achieves superior performance in tasks with long texts. We release the theoretical analysis along with some preliminary experiment results on Chinese data. The undergoing experiment for English benchmark will soon be updated.

Su et al. (2021)

Rotary Position Embeddings (RoPE)




Figure 1: Implementation of Rotary Position Embedding(RoPE).

Su et al. (2021)

https://www.youtube.com/watch?v=o29P0Kpobz0

Rotary Position Embeddings (RoPE)

- Rotation instead of addition!





Image Credit: Sushant Kumar

Rotary Position Embeddings (RoPE)

- Rotation instead of addition, such that
  — embeddings are invariant to absolute position
  — inner products are invariant to arbitrary rotation
- captures both absolute position and relative distance!




Su et al. (2021)

Rotary Position Embeddings (RoPE)

- In 2D, a rotation matrix can be defined in the following form:

$$R_{\theta,\ m} = \begin{pmatrix} \cos m\theta & -\sin m\theta \\ \sin m\theta & \cos m\theta \end{pmatrix}$$



- The rotation increases with increasing θ and m.

- Apply rotation after getting Q and K vectors (not V)

Su et al. (2021)

Rotary Position Embeddings (RoPE)

- In practice, rotate d dimensional embedding matrices.
- Idea: rotate different dimensions with different angles $\Theta = \{\theta_0, \theta_1, \theta_2, \theta_3, \ldots, \theta_{d/2}\}$

$$\mathbf{R}^d_{\Theta,t} = \begin{pmatrix} \cos t\theta_1 & -\sin t\theta_1 & 0 & 0 & \cdots & 0 & 0 \\ \sin t\theta_1 & \cos t\theta_1 & 0 & 0 & \cdots & 0 & 0 \\ 0 & 0 & \cos t\theta_2 & -\sin t\theta_2 & \cdots & 0 & 0 \\ 0 & 0 & \sin t\theta_2 & \cos t\theta_2 & \cdots & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \vdots & \vdots \\ 0 & 0 & 0 & 0 & \cdots & \cos t\theta_{d/2} & -\sin t\theta_{d/2} \\ 0 & 0 & 0 & 0 & \cdots & \sin t\theta_{d/2} & \cos t\theta_{d/2} \end{pmatrix}$$

Su et al. (2021)

Rotary Position Embeddings (RoPE)

- A more computational efficient realization, taking advantage of the sparsity

$$\mathbf{R}^{d}_{\Theta,t}\mathbf{u} = \begin{pmatrix} u_1 \\ u_2 \\ u_3 \\ u_4 \\ \vdots \\ u_{d-1} \\ u_d \end{pmatrix} \otimes \begin{pmatrix} \cos m\theta_1 \\ \cos t\theta_1 \\ \cos t\theta_2 \\ \cos t\theta_2 \\ \vdots \\ \cos t\theta_{d/2} \\ \cos t\theta_{d/2} \end{pmatrix} + \begin{pmatrix} -u_2 \\ u_1 \\ -u_4 \\ u_3 \\ \vdots \\ -u_d \\ u_{d-1} \end{pmatrix} \otimes \begin{pmatrix} \sin t\theta_1 \\ \sin t\theta_1 \\ \sin t\theta_2 \\ \sin t\theta_2 \\ \vdots \\ \sin t\theta_{d/2} \\ \sin t\theta_{d/2} \end{pmatrix}$$

Su et al. (2021)

Rotary Position Embeddings (RoPE)

- Inner product decays as relative distance increases




Figure 2: Long-term decay of RoPE.

Su et al. (2021)

Tokenization

Tokenization

- The non-google world uses BPE. Google uses the SentencePiece library, which (sometimes) refers to a non-BPE subword tokenizer

Model	Tokenizer
Original transformer	BPE
GPT 1/2/3	BPE
T5 / mT5 / T5v1.1	SentencePiece (Unigram)
Gopher/Chinchilla	SentencePiece (??)
PaLM	SentencePiece (??)
LLaMA	BPE

Tokenization

Monolingual models (30-50k vocab)


Model	Token count
Original transformer	37000
GPT	40257
GPT2/3	50257
T5/T5v1.1	32128
LLaMA	32000

Multilingual / Production Systems (100-250k vocab)

Model	Token count
mT5	250000
PaLM	256000
GPT4	100276
BLOOM	250680
DeepSeek	100000
Qwen 15B	152064
Yi	64000

Tokenization

- Different treatments for white space, and digits … mainly for math/code



Multi-whitespace tokenization

Tokenizer. We tokenize the data with the byte-pair encoding (BPE) algorithm (Sennrich et al., 2015), using the implementation from SentencePiece (Kudo and Richardson, 2018). Notably, we split all numbers into individual digits, and fallback to bytes to decompose unknown UTF-8 characters.

Individual digit tokenization (LLaMA/DeepSeek)

LLaMA

- LLaMA-13B matches or outperforms OPT and (old) GPT-3 for zero-shot and few-shot performance

		BoolQ	PIQA	SIQA	HellaSwag	WinoGrande	ARC-e	ARC-c	OBQA
GPT-3	175B	60.5	81.0	-	78.9	70.2	68.8	51.4	57.6
Gopher	280B	79.3	81.8	50.6	79.2	70.1	-	-	-
Chinchilla	70B	83.7	81.8	51.3	80.8	74.9	-	-	-
PaLM	62B	84.8	80.5	-	79.7	77.0	75.2	52.5	50.4
PaLM-cont	62B	83.9	81.4	-	80.6	77.0	-	-	-
PaLM	540B	**88.0**	82.3	-	83.4	**81.1**	76.6	53.0	53.4
LLaMA	7B	76.5	79.8	48.9	76.1	70.1	72.8	47.6	57.2
	13B	78.1	80.1	50.4	79.2	73.0	74.8	52.7	56.4
	33B	83.1	82.3	50.4	82.8	76.0	**80.0**	**57.8**	58.6
	65B	85.3	**82.8**	**52.3**	**84.2**	77.0	78.9	56.0	**60.2**

Table 3: **Zero-shot performance on Common Sense Reasoning tasks.**

		0-shot	1-shot	5-shot	64-shot
GPT-3	175B	14.6	23.0	-	29.9
Gopher	280B	10.1	-	24.5	28.2
Chinchilla	70B	16.6	-	31.5	35.5
PaLM	8B	8.4	10.6	-	14.6
	62B	18.1	26.5	-	27.6
	540B	21.2	29.3	-	39.6
LLaMA	7B	16.8	18.7	22.0	26.1
	13B	20.1	23.4	28.1	31.9
	33B	**24.9**	28.3	32.9	36.0
	65B	23.8	**31.0**	**35.0**	**39.9**

Table 4: **NaturalQuestions.** Exact match performance.

LLaMA2

- Improved version of LLaMA released on **July 18, 2023**
- Trained on 40% more data than LLaMA1 and has double the context length (4096).
- 7B, 13B, and 70B parameter versions.
- Includes LLaMA2-Chat, a version fine-tuned for chat that uses 27,540 supervised demonstrations, and over 1M human comparison judgments (for RLHF).

Touvron et. al. (2023)

LLaMA2




Figure 1: Helpfulness human evaluation results for LLAMA 2-CHAT compared to other open-source and closed-source models. Human raters compared model generations on ~4k prompts consisting of both single and multi-turn prompts. The 95% confidence intervals for this evaluation are between 1% and 2%. More details in Section 3.4.2. While reviewing these results, it is important to note that human evaluations can be noisy due to limitations of the prompt set, subjectivity of the review guidelines, subjectivity of individual raters, and the inherent difficulty of comparing generations.




Figure 2: Win-rate % for helpfulness and safety between commercial-licensed baselines and LLAMA 2-CHAT, according to GPT-4. To complement the human evaluation, we used a more capable model, not subject to our own guidance. Green area indicates our model is better according to GPT-4. To remove ties, we used $win/(win + loss)$. The orders in which the model responses are presented to GPT-4 are randomly swapped to alleviate bias.

Touvron et. al. (2023)

Llama3

- Released April 18, 2024
- Very similar architecture to Llama2
- Main improvements have to do with increased data and compute.
  - Pre-trained on a corpus of 15T tokens (as compared to 1.8T for Llama2)
- Flagship model is trained with 50x more compute than Llama2
  - 405B parameter model trained on 15.6T text tokens

Dubey et. al. (2024)

Llama3

Category	Benchmark	Llama 3 8B	Gemma 2 9B	Mistral 7B	Llama 3 70B	Mixtral 8x22B	GPT 3.5 Turbo	Llama 3 405B	Nemotron 4 340B	GPT-4 (0125)	GPT-4o	Claude 3.5 Sonnet
General	MMLU (5-shot)	69.4	**72.3**	61.1	**83.6**	76.9	70.7	87.3	82.6	85.1	89.1	**89.9**
	MMLU (0-shot, CoT)	**73.0**	72.3△	60.5	**86.0**	79.9	69.8	88.6	78.7◁	85.4	**88.7**	88.3
	MMLU-Pro (5-shot, CoT)	**48.3**	–	36.9	**66.4**	56.3	49.2	73.3	62.7	64.8	74.0	**77.0**
	IFEval	**80.4**	73.6	57.6	**87.5**	72.7	69.9	**88.6**	85.1	84.3	85.6	88.0
Code	HumanEval (0-shot)	**72.6**	54.3	40.2	**80.5**	75.6	68.0	89.0	73.2	86.6	90.2	**92.0**
	MBPP EvalPlus (0-shot)	**72.8**	71.7	49.5	**86.0**	78.6	82.0	88.6	72.8	83.6	87.8	**90.5**
Math	GSM8K (8-shot, CoT)	**84.5**	76.7	53.2	**95.1**	88.2	81.6	**96.8**	92.3◇	94.2	96.1	96.4◇
	MATH (0-shot, CoT)	**51.9**	44.3	13.0	**68.0**	54.1	43.1	73.8	41.1	64.5	**76.6**	71.1
Reasoning	ARC Challenge (0-shot)	83.4	**87.6**	74.2	**94.8**	88.7	83.7	**96.9**	94.6	96.4	96.7	96.7
	GPQA (0-shot, CoT)	32.8	–	28.8	**46.7**	33.3	30.8	51.1	–	41.4	53.6	**59.4**
Tool use	BFCL	**76.1**	–	60.4	84.8	–	**85.9**	88.5	86.5	88.3	80.5	**90.2**
	Nexus	**38.5**	30.0	24.7	**56.7**	48.5	37.2	**58.7**	–	50.3	56.1	45.7
Long context	ZeroSCROLLS/QuALITY	81.0	–	–	90.5	–	–	**95.2**	–	**95.2**	90.5	90.5
	InfiniteBench/En.MC	65.1	–	–	78.2	–	–	**83.4**	–	72.1	82.5	–
	NIH/Multi-needle	98.8	–	–	97.5	–	–	98.1	–	**100.0**	**100.0**	90.8
Multilingual	MGSM (0-shot, CoT)	**68.9**	53.2	29.9	**86.9**	71.1	51.4	**91.6**	–	85.9	90.5	**91.6**


Table 2 Performance of finetuned Llama 3 models on key benchmark evaluations. The table compares the performance of the 8B, 70B, and 405B versions of Llama 3 with that of competing models. We **boldface** the best-performing model in each of three model-size equivalence classes. △Results obtained using 5-shot prompting (no CoT). ◁Results obtained without CoT. ◇Results obtained using zero-shot prompting.

Dubey et. al. (2024)

Other Open-source Efforts

Alpaca

- Released by Stanford on March 13, 2023
- Fine-tuned Meta's LLaMA-7B on 52k instruction-following demonstrated generated (Self-Instruct) using GPT-3.5 (text-davinci-003) for $500.



Taori et al. (2022)

Self-Instruct

- Address the labor-intense process for creating human-written instructions




Figure 1: A high-level overview of SELF-INSTRUCT. The process starts with a small seed set of tasks (one instruction and one input-output instance for each task) as the task pool. Random tasks are sampled from the task pool, and used to prompt an off-the-shelf LM to generate both new instructions and corresponding instances, followed by filtering low-quality or similar generations, and then added back to the initial repository of tasks. The resulting data can be used for the instruction tuning of the language model itself later to follow instructions better. Tasks shown in the figure are generated by GPT3. See Table 10 for more creative examples.

Wang et al. (2022)

Self-Instruct

- Using multiple prompting templates to (a) generate the instruction, (b) classifying whether an instruction represents a classification task or not, (c) generating non-classification or classification instances

```
Come up with a series of tasks:

Task 1:  {instruction for existing task 1}
Task 2:  {instruction for existing task 2}
Task 3:  {instruction for existing task 3}
Task 4:  {instruction for existing task 4}
Task 5:  {instruction for existing task 5}
Task 6:  {instruction for existing task 6}
Task 7:  {instruction for existing task 7}
Task 8:  {instruction for existing task 8}
Task 9:
```

Table 6: Prompt used for generating new instructions. 8 existing instructions are randomly sampled from the task pool for in-context demonstration. The model is allowed to generate instructions for new tasks, until it stops its generation, reaches its length limit or generates "Task 16" tokens.

Wang et al. (2022)

Self-Instruct

```
Given the classification task definition and the class labels, generate an input that
corresponds to each of the class labels.  If the task doesn't require input, just generate the
correct class label.

Task:  Classify the sentiment of the sentence into positive, negative, or mixed.
Class label:  mixed
Sentence:  I enjoy the flavor of the restaurant but their service is too slow.
Class label:  Positive
Sentence:  I had a great day today.  The weather was beautiful and I spent time with friends.
Class label:  Negative
Sentence:  I was really disappointed by the latest superhero movie.  I would not recommend it.

...

Task:  Tell me the first number of the given list.
Class label:  1
List:  1, 2, 3
Class label:  2
List:  2, 9, 10

Task:  Which of the following is not an input type?  (a) number (b) date (c) phone number (d)
email address (e) all of these are valid inputs.
Class label:  (e)

Task:  {instruction for the target task}
```

Table 9: Prompt used for the output-first approach of instance generation. The model is prompted to generate the class label first, and then generate the corresponding input. This prompt is used for generating the instances for classification tasks.

Wang et al. (2022)

Self-Instruct





Figure 5: Performance of GPT3 model and its instruction-tuned variants, evaluated by human experts on our 252 user-oriented instructions (§5.4). Human evaluators are instructed to rate the models' responses into four levels. The results indicate that $\text{GPT3}_{\text{SELF-INST}}$ outperforms all the other GPT3 variants trained on publicly available instruction datasets. Additionally, $\text{GPT3}_{\text{SELF-INST}}$ scores nearly as good as InstructGPT_{001} (c.f., footnote 1).

Wang et al. (2022)

Alpaca

- Released by Stanford on March 13, 2023
- Fine-tuned Meta's LLaMA-7B on 52k instruction-following demonstrated generated (Self-Instruct) using GPT-3.5 (text-davinci-003) for $500.



Taori et al. (2022)

LoRA (Low-Rank Adaptation of LLMs)

- Fine-tuning Alpaca took 3 hours on 8 80GB A100 GPUs (costs <$100 on cloud compute providers)
- Parameter-efficient fine-tuning methods (e.g. LoRA) can further reduce costs, but might sacrifice performance compared to full fine-tuning.




Figure 1: Our reparametrization. We only train A and B.

$$W_0 \in \mathbb{R}^{d \times k} \qquad A \in \mathbb{R}^{r \times k} \qquad B \in \mathbb{R}^{d \times r}$$

Pre-trained parameters (frozen) — Random init. — 0 init.

$$W_0 + \Delta W = W_0 + BA$$

Gradient update (factorized using low-rank matrices - A and B)

$$h = W_0 x + \Delta W x = W_0 x + BAx$$

Modified forward pass

Hu et. al. 2021

OLMo

- Released by AI2 on Feb 28, 2024
- Open-source not only the training code and model weights, but the full pre-training data (Dolma dataset) and intermediate checkpoints

Size	Layers	Hidden Size	Attention Heads	Tokens Trained
1B	16	2048	16	2T
7B	32	4086	32	2.46T
65B*	80	8192	64	

Table 1: OLMo model sizes and the maximum number of tokens trained to.
* *At the time of writing our 65B model is still training.*

Groeneveld et al. (2024)

Takeaways

- New and actively developing situation. A lot is going on …